

Q:\MAY-2017\516\Projects\Special Details\Howerton\Standard Drawings\Details in Lieu of Standards\Division 8\862d01 862d03 862d03\862d01.dgn
 Howerton AT CSD-262598

STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C.	ROADWAY DETAIL DRAWING FOR GUARDRAIL PLACEMENT	SHEET 8 OF 11 862D01
NOTES: SHOP CURVED GUARDRAIL IS DEFINED AS HAVING A RADIUS OF 150' OR LESS. WHEN RADIUS IS LESS THAN 20' REFER TO SHEET 9. WHENEVER SHOP CURVED GUARDRAIL IS USED AS AN ANCHOR AND THE RADIUS IS FROM 20' TO 75', USE A MINIMUM LENGTH OF 50' OF SHOP CURVED GUARDRAIL AND FLARE WITH AN AT-1 ANCHOR UNIT. REFER TO DETAIL 1. WHENEVER SHOP CURVED GUARDRAIL RADIUS IS MORE THAN 75', REFER TO DETAIL 2. MAINTAIN CLEAR SIGHT DISTANCE. FOR POSTED SPEEDS ≥ 45mph USE GREU TYPE TL-3 FOR POSTED SPEEDS < 45mph USE GREU TYPE TL-2		
ROADWAY DETAIL DRAWING FOR GUARDRAIL PLACEMENT		
STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C.		

STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C.	ROADWAY DETAIL DRAWING FOR GUARDRAIL PLACEMENT	SHEET 7 OF 11 862D01
NOTES: * GUARDRAIL OPENING MAY BE SPACED AS CLOSE AS 350 FT. FROM STRUCTURE IF NECESSARY TO ALLOW MOWER ACCESS TO MEDIAN * 500' TO 5280' FROM BRIDGE * 500' TO 5280' FROM BRIDGE FOR POSTED SPEEDS ≥ 45mph USE GREU TYPE TL-3 FOR POSTED SPEEDS < 45mph USE GREU TYPE TL-2		
ROADWAY DETAIL DRAWING FOR GUARDRAIL PLACEMENT		
STATE OF NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C.		

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

CONTRACT STANDARDS AND DEVELOPMENT UNIT	
Office 919-707-6950	FAX 919-250-4119
SEE TITLE BLOCK	
ORIGINAL BY: J HOWERTON	DATE: 06-22-12
MODIFIED BY:	DATE:
CHECKED BY:	DATE:
FILE SPEC.:	

