

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**

SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5703	1	42

CONTENTS

SHEET	DESCRIPTION
1	TITLE SHEET
2	LEGEND
3	PLAN SHEET
4 - 5	PROFILES
6 - 11	BORING LOGS
12 - 42	LABORATORY TEST RESULTS

**STRUCTURE
SUBSURFACE INVESTIGATION**

COUNTY LENOIR

PROJECT DESCRIPTION C.F. HARVEY PARKWAY AND NC 58 TO
INTERSECTION OF NC 11 AND GRANGER STATION ROAD
GRADING, PAVING, DRAINAGE, STRUCTURES AND SIGNALS

SITE DESCRIPTION BRIDGE NO. 208 AND NO. 209 ON -L-
(FELIX HARVEY PARKWAY) OVER -YI- (NC 58) BETWEEN
SR 1581 AND SR 1730

INVENTORY

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF PREPARING THE SCOPE OF WORK TO BE INCLUDED IN THE REQUEST FOR PROPOSAL. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N.C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

SOIL AND ROCK BOUNDARIES WITHIN A BOREHOLE ARE BASED ON GEOTECHNICAL INTERPRETATION UNLESS ENCOUNTERED IN A SAMPLE. INTERPRETED BOUNDARIES MAY NOT NECESSARILY REFLECT ACTUAL SUBSURFACE CONDITIONS BETWEEN SAMPLED STRATA AND BOREHOLE INFORMATION MAY NOT NECESSARILY REFLECT ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

S. LANEY

K. HILL

S. MITCHELL

S. TIERNAN

C. CHANDLER

F. WRIGHT

E. BLONSHINE

J. PEELE

M. RAWLS

INVESTIGATED BY S&ME, INC.

DRAWN BY C. CHANDLER

CHECKED BY S. MITCHELL

SUBMITTED BY S&ME, INC.

DATE MAY 2017

REFERENCE: R-5703

PROJECT: 46375



SIGNATURE


DATE

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED


**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION			GRADATION			ROCK DESCRIPTION			TERMS AND DEFINITIONS																																																																																																																																																																	
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF GRAY SILTY CLAY MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6			WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.			HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:			ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC%) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (IN OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SRC%) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																																																																	
SOIL LEGEND AND AASHTO CLASSIFICATION <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>GENERAL CLASS.</th> <th colspan="6">GRANULAR MATERIALS (<= 35% PASSING #200)</th> <th colspan="4">SILT-CLAY MATERIALS (> 35% PASSING #200)</th> <th colspan="3">ORGANIC MATERIALS</th> </tr> <tr> <td>GROUP CLASS.</td> <td colspan="2">A-1</td> <td colspan="2">A-2</td> <td colspan="2">A-3</td> <td colspan="2">A-4</td> <td colspan="2">A-5</td> <td colspan="2">A-6</td> <td colspan="2">A-7</td> <td colspan="2">A-1, A-2</td> <td colspan="2">A-4, A-5</td> </tr> <tr> <td>SYMBOL</td> <td colspan="2">A-1-a</td> <td colspan="2">A-1-b</td> <td colspan="2">A-2-4</td> <td colspan="2">A-2-5</td> <td colspan="2">A-2-6</td> <td colspan="2">A-2-7</td> <td colspan="2">A-4</td> <td colspan="2">A-5</td> <td colspan="2">A-6, A-7</td> </tr> <tr> <td>% PASSING #10 #40 #200</td> <td colspan="2">50 MX 30 MX 15 MX</td> <td colspan="2">50 MX 25 MX 10 MX</td> <td colspan="2">35 MX 35 MX 35 MX</td> <td colspan="2">35 MX 35 MX 35 MX</td> <td colspan="2">36 MN 36 MN 36 MN</td> <td colspan="2">36 MN 36 MN 36 MN</td> <td colspan="2">36 MN 36 MN 36 MN</td> <td colspan="2">GRANULAR SOILS</td> <td colspan="2">SILT-CLAY SOILS</td> </tr> <tr> <td>MATERIAL PASSING #40 LL PI</td> <td colspan="2">- 6 MX</td> <td colspan="2">- NP</td> <td colspan="2">40 MX 41 MN 40 MX 41 MN</td> <td colspan="2">40 MX 41 MN 40 MX 41 MN</td> <td colspan="2">40 MX 41 MN 40 MX 41 MN</td> <td colspan="2">40 MX 41 MN 40 MX 41 MN</td> <td colspan="2">40 MX 41 MN 40 MX 41 MN</td> <td colspan="2">SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER</td> <td colspan="2">HIGHLY ORGANIC SOILS</td> </tr> <tr> <td>GROUP INDEX</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">4 MX</td> <td colspan="2">8 MX</td> <td colspan="2">12 MX</td> <td colspan="2">16 MX</td> <td colspan="2">NO MX</td> <td colspan="2"></td> </tr> <tr> <td>USUAL TYPES OF MAJOR MATERIALS</td> <td colspan="2">STONE FRAGS. GRAVEL, AND SAND</td> <td colspan="2">FINE SAND</td> <td colspan="2">SILTY OR CLAYEY GRAVEL AND SAND</td> <td colspan="2">SILTY SOILS</td> <td colspan="2">CLAYEY SOILS</td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> </tr> <tr> <td>GEN. RATING AS SUBGRADE</td> <td colspan="6">EXCELLENT TO GOOD</td> <td colspan="4">FAIR TO POOR</td> <td colspan="2">FAIR TO POOR</td> <td colspan="2">POOR</td> <td colspan="2">UNSATURABLE</td> <td colspan="2"></td> </tr> </table> <p style="font-size: 8px;">PI OF A-7-5 SUBGROUP IS <= LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30</p>			GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS			GROUP CLASS.	A-1		A-2		A-3		A-4		A-5		A-6		A-7		A-1, A-2		A-4, A-5		SYMBOL	A-1-a		A-1-b		A-2-4		A-2-5		A-2-6		A-2-7		A-4		A-5		A-6, A-7		% PASSING #10 #40 #200	50 MX 30 MX 15 MX		50 MX 25 MX 10 MX		35 MX 35 MX 35 MX		35 MX 35 MX 35 MX		36 MN 36 MN 36 MN		36 MN 36 MN 36 MN		36 MN 36 MN 36 MN		GRANULAR SOILS		SILT-CLAY SOILS		MATERIAL PASSING #40 LL PI	- 6 MX		- NP		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS		GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		16 MX		NO MX				USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS										GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD						FAIR TO POOR				FAIR TO POOR		POOR		UNSATURABLE				MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.			WEATHERING FRESH: ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE. VERY SLIGHT (V SL.): ROCK GENERALLY FRESH. JOINTS STAINED. SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE. SLIGHT (SL.): ROCK GENERALLY FRESH. JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. MODERATE (MOD.): SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED. SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK. MODERATELY SEVERE (MOD. SEV.): ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. <i>IF TESTED, WOULD YIELD SPT REFUSAL</i> SEVERE (SEV.): ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF</i> VERY SEVERE (V SEV.): ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <i>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</i> COMPLETE: ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.			CONSISTENCY OR DENSENESS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT²)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>< 4 4 TO 10 10 TO 30 30 TO 50 > 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30</td> <td>< 0.25 0.25 TO 1.0 1 TO 2 2 TO 4 > 4</td> </tr> </table>			PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 1.0 1 TO 2 2 TO 4 > 4
GENERAL CLASS.	GRANULAR MATERIALS (<= 35% PASSING #200)						SILT-CLAY MATERIALS (> 35% PASSING #200)				ORGANIC MATERIALS																																																																																																																																																															
GROUP CLASS.	A-1		A-2		A-3		A-4		A-5		A-6		A-7		A-1, A-2		A-4, A-5																																																																																																																																																									
SYMBOL	A-1-a		A-1-b		A-2-4		A-2-5		A-2-6		A-2-7		A-4		A-5		A-6, A-7																																																																																																																																																									
% PASSING #10 #40 #200	50 MX 30 MX 15 MX		50 MX 25 MX 10 MX		35 MX 35 MX 35 MX		35 MX 35 MX 35 MX		36 MN 36 MN 36 MN		36 MN 36 MN 36 MN		36 MN 36 MN 36 MN		GRANULAR SOILS		SILT-CLAY SOILS																																																																																																																																																									
MATERIAL PASSING #40 LL PI	- 6 MX		- NP		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		40 MX 41 MN 40 MX 41 MN		SOILS WITH LITTLE OR MODERATE AMOUNTS OF ORGANIC MATTER		HIGHLY ORGANIC SOILS																																																																																																																																																									
GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		16 MX		NO MX																																																																																																																																																											
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND		FINE SAND		SILTY OR CLAYEY GRAVEL AND SAND		SILTY SOILS		CLAYEY SOILS																																																																																																																																																																	
GEN. RATING AS SUBGRADE	EXCELLENT TO GOOD						FAIR TO POOR				FAIR TO POOR		POOR		UNSATURABLE																																																																																																																																																											
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT ²)																																																																																																																																																																							
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																																							
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																																							
TEXTURE OR GRAIN SIZE <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> <tr> <td>BOULDER (BLDR.)</td> <td colspan="2">COBBLE (COB.)</td> <td colspan="2">GRAVEL (GR.)</td> <td colspan="2">COARSE SAND (CSE. SD.)</td> <td>FINE SAND (F. SD.)</td> <td>SILT (SL.)</td> <td>CLAY (CL.)</td> </tr> <tr> <td>GRAIN SIZE</td> <td>MM 305 IN. 12</td> <td>75 3</td> <td colspan="2">2.0</td> <td colspan="2">0.25</td> <td>0.05</td> <td>0.005</td> <td></td> </tr> </table>			U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)		GRAVEL (GR.)		COARSE SAND (CSE. SD.)		FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)	GRAIN SIZE	MM 305 IN. 12	75 3	2.0		0.25		0.05	0.005		MISCELLANEOUS SYMBOLS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</td> <td>DIP & DIP DIRECTION OF ROCK STRUCTURES (25/025)</td> <td>SLOPE INDICATOR INSTALLATION</td> </tr> <tr> <td>SOIL SYMBOL</td> <td>TEST BORING (SPT, DMT, VST, PMT)</td> <td>CONE PENETROMETER TEST</td> </tr> <tr> <td>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</td> <td>AUGER BORING</td> <td>SOUNDING ROD</td> </tr> <tr> <td>INFERRED SOIL BOUNDARY</td> <td>CORE BORING</td> <td>TEST BORING WITH CORE</td> </tr> <tr> <td>INFERRED ROCK LINE</td> <td>MONITORING WELL</td> <td>SPT N-VALUE</td> </tr> <tr> <td>ALLUVIAL SOIL BOUNDARY</td> <td>PIEZOMETER INSTALLATION</td> <td></td> </tr> </table>			ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	DIP & DIP DIRECTION OF ROCK STRUCTURES (25/025)	SLOPE INDICATOR INSTALLATION	SOIL SYMBOL	TEST BORING (SPT, DMT, VST, PMT)	CONE PENETROMETER TEST	ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	AUGER BORING	SOUNDING ROD	INFERRED SOIL BOUNDARY	CORE BORING	TEST BORING WITH CORE	INFERRED ROCK LINE	MONITORING WELL	SPT N-VALUE	ALLUVIAL SOIL BOUNDARY	PIEZOMETER INSTALLATION		ROCK HARDNESS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>VERY HARD</td> <td>CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.</td> </tr> <tr> <td>HARD</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.</td> </tr> <tr> <td>MODERATELY HARD</td> <td>CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.</td> </tr> <tr> <td>MEDIUM HARD</td> <td>CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.</td> </tr> <tr> <td>SOFT</td> <td>CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.</td> </tr> <tr> <td>VERY SOFT</td> <td>CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.</td> </tr> </table>			VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.																																																																																																		
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																																																				
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																																																																																				
BOULDER (BLDR.)	COBBLE (COB.)		GRAVEL (GR.)		COARSE SAND (CSE. SD.)		FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																																																	
GRAIN SIZE	MM 305 IN. 12	75 3	2.0		0.25		0.05	0.005																																																																																																																																																																		
ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION	DIP & DIP DIRECTION OF ROCK STRUCTURES (25/025)	SLOPE INDICATOR INSTALLATION																																																																																																																																																																								
SOIL SYMBOL	TEST BORING (SPT, DMT, VST, PMT)	CONE PENETROMETER TEST																																																																																																																																																																								
ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT	AUGER BORING	SOUNDING ROD																																																																																																																																																																								
INFERRED SOIL BOUNDARY	CORE BORING	TEST BORING WITH CORE																																																																																																																																																																								
INFERRED ROCK LINE	MONITORING WELL	SPT N-VALUE																																																																																																																																																																								
ALLUVIAL SOIL BOUNDARY	PIEZOMETER INSTALLATION																																																																																																																																																																									
VERY HARD	CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.																																																																																																																																																																									
HARD	CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.																																																																																																																																																																									
MODERATELY HARD	CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.																																																																																																																																																																									
MEDIUM HARD	CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PIECES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.																																																																																																																																																																									
SOFT	CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.																																																																																																																																																																									
VERY SOFT	CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.																																																																																																																																																																									
SOIL MOISTURE - CORRELATION OF TERMS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td rowspan="4">LL PLASTIC RANGE (PI) PL</td> <td>LIQUID LIMIT</td> <td>- SATURATED - (SAT.) USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PLASTIC LIMIT</td> <td>- WET - (W) SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td></td> <td>- MOIST - (M) SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td></td> <td>- DRY - (D) REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>			SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL PLASTIC RANGE (PI) PL	LIQUID LIMIT	- SATURATED - (SAT.) USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PLASTIC LIMIT	- WET - (W) SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE		- MOIST - (M) SOLID; AT OR NEAR OPTIMUM MOISTURE		- DRY - (D) REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	RECOMMENDATION SYMBOLS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</td> <td>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</td> </tr> <tr> <td>UNDERCUT</td> <td></td> <td></td> </tr> <tr> <td>SHALLOW UNDERCUT</td> <td></td> <td></td> </tr> </table>			UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE	UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK	UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL	UNDERCUT			SHALLOW UNDERCUT																																																																																																																																																		
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																																								
LL PLASTIC RANGE (PI) PL	LIQUID LIMIT	- SATURATED - (SAT.) USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																																								
	PLASTIC LIMIT	- WET - (W) SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																								
		- MOIST - (M) SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																																								
		- DRY - (D) REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																																								
UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE	UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK	UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL																																																																																																																																																																								
UNDERCUT																																																																																																																																																																										
SHALLOW UNDERCUT																																																																																																																																																																										
PLASTICITY <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th></th> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>NON PLASTIC</td> <td>0-5</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC</td> <td>6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC</td> <td>16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC</td> <td>26 OR MORE</td> <td>HIGH</td> </tr> </table>				PLASTICITY INDEX (PI)	DRY STRENGTH	NON PLASTIC	0-5	VERY LOW	SLIGHTLY PLASTIC	6-15	SLIGHT	MODERATELY PLASTIC	16-25	MEDIUM	HIGHLY PLASTIC	26 OR MORE	HIGH	ABBREVIATIONS <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>AR - AUGER REFUSAL</td> <td>MED. - MEDIUM MICA - MICACEOUS</td> <td>VST - VANE SHEAR TEST</td> </tr> <tr> <td>BT - BORING TERMINATED</td> <td>MOD. - MODERATELY</td> <td>WEA. - WEATHERED</td> </tr> <tr> <td>CL - CLAY</td> <td>NP - NON PLASTIC</td> <td>W - UNIT WEIGHT</td> </tr> <tr> <td>CPT - CONE PENETRATION TEST</td> <td>ORG. - ORGANIC</td> <td>W_d - DRY UNIT WEIGHT</td> </tr> <tr> <td>CSE - COARSE</td> <td>PMT - PRESSUREMETER TEST</td> <td></td> </tr> <tr> <td>DMT - DILATOMETER TEST</td> <td>SAP. - SAPROLITIC</td> <td>SAMPLE ABBREVIATIONS</td> </tr> <tr> <td>DPT - DYNAMIC PENETRATION TEST</td> <td>SD. - SAND, SANDY</td> <td>S - BULK</td> </tr> <tr> <td>e - VOID RATIO</td> <td>SL. - SILTY, SILTY</td> <td>SS - SPLIT SPOON</td> </tr> <tr> <td>f - FINE</td> <td>SLI. - SLIGHTLY</td> <td>ST - SHELBY TUBE</td> </tr> <tr> <td>FOSS. - FOSSILIFEROUS</td> <td>TCR - TRICONE REFUSAL</td> <td>RS - ROCK</td> </tr> <tr> <td>FRAC. - FRACTURED, FRACTURES</td> <td>w - MOISTURE CONTENT</td> <td>RT - RECOMPACTED TRIAXIAL RATIO</td> </tr> <tr> <td>FRAGS. - FRAGMENTS</td> <td></td> <td>CBR - CALIFORNIA BEARING RATIO</td> </tr> <tr> <td>HI. - HIGHLY</td> <td></td> <td></td> </tr> </table>			AR - AUGER REFUSAL	MED. - MEDIUM MICA - MICACEOUS	VST - VANE SHEAR TEST	BT - BORING TERMINATED	MOD. - MODERATELY	WEA. - WEATHERED	CL - CLAY	NP - NON PLASTIC	W - UNIT WEIGHT	CPT - CONE PENETRATION TEST	ORG. - ORGANIC	W _d - DRY UNIT WEIGHT	CSE - COARSE	PMT - PRESSUREMETER TEST		DMT - DILATOMETER TEST	SAP. - SAPROLITIC	SAMPLE ABBREVIATIONS	DPT - DYNAMIC PENETRATION TEST	SD. - SAND, SANDY	S - BULK	e - VOID RATIO	SL. - SILTY, SILTY	SS - SPLIT SPOON	f - FINE	SLI. - SLIGHTLY	ST - SHELBY TUBE	FOSS. - FOSSILIFEROUS	TCR - TRICONE REFUSAL	RS - ROCK	FRAC. - FRACTURED, FRACTURES	w - MOISTURE CONTENT	RT - RECOMPACTED TRIAXIAL RATIO	FRAGS. - FRAGMENTS		CBR - CALIFORNIA BEARING RATIO	HI. - HIGHLY																																																																																																																	
	PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																																																																								
NON PLASTIC	0-5	VERY LOW																																																																																																																																																																								
SLIGHTLY PLASTIC	6-15	SLIGHT																																																																																																																																																																								
MODERATELY PLASTIC	16-25	MEDIUM																																																																																																																																																																								
HIGHLY PLASTIC	26 OR MORE	HIGH																																																																																																																																																																								
AR - AUGER REFUSAL	MED. - MEDIUM MICA - MICACEOUS	VST - VANE SHEAR TEST																																																																																																																																																																								
BT - BORING TERMINATED	MOD. - MODERATELY	WEA. - WEATHERED																																																																																																																																																																								
CL - CLAY	NP - NON PLASTIC	W - UNIT WEIGHT																																																																																																																																																																								
CPT - CONE PENETRATION TEST	ORG. - ORGANIC	W _d - DRY UNIT WEIGHT																																																																																																																																																																								
CSE - COARSE	PMT - PRESSUREMETER TEST																																																																																																																																																																									
DMT - DILATOMETER TEST	SAP. - SAPROLITIC	SAMPLE ABBREVIATIONS																																																																																																																																																																								
DPT - DYNAMIC PENETRATION TEST	SD. - SAND, SANDY	S - BULK																																																																																																																																																																								
e - VOID RATIO	SL. - SILTY, SILTY	SS - SPLIT SPOON																																																																																																																																																																								
f - FINE	SLI. - SLIGHTLY	ST - SHELBY TUBE																																																																																																																																																																								
FOSS. - FOSSILIFEROUS	TCR - TRICONE REFUSAL	RS - ROCK																																																																																																																																																																								
FRAC. - FRACTURED, FRACTURES	w - MOISTURE CONTENT	RT - RECOMPACTED TRIAXIAL RATIO																																																																																																																																																																								
FRAGS. - FRAGMENTS		CBR - CALIFORNIA BEARING RATIO																																																																																																																																																																								
HI. - HIGHLY																																																																																																																																																																										
EQUIPMENT USED ON SUBJECT PROJECT <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <td>DRILL UNITS:</td> <td>ADVANCING TOOLS:</td> <td>HAMMER TYPE:</td> </tr> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> -B <input type="checkbox"/> -H</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> -N</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td>HAND TOOLS:</td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-550</td> <td><input checked="" type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td><input checked="" type="checkbox"/> D-25</td> <td><input checked="" type="checkbox"/> TRICONE 2 15/16" STEEL TEETH</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td></td> <td><input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.</td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> <tr> <td></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> </table>			DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:	<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B <input type="checkbox"/> -H	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:	<input checked="" type="checkbox"/> CME-550	<input checked="" type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER	<input checked="" type="checkbox"/> D-25	<input checked="" type="checkbox"/> TRICONE 2 15/16" STEEL TEETH	<input type="checkbox"/> HAND AUGER		<input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD		<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST		<input type="checkbox"/>	<input type="checkbox"/>	FRACTURE SPACING <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table>			TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																								
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																																																																								
<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																																																																								
<input type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																																																																																																																								
<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> -B <input type="checkbox"/> -H																																																																																																																																																																								
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> -N																																																																																																																																																																								
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:																																																																																																																																																																								
<input checked="" type="checkbox"/> CME-550	<input checked="" type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																																																																								
<input checked="" type="checkbox"/> D-25	<input checked="" type="checkbox"/> TRICONE 2 15/16" STEEL TEETH	<input type="checkbox"/> HAND AUGER																																																																																																																																																																								
	<input type="checkbox"/> TRICONE <input type="checkbox"/> TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD																																																																																																																																																																								
	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																																																																								
	<input type="checkbox"/>	<input type="checkbox"/>																																																																																																																																																																								
TERM	SPACING																																																																																																																																																																									
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																																									
WIDE	3 TO 10 FEET																																																																																																																																																																									
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																																									
CLOSE	0.16 TO 1 FOOT																																																																																																																																																																									
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																																									
INDURATION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC. FRIABLE: RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED: GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. INDURATED: GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. EXTREMELY INDURATED: SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.			BEDDING <table border="1" style="width: 100%; border-collapse: collapse; font-size: 8px;"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>			TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET																																																																																																																																																							
TERM	THICKNESS																																																																																																																																																																									
VERY THICKLY BEDDED	4 FEET																																																																																																																																																																									
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																																									
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																																									
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																																									
THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																																									
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																																									
COLOR DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.			NOTES: FIAD - FILLED IMMEDIATELY AFTER DRILLING																																																																																																																																																																							
BENCH MARK: 81.85 FEET RIGHT -L- 87+34 BM IO RR SPIKE IN BASE OF 24" PINE N 577,986.3920 E 2,422,782.2840 ELEVATION: 76.99 FEET			DATE: 8-15-14																																																																																																																																																																							

SKEW 84°05'30"
SITE I



-L- POT Sta.89+28.52 =
-YI- POT Sta.28+62.92




5/14/99

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)				% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	60	200		
							42	37	5	9	93	80	51	15.6		
ST-1	36' LT	88+89	10.5 - 12.5	A-2-4 (0)	24	2	42	37	5	9	93	80	51	15.6	29.3	ND
ST-2	34' LT	89+50	8.0 - 10.0	A-2-4 (0)	30	1	35	39	8	8	90	75	55	19.3	30.6	ND

PROJECT REFERENCE NO. R-5703	SHEET NO. 4
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS <small>DO NOT USE FOR A/W ACQUISITION</small>	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

PROFILE THROUGH BORINGS PROJECTED ALONG LEFT LANE CONTROL LINE

VE 1:1



NOTE : GROUNDLINE ALONG LEFT LANE CONTROL LINE 23 FEET LEFT OF -L- FROM PRELIMINARY GENERAL DRAWING FOR BRIDGE ON C.F. HARVEY PARKWAY OVER NC. HWY 58 BETWEEN SR 158 AND SR 1730

NOTE : INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE PROFILE

SCHEMATIC DESIGN

88 + 50 89 + 50 90 + 50

5/14/99

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)				% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	60	200		
SS-7	33' RT	89+45	1.0 - 2.5	A-4 (1)	21	8	16	43	21	20	100	91	84	47.4	13.4	1.8

PROJECT REFERENCE NO. R-5703 SHEET NO. 5


ROADWAY DESIGN ENGINEER HYDRAULICS ENGINEER

INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

VE 1:1

PROFILE THROUGH BORINGS PROJECTED ALONG RIGHT LANE CONTROL LINE



ROADWAY EMBANKMENT
SOFT BROWN GRAY SANDY CLAY TRACE GRAVEL TRACE ROOTLETS (MOIST)

ROADWAY EMBANKMENT
SOFT GRAY FINE SANDY SILT TRACE MICA (MOIST)

COASTAL PLAIN
LOOSE TO VERY DENSE BROWN GRAY CLAYEY COARSE TO FINE SAND (MOIST TO WET) [PEEDEE FORMATION]

MEDIUM STIFF TO VERY STIFF BLACK GRAY FINE SANDY CLAY TRACE MICA (MOIST TO WET)

UNDIVIDED COASTAL PLAIN
VERY SOFT TO STIFF BROWN TAN SILTY SANDY CLAY TRACE GRAVEL (DRY TO MOIST)

STIFF TO VERY STIFF BLACK GRAY FINE SANDY CLAY WITH SHELLS (MOIST)

LOOSE TO VERY DENSE BLUE GRAY CLAYEY COARSE TO FINE SAND WITH SHELL FRAGMENTS AND CEMENTED SAND LAYERS (MOIST TO WET) [PEEDEE FORMATION]

VERY STIFF TO HARD BLUE GRAY FINE SANDY CLAY TRACE SHELLS (MOIST)

NOTE: GROUNDLINE ALONG RIGHT LANE CONTROL LINE 23 FEET RIGHT OF -L- FROM PRELIMINARY GENERAL DRAWING FOR BRIDGE ON C.F. HARVEY PARKWAY OVER NC HWY 58 BETWEEN SR 1581 AND SR 1730

NOTE: INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE PROFILE

DATE: 5/14/99
BY: STJ
CHECKED: JLD
DRAWN: JLD





NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Peele, J.E.
SITE DESCRIPTION Bridge No. 208 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. EB1-A Lt. Ln.	STATION 88+33	OFFSET 38 ft LT	ALIGNMENT -L-
COLLAR ELEV. 75.3 ft	TOTAL DEPTH 99.5 ft	NORTHING 578,131	EASTING 2,422,839
DRILL RIG/HAMMER EFF./DATE MID5152 D-25 90% 08/16/2016		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER Fowler, A.	START DATE 08/30/16	COMP. DATE 08/31/16	SURFACE WATER DEPTH N/A

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Peele, J.E.
SITE DESCRIPTION Bridge No. 208 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. EB1-A Lt. Ln.	STATION 88+33	OFFSET 38 ft LT	ALIGNMENT -L-
COLLAR ELEV. 75.3 ft	TOTAL DEPTH 99.5 ft	NORTHING 578,131	EASTING 2,422,839
DRILL RIG/HAMMER EFF./DATE MID5152 D-25 90% 08/16/2016		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER Fowler, A.	START DATE 08/30/16	COMP. DATE 08/31/16	SURFACE WATER DEPTH N/A



NCDOT BORE DOUBLE SITE 1.GPJ NC_DOT_GDT 5/3/17





NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 208 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. B-1	STATION 88+89	OFFSET 32 ft LT	ALIGNMENT -L-
COLLAR ELEV. 77.3 ft	TOTAL DEPTH 99.9 ft	NORTHING 578,142	EASTING 2,422,895
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/11/16	COMP. DATE 08/11/16	SURFACE WATER DEPTH N/A

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 208 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. B-1	STATION 88+89	OFFSET 32 ft LT	ALIGNMENT -L-
COLLAR ELEV. 77.3 ft	TOTAL DEPTH 99.9 ft	NORTHING 578,142	EASTING 2,422,895
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/11/16	COMP. DATE 08/11/16	SURFACE WATER DEPTH N/A



NCDOT BORE DOUBLE SITE 1.GPJ NC_DOT_GDT 5/3/17





NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 208 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. EB2-A Lt. Ln.	STATION 89+50	OFFSET 31 ft LT	ALIGNMENT -L-
COLLAR ELEV. 76.0 ft	TOTAL DEPTH 98.9 ft	NORTHING 578,160	EASTING 2,422,953
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/03/16	COMP. DATE 08/04/16	SURFACE WATER DEPTH N/A

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 208 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. EB2-A Lt. Ln.	STATION 89+50	OFFSET 31 ft LT	ALIGNMENT -L-
COLLAR ELEV. 76.0 ft	TOTAL DEPTH 98.9 ft	NORTHING 578,160	EASTING 2,422,953
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/03/16	COMP. DATE 08/04/16	SURFACE WATER DEPTH N/A





NCDOT BORE DOUBLE SITE 1.GPJ NC_DOT_GDT 5/3/17

NCDOT GEOTECHNICAL ENGINEERING UNIT BORELOG REPORT

Table with borehole parameters: WBS 46375.1.1, TIP R-5703, COUNTY LENOIR, GEOLOGIST Peele, J.E., SITE DESCRIPTION Bridge No. 209 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58), BORING NO. EB1-B Rt. Ln., STATION 88+53, OFFSET 75 ft RT, ALIGNMENT -L-, GROUND WTR (ft) 0 HR. 2.0, COLLAR ELEV. 75.1 ft, TOTAL DEPTH 99.3 ft, NORTHING 578,029, EASTING 2,422,894, 24 HR. 2.1, DRILL RIG/HAMMER EFF./DATE MID5152 D-25 90% 08/16/2016, DRILL METHOD Mud Rotary, HAMMER TYPE Automatic, DRILLER Fowler, A., START DATE 08/29/16, COMP. DATE 08/29/16, SURFACE WATER DEPTH N/A

Table with borehole parameters: WBS 46375.1.1, TIP R-5703, COUNTY LENOIR, GEOLOGIST Peele, J.E., SITE DESCRIPTION Bridge No. 209 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58), BORING NO. EB1-B Rt. Ln., STATION 88+53, OFFSET 75 ft RT, ALIGNMENT -L-, GROUND WTR (ft) 0 HR. 2.0, COLLAR ELEV. 75.1 ft, TOTAL DEPTH 99.3 ft, NORTHING 578,029, EASTING 2,422,894, 24 HR. 2.1, DRILL RIG/HAMMER EFF./DATE MID5152 D-25 90% 08/16/2016, DRILL METHOD Mud Rotary, HAMMER TYPE Automatic, DRILLER Fowler, A., START DATE 08/29/16, COMP. DATE 08/29/16, SURFACE WATER DEPTH N/A



NCDOT BORE DOUBLE SITE 1.GPJ NC_DOT.GDT 5/3/17





NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 209 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. B-2	STATION 88+95	OFFSET 43 ft RT	ALIGNMENT -L-
COLLAR ELEV. 77.6 ft	TOTAL DEPTH 99.3 ft	NORTHING 578,072	EASTING 2,422,924
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/10/16	COMP. DATE 08/10/16	SURFACE WATER DEPTH N/A

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 209 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. B-2	STATION 88+95	OFFSET 43 ft RT	ALIGNMENT -L-
COLLAR ELEV. 77.6 ft	TOTAL DEPTH 99.3 ft	NORTHING 578,072	EASTING 2,422,924
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/10/16	COMP. DATE 08/10/16	SURFACE WATER DEPTH N/A



NCDOT BORE DOUBLE SITE 1.GPJ NC_DOT.GDT 5/3/17





NCDOT GEOTECHNICAL ENGINEERING UNIT

BORELOG REPORT

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 209 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. EB2-B Rt. Ln.	STATION 89+45	OFFSET 33 ft RT	ALIGNMENT -L-
COLLAR ELEV. 76.6 ft	TOTAL DEPTH 93.8 ft	NORTHING 578,097	EASTING 2,422,968
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/08/16	COMP. DATE 08/08/16	SURFACE WATER DEPTH N/A

WBS 46375.1.1	TIP R-5703	COUNTY LENOIR	GEOLOGIST Blonshine, E.G.
SITE DESCRIPTION Bridge No. 209 on -L- (Felix Harvey Pkwy) over -Y1- (NC HWY 58)			GROUND WTR (ft)
BORING NO. EB2-B Rt. Ln.	STATION 89+45	OFFSET 33 ft RT	ALIGNMENT -L-
COLLAR ELEV. 76.6 ft	TOTAL DEPTH 93.8 ft	NORTHING 578,097	EASTING 2,422,968
DRILL RIG/HAMMER EFF./DATE HPC2473 CME-550 92% 12/09/2015		DRILL METHOD Mud Rotary	HAMMER TYPE Automatic
DRILLER White, J.	START DATE 08/08/16	COMP. DATE 08/08/16	SURFACE WATER DEPTH N/A



NCDOT BORE DOUBLE SITE 1.GPJ NC_DOT_GDT 5/3/17

Particle Size Analysis of Soils


AASHTO T88 as Modified by NCDOT



Quality Assurance


S&ME, Inc. Raleigh, 3201 Spring Forest Road, Raleigh, North Carolina 27616

S&ME Project #:	6235-16-010	Report Date:	12/27/16
Project Name:	C.F. Harvey Parkway Extension R-5703	Test Date(s):	12/24 - 12/27/16
State Project #:	N/A	F.A. Project No:	N/A
Client Name:	Michael Baker Engineering	TIP NO:	N/A
Address:	Raleigh, NC		
Boring #:	B-1	Sample #:	ST-1
Location:	88+89	Sample Date:	N/A
		Offset:	36 LT
		Depth (ft):	10.5 - 12.5 ft.
Sample Description:	Gray Silty Clayey Fine to Coarse SAND A-2-4 (0)		



As Defined by NCDOT		Fine Sand		< 0.25 mm and > 0.05 mm	
Gravel	< 75 mm and > 2.00 mm	Silt	< 0.05 and > 0.005 mm		
Coarse Sand	< 2.00 mm and > 0.25 mm	Clay	< 0.005 mm		
Maximum Particle Size	3/8"	Coarse Sand	42%	Silt	5%
Gravel	7%	Fine Sand	37%	Clay	9%
Apparent Relative Density	ND	Moisture Content	29.3%	% Passing #200	15.6%
Liquid Limit	24	Plastic Limit	22	Plastic Index	2
Soil Mortar (-#10 Sieve)					
Coarse Sand	45%	Fine Sand	40%	Silt	5%
				Clay	10%
Description of Sand & Gravel Particles:	Rounded	<input type="checkbox"/>	Angular	<input checked="" type="checkbox"/>	
Hard & Durable	<input checked="" type="checkbox"/>	Soft	<input type="checkbox"/>	Weathered & Friable	<input type="checkbox"/>

References / Comments / Deviations: ND=Not Determined.


<u>Mal Krajan, ET</u> Technician Name	<u>104-01-0703</u> Certification No.	<u>Laboratory Manager</u> Position	<u>12/27/2016</u> Date
<u>Mal Krajan, ET</u> Technical Responsibility	 Signature	<u>Laboratory Manager</u> Position	<u>9/26/2016</u> Date

This report shall not be reproduced, except in full, without the written approval of S&ME, Inc.

Oedometer Settlement Tests

Sample details

Sketch showing specimen location in original Sample



Depth	10.5 - 12.5 ft.
Description:	Gray Silty Clayey Fine to Coarse SAND (A-2-4) (0)
Type	Undisturbed
Height H ₀ (in)	0.998
Diameter D ₀ (in)	2.501
Weight W ₀ (gr)	150.89
Bulk Density ρ (PCF)	117.24
Particle Density ρ _s	2.658 (measured)

Initial Conditions

Settlement Channel	1942
Moisture Content w ₀ %	27.6
Dry Density ρ _d (PCF)	91.91
Voids Ratio e ₀	0.8045
Deg of Saturation S ₀ %	91.0
Swelling Pressure S _s (TSF)	0.000

Final Conditions


Moisture Content w _f %	24.2
Dry Density ρ _d (PCF)	100.73
Voids Ratio e _f	0.6465
Deg of Saturation S _f %	99.51
Settlement: (in)	0.087
Compression Index C _c	0.150

Notes: Test specimen taken from the middle portion of UD tube.




ASTM D2435-96	Test name	Consolidation
Site Reference: C.F. Harvey	Date of Test:	12-5-16
Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: <u>MLK</u>	Borehole:	B-1
Checked: <u>MLK</u>	Approved:	

Oedometer Settlement Tests




Oedometer Settlement Tests




	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey Jobfile: E:\16010.JOB	Date of Test: 12-5-16
	Operator: <i>MLL</i>	Sample: ST-1 Borehole: B-1
	Checked: <i>MLL</i>	Approved:

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey Jobfile: E:\16010.JOB	Date of Test: 12-5-16
	Operator: <i>mk</i>	Sample: ST-1 Borehole: B-1
	Checked: <i>MLL</i>	Approved:

Oedometer Settlement Tests




Oedometer Settlement Tests



	ASTM D2435-96		Test name: Consolidation
	Site Reference: C.F. Harvey		Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1	Borehole: B-1
Operator: <i>MLC</i>	Checked: <i>MLC</i>	Approved:	

	ASTM D2435-96		Test name: Consolidation
	Site Reference: C.F. Harvey		Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1	Borehole: B-1
Operator: <i>MLC</i>	Checked: <i>MLC</i>	Approved:	

Oedometer Settlement Tests



Oedometer Settlement Tests

Stress (TSF)	Initial Temp. oC	Settlement Total (in)	Cal Corr. (in)	Final Temp. oC	Voids Ratio e _f	t ₅₀ (mins)	Secondary Compr C _{sec}	c _v (ft ² /day)	m _v (ft ² /ton)
0.050	21.6	0.0057	0.0	21.6	0.7942	2.630	0.0006	0.188	0.115
0.250	21.6	0.0167	0.0	21.6	0.7743	1.175	0.0006	0.415	0.056
0.500	21.6	0.0319	0.0	21.6	0.7468	0.783	0.0008	0.605	0.063
1.000	21.6	0.0479	0.0	21.6	0.7179	0.590	0.0007	0.779	0.034
2.000	21.6	0.0705	0.0	21.6	0.6771	0.462	0.0079	0.953	0.024
4.000	21.6	0.0943	0.0	21.6	0.6340	0.391	0.0001	1.072	0.013
2.000	21.6	0.0927	0.0	21.6	0.6369				0.001
0.500	21.6	0.0906	0.0	21.6	0.6407				0.002
0.050	21.6	0.0874	0.0	21.6	0.6465				0.008

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey Jobfile: E:\16010.JOB	Date of Test: 12-5-16
	Operator: <i>MLC</i>	Checked: <i>MLC</i>
		Sample: ST-1 Borehole: B-1
		Approved:

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey Jobfile: E:\16010.JOB	Date of Test: 12-5-16
	Operator: <i>MLC</i>	Checked: <i>MLC</i>
		Sample: ST-1 Borehole: B-1
		Approved:


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	0	0.0000	0.0000
2	0.017	1	0.0001	0.0001
3	0.167	9	0.0009	0.0009
4	0.417	13	0.0013	0.0013
5	0.917	17	0.0017	0.0017
6	1.917	24	0.0024	0.0024
7	3.917	33	0.0033	0.0033
8	7.917	41	0.0041	0.0041
9	14.917	49	0.0049	0.0049
10	29.917	54	0.0054	0.0054
11	59.917	56	0.0056	0.0056
12	98.200	57	0.0057	0.0057

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.050
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0057
Voids Ratio e	0.7942
Final Temp oC	0.0
t ₅₀ (mins)	2.63
c _v (ft ² /day)	0.188
m _v (ft ² /ton)	0.115
Sec Compression C _{sec}	0.0006



	ASTM D2435-96	Test name: Consolidation Load: 0.050 (TSF)
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
Operator: MK	Checked: MK	Approved:

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
Operator: MK	Checked: MK	Approved:


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	57	0.0057	0.0057
2	0.017	65	0.0065	0.0065
3	0.033	65	0.0065	0.0065
4	0.050	73	0.0073	0.0073
5	0.067	77	0.0077	0.0077
6	0.083	79	0.0079	0.0079
7	0.100	80	0.0080	0.0080
8	0.200	86	0.0086	0.0086
9	0.400	94	0.0094	0.0094
10	0.800	105	0.0105	0.0105
11	1.000	112	0.0112	0.0112
12	2.000	122	0.0122	0.0122
13	4.000	137	0.0137	0.0137
14	8.000	150	0.0150	0.0150
15	10.000	153	0.0153	0.0153
16	20.000	160	0.0160	0.0160
17	40.000	163	0.0163	0.0163
18	80.000	165	0.0165	0.0165
19	100.000	166	0.0166	0.0166
20	163.170	167	0.0167	0.0167

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.250
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.011
Voids Ratio e	0.7743
Final Temp oC	0.0
t ₅₀ (mins)	1.17
c _v (ft ² /day)	0.415
m _v (ft ² /ton)	0.056
Sec Compression C _{sec}	0.0006



	ASTM D2435-96	Test name	Consolidation Load: 0.250 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: <i>mk</i>	Checked: <i>MLZ</i>	Borehole:	B-1
		Approved:	

	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: <i>mk</i>	Checked: <i>mk</i>	Borehole:	B-1
		Approved:	


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	167	0.0167	0.0167
2	0.017	168	0.0168	0.0168
3	0.033	170	0.0170	0.0170
4	0.050	177	0.0177	0.0177
5	0.067	182	0.0182	0.0182
6	0.083	184	0.0184	0.0184
7	0.100	185	0.0185	0.0185
8	0.200	198	0.0198	0.0198
9	0.400	217	0.0217	0.0217
10	0.800	237	0.0237	0.0237
11	1.000	241	0.0241	0.0241
12	2.000	264	0.0264	0.0264
13	4.000	281	0.0281	0.0281
14	8.000	296	0.0296	0.0296
15	10.000	298	0.0298	0.0298
16	20.000	305	0.0305	0.0305
17	40.000	312	0.0312	0.0312
18	80.000	316	0.0316	0.0316
19	100.000	317	0.0317	0.0317
20	196.000	319	0.0319	0.0319

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.500
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0152
Voids Ratio e	0.7468
Final Temp oC	0.0
t ₅₀ (mins)	0.78
c _v (ft ² /day)	0.605
m _v (ft ² /ton)	0.063
Sec Compression C _{sec}	0.0008



	ASTM D2435-96	Test name	Consolidation Load: 0.500 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: <i>mk</i>	Checked: <i>mk</i>	Borehole:	B-1
		Approved:	

	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: <i>mk</i>	Checked: <i>mk</i>	Borehole:	B-1
		Approved:	


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	319	0.0319	0.0319
2	0.017	335	0.0335	0.0335
3	0.033	335	0.0335	0.0335
4	0.050	353	0.0353	0.0353
5	0.067	358	0.0358	0.0358
6	0.083	361	0.0361	0.0361
7	0.100	366	0.0366	0.0366
8	0.200	377	0.0377	0.0377
9	0.400	393	0.0393	0.0393
10	0.800	415	0.0415	0.0415
11	1.000	421	0.0421	0.0421
12	2.000	441	0.0441	0.0441
13	4.000	457	0.0457	0.0457
14	8.000	465	0.0465	0.0465
15	10.000	465	0.0465	0.0465
16	20.000	473	0.0473	0.0473
17	40.000	476	0.0476	0.0476
18	80.000	478	0.0478	0.0478
19	100.000	478	0.0478	0.0478
20	136.630	479	0.0479	0.0479

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	1.000
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.016
Void Ratio e	0.7179
Final Temp oC	0.0
t ₅₀ (mins)	0.59
c _v (ft ² /day)	0.779
m _v (ft ² /ton)	0.034
Sec Compression C _{sec}	0.0007



	ASTM D2435-96		Test name	Consolidation Load: 1.000 (TSF)
	Site Reference: C.F. Harvey Jobfile: E:\16010.JOB		Date of Test:	12-5-16
	Operator: <i>MLC</i>		Sample: ST-1 Borehole: B-1	Checked: <i>MLC</i>

	ASTM D2435-96		Test name	Consolidation
	Site Reference: C.F. Harvey Jobfile: E:\16010.JOB		Date of Test:	12-5-16
	Operator: <i>MLC</i>		Sample: ST-1 Borehole: B-1	Checked: <i>MLC</i>

Oedometer Settlement Tests


No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	479	0.0479	0.0479
2	0.017	480	0.0480	0.0480
3	0.033	527	0.0527	0.0527
4	0.050	543	0.0543	0.0543
5	0.067	557	0.0557	0.0557
6	0.083	561	0.0561	0.0561
7	0.100	569	0.0569	0.0569
8	0.200	590	0.0590	0.0590
9	0.400	614	0.0614	0.0614
10	0.800	638	0.0638	0.0638
11	1.000	645	0.0645	0.0645
12	2.000	665	0.0665	0.0665
13	4.000	678	0.0678	0.0678
14	8.000	686	0.0686	0.0686
15	10.000	688	0.0688	0.0688
16	20.000	693	0.0693	0.0693
17	40.000	696	0.0696	0.0696
18	80.000	697	0.0697	0.0697
19	100.000	698	0.0698	0.0698
20	200.000	702	0.0702	0.0702
21	400.000	704	0.0704	0.0704
22	800.000	705	0.0705	0.0705
23	949.100	705	0.0705	0.0705

	ASTM D2435-96	Test name: Consolidation Load: 2.000 (TSF)
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
	Operator: <i>mk</i>	Borehole: B-1
	Checked: <i>mk</i>	Approved:

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	2.000
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0226
Voids Ratio e	0.6771
Final Temp oC	0.0
t ₅₀ (mins)	0.46
c _v (ft ² /day)	0.953
m _v (ft ² /ton)	0.024
Sec Compression C _{sec}	0.0079



	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
	Operator: <i>mk</i>	Borehole: B-1
	Checked: <i>mk</i>	Approved:


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	705	0.0705	0.0705
2	0.017	714	0.0714	0.0714
3	0.033	736	0.0736	0.0736
4	0.050	777	0.0777	0.0777
5	0.067	790	0.0790	0.0790
6	0.083	801	0.0801	0.0801
7	0.100	808	0.0808	0.0808
8	0.200	837	0.0837	0.0837
9	0.400	864	0.0864	0.0864
10	0.800	889	0.0889	0.0889
11	1.000	896	0.0896	0.0896
12	2.000	912	0.0912	0.0912
13	4.000	921	0.0921	0.0921
14	8.000	929	0.0929	0.0929
15	10.000	929	0.0929	0.0929
16	20.000	936	0.0936	0.0936
17	40.000	937	0.0937	0.0937
18	80.000	943	0.0943	0.0943
19	100.000	943	0.0943	0.0943
20	161.130	943	0.0943	0.0943

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	4.000
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0238
Voids Ratio e	0.6340
Final Temp oC	0.0
t ₅₀ (mins)	0.39
c _v (ft ² /day)	1.072
m _v (ft ² /ton)	0.013
Sec Compression C _{sec}	0.0001



	ASTM D2435-96	Test name	Consolidation Load: 4.000 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1	Borehole: B-1
Operator: <i>mk</i>	Checked: <i>mk</i>	Approved:	

	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1	Borehole: B-1
Operator: <i>mk</i>	Checked: <i>mk</i>	Approved:	


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	943	0.0943	0.0943
2	0.017	933	0.0933	0.0933
3	0.033	933	0.0933	0.0933
4	0.050	932	0.0932	0.0932
5	0.067	930	0.0930	0.0930
6	0.083	930	0.0930	0.0930
7	0.100	930	0.0930	0.0930
8	0.200	930	0.0930	0.0930
9	0.400	929	0.0929	0.0929
10	0.800	929	0.0929	0.0929
11	1.000	928	0.0928	0.0928
12	2.000	928	0.0928	0.0928
13	4.000	928	0.0928	0.0928
14	8.000	928	0.0928	0.0928
15	10.000	928	0.0928	0.0928
16	20.000	927	0.0927	0.0927
17	40.000	927	0.0927	0.0927
18	79.330	927	0.0927	0.0927

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	2.000
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0016
Void Ratio e	0.6369
Final Temp oC	
t ₅₀ (mins)	
c _v (ft ² /day)	
m _v (ft ² /ton)	
Sec Compression C _{sec}	



	ASTM D2435-96	Test name	Consolidation Load: 2.000 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: MK	Checked: MK	Borehole:	B-1
		Approved:	

	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: MK	Checked: MK	Borehole:	B-1
		Approved:	


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	927	0.0927	0.0927
2	0.017	921	0.0921	0.0921
3	0.033	921	0.0921	0.0921
4	0.050	913	0.0913	0.0913
5	0.067	913	0.0913	0.0913
6	0.083	913	0.0913	0.0913
7	0.100	913	0.0913	0.0913
8	0.200	912	0.0912	0.0912
9	0.400	911	0.0911	0.0911
10	0.800	911	0.0911	0.0911
11	1.000	910	0.0910	0.0910
12	2.000	910	0.0910	0.0910
13	4.000	910	0.0910	0.0910
14	8.000	909	0.0909	0.0909
15	10.000	909	0.0909	0.0909
16	20.000	909	0.0909	0.0909
17	40.000	907	0.0907	0.0907
18	80.000	906	0.0906	0.0906
19	86.333	906	0.0906	0.0906

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.500
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0021
Voids Ratio e	0.6407
Final Temp oC	
t ₅₀ (mins)	
c _v (ft ² /day)	
m _v (ft ² /ton)	
Sec Compression C _{sec}	



	ASTM D2435-96	Test name	Consolidation Load: 0.500 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: MK	Checked: MK	Borehole:	B-1
		Approved:	

	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-5-16
	Jobfile: E:\16010.JOB	Sample:	ST-1
Operator: MK	Checked: MK	Borehole:	B-1
		Approved:	


Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	906	0.0906	0.0906
2	0.017	902	0.0902	0.0902
3	0.033	902	0.0902	0.0902
4	0.050	897	0.0897	0.0897
5	0.067	896	0.0896	0.0896
6	0.083	895	0.0895	0.0895
7	0.100	894	0.0894	0.0894
8	0.200	891	0.0891	0.0891
9	0.400	889	0.0889	0.0889
10	0.800	886	0.0886	0.0886
11	1.000	884	0.0884	0.0884
12	2.000	881	0.0881	0.0881
13	4.000	880	0.0880	0.0880
14	8.000	879	0.0879	0.0879
15	10.000	878	0.0878	0.0878
16	20.000	877	0.0877	0.0877
17	40.000	876	0.0876	0.0876
18	80.000	875	0.0875	0.0875
19	100.000	875	0.0875	0.0875
20	200.000	874	0.0874	0.0874
21	216.330	874	0.0874	0.0874

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.050
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0032
Voids Ratio e	0.6465
Final Temp oC	
t ₅₀ (mins)	
c _v (ft ² /day)	
m _v (ft ² /ton)	
Sec Compression C _{sec}	



	ASTM D2435-96	Test name: Consolidation Load: 0.050 (TSF)
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
Operator: <i>MLC</i>	Checked: <i>MLC</i>	Approved:

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
Operator: <i>MLC</i>	Checked: <i>MLC</i>	Approved:

Effective Stress Triaxial Compression

Consolidated Undrained

Sample details

Sketch showing specimen location in original Sample



Depth: 10.5 - 12.5 ft.
Description: Gray Silty Clayey Fine to Coarse SAND (A-2-4) (0)

	Specimen 1	Specimen 2	Specimen 3
Type	Undisturbed	Undisturbed	Undisturbed
Height H_0 (in)	5.9714	6.034	5.923
Diameter D_0 (in)	2.863	2.863	2.867
Weight W_0 (gr)	1181.6	1184.6	1182.4
Bulk Density ρ (PCF)	117.09	116.17	117.80
Particle Density ρ_s	2.658	2.658	2.658
	(measured)	(measured)	(measured)

Initial Conditions


	Specimen 1	Specimen 2	Specimen 3
Cell Pressure σ_3 (lb/in ²)	5.5	18.0	30.0
Pore Pressure u (lb/in ²)	0.0	0.0	0.0
Machine Speed d_r (in/min)	0.0059	0.0051	0.0061
No. of Membranes	1	1	1
Total Thickness (in)	0.012	0.012	0.012
Strain Channel	1798	1798	1798
Load Channel	1776	1776	1776
Pore P. Channel	1779	1779	1779
Volume Channel	Volume Chang	Volume Chang	Volume Chang
Moisture Content w_0 %	29.3	29.8	28.9
Dry Density ρ_{d0} (PCF)	90.53	89.50	91.41
Voids Ratio e_0	0.83	0.85	0.81
Deg of Saturation S_0 %	93.74	92.85	94.22
Final B Value	0.98	0.99	0.99

Final Conditions

	Specimen 1	Specimen 2	Specimen 3
Moisture Content w_f %	28.8	27.3	25.3
Dry Density ρ_d (PCF)	93.06	94.57	97.44
Voids Ratio e_f	0.78	0.75	0.70
Deg of Saturation S_f %	97.97	96.20	95.80
Failure Criteria	Mx Stress Ratio	Mx Stress Ratio	Mx Stress Ratio
Axial Strain ϵ_f %	4.0	6.0	7.0
Corr Dev Stress $(\sigma_1 - \sigma_3)_f$ (lb/in ²)	10.6	17.6	31.4
Minor Stress σ_{3f} (lb/in ²)	2.2	5.5	11.3
Major Stress σ_{1f} (lb/in ²)	12.8	23.1	42.7
Stress Ratio $(\sigma_1/\sigma_3)_f$	5.8	4.2	3.8

Notes:




Failure Sketch



Surface Inclination

Effective Stress Triaxial Compression

Consolidated Undrained





Test Method: ASTM D4767-95	Test name: CU Triaxial (SS, MS)
Site Reference: C.F. Harvey	Date of Test: 12-5-16
Jobfile: E:\16010.JOB	Sample: ST-1
Operator: <i>MLC</i>	Borehole: B-1
Checked: <i>MLC</i>	Approved:



Test Method: ASTM D4767-95	Test name: CU Triaxial (SS, MS)
Site Reference: C.F. Harvey	Date of Test: 12-5-16
Jobfile: E:\16010.JOB	Sample: ST-1
Operator: <i>MLC</i>	Borehole: B-1
Checked: <i>MLC</i>	Approved:


Effective Stress Triaxial Compression

Consolidated Undrained



Effective Stress Triaxial Compression

Consolidated Undrained



	Test Method: ASTM D4767-95	Test name: CU Triaxial (SS, MS)
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
	Operator: <i>MLK</i>	Borehole: B-1
Checked: <i>MLK</i>	Approved:	

	Test Method: ASTM D4767-95	Test name: CU Triaxial (SS, MS)
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
	Operator: <i>MLK</i>	Borehole: B-1
Checked: <i>MLK</i>	Approved:	

Effective Stress Triaxial Compression

Consolidated Undrained Shear (Specimen 1)

No.	Strain (divs)	Strain ε%	Load (divs)	Load (lbs)	Pore Prs (divs)	Pore Prs (lbf/in2)	D. Stress (σ ₁ - σ ₃) _m (lbf/in2)	D. Stress (σ ₁ - σ ₃) _c (lbf/in2)	Minor Str σ ₃ ' (lbf/in2)	Major Str σ ₁ ' (lbf/in2)	Ratio σ ₁ '/σ ₃ '
1	41	0.00	519	0.0	0	0.0	0.0	0.0	5.50	5.50	1.00
2	91	0.08	619	10.0	3	0.3	1.6	1.6	5.20	6.78	1.30
3	145	0.18	811	29.2	5	0.5	4.6	4.6	5.00	9.61	1.92
4	201	0.27	917	39.8	7	0.7	6.3	6.3	4.80	11.08	2.31
5	252	0.36	972	45.3	9	0.9	7.1	7.1	4.60	11.74	2.55
6	306	0.45	1003	48.4	11	1.1	7.6	7.6	4.40	12.02	2.73
7	365	0.55	1031	51.2	12	1.2	8.1	7.9	4.30	12.20	2.84
8	420	0.64	1045	52.6	14	1.4	8.3	8.1	4.10	12.21	2.98
9	474	0.73	1058	53.9	15	1.5	8.5	8.3	4.00	12.31	3.08
10	534	0.83	1072	55.3	17	1.7	8.7	8.5	3.80	12.32	3.24
11	587	0.92	1081	56.2	20	2.0	8.8	8.7	3.50	12.15	3.47
12	642	1.02	1089	57.0	22	2.2	8.9	8.8	3.30	12.07	3.66
13	702	1.12	1103	58.4	24	2.4	9.1	9.0	3.10	12.08	3.90
14	1210	1.98	1164	64.5	31	3.1	10.0	9.7	2.40	12.12	5.05
15	1830	3.02	1214	69.5	33	3.3	10.7	10.3	2.20	12.51	5.68
16	2397	3.98	1250	73.1	33	3.3	11.1	10.6	2.20	12.83	5.83
17	3025	5.04	1286	76.7	30	3.0	11.5	11.0	2.50	13.47	5.39
18	3592	6.00	1311	79.2	27	2.7	11.8	11.1	2.80	13.94	4.98
19	4164	6.97	1328	80.9	25	2.5	11.9	11.2	3.00	14.19	4.73
20	4791	8.03	1347	82.8	24	2.4	12.0	11.3	3.10	14.35	4.63
21	5364	9.00	1367	84.8	23	2.3	12.2	11.3	3.20	14.53	4.54
22	5933	9.96	1389	87.0	21	2.1	12.4	11.4	3.40	14.84	4.36
23	6563	11.02	1403	88.4	21	2.1	12.4	11.4	3.40	14.81	4.36
24	7132	11.98	1417	89.8	20	2.0	12.5	11.4	3.50	14.89	4.25
25	7703	12.95	1436	91.7	19	1.9	12.6	11.5	3.60	15.05	4.18
26	8330	14.01	1459	94.0	18	1.8	12.8	11.5	3.70	15.23	4.12
27	8901	14.97	1478	95.9	17	1.7	12.9	11.6	3.80	15.39	4.05
28	9530	16.04	1500	98.1	16	1.6	13.0	11.7	3.90	15.55	3.99
29	10102	17.00	1523	100.4	15	1.5	13.2	11.7	4.00	15.73	3.93
30	10675	17.97	1545	102.6	15	1.5	13.3	11.8	4.00	15.80	3.95
31	11303	19.03	1556	103.7	14	1.4	13.3	11.7	4.10	15.83	3.86
32	11865	19.98	1569	105.0	13	1.3	13.3	11.7	4.20	15.90	3.79

	Test Method: ASTM D4767-95		Test name: CU Triaxial (SS, MS) Shear (Specimen 1)	
	Date of Test:		12-5-16	
	Site Reference: C.F. Harvey	Sample: ST-1		
	Jobfile: E:\16010.JOB	Borehole: B-1		
Operator: <i>MK</i>	Checked: <i>MK</i>	Approved:		

Effective Stress Triaxial Compression

Consolidated Undrained Shear (Specimen 2)

No.	Strain (divs)	Strain ε%	Load (divs)	Load (lbs)	Pore Prs (divs)	Pore Prs (lbf/in2)	D. Stress (σ ₁ - σ ₃) _m (lbf/in2)	D. Stress (σ ₁ - σ ₃) _c (lbf/in2)	Minor Str σ ₃ ' (lbf/in2)	Major Str σ ₁ ' (lbf/in2)	Ratio σ ₁ '/σ ₃ '
1	35	0.00	602	0.0	0	0.0	0.0	0.0	18.00	18.00	1.00
2	90	0.09	753	15.1	2	0.2	2.4	2.4	17.80	20.23	1.14
3	143	0.18	828	22.6	5	0.5	3.6	3.6	17.50	21.14	1.21
4	201	0.28	869	26.7	8	0.8	4.3	4.3	17.20	21.49	1.25
5	255	0.37	894	29.2	10	1.0	4.7	4.7	17.00	21.69	1.28
6	308	0.46	952	35.0	14	1.4	5.6	5.6	16.60	22.21	1.34
7	367	0.56	999	39.7	17	1.7	6.4	6.2	16.30	22.50	1.38
8	421	0.65	1025	42.3	21	2.1	6.8	6.6	15.90	22.51	1.42
9	475	0.74	1065	46.3	25	2.5	7.4	7.2	15.50	22.75	1.47
10	534	0.84	1096	49.4	29	2.9	7.9	7.7	15.10	22.83	1.51
11	587	0.93	1112	51.0	32	3.2	8.1	8.0	14.80	22.78	1.54
12	642	1.02	1143	54.1	36	3.6	8.6	8.5	14.40	22.87	1.59
13	699	1.12	1158	55.6	38	3.8	8.9	8.7	14.20	22.90	1.61
14	1203	1.97	1399	79.7	65	6.5	12.6	12.3	11.50	23.81	2.07
15	1811	3.00	1589	98.7	85	8.5	15.4	15.1	9.50	24.57	2.59
16	2427	4.04	1706	110.4	107	10.7	17.1	16.6	7.30	23.90	3.27
17	2987	4.98	1759	115.7	118	11.8	17.7	17.2	6.20	23.36	3.77
18	3608	6.03	1806	120.4	125	12.5	18.2	17.6	5.50	23.10	4.20
19	4168	6.98	1837	123.5	124	12.4	18.5	17.8	5.60	23.40	4.18
20	4788	8.02	1867	126.5	121	12.1	18.8	18.0	5.90	23.85	4.04
21	5350	8.97	1895	129.3	118	11.8	19.0	18.1	6.20	24.29	3.92
22	5972	10.02	1923	132.1	117	11.7	19.2	18.2	6.30	24.50	3.89
23	6537	10.97	1928	132.6	115	11.5	19.0	18.0	6.50	24.49	3.77
24	7160	12.03	1953	135.1	113	11.3	19.2	18.0	6.70	24.74	3.69
25	7724	12.98	1959	135.7	111	11.1	19.0	17.9	6.90	24.75	3.59
26	8347	14.03	1964	136.2	110	11.0	18.9	17.6	7.00	24.61	3.52
27	8913	14.98	1987	138.5	108	10.8	19.0	17.7	7.20	24.86	3.45
28	9536	16.04	2009	140.7	108	10.8	19.0	17.7	7.20	24.86	3.45
29	10100	16.99	2009	140.7	107	10.7	18.8	17.4	7.30	24.67	3.38
30	10725	18.04	2028	142.6	106	10.6	18.8	17.3	7.40	24.72	3.34
31	11293	19.00	2030	142.8	104	10.4	18.6	17.1	7.60	24.69	3.25
32	11898	20.02	2045	144.3	103	10.3	18.6	17.0	7.70	24.71	3.21

	Test Method: ASTM D4767-95		Test name: CU Triaxial (SS, MS) Shear (Specimen 2)	
	Date of Test:		12-5-16	
	Site Reference: C.F. Harvey	Sample: ST-1		
	Jobfile: E:\16010.JOB	Borehole: B-1		
Operator: <i>MK</i>	Checked: <i>MK</i>	Approved:		


Effective Stress Triaxial Compression

Consolidated Undrained Shear (Specimen 3)

No.	Strain (divs)	Strain ε%	Load (divs)	Load (lbs)	Pore Prs (divs)	Pore Prs (lbf/in ²)	D. Stress (σ ₁ - σ ₃) _m (lbf/in ²)	D. Stress (σ ₁ - σ ₃) _c (lbf/in ²)	Minor Str σ ₃ ' (lbf/in ²)	Major Str σ ₁ ' (lbf/in ²)	Ratio σ ₁ '/σ ₃ '
1	247	0.00	688	0.0	0	0.0	0.0	0.0	30.00	30.00	1.00
2	302	0.09	894	20.6	8	0.8	3.3	3.3	29.20	32.53	1.11
3	359	0.19	1186	49.8	23	2.3	8.0	8.0	27.70	35.74	1.29
4	414	0.29	1442	75.4	54	5.4	12.2	12.2	24.60	36.76	1.49
5	468	0.38	1606	91.8	77	7.7	14.8	14.8	22.30	37.09	1.66
6	526	0.48	1739	105.1	99	9.9	16.9	16.9	20.10	37.01	1.84
7	580	0.57	1806	111.8	122	12.2	18.0	17.8	17.80	35.61	2.00
8	634	0.67	1853	116.5	137	13.7	18.7	18.6	16.30	34.85	2.14
9	694	0.77	1903	121.5	149	14.9	19.5	19.3	15.10	34.44	2.28
10	749	0.87	1931	124.3	161	16.1	19.9	19.8	13.90	33.67	2.42
11	805	0.96	1956	126.8	169	16.9	20.3	20.1	13.10	33.25	2.54
12	863	1.06	1987	129.9	175	17.5	20.8	20.6	12.50	33.12	2.65
13	919	1.16	2006	131.8	181	18.1	21.1	20.9	11.90	32.81	2.76
14	1428	2.04	2165	147.7	200	20.0	23.4	23.1	10.00	33.12	3.31
15	1994	3.01	2329	164.1	201	20.1	25.7	25.4	9.90	35.28	3.56
16	2566	4.00	2465	177.7	199	19.9	27.6	27.1	10.10	37.21	3.68
17	3134	4.98	2587	189.9	196	19.6	29.2	28.6	10.40	39.02	3.75
18	3702	5.96	2698	201.0	192	19.2	30.6	29.9	10.80	40.73	3.77
19	4330	7.04	2823	213.5	187	18.7	32.1	31.4	11.30	42.68	3.78
20	4897	8.02	2921	223.3	182	18.2	33.2	32.4	11.80	44.22	3.75
21	5472	9.01	3004	231.6	177	17.7	34.1	33.2	12.30	45.50	3.70
22	6039	9.99	3087	239.9	173	17.3	34.9	34.0	12.70	46.66	3.67
23	6609	10.97	3171	248.3	171	17.1	35.7	34.7	12.90	47.61	3.69
24	7183	11.96	3251	256.3	169	16.9	36.5	35.4	13.10	48.47	3.70
25	7808	13.04	3318	263.0	167	16.7	37.0	35.8	13.30	49.10	3.69
26	8383	14.03	3369	268.1	165	16.5	37.3	36.0	13.50	49.51	3.67
27	8952	15.01	3399	271.1	161	16.1	37.3	35.9	13.90	49.84	3.59
28	9523	16.00	3420	273.2	157	15.7	37.1	35.7	14.30	50.03	3.50
29	10100	16.99	3460	277.2	155	15.5	37.2	35.8	14.50	50.26	3.47
30	10654	17.95	3499	281.1	153	15.3	37.3	35.8	14.70	50.48	3.43
31	11260	18.99	3520	283.2	151	15.1	37.1	35.5	14.90	50.44	3.39
32	11863	20.03	3555	286.7	150	15.0	37.1	35.5	15.00	50.48	3.37



S&ME, Inc. Raleigh, 3201 Spring Forest Road, Raleigh, North Carolina 27616			
S&ME Project #:	6235-16-010	Report Date:	12/27/16
Project Name:	C.F. Harvey Parkway Extension R-5703	Test Date(s):	12/24 - 12/27/16
State Project #:	N/A	F.A. Project No:	N/A
		TIP NO:	N/A
Client Name:	Michael Baker Engineering		
Address:	Raleigh, NC		
Boring #:	EB2-A LT LN	Sample #:	ST-2
		Sample Date:	N/A
Location:	89+50	Offset:	34 LT
		Depth (ft):	8.0 - 10.0 ft.
Sample Description:	Gray Silty Clayey Coarse to Fine SAND A-2-4 (0)		



As Defined by NCDOT		Fine Sand	< 0.25 mm and > 0.05 mm
Gravel	< 75 mm and > 2.00 mm	Silt	< 0.05 and > 0.005 mm
Coarse Sand	< 2.00 mm and > 0.25 mm	Clay	< 0.005 mm

Maximum Particle Size	#4	Coarse Sand	35%	Silt	8%
Gravel	10%	Fine Sand	39%	Clay	8%
Apparent Relative Density	ND	Moisture Content	30.6%	% Passing #200	19.3%
Liquid Limit	30	Plastic Limit	29	Plastic Index	1

Soil Mortar (-#10 Sieve)					
Coarse Sand	39%	Fine Sand	44%	Silt	8%
				Clay	9%

Description of Sand & Gravel Particles:	Rounded	<input type="checkbox"/>	Angular	<input checked="" type="checkbox"/>	
Hard & Durable	<input checked="" type="checkbox"/>	Soft	<input type="checkbox"/>	Weathered & Friable	<input type="checkbox"/>

References / Comments / Deviations: ND=Not Determined.

Mal Krajan, ET
Technician Name

104-01-0703
Certification No.

Laboratory Manager
Position

12/27/2016
Date

Mal Krajan, ET
Technical Responsibility

Signature

Laboratory Manager
Position

9/26/2016
Date

This report shall not be reproduced, except in full, without the written approval of S&ME, Inc.

	Test Method: ASTM D4767-95	Test name: CU Triaxial (SS, MS) Shear (Specimen 3)
	Site Reference: C.F. Harvey	Date of Test: 12-5-16
	Jobfile: E:\16010.JOB	Sample: ST-1
	Operator: <i>mlk</i>	Borehole: B-1
Checked: <i>mlk</i>	Approved:	

Oedometer Settlement Tests

Sample details

Sketch showing specimen location in original Sample



Depth: 8.0 - 10.0 ft.
Description: Gray Silty Clayey Coarse to Fine SAND (A-2-4) (0)

Type: Undisturbed
Height H_0 (in): 0.997
Diameter D_0 (in): 2.501
Weight W_0 (gr): 148.43
Bulk Density ρ (PCF): 115.45
Particle Density ρ_s : 2.653 (measured)

Initial Conditions


Settlement Channel: 1065
Moisture Content w_0 (%): 30.6
Dry Density ρ_d (PCF): 88.38
Voids Ratio e_0 : 0.8732
Deg of Saturation S_0 (%): 93.1
Swelling Pressure S_s (TSF): 0.000

Final Conditions

Moisture Content w_f (%): 34.0
Dry Density ρ_d (PCF): 91.94
Voids Ratio e_f : 0.8007
Deg of Saturation S_f (%): 100.00
Settlement (in): 0.039
Compression Index C_c : 0.168

Notes: Test specimen taken from the middle portion of UD tube.


Oedometer Settlement Tests




	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>MLC</i>	Borehole: EB2-A LT LN
	Checked: <i>MLC</i>	Approved:

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>MLC</i>	Borehole: EB2-A LT LN
	Checked: <i>MLC</i>	Approved:

Oedometer Settlement Tests




Oedometer Settlement Tests




	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mk</i>	Borehole: EB2-A LT LN
	Checked: <i>mk</i>	Approved:

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mk</i>	Borehole: EB2-A LT LN
	Checked: <i>mk</i>	Approved:

Oedometer Settlement Tests



Oedometer Settlement Tests



	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mc</i>	Borehole: EB2-A LT LN
	Checked: <i>mc</i>	Approved:

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mc</i>	Borehole: EB2-A LT LN
	Checked: <i>mc</i>	Approved:

Oedometer Settlement Tests

Stress (TSF)	Initial Temp. oC	Settlement Total (in)	Cal Corr. (in)	Final Temp. oC	Voids Ratio e_f	t_{50} (mins)	Secondary Compr C_{sec}	c_v (ft ² /day)	m_v (ft ² /ton)
0.050	21.6	0.0011	0.0	21.6	0.8712	0.860	0.00	0.577	0.022
0.250	21.6	0.0043	0.0	21.6	0.8651	0.367	0.0001	1.347	0.016
0.500	21.6	0.0086	0.0	21.6	0.8571	0.393	0.0002	1.248	0.017
1.000	21.6	0.0166	0.0	21.6	0.8420	0.356	0.0002	1.362	0.016
2.000	21.6	0.0297	0.0	21.6	0.8174	0.359	0.0002	1.322	0.014
4.000	21.6	0.0559	0.0	21.6	0.7682	0.398	0.0011	1.145	0.014
2.000	21.6	0.0535	0.0	21.6	0.7727				0.001
0.500	21.6	0.0468	0.0	21.6	0.7853				0.005
0.050	21.6	0.0386	0.0	21.6	0.8007				0.019

Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	0	0.0000	0.0000
2	0.017	1	0.0001	0.0001
3	0.033	1	0.0001	0.0001
4	0.050	1	0.0001	0.0001
5	0.067	1	0.0001	0.0001
6	0.083	1	0.0001	0.0001
7	0.100	4	0.0004	0.0004
8	0.200	5	0.0005	0.0005
9	0.400	6	0.0006	0.0006
10	0.800	7	0.0007	0.0007
11	1.000	7	0.0007	0.0007
12	2.000	9	0.0009	0.0009
13	4.000	9	0.0009	0.0009
14	8.000	10	0.0010	0.0010
15	10.000	10	0.0010	0.0010
16	20.000	11	0.0011	0.0011
17	40.000	11	0.0011	0.0011
18	46.167	11	0.0011	0.0011


	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
Operator: <i>mlc</i>	Checked: <i>mlc</i>	Borehole:	EB2-A LT LN
		Approved:	

	ASTM D2435-96	Test name	Consolidation Load: 0.050 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
Operator: <i>mlc</i>	Checked: <i>mlc</i>	Borehole:	EB2-A LT LN
		Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.050
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0011
Voids Ratio e	0.8712
Final Temp oC	0.0
t ₅₀ (mins)	0.86
c _v (ft ² /day)	0.577
m _v (ft ² /ton)	0.022
Sec Compression C _{sec}	0.00



Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	11	0.0011	0.0011
2	0.017	14	0.0014	0.0014
3	0.033	23	0.0023	0.0023
4	0.050	26	0.0026	0.0026
5	0.067	27	0.0027	0.0027
6	0.083	28	0.0028	0.0028
7	0.100	29	0.0029	0.0029
8	0.200	32	0.0032	0.0032
9	0.400	35	0.0035	0.0035
10	0.800	37	0.0037	0.0037
11	1.000	38	0.0038	0.0038
12	2.000	40	0.0040	0.0040
13	4.000	41	0.0041	0.0041
14	8.000	42	0.0042	0.0042
15	10.000	42	0.0042	0.0042
16	20.000	43	0.0043	0.0043
17	35.867	43	0.0043	0.0043


	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>MLK</i>	Borehole: EB2-A LT LN
	Checked: <i>MLK</i>	Approved:

	ASTM D2435-96	Test name: Consolidation Load: 0.250 (TSF)
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>MLK</i>	Borehole: EB2-A LT LN
	Checked: <i>MLK</i>	Approved:

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.250
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0032
Voids Ratio e	0.8651
Final Temp oC	0.0
t ₅₀ (mins)	0.37
c _v (ft ² /day)	1.347
m _v (ft ² /ton)	0.016
Sec Compression C _{sec}	0.0001



Oedometer Settlement Tests

No.	Time (mins)	Disolacement (divs)	Displacement (in)	Settlement (in)
1	0.000	43	0.0043	0.0043
2	0.017	50	0.0050	0.0050
3	0.033	57	0.0057	0.0057
4	0.050	59	0.0059	0.0059
5	0.067	61	0.0061	0.0061
6	0.083	62	0.0062	0.0062
7	0.100	64	0.0064	0.0064
8	0.200	68	0.0068	0.0068
9	0.400	72	0.0072	0.0072
10	0.800	76	0.0076	0.0076
11	1.000	78	0.0078	0.0078
12	2.000	80	0.0080	0.0080
13	4.250	82	0.0082	0.0082
14	8.250	84	0.0084	0.0084
15	10.250	84	0.0084	0.0084
16	20.250	85	0.0085	0.0085
17	40.250	86	0.0086	0.0086
18	67.350	86	0.0086	0.0086


	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
	Operator: <i>mlc</i>	Borehole:	EB2-A LT LN
	Checked: <i>mlc</i>	Approved:	

	ASTM D2435-96	Test name	Consolidation Load: 0.500 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
	Operator: <i>mlc</i>	Borehole:	EB2-A LT LN
	Checked: <i>mlc</i>	Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.500
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0043
Voids Ratio e	0.8571
Final Temp oC	0.0
t ₅₀ (mins)	0.39
c _v (ft ² /day)	1.248
m _v (ft ² /ton)	0.017
Sec Compression C _{sec}	0.0002



Oedometer Settlement Tests


No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	86	0.0086	0.0086
2	0.017	90	0.0090	0.0090
3	0.033	90	0.0090	0.0090
4	0.050	109	0.0109	0.0109
5	0.067	116	0.0116	0.0116
6	0.083	118	0.0118	0.0118
7	0.100	121	0.0121	0.0121
8	0.200	129	0.0129	0.0129
9	0.400	138	0.0138	0.0138
10	0.800	147	0.0147	0.0147
11	1.000	150	0.0150	0.0150
12	2.000	155	0.0155	0.0155
13	4.000	159	0.0159	0.0159
14	8.000	160	0.0160	0.0160
15	10.000	160	0.0160	0.0160
16	20.000	161	0.0161	0.0161
17	40.000	163	0.0163	0.0163
18	80.000	164	0.0164	0.0164
19	100.000	164	0.0164	0.0164
20	200.000	165	0.0165	0.0165
21	400.000	165	0.0165	0.0165
22	800.000	166	0.0166	0.0166
23	1039.917	166	0.0166	0.0166

	ASTM D2435-96	Test name	Consolidation Load: 1.000 (TSF)
		Date of Test:	12-16-16
	Site Reference: C.F. Harvey	Sample:	ST-2
	Jobfile: E:\16010.JOB	Borehole:	EB2-A LT LN
Operator: <i>mlc</i>	Checked: <i>mlc</i>	Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	1.000
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.008
Voids Ratio e	0.8420
Final Temp oC	0.0
t ₅₀ (mins)	0.36
c _v (ft ² /day)	1.362
m _v (ft ² /ton)	0.016
Sec Compression C _{sec}	0.0002



Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	166	0.0166	0.0166
2	0.017	169	0.0169	0.0169
3	0.033	189	0.0189	0.0189
4	0.050	206	0.0206	0.0206
5	0.067	212	0.0212	0.0212
6	0.083	220	0.0220	0.0220
7	0.100	223	0.0223	0.0223
8	0.200	237	0.0237	0.0237
9	0.400	253	0.0253	0.0253
10	0.800	268	0.0268	0.0268
11	1.000	272	0.0272	0.0272
12	2.000	283	0.0283	0.0283
13	4.000	289	0.0289	0.0289
14	8.000	292	0.0292	0.0292
15	10.000	293	0.0293	0.0293
16	20.000	295	0.0295	0.0295
17	40.000	296	0.0296	0.0296
18	80.000	297	0.0297	0.0297
19	96.330	297	0.0297	0.0297


	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
	Operator: <i>mk</i>	Borehole:	EB2-A LT LN
	Checked: <i>mk</i>	Approved:	

	ASTM D2435-96	Test name	Consolidation Load: 2.000 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
	Operator: <i>mk</i>	Borehole:	EB2-A LT LN
	Checked: <i>mk</i>	Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	2.000
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0131
Voids Ratio e	0.8174
Final Temp oC	0.0
t ₅₀ (mins)	0.36
c _v (ft ² /day)	1.322
m _v (ft ² /ton)	0.014
Sec Compression C _{sec}	0.0002



Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	297	0.0297	0.0297
2	0.017	301	0.0301	0.0301
3	0.033	315	0.0315	0.0315
4	0.050	373	0.0373	0.0373
5	0.067	381	0.0381	0.0381
6	0.083	387	0.0387	0.0387
7	0.100	396	0.0396	0.0396
8	0.200	422	0.0422	0.0422
9	0.400	452	0.0452	0.0452
10	0.800	485	0.0485	0.0485
11	1.000	495	0.0495	0.0495
12	2.000	523	0.0523	0.0523
13	4.000	540	0.0540	0.0540
14	8.000	548	0.0548	0.0548
15	10.000	550	0.0550	0.0550
16	20.000	553	0.0553	0.0553
17	40.000	557	0.0557	0.0557
18	65.600	559	0.0559	0.0559


	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mlc</i>	Borehole: EB2-A LT LN
Checked: <i>mlc</i>	Approved:	

	ASTM D2435-96	Test name: Consolidation Load: 4.000 (TSF)
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mlc</i>	Borehole: EB2-A LT LN
Checked: <i>mlc</i>	Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	4.000
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0262
Voids Ratio e	0.7682
Final Temp oC	0.0
t ₅₀ (mins)	0.40
c _v (ft ² /day)	1.145
m _v (ft ² /ton)	0.014
Sec Compression C _{sec}	0.0011



Oedometer Settlement Tests

No.	Time (mins)	Disolacement (divs)	Displacement (in)	Settlement (in)
1	0.000	559	0.0559	0.0559
2	0.017	556	0.0556	0.0556
3	0.033	556	0.0556	0.0556
4	0.050	545	0.0545	0.0545
5	0.067	544	0.0544	0.0544
6	0.083	543	0.0543	0.0543
7	0.100	542	0.0542	0.0542
8	0.200	540	0.0540	0.0540
9	0.400	539	0.0539	0.0539
10	0.800	537	0.0537	0.0537
11	1.000	537	0.0537	0.0537
12	2.000	536	0.0536	0.0536
13	4.000	536	0.0536	0.0536
14	8.000	535	0.0535	0.0535
15	10.000	535	0.0535	0.0535
16	20.000	535	0.0535	0.0535
17	40.000	535	0.0535	0.0535
18	55.167	535	0.0535	0.0535


	ASTM D2435-96	Test name	Consolidation
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
	Operator: <i>MLC</i>	Borehole:	EB2-A LT LN
	Checked: <i>MLC</i>	Approved:	

	ASTM D2435-96	Test name	Consolidation Load: 2.000 (TSF)
	Site Reference: C.F. Harvey	Date of Test:	12-16-16
	Jobfile: E:\16010.JOB	Sample:	ST-2
	Operator: <i>MLC</i>	Borehole:	EB2-A LT LN
	Checked: <i>MLC</i>	Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF) 2.000
 Initial Temp oC 21.6
 Correction (in) 0.0
 Settlement (in) 0.0024
 Voids Ratio e 0.7727
 Final Temp oC
 t₅₀ (mins)
 c_v (ft²/day)
 m_v (ft²/ton)
 Sec Compression C_{sec}



Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	535	0.0535	0.0535
2	0.017	534	0.0534	0.0534
3	0.033	534	0.0534	0.0534
4	0.050	525	0.0525	0.0525
5	0.067	521	0.0521	0.0521
6	0.083	513	0.0513	0.0513
7	0.100	510	0.0510	0.0510
8	0.200	503	0.0503	0.0503
9	0.400	497	0.0497	0.0497
10	0.800	489	0.0489	0.0489
11	1.000	486	0.0486	0.0486
12	2.000	479	0.0479	0.0479
13	4.000	474	0.0474	0.0474
14	8.000	472	0.0472	0.0472
15	10.000	471	0.0471	0.0471
16	20.000	470	0.0470	0.0470
17	40.000	469	0.0469	0.0469
18	80.000	468	0.0468	0.0468
19	100.000	468	0.0468	0.0468
20	163.330	468	0.0468	0.0468

	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mk</i>	Borehole: EB2-A LT LN
Checked: <i>mk</i>	Approved:	


	ASTM D2435-96	Test name: Consolidation Load: 0.500 (TSF)
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mk</i>	Borehole: EB2-A LT LN
Checked: <i>mk</i>	Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF) 0.500
 Initial Temp oC 21.6
 Correction (in) 0.0
 Settlement (in) 0.0067
 Voids Ratio e 0.7853

Final Temp oC
 t_{50} (mins)
 c_v (ft²/day)
 m_v (ft²/ton)
 Sec Compression C_{sec}



Oedometer Settlement Tests

No.	Time (mins)	Displacement (divs)	Displacement (in)	Settlement (in)
1	0.000	468	0.0468	0.0468
2	0.017	465	0.0465	0.0465
3	0.033	465	0.0465	0.0465
4	0.050	458	0.0458	0.0458
5	0.067	455	0.0455	0.0455
6	0.083	453	0.0453	0.0453
7	0.100	453	0.0453	0.0453
8	0.200	448	0.0448	0.0448
9	0.400	441	0.0441	0.0441
10	0.800	432	0.0432	0.0432
11	1.000	429	0.0429	0.0429
12	2.000	417	0.0417	0.0417
13	4.000	405	0.0405	0.0405
14	8.000	397	0.0397	0.0397
15	10.000	395	0.0395	0.0395
16	20.000	391	0.0391	0.0391
17	40.000	388	0.0388	0.0388
18	80.000	387	0.0387	0.0387
19	100.000	386	0.0386	0.0386
20	147.470	386	0.0386	0.0386


	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mk</i>	Borehole: EB2-A LT LN
Checked: <i>mk</i>	Approved:	

	ASTM D2435-96	Test name: Consolidation Load: 0.050 (TSF)
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: <i>mk</i>	Borehole: EB2-A LT LN
Checked: <i>mk</i>	Approved:	

Oedometer Settlement Tests

Settlement Stage Results

Vertical Stress (TSF)	0.050
Initial Temp oC	21.6
Correction (in)	0.0
Settlement (in)	0.0082
Void Ratio e	0.8007
Final Temp oC	
t ₅₀ (mins)	
c _v (ft ² /day)	
m _v (ft ² /ton)	
Sec Compression C _{sec}	



	ASTM D2435-96	Test name: Consolidation
	Site Reference: C.F. Harvey	Date of Test: 12-16-16
	Jobfile: E:\16010.JOB	Sample: ST-2
	Operator: MK	Borehole: EB2-A LT LN
Checked: MK	Approved:	

Form No. TR-T88

Revision No. 0

Revision Date: 12/20/09


Particle Size Analysis of Soils

AASHTO T88 as Modified by NCDOT



Quality Assurance

S&ME, Inc. Raleigh, 3201 Spring Forest Road, Raleigh, North Carolina 27616			
S&ME Project #:	6235-16-010	Report Date:	11/14/16
Project Name:	C.F. Harvey Parkway Extension R-5703	Test Date(s):	10/7 - 11/14/16
State Project #:	N/A	F.A. Project No:	N/A
Client Name:	Michael Baker Engineering	TIP NO:	N/A
Address:	Raleigh, NC		
Boring #:	EB2-B RT LN	Sample #:	SS-7
Location:	89+45	Sample Date:	N/A
Sample Description:	Gray Coarse to Fine Sandy Clayey SILT	Offset:	33 RT
		Depth (ft):	1.0 - 2.5
			A-4 (1)



As Defined by NCDOT		Fine Sand	< 0.25 mm and > 0.05 mm
Gravel	< 75 mm and > 2.00 mm	Silt	< 0.05 and > 0.005 mm
Coarse Sand	< 2.00 mm and > 0.25 mm	Clay	< 0.005 mm

Maximum Particle Size	#4	Coarse Sand	16%	Silt	21%
Gravel	0%	Fine Sand	43%	Clay	20%
Apparent Relative Density	ND	Moisture Content	13.4%	% Passing #200	47.4%
Liquid Limit	21	Plastic Limit	13	Plastic Index	8

Soil Mortar (-#10 Sieve)					
Coarse Sand	16%	Fine Sand	43%	Silt	21%
				Clay	20%

Description of Sand & Gravel Particles:	Rounded	<input type="checkbox"/>	Angular	<input type="checkbox"/>	
Hard & Durable	<input type="checkbox"/>	Soft	<input type="checkbox"/>	Weathered & Friable	<input type="checkbox"/>

References / Comments / Deviations: ND=Not Determined.

Mal Krajan, ET
Technician Name

104-01-0703
Certification No.

Laboratory Manager
Position

11/14/2016
Date

Mal Krajan, ET
Technical Responsibility

Signature

Laboratory Manager
Position

11/14/2016
Date

This report shall not be reproduced, except in full, without the written approval of S&ME, Inc.

Form No: TR-T267
 Revision No. 0
 Revision Date: 07/10/08

Moisture, Ash, and Organic Matter



AASHTO T-267

Quality Assurance

S&ME, Inc. Raleigh, 3201 Spring Forest Road, Raleigh, North Carolina 27616			
Project #:	6235-16-010	Report Date:	10/21/16
Project Name:	C.F. Harvey Parkway Extension R-5703	Test Date(s):	10/18 - 10/21/16
Client Name:	Michael Baker Engineering		
Client Address:	Raleigh, NC		
Boring #:	EB2-B RT LN	Sample #:	SS-7
		Sample Date:	N/A
Location:	89+45	Offset:	33 RT
		Depth (ft):	1.0 - 2.5
Sample Description: Gray Coarse to Fine Sandy Clayey SILT (A-4) (1)			
Equipment: Balance: 0.01 g. Readability, 500g. Minimum Capacity			
Balance:	S&ME ID #: 1024	Cal. Date:	11/06/16
		Due:	11/06/17

Method A: Moisture Content Determination

Required Oven Temperature: 105 ± 5 °C

Oven Temperature: 105 °C		Tare #	h
t	Tare Weight (Dish plus Aluminum Foil Cover)	grams	45.60
a	Mass of As-Received Specimen + Tare Wt.	grams	91.99
b	Mass of Oven Dry Specimen + Tare Wt.	grams	86.51
w	Water Weight	(a-b)	5.48
A	Mass of As-Received Specimen	(a-t)	46.39
B	Mass of Oven Dry Specimen	(b-t)	40.91
% Moisture Content as a % of As Received or Total Mass		(w/A)*100	11.8%
% Moisture Content as a % of Oven-dried Mass		(w/B)*100	13.4%

Oven	S&ME ID #: 1454	Cal. Date:	10/7/16	Due:	10/7/17
------	-----------------	------------	---------	------	---------

Method C (440° C) or D (750° C): Ash Content and Organic Matter Determination

Muffle Furnace: 455 °C		Tare #	84
t	Tare Weight (Dish plus Aluminum Foil Cover)	grams	49.60
b	Mass of Oven Dry Specimen + Tare Wt.	grams	85.32
c	Ash Weight + Tare Wt.	grams	84.68
C	Ash Weight	c-t	35.08
B	Mass of Oven Dry Specimen	(b-t)	35.72
D	% Ash Content	(C/B)*100	98.2%
	% Organic Matter	100-D	1.8%

Muffle Furnace:	S&ME ID #: 00261
-----------------	------------------

Notes / Deviations / References:

Mal Krajan, ET
 Technical Responsibility

Signature

Laboratory Manager
 Position

11/14/2016
 Date

This report shall not be reproduced, except in full, without the written approval of S&ME, Inc.

Form No: TR-T289-1
 Revision No. 0
 Revision Date: 07/10/08

pH of Soil



AASHTO T289

Quality Assurance

S&ME, Inc. Raleigh, 3201 Spring Forest Road, Raleigh, North Carolina 27616					
Project #:	6235-16-010	Report Date:	11/7/16		
Project Name:	C.F. Harvey Parkway Extension R-5703	Test Date(s):	11/5 - 11/7/16		
Client Name:	Michael Baker Engineering				
Client Address:	Raleigh, NC				
Boring #:	EB2-B RT LN	Sample #:	SS-7	Sample Date:	N/A
Location:	89+45	Offset:	33 RT	Depth (ft):	1.0 - 2.5
Sample Description: Gray Coarse to Fine Sandy Clayey SILT (A-4) (1)					
Equipment:					
Balance	S&ME ID# 1024	Cal. Date:	11/6/16	Due:	11/6/17
Sieve: #10	S&ME ID# 13223	Cal. Date:	6/11/16	Due:	6/11/17
pH Meter:	S&ME ID# 1365	Cal. Date:	11/7/16	Due:	NA

pH Meter Calibration

Buffer Solution	Results
pH buffer 7.0	7.02
pH buffer 4.01	4.01
pH buffer 10.0	10.03
Buffer Temperature °C	22.4

Measuring pH of Soil

Measurements	
Weight of Air Dry Soil (g)	30.00
Distilled Water (g)	30.01
Temperature °C	22.2
pH Readings	5.69

Notes / Deviations / References: AASHTO T-289: Determining pH of Soil for Use in Corrosion Testing

Mal Krajan, ET
 Technical Responsibility

Signature

Laboratory Manager
 Position

11/14/2016
 Date

This report shall not be reproduced, except in full, without the written approval of S&ME, Inc.