

AS-BUILT REPAIR QUANTITY TABLE									
BENT 4 REPAIRS	QUANTITIES								
DENI 4 REFAIRS	ESTI	ACTUAL							
SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	DEPTH FT	VOLUME CF				
CAP (VERTICAL FACE)	17.0	8.5							
CAP (HORIZONTAL, CORNER)	0	0							
COLUMN	0	0							

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1" BEHIND REBAR AND MIN. 2"CL TO SAWCUT. SEE REPAIR DETAILS.

NOTES:

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION AVAILABLE, IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE INSPECTOR OR ENGINEER THE CONTRACTOR SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ADJUST THE ACTUAL QUANTITIES ENTERED INTO THE REPAIR QUANTITY TABLE.

SHOTCRETE REPAIRS MAY BE REPLACED WITH CONCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIR DETAILS, SEE "TYPICAL CAP & COLUMN REPAIR DETAILS" SHEET.

- SHOTCRETE REPAIR

- CONCRETE REPAIR

	PROJECT NO. <u>I-5889A</u> <u>BUNCOMBE</u> county Bridge no. <u>352</u>							
	RTH CAROL ROFESSION SEAL 020208	STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH						
	DocuSigned by: Ein BARL A 11/16/2017 BA9F91762D7044A	BENT 4 SPAN D SIDE						
Road			SHEET NO.					
607-3073	DOCUMENT NOT CONSIDERED	NO. BY:	DATE:	NO. BY:	DATE:	S-60		
0 •0270	FINAL UNLESS ALL SIGNATURES COMPLETED	1		3 4		TOTAL SHEETS		
	SIGNATURES CUMFLETED	ß		代		208		