

**This electronic collection of documents is provided  
for the convenience of the user  
and is Not a Certified Document –**

**The documents contained herein were originally issued  
and sealed by the individuals whose names and license  
numbers appear on each page, on the dates appearing  
with their signature on that page.**

**This file or an individual page  
shall not be considered a certified document.**

REFERENCE: R-5749

PROJECT: 53086

**STATE OF NORTH CAROLINA**  
**DEPARTMENT OF TRANSPORTATION**  
**DIVISION OF HIGHWAYS**  
**GEOTECHNICAL ENGINEERING UNIT**

**ROADWAY**  
**SUBSURFACE INVESTIGATION**

COUNTY COLUMBUS  
 PROJECT DESCRIPTION US 74-76 AT SR 1001  
(HALLSBORO ROAD), CONVERT AT GRADE  
INTERSECTION TO INTERCHANGE

**INVENTORY**

**CONTENTS**

LINE	STATION	PLAN	PROFILE
-L-	20+00 TO 83+14	4-7	9-11
-YRPA-	5+00 TO 25+80	5,6,8	12
-YRPB-	5+00 TO 24+85	5,8	13
-YRPC-	5+00 TO 27+31	5	14
-YRPD-	5+00 TO 25+73	5,6	15
-Y-	17+55 TO 42+00	5,8	16
-DET-	8+90 TO 34+07	5,8	17

**CROSS SECTIONS**

LINE	STATION	SHEETS
-L-	20+50 TO 21+50	18
-L-	22+50 TO 23+50	19
-L-	24+50 TO 25+50	20-21
-L-	26+50 TO 27+50	21-22
-L-	28+50 TO 29+50	23-24
-L-	30+50 TO 31+50	24-25
-L-	32+50 TO 33+50	26-27
-L-	34+50 TO 35+50	27-28
-L-	36+00 TO 37+50	29
-L-	38+50 TO 39+50	30
-L-	40+50 TO 41+50	31
-L-	42+50 TO 43+50	32-33
-L-	44+50 TO 45+50	33-34
-L-	46+50 TO 47+50	35-36
-L-	48+50 TO 49+50	36-37
-L-	51+00 TO 53+50	38-42
-L-	54+50 TO 55+50	43
-L-	56+50 TO 57+50	44-45
-L-	58+50 TO 59+50	45-46
-L-	60+50 TO 61+50	47-48
-L-	62+50 TO 63+50	48-49
-L-	64+50 TO 65+50	50-51
-L-	66+50 TO 69+50	51-53
-L-	70+50 TO 71+10	54-55
-L-	72+81 TO 83+14	55-62
-YRPA-	9+00 TO 25+50	63-75
-YRPB-	9+00 TO 24+50	76-87
-YRPC-	10+50 TO 17+50	88-92
-YRPC-	18+50 TO 19+50	93-94
-YRPC-	20+50 TO 27+00	94-99
-YRPD-	9+50 TO 15+50	100-102
-YRPD-	16+50 TO 25+50	102-108
-Y-	17+55 TO 18+50	109
-Y-	19+50 TO 23+00	110-113
-Y-	24+00 TO 26+50	114-116
-Y-	28+50 TO 31+50	117-123
-Y-	32+50 TO 33+50	124-126
-Y-	34+50 TO 35+50	126-127
-Y-	36+50 TO 37+50	128
-Y-	38+50 TO 41+50	129-130
-DET-	11+00 TO 20+50	131-136
-DET-	21+50 TO 22+00	137
-DET-	23+50 TO 30+50	138-144

**APPENDICES**

APPENDIX	TITLE	SHEETS
A	LABORATORY RESULTS	145-146

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5749	1	146

**CAUTION NOTICE**

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT 1919 T07-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
  2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

- T. WELLS
- B. JOHNSON
- D. KUBINSKI
- G. EISTER
- G. BRIDGER
- M. RADFORD

INVESTIGATED BY B. JOHNSON

DRAWN BY B. JOHNSON

CHECKED BY X. BARRETT

SUBMITTED BY KLEINFELDER, INC.

DATE NOVEMBER 2016

NC REGISTERED FIRM LICENSE NO. F-1132



DocuSigned by:  
Xavier C. Barrett 11/28/2016

2D00374FA588407 SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL  
 UNLESS ALL SIGNATURES COMPLETED**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
 DIVISION OF HIGHWAYS  
 GEOTECHNICAL ENGINEERING UNIT  
**SUBSURFACE INVESTIGATION**  
 SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																																																							
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6										WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.										HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:										ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																																																							
<p><b>SOIL LEGEND AND AASHTO CLASSIFICATION</b></p> <table border="1"> <tr> <th>GENERAL CLASS.</th> <th colspan="6">GRANULAR MATERIALS (<math>\leq 35\%</math> PASSING #200)</th> <th colspan="4">SILT-CLAY MATERIALS (<math>&gt; 35\%</math> PASSING #200)</th> <th colspan="4">ORGANIC MATERIALS</th> </tr> <tr> <th>GROUP CLASS.</th> <th>A-1</th> <th>A-1-b</th> <th>A-2</th> <th>A-2-4</th> <th>A-2-5</th> <th>A-2-6</th> <th>A-2-7</th> <th>A-4</th> <th>A-5</th> <th>A-6</th> <th>A-7</th> <th>A-1, A-2</th> <th>A-3</th> <th>A-4, A-5</th> <th>A-6, A-7</th> <th></th> </tr> <tr> <th>SYMBOL</th> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> <td colspan="2">○○○○○○○○○○</td> </tr> <tr> <th>% PASSING</th> <td colspan="2">50 MX</td> <td colspan="2">30 MX</td> <td colspan="2">10 MX</td> <td colspan="2">5 MN</td> <td colspan="2">35 MX</td> <td colspan="2">35 MX</td> <td colspan="2">35 MX</td> <td colspan="2">35 MX</td> </tr> <tr> <th>MATERIAL PASSING #40</th> <td colspan="2">-</td> <td colspan="2">-</td> <td colspan="2">40 MX</td> <td colspan="2">41 MN</td> <td colspan="2">40 MX</td> <td colspan="2">41 MN</td> <td colspan="2">40 MX</td> <td colspan="2">41 MN</td> </tr> <tr> <th>GROUP INDEX</th> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">0</td> <td colspan="2">4 MX</td> <td colspan="2">8 MX</td> <td colspan="2">12 MX</td> <td colspan="2">16 MX</td> <td colspan="2">NO MX</td> </tr> </table>										GENERAL CLASS.	GRANULAR MATERIALS ( $\leq 35\%$ PASSING #200)						SILT-CLAY MATERIALS ( $> 35\%$ PASSING #200)				ORGANIC MATERIALS				GROUP CLASS.	A-1	A-1-b	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7		SYMBOL	○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		% PASSING	50 MX		30 MX		10 MX		5 MN		35 MX		35 MX		35 MX		35 MX		MATERIAL PASSING #40	-		-		40 MX		41 MN		40 MX		41 MN		40 MX		41 MN		GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		16 MX		NO MX		<p><b>MINERALOGICAL COMPOSITION</b></p> <p>MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p> <p><b>COMPRESSION</b></p> <p>SLIGHTLY COMPRESSIBLE LL &lt; 31      MODERATELY COMPRESSIBLE LL = 31 - 50      HIGHLY COMPRESSIBLE LL &gt; 50</p> <p><b>PERCENTAGE OF MATERIAL</b></p> <table border="1"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>&gt; 10%</td> <td>&gt; 20%</td> <td>HIGHLY</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY	<p><b>WEATHERING</b></p> <p>FRESH - ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> <p>VERY SLIGHT (V SL.) - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> <p>SLIGHT (SL.) - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> <p>MODERATE (MOD.) - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> <p>MODERATELY SEVERE (MOD. SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL.</p> <p>SEVERE (SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES &gt; 100 BPF.</p> <p>VERY SEVERE (V SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES &lt; 100 BPF.</p> <p>COMPLETE - ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. FABRIC MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>									
GENERAL CLASS.	GRANULAR MATERIALS ( $\leq 35\%$ PASSING #200)						SILT-CLAY MATERIALS ( $> 35\%$ PASSING #200)				ORGANIC MATERIALS																																																																																																																																										
GROUP CLASS.	A-1	A-1-b	A-2	A-2-4	A-2-5	A-2-6	A-2-7	A-4	A-5	A-6	A-7	A-1, A-2	A-3	A-4, A-5	A-6, A-7																																																																																																																																						
SYMBOL	○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○		○○○○○○○○○○																																																																																																																																						
% PASSING	50 MX		30 MX		10 MX		5 MN		35 MX		35 MX		35 MX		35 MX																																																																																																																																						
MATERIAL PASSING #40	-		-		40 MX		41 MN		40 MX		41 MN		40 MX		41 MN																																																																																																																																						
GROUP INDEX	0		0		0		4 MX		8 MX		12 MX		16 MX		NO MX																																																																																																																																						
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																																																		
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																																																		
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																																																		
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																																																		
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY																																																																																																																																																		
<p><b>TEXTURE OR GRAIN SIZE</b></p> <table border="1"> <tr> <th>U.S. STD. SIEVE SIZE OPENING (MM)</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <td></td> <td>4.76</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table> <table border="1"> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table> <table border="1"> <tr> <th>GRAIN SIZE</th> <th>MM</th> <th>305</th> <th>75</th> <th>2.0</th> <th>0.25</th> <th>0.05</th> <th>0.005</th> </tr> <tr> <td></td> <td>IN.</td> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270		4.76	2.00	0.42	0.25	0.075	0.053	BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)								GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005		IN.	12	3					<p><b>MISCELLANEOUS SYMBOLS</b></p> <p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION</p> <p>SOIL SYMBOL</p> <p>ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT</p> <p>INFERRED SOIL BOUNDARY</p> <p>INFERRED ROCK LINE</p> <p>ALLUVIAL SOIL BOUNDARY</p> <p>DIP &amp; DIP DIRECTION OF ROCK STRUCTURES</p> <p>SPT TEST BORING</p> <p>AUGER BORING</p> <p>CORE BORING</p> <p>MONITORING WELL</p> <p>PIEZOMETER INSTALLATION</p> <p>SLOPE INDICATOR INSTALLATION</p> <p>CONE PENETROMETER TEST</p> <p>SOUNDING ROD</p> <p>TEST BORING WITH CORE</p> <p>SPT N-VALUE</p>																																																																																															
U.S. STD. SIEVE SIZE OPENING (MM)	4	10	40	60	200	270																																																																																																																																															
	4.76	2.00	0.42	0.25	0.075	0.053																																																																																																																																															
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																																															
GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005																																																																																																																																														
	IN.	12	3																																																																																																																																																		
<p><b>CONSISTENCY OR DENSENESS</b></p> <table border="1"> <tr> <th>PRIMARY SOIL TYPE</th> <th>COMPACTNESS OR CONSISTENCY</th> <th>RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)</th> <th>RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT<sup>2</sup>)</th> </tr> <tr> <td>GENERALLY GRANULAR MATERIAL (NON-COHESIVE)</td> <td>VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE</td> <td>&lt; 4 4 TO 10 10 TO 30 30 TO 50 &gt; 50</td> <td>N/A</td> </tr> <tr> <td>GENERALLY SILT-CLAY MATERIAL (COHESIVE)</td> <td>VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD</td> <td>&lt; 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 &gt; 30</td> <td>&lt; 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 &gt; 4</td> </tr> </table>										PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )	GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A	GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4	<p><b>RECOMMENDATION SYMBOLS</b></p> <p>UNDERCUT</p> <p>SHALLOW UNDERCUT</p> <p>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE</p> <p>UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</p> <p>UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL</p>																																																																																																																															
PRIMARY SOIL TYPE	COMPACTNESS OR CONSISTENCY	RANGE OF STANDARD PENETRATION RESISTANCE (N-VALUE)	RANGE OF UNCONFINED COMPRESSIVE STRENGTH (TONS/FT <sup>2</sup> )																																																																																																																																																		
GENERALLY GRANULAR MATERIAL (NON-COHESIVE)	VERY LOOSE LOOSE MEDIUM DENSE DENSE VERY DENSE	< 4 4 TO 10 10 TO 30 30 TO 50 > 50	N/A																																																																																																																																																		
GENERALLY SILT-CLAY MATERIAL (COHESIVE)	VERY SOFT SOFT MEDIUM STIFF STIFF VERY STIFF HARD	< 2 2 TO 4 4 TO 8 8 TO 15 15 TO 30 > 30	< 0.25 0.25 TO 0.5 0.5 TO 1.0 1 TO 2 2 TO 4 > 4																																																																																																																																																		
<p><b>SOIL MOISTURE - CORRELATION OF TERMS</b></p> <table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE SHRINKAGE LIMIT</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<p><b>ABBREVIATIONS</b></p> <p>AR - AUGER REFUSAL      BT - BORING TERMINATED      CL - CLAY      CPT - COARSE PENETRATION TEST      CSE - COARSE      DMT - DILATOMETER TEST      DPT - DYNAMIC PENETRATION TEST      e - VOID RATIO      F - FINE      FOSS. - FOSSILIFEROUS      FRAC. - FRACTURED, FRACTURES      FRAGS. - FRAGMENTS      HI. - HIGHLY</p> <p>MED. - MEDIUM      MICA - MICACEOUS      MOD. - MODERATELY      NP - NON PLASTIC      ORG. - ORGANIC      PMT - PRESSUREMETER TEST      SAP. - SAPROLITIC      SD. - SAND, SANDY      SL. - SILTY, SILTY      SLI. - SLIGHTLY      TCR - TRICONE REFUSAL      w - MOISTURE CONTENT      V - VERY</p> <p>VST - VANE SHEAR TEST      WEA. - WEATHERED      W - UNIT WEIGHT      W<sub>d</sub> - DRY UNIT WEIGHT</p> <p>SAMPLE ABBREVIATIONS      S - BULK      SS - SPLIT SPOON      ST - SHELBY TUBE      RS - ROCK      RT - RECOMPACTED TRIAXIAL      CBR - CALIFORNIA BEARING RATIO</p>																																																																																																																												
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																																																			
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																																																			
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																			
OM - OPTIMUM MOISTURE SHRINKAGE LIMIT	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																																																			
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																																																			
<p><b>PLASTICITY</b></p> <table border="1"> <tr> <th>NON PLASTIC</th> <th>SLIGHTLY PLASTIC</th> <th>MODERATELY PLASTIC</th> <th>HIGHLY PLASTIC</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> </tr> </table> <p>PLASTICITY INDEX (PI)      0-5 VERY LOW      6-15 SLIGHT      16-25 MEDIUM      26 OR MORE HIGH</p> <p>DRY STRENGTH      VERY LOW      SLIGHT      MEDIUM      HIGH</p>										NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC					<p><b>EQUIPMENT USED ON SUBJECT PROJECT</b></p> <p>DRILL UNITS:  <input checked="" type="checkbox"/> CME-45C  <input type="checkbox"/> CME-55  <input type="checkbox"/> CME-550  <input type="checkbox"/> VANE SHEAR TEST  <input type="checkbox"/> PORTABLE HOIST</p> <p>ADVANCING TOOLS:  <input type="checkbox"/> CLAY BITS  <input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER  <input type="checkbox"/> 8" HOLLOW AUGERS  <input type="checkbox"/> HARD FACED FINGER BITS  <input type="checkbox"/> TUNG-CARBIDE INSERTS  <input checked="" type="checkbox"/> CASING  <input type="checkbox"/> w/ ADVANCER  <input checked="" type="checkbox"/> TRICONE 2 15/16" STEEL TEETH  <input type="checkbox"/> TRICONE  <input type="checkbox"/> CORE BIT</p> <p>HAMMER TYPE:  <input checked="" type="checkbox"/> AUTOMATIC  <input type="checkbox"/> MANUAL</p> <p>CORE SIZE:  <input type="checkbox"/> -B  <input type="checkbox"/> -H  <input type="checkbox"/> -N</p> <p>HAND TOOLS:  <input type="checkbox"/> POST HOLE DIGGER  <input checked="" type="checkbox"/> HAND AUGER  <input type="checkbox"/> SOUNDING ROD  <input type="checkbox"/> VANE SHEAR TEST</p>																																																																																																																																			
NON PLASTIC	SLIGHTLY PLASTIC	MODERATELY PLASTIC	HIGHLY PLASTIC																																																																																																																																																		
<p><b>FRACURE SPACING</b></p> <table border="1"> <tr> <th>TERM</th> <th>SPACING</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> </tr> </table>										TERM	SPACING	VERY WIDE	MORE THAN 10 FEET	WIDE	3 TO 10 FEET	MODERATELY CLOSE	1 TO 3 FEET	CLOSE	0.16 TO 1 FOOT	VERY CLOSE	LESS THAN 0.16 FEET	<p><b>BEDDING</b></p> <table border="1"> <tr> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td>THINLY LAMINATED</td> <td>&lt; 0.008 FEET</td> </tr> </table>										TERM	THICKNESS	VERY THICKLY BEDDED	4 FEET	THICKLY BEDDED	1.5 - 4 FEET	THINLY BEDDED	0.16 - 1.5 FEET	VERY THINLY BEDDED	0.03 - 0.16 FEET	THINLY LAMINATED	0.008 - 0.03 FEET	THINLY LAMINATED	< 0.008 FEET																																																																																																								
TERM	SPACING																																																																																																																																																				
VERY WIDE	MORE THAN 10 FEET																																																																																																																																																				
WIDE	3 TO 10 FEET																																																																																																																																																				
MODERATELY CLOSE	1 TO 3 FEET																																																																																																																																																				
CLOSE	0.16 TO 1 FOOT																																																																																																																																																				
VERY CLOSE	LESS THAN 0.16 FEET																																																																																																																																																				
TERM	THICKNESS																																																																																																																																																				
VERY THICKLY BEDDED	4 FEET																																																																																																																																																				
THICKLY BEDDED	1.5 - 4 FEET																																																																																																																																																				
THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																																																				
VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																																																				
THINLY LAMINATED	0.008 - 0.03 FEET																																																																																																																																																				
THINLY LAMINATED	< 0.008 FEET																																																																																																																																																				
<p><b>INDURATION</b></p> <p>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</p> <p>FRIABLE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</p> <p>MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</p> <p>INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</p> <p>EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p><b>NOTES:</b>      TOP OF BORING ELEVATIONS OBTAINED FROM PROJECT TIN FILE (R5749) IS TIN TIN, DATED MAY 12, 2016.      FIAD - FILLED IMMEDIATELY AFTER DRILLING      UCP - UNDIVIDED COASTAL PLAIN</p>																																																																																																																																											
<p><b>COLOR</b></p> <p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p><b>BENCH MARK:</b> N/A</p> <p>ELEVATION: N/A FEET</p>																																																																																																																																											

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5749	3	146
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
53086.1.FD1	HSIP-0074 (169)	P.E.	
53086.2.1	HSIP-0074 (169)	RW / UTIL	
53086.3.1	HSIP-0074 (169)	CONST.	

STATE OF NORTH CAROLINA  
DIVISION OF HIGHWAYS

# COLUMBUS COUNTY


LOCATION: US 7476 AT SR 1001 (HALLSBORO ROAD)  
CONVERT AT GRADE INTERSECTION TO INTERCHANGE

TYPE OF WORK: GRADING, DRAINAGE, PAVING, STRUCTURE,  
AND SIGNING


25% PRELIMINARY PLANS



See Sheet 1-A For Index of Sheets  
See Sheet 1-B For Conventional Symbols




TIP PROJECT: R-5749



THIS PROJECT IS NOT WITHIN ANY MUNICIPAL BOUNDARIES.  
THIS IS A CONTROLLED ACCESS PROJECT WITH ACCESS  
BEING LIMITED TO THE INTERCHANGE AT US 7476 AND SR 1001  
(HALLSBORO ROAD).  
CLEARING ON THIS PROJECT SHALL BE PERFORMED  
TO THE LIMITS ESTABLISHED BY METHOD III.

**INCOMPLETE PLANS**  
DO NOT USE FOR R/W ACQUISITION  
DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED



**DESIGN DATA**

ADT 2018 =	12,900
ADT 2038 =	18,700
DHV =	55 %
D =	8 %
T =	16 % *
V =	75 MPH
* TTST =	3 DUAL = 13
FUNC CLASS =	INTERSTATE
STATEWIDE TIER	

**PROJECT LENGTH**

LENGTH ROADWAY TIP PROJECT R-5749	=	1.212	MILES
LENGTH STRUCTURE TIP PROJECT R-5749	=	0.000	MILES
TOTAL LENGTH TIP PROJECT R-5749	=	1.212	MILES

Prepared in the Office of:  
**CDM Smith**  
CDM Smith Inc.  
5400 Glenwood Avenue  
Suite 400  
Raleigh, NC 27612-3228  
NC CDA No. F-0412

FOR THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
2012 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:  
MARCH 2017

LETTING DATE:  
FEBRUARY 2018

DAVID J. CLODGO, P.E.  
PROJECT ENGINEER

CURTIS J. TILLMAN, P.E.  
PROJECT DESIGN ENGINEER


SEAN MATUSZEWSKI  
NCDOT CONTACT

**HYDRAULICS ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.

**ROADWAY DESIGN ENGINEER**

SIGNATURE: \_\_\_\_\_ P.E.



21-SEP-2016 16:11 W:\share\GEO\TECHNICAL\Projects\2015\548.024A R-5749 Roadway\5749\_GEO\_RDWY\CADD\_GEO\TECH\PlanPr of NR5749\_GEO\_inv3.dgn bajohnson AT KAZ06660



November 4, 2016  
File No. 20151548.025A

STATE PROJECT: 53086.1.FD1 (R-5749)  
FEDERAL PROJECT: HSIP-0074(169)  
COUNTY: Columbus  
DESCRIPTION: US 74/76 at SR 1001 (Hallsboro Road), Convert at Grade Intersection to Interchange

**SUBJECT: GEOTECHNICAL REPORT - INVENTORY**

**PROJECT DESCRIPTION**

This project consists of the reconstruction of the interchange of US 74/76 (-L-) and Hallsboro Road (-Y-). Also proposed is the construction of at grade ramps (-YRPA-, -YRPB-, -YRPC-, and -YRPD-) and a temporary detour of Hallsboro Road (-DET-). Embankments up to 27 feet are expected.

The geotechnical investigation was conducted between June and October of 2016. Standard Penetration Test borings were advanced with a CME 45 with automatic hammer. Hand auger borings were also completed. Representative soil samples were collected for visual classification in the field and selected samples were submitted for laboratory analysis by Kleinfelder Southeast, Inc.

The following alignments, totaling 3.72 miles, were investigated. Subsurface profiles and cross sections of these alignments are included in this report.

<u>LINE</u>	<u>STATIONS</u>
-L-	20+00 to 83+14
-YRPA-	5+00 to 25+62
-YRPB-	5+00 to 24+48
-YRPC-	5+00 to 27+12
-YRPD-	5+00 to 25+36
-Y-	17+55 to 42+00
-DET-	8+90 to 34+07

**AREAS OF SPECIAL GEOTECHNICAL INTEREST**

1) Moderately to Highly Plastic Clays: Moderate to Highly plastic clays (PI > 15) were encountered on the project at the following locations:

<u>LINE</u>	<u>STATIONS</u>	<u>OFFSETS</u>
-L-	20+00 to 83+00	LT to RT
-YRPA-	11+00 to 25+00	LT to RT
-YRPB-	11+00 to 25+00	LT to RT
-YRPC-	11+00 to 25+00	LT to RT
-YRPD-	11+00 to 25+00	LT to RT
-Y-	17+55 to 42+00	LT to RT
-DET-	14+00 to 30+00	LT to RT

A discussion of these moderate to highly plastic clay soils is located below in the section titled "Soil Properties".

2) Groundwater: The following areas exhibit a high water table, seasonal high groundwater or the potential for groundwater related construction problems:

<u>LINE</u>	<u>STATIONS</u>
-L-	20+00 to 83+14
-YRPA-	5+00 to 25+62
-YRPB-	5+00 to 24+48
-YRPC-	5+00 to 27+12
-YRPD-	5+00 to 25+36
-Y-	17+55 to 42+00
-DET-	8+90 to 34+07

**PHYSIOGRAPHY AND GEOLOGY**

The project is located in the Coastal Plain Physiographic Province. The project corridor is comprised primarily of residential and undeveloped properties. The general topography along the project is generally flat to gently sloping.

Geologically, the soils in the project area generally consist of undivided coastal plain soils underlain by the Waccamaw and Pee Dee Formations.

**SOIL PROPERTIES**

Soils encountered during this investigation are separated into four categories based on origin. They consist of roadway embankment, undivided coastal plain, and coastal plain soils belonging to the Waccamaw and Pee Dee Formations.

Roadway Embankment soils are present along the existing roadways on the project. These soils consist of moist to wet, loose to dense, non-plastic to slightly plastic, fine sands, silty, fine to coarse sands (A-3, A-2-4) and moist to wet, soft to stiff, slightly to highly plastic, clays, silty clays, fine sandy, silty clays, and silty, fine sandy clays (A-6, A-7-5, A-7-6).

Soils identified as undivided coastal plain consist of moist to wet, soft to very stiff, slightly plastic to highly plastic clays, silty clays, fine sandy, silty clays, and silty, fine sandy clays, fine sandy silts (A-6, A-7-5, A-7-6, A-4), moist to wet, loose to very dense, clayey, fine to coarse sands, silty, fine to coarse sands, fine sands (A-3, A-2-4, A-2-6), and limestone.


Soils identified as Coastal Plain - Waccamaw Formation consist of moist, soft, highly plastic clays, and silty clays, (A-7-5).

Soils identified as Coastal Plain - Peedee Formation consist of moist to wet, soft to very stiff, slightly to moderately plastic, fine sandy clays (A-6), non-plastic, loose to very dense, dark gray, clayey, fine to coarse sand (A-2-6).

**GROUNDWATER**

Groundwater was encountered at elevations ranging from 47.8 to 64.5 feet MSL along the proposed roadways of the project.

Prepared by,



Thomas R. Wells, PE  
Senior Professional



Xavier C. Barrett, PE  
Principal Professional

TRW/XCB:cas









5/14/09

PROJECT REFERENCE NO. <b>R-5749</b>	SHEET NO. <b>6</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	



NAD 83/NSRS 2007



MATCH LINE -L- POT STA. 62+00.00 SEE SHEET 5

MATCH LINE -L- POT STA. 76+00.00 SEE SHEET 7

-YRPA-	
Pis Sta 9+65.61	PI Sta 14+44.61
Os = 4° 20' 09.2"	Δ = 30° 33' 48.6" (RT)
Ls = 224.00'	D = 3° 52' 16.8"
LT = 149.38'	L = 789.48'
ST = 74.71'	T = 404.38'
	R = 1,480.00'
	SE = 0.08
	RO = 224.00'
	DS = 65 MPH

-YRPD-	
Pis Sta 6+49.35	PI Sta 11+90.60
Os = 3° 00' 05.3"	Δ = 24° 37' 21.1" (LT)
Ls = 224.00'	D = 2° 40' 47.6"
LT = 149.35'	L = 918.79'
ST = 74.69'	T = 466.60'
	R = 2,138.00'
	SE = 0.08
	RO = 224.00'
	DS = 65 MPH

10 (-YRPD-)




CULVERT #1  
20' BARRELS

	NORTH	EAST	ELEV.
CUL1	212352.04	2122915.73	44.91
CUL2	212351.98	2122921.20	44.89
CUL3	212352.00	2122922.09	44.85
CUL4	212351.80	2122928.11	44.90
CE1	212351.72	2122915.77	49.91
HW1	212351.03	2122928.77	51.44
CUL5	212167.30	2123048.58	44.68
CUL6	212167.41	2123054.49	44.72
CUL7	212167.41	2123054.49	44.72
CUL8	212167.07	2123060.34	44.66
CE2	212167.77	2123048.54	49.70
HW2	212168.97	2123061.31	51.33

19-SEP-2016 15:29 20151548.dwg 19-SEP-2016 15:29 20151548.dwg 19-SEP-2016 15:29 20151548.dwg  
 20151548.dwg 19-SEP-2016 15:29 20151548.dwg 19-SEP-2016 15:29 20151548.dwg



19-SEP-2016 15:29 20151548.dwg 19-SEP-2016 15:29 20151548.dwg 19-SEP-2016 15:29 20151548.dwg 19-SEP-2016 15:29 20151548.dwg



PROJECT REFERENCE NO. <b>R-5749</b>	SHEET NO. <b>8</b>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>INCOMPLETE PLANS</b> DO NOT USE FOR R/W ACQUISITION	
<b>DOCUMENT NOT CONSIDERED FINAL</b> UNLESS ALL SIGNATURES COMPLETED	



**COASTAL PLAIN**  
NAD 83/NSRS 2007

WAGNER & SONS WOOD CORPORATION  
DB 72 PG 27  
PB 72 PG 69



**END CONSTRUCTION**  
-Y- POT STA. 42+00.00

45 (-Y-)



5/28/99  
 19-SEP-2016 15:23  
 M:\shore\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\Roadway\5749\_GEO\_RDWY\CADD\_GEO\RDWY\5749\_GEO.pfl\_sht.dgn  
 24/26/2016



5/28/99  
 19-SEP-2016 15:23  
 M:\shore\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\RDY\RDY\CADD\_GEO\RDY\R5749\_GED.pfl\_sht.dgn  
 2426560





5/28/99





**THIS SPACE INTENTIONALLY BLANK**

19-SEP-2016 15:23  
 M:\shore\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\RDWY\GEO.pfl\_sht.dgn  
 4826560

5/28/99  
 19-SEP-2016 15:30  
 M:\shere\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\RDWY\Plan\Prof\R5749\_GEO.pfl\_sht.dgn  
 4826560





5/28/99  
 19-SEP-2016 15:30  
 M:\shere\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\RDWY\Plan\Prof\R5749\_GEO.pfl\_sht.dgn  
 24/26/2016







5/28/99  
 28-OCT-2016 08:55  
 W:\shore\GEO\TECHNICAL\Projects\Active Projects\20151548\024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\RDWY\R5749\_GEO.pfl\_sht.dgn  
 28-02-2016 11:48:26 AM





5/28/99  
 19-SEP-2016 15:30  
 M:\shore\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\RDWY\Plan\Prof\R5749\_GEO.pfl\_sht.dgn




5/28/99


21-SEP-2016 11:41 W:\shore\_GEO\TECHNICAL\Projects\Active Projects\20151548\024A R-5749 Roadway\CAD\CADD\_GED\RDWY\R5749\_GED.pfl\_sht.dgn









8/23/99




19-SEP-2016 15:30  
 W:\shere\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI.L.dgn  
 ka226660



I:\SEP-2016\15130  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\15148.024A R-5749 Roadway\15148.024A\_GEO\RDWY\CADD\GEO\TECH\15148.024A\_GEO\15148.024A\_GEO.dgn  
 ka226660  
 ba johnson




8/23/99



19-SEP-2016 15:30  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\GEO\GEO\GEO\RS749\_GEO\_xsi.L.dgn  
ba.johnson




8/23/99




19-SEP-2016 15:30  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSL.dgn  
 ka.johnson

8/23/99  
19-SEP-2016 15:30  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A R-5749 Roadway\1548.024A R-5749 GEO\RDWY\CADD\_GEO\TECH\1548.024A R-5749 GEO\1548.024A R-5749 GEO.dgn  
ba.johnson




8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




19-SEP-2016 15:30  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
 ka206660

8/23/99



19-SEP-2016 15:30  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSL.dgn  
 ka226660


8/23/99




19-SEP-2016 15:30  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI.L.dgn  
 ka206660

8/23/99


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



19-SEP-2016 15:30  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
 ba johnson AT




8/23/99



19-SEP-2016 15:33  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.0244 R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO\_XSI.L.dgn  
 ba johnson




8/23/99




19-SEP-2016 15:53  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.0244 R-5749 Roadway\1548.0244\_R-5749\_Roadway\1548.0244\_GEO\RDWY\CADD\_GEO\TECH\1548.0244\_GEO\_1548.0244.dgn  
 ka226660  
 Johnson

-L-







19-SEP-2016 15:53:31  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\48,024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO\_XSI.L.dgn  
 ka226660



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150









8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



I:\SEP-2016\JES31  
 M:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
 ka206660


8/23/99




19-SEP-2016 15:53  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A\_GEO\_RDWY\CADD\_GEO\TECH\1548.024A\_GEO\_xsi.L.dgn  
 ka206660

-L-






I:\SEP-2016\151548.0244 R-5749 Roadway\Projects\Active Projects\2015\151548.0244 R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI.L.dgn  
 W:\sherev\GEO\TECH\XSEC\KAT\206660





8/23/99




I:\SEP-2016\1515148\0244 R-5749 Roadway\Roadway\RDWY\CADD\GEO\TECH\XSEC\RS5749\_GEO.XSL.dgn  
 W:\sherev\GEO\TECH\XSEC\RS5749\_GEO.XSL.dgn  
 K:\johnson






8/23/99  
19-SEP-2016 15:32  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
ba.johnson




8/23/99




19-SEP-2016 15:32  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
ba johnson AT

-L-












8/23/99  
19-SEP-2016 15:32  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\GEO\GEO\RS749\_GEO\_xsi.L.dgn  
ba.johnson





8/23/99




19-SEP-2016 15:32  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
ba johnson AT

— L —


8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




— L —



19-SEP-2016 15:32  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
 ka206660





21-SEP-2016 16:51  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSL.L.dgn  
 ka johnson













19-SEP-2016 15:33  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSL.dgn  
 ka226660




8/23/99




19-SEP-2016 15:33  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI.L.dgn  
ba.johnson AT




19-SEP-2016 15:33  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
 ka.johnson






19-SEP-2016 15:33  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.L.dgn  
 ba johnson AT K4206660


8/23/99  
19-SEP-2016 15:33  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\_GEO\GEO\RDWY\5749\_GEO\_xsi.L.dgn  
K42266660






8/23/99  
19-SEP-2016 15:33  
W:\shere\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO\_XSI.L.dgn  
ba.johnson





-YRPA-


8/23/99



-YRPA-

I:\SEP-2016\151337  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\201515148.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSL\YRPA.dgn  
K Johnson

8/23/99  
19-SEP-2016 15:33  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPA.dgn  
K226660  
A1 Johnson



**ROADWAY EMBANKMENT:**  
MOIST, NON PLASTIC, LOOSE,  
BROWN FINE SAND

**UCP:** MOIST, MODERATELY PLASTIC, SOFT TO STIFF, BROWN-GRAY-ORANGE, FINE SANDY, SILTY CLAY AND SILTY, FINE SANDY CLAY

12 + 50.00


**ROADWAY EMBANKMENT:**  
MOIST, NON PLASTIC, LOOSE,  
BROWN FINE SAND

**UCP:** MOIST, MODERATELY TO HIGHLY PLASTIC, SOFT TO STIFF, BROWN-GRAY-ORANGE, SILTY, FINE SANDY CLAY AND CLAY

12 + 00.00


-YRPA-

8/23/99



19-SEP-2016 15:33  
M:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A R-5749\Roadway\1548.024A R-5749\GEO\RDWY\CADD\GEO\TECH\XSEC\1548.024A R-5749\GEO.XSL.YRPA.dgn  
ba.johnson


-YRPA-



19-SEP-2016 15:33  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPA.dgn  
 ba johnson AT

14+00.00  
-YRPA-

8/23/99



06/16  
 UCP:  
 MOIST, MODERATELY PLASTIC, SOFT TO  
 B.T. STIFF, BROWN-GRAY-ORANGE, SILTY, FINE  
 SANDY CLAY AND FINE SANDY, SILTY CLAY

17 + 00.00


06/16  
 UCP:  
 MOIST, MODERATELY PLASTIC, SOFT TO  
 STIFF, BROWN-GRAY-ORANGE, SILTY, FINE  
 SANDY CLAY AND FINE SANDY, SILTY CLAY

16 + 50.00

-YRPA-


19-SEP-2016 15:33  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPA.dgn  
 ka206660

8/23/99  
19-SEP-2016 15:33  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSL\_YRPA.dgn  
KJohnson  
AT






8/23/99



19-SEP-2016 15:33  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPA.dgn  
K Johnson

-YRPA-

8/23/99




I:\SEP-2016\15133\W\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\15148.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSL\_YRPA.dgn

UCP:  
MOIST, MODERATELY PLASTIC, SOFT TO  
STIFF, BROWN-GRAY-ORANGE, FINE SANDY  
CLAY  
20 + 50.00

UCP:  
MOIST, MODERATELY PLASTIC, SOFT,  
BROWN-GRAY, SILTY, FINE SANDY CLAY  
20 + 00.00  
-YRPA-

8/23/99




-YRPA-

19-SEP-2016 15:33  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\Roadway\1548.024A\GEO\RDWY\CADD\GEO\TECH\1548.024A\1548.024A.dgn  
 ka206660

8/23/99


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



I:\SEP-2016\15337  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.0244 R-5749 Roadway\15749\_GEO\_RDWY\CADD\_GEO\TECH\15749\_GEO\_15749.dgn  
 ba johnson  
 AT 14206660




8/23/99



19-SEP-2016 15:33  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A\GEO\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPA.dgn  
ba johnson

-YRPA-


8/23/99



19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI\_YRPB.dgn  
 ka206660

-YRPB-


8/23/99



19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI\_YRPB.dgn  
 ka206660




8/23/99



-YRPB-

19-SEP-2016 15:34  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GED.XSI\_YRPB.dgn  
K226660




-YRPB-

19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPB.dgn  
 ka206660


8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



I:\SEP-2016\1534  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A\GEO\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI.YRPB.dgn  
 ka206660  
 At Johnson


8/23/99



19-SEP-2016 15:34  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI\_YRPB.dgn  
KJohnson  
AT

-YRPB-






19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\195749\_GEO\_RDWY\CADD\_GEO\TECH\195749\_GEO\_xsl\_YRPB.dgn  
 ka Johnson AT K426660

-YRPB-



8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




I:\SEP-2016\1534  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPB.dgn  
 KAJ206660  
 AT

-YRPB-




8/23/99



-YRPB-

19-SEP-2016 15:34  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI\_YRPB.dgn  
KAT206660


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




UCP: 61.72  
 MOIST TO WET, HIGHLY PLASTIC, SOFT TO STIFF, BROWN-GRAY-ORANGE, SILTY, FINE SANDY CLAY  
 24 + 50.00

UCP: 61.72  
 MOIST TO WET, HIGHLY PLASTIC, SOFT TO STIFF, BROWN-GRAY-ORANGE, SILTY, FINE SANDY CLAY  
 24 + 00.00


-YRPB-






-YRPC-


8/23/99



19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A\GEO\RDWY\CADD\GEO\TECH\1548.024A\1548.024A.dgn  
 ka206660


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150





-YRPC-


8/23/99



19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\185749\_GEO\_RDWY\CADD\_GEO\TECH\185749\_GEO\_xsl\_YRPC.dgn  
 ka johnson




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\195749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\195749\_GEO.XSI\_YRPC.dgn  
 ba johnson AT


8/23/99



19-SEP-2016 15:34  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPC.dgn  
KJohnson

-YRPC-


8/23/99



19-SEP-2016 15:34  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPC.dgn  
KJohnson

8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




-YRPC-

I:\SEP-2016\15134  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\15148\0244 R-5749 Roadway\RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPC.dgn  
 ka206660  
 ba johnson

8/23/99


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




I:\SEP-2016\1534  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPC.dgn  
 KAJ206660  
 At Johnson


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

I:\Projects\2015\1548\024A R-5749 Roadway\RDWY\CADD\GEO\GEO\TECH\XSEC\R5749\_GEO.XSI.YRPC.dgn  
 19-SEP-2016 15:34  
 W:\sherev\GEO\TECH\XSEC\AT\_KA206660



8/23/99  
02-NOV-2016 13:54  
M:\shoran\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPD.dgn  
K.A. Johnson







I:\SEP-2016\15134  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\15148.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPD.dgn  
 ba johnson  
 AT K420660

-YRPD-






8/23/99



-YRPD-

19-SEP-2016 15:34  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\175749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\175749\_GEO.XSL.YRPD.dgn  
KJohnson

8/23/99



19-SEP-2016 15:34  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\195749\_GEO\_RDWY\CADD\_GEO\TECH\195749\_GEO\_xsl\_YRPD.dgn  
ba.johnson AT K4226660

19 + 50.00

S-21

19 + 00.00

18 + 50.00


-YRPD-

UCP:  
MOIST TO WET, MODERATELY PLASTIC, SOFT  
TO STIFF, BROWN-GRAY-ORANGE, SILTY,  
FINE SANDY CLAY

B.T.  
MOIST TO WET, MODERATELY PLASTIC, SOFT  
TO STIFF, BROWN-GRAY-ORANGE, SILTY,  
FINE SANDY CLAY

UCP:  
MOIST TO WET, MODERATELY PLASTIC, SOFT  
TO STIFF, BROWN-GRAY-ORANGE, SILTY,  
FINE SANDY CLAY

8/23/99



21 + 00.00

**UCP:**  
 MOIST TO WET, MODERATELY PLASTIC, SOFT  
 TO STIFF, BROWN-GRAY-ORANGE, SILTY,  
 FINE SANDY CLAY AND FINE SANDY, SILTY  
 CLAY

20 + 50.00

**UCP:**  
 MOIST TO WET, MODERATELY PLASTIC, SOFT  
 TO STIFF, BROWN-GRAY-ORANGE, SILTY,  
 FINE SANDY CLAY

20 + 00.00


**UCP:**  
 MOIST TO WET, MODERATELY PLASTIC, SOFT  
 TO STIFF, BROWN-GRAY-ORANGE, SILTY,  
 FINE SANDY CLAY

-YRPD-

19-SEP-2016 15:34  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.0244 R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPD.dgn  
 ka206660  
 Johnson



8/23/99



**UCP:**  
 MOIST TO WET, HIGHLY PLASTIC, SOFT TO STIFF, BROWN-GRAY-ORANGE, FINE SANDY, SILTY CLAY TO CLAY.  
**24 + 00.00**

**UCP:**  
 MOIST TO WET, HIGHLY PLASTIC, SOFT TO STIFF, BROWN-GRAY-ORANGE, FINE SANDY, SILTY CLAY TO CLAY.  
**23 + 50.00**


**S-22**  
 06/16  
 B.T.  
 60.35  
**UCP:**  
 MOIST TO WET, HIGHLY PLASTIC, SOFT TO STIFF, BROWN-GRAY-ORANGE, FINE SANDY, SILTY CLAY TO CLAY.  
**23 + 00.00**

-YRPD-

19-SEP-2016 15:35  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_YRPD.dgn  
 ka johnson



8/23/99  
19-SEP-2016 15:35  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI.X.DGN  
K2266660











8/23/99



19-SEP-2016 15:35  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.Y.dgn  
 ka206660

8/23/99  
19-SEP-2016 15:35  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\GEO\RS749\_GEO\_xsl.y.dgn  
ba.johnson



Ⓐ ROADWAY EMBANKMENT:  
MOIST, NON PLASTIC, LOOSE, BROWN,  
SILTY, FINE SAND WITH ROOTLETS

4:1

4:1

Ⓐ

UCP:  
MOIST, HIGHLY PLASTIC, SOFT TO STIFF,  
GRAY-ORANGE-RED, SILTY, FINE SANDY CLAY

23 + 00.00

Ⓐ ROADWAY EMBANKMENT:  
MOIST, NON PLASTIC, LOOSE, BROWN,  
SILTY, FINE SAND WITH ROOTLETS

4:1

4:1

Ⓐ

UCP:  
MOIST, HIGHLY PLASTIC, SOFT TO STIFF,  
GRAY-ORANGE-RED, SILTY, FINE SANDY CLAY


22 + 50.00


-DET-  
STA 14+00  
67' RT.

0.5/16


B.T.

-Y-





8/23/99  
19-SEP-2016 15:35  
M:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A R-5749 Roadway\1548.024A R-5749\_GEO\RDWY\CADD\_GEO\TECH\1548.024A R-5749\_GEO\1548.024A R-5749\_GEO.dgn  
ba johnson



**(A) ROADWAY EMBANKMENT:**  
MOIST, NON PLASTIC, LOOSE, BROWN,  
SILTY, FINE SAND WITH ROOTLETS

**(B) UCP:**  
MOIST, NON PLASTIC, LOOSE,  
BROWN, CLAYEY, FINE SAND  
**(C) SLIGHTLY PLASTIC, MEDIUM STIFF,**  
4:1 BROWN-RED, SILTY, FINE SANDY CLAY


**COASTAL PLAIN:** HIGHLY PLASTIC, SOFT, GRAY, SILTY CLAY  
(WACCAMAW FORMATION)

**COASTAL PLAIN SEDIMENTARY ROCK:** SOFT, GRAY, LIMESTONE

26 + 50.00

-Y-


8/23/99



28-OCT-2016 10:49  
 W:\sharv\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO\_XSI.Y.dgn  
 ka206660  
 ba johnson



8/23/99




02-NOV-2016 10:01 AM \\shereva\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.Y.dgn ka206660

29 + 00.00  
-Y-






8/23/99



19-SEP-2016 15:35  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\1548.024A GEO\RDWY\CADD\GEO\TECH\1548\1548.024A GEO\1548.024A GEO.dgn  
ba johnson


8/23/99



02-NOV-2016 10:01 AM W:\shorva\GEO\TECHNICAL\Projects\Active Projects\20151548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.Y.dgn ka206660

-Y-


8/23/99



I:\SEP-2016\1535E  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\R5749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI.Y.dgn  
 ka206660  
 ba.johnson

8/23/99

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




-Y-

19-SEP-2016 15:35  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.X.DGN  
ba.johnson










8/23/99  
19-SEP-2016 15:35  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI.Y.DGN  
ba.johnson




37 + 50.00

37 + 00.00

36 + 50.00


-Y-



I:\SEP-2016\15356  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.0244 R-5749 Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI.Y.dgn  
 ka206660





8/23/99  
19-SEP-2016 15:35  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\GEO\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_DET.dgn  
ba johnson




-DET-





-DET-





UCP:  
 MOIST TO WET, MODERATELY PLASTIC, SOFT,  
 BROWN-GRAY, SILTY, FINE SANDY CLAY

16 + 50.00

UCP:  
 B.T. MOIST TO WET, MODERATELY PLASTIC, SOFT,  
 BROWN-GRAY, SILTY, FINE SANDY CLAY


16 + 00.00

UCP:  
 MOIST TO WET, MODERATELY PLASTIC, SOFT,  
 BROWN-GRAY, SILTY, FINE SANDY CLAY

15 + 50.00

-DET-


8/23/99



-DET-


19-SEP-2016 15:35  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_DET.dgn  
A1 K426660

8/23/99




I:\SEP-2016\15136\W\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\15148\024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\RS749\_GEO.XSI\_DET.dgn

8/23/99



PROJ. REFERENCE NO.  
R-5749

SHEET NO.  
137



ROADWAY EMBANKMENT:  
MOIST, NON PLASTIC, MEDIUM DENSE,  
BROWN, FINE SAND

22 + 00.00

06.7/6  
B.T.

ROADWAY EMBANKMENT:  
MOIST, NON PLASTIC, MEDIUM DENSE,  
BROWN, FINE SAND

21 + 85.49


ROADWAY EMBANKMENT:  
MOIST, NON PLASTIC, MEDIUM DENSE,  
BROWN, FINE SAND

21 + 50.00


-DET-

19-SEP-2016 15:36  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\_GEO\TECH\XSEC\R5749\_GEO.XSI\_DET.dgn  
KJohnson

8/23/99




19-SEP-2016 15:36  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\Roadway\RS749\_GEO\_RDWY\CADD\_GEO\TECH\XSEC\RS749\_GEO.XSI\_DET.dgn  
 ba johnson AT KAZ26660



19-SEP-2016 15:36  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_DET.dgn  
 ka Johnson AT K426660

-DET-





19-SEP-2016 15:36  
 W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_DET.dgn  
 ka206660


-DET-







8/23/99  
19-SEP-2016 15:36  
W:\sherev\GEO\TECHNICAL\Projects\Active Projects\2015\1548.024A R-5749 Roadway\RDWY\CADD\GEO\TECH\XSEC\R5749\_GEO.XSI\_DET.dgn  
ba johnson  
AT K420660



NORTH CAROLINA DEPARTMENT OF TRANSPORTATION  
DIVISION OF HIGHWAYS  
GEOTECHNICAL ENGINEERING UNIT  
SUBSURFACE INVESTIGATION  
APPENDIX A  
LABORATORY RESULTS

REFERENCE: R-5749

PROJECT: 53086

XCB 7/8/16  
INITIALS DATE

**SUMMARY OF LABORATORY TEST DATA**

**PROJECT NO. 53086.1.FD1 (R-5749)**  
**COUNTY: COLUMBUS**  
**US 74/76 AT SR 1001 (HALLSBORO ROAD CONVERT AT GRADE INTERSECTION TO INTERCHANGE)**

Sample No.	Boring Number	Station	Offset	Alignment	Sample Depth (ft.)	Natural Moisture Content (%)	AASHTO Class (Group Index)	N-Value (blows/ ft.)	Atterberg Limits			Gradation Results							
									L.L.	P.L.	P.I.	Pass #10 Sieve	Pass #40 Sieve	Pass #200 Sieve	Retained #270 Sieve	Coarse Sand (%)	Fine Sand (%)	Silt (%)	Clay (%)
S-1	L_2700	27+00	100' LT	-L-	2.0-2.5	17.6	A-6(14)	-	39	10	29	100	92	61	45	13.4	31.6	20.6	34.4
S-2	L_3500	35+00	100' LT	-L-	1.0-1.5	15.8	A-6(13)	-	36	12	24	100	95	65	41	10.9	29.6	25.3	34.2
S-3	L_4300	43+00	30' LT	-L-	3.0-3.5	16.7	A-6(10)	-	32	12	20	100	99	65	43	4.2	38.8	23.3	33.7
S-4	L_5700	57+00	CL	-L-	3.5-4.0	25.8	A-7-6(24)	-	49	15	34	100	98	74	34	5	28.6	24.0	42.4
S-5	L_6700	67+00	110' LT	-L-	1.5-2.0	17.1	A-6(6)	-	26	11	15	100	94	60	46	11.2	34.9	26.7	27.2
S-6	L_7500	75+00	90' RT	-L-	1.0-1.5	15.2	A-6(7)	-	27	12	15	100	96	68	40	8.7	31.5	29.6	30.2
S-7	YRPA_1100	11+00	CL	-YRPA-	3.5-4.0	18.0	A-6(6)	-	28	10	18	100	93	57	50	12.5	37	21	29.5
S-8	YRPA_1500	15+00	CL	-YRPA-	4.0-4.5	26.0	A-6(12)	-	37	13	24	100	97	64	45	5.9	38.7	26.1	29.3
S-9	YRPA_1900	19+00	CL	-YRPA-	1.5-2.0	18.5	A-6(11)	-	32	13	19	100	98	73	37	4.1	32.5	34.3	29.1
S-10	YRPA_2300	23+00	CL	-YRPA-	4.0-4.5	29.0	A-7-6(24)	-	49	14	35	100	99	74	37	3.5	33.6	21.7	41.2
S-11	YRPB_1100	11+00	CL	-YRPB-	1.0-1.5	25.1	A-7-6(22)	-	46	12	34	100	99	73	36	4.1	31.5	20.4	44.0
S-12	YRPB_1500	15+00	CL	-YRPB-	3.0-3.5	20.6	A-6(7)	-	30	12	18	100	98	60	49	5.4	43.6	22.8	28.2
S-13	YRPB_1900	19+00	CL	-YRPB-	3.5-4.0	26.4	A-6(9)	-	32	13	19	100	98	63	48	5.4	42.1	19.5	33.0
S-14	YRPB_2300	23+00	CL	-YRPB-	5.0-5.5	21.0	A-6(16)	-	40	11	29	100	99	67	42	4.6	37.1	19.7	38.6
S-15	YRPC_1300	13+00	CL	-YRPC-	3.0-3.5	20.2	A-7-6(15)	-	42	14	28	100	98	65	44	5.0	38.6	17.6	38.8
S-16	YRPC_1300	13+00	CL	-YRPC-	5.0-5.5	27.8	A-7-6(46)	-	68	10	58	100	98	79	27	3.2	23.8	22.2	50.8
S-17	YRPC_2300	23+00	CL	-YRPC-	4.0-4.5	29.5	A-7-6(13)	-	42	17	25	100	97	62	45	6.7	37.8	17.4	38.1
S-18	YRPC_2500	25+00	CL	-YRPC-	4.0-4.5	23.9	A-6(5)	-	26	13	13	100	98	61	48	5.1	43.0	24.9	27.0
S-19	YRPD_1100	11+00	CL	-YRPD-	1.0-1.5	17.4	A-6(5)	-	27	12	15	100	93	55	51	12.0	39.0	21.7	27.3
S-20	YRPD_1500	15+00	CL	-YRPD-	1.5-2.0	17.7	A-4(0)	-	15	NP	NP	100	95	48	60	9.1	51.0	26.3	13.6
S-21	YRPD_1900	19+00	CL	-YRPD-	3.5-4.0	22.8	A-6(11)	-	39	14	25	100	96	58	49	6.7	42.6	17.9	32.8
S-22	YRPD_2300	23+00	CL	-YRPD-	1.5-2.0	23.8	A-7-6(21)	-	45	14	31	100	97	73	34	4.7	29.7	27.7	37.9
S-23	Y_1800	18+00	20' LT	-Y-	1.0-1.5	20.7	A-6(12)	-	34	13	21	100	99	71	40	3.4	36.3	29.1	31.2
S-24	Y_2200	22+00	20' RT	-Y-	0.5-1.0	17.0	A-6(3)	-	23	13	10	100	98	65	46	4.4	41.7	32.2	21.7
S-25	Y_3900	39+00	30' LT	-Y-	0.5-1.0	24.0	A-6(12)	-	36	13	23	100	97	67	41	5.7	35.4	26.0	32.9
S-26	DET_1800	18+00	CL	-DET-	4.0-4.5	18.3	A-6(9)	-	29	12	17	100	99	72	36	4.2	32.0	29.1	34.7
S-27	DET_2000	20+00	CL	-DET-	3.0-3.5	19.2	A-6(14)	-	34	12	22	100	98	75	32	3.6	28.8	29.3	38.3
S-28	DET_2400	24+00	CL	-DET-	0.5-1.0	23.6	A-6(9)	-	32	13	19	100	99	64	45	3.7	41.2	23.5	31.6
S-29	DET_2800	28+00	CL	-DET-	0.5-1.0	22.3	A-4(1)	-	21	14	7	100	96	56	54	6.8	46.8	27.9	18.5
ST-1	EB1-A	28+46	24' LT	-Y-	5.0-7.0	-	A-7-6 (45)	-	64	13	51	98	98	85	32	0.6	31.5	33.4	34.5
ST-2	EB1-A	28+46	24' LT	-Y-	30.0-32.0	-	A-6 (3)	-	33	12	21	97	93	39	38	19.9	41.5	16.5	22.2
ST-3	EB1-A	28+46	24' LT	-Y-	45.0-47.0	-	A-6 (4)	-	35	16	19	100	97	43	34	17.7	48.1	14.0	20.2
ST-4	Y_2892	28+92	38' LT	-Y-	8.0-10.0	-	A-7-6 (15)	3	47	19	28	100	98	63	45	5.0	40.0	19.9	35.1
ST-5	Y_2892	28+92	38' LT	-Y-	10.0-12.0	-	A-7-6 (28)	2	59	16	43	100	98	69	40	5.1	35.0	36.8	23.7
ST-6	Y_2904	29+04	73' RT	-Y-	10.0-12.0	-	A-2-6 (0)	1	32	20	12	98	77	27	73	38.4	34.9	4.6	22.0
ST-7	Y_3117	31+17	44' RT	-Y-	10.0-12.0	-	A-7-6 (58)	3	74	18	56	100	100	94	20	0.2	19.4	27.5	53.0
ST-8	Y_3117	31+17	46' LT	-Y-	9.0-11.0	-	A-7-6 (28)	3	50	18	32	100	99	86	35	0.9	33.7	28.8	36.6
ST-9	Y_3117	31+17	46' LT	-Y-	11.0-13.0	-	A-2-6 (0)	1	29	17	12	97	75	30	71	34.8	35.7	9.6	20.0

SS = Split-Barrel Sample (ASTM-D-1586) ST = Shelby Tube (Undisturbed) Sample S = Grab Sample NP -- Non Plastic NA-- Non Applicable