



| PAVEMENT SCHEDULE |  |
|-------------------|--|
| C                 | PROP. APPROX. 1½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, TO BE APPLIED AT AN AVERAGE RATE OF 165 LBS PER SQ. YD.   |
| C1                | PROP. APPROX. 2" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, TO BE APPLIED AT AN AVERAGE RATE OF 224 LBS PER SQ. YD.  |
| C2                | PROP. APPROX. 1½" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, TO BE APPLIED AT AN AVERAGE RATE OF 168 LBS PER SQ. YD.   |
| C3                | PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH. TO BE PLACED IN LAYERS NOT TO EXCEED 2" IN DEPTH. |
| M1                | MILL ASPHALT PAVEMENT, 1½" DEPTH   |
| M2                | MILL ASPHALT PAVEMENT, 0" TO 1½"   |
| S                 | SHOULDER RECONSTRUCTION (SEE DETAIL)   |
| U                 | EXISTING PAVEMENT  |