


**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**



PLAN

NOTES:

FOR BERM WIDTHS, ELEVATIONS AND HORIZONTAL DIMENSIONS, SEE GENERAL DRAWING.
FOR SECTIONS A-A, B-B, C-C, & D-D SEE SHEET 2 OF 2.


* THE PROPOSED LIMITS OF SLOPE PROTECTION ADJACENT TO THE EXISTING SLOPE PROTECTION ARE BASED ON AN APPROXIMATE LOCATION OF THE CURRENT EDGE OF THE EXISTING SLOPE PROTECTION. THE CONTRACTOR SHALL ADJUST THE PROPOSED SLOPE PROTECTION LIMITS BASED ON THE ACTUAL LOCATION OF THE EXISTING SLOPE PROTECTION. IF THE EXISTING SLOPE PROTECTION IS DAMAGED OR PARTIALLY REMOVED DURING THE ABUTMENT OR PIER CONSTRUCTION OPERATIONS FOR THE PROPOSED BRIDGE, THAT EXISTING SLOPE PROTECTION SHALL BE REMOVED BACK TO THE NEAREST VERTICAL CONSTRUCTION JOINT FROM THE TOP OF THE EXISTING BERM TO THE TOE OF THE EXISTING SLOPE. THE LIMITS OF THE PROPOSED SLOPE PROTECTION WILL THEN BE EXTENDED TO MATCH AGAINST THE ADJUSTED EDGE OF EXISTING SLOPE PROTECTION.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 23+62.98 -S2-

SHEET 1 OF 2

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SLOPE PROTECTION
DETAILS




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609


DRAWN BY B. VAUGHN DATE 10/17
CHECKED BY R. RAPP DATE 10/17 DWG. NO. 55

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S5-55
1			3			TOTAL SHEETS
2			4			56




PLAN WHERE CONCRETE SLOPE PROTECTION MUST BE PLACED AROUND A PIER COLUMN


(BENCH WALL NOT SHOWN FOR CLARITY)



SECTION A-A



POURING DETAIL



OPTIONAL POURING DETAIL

GENERAL NOTES:


SLOPE PROTECTION SHALL BE PLACED UNDER THE ENDS OF THE BRIDGE AS SHOWN IN THE DETAILS. MEASUREMENT AND PAYMENT SHALL BE AS PRESCRIBED IN SECTION 462 OF THE STANDARD SPECIFICATIONS. FOR BERM WIDTH, SEE GENERAL DRAWING.

SLOPE PROTECTION SHALL CONSIST OF 4" POURED-IN-PLACE CONCRETE PAVING AS SHOWN IN THE DETAILS ON THIS SHEET. CONCRETE SHALL BE CLASS "B". THE CONCRETE SURFACE SHALL BE FLOATED WITH A WOODEN FLOAT AND FINISHED. WELDED WIRE FABRIC REINFORCING SHALL BE 6 X 6 - W1.4 X W1.4, 60" WIDE. SLOPE PROTECTION SHALL BE POURED IN 5' STRIPS AS SHOWN IN THE "POURING DETAIL" WITH 2'-0" LONG #4 BARS PLACED ALONG THE SLOPE BETWEEN STRIPS AT 1'-6" MAXIMUM SPACING. SLOPE PROTECTION MAY BE POURED IN ALTERNATE 4' AND 5' STRIPS AS SHOWN IN THE "OPTIONAL POURING DETAIL" WITH ADJACENT RUNS OF WELDED WIRE FABRIC LAPPING AT LEAST 6". THE COST OF THE WELDED WIRE FABRIC AND #4 BARS, IF USED, SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE BID PER SQUARE YARD FOR SLOPE PROTECTION.


ADDITIONAL SLOPE PROTECTION REQUIRED TO PROPERLY MATCH UP TO EXISTING SLOPE PROTECTION, AS DESCRIBED ON SHEET 1 OF 2, SHALL BE INCIDENTAL TO THE CONTRACT BID PRICE FOR THE PROVIDED QUANTITY.

BRIDGE @ STA. 23+62.98 -S2-	4 INCH SLOPE PROTECTION	* WELDED WIRE FABRIC 60 INCHES WIDE
	SQUARE YARDS	APPROX. L.F.
ABUTMENT 1	282	508
ABUTMENT 2	315	567


* QUANTITY SHOWN IS BASED ON 5'-0" POURS PER THE "POURING DETAIL".



SECTION B-B



SECTION D-D



SECTION C-C


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 23+62.98 -S2-

SHEET 2 OF 2

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SLOPE PROTECTION

DETAILS




DocuSigned by:
 SEAL 44886
 50683197C228434...
 2/21/2018

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609 DRAWN BY <u>B. VAUGHN</u> DATE <u>10/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>10/17</u> DWG. NO. 56	REVISIONS						SHEET NO.
	NO.	BY	DATE	NO.	BY	DATE	S5-56
	1			3			TOTAL SHEETS
			4			56	

0012DEL_P28



NOTE:
 SEE "GENERAL DRAWING: GENERAL NOTES (SHEET 3 OF 3)" FOR GENERAL NOTES.

FOR SUBSTRUCTURE SHEETS, REFER TO "BRIDGE ON STATION TRACK 2 OVER W 4TH STREET" PLANS.

MVC = MINIMUM VERTICAL CLEARANCE
 MHC = MINIMUM HORIZONTAL CLEARANCE

← STRUCTURE DRAINAGE OUTLET AND DIRECTION.




-Y- ROADWAY CURVE DATA
 SEE ROADWAY PLANS.

SEE ROADWAY PLANS FOR EXISTING PAVEMENT ELEVATIONS.

GRADE DATA -Y-

-S1- TRACK CURVE DATA

PIs STA. 28+73.70
 Δs = 0° 15' 30.0"
 Ls = 31.00'
 LT = 20.67'
 ST = 10.33'




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1- = POC STA. 11+60.17 -Y-
 MILE POST: NS 377.70
 SHEET 1 OF 3 BRIDGE NO. _____

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 GENERAL DRAWING
 BRIDGE ON STATION TRACK 1 OVER W 4TH STREET BETWEEN W TRADE STREET AND W MOREHEAD STREET

HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	
DRAWN BY B. VAUGHN	DATE 8/17	DWG. NO. 1	
CHECKED BY R. RAPP	DATE 9/17		

REVISIONS				SHEET NO.	
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		
				TOTAL SHEETS 19	



NOTE:
FOR SUBSTRUCTURE BILL OF MATERIAL, REFER TO "BRIDGE ON STATION TRACK 2 OVER W 4TH STREET" PLANS.


* SUBSTRUCTURE SHOWN FOR INFORMATION ONLY. FOR SUBSTRUCTURE SHEETS, REFER TO "BRIDGE ON STATION TRACK 2 OVER W 4TH STREET" PLANS.

TOTAL BILL OF MATERIAL								
	REINFORCED CONCRETE DECK SLAB	APPROX. 233,588 LBS. STRUCTURAL STEEL	PAINTING OF STRUCTURAL STEEL	WATERPROOFING	CONCRETE PARAPET	SELF-LUBRICATING EXPANSION BEARING ASSEMBLIES	STRUCTURE DRAINAGE SYSTEM AT STA. 28+17.22 -S1-	APPLICATION OF BRIDGE COATING
	SQ. FEET	LUMP SUM	LUMP SUM	SQ. YARDS	L.F.	LUMP SUM	LUMP SUM	LUMP SUM
SUPERSTRUCTURE	2,568.8	LUMP SUM	LUMP SUM	265.6	231.4	LUMP SUM	LUMP SUM	LUMP SUM
TOTAL	2,568.8	LUMP SUM	LUMP SUM	265.6	231.4	LUMP SUM	LUMP SUM	LUMP SUM

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 28+17.22 -S1-

SHEET 2 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
GENERAL DRAWING
LOCATION SKETCH
AND
TOTAL BILL OF MATERIAL



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
CHECKED BY R. RAPP DATE 9/17 DWG. NO. 2

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S6-2
1	JRR	05/02/2018	3			TOTAL SHEETS
2			4			19

GENERAL NOTES:

ASSUMED LIVE LOAD = AREMA E80 OR ALTERNATE LIVE LOAD

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE 2016 EDITION OF AREMA'S "MANUAL FOR RAILWAY ENGINEERING, VOL. 2, STRUCTURES", AND "NORFOLK SOUTHERN GUIDELINES FOR DESIGN OF GRADE SEPARATION STRUCTURES, UNDERPASS GRADE SEPARATION DESIGN CRITERIA".

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE 2016 EDITION OF AREMA'S "MANUAL FOR RAILWAY ENGINEERING VOL. 2, CHP. 9, SEISMIC DESIGN FOR RAILWAY".

REINFORCING STEEL SHALL BE ASTM DESIGNATION A615, GRADE 60. ALL DIMENSIONS RELATING TO BAR SPACING ARE TO BAR CENTERS UNLESS NOTED. FABRICATION TO BE IN ACCORDANCE WITH THE "MANUAL OF STANDARD PRACTICE", A.C.I. 315-80. ALL REINFORCING IN THE CONCRETE DECK SLAB AND PARAPETS SHALL BE EPOXY COATED.

EXPANSION JOINT MATERIAL SHALL BE EITHER RUBBER OR CORK CONFORMING WITH AASHTO SPECIFICATIONS M-153-84 EXCEPT AS SHOWN ON THE PLANS OR IN THE SPECIAL PROVISIONS. CELLULAR AND BULB TYPE WATERSTOPS AND RUBBER JOINT COMPOUNDS SHALL BE AS SHOWN ON THE PLANS AND IN THE SPECIAL PROVISIONS.

STRUCTURE DRAINAGE SYSTEM: DUCTILE IRON PIPE COLLECTOR SYSTEM SHALL BE AS SHOWN ON THE PLANS AND OUTLINED IN THE SPECIAL PROVISIONS. DETAILS OF THE DRAINAGE SYSTEM SHALL BE SUBMITTED TO THE CHIEF ENGINEER BRIDGES AND STRUCTURES, NORFOLK SOUTHERN CORPORATION, ATLANTA, GA. FOR APPROVAL.

WATERPROOFING: BRIDGE DECK AND ALL CONSTRUCTION JOINTS WHICH WILL BE COVERED BY FILL SHALL BE WATERPROOFED WITH A COLD LIQUID-APPLIED ELASTOMERIC MEMBRANE. FOR WATERPROOFING, SEE SPECIAL PROVISIONS.

WATERPROOFING IS REQUIRED AT THE FOLLOWING LOCATION:
1. BRIDGE DECK AND INSIDE OF CONCRETE PARAPET AS SHOWN ON "TYPICAL SECTION" SHEET.

WATERPROOFING SHALL BE 24" WIDE AND SHALL BE CENTERED OVER JOINTS OR CRACKS.

THE CONTRACTOR SHALL PROVIDE INDEPENDENT ASSURANCE SAMPLES OF REINFORCING STEEL AS FOLLOWS: FOR PROJECTS REQUIRING UP TO 400 TONS OF REINFORCING STEEL, ONE 30 INCH SAMPLE OF EACH SIZE BAR USED, AND FOR PROJECTS REQUIRING OVER 400 TONS OF REINFORCING STEEL, TWO 30 INCH SAMPLES OF EACH SIZE BAR USED. THE BARS FROM WHICH THE SAMPLES ARE TAKEN MUST THEN BE SPLICED WITH REPLACEMENT BARS OF THE SIZE AND LENGTH OF THE SAMPLE, PLUS A MINIMUM LAP SPLICE OF THIRTY BAR DIAMETERS. PAYMENT FOR THE SAMPLES OF REINFORCING STEEL SHALL BE CONSIDERED INCIDENTAL TO VARIOUS PAY ITEMS.

ALL MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES", JANUARY 2018, NORTH CAROLINA DEPARTMENT OF TRANSPORTATION (HEREIN CALLED STANDARD SPECIFICATIONS), EXCEPT AS NOTED HEREIN, ELSEWHERE ON PLANS, OR IN THE SPECIAL PROVISIONS (STRUCTURAL STEEL IN ACCORDANCE WITH THE 2016 AREMA SPECIFICATIONS).

ALL CONCRETE SHALL BE 4,500 PSI CLASS AA CONCRETE WITH NO. 57 OR 67 COARSE AGGREGATE AND SHALL BE AIR-ENTRAINED. MINIMUM CEMENT CONTENT PER CUBIC YARD OF CONCRETE SHALL BE 6.5 BAGS. NO SUBSTITUTION OF FLYASH, BLAST FURNACE SLAG OR OTHER MATERIAL WILL BE PERMITTED IN MEETING THIS MINIMUM CEMENT REQUIREMENT. CHAMFER ALL EXPOSED EDGES AND CORNERS 3/4" EXCEPT AS NOTED. THE USE OF GROUND GRANULATED BLAST FURNACE SLAG IS NOT PERMITTED IN THIS STRUCTURE.

CONTROL OF WORK: ALL WORK INVOLVED IN THE CONSTRUCTION OF THE RAILWAY STRUCTURE SHALL BE PERFORMED SATISFACTORY TO THE ENGINEER AND COMPLIANT WITH THE DESIGN STANDARDS OF NORFOLK SOUTHERN RAILWAY COMPANY. ALL METHODS OF HANDLING THE WORK AFFECTING THE SAFETY OF RAIL OPERATIONS MUST BE APPROVED BY THE RAILWAY COMPANY, AS A SUBMITTAL THROUGH THE ENGINEER, AT LEAST TWO WEEKS BEFORE PROCEEDING WITH THAT PORTION OF THE WORK. RAIL TRAFFIC SHALL, AT ALL TIMES, BE MAINTAINED AND PROTECTED. THE CONTRACTOR SHALL NOT AT ANY TIME DELAY OR INTERFERE WITH RAIL OPERATIONS.

NEEDLE BEAMS WILL NOT BE ALLOWED UNLESS OTHERWISE CALLED FOR ON THE PLANS OR APPROVED BY THE ENGINEER.

REMOVABLE FORMS MAY BE USED IN LIEU OF METAL STAY-IN-PLACE FORMS IN ACCORDANCE WITH ARTICLE 420-3 OF THE STANDARD SPECIFICATIONS.

FOR SELF-LUBRICATING EXPANSION BEARING ASSEMBLIES, SEE SPECIAL PROVISIONS.

FOR CONDUIT IN PARAPETS, SEE SPECIAL PROVISIONS.

FOR PORTLAND CEMENT, SEE SPECIAL PROVISIONS.

FOR FINE AND COARSE AGGREGATE, SEE SPECIAL PROVISIONS.

SEE "STRUCTURAL STEEL DETAILS" SHEET FOR STRUCTURAL STEEL NOTES.

FOR PAINTING STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

FOR WATERSTOPS, SEE SPECIAL PROVISIONS.

FOR ELASTOMERIC FLASHING, SEE SPECIAL PROVISIONS.

FOR RUBBER JOINT COMPOUNDS, SEE SPECIAL PROVISIONS.

FOR STRUCTURE DRAINAGE SYSTEM, SEE SPECIAL PROVISIONS.

FOR STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

FOR RAILROAD TRACKWORK, SEE RAILROAD TRACKWORK PLANS.

FOR MAINTENANCE AND PROTECTION OF TRAFFIC BENEATH PROPOSED STRUCTURE, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR CONCRETE PARAPET, SEE SPECIAL PROVISIONS.

FOR WATERPROOFING, SEE SPECIAL PROVISIONS.

FOR PLACING LOAD ON STRUCTURE MEMBERS, SEE SPECIAL PROVISIONS.

FOR APPLICATION OF BRIDGE COATING, SEE SPECIAL PROVISIONS.

FOR EXPANSION JOINTS, SEE SPECIAL PROVISIONS.

INDEX OF DRAWINGS

- 1 GENERAL DRAWING: GENERAL PLAN AND ELEVATION (SHEET 1 OF 3)
- 2 GENERAL DRAWING: LOCATION SKETCH AND TOTAL BILL OF MATERIAL (SHEET 2 OF 3)
- 3 GENERAL DRAWING: GENERAL NOTES (SHEET 3 OF 3)
- 4 SUPERSTRUCTURE: TYPICAL SECTION
- 5 SUPERSTRUCTURE: DECK DETAILS
- 6 SUPERSTRUCTURE: PLAN OF DECK - SPAN A
- 7 SUPERSTRUCTURE: PLAN OF DECK - SPAN B
- 8 SUPERSTRUCTURE: PLAN OF DECK - SPAN C
- 9 SUPERSTRUCTURE: FRAMING PLAN AND GIRDER DETAILS - SPAN A AND SPAN C
- 10 SUPERSTRUCTURE: FRAMING PLAN AND GIRDER DETAILS - SPAN B
- 11 SUPERSTRUCTURE: STRUCTURAL STEEL DETAILS
- 12 SUPERSTRUCTURE: BEARING DETAILS - SPAN A AND SPAN C
- 13 SUPERSTRUCTURE: BEARING DETAILS - SPAN B
- 14 SUPERSTRUCTURE: EXPANSION PLATE DETAILS
- 15 SUPERSTRUCTURE: PARAPET DETAILS (SHEET 1 OF 2)
- 16 SUPERSTRUCTURE: PARAPET DETAILS (SHEET 2 OF 2)
- 17 SUPERSTRUCTURE: BILL OF MATERIAL
- 18 STRUCTURE: DRAINAGE DETAILS (SHEET 1 OF 2)
- 19 STRUCTURE: DRAINAGE DETAILS (SHEET 2 OF 2)

FOR SUBSTRUCTURE SHEETS, REFER TO "BRIDGE ON STATION TRACK 2 OVER W 4TH STREET" PLANS.


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 28+17.22 -S1-

SHEET 3 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

GENERAL DRAWING


GENERAL NOTES



DocuSigned by:
568316C226434...
2/21/2018

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS						SHEET NO. S6-3 TOTAL SHEETS 19
	NO.	BY	DATE	NO.	BY	DATE	
	1		8/17	3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u>	DWG. NO. 3		2		4		



NOTES FOR SIGNAL CONDUIT IN PARAPET

SIGNAL CONDUIT TO BE 4" DIA. IN ACCORDANCE WITH UNDERWRITER'S LABORATORY SPECIFICATIONS.

PROVISIONS SHALL BE MADE FOR EXPANSION BETWEEN DECK SLABS AT EXPANSION JOINTS AT PIERS 1 & 2 (GALVANIZED EXPANSION FITTINGS).

COUPLING SHALL BE PROVIDED BEHIND BACKWALL OF ABUTMENT 1 AND 2 FOR CONNECTION TO 4" DIA. RIGID PIPE (RIGID PIPE BY RAILWAY COMPANY).

FOR SIGNAL CONDUIT IN PARAPET SEE PROJECT SPECIAL PROVISIONS.

NOTES:


ALL REINFORCING STEEL IN THE DECK AND PARAPETS SHALL BE EPOXY COATED. CLEAR COVER TO ALL REINFORCING IS 2" MINIMUM UNLESS NOTED OTHERWISE.

FOR ALUMINUM ARCHITECTURAL HANDRAIL DETAILS, SEE ARCHITECTURAL FIN RAIL PLANS.


FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.

DESIGN INCLUDES WEIGHT OF 6" ADDITIONAL BALLAST TO ACCOUNT FOR FUTURE RESURFACING OF TRACK.

* MINIMUM GAP REMAINING AFTER CONSIDERING ALL PLATFORM DEFLECTIONS.







PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 TYPICAL SECTION

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S6-4 TOTAL SHEETS 19		
	NO.	BY	DATE	NO.		BY	DATE
	1			3			
DRAWN BY: <u>J. JEFFERS</u> CHECKED BY: <u>R. RAPP</u>	DATE: <u>8/17</u> DATE: <u>9/17</u>	DWG. NO. <u>4</u>					




PART SECTION AT EXPANSION JOINT
NOTE: FOR ADDITIONAL PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 28+17.22 -S1-



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u>	DWG. NO. 5	REVISIONS				SHEET NO. S6-5 TOTAL SHEETS 19
			NO.	BY	DATE		
			1		3		
		2		4			




NOTES:

- ALL REINFORCING SHALL BE EPOXY COATED.
- FOR SECTIONS A-A & B-B SEE "DECK DETAILS" SHEET.
- FOR DECK DRAIN DETAIL SEE DETAIL "B" ON "STRUCTURE: DRAINAGE DETAILS", SHEET 2 OF 2.
- FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.
- SLAB BARS MAY BE ADJUSTED TO AVOID DECK DRAIN LOCATIONS.

PLAN - SPAN A




DETAIL A



DETAIL B

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-




DocuSigned by:
 Joel R. Rapp
 55683197C228434
 2/21/2018


DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 PLAN OF DECK - SPAN A


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO.		
	NO.	BY	DATE	NO.	BY	DATE	S6-6
	1			3			TOTAL SHEETS
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>9/17</u> DWG. NO. 6	2			4			19



PLAN - SPAN B




DETAIL A



DETAIL B

- NOTES:
- ALL REINFORCING SHALL BE EPOXY COATED.
 - FOR SECTION B-B SEE "DECK DETAILS" SHEET.
 - FOR DECK DRAIN DETAIL SEE DETAIL "B" ON "STRUCTURE DRAINAGE DETAILS", SHEET 2 OF 2.
 - FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.
 - SLAB BARS MAY BE ADJUSTED TO AVOID DECK DRAIN LOCATIONS.



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH


SUPERSTRUCTURE

PLAN OF DECK - SPAN B


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS					SHEET NO. S6-7 TOTAL SHEETS 19	
	NO.	BY	DATE	NO.	BY		DATE
	1			3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>9/17</u> DWG. NO. 7	2			4			



PLAN - SPAN C




DETAIL A



DETAIL B

- NOTES:**
- ALL REINFORCING SHALL BE EPOXY COATED.
 - FOR SECTIONS A-A & B-B SEE "DECK DETAILS" SHEET.
 - FOR DECK DRAIN DETAIL SEE DETAIL "B" ON "STRUCTURE: DRAINAGE DETAILS", SHEET 2 OF 2.
 - FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.
 - SLAB BARS MAY BE ADJUSTED TO AVOID DECK DRAIN LOCATIONS.


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 PLAN OF DECK - SPAN C


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS					SHEET NO. S6-8 TOTAL SHEETS 19	
	DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>9/17</u>	NO. <u>1</u> BY <u> </u> DATE <u> </u>	NO. <u>3</u> BY <u> </u> DATE <u> </u>	NO. <u> </u> BY <u> </u> DATE <u> </u>	NO. <u> </u> BY <u> </u> DATE <u> </u>		NO. <u> </u> BY <u> </u> DATE <u> </u>
	DWG. NO. 8	NO. <u>2</u> BY <u> </u> DATE <u> </u>	NO. <u>4</u> BY <u> </u> DATE <u> </u>	NO. <u> </u> BY <u> </u> DATE <u> </u>	NO. <u> </u> BY <u> </u> DATE <u> </u>		




SPAN A FRAMING PLAN



SPAN C FRAMING PLAN




SPAN A TYPICAL GIRDER ELEVATION (INTERIOR GIRDER SHOWN, EXTERIOR GIRDER SIMILAR)



SPAN C TYPICAL GIRDER ELEVATION (INTERIOR GIRDER SHOWN, EXTERIOR GIRDER SIMILAR)

SPAN A GIRDER DIMENSIONS		
GIRDER	DIM. "A"	DIM. "B"
AG1-1	8'-9 ⁵ / ₁₆ "	10'-1 ⁵ / ₁₆ "
AG2-1	9'-1 ¹ / ₈ "	9'-10 ³ / ₄ "
AG3-1	9'-4 ¹⁵ / ₁₆ "	9'-7 ⁹ / ₁₆ "
AG4-1	9'-7 ⁹ / ₁₆ "	9'-4 ⁵ / ₁₆ "
AG5-1	9'-10 ³ / ₄ "	9'-1 ¹ / ₈ "
AG6-1	10'-1 ⁵ / ₁₆ "	8'-9 ⁵ / ₁₆ "

SPAN C GIRDER DIMENSIONS		
GIRDER	DIM. "A"	DIM. "B"
CG1-1	7'-11 ⁷ / ₁₆ "	9'-3 ⁷ / ₁₆ "
CG2-1	8'-2 ⁵ / ₈ "	9'-0 ¹ / ₄ "
CG3-1	8'-5 ¹³ / ₁₆ "	8'-9 ¹ / ₁₆ "
CG4-1	8'-9 ¹ / ₁₆ "	8'-5 ¹³ / ₁₆ "
CG5-1	9'-0 ¹ / ₄ "	8'-2 ⁹ / ₁₆ "
CG6-1	9'-3 ¹ / ₁₆ "	7'-11 ⁷ / ₁₆ "




DETAIL "A" (RIGHT SIDE OF WEB SHOWN, LEFT SIDE SIMILAR)

NOTES:
 ALL DIMENSIONS ON THIS DRAWING ARE HORIZONTAL.
 ALL ABUTMENT FILL FACES, C PIER, AND C BEARINGS ARE PARALLEL.
 NO SHOP CAMBER REQUIRED, TURN NATURAL MILL CAMBER UP.
 REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR:


- STRUCTURAL STEEL NOTES
- DIAPHRAGM DETAILS
- STIFFENER AND CONNECTOR P DETAILS
- SHEAR CONNECTOR DETAILS
- FLANGE TO WEB WELD DETAILS

FOR BEARINGS, SEE "BEARING DETAILS SPAN A AND SPAN C" SHEET.
 FOR DRAIN PIPE SUPPORT DETAILS, SEE "STRUCTURE DRAINAGE DETAILS" SHEETS.
 FLANGE AND WELD SHOP SPLICES SHALL BE MADE WITH FULL PENETRATION GROOVE WELDS. SEE DETAILS ON "STRUCTURAL STEEL DETAILS" SHEET. FABRICATOR IS TO SHOW WELD CONFIGURATION AND JOINT PREPARATION ON SHOP DRAWINGS FOR APPROVAL.
 FLANGE AND WEB SHOP SPLICES SHALL BE STAGGERED LONGITUDINALLY A MINIMUM OF 2'-0". SEE "STRUCTURAL STEEL DETAILS" SHEET FOR DETAILS.
 FC = "FRACTURE CRITICAL"
 INT = NON-FRACTURE CRITICAL MEMBERS OR COMPONENTS REQUIRING IMPROVED NOTCH TOUGHNESS.




@ ABUTMENT 1

BOTTOM FLANGE GIRDER END DETAILS - SPAN A




@ PIER 1




@ PIER 2

BOTTOM FLANGE GIRDER END DETAILS - SPAN C



@ ABUTMENT 2



DocuSigned by:
 2/21/2018


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUPERSTRUCTURE
 FRAMING PLAN
 AND GIRDER DETAILS
 SPAN A AND SPAN C

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S6-9		
	NO.	BY	DATE	NO.		BY	DATE
	1			3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u> DWG. NO. 9	2			4		TOTAL SHEETS 19	



SPAN B GIRDER DIMENSIONS		
GIRDER	DIM. "A"	DIM. "B"
BG1-1	8'-6 ⁵ / ₁₆ "	9'-11"
BG2-1	8'-10 ³ / ₁₆ "	9'-7 ³ / ₄ "
BG3-1	9'-1 ³ / ₈ "	9'-4 ⁹ / ₁₆ "
BG4-1	9'-4 ⁹ / ₁₆ "	9'-1 ³ / ₈ "
BG5-1	9'-7 ³ / ₄ "	8'-10 ³ / ₁₆ "
BG6-1	9'-11"	8'-6 ⁵ / ₁₆ "

NOTES:

ALL DIMENSIONS ON THIS DRAWING ARE HORIZONTAL.

ALL C PIER AND C BEARINGS ARE PARALLEL.

NO SHOP CAMBER REQUIRED, TURN NATURAL MILL CAMBER UP.

REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR:

- STRUCTURAL STEEL NOTES
- DIAPHRAGM DETAILS
- STIFFENER AND CONNECTOR P DETAILS
- SHEAR CONNECTOR DETAILS
- FLANGE TO WEB WELD DETAILS

FOR BEARINGS, SEE "BEARING DETAILS SPAN B" SHEET.

FOR DRAIN PIPE SUPPORT DETAILS, SEE "STRUCTURE DRAINAGE DETAILS" SHEETS.


FLANGE AND WELD SHOP SPLICES SHALL BE MADE WITH FULL PENETRATION GROOVE WELDS. SEE DETAILS ON "STRUCTURAL STEEL DETAILS" SHEET. FABRICATOR IS TO SHOW WELD CONFIGURATION AND JOINT PREPARATION ON SHOP DRAWINGS FOR APPROVAL.

FLANGE AND WEB SHOP SPLICES SHALL BE STAGGERED LONGITUDINALLY A MINIMUM OF 2'-0". SEE "STRUCTURAL STEEL DETAILS" SHEET FOR DETAILS.


FC = "FRACTURE CRITICAL"

INT = NON-FRACTURE CRITICAL MEMBERS OR COMPONENTS REQUIRING IMPROVED NOTCH TOUGHNESS.


SPAN B FRAMING PLAN



SPAN B TYPICAL GIRDER ELEVATION (INTERIOR GIRDER SHOWN, EXTERIOR GIRDER SIMILAR)




DETAIL "A" (RIGHT SIDE OF WEB SHOWN, LEFT SIDE SIMILAR)



BOTTOM FLANGE GIRDER END DETAILS - SPAN B


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S6-10 TOTAL SHEETS 19		
	NO.	BY	DATE	NO.		BY	DATE
	1		8/17	3			
2		9/17	4				


DRAWN BY B. VAUGHN DATE 8/17 DWG. NO. 10
 CHECKED BY R. RAPP DATE 9/17




SECTION @ END DIAPHRAGM (D1, D4, D5, & D6)




SECTION @ INTERMEDIATE DIAPHRAGM (D2 & D3)




SHEAR CONNECTOR DETAILS




FLANGE TO WEB WELD DETAIL




DETAIL "A"



STIFFENER/CONN. DETAILS



WELD TERMINATION DETAILS (FILLET WELDS ONLY)



NOTES:
ELECTROSLAG WELDING IS NOT PERMITTED.
ULTRASONIC OR RADIOGRAPHIC INSPECTION IS REQUIRED FOR ALL FLANGE AND WEB SPLICE WELDS. SEE SPECIAL PROVISIONS.
GRIND WELDS IN DIRECTION OF STRESS ONLY (I.E. PARALLEL TO G GIRDER).

SHOP SPLICE DETAILS

STRUCTURAL STEEL NOTES

STRUCTURAL STEEL SHALL CONFORM TO THE FOLLOWING ASTM SPECIFICATIONS:

- GIRDER FLANGES AND WEB: A709, GRADE 50.
- MISCELLANEOUS MATERIAL: A709, GRADE 50.
- ANCHOR BOLTS FOR BEARING DEVICES SHALL CONFORM TO ASTM F1554, GRADE 105. ANCHOR BOLTS, NUTS, AND PLATE WASHERS SHALL BE HOT-DIPPED GALVANIZED IN ACCORDANCE WITH ASTM F2329.

STRUCTURAL STEEL ELEMENTS DENOTED AS "FC" ARE FRACTURE CRITICAL AND SHALL MEET IMPACT TEST REQUIREMENTS SET FORTH IN THE FRACTURE CONTROL PLAN OF THE AREMA MANUAL, CHAPTER 15, SECTION 1.14. NOTCH TOUGHNESS REQUIREMENTS AND TESTING SHALL BE BASED ON ZONE 2 REQUIREMENTS.

STRUCTURAL STEEL ELEMENTS DENOTED AS "INT" SHALL MEET IMPACT TEST REQUIREMENTS SET FORTH IN THE FRACTURE CONTROL PLAN OF THE AREMA MANUAL, CHAPTER 15, SECTION 1.2. TESTING SHALL BE BASED ON ZONE 2 REQUIREMENTS.

ALL DIMENSIONS SHOWN ARE HORIZONTAL OR VERTICAL UNLESS OTHERWISE NOTED. ALL DIMENSIONS ARE SHOWN AT 60°F.

NC DOT RAILS DIVISION SHALL BE FURNISHED COPIES OF MILL TEST REPORTS FOR ALL MATERIALS EXCEPT MISCELLANEOUS PLATES AND SHAPES. REPORTS SHALL INDICATE COMPLIANCE WITH ALL SPECIFIED REQUIREMENTS.

SHOP INSPECTION SHALL BE BY NORFOLK SOUTHERN CORPORATION OR ITS AUTHORIZED AGENT. SEE STRUCTURAL STEEL SPECIAL PROVISION FOR ADDITIONAL WELDING INSPECTION OF FLANGE PLATE TO WEB PLATE WELDS.

FOR PAINTING STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

BOLTED CONNECTIONS SHALL BE MADE WITH 7/8" Ø ASTM A325, TYPE 1 HIGH STRENGTH BOLTS WITH HEAVY HEX HEAD, HEAVY HEX NUT AND HARDENED WASHERS IN ACCORDANCE WITH A.R.E.M.A. SPECIFICATIONS USING THE TURN OF THE NUT METHOD. DIRECT TENSION INDICATORS SHALL NOT BE USED.

SHOP DRAWINGS SHALL BE APPROVED BY THE CHIEF ENGINEER - BRIDGES AND STRUCTURES, NORFOLK SOUTHERN CORPORATION, ATLANTA, GA. SHOP DRAWINGS SHALL BE LABELED "NORFOLK SOUTHERN MP 377.70".

BOLT HOLES IN STRUCTURAL STEEL MEMBERS SHALL BE STANDARD SIZE UNLESS OTHERWISE INDICATED ON THE PLANS.

HIGH STRENGTH BOLTS, NUTS & WASHERS SHALL BE MECHANICALLY GALVANIZED IN ACCORDANCE WITH ASTM B695.

ANCHOR BOLTS SHALL BE 1/4" Ø IN ACCORDANCE WITH A.R.E.M.A. SPECIFICATIONS AND SHALL BE GROUTED IN FORMED HOLES AFTER GIRDERS ARE ERECTED.

BEARING PADS SHALL BE USED WHENEVER STEEL MASONRY PLATE, OR OTHER STEEL BEARING PLATE, BEARS ON CONCRETE. PADS SHALL BE PREFORMED FABRIC BEARING PADS, 1/2" THICK. FOR PAD REQUIREMENTS, SEE STRUCTURAL STEEL SPECIAL PROVISIONS.

SHEAR CONNECTORS ON GIRDERS MAY BE SHIFTED AS NECESSARY TO CLEAR FLANGE SPLICE WELDS.

WEB SHOP SPLICES ARE PERMITTED TO LIMIT THE MAXIMUM REQUIRED WEB PIECE LENGTHS TO 45'-0". PERMITTED WEB SHOP SPLICES SHALL NOT BE LOCATED WITHIN 15'-0" OF MAXIMUM DEAD LOAD DEFLECTION AND WEB SHOP SPLICES SHALL CONFORM TO SHOP SPLICE DETAILS SHOWN ON THE PLANS.


ALL WELDING CONNECTIONS SHALL BE MADE WITH SERIES E70 WELDING ELECTRODES.

FOR DIAPHRAGM LOCATIONS, SEE FRAMING PLANS.

FOR DETAILS OF DIAPHRAGM SUPPORT ANGLES (DSA), SEE "STRUCTURE DRAINAGE DETAILS" SHEET 2 OF 2.

STIFFENER/CONN. SCHEDULE		
TYPE	SPANS A & C	SPAN B
BRG. STIFF.	1/2" x 5"	1" x 9 1/2"
DIAPH. CONN.	1/2" x 5 1/2"	1/2" x 6"
INT. STIFF.	1/2" x 5 1/2"	1/2" x 6"

NOTE: SEE FRAMING PLANS FOR STIFFENER/CONN. LOCATIONS



DocuSigned by:
2/21/2018

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED


HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY: B. VAUGHN DATE: 8/17
CHECKED BY: K. ERVIN DATE: 9/17 DWG. NO. 11


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 28+17.22 -S1-

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
SUPERSTRUCTURE
STRUCTURAL STEEL DETAILS

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S6-11
1			3			TOTAL SHEETS
2			4			19




FIXED BEARINGS




EXPANSION BEARINGS


BRONZE PLATE TO BE ASTM B22 - COPPER ALLOY 911 OR ASTM B100 - COPPER ALLOY 510. TOP SURFACE TO BE SELF LUBRICATING.



FIXED BEARING ASSEMBLY (FBA-1)
(12 REQ'D)



ANCHOR BOLT DETAIL



EXPANSION BEARING ASSEMBLY (EBA-1)
(12 REQ'D)

NOTES:

ANCHOR BOLTS, SLIDING PLATE (EXPANSION BEARING) AND MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL BE HOT DIPPED GALVANIZED.

ALL PLATE SURFACES SHALL BE PAINTED WITH A 3 COAT PAINT SYSTEM EXCEPT AS SPECIFIED BELOW.

(A) THE SLIDING PLATE (EXPANSION BEARING) SHALL NOT BE PAINTED BUT SHALL RECEIVE A COAT OF LUBRICATION.

(B) THE MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL NOT BE PAINTED.

(C) THE BOTTOM SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED BUT SHALL RECEIVE A SINGLE COAT OF PRIMER APPLIED IN THE SHOP.


(D) THE TOP SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED IN THE VICINITY OF THE WELD BETWEEN THE SOLE PLATE AND THE BOTTOM FLANGE.

FOR ACRYLIC PAINT SYSTEM FOR STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

FOR SELF LUBRICATING EXPANSION BEARING ASSEMBLIES, SEE SPECIAL PROVISIONS.

REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR ADDITIONAL NOTES.

BEARING PLATE SCHEDULE										
GIRDER	DIMENSIONS									
	FIXED BEARING (FBA-1)					EXPANSION BEARING (EBA-1)				
	"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"	"J"	"K"
AG1-1	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG2-1	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG3-1	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG4-1	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG5-1	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG6-1	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
CG1-1	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 5/8"	6 5/8"	9 1/2"	2" x 3"
CG2-1	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 5/8"	6 5/8"	9 1/2"	2" x 3"
CG3-1	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 5/8"	6 5/8"	9 1/2"	2" x 3"
CG4-1	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"
CG5-1	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"
CG6-1	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"



DocuSigned by:
Joel R. Rapp
50863197C228434...
2/21/2018

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 28+17.22 -S1-

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH


SUPERSTRUCTURE
BEARING DETAILS
SPAN A AND SPAN C

HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	
DRAWN BY <u>B. VAUGHN</u>	DATE <u>8/17</u>	DWG. NO. 12	
CHECKED BY <u>R. RAPP</u>	DATE <u>9/17</u>		

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S6-12
1			3			TOTAL SHEETS
2			4			19




FIXED BEARINGS




EXPANSION BEARINGS

BRONZE PLATE TO BE ASTM B22 - COPPER ALLOY 911 OR ASTM B100 - COPPER ALLOY 510. TOP SURFACE TO BE SELF LUBRICATING.



FIXED BEARING ASSEMBLY (FBA-2)
(6 REQ'D)



ANCHOR BOLT DETAIL

NOTES:

ANCHOR BOLTS, SLIDING PLATE (EXPANSION BEARING) AND MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL BE HOT DIPPED GALVANIZED.

ALL PLATE SURFACES SHALL BE PAINTED WITH A 3 COAT PAINT SYSTEM EXCEPT AS SPECIFIED BELOW.

(A) THE SLIDING PLATE (EXPANSION BEARING) SHALL NOT BE PAINTED BUT SHALL RECEIVE A COAT OF LUBRICATION.

(B) THE MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL NOT BE PAINTED.


(C) THE BOTTOM SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED BUT SHALL RECEIVE A SINGLE COAT OF PRIMER APPLIED IN THE SHOP.

(D) THE TOP SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED IN THE VICINITY OF THE WELD BETWEEN THE SOLE PLATE AND THE BOTTOM FLANGE.

FOR ACRYLIC PAINT SYSTEM FOR STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

FOR SELF LUBRICATING EXPANSION BEARING ASSEMBLIES, SEE SPECIAL PROVISIONS.


REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR ADDITIONAL NOTES.



EXPANSION BEARING ASSEMBLY (EBA-2)
(6 REQ'D)

1/2" Ø STANDARD PIPE SLEEVE THRU SOLE PLATE & SLIDING PLATE & 1/8" ABOVE SOLE PLATE (GALVANIZED STEEL PIPE) (TYP.)

BEARING PLATE SCHEDULE										
GIRDER	DIMENSIONS									
	FIXED BEARING (FBA-2)					EXPANSION BEARING (EBA-2)				
	"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"	"J"	"K"
BG1-1	1 1/2"	2 5/8"	4 5/8"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG2-1	1 1/2"	2 5/8"	4 5/8"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG3-1	1 1/2"	2 5/8"	4 5/8"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG4-1	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG5-1	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG6-1	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"



DocuSigned by:
Joel R. Rapp
55663197C228434
2/21/2018

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 28+17.22 -S1-


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE
BEARING DETAILS
SPAN B


HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
CHECKED BY R. RAPP DATE 9/17 DWG. NO. 13


REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S6-13
1			3			TOTAL SHEETS
2			4			19



DETAIL A




SECTION A-A



SECTION B-B

DETAIL OF EXPANSION ANCHOR AND PLATE

SEE DETAIL A ON "DECK DETAILS" SHEET FOR ADDITIONAL JOINT INFORMATION.




PLAN - EXPANSION PLATE
(4 REQUIRED)

NOTE: PAYMENT FOR THE EXPANSION PLATE AND EXPANSION ANCHORS IS INCLUDED IN THE COST FOR STRUCTURE STEEL.

PLATE SHALL BE ANCHORED AT BACKWALL OF ABUTMENT 1 & 2, SPAN B SIDE OF PIER 1, AND SPAN B SIDE OF PIER 2.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-



DocuSigned by:
 [Signature]
 55683197C228434...
 2/21/2018


DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 EXPANSION PLATE DETAILS


HNTB HNTB NORTH CAROLINA, P.C.
 NC License No. C-1554
 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
 CHECKED BY R. RAPP DATE 9/17 DWG. NO. 14


REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S6-14
1			3			TOTAL SHEETS
2			4			19




PLAN - SPAN A PARAPETS



SECTION THRU OPEN JOINT IN PARAPET



SECTION A-A THRU PARAPET



SECTION B-B THRU PARAPET

NOTES:

ALUMINUM ARCHITECTURAL HANDRAIL NOT SHOWN FOR CLARITY.

ALL HORIZONTAL DIMENSIONS SHOWN ARE MEASURED ALONG EXTERIOR FACE OF PARAPET.

ALL REINFORCING SHALL BE EPOXY COATED.

FOR LOCATION AND DETAILS OF SIGNAL CONDUIT IN CONCRETE PARAPET, SEE "TYPICAL SECTION" SHEET.

FOR ALUMINUM ARCHITECTURAL HANDRAIL DETAILS, SEE ARCHITECTURAL FIN RAIL PLANS.

VERTICAL GROOVED CONTRACTION JOINTS, 1/2" IN DEPTH, SHALL BE TOOLED IN ALL EXPOSED FACES OF PARAPET AND IN ACCORDANCE WITH THE SPECIAL PROVISION FOR "CONCRETE PARAPET". THE CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN PARAPET EXPANSION JOINTS.

#5S1 AND #5S2 BARS IN PARAPET MAY BE SHIFTED SLIGHTLY TO MAINTAIN PROPER CLEARANCE TO EXPANSION JOINTS IN PARAPET.

E.F. = EACH FACE

PAYMENT FOR CONCRETE PARAPET SHALL BE INCLUDED IN THE UNIT COST PAY ITEM FOR CONCRETE PARAPET.


PAY LENGTH = 231.4'

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-

SHEET 1 OF 2

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUPERSTRUCTURE
 PARAPET DETAILS




DocuSigned by:
 2/21/2018

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C.
 NC License No. C-1554
 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
 CHECKED BY R. RAPP DATE 9/17 DWG. NO. 15

REVISIONS						SHEET NO. S6-15
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 19
2			4			




NOTE:
SEE SHEET 1 OF 2 FOR NOTES AND SECTIONS.

PLAN - SPAN B & SPAN C PARAPETS

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POT STA. 28+17.22 -S1-

SHEET 2 OF 2



DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE

PARAPET DETAILS

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609		DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u>		DWG. NO. 16		<table border="1"> <thead> <tr> <th colspan="6">REVISIONS</th> </tr> <tr> <th>NO.</th> <th>BY</th> <th>DATE</th> <th>NO.</th> <th>BY</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td></td> <td>3</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td></td> <td></td> <td>4</td> <td></td> <td></td> </tr> </tbody> </table>		REVISIONS						NO.	BY	DATE	NO.	BY	DATE	1			3			2			4			SHEET NO. S6-16 TOTAL SHEETS 19
REVISIONS																																
NO.	BY	DATE	NO.	BY	DATE																											
1			3																													
2			4																													


EPOXY-COATED REINFORCING STEEL																		
SPAN A						SPAN B						SPAN C						
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	
A1	85	5	STR.	21'-9"	1,929	A1	177	5	STR.	21'-9"	4,016	A1	49	5	STR.	21'-9"	1,122	
A2	8	5	STR.	21'-9"	188	A2	8	5	STR.	21'-9"	182	A2	8	5	STR.	21'-9"	182	
A3	2	5	STR.	16'-10"	36	A7	2	5	STR.	17'-11"	38	A3	2	5	STR.	16'-10"	36	
A4	2	5	STR.	10'-3"	22	A8	2	5	STR.	11'-4"	24	A4	2	5	STR.	10'-3"	22	
A5	4	5	STR.	3'-8"	16	A9	4	5	STR.	4'-10"	21	A5	4	5	STR.	3'-8"	16	
A6	2	5	STR.	15'-2"	32	A10	2	5	STR.	15'-2"	32	A11	2	5	STR.	14'-7"	31	
B1	67	4	STR.	18'-7"	832	B3	134	4	STR.	30'-0"	2,686	B1	67	4	STR.	18'-7"	832	
B2	67	4	STR.	15'-1"	676	B4	67	4	STR.	8'-6"	381	B7	20	5	STR.	18'-8"	390	
B5	40	5	STR.	15'-7"	651	B6	60	5	STR.	21'-2"	1,325							
S1	34	5	1	6'-6"	231	S1	69	5	1	6'-6"	468	S1	20	5	1	6'-6"	136	
S2	34	5	2	12'-0"	426	S2	69	5	2	12'-0"	864	S2	20	5	2	12'-0"	251	
				TOTAL	5,039					TOTAL	10,037					TOTAL	3,018	



ALL BAR DIMENSIONS ARE OUT TO OUT


	EPOXY COATED REINFORCING STEEL (LBS.)	CLASS AA CONCRETE (CU. YDS.)	
		DECK SLAB	PARAPETS
SPAN "A"	5,039	24.6	8.0
SPAN "B"	10,037	45.4	16.2
SPAN "C"	3,018	14.5	4.8
TOTALS	18,094	84.4	29.0

	REINFORCED CONCRETE DECK SLAB	EPOXY COATED REINFORCING STEEL	CLASS AA CONCRETE
	SQ. FT.	LBS.	CU. YDS.
DECK SLAB	2,568.8	13,352	84.4
PARAPET	—	4,742	29.0
TOTALS	2,568.8	18,094	113.4



LAYOUT FOR COMPUTING AREA OF REINFORCED CONCRETE DECK SLAB (SQ. FEET = 2,568.8)

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-




DocuSigned by:
 2/21/2018

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 BILL OF MATERIAL

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S6-17		
	NO.	BY	DATE	NO.		BY	DATE
	1			3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>9/17</u>	DWG. NO. 17				TOTAL SHEETS 19		



DRAINAGE DETAILS - SPAN A AND PORTION OF SPAN B

NOTES:
 ALL DIMENSIONS ARE SUBJECT TO ADJUSTMENTS TO FIT MEASUREMENTS TAKEN AFTER DECKS HAVE BEEN POURED.
 D.I. = DUCTILE IRON
 P.L. = PIPE LENGTH
 P.E. = PLAIN END
 DRAINAGE LINE 1 IS LOCATED TO THE LEFT LOOKING AHEAD STATION AND DRAINAGE LINE 2 IS LOCATED TO THE RIGHT LOOKING AHEAD STATION.
 FOR ADDITIONAL NOTES AND DETAILS, SEE "STRUCTURE: DRAINAGE DETAILS" SHEET 2 OF 2.




DRAINAGE DETAILS - PORTION OF SPAN B AND SPAN C

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-

SHEET 1 OF 2


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STRUCTURE
 DRAINAGE
 DETAILS



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u> DWG. NO. 18				
	REVISIONS				
	NO.	BY	DATE	NO.	BY
1			3		
2			4		
SHEET NO. S6-18 TOTAL SHEETS 19					




* ADJUST AS NECESSARY TO ALLOW FOR STRAY CURRENT PROTECTION. SEE NOTES.

ELEVATION

* ADJUST AS NECESSARY TO ALLOW FOR STRAY CURRENT PROTECTION. SEE NOTES.




ELEVATION




PLAN
PIPE SUPPORT ANGLE (PSA)
(12 REQ'D.)


NOTE:
DIAPHRAGM FLANGE NOT SHOWN FOR CLARITY



PLAN
DIAPHRAGM SUPPORT ANGLE (DSA)
(16 REQ'D.)



DETAIL "B"



DETAIL "A"

DSA	"Y"	DSA	"Y"	DSA	"Y"	PSA	"Y"
A1	2'-11"	B1	1'-11 3/16"	C1	3'-1 1/16"	A1	3'-3 3/16"
A2	2'-4 3/16"	B2	2'-2 1/8"			A2	2'-2 9/16"
		B3	2'-4 3/8"			A3	3'-3 3/16"
		B4	2'-6 11/16"			A4	2'-2 9/16"
		B5	2'-9"			B1	2'-0 1/16"
						B2	2'-11 1/8"
						C1	3'-1 1/16"
						C2	3'-3 3/16"
						C3	3'-1 1/16"
						C4	3'-2 15/16"

NOTES:

ALL PIPES, FLANGES AND FITTINGS SHALL BE CLASS 53 DUCTILE IRON.
 ALL BENDS TO BE SHORT RADIUS, INCLUDING FLANGE & FLARE BENDS, UNLESS OTHERWISE NOTED.
 FOR LOCATIONS AND DESIGNATIONS OF DSA & PSA, SEE FRAMING PLAN SHEETS.
 PIPE LENGTHS SHOWN ALLOW FOR 1/8" THICK GASKETS TO BE USED AT ALL BOLTED FLANGE CONNECTIONS.
 MAKE FINAL PIPE ALIGNMENT AND TIGHTEN U-BOLTS AFTER RAILROAD TRACK HAS BEEN LAID ACROSS THE BRIDGE.

PAYMENT FOR ALL MATERIALS, FABRICATION, INSTALLATION AND ADJUSTMENTS RELATED TO STRUCTURE DRAINAGE SHALL BE INCLUDED IN THE CONTRACT LUMP SUM PRICE BID FOR "STRUCTURE DRAINAGE SYSTEM". NO SEPARATE MEASUREMENT OR PAYMENT SHALL BE MADE FOR ANY COMPONENT OF THE STRUCTURE DRAINAGE SYSTEM INCLUDING, BUT NOT LIMITED TO:

- o DUCTILE IRON PIPE AND FITTINGS AND CAST IRON GRATES
- o GASKETS AND PVC OR NEOPRENE COATED STRIPS
- o STEEL SUPPORT ANGLES AND PLATES
- o U-BOLTS AND H.S. BOLTS, WASHERS AND NUTS
- o OFFSET PIPE CLAMPS AND EXPANSION ANCHOR BOLTS
- o EXPANSION JOINT

PROVIDE PVC OR NEOPRENE-COATED STRIPS, EPOXY-CEMENTED TO THE U-BOLT OR PIPE FOR STRAY CURRENT PROTECTION.

THE OUTSIDE COATING FOR D.I. PIPE SHALL BE PAINTED WITH A SHOP PRIME COAT OF INORGANIC ZINC PRIMER AND A FINISH (FIELD) COATING OF ACRYLIC PAINT AS SPECIFIED FOR THE STRUCTURAL STEEL.

FOR STRUCTURE DRAINAGE SYSTEM, SEE SPECIAL PROVISIONS.


SUPERSTRUCTURE DRAINAGE SYSTEM ESTIMATED QUANTITIES		
ITEM	UNIT	TOTAL
6" I.D. DUCTILE IRON PIPE, CLASS 53 (FLANGED BOTH ENDS)	FEET	168'-9 15/16"
6" I.D. DUCTILE IRON PIPE, CLASS 53 (FLANGE & P.E.)	FEET	7'-0 3/8"
6" I.D. DUCTILE IRON PIPE, CLASS 53 (BELL & P.E.)	FEET	38'-7 15/16"
6" I.D. DUCTILE IRON PIPE FLANGED FITTINGS, 250 psi P.R.	LBS	3,070
6" I.D. DUCTILE IRON BLIND FLANGES	LBS	200
EXPANSION JOINT	EA.	2
HEAVY DUTY CAST IRON GRATES	EA.	22
PIPE SUPPORT ANGLES (PSA) *	EA.	12
DIAPHRAGM SUPPORT ANGLES (DSA) *	EA.	16

* INCLUDES U-BOLTS, ANGLES, NUTS, BOLTS, WASHERS AND PLATES.

FOR SUBSTRUCTURE DRAINAGE SYSTEM ESTIMATED QUANTITIES, SEE "BRIDGE ON STATION TRACK 2 OVER W 4TH STREET" PLANS.

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POT STA. 28+17.22 -S1-

SHEET 2 OF 2



DocuSigned by:
 55683197C22B434...
 2/21/2018

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

STRUCTURE
 DRAINAGE
 DETAILS

HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609		REVISIONS					SHEET NO.
NO.	BY	DATE	NO.	BY	DATE				
1		8/17	3					TOTAL SHEETS	
2		9/17	4					19	

DRAWN BY B. VAUGHN DATE 8/17 DWG. NO. 19
 CHECKED BY R. RAPP DATE 9/17

0012DEL_P28




NOTE:
 SEE "GENERAL DRAWING: GENERAL NOTES (SHEET 4 OF 4)" FOR GENERAL NOTES.
 SEE ROADWAY PLANS FOR TEMPORARY TCP SHORING DETAILS AND PAY ITEMS.
 MVC = MINIMUM VERTICAL CLEARANCE
 MHC = MINIMUM HORIZONTAL CLEARANCE
 ← STRUCTURE DRAINAGE OUTLET AND DIRECTION.


-Y- ROADWAY CURVE DATA
 SEE ROADWAY PLANS.

-S2- TRACK CURVE DATA
 PIs STA 28+24.81 PI STA 28+81.33
 Δs = 0° 15' 30.0" Δ = 1° 32' 22.2" (LT)
 Ls = 31.00' D = 1° 40' 00.0"
 LT = 20.67' L = 92.37'
 ST = 10.33' T = 46.19'
 R = 3,437.87'


SEE ROADWAY PLANS FOR EXISTING PAVEMENT ELEVATIONS.
GRADE DATA -Y-



GRADE DATA -S2-



PLAN
 NOTES: PILES NOT SHOWN FOR CLARITY.
 ALL ABUTMENTS AND PIERS ARE PARALLEL.



DocuSigned by:
 Joel R. Rapp
 5068319228434...
 2/21/2018



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2- = POC STA. 12+06.49 -Y-
 MILE POST: NS 377.70
 SHEET 1 OF 4 BRIDGE NO. _____

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
 RALEIGH
GENERAL DRAWING
 BRIDGE ON STATION TRACK 2 OVER W 4TH STREET BETWEEN W TRADE STREET AND W MOREHEAD STREET

HNTB HNTB NORTH CAROLINA, P.C.
 NC License No. C-1554
 343 E. Six Forks Rd., Suite 200, Raleigh, NC, 27609
 DRAWN BY: B. VAUGHN DATE: 8/17
 CHECKED BY: R. RAPP DATE: 9/17 DWG. NO. 1

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S7-1
1			3			TOTAL SHEETS
2			4			51



FOUNDATION LAYOUT

FOUNDATION NOTES:

◀◻ INDICATES PILE TO BE BATTERED 3:12 OR 1:12 IN DIRECTION OF ARROW.

FOR PILES, SEE GEOTECHNICAL SPECIAL PROVISION.

PILES AT ABUTMENT NO. 1 ARE DESIGNED FOR AN ALLOWABLE BEARING CAPACITY OF 80 TONS PER PILE.

DRIVE PILES AT ABUTMENT NO. 1 TO A REQUIRED BEARING CAPACITY OF 160 TONS PER PILE.

PILES AT PIER NO. 1 ARE DESIGNED FOR AN ALLOWABLE BEARING CAPACITY OF 115 TONS PER PILE.

DRIVE PILES AT PIER NO. 1 TO A REQUIRED BEARING CAPACITY OF 230 TONS PER PILE.

PREDRILLING FOR THE 8 RIGHTMOST PILES AT PIER NO. 1 IS REQUIRED. PREDRILL PILE LOCATIONS TO AN ELEVATION NO LOWER THAN 695 FT WITH EQUIPMENT THAT WILL RESULT IN A MAXIMUM PREDRILLING DIAMETER OF 12". FOR PREDRILLING PILES, SEE GEOTECHNICAL SPECIAL PROVISION. RIGHT IS DEFINED LOOKING AHEAD STATION.

PILES AT PIER NO. 2 ARE DESIGNED FOR AN ALLOWABLE BEARING CAPACITY OF 140 TONS PER PILE.

DRIVE PILES AT PIER NO. 2 TO A REQUIRED BEARING CAPACITY OF 280 TONS PER PILE.

PILES AT ABUTMENT NO. 2 ARE DESIGNED FOR AN ALLOWABLE BEARING CAPACITY OF 100 TONS PER PILE.

DRIVE PILES AT ABUTMENT NO. 2 TO A REQUIRED BEARING CAPACITY OF 200 TONS PER PILE.

TESTING THE FIRST PRODUCTION PILE AT ABUTMENT NO. 1, PIER NO. 2, AND ABUTMENT NO. 2 WITH THE PDA DURING DRIVING, RESTRIKING OR REDRIVING IS REQUIRED AT THIS SITE. FOR PDA TESTING, SEE GEOTECHNICAL SPECIAL PROVISION.

IT HAS BEEN ESTIMATED THAT A HAMMER WITH AN EQUIVALENT RATED ENERGY IN THE RANGE OF 20,000 TO 40,000 FT-LBS PER BLOW WILL BE REQUIRED TO DRIVE PILES AT THIS SITE. THIS ESTIMATED ENERGY RANGE DOES NOT RELEASE THE CONTRACTOR FROM PROVIDING DRIVING EQUIPMENT IN ACCORDANCE WITH GEOTECHNICAL SPECIAL PROVISION.

ALL DIMENSIONS ARE PARALLEL OR NORMAL TO FILL FACE ABUTMENTS OR PIER CENTERS.

FOR FOUNDATION ELEVATIONS AND DETAILS, SEE "SUBSTRUCTURE: ABUTMENT" AND "SUBSTRUCTURE: PIER" SHEETS.

ALL PILES ARE STEEL HP 14x73.

ALL DIMENSIONS TO BATTERED PILES ARE AT BOTTOM OF CAP ELEVATION.


* CLEARANCE DIMENSIONS SHOWN TO THE EXISTING BRIDGE ARE BASED ON THE MINIMUM OF THE CLEARANCE TO THE EXISTING SUPERSTRUCTURE OR CLEARANCE TO THE EXISTING SUBSTRUCTURE.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 2 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING
 FOUNDATION LAYOUT
 AND
 FOUNDATION NOTES




DocuSigned by:
 55683197C2B434...
 2/21/2018

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C.
 NC License No. C-1554
 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 10/17
 CHECKED BY R. RAPP DATE 10/17 DWG. NO. 2


REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S7-2
1			3			TOTAL SHEETS
2			4			51



TOTAL BILL OF MATERIAL

	TEMP. RAILROAD SHORING/ABUT. 1 STA. 28+12.88 -S2-	TEMP. RAILROAD SHORING/PIER 1 STA. 28+12.88 -S2-	TEMP. RAILROAD SHORING/PIER 2 STA. 28+12.88 -S2-	TEMP. RAILROAD SHORING/ABUT. 2 STA. 28+12.88 -S2-	REMOVAL OF EXIST. STRUCT. AT STA. 28+12.88 -S2-	FOUND. EXCAV. FOR PIER 1 AT STA. 28+12.88 -S2-	FOUND. EXCAV. FOR PIER 2 AT STA. 28+12.88 -S2-	PREDRILLING FOR PILES	PDA TESTING	REINFORCED CONCRETE DECK SLAB	CLASS AA CONCRETE	REINFORCING STEEL	SPIRAL COLUMN REINFORCING STEEL	APPROX. 233,588 LBS. STRUCTURAL STEEL	PAINTING OF STRUCTURAL STEEL
	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	L.F.	EACH	SQ. FEET	CU. YARDS	LBS.	LBS.	LUMP SUM	LUMP SUM
SUPERSTRUCTURE	---	---	---	---	---	---	---	---	---	2,617.3	---	---	---	LUMP SUM	LUMP SUM
ABUTMENT 1	LUMP SUM	---	---	---	---	---	---	---	1	---	227.5	22,293	---	---	---
PIER 1	---	LUMP SUM	---	---	---	LUMP SUM	---	128	1	---	301.2	64,276	5,383	---	---
PIER 2	---	---	LUMP SUM	---	---	---	LUMP SUM	---	1	---	285.9	63,422	4,878	---	---
ABUTMENT 2	---	---	---	LUMP SUM	---	---	---	---	1	---	239.9	25,318	---	---	---
TOTAL	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM	128	4	2,617.3	1,054.5	175,309	10,261	LUMP SUM	LUMP SUM

	HP 14 x 73 STEEL PILES	PILE DRIVING EQUIPMENT SETUP FOR HP14x73 STEEL PILES	WATERPROOFING	METHOD B DAMPPROOFING	METAL RAIL (ALUMINUM)	METAL RAIL (STEEL) & FENCE	CONCRETE PARAPET	4" SLOPE PROTECTION	SELF-LUBRICATING EXPANSION BEARING ASSEMBLIES	STRUCTURE DRAINAGE SYSTEM AT STA. 28+12.88 -S2-	APPLICATION OF BRIDGE COATING	ASBESTOS ASSESSMENT	
	NO.	L.F.	EACH	SQ. YARDS	SQ. YARDS	L.F.	L.F.	L.F.	SQ. YARDS	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM
SUPERSTRUCTURE	---	---	---	270.7	---	---	116.3	231.4	---	LUMP SUM	LUMP SUM	LUMP SUM	---
ABUTMENT 1	40	2,133	40	64.2	203.0	20.5	5.6	---	175	---	LUMP SUM	LUMP SUM	---
PIER 1	26	1,083	26	26.9	37.0	---	---	---	---	---	LUMP SUM	---	---
PIER 2	20	733	20	53.0	90.1	---	---	---	---	---	LUMP SUM	---	---
ABUTMENT 2	30	1,200	30	71.3	227.2	16.5	8.3	---	258	---	LUMP SUM	LUMP SUM	---
TOTAL	116	5,149	116	486.1	557.3	37.0	130.2	231.4	433	LUMP SUM	LUMP SUM	LUMP SUM	LUMP SUM



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-

SHEET 3 OF 4

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
GENERAL DRAWING
LOCATION SKETCH AND
TOTAL BILL OF MATERIAL

HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609		DWG. NO. 3		REVISIONS		SHEET NO.	
NO.	BY	DATE	NO.	BY	DATE			ST-3	
1	JRR	05/02/2018	3					TOTAL SHEETS	
2			4					51	

GENERAL NOTES:

ASSUMED LIVE LOAD = AREMA E80 OR ALTERNATE LIVE LOAD

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

FOR EROSION CONTROL MEASURES, SEE EROSION CONTROL PLANS.

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE 2016 EDITION OF AREMA'S "MANUAL FOR RAILWAY ENGINEERING, VOL. 2, STRUCTURES", AND "NORFOLK SOUTHERN GUIDELINES FOR DESIGN OF GRADE SEPARATION STRUCTURES, UNDERPASS GRADE SEPARATION DESIGN CRITERIA".

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE 2016 EDITION OF AREMA'S "MANUAL FOR RAILWAY ENGINEERING VOL. 2, CHP. 9, SEISMIC DESIGN FOR RAILWAY".

REINFORCING STEEL SHALL BE ASTM DESIGNATION A615, GRADE 60. ALL DIMENSIONS RELATING TO BAR SPACING ARE TO BAR CENTERS UNLESS NOTED. FABRICATION TO BE IN ACCORDANCE WITH THE "MANUAL OF STANDARD PRACTICE", A.C.I. 315-80. ALL REINFORCING IN THE CONCRETE DECK SLAB AND PARAPETS SHALL BE EPOXY COATED.

EXPANSION JOINT MATERIAL SHALL BE EITHER RUBBER OR CORK CONFORMING WITH AASHTO SPECIFICATIONS M-153-84 EXCEPT AS SHOWN ON THE PLANS OR IN THE SPECIAL PROVISIONS. CELLULAR AND BULB TYPE WATERSTOPS AND RUBBER JOINT COMPOUNDS SHALL BE AS SHOWN ON THE PLANS AND IN THE SPECIAL PROVISIONS.

STRUCTURE DRAINAGE SYSTEM: METAL DRAINS BEHIND ABUTMENTS AND IN BALLAST THOUGH OF BRIDGE, INCLUDING DUCTILE IRON PIPE COLLECTOR SYSTEM SHALL BE AS SHOWN ON THE PLANS AND OUTLINED IN THE SPECIAL PROVISIONS. DETAILS OF THE DRAINAGE SYSTEM SHALL BE SUBMITTED TO THE CHIEF ENGINEER BRIDGES AND STRUCTURES, NORFOLK SOUTHERN CORPORATION, ATLANTA, GA. FOR APPROVAL.

DAMPPOOFING: PIER COLUMNS AND BENCH WALLS UP TO GROUND LINE, BACK OF BACKWALL AND ABUTMENT SEATS, AND BACK OF WINGWALLS SHALL BE DAMPPOOFED WITH METHOD "B" DAMPPOOFING.

WATERPROOFING: BRIDGE DECK AND ALL CONSTRUCTION JOINTS WHICH WILL BE COVERED BY FILL SHALL BE WATERPROOFED WITH A COLD LIQUID-APPLIED ELASTOMERIC MEMBRANE. FOR WATERPROOFING, SEE SPECIAL PROVISIONS.

WATERPROOFING IS REQUIRED AT THE FOLLOWING LOCATION:

1. BRIDGE DECK AND INSIDE OF CONCRETE PARAPET AS SHOWN ON "TYPICAL SECTION" SHEET.
2. ALONG FULL CIRCUMFERENCE/PERIMETER OF EACH BOTTOM OF COLUMN AND BENCH WALL TO TOP OF FOOTING INTERFACE. ALONG TOP AND SIDES OF FOOTING AT CONSTRUCTION JOINTS.
3. ALONG FILL FACE OF ALL HORIZONTAL AND VERTICAL CONSTRUCTION JOINTS AT EACH ABUTMENT.

WATERPROOFING SHALL BE 24" WIDE AND SHALL BE CENTERED OVER JOINTS OR CRACKS.

THE CONTRACTOR SHALL PROVIDE INDEPENDENT ASSURANCE SAMPLES OF REINFORCING STEEL AS FOLLOWS: FOR PROJECTS REQUIRING UP TO 400 TONS OF REINFORCING STEEL, ONE 30 INCH SAMPLE OF EACH SIZE BAR USED, AND FOR PROJECTS REQUIRING OVER 400 TONS OF REINFORCING STEEL, TWO 30 INCH SAMPLES OF EACH SIZE BAR USED. THE BARS FROM WHICH THE SAMPLES ARE TAKEN MUST THEN BE SPLICED WITH REPLACEMENT BARS OF THE SIZE AND LENGTH OF THE SAMPLE, PLUS A MINIMUM LAP SPLICE OF THIRTY BAR DIAMETERS. PAYMENT FOR THE SAMPLES OF REINFORCING STEEL SHALL BE CONSIDERED INCIDENTAL TO VARIOUS PAY ITEMS.

ALL MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH "STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES", JANUARY 2018, NORTH CAROLINA DEPARTMENT OF TRANSPORTATION (HEREIN CALLED STANDARD SPECIFICATIONS), EXCEPT AS NOTED HEREIN, ELSEWHERE ON PLANS, OR IN THE SPECIAL PROVISIONS (STRUCTURAL STEEL IN ACCORDANCE WITH THE 2016 AREMA SPECIFICATIONS).

ALL CONCRETE SHALL BE 4,500 PSI CLASS AA CONCRETE WITH NO. 57 OR 67 COARSE AGGREGATE AND SHALL BE AIR-ENTRAINED. MINIMUM CEMENT CONTENT PER CUBIC YARD OF CONCRETE SHALL BE 6.5 BAGS. NO SUBSTITUTION OF FLYASH, BLAST FURNACE SLAG OR OTHER MATERIAL WILL BE PERMITTED IN MEETING THIS MINIMUM CEMENT REQUIREMENT. CHAMFER ALL EXPOSED EDGES AND CORNERS 3/4" EXCEPT AS NOTED. THE USE OF GROUND GRANULATED BLAST FURNACE SLAG IS NOT PERMITTED IN THIS STRUCTURE.

CONTROL OF WORK: ALL WORK INVOLVED IN THE CONSTRUCTION OF THE RAILWAY STRUCTURE SHALL BE PERFORMED SATISFACTORY TO THE ENGINEER AND COMPLIANT WITH THE DESIGN STANDARDS OF NORFOLK SOUTHERN RAILWAY COMPANY. ALL METHODS OF HANDLING THE WORK AFFECTING THE SAFETY OF RAIL OPERATIONS MUST BE APPROVED BY THE RAILWAY COMPANY, AS A SUBMITTAL THROUGH THE ENGINEER, AT LEAST TWO WEEKS BEFORE PROCEEDING WITH THAT PORTION OF THE WORK. RAIL TRAFFIC SHALL, AT ALL TIMES, BE MAINTAINED AND PROTECTED. THE CONTRACTOR SHALL NOT AT ANY TIME DELAY OR INTERFERE WITH RAIL OPERATIONS.

NEEDLE BEAMS WILL NOT BE ALLOWED UNLESS OTHERWISE CALLED FOR ON THE PLANS OR APPROVED BY THE ENGINEER.

REMOVABLE FORMS MAY BE USED IN LIEU OF METAL STAY-IN-PLACE FORMS IN ACCORDANCE WITH ARTICLE 420-3 OF THE STANDARD SPECIFICATIONS.

FOR METAL RAIL (STEEL) AND FENCE, SEE SPECIAL PROVISIONS.

FOR METAL RAIL (ALUMINUM), SEE SPECIAL PROVISIONS.

FOR SELF-LUBRICATING EXPANSION BEARING ASSEMBLIES, SEE SPECIAL PROVISIONS.

FOR CONDUIT IN PARAPETS, SEE SPECIAL PROVISIONS.

FOR PORTLAND CEMENT, SEE SPECIAL PROVISIONS.

FOR FINE AND COARSE AGGREGATE, SEE SPECIAL PROVISIONS.

SEE "STRUCTURAL STEEL DETAILS" SHEET FOR STRUCTURAL STEEL NOTES.

FOR BACKFILL BEHIND ABUTMENTS AND OTHER BACKFILL AROUND THE STRUCTURE, SEE SPECIAL PROVISION "BACKFILLING AROUND STRUCTURES".

FOR PAINTING STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

FOR WATERSTOPS, SEE SPECIAL PROVISIONS.

FOR ELASTOMERIC FLASHING, SEE SPECIAL PROVISIONS.

FOR RUBBER JOINT COMPOUNDS, SEE SPECIAL PROVISIONS.

FOR STRUCTURE DRAINAGE SYSTEM, SEE SPECIAL PROVISIONS.

FOR STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

FOR RAILROAD TRACKWORK, SEE RAILROAD TRACKWORK PLANS.

FOR MAINTENANCE AND PROTECTION OF TRAFFIC BENEATH PROPOSED STRUCTURE, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR CONCRETE PARAPET, SEE SPECIAL PROVISIONS.

FOR WATERPROOFING, SEE SPECIAL PROVISIONS.

FOR PLACING LOAD ON STRUCTURE MEMBERS, SEE SPECIAL PROVISIONS.

FOR APPLICATION OF BRIDGE COATING, SEE SPECIAL PROVISIONS.

FOR TEMPORARY RAILROAD SHORING, SEE SPECIAL PROVISIONS.

FOR ASBESTOS ASSESSMENT FOR BRIDGE DEMOLITION AND RENOVATION ACTIVITIES, SEE SPECIAL PROVISIONS.

FOR EXPANSION JOINTS, SEE SPECIAL PROVISIONS.

FOR JOINT SEALANT, SEE SPECIAL PROVISIONS.


INDEX OF DRAWINGS

- 1 GENERAL DRAWING: GENERAL PLAN AND ELEVATION (SHEET 1 OF 4)
- 2 GENERAL DRAWING: FOUNDATION LAYOUT AND FOUNDATION NOTES (SHEET 2 OF 4)
- 3 GENERAL DRAWING: LOCATION SKETCH AND TOTAL BILL OF MATERIAL (SHEET 3 OF 4)
- 4 GENERAL DRAWING: GENERAL NOTES (SHEET 4 OF 4)
- 5 SUPERSTRUCTURE: TYPICAL SECTION
- 6 SUPERSTRUCTURE: DECK DETAILS
- 7 SUPERSTRUCTURE: PLAN OF DECK - SPAN A
- 8 SUPERSTRUCTURE: PLAN OF DECK - SPAN B
- 9 SUPERSTRUCTURE: PLAN OF DECK - SPAN C
- 10 SUPERSTRUCTURE: FRAMING PLAN AND GIRDER DETAILS - SPAN A AND SPAN C
- 11 SUPERSTRUCTURE: FRAMING PLAN AND GIRDER DETAILS - SPAN B
- 12 SUPERSTRUCTURE: STRUCTURAL STEEL DETAILS
- 13 SUPERSTRUCTURE: BEARING DETAILS - SPAN A AND SPAN C
- 14 SUPERSTRUCTURE: BEARING DETAILS - SPAN B
- 15 SUPERSTRUCTURE: EXPANSION PLATE DETAILS
- 16 SUPERSTRUCTURE: PARAPET DETAILS (SHEET 1 OF 2)
- 17 SUPERSTRUCTURE: PARAPET DETAILS (SHEET 2 OF 2)
- 18 SUPERSTRUCTURE: BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS (SHEET 1 OF 3)
- 19 SUPERSTRUCTURE: BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS (SHEET 2 OF 3)
- 20 SUPERSTRUCTURE: BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS (SHEET 3 OF 3)
- 21 SUPERSTRUCTURE: BILL OF MATERIAL
- 22 SUBSTRUCTURE: ABUTMENT 1 SHORING
- 23 SUBSTRUCTURE: ABUTMENT 1 (SHEET 1 OF 6)
- 24 SUBSTRUCTURE: ABUTMENT 1 (SHEET 2 OF 6)
- 25 SUBSTRUCTURE: ABUTMENT 1 (SHEET 3 OF 6)
- 26 SUBSTRUCTURE: ABUTMENT 1 (SHEET 4 OF 6)
- 27 SUBSTRUCTURE: ABUTMENT 1 (SHEET 5 OF 6)
- 28 SUBSTRUCTURE: ABUTMENT 1 (SHEET 6 OF 6)
- 29 SUBSTRUCTURE: PIER 1 SHORING
- 30 SUBSTRUCTURE: PIER 1 (SHEET 1 OF 4)
- 31 SUBSTRUCTURE: PIER 1 (SHEET 2 OF 4)
- 32 SUBSTRUCTURE: PIER 1 (SHEET 3 OF 4)
- 33 SUBSTRUCTURE: PIER 1 (SHEET 4 OF 4)
- 34 SUBSTRUCTURE: PIER 1 SHORING
- 35 SUBSTRUCTURE: PIER 2 (SHEET 1 OF 4)
- 36 SUBSTRUCTURE: PIER 2 (SHEET 2 OF 4)
- 37 SUBSTRUCTURE: PIER 2 (SHEET 3 OF 4)
- 38 SUBSTRUCTURE: PIER 2 (SHEET 4 OF 4)
- 39 SUBSTRUCTURE: ABUTMENT 2 SHORING
- 40 SUBSTRUCTURE: ABUTMENT 2 (SHEET 1 OF 6)
- 41 SUBSTRUCTURE: ABUTMENT 2 (SHEET 2 OF 6)
- 42 SUBSTRUCTURE: ABUTMENT 2 (SHEET 3 OF 6)
- 43 SUBSTRUCTURE: ABUTMENT 2 (SHEET 4 OF 6)
- 44 SUBSTRUCTURE: ABUTMENT 2 (SHEET 5 OF 6)
- 45 SUBSTRUCTURE: ABUTMENT 2 (SHEET 6 OF 6)
- 46 STRUCTURE: DRAINAGE DETAILS (SHEET 1 OF 4)
- 47 STRUCTURE: DRAINAGE DETAILS (SHEET 2 OF 4)
- 48 STRUCTURE: DRAINAGE DETAILS (SHEET 3 OF 4)
- 49 STRUCTURE: DRAINAGE DETAILS (SHEET 4 OF 4)
- 50 SLOPE PROTECTION SHEET (SHEET 1 OF 2)
- 51 SLOPE PROTECTION SHEET (SHEET 2 OF 2)

FOR TRACK 1 SUPERSTRUCTURE SHEETS, REFER TO "BRIDGE ON STATION TRACK 1 OVER W 4TH STREET" PLANS.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-

SHEET 4 OF 4



DocuSigned by:
 [Signature]
 55683187C228434...
 2/21/2018


DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
 RALEIGH

GENERAL DRAWING

GENERAL NOTES

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS					SHEET NO. S7-4	
	NO.	BY	DATE	NO.	BY		DATE
	1		8/17	3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u>	DWG. NO. 4					TOTAL SHEETS 51	



TYPICAL SECTION
(ALL SPANS SIMILAR)

NOTES FOR SIGNAL CONDUIT IN PARAPET

SIGNAL CONDUIT TO BE 4" DIA. IN ACCORDANCE WITH UNDERWRITER'S LABORATORY SPECIFICATIONS.

PROVISIONS SHALL BE MADE FOR EXPANSION BETWEEN DECK SLABS AT EXPANSION JOINTS AT PIERS 1 & 2 (GALVANIZED EXPANSION FITTINGS).

COUPLING SHALL BE PROVIDED BEHIND BACKWALL OF ABUTMENT 1 AND 2 FOR CONNECTION TO 4" DIA. RIGID PIPE (RIGID PIPE BY RAILWAY COMPANY).

FOR SIGNAL CONDUIT IN PARAPET SEE PROJECT SPECIAL PROVISIONS.

NOTES:


ALL REINFORCING STEEL IN THE DECK AND PARAPETS SHALL BE EPOXY COATED. CLEAR COVER TO ALL REINFORCING IS 2" MINIMUM UNLESS NOTED OTHERWISE.

FOR BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS, SEE "BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS" SHEETS.

FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.


DESIGN INCLUDES WEIGHT OF 6" ADDITIONAL BALLAST TO ACCOUNT FOR FUTURE RESURFACING OF TRACK.

* MINIMUM GAP REMAINING AFTER CONSIDERING ALL PLATFORM DEFLECTIONS.



DETAIL "A"

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	
DRAWN BY: J. JEFFERS	DATE: 8/17	DWG. NO. 5	
CHECKED BY: R. RAPP	DATE: 9/17		

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE

TYPICAL SECTION


REVISIONS					SHEET NO. ST-5
NO.	BY	DATE	NO.	DATE	
1			3		TOTAL SHEETS 51
2			4		




NOTES:
JOINT SHALL BE TESTED FOR LEAKS AND MADE WATERTIGHT BEFORE FLASHING AND EXP. PLATE COVER ARE INSTALLED.

FOR EXPANSION PLATE DETAILS, SEE "EXPANSION PLATE DETAILS" SHEET.


** NOT APPLICABLE AT ABUTMENT



NOTE: FOR ADDITIONAL PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.



PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


HNTB HNTB NORTH CAROLINA, P.C.
 NC License No. C-1554
 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
 CHECKED BY R. RAPP DATE 9/17 DWG. NO. 6


STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUPERSTRUCTURE					
DECK DETAILS					
REVISIONS					SHEET NO.
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		
					TOTAL SHEETS 51



PLAN - SPAN A




DETAIL A



DETAIL B

NOTES:
 ALL REINFORCING SHALL BE EPOXY COATED.
 FOR SECTIONS A-A & B-B SEE "DECK DETAILS" SHEET.
 FOR DECK DRAIN DETAIL SEE DETAIL "B" ON "STRUCTURE DRAINAGE DETAILS", SHEET 2 OF 4.
 FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.
 SLAB BARS MAY BE ADJUSTED TO AVOID DECK DRAIN LOCATIONS.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


HNTB HNTB NORTH CAROLINA, P.C.
 NC License No. C-1554
 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
 CHECKED BY K. ERVIN DATE 9/17 DWG. NO. 7


REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	ST-7
1			3			TOTAL SHEETS
2			4			51



PLAN - SPAN B




DETAIL A



DETAIL B

- NOTES:**
- ALL REINFORCING SHALL BE EPOXY COATED.
 - FOR SECTION B-B SEE "DECK DETAILS" SHEET.
 - FOR DECK DRAIN DETAIL SEE DETAIL "B" ON "STRUCTURE: DRAINAGE DETAILS", SHEET 2 OF 4.
 - FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.
 - SLAB BARS MAY BE ADJUSTED TO AVOID DECK DRAIN LOCATIONS.


PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 PLAN OF DECK - SPAN B


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-8 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1			3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>9/17</u> DWG. NO. 8							



PLAN - SPAN C



DETAIL A




DETAIL B

NOTES:

- ALL REINFORCING SHALL BE EPOXY COATED.
- FOR SECTIONS A-A & B-B SEE "DECK DETAILS" SHEET.
- FOR DECK DRAIN DETAIL SEE DETAIL "B" ON "STRUCTURE: DRAINAGE DETAILS", SHEET 2 OF 4.
- FOR PARAPET DETAILS, SEE "PARAPET DETAILS" SHEETS.
- SLAB BARS MAY BE ADJUSTED TO AVOID DECK DRAIN LOCATIONS.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-




DocuSigned by:
 [Signature]
 2/21/2018

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUPERSTRUCTURE
 PLAN OF DECK - SPAN C

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS					SHEET NO. S7-9	
	NO.	BY	DATE	NO.	BY		DATE
	1	B. VAUGHN	8/17	3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>9/17</u> DWG. NO. 9	2			4		TOTAL SHEETS 51	



SPAN A
FRAMING PLAN




SPAN C
FRAMING PLAN

NOTES:
 ALL DIMENSIONS ON THIS DRAWING ARE HORIZONTAL.
 ALL ABUTMENT FILL FACES, C PIER, AND C BEARINGS ARE PARALLEL.
 NO SHOP CAMBER REQUIRED, TURN NATURAL MILL CAMBER UP.
 REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR:


- STRUCTURAL STEEL NOTES
- DIAPHRAGM DETAILS
- STIFFENER AND CONNECTOR P DETAILS
- SHEAR CONNECTOR DETAILS
- FLANGE TO WEB WELD DETAILS

FOR BEARINGS, SEE "BEARING DETAILS SPAN A AND SPAN C" SHEET.
 FOR DRAIN PIPE SUPPORT DETAILS, SEE "STRUCTURE DRAINAGE DETAILS" SHEETS.
 FLANGE AND WELD SHOP SPLICES SHALL BE MADE WITH FULL PENETRATION GROOVE WELDS. SEE DETAILS ON "STRUCTURAL STEEL DETAILS" SHEET. FABRICATOR IS TO SHOW WELD CONFIGURATION AND JOINT PREPARATION ON SHOP DRAWINGS FOR APPROVAL.
 FLANGE AND WEB SHOP SPLICES SHALL BE STAGGERED LONGITUDINALLY A MINIMUM OF 2'-0". SEE "STRUCTURAL STEEL DETAILS" SHEET FOR DETAILS.
 FC = "FRACTURE CRITICAL"
 INT = NON-FRACTURE CRITICAL MEMBERS OR COMPONENTS REQUIRING IMPROVED NOTCH TOUGHNESS.




SPAN A
TYPICAL GIRDER ELEVATION
(INTERIOR GIRDER SHOWN, EXTERIOR GIRDER SIMILAR)

SPAN A GIRDER DIMENSIONS		
GIRDER	DIM. "A"	DIM. "B"
AG1-2	8'-9 5/16"	10'-11 5/16"
AG2-2	9'-1 1/8"	9'-10 3/4"
AG3-2	9'-4 9/16"	9'-7 9/16"
AG4-2	9'-7 9/16"	9'-4 9/16"
AG5-2	9'-10 3/4"	9'-1 1/8"
AG6-2	10'-1 5/16"	8'-9 9/16"




SPAN C
TYPICAL GIRDER ELEVATION
(INTERIOR GIRDER SHOWN, EXTERIOR GIRDER SIMILAR)


SPAN C GIRDER DIMENSIONS		
GIRDER	DIM. "A"	DIM. "B"
CG1-2	7'-11 1/16"	9'-3 7/16"
CG2-2	8'-2 5/8"	9'-0 1/4"
CG3-2	8'-5 3/16"	8'-9 1/16"
CG4-2	8'-9 1/16"	8'-5 3/16"
CG5-2	9'-0 1/4"	8'-2 5/8"
CG6-2	9'-3 7/16"	7'-11 1/16"




DETAIL "A"
(RIGHT SIDE OF WEB SHOWN, LEFT SIDE SIMILAR)




@ ABUTMENT 1
BOTTOM FLANGE GIRDER END DETAILS - SPAN A



@ PIER 1



@ PIER 2




@ ABUTMENT 2

NOTE: BEARING STIFFENERS ARE ORIENTED PERPENDICULAR TO THE WEB.

NOTE: BEARING STIFFENERS ARE ORIENTED PERPENDICULAR TO THE WEB.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




DocuSigned by:
 55683197C22B434...
 2/21/2018

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 FRAMING PLAN
 AND GIRDER DETAILS
 SPAN A AND SPAN C

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-10 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1			3			
2			4				

DRAWN BY B. VAUGHN DATE 8/17
 CHECKED BY R. RAPP DATE 9/17
 DWG. NO. 10



SPAN B GIRDER DIMENSIONS		
GIRDER	DIM. "A"	DIM. "B"
BG1-2	8'-6 5/16"	9'-11"
BG2-2	8'-10 3/16"	9'-7 3/4"
BG3-2	9'-1 3/8"	9'-4 9/16"
BG4-2	9'-4 9/16"	9'-1 3/8"
BG5-2	9'-7 3/4"	8'-10 3/16"
BG6-2	9'-11"	8'-6 5/16"

NOTES:

ALL DIMENSIONS ON THIS DRAWING ARE HORIZONTAL.

ALL CL PIERS AND CL BEARINGS ARE PARALLEL.

NO SHOP CAMBER REQUIRED, TURN NATURAL MILL CAMBER UP.

REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR:

- STRUCTURAL STEEL NOTES
- DIAPHRAGM DETAILS
- STIFFENER AND CONNECTOR P DETAILS
- SHEAR CONNECTOR DETAILS
- FLANGE TO WEB WELD DETAILS

FOR BEARINGS, SEE "BEARING DETAILS SPAN B" SHEET.




FOR DRAIN PIPE SUPPORT DETAILS, SEE "STRUCTURE DRAINAGE DETAILS" SHEETS.

FLANGE AND WELD SHOP SPLICES SHALL BE MADE WITH FULL PENETRATION GROOVE WELDS. SEE DETAILS ON "STRUCTURAL STEEL DETAILS" SHEET. FABRICATOR IS TO SHOW WELD CONFIGURATION AND JOINT PREPARATION ON SHOP DRAWINGS FOR APPROVAL.


FLANGE AND WEB SHOP SPLICES SHALL BE STAGGERED LONGITUDINALLY A MINIMUM OF 2'-0". SEE "STRUCTURAL STEEL DETAILS" SHEET FOR DETAILS.

FC = "FRACTURE CRITICAL"

INT = NON-FRACTURE CRITICAL MEMBERS OR COMPONENTS REQUIRING IMPROVED NOTCH TOUGHNESS.




PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-11 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1			3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u> DWG. NO. <u>11</u>							




SECTION @ END DIAPHRAGM (D1, D4, D5, & D6)




SECTION @ INTERMEDIATE DIAPHRAGM (D2 & D3)




SHEAR CONNECTOR DETAILS




FLANGE TO WEB WELD DETAIL




DETAIL "A"



STIFFENER/CONN. P. DETAILS



WELD TERMINATION DETAILS



NOTES:
ELECTROSLAG WELDING IS NOT PERMITTED.
ULTRASONIC OR RADIOGRAPHIC INSPECTION IS REQUIRED FOR ALL FLANGE AND WEB SPLICE WELDS. SEE SPECIAL PROVISIONS.
GRIND WELDS IN DIRECTION OF STRESS ONLY (I.E. PARALLEL TO G GIRDER).

SHOP SPLICE DETAILS

STRUCTURAL STEEL NOTES

STRUCTURAL STEEL SHALL CONFORM TO THE FOLLOWING ASTM SPECIFICATIONS:

- GIRDER FLANGES AND WEB: A709, GRADE 50.
- MISCELLANEOUS MATERIAL: A709, GRADE 50.
- ANCHOR BOLTS FOR BEARING DEVICES SHALL CONFORM TO ASTM F1554, GRADE 105. ANCHOR BOLTS, NUTS, AND PLATE WASHERS SHALL BE HOT-DIPPED GALVANIZED IN ACCORDANCE WITH ASTM F2329.

STRUCTURAL STEEL ELEMENTS DENOTED AS "FC" ARE FRACTURE CRITICAL AND SHALL MEET IMPACT TEST REQUIREMENTS SET FORTH IN THE FRACTURE CONTROL PLAN OF THE AREMA MANUAL, CHAPTER 15, SECTION 1.14. NOTCH TOUGHNESS REQUIREMENTS AND TESTING SHALL BE BASED ON ZONE 2 REQUIREMENTS.

STRUCTURAL STEEL ELEMENTS DENOTED AS "INT" SHALL MEET IMPACT TEST REQUIREMENTS SET FORTH IN THE FRACTURE CONTROL PLAN OF THE AREMA MANUAL, CHAPTER 15, SECTION 1.2. TESTING SHALL BE BASED ON ZONE 2 REQUIREMENTS.

ALL DIMENSIONS SHOWN ARE HORIZONTAL OR VERTICAL UNLESS OTHERWISE NOTED. ALL DIMENSIONS ARE SHOWN AT 60°F.

NC DOT RAILS DIVISION SHALL BE FURNISHED COPIES OF MILL TEST REPORTS FOR ALL MATERIALS EXCEPT MISCELLANEOUS PLATES AND SHAPES. REPORTS SHALL INDICATE COMPLIANCE WITH ALL SPECIFIED REQUIREMENTS.

SHOP INSPECTION SHALL BE BY NORFOLK SOUTHERN CORPORATION OR ITS AUTHORIZED AGENT. SEE STRUCTURAL STEEL SPECIAL PROVISION FOR ADDITIONAL WELDING INSPECTION OF FLANGE PLATE TO WEB PLATE WELDS.

FOR PAINTING STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

BOLTED CONNECTIONS SHALL BE MADE WITH 7/8" Ø ASTM A325, TYPE 1 HIGH STRENGTH BOLTS WITH HEAVY HEX HEAD, HEAVY HEX NUT AND HARDENED WASHERS IN ACCORDANCE WITH A.R.E.M.A. SPECIFICATIONS USING THE TURN OF THE NUT METHOD. DIRECT TENSION INDICATORS SHALL NOT BE USED.

SHOP DRAWINGS SHALL BE APPROVED BY THE CHIEF ENGINEER - BRIDGES AND STRUCTURES, NORFOLK SOUTHERN CORPORATION, ATLANTA, GA. SHOP DRAWINGS SHALL BE LABELED "NORFOLK SOUTHERN MP 377.70".

BOLT HOLES IN STRUCTURAL STEEL MEMBERS SHALL BE STANDARD SIZE UNLESS OTHERWISE INDICATED ON THE PLANS.

HIGH STRENGTH BOLTS, NUTS & WASHERS SHALL BE MECHANICALLY GALVANIZED IN ACCORDANCE WITH ASTM B695.

ANCHOR BOLTS SHALL BE 1/4" Ø IN ACCORDANCE WITH A.R.E.M.A. SPECIFICATIONS AND SHALL BE GROUTED IN FORMED HOLES AFTER GIRDERS ARE ERECTED.

BEARING PADS SHALL BE USED WHENEVER STEEL MASONRY PLATE, OR OTHER STEEL BEARING PLATE, BEARS ON CONCRETE. PADS SHALL BE PREFORMED FABRIC BEARING PADS, 1/2" THICK. FOR PAD REQUIREMENTS, SEE STRUCTURAL STEEL SPECIAL PROVISIONS.

SHEAR CONNECTORS ON GIRDERS MAY BE SHIFTED AS NECESSARY TO CLEAR FLANGE SPLICE WELDS.

WEB SHOP SPLICES ARE PERMITTED TO LIMIT THE MAXIMUM REQUIRED WEB PIECE LENGTHS TO 45'-0". PERMITTED WEB SHOP SPLICES SHALL NOT BE LOCATED WITHIN 15'-0" OF MAXIMUM DEAD LOAD DEFLECTION AND SHALL BE LOCATED 6" MIN. FROM CONNECTOR PLATE OR INTERMEDIATE STIFFENER WELDS. FLANGE AND WEB SHOP SPLICES SHALL CONFORM TO SHOP SPLICE DETAILS SHOWN ON THE PLANS.


ALL WELDING CONNECTIONS SHALL BE MADE WITH SERIES E70 WELDING ELECTRODES.

FOR DIAPHRAGM LOCATIONS, SEE FRAMING PLANS.

FOR DETAILS OF DIAPHRAGM SUPPORT ANGLES (DSA), SEE "STRUCTURE DRAINAGE DETAILS" SHEET 2 OF 4.

STIFFENER/CONN. P. SCHEDULE		
TYPE	SPANS A & C	SPAN B
BRG. STIFF.	P 1/2" x 5"	P 1" x 9 1/2"
DIAPH. CONN. P.	P 1/2" x 5 1/2"	P 1/2" x 6"
INT. STIFF.	P 1/2" x 5 1/2"	P 1/2" x 6"

NOTE: SEE FRAMING PLANS FOR STIFFENER/CONN. P. LOCATIONS



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY: B. VAUGHN DATE: 8/17
CHECKED BY: K. ERVIN DATE: 9/17



DWG. NO. 12

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-




STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE
STRUCTURAL STEEL DETAILS

REVISIONS						SHEET NO. S7-12
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS
2			4			51



BRONZE PLATE TO BE ASTM B22 - COPPER ALLOY 911 OR ASTM B100 - COPPER ALLOY 510. TOP SURFACE TO BE SELF LUBRICATING.



NOTES:

ANCHOR BOLTS, SLIDING PLATE (EXPANSION BEARING) AND MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL BE HOT DIPPED GALVANIZED.

ALL PLATE SURFACES SHALL BE PAINTED WITH A 3 COAT PAINT SYSTEM EXCEPT AS SPECIFIED BELOW.

(A) THE SLIDING PLATE (EXPANSION BEARING) SHALL NOT BE PAINTED BUT SHALL RECEIVE A COAT OF LUBRICATION.

(B) THE MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL NOT BE PAINTED.

(C) THE BOTTOM SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED BUT SHALL RECEIVE A SINGLE COAT OF PRIMER APPLIED IN THE SHOP.


(D) THE TOP SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED IN THE VICINITY OF THE WELD BETWEEN THE SOLE PLATE AND THE BOTTOM FLANGE.

FOR ACRYLIC PAINT SYSTEM FOR STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.

FOR SELF LUBRICATING EXPANSION BEARING ASSEMBLIES, SEE SPECIAL PROVISIONS.

REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR ADDITIONAL NOTES.

GIRDER	BEARING PLATE SCHEDULE									
	DIMENSIONS									
	FIXED BEARING (FBA-1)					EXPANSION BEARING (EBA-1)				
	"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"	"J"	"K"
AG1-2	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG2-2	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG3-2	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG4-2	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG5-2	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
AG6-2	1 1/2"	2"	4"	6 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	9 1/2"	2" x 3"
CG1-2	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"
CG2-2	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"
CG3-2	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"
CG4-2	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"
CG5-2	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"
CG6-2	1 1/2"	1 3/4"	3 3/4"	6 1/2"	1 1/2"	1 1/2"	2 3/4"	6 3/4"	9 1/2"	2" x 3"




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
SUPERSTRUCTURE
BEARING DETAILS
SPAN A AND SPAN C

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-13 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1			3			
2			4				

DRAWN BY B. VAUGHN DATE 8/17
CHECKED BY R. RAPP DATE 9/17 DWG. NO. 13




FIXED BEARINGS




EXPANSION BEARINGS

BRONZE PLATE TO BE ASTM B22 - COPPER ALLOY 911 OR ASTM B100 - COPPER ALLOY 510. TOP SURFACE TO BE SELF LUBRICATING.



FIXED BEARING ASSEMBLY (FBA-2)
(6 REQ'D)



ANCHOR BOLT DETAIL

NOTES:

ANCHOR BOLTS, SLIDING PLATE (EXPANSION BEARING) AND MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL BE HOT DIPPED GALVANIZED.

ALL PLATE SURFACES SHALL BE PAINTED WITH A 3 COAT PAINT SYSTEM EXCEPT AS SPECIFIED BELOW.

(A) THE SLIDING PLATE (EXPANSION BEARING) SHALL NOT BE PAINTED BUT SHALL RECEIVE A COAT OF LUBRICATION.

(B) THE MASONRY PLATE (FIXED AND EXPANSION BEARINGS) SHALL NOT BE PAINTED.


(C) THE BOTTOM SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED BUT SHALL RECEIVE A SINGLE COAT OF PRIMER APPLIED IN THE SHOP.

(D) THE TOP SURFACE OF THE SOLE PLATE SHALL NOT BE PAINTED IN THE VICINITY OF THE WELD BETWEEN THE SOLE PLATE AND THE BOTTOM FLANGE.

FOR ACRYLIC PAINT SYSTEM FOR STRUCTURAL STEEL, SEE SPECIAL PROVISIONS.


FOR SELF LUBRICATING EXPANSION BEARING ASSEMBLIES, SEE SPECIAL PROVISIONS.

REFER TO "STRUCTURAL STEEL DETAILS" SHEET FOR ADDITIONAL NOTES.



EXPANSION BEARING ASSEMBLY (EBA-2)
(6 REQ'D)

GIRDER	BEARING PLATE SCHEDULE									
	DIMENSIONS									
	FIXED BEARING (FBA-2)					EXPANSION BEARING (EBA-2)				
	"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"	"J"	"K"
BG1-2	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG2-2	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG3-2	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG4-2	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG5-2	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"
BG6-2	1 1/2"	2 3/4"	4 3/4"	8 1/2"	1 1/2"	1 1/2"	1 3/4"	5 3/4"	8 1/2"	2" x 4"



DocuSigned by:
Joel R. Rapp
2/21/2018


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH
SUPERSTRUCTURE
BEARING DETAILS
SPAN B

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS					SHEET NO. S7-14 TOTAL SHEETS 51	
	NO.	BY	DATE	NO.	BY		DATE
	1	B. VAUGHN	8/17	3			
2	R. RAPP	9/17	4				


DRAWN BY B. VAUGHN DATE 8/17 DWG. NO. 14
CHECKED BY R. RAPP DATE 9/17



DETAIL A




SECTION A-A



SECTION B-B

DETAIL OF EXPANSION ANCHOR AND PLATE

SEE DETAIL A ON "DECK DETAILS" SHEET FOR ADDITIONAL JOINT INFORMATION.




PLAN - EXPANSION PLATE
(4 REQUIRED)

NOTE: PAYMENT FOR THE EXPANSION PLATE AND EXPANSION ANCHORS IS INCLUDED IN THE COST FOR STRUCTURE STEEL.

PLATE SHALL BE ANCHORED AT BACKWALL OF ABUTMENT 1 & 2, SPAN B SIDE OF PIER 1, AND SPAN B SIDE OF PIER 2.

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-



DocuSigned by:
Joel R. Rapp
55683197C22B434...
2/21/2018

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE
EXPANSION PLATE DETAILS

HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
CHECKED BY R. RAPP DATE 9/17 DWG. NO. 15

REVISIONS						SHEET NO. S7-15	TOTAL SHEETS 51
NO.	BY	DATE	NO.	BY	DATE		
1			3				
2			4				



PLAN - SPAN A PARAPETS

NOTES:

BRIDGE MOUNTED FENCE AND HANDRAIL NOT SHOWN FOR CLARITY.

ALL HORIZONTAL DIMENSIONS SHOWN ARE MEASURED ALONG EXTERIOR FACE OF PARAPET.

ALL REINFORCING SHALL BE EPOXY COATED.

FOR LOCATION AND DETAILS OF SIGNAL CONDUIT IN CONCRETE PARAPET, SEE "TYPICAL SECTION" SHEET.

FOR BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS, SEE "BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS" SHEETS.


VERTICAL GROOVED CONTRACTION JOINTS, 1/2" IN DEPTH, SHALL BE TOOLED IN ALL EXPOSED FACES OF PARAPET AND IN ACCORDANCE WITH THE SPECIAL PROVISION FOR "CONCRETE PARAPET", THE CONTRACTION JOINT SHALL BE LOCATED AT EACH THIRD POINT BETWEEN PARAPET EXPANSION JOINTS.

#5S1 AND #5S2 BARS IN PARAPET MAY BE SHIFTED SLIGHTLY TO MAINTAIN PROPER CLEARANCE TO EXPANSION JOINTS IN PARAPET.


E.F. = EACH FACE

PAYMENT FOR CONCRETE PARAPET SHALL BE INCLUDED IN THE UNIT COST PAY ITEM FOR CONCRETE PARAPET.


PAY LENGTH = 231.4'




SECTION THRU OPEN JOINT IN PARAPET



SECTION A-A THRU PARAPET



SECTION B-B THRU PARAPET



DocuSigned by:
Joel R. Rapp
59883197C2B434
2/21/2018

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-


SHEET 1 OF 2

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE
PARAPET DETAILS

HNTB	HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609
DRAWN BY <u>B. VAUGHN</u>	DATE <u>8/17</u>
CHECKED BY <u>R. RAPP</u>	DATE <u>9/17</u>
DWG. NO. 16	

REVISIONS						SHEET NO. S7-16
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 51
2			4			



NOTE:
SEE SHEET 1 OF 2 FOR NOTES
AND SECTIONS.

PLAN - SPAN B & SPAN C PARAPETS


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-

SHEET 2 OF 2

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUPERSTRUCTURE

PARAPET DETAILS




DocuSigned by:
Joel R. Rapp
55683197C228434
2/21/2018

DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
CHECKED BY R. RAPP DATE 9/17 DWG. NO. 17

REVISIONS						SHEET NO. S7-17
NO.	BY	DATE	NO.	BY	DATE	
1			3			TOTAL SHEETS 51
2			4			



LEGEND:

- - END POST (ALUMINUM HANDRAIL)
- - INTERIOR POST (FENCE AND STEEL HANDRAIL)
- - INTERIOR POST (ALUMINUM HANDRAIL)


NOTES:

SEE SHEET 2 OF 3 FOR FENCE AND STEEL HANDRAIL DETAILS AND NOTES.
SEE SHEET 3 OF 3 FOR ALUMINUM HANDRAIL DETAILS AND NOTES.

* FOR TRACK -S1- BRIDGE WORKLINE AND WORKPOINT DEFINITIONS, REFER TO "BRIDGE ON STATION TRACK 1 OVER W 4TH STREET" PLANS.


ALUMINUM HANDRAIL POST SPACING - BACKWALL/WINGWALL

(ALL DIMENSIONS SHOWN ARE ALONG EXTERIOR FACE OF BACKWALL/WINGWALL UNO)




FENCE AND STEEL HANDRAIL POST SPACING - BRIDGE & WINGWALLS


(ALL DIMENSIONS SHOWN ARE ALONG EXTERIOR FACE OF PARAPET/WINGWALL)



DETAILS FOR CHAIN LINK FENCE
(HANDRAIL NOT SHOWN FOR CLARITY)



TOP RAIL SLEEVE DETAIL



DocuSigned by:
55683197C2B434
2/21/2018

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-

SHEET 1 OF 3

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH



SUPERSTRUCTURE

BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS



HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY B. VAUGHN DATE 8/17
CHECKED BY R. RAPP DATE 9/17 DWG. NO. 18

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			51
2			4			



DETAILS FOR PIPE RAILING



HANDRAIL EXPANSION JOINT DETAIL

BASE PLATE DETAIL

NOTES:

- SEE "FENCE AND STEEL HANDRAIL POST SPACING - BRIDGE AND WINGWALLS" DETAIL ON SHEET 1 OF 3 FOR POST SPACING AND LOCATION OF EXPANSION JOINTS IN HANDRAIL.
- ALL HANDRAIL PIPE, SLEEVES, AND EXPANSION JOINTS TO BE SMOOTH AND FREE OF SHARP EDGES.
- FENCE POSTS, RAIL, AND HANDRAIL PIPE SHALL BE SCHEDULE 40 STEEL PIPE IN ACCORDANCE WITH ASTM F1043.
- PROVISIONS SHALL BE MADE FOR THE DRAINAGE OF WATER FROM INSIDE THE FENCE POSTS.
- CHAIN LINK FABRIC AND FITTINGS SHALL MEET THE REQUIREMENTS OF ASTM F668 AND HAVE A BONDED BLACK FUSION VINYL COATING.
- MISCELLANEOUS METAL COMPONENTS SHALL MEET THE REQUIREMENTS OF ASTM A36.
- STAINLESS STEEL BOLTS, NUTS, AND ANCHOR RODS TO BE ASTM A276, TYPE 304. STAINLESS STEEL WASHERS TO BE ASTM A276, TYPE 302. ANCHOR ROD THREADS SHALL BE ROLLED, NOT CUT.
- POST TO BE SET PERPENDICULAR TO TOP OF PARAPET/WINGWALL AND RAILS SHALL BE PLACED PARALLEL TO THE GRADE OF THE BRIDGE.
- CERTIFIED MILL REPORTS ARE REQUIRED FOR POST, RAIL, AND FENCE FABRIC. SHOP INSPECTION IS NOT REQUIRED.
- AFTER ANCHOR BOLT AND OTHER BOLT NUTS HAVE BEEN TIGHTENED, THREADS SHALL BE NICKED TO LOCK NUTS.
- THE BRACE BANDS USED TO SECURE HANDRAIL SLEEVE SHALL BE OF SUCH SIZE NECESSARY TO CLAMP TIGHTLY TO FENCE POST.
- WELDING SHALL BE IN ACCORDANCE WITH THE CURRENT AWS BRIDGE WELDING CODE.
- ANCHOR PLATE SHALL BE STEEL CONFORMING TO ASTM SPECIFICATION A36.
- UPPER ANCHOR ROD NUTS SHALL BE HEAVY HEX NUTS, PER ASTM A276 TYPE 302 OR 304 STAINLESS STEEL.
- LOWER ANCHOR ROD NUTS SHALL BE HEAVY HEX NUTS, PER ASTM A307.
- FENCE FRAMEWORK INCLUDING BASE PLATES, HANDRAIL, HANDRAIL SLEEVES, AND ALL SUPPORT COMPONENTS TO HAVE A FUSION BONDED BLACK VINYL COATING IN ACCORDANCE WITH THE REQUIREMENTS OF ASTM F1043.
- SHOP DRAWINGS FOR FENCE AND HANDRAIL ARE REQUIRED AND SHALL BE SUBMITTED FOR APPROVAL.
- PAY LENGTH = 130.2'


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 2 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH




SUPERSTRUCTURE

BRIDGE MOUNTED FENCE
 AND HANDRAIL DETAILS





DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-19 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1		8/17	3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>R. RAPP</u> DATE <u>9/17</u> DWG. NO. 19							



ALUMINUM HANDRAIL AND POST



NOTES:

SEE "ALUMINUM HANDRAIL POST SPACING - BACKWALL/WINGWALL" DETAIL ON SHEET 1 OF 3 FOR POST SPACING AND LOCATION OF EXPANSION JOINTS IN HANDRAIL.

ALUMINUM PIPE TO BE ASTM B429, ALLOY 6061-T6 AND BASE PLATE TO BE ASTM B209, ALLOY 6061-T6.

STAINLESS STEEL BOLTS, CAP SCREWS, AND NUTS TO BE ASTM A276 TYPE 304. STAINLESS STEEL WASHERS TO BE ASTM A276 TYPE 302.

POSTS TO BE SET PERPENDICULAR TO TOP OF BACKWALL/WINGWALL AND RAILS SHALL BE PLACED PARALLEL TO THE GRADE OF THE BRIDGE.

CERTIFIED MILL REPORTS ARE REQUIRED FOR RAIL AND POSTS. SHOP INSPECTIONS ARE NOT REQUIRED BY THE RAILROAD BUT MAY BE REQUIRED BY NCDOT.

AFTER ANCHOR ROD NUTS HAVE BEEN TIGHTENED, THREADS SHALL BE NICKED TO LOCK NUTS.

ANCHOR PLATES SHALL BE STEEL CONFORMING TO ASTM SPECIFICATION A36.

ANCHOR RODS SHALL CONFORM TO ASTM SPECIFICATION A276 TYPE 302 OR 304 STAINLESS STEEL AND THREADS SHALL BE ROLLED, NOT CUT.

UPPER ANCHOR ROD NUTS SHALL BE HEAVY HEX NUTS, PER ASTM A276 TYPE 302 OR 304 STAINLESS STEEL.

LOWER ANCHOR ROD NUTS SHALL BE HEAVY STEEL HEX NUTS, PER ASTM A563.

THE CENTERLINE OF ANY SPLICE AND/OR EXPANSION JOINT IS TO BE LOCATED AT LEAST 2'-0" AWAY FROM CENTERLINE OF POST. EXPANSION AND/OR SPLICE JOINTS FOR EACH RAIL OF TWO RAILINGS ARE TO BE PLACED IN THE SAME LOCATION AND IN THE SAME PANEL.

WELDING SHALL BE IN ACCORDANCE WITH THE CURRENT AWS STRUCTURAL WELDING CODE FOR ALUMINUM.

THE LENGTH OF METAL RAIL TO BE PAID FOR SHALL BE THE CONTINUOUS LENGTH MEASURED FROM END TO END OF RAIL, ALONG THE TOP RAIL.

SHOP DRAWINGS FOR RAILINGS ARE REQUIRED AND SHALL BE SUBMITTED FOR APPROVAL.

FOR METAL RAIL (ALUMINUM), SEE SPECIAL PROVISIONS.

PAY LENGTH = 37.0'


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 3 OF 3

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUPERSTRUCTURE

BRIDGE MOUNTED FENCE
 AND HANDRAIL DETAILS




DocuSigned by:
 2/21/2018

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS					SHEET NO. S7-20 TOTAL SHEETS 51	
	NO.	BY	DATE	NO.	BY		DATE
	1		10/17	3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>10/17</u> CHECKED BY <u>L. RAPP</u> DATE <u>10/17</u> DWG. NO. 20							


EPOXY-COATED REINFORCING STEEL												BAR TYPES						
SPAN A						SPAN B						SPAN C						
BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	BAR	NO.	SIZE	TYPE	LENGTH	WEIGHT	
A1	85	5	STR.	22'-2"	1,966	A1	177	5	STR.	22'-2"	4,093	A1	49	5	STR.	22'-2"	1,133	
A2	8	5	STR.	22'-2"	185	A2	8	5	STR.	22'-2"	185	A2	8	5	STR.	22'-2"	185	
A3	2	5	STR.	17'-0"	36	A7	2	5	STR.	18'-2"	38	A3	2	5	STR.	17'-0"	36	
A4	2	5	STR.	10'-6"	22	A8	2	5	STR.	11'-7"	25	A4	2	5	STR.	10'-6"	22	
A5	4	5	STR.	3'-11"	17	A9	4	5	STR.	5'-0"	21	A5	4	5	STR.	3'-11"	17	
A6	2	5	STR.	15'-5"	33	A10	2	5	STR.	15'-5"	33	A11	2	5	STR.	14'-10"	31	
B1	68	4	STR.	18'-7"	845	B3	136	4	STR.	30'-0"	2,726	B1	68	4	STR.	18'-7"	845	
B2	68	4	STR.	15'-1"	686	B4	68	4	STR.	8'-6"	387	B7	20	5	STR.	18'-8"	390	
B5	40	5	STR.	15'-7"	651	B6	60	5	STR.	21'-2"	1,325							
S1	34	5	1	6'-6"	231	S1	69	5	1	6'-6"	468	S1	20	5	1	6'-6"	136	
S2	34	5	2	12'-0"	426	S2	69	5	2	12'-0"	864	S2	20	5	2	12'-0"	251	
				TOTAL	5,098					TOTAL	10,165					TOTAL	3,046	



ALL BAR DIMENSIONS ARE OUT TO OUT


	QUANTITY BREAKDOWN BY SPAN		
	EPOXY COATED REINFORCING STEEL (LBS.)	CLASS AA CONCRETE (CU. YDS.)	
		DECK SLAB	PARAPETS
SPAN "A"	5,098	25.1	8.0
SPAN "B"	10,165	46.4	16.2
SPAN "C"	3,046	14.7	4.8
TOTALS	18,309	86.2	29.0

	TOTAL SUPERSTRUCTURE QUANTITIES		
	REINFORCED CONCRETE DECK SLAB	EPOXY COATED REINFORCING STEEL	CLASS AA CONCRETE
	SQ. FT.	LBS.	CU. YDS.
DECK SLAB	2,617.3	13,567	86.2
PARAPET	—	4,742	29.0
TOTALS	2,617.3	18,309	115.2



LAYOUT FOR COMPUTING AREA OF REINFORCED CONCRETE DECK SLAB (SQ. FEET = 2,617.3)


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUPERSTRUCTURE
 BILL OF MATERIAL

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS					SHEET NO. S7-21 TOTAL SHEETS 51	
	NO.	BY	DATE	NO.	BY		DATE
	1			3			
DRAWN BY <u>B. VAUGHN</u> DATE <u>8/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>9/17</u>	DWG. NO. <u>21</u>						



TEMPORARY SHORING PLAN



TEMPORARY SHORING ELEVATION
(LOOKING NORTH TOWARDS EXISTING TRACK)

NOTES:

SHORING HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE 2016 EDITION OF AREMA'S "MANUAL FOR RAILWAY ENGINEERING, VOL. 2, STRUCTURES", AND "NORFOLK SOUTHERN GUIDELINES FOR DESIGN OF GRADE SEPARATION STRUCTURES, UNDERPASS GRADE SEPARATION DESIGN CRITERIA."

MAXIMUM WALL DEFLECTION LIMITED TO 3/8".

ALL SHORING MATERIAL SHALL BE IN "LIKE NEW" CONDITION.

SHEET PILING SHALL BE ASTM A572 GRADE 50 STEEL (HOT ROLLED) AND SHALL HAVE THE FOLLOWING MINIMUM PROPERTIES:

MOMENT OF INERTIA/FT. 490.85 in⁴
SECTION MODULUS/FT. 60.7 in³

ASSUMED SOIL PARAMETERS


COARSE GRAINED SOILS:
SOIL MOIST UNIT WEIGHT - 120 PCF
SOIL FRICTION ANGLE - 30 DEGREES
UNDRAINED SHEAR STRENGTH - 0 PSF

EXISTING WINGWALL TO BE PARTIALLY REMOVED IN ACCORDANCE WITH SECTION 402 OF THE STANDARD SPECIFICATIONS.

REBAR IN THE PORTION OF THE EXISTING WINGWALL TO REMAIN SHALL BE CUT BACK TO A MINIMUM DEPTH OF 1" BELOW CONCRETE SURFACE AND PATCHED WITH AN EPOXY COMPOUND.


CONSTRUCTION SEQUENCE:

1. INSTALL SHORING TO REQUIRED TIP ELEVATION.
2. REMOVE EXISTING WINGWALL TO LIMITS SHOWN.
3. CONSTRUCT PROPOSED ABUTMENT.
4. BACKFILL PROPOSED ABUTMENT.
5. REMOVE SHORING.



SECTION A-A

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-



DocuSigned by:
2/21/2018

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE
ABUTMENT 1
SHORING


HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	
DRAWN BY <u>B. VAUGHN</u>	DATE <u>10/17</u>	DWG. NO. <u>22</u>	
CHECKED BY <u>L. RAPP</u>	DATE <u>10/17</u>		

REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		

SHEET NO. S7-22
TOTAL SHEETS 51



PLAN




ELEVATION

(LOOKING AHEAD STATION)

NOTES:


- FOR SECTION A-A, SEE SHEETS 3 OF 6 AND 4 OF 6.
- FOR SECTIONS B-B, C-C, AND D-D, SEE SHEET 5 OF 6.
- FOR WINGWALL ELEVATIONS AND SECTIONS, SEE SHEETS 3 OF 6 AND 4 OF 6.
- FOR LAYOUT AND DETAILS OF CONTINUOUS FRENCH DRAIN SYSTEM BEHIND ABUTMENT SEE "STRUCTURE DRAINAGE DETAILS" SHEETS 3 OF 4 AND 4 OF 4.
- [Symbol] INDICATES 3:12 PILE BATTER IN DIRECTION SHOWN.
- CONDUIT TO BE 4"Ø IN ACCORDANCE WITH UNDERWRITERS LABORATORY SPECIFICATIONS.
- FOR LOCATIONS OF FENCE AND HANDRAIL ANCHORAGES IN TOP OF BACKWALL/WINGWALLS, SEE "SUPERSTRUCTURE: BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS" SHEETS.
- FOR FOOTING REINFORCING, SEE ABUTMENT SECTIONS AND FOOTING REINFORCING PLAN ON SHEET 5 OF 6.
- *5K2, *5K4, *5K5, *5S2, AND *5S3 MAY BE ADJUSTED AS NECESSARY TO CLEAR ANCHOR BOLTS. DO NOT EXCEED 12" BETWEEN BARS.
- FOR LIMITS OF EXISTING BRIDGE WINGWALL REMOVAL, SEE "ABUTMENT 1 SHORING" SHEET.



DETAIL A - BRIDGE GIRDER ANCHOR BOLT LAYOUT

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 1 OF 6




DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED




HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	
DRAWN BY: J. JEFFERS	DATE: 10/17	DWG. NO. 23	
CHECKED BY: K. ERVIN	DATE: 10/17		

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH					
SUBSTRUCTURE ABUTMENT 1					
REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		


SHEET NO.	S7-23
TOTAL SHEETS	51



NOTE:
FOR NOTES, SEE SHEET 1 OF 6.



PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

SHEET 2 OF 6


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE
ABUTMENT 1

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S7-24
1	JRR	05/02/2018	3			TOTAL SHEETS
2			4			51

HNTB HNTB NORTH CAROLINA, P.C.
NC License No. C-1554
343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609


DRAWN BY J. JEFFERS DATE 10/17
CHECKED BY K. ERVIN DATE 10/17 DWG. NO. 24




NOTES:
 FOR ABUTMENT AND WINGWALL DIMENSIONS, AND ABUTMENT ELEVATION, SEE SHEETS 1 OF 6 AND 2 OF 6.
 FOR LOCATIONS OF FENCE AND HANDRAIL ANCHORAGES IN TOP OF BACKWALL/WINGWALLS, SEE "SUPERSTRUCTURE: BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS" SHEETS.
 FOR KEYED CONSTRUCTION JOINT DETAILS, SEE SHEET 6 OF 6.

SECTION A-A


(*5V11 AND *7V10/*7V7 BARS ON FRONT FACE AND FILL FACE OF PLATFORM GIRDER STEM WALL NOT SHOWN FOR CLARITY)




ELEVATION OF WINGWALL (W1)




SECTION E-E



ELEVATION OF WINGWALL (W2)



SECTION F-F




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 3 OF 6
 STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUBSTRUCTURE
 ABUTMENT 1


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-25 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1		10/17	3			
DRAWN BY <u>J. JEFFERS</u> DATE <u>10/17</u> CHECKED BY <u>K. ERVIN</u> DATE <u>10/17</u>	DWG. NO. 25	2	4				




NOTES:
 FOR ABUTMENT AND WINGWALL DIMENSIONS, AND ABUTMENT ELEVATION, SEE SHEETS 1 OF 6 AND 2 OF 6.
 FOR LOCATIONS OF FENCE AND HANDRAIL ANCHORAGES IN TOP OF BACKWALL/WINGWALLS, SEE "SUPERSTRUCTURE: BRIDGE MOUNTED FENCE AND HANDRAIL DETAILS" SHEETS.
 FOR KEYED CONSTRUCTION JOINT DETAILS, SEE SHEET 6 OF 6.

SECTION A-A


(*5V11 AND *7V10/*7V7 BARS ON FRONT FACE AND FILL FACE OF PLATFORM GIRDER STEM WALL NOT SHOWN FOR CLARITY)




ELEVATION OF WINGWALL (W3)




SECTION G-G



ELEVATION OF WINGWALL (W4)



SECTION H-H



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-


SHEET 4 OF 6

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 ABUTMENT 1

HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609		DWG. NO. 26	
DRAWN BY: J. JEFFERS		DATE: 10/17		SHEET NO. S7-26	
CHECKED BY: K. ERVIN		DATE: 10/17		TOTAL SHEETS 51	



REVISIONS					
NO.	BY	DATE	NO.	BY	DATE
1			3		
2			4		




FOOTING REINFORCING PLAN
(WINGWALL BARS NOT SHOWN FOR CLARITY)

NOTE:
FOR FOOTING LAYOUT, LOCATIONS OF SECTIONS B-B, C-C, AND D-D, AND ADDITIONAL DIMENSIONS, SEE SHEETS 1 OF 6 AND 2 OF 6.


BULB-TYPE WATERSTOP REQUIRED FOR DETAILS OF BULB-TYPE WATERSTOP, SEE DETAIL "A" ON "DECK DETAILS" SHEET.



SECTION C-C



SECTION B-B




SECTION D-D

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-

SHEET 5 OF 6


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE
ABUTMENT 1




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED


HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609		DWG. NO. 27	
DRAWN BY: J. JEFFERS DATE: 10/17		CHECKED BY: K. ERVIN DATE: 10/17	
REVISIONS			
NO.	BY	DATE	NO.
1			3
2			4
SHEET NO. 57-27			TOTAL SHEETS 51




WATERSTOP/KEYED CONSTRUCTION JOINT DETAIL



KEYED CONSTRUCTION JOINT DETAIL



FOOTING OR ABUT. STEM CONSTRUCTION JOINT DETAILS



BACKWALL CONSTRUCTION JOINT DETAILS

BAR TYPES			
MARK	B	C	D
H1	5'-7"	1'-2"	2"
H2	5'-7"	2'-5"	2 3/4"
H3	5'-7"	2'-5"	2 1/8"
H4	6'-1"	10"	0 3/4"
H5	5'-7"	1'-2"	1 1/16"
K8	3'-7"	10"	1 3/8"
K9	3'-7"	10"	0 3/4"

NOTE: 'D' IS PARALLEL TO WINGWALL.

ALL BAR DIMENSIONS ARE OUT TO OUT

BILL OF REINFORCING											
MARK	NO.	SIZE	TYPE	LENGTH	WEIGHT	MARK	NO.	SIZE	TYPE	LENGTH	WEIGHT
ABUTMENT 1											
H1	12	7	1	6'-9"	166	T1	166	7	4	12'-5"	4214
H2	40	5	1	8'-0"	334	T2	4	7	4	7'-8"	63
H3	29	5	2	8'-0"	242	T3	36	5	5	42'-5"	1593
H4	9	5	2	6'-11"	65	T4	36	5	5	47'-5"	1781
H5	10	7	2	6'-9"	138	T5	12	5	STR.	40'-7"	508
H6	3	5	STR.	5'-8"	18	T6	12	5	STR.	45'-7"	571
H7	3	7	STR.	5'-8"	35	T7	6	5	STR.	9'-3"	58
						T8	6	5	STR.	8'-10"	56
K1	4	5	STR.	15'-11"	67	V1	36	5	STR.	11'-7"	435
K2	23	5	STR.	38'-8"	928	V2	17	8	STR.	12'-9"	579
K3	20	5	STR.	25'-3"	527	V3	24	5	STR.	5'-5"	136
K4	23	5	STR.	23'-9"	570	V4	1	5	STR.	11'-8"	13
K5	13	5	STR.	22'-8"	308	V5	32	7	5	14'-7"	954
K6	27	5	STR.	11'-0"	310	V6	16	5	STR.	8'-11"	149
K7	27	5	3	5'-7"	158	V7	135	7	5	12'-8"	3496
K8	8	5	1	4'-5"	37	V8	43	5	STR.	6'-11"	311
K9	8	5	2	4'-5"	37	V9	92	5	5	6'-6"	624
S1	85	5	4	3'-11"	348	V10	51	7	STR.	8'-3"	861
S2	61	5	4	6'-11"	441	V11	29	5	STR.	10'-2"	308
S3	23	5	4	6'-8"	160	V12	26	5	STR.	3'-11"	107
S4	3	5	4	4'-6"	15	V13	71	5	5	2'-9"	204
S5	3	5	4	4'-5"	14	V14	27	5	STR.	9'-8"	273
S6	3	5	4	4'-4"	14						
S7	3	5	4	4'-3"	14						
S8	3	5	4	4'-2"	14						
S9	3	5	4	4'-1"	13						
S10	3	5	4	4'-0"	13						
S11	3	5	4	3'-11"	13						

QUANTITIES


ITEM	TOTAL
REINFORCING STEEL	LBS. 22,293
CLASS AA CONCRETE BREAKDOWN:	
POUR 1 FOOTING	CU. YDS 129.0
POUR 2 ABUTMENT STEM & BOTT. OF WINGS	CU. YDS 39.7
POUR 3 BRIDGE BACKWALL AND WINGS	CU. YDS 23.0
POUR 4 PLATFORM GIRDER STEM WALL & WINGS	CU. YDS 31.3
POUR 5 PLATFORM GIRDER BACKWALL AND WINGS	CU. YDS 4.5
TOTAL	CU. YDS 227.5
HP 14 X 73 STEEL PILES	NO. 40
	L.F. 2,133

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 6 OF 6


STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH

SUBSTRUCTURE
 ABUTMENT 1



NOTE:
 SEE "ABUTMENT 1 SHORING"
 SHEET FOR ADDITIONAL INFORMATION

EXISTING ABUTMENT INTERFACE DETAIL




DocuSigned by:
 50683191c22b434...
 2/21/2018

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C.
 NC License No. C-1554
 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609

DRAWN BY J. JEFFERS DATE 10/17
 CHECKED BY K. ERVIN DATE 10/17 DWG. NO. 28

REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	S7-28
1			3			TOTAL SHEETS
2			4			51



TEMPORARY SHORING PLAN

NOTES:

SHORING HAS BEEN DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF THE 2016 EDITION OF AREMA'S "MANUAL FOR RAILWAY ENGINEERING, VOL. 2, STRUCTURES", AND "NORFOLK SOUTHERN GUIDELINES FOR DESIGN OF GRADE SEPARATION STRUCTURES, UNDERPASS GRADE SEPARATION DESIGN CRITERIA".

MAXIMUM WALL DEFLECTION LIMITED TO 1/2".

ALL SHORING MATERIAL SHALL BE IN "LIKE NEW" CONDITION.

SHEET PILING SHALL BE ASTM A572 GRADE 50 STEEL (HOT ROLLED) AND SHALL HAVE THE FOLLOWING MINIMUM PROPERTIES:

SECTION 1:
MOMENT OF INERTIA/FT. 656.2 in⁴
SECTION MODULUS/FT. 66.8 in³


SECTION 2:
MOMENT OF INERTIA/FT. 156.9 in⁴
SECTION MODULUS/FT. 23.2 in³

ASSUMED SOIL PARAMETERS
COARSE GRAINED SOILS:
SOIL MOIST UNIT WEIGHT - 120 PCF
SOIL FRICTION ANGLE - 30 DEGREES
UNDRAINED SHEAR STRENGTH - 0 PSF

* CONSTRUCTION SEQUENCE:


1. INSTALL SHORING TO REQUIRED TIP ELEVATION.
2. EXCAVATE TO EXCAVATION LIMIT SHOWN.
3. CONSTRUCT PROPOSED PIER.
4. BACKFILL PROPOSED PIER.
5. CONSTRUCT PROPOSED RETAINING WALL.
6. BACKFILL PROPOSED RETAINING WALL.
7. REMOVE SHORING.

* COMPLETE SHORING REMOVAL PRIOR TO ABUTMENT 1 EMBANKMENT CONSTRUCTION AND PILE INSTALLATION.



TEMPORARY SHORING ELEVATION
(LOOKING AWAY FROM FOOTING)

PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-



DocuSigned by:
2/21/2018


DOCUMENT NOT CONSIDERED
FINAL UNLESS ALL
SIGNATURES COMPLETED

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE

PIER 1
SHORING


HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609		REVISIONS			SHEET NO.
DRAWN BY <u>B. VAUGHN</u>	DATE <u>10/17</u>	DATE <u>10/17</u>	DWG. NO. <u>29</u>	NO.	BY	DATE	S7-29
CHECKED BY <u>L. RAPP</u>	DATE <u>10/17</u>			1			TOTAL SHEETS
				2			51




PLAN

NOTES:


- ALL DIMENSIONS SHOWN ARE PARALLEL OR NORMAL TO C PIER UNLESS NOTED.
- STIRRUPS IN CAP MAY BE SHIFTED AS NECESSARY TO CLEAR ANCHOR BOLTS.
- HOOKS ON "V" AND "M" BARS MAY BE TURNED AS NECESSARY FOR PLACING REINFORCING STEEL.
- TOP MAT OF FOOTING LONGITUDINAL AND TRANSVERSE REINFORCEMENT MAY BE SHIFTED AS NECESSARY TO CLEAR COLUMN REINFORCEMENT. DO NOT EXCEED 12" BETWEEN BARS.



DETAIL A - BRIDGE GIRDER ANCHOR BOLT LAYOUT



ELEVATION




DETAIL C

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 1 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH




SUBSTRUCTURE
 PIER 1



DocuSigned by:
 2/21/2018

DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-30 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1		9/17	3			
DRAWN BY <u>B. VAUGHN</u> CHECKED BY <u>L. RAPP</u>	DATE <u>10/17</u>	DWG. NO. <u>30</u>	DATE <u>10/17</u>	NO. <u>4</u>	DATE		




PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-

SHEET 2 OF 4

STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH




SUBSTRUCTURE
 PIER 1




DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	
DRAWN BY: <u>B. VAUGHN</u>	DATE: <u>9/17</u>	DWG. NO. <u>31</u>	
CHECKED BY: <u>L. RAPP</u>	DATE: <u>10/17</u>		
REVISIONS			
NO.	BY	DATE	NO.
1			3
2			4

SHEET NO.	S7-31
TOTAL SHEETS	51




FOOTING CONSTRUCTION JOINT DETAILS



FOOTING REINFORCING PLAN

PROJECT NO. P-5705BA
 MECKLENBURG COUNTY
 STATION: POS STA. 28+12.88 -S2-


SHEET 3 OF 4
 STATE OF NORTH CAROLINA
 DEPARTMENT OF TRANSPORTATION
 RALEIGH
 SUBSTRUCTURE
 PIER 1




DOCUMENT NOT CONSIDERED
 FINAL UNLESS ALL
 SIGNATURES COMPLETED

HNTB		HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	
DRAWN BY: <u>B. VAUGHN</u>	DATE: <u>9/17</u>	DWG. NO. <u>32</u>	
CHECKED BY: <u>L. RAPP</u>	DATE: <u>10/17</u>		


REVISIONS						SHEET NO.
NO.	BY	DATE	NO.	BY	DATE	TOTAL SHEETS
1			3			51
2			4			




SECTION A-A
(COLUMN REINFORCING AND #5S10 BARS NOT SHOWN FOR CLARITY)




SECTION B-B
(CAP REINFORCING NOT SHOWN FOR CLARITY)



SECTION C-C




SECTION D-D
(V1 BARS NOT SHOWN FOR CLARITY)



DETAIL OF WOOD CORE FOR ANCHOR BOLT HOLES

BAR TYPES



* #5S3 CIRCULAR TIES SHALL BE ASTM DESIGNATION A706, GRADE 60. FABRICATION TO BE IN ACCORDANCE WITH THE 'MANUAL OF STANDARD PRACTICE', A.C.I. 315.80.
* THE SP-1 SPIRAL REINFORCING STEEL SHALL BE W31 OR D31 COLD DRAWN WIRE OR #5 PLAIN OR DEFORMED BAR.

BILL OF REINFORCING

PIER 1					
MARK	NO.	SIZE	TYPE	LENGTH	WEIGHT
B1	8	9	1	45'-11"	1,249
B2	24	9	STR.	44'-8"	3,645
B3	10	5	STR.	40'-6"	422
B4	32	9	5	32'-10"	3,572
B5	10	5	5	32'-10"	342
B6	8	9	1	8'-5"	229
B7	30	6	STR.	22'-8"	1,021
B8	6	6	3	24'-8"	222
S1	180	5	2	13'-9"	2,581
S2	139	4	3	6'-2"	573
*S3	168	5	4	11'-7"	2,030
S4	18	4	3	6'-1"	73
S5	16	4	3	6'-6"	69
S6	45	4	3	5'-8"	170
S7	45	4	2	19'-4"	581
S8	12	4	3	9'-6"	76
S9	32	4	8	5'-7"	119
S10	35	5	3	13'-6"	493
M1	182	11	1	13'-3"	12,812
T1	14	8	6	48'-11"	1,829
T2	14	8	1	46'-3"	1,729
T3	6	5	STR.	42'-7"	266
T4	14	8	6	38'-4"	1,433
T5	14	8	1	35'-8"	1,333
T6	6	5	STR.	34'-9"	217
T7	80	6	3	18'-6"	2,223
T8	80	10	7	14'-4"	4,934
T9	6	5	STR.	11'-6"	72
V1	182	11	1	20'-1"	19,420
V2	90	4	STR.	9'-0"	541
SP-1	7	*	9	737'-4"	5,383

QUANTITIES

ITEM	TOTAL
REINFORCING STEEL	LBS 64,276
SPIRAL COLUMN REINFORCING STEEL	LBS 5,383
CLASS AA CONCRETE:	
POUR 1	C.Y. 166.3
POUR 2	C.Y. 48.9
POUR 3	C.Y. 31.3
POUR 4	C.Y. 27.5
POUR 5	C.Y. 27.2
TOTAL	C.Y. 301.2
HP14x73 STEEL PILES	NO. 26 L.F. 1,083


PROJECT NO. P-5705BA
MECKLENBURG COUNTY
STATION: POS STA. 28+12.88 -S2-

SHEET 4 OF 4

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

SUBSTRUCTURE

PIER 1



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

HNTB HNTB NORTH CAROLINA, P.C. NC License No. C-1554 343 E. Six Forks Rd., Suite 200, Raleigh, N.C. 27609	REVISIONS				SHEET NO. S7-33 TOTAL SHEETS 51		
	NO.	BY	DATE	NO.		BY	DATE
	1		9/17	3			
2		10/17	4				

DRAWN BY B. VAUGHN DATE 9/17 DWG. NO. 33
CHECKED BY L. RAPP DATE 10/17