

PROJECT REFERENCE NO.	SHEET NO.
U-4405	EC-56/CONST.19
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

NOTES: ANY DEVIATION FROM OPTIONS GIVEN WILL REQUIRE PRIOR APPROVAL BY ENGINEER.

ADDITIONAL EROSION CONTROL DEVICES MAY NEED TO BE INSTALLED AS DIRECTED.

INSTALL FABRIC INSERT INLET PROTECTION DEVICE IN LIEU OF ROCK INLET SEDIMENT TRAP TYPE 'C' AS DIRECTED TO AVOID PONDING OF RUNOFF IN ROADWAY OPEN TO PUBLIC TRAFFIC

-L-
 PI Sta 215+19.81
 $\Delta = 2' 4" 44.8" (RT)$
 $D = 0' 34" 22.6"$
 $L = 470.50'$
 $T = 235.29'$
 $R = 10,000.00'$
 SE = NC

NC GRID
 NAD 83/NA 2011

MATCHLINE SEE SHEET 18
 -L- STA 205+00

MATCHLINE SEE SHEET 20
 -L- STA 218+50

8/17/99
 REVISIONS
 10:37:52 AM
 R:\Environmental\Design\4405.REU.EC.psh.19_Final.dgn
 R:\Environmental\Design\4405.REU.EC.psh.19_Final.dgn

★ PROPOSED SIGNAL
 █ PROP CONC SIDEWALK
 ** A DESIGN EXCEPTION FOR LANE WIDTH IS REQUIRED FOR -L- STA. 38+95.00 TO -L- 319+95.00

NOTE: SEE SHEET 39 & 40 FOR -L- PROFILE
 SEE SHEET 48 FOR -Y23- PROFILE

