

**This electronic collection of documents is provided  
for the convenience of the user  
and is Not a Certified Document –**




**The documents contained herein were originally issued  
and sealed by the individuals whose names and license  
numbers appear on each page, on the dates appearing  
with their signature on that page.**

**This file or an individual page  
shall not be considered a certified document.**





PROJECT REFERENCE NO. <i>U-5833</i>	SHEET NO. <i>EC-2</i>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

# WATTLE WITH POLYACRYLAMIDE (PAM) DETAIL




**NOTES:**

- USE MINIMUM 12 IN. DIAMETER EXCELSIOR WATTLE.
- USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.
- ONLY INSTALL WATTLE(S) TO A HEIGHT IN DITCH SO FLOW WILL NOT WASH AROUND WATTLE AND SCOUR DITCH SLOPES AND AS DIRECTED.
- INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.
- PROVIDE STAPLES MADE OF 0.125 IN. DIAMETER STEEL WIRE FORMED INTO A U SHAPE NOT LESS THAN 12" IN LENGTH.
- INSTALL STAPLES APPROXIMATELY EVERY 1 LINEAR FOOT ON BOTH SIDES OF WATTLE AND AT EACH END TO SECURE IT TO THE SOIL.
- INSTALL MATTING IN ACCORDANCE WITH SECTION 1631 OF THE STANDARD SPECIFICATIONS.
- PRIOR TO POLYACRYLAMIDE (PAM) APPLICATION, OBTAIN A SOIL SAMPLE FROM PROJECT LOCATION, AND FROM OFFSITE MATERIAL, AND ANALYZE FOR APPROPRIATE PAM FLOCCULANT TO BE APPLIED TO EACH WATTLE.
- INITIALLY APPLY 2 OUNCES OF ANIONIC OR NEUTRALLY CHARGED PAM OVER WATTLE WHERE WATER WILL FLOW AND 1 OUNCE OF PAM ON EACH SIDE OF WATTLE. REAPPLY PAM AFTER EVERY RAINFALL EVENT THAT IS EQUAL TO OR EXCEEDS 0.50 IN.



PROJECT REFERENCE NO. U-5833	SHEET NO. EC-2A
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

# TEMPORARY ROCK SILT CHECK TYPE 'A' WITH EXCELSIOR MATTING AND POLYACRYLAMIDE (PAM)



PLAN


NOTES:

INSTALL TEMPORARY ROCK SILT CHECK TYPE A IN ACCORDANCE WITH ROADWAY STANDARD DRAWING NO. 1633.01.


USE EXCELSIOR FOR MATTING MATERIAL AND ANCHOR MATTING SECTION AT TOP AND BOTTOM WITH CLASS B STONE.

PRIOR TO POLYACRYLAMIDE (PAM) APPLICATION, OBTAIN A SOIL SAMPLE FROM PROJECT LOCATION, AND FROM OFFSITE MATERIAL, AND ANALYZE FOR APPROPRIATE PAM FLOCCULANT TO BE APPLIED TO EACH ROCK SILT CHECK.


INITIALLY APPLY 4 OUNCES OF POLYACRYLAMIDE (PAM) TO TOP OF MATTING SECTION AND AFTER EVERY RAINFALL EVENT THAT EQUALS OR EXCEEDS 0.50 INCHES.



INSET A



SECTION A-A



SECTION B-B

NOT TO SCALE

DIVISION OF HIGHWAYS  
STATE OF NORTH CAROLINA

---



---


PROJECT REFERENCE NO. <i>U-5833</i>	SHEET NO. <i>EC-3</i>
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER



## ***SOIL STABILIZATION TIMEFRAMES***

<i>SITE DESCRIPTION</i>	<i>STABILIZATION TIME</i>	<i>TIMEFRAME EXCEPTIONS</i>
PERIMETER DIKES, SWALES, DITCHES AND SLOPES	7 DAYS	NONE
HIGH QUALITY WATER (HQW) ZONES	7 DAYS	NONE
SLOPES STEEPER THAN 3:1	7 DAYS	IF SLOPES ARE 10' OR LESS IN LENGTH AND ARE NOT STEEPER THAN 2:1, 14 DAYS ARE ALLOWED.
SLOPES 3:1 OR FLATTER	14 DAYS	7 DAYS FOR SLOPES GREATER THAN 50' IN LENGTH.
ALL OTHER AREAS WITH SLOPES FLATTER THAN 4:1	14 DAYS	NONE, EXCEPT FOR PERIMETERS AND HQW ZONES.

### ***MATTING FOR EROSION CONTROL***



<i>CONST SHEET NO.</i>	<i>LINE</i>	<i>FROM STATION</i>	<i>TO STATION</i>	<i>SIDE</i>	<i>ESTIMATE (SY)</i>
5	L	17+26	17+62	LT	30
6	L	27+50	30+38	LT	145
<i>SUBTOTAL</i>					175
<i>MISCELLANEOUS MATTING TO BE INSTALLED AS DIRECTED BY THE ENGINEER</i>					7650
<i>TOTAL</i>					7825
<i>SAY</i>					7825

PROJECT REFERENCE NO. <i>U-5833</i>	SHEET NO. <i>EC-04/CONST.4</i>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	




**-Y- CURVE DATA**  
 PI Sta 12+11.08  
 $\Delta = 17^{\circ} 31' 04.3''$  (RT)  
 $D = 410' 55.8''$   
 $L = 418.87'$   
 $T = 211.08'$   
 $R = 1,370.00'$   
 $SE = 0.10$   
 $DS = 60$  MPH




**-L- CURVE DATA**  
 PI Sta 10+72.18  
 $\Delta = 32^{\circ} 12' 30.4''$  (RT)  
 $D = 22' 55' 05.9''$   
 $L = 140.54'$   
 $T = 72.18'$   
 $R = 250.00'$   
 $SE = 0.02$   
 $DS < 15$  MPH  
 Ⓣ -L-PT 11+40.54



**NOTE:**  
 CLEARING AND GRUBBING  
 EROSION CONTROL FOR  
 CONSTRUCTION SHEET 4

PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B  
 AND TEMPORARY ROCK SILT CHECKS TYPE - A AT  
 DRAINAGE OUTLETS.

PROJECT REFERENCE NO. U-5833	SHEET NO. EC-05/CONST.5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804 C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	



-L- CURVE DATA


PI Sta 16+18.51 Δ = 12° 28' 03.1" (LT) D = 3' 34' 51.6" L = 348.16' T = 174.77' R = 1,600.00' SE = 0.04 DS > 60 MPH	PI Sta 22+88.92 Δ = 5° 00' 34.2" (RT) D = 1' 54' 35.5" L = 262.30' T = 131.23' R = 3,000.00' SE = 0.04 DS > 60 MPH
--	---


MATCH LINE STA. -L- 12+50.00  
MATCH TO SHEET NO. 4

MATCH LINE STA. -L- 24+00.00  
MATCH TO SHEET NO. 6

CLEARING AND GRUBBING  
EROSION CONTROL FOR  
CONSTRUCTION SHEET 5

NOTE:  
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B  
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT  
DRAINAGE OUTLETS.

PROJECT REFERENCE NO. U-5833	SHEET NO. EC-06/CONST.6
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804 C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	




-L- CURVE DATA

PI Sta 22+88.92	PI Sta 32+45.66
$\Delta = 5^{\circ}00'34.2''$ (RT)	$\Delta = 19^{\circ}08'05.9''$ (RT)
$D = 1^{\circ}54'35.5''$	$D = 4^{\circ}50'06.3''$
$L = 262.30'$	$L = 395.75'$
$T = 131.23'$	$T = 199.74'$
$R = 3,000.00'$	$R = 1,185.00'$
$SE = 0.04$	$DS = 0.04$
$DS > 60$ MPH	$DS = 50$ MPH

MATCH LINE STA. -L- 24+00.00  
MATCH TO SHEET NO. 5


MATCH LINE STA. -L- 38+00.00  
MATCH TO SHEET NO. 7




CLEARING AND GRUBBING  
EROSION CONTROL FOR  
CONSTRUCTION SHEET 6

NOTE:  
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B  
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT  
DRAINAGE OUTLETS.




PROJECT REFERENCE NO.	SHEET NO.
U-5833	EC-07/CONST.7
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	



NAD '83/2011



CLEARING AND GRUBBING  
EROSION CONTROL FOR  
CONSTRUCTION SHEET 7



NOTE:  
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B  
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT  
DRAINAGE OUTLETS.


PROJECT REFERENCE NO. <i>U-5833</i>	SHEET NO. <i>EC-08/CONST.4</i>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804-C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	






-Y- CURVE DATA  
 PI Sta 12+11.08  
 $\Delta = 17^{\circ} 31' 04.3''$  (RT)  
 $D = 410' 55.8''$   
 $L = 418.87'$   
 $T = 211.08'$   
 $R = 1,370.00'$   
 $SE = 0.10$   
 $DS = 60$  MPH

-L- CURVE DATA  
 PI Sta 10+72.18  
 $\Delta = 32^{\circ} 12' 30.4''$  (RT)  
 $D = 22' 55' 05.9''$   
 $L = 140.54'$   
 $T = 72.18'$   
 $R = 250.00'$   
 $SE = 0.02$   
 $DS < 15$  MPH  
 Ⓣ -L-PT 11+40.54



PROJECT REFERENCE NO.	SHEET NO.
U-5833	EC-09/CONST.5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804 C. N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	



-L- CURVE DATA

PI Sta 16+18.51	PI Sta 22+88.92
$\Delta = 12^\circ 28' 03.1''$ (LT)	$\Delta = 5^\circ 00' 34.2''$ (RT)
$D = 3' 34' 51.6''$	$D = 1' 54' 35.5''$
$L = 348.16'$	$L = 262.30'$
$T = 174.77'$	$T = 131.23'$
$R = 1,600.00'$	$R = 3,000.00'$
$SE = 0.04$	$SE = 0.04$
$DS > 60$ MPH	$DS > 60$ MPH


**INSTALL MATTING IN THE  
PROPOSED DITCH LINE  
-L- STA 17+26 TO 17+62 LT  
EST. 30 SY**

**Place Matting for Erosion Control  
on Slope as Work Allows.  
-L- Sta. 23+00 to 27+50 RT**

**Place Matting for Erosion Control  
on Slopes Adjacent to Permitted  
Wetlands as Work Allows.**

**MATCH LINE STA. -L- 12+50.00  
MATCH TO SHEET NO. 4**

**MATCH LINE STA. -L- 24+00.00  
MATCH TO SHEET NO. 6**


PROJECT REFERENCE NO. U-5833	SHEET NO. EC-10/CONST.6
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804 C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	



INSTALL MATTING IN THE PROPOSED DITCH LINE  
 -L- STA 27+50 TO 30+38 LT  
 EST. 145 SY


-L- CURVE DATA

PI Sta 22+88.92	PI Sta 32+45.66
$\Delta = 5^{\circ}00'34.2"$ (RT)	$\Delta = 19^{\circ}08'05.9"$ (RT)
$D = 1^{\circ}54'35.5"$	$D = 4^{\circ}50'06.3"$
$L = 262.30'$	$L = 395.75'$
$T = 131.23'$	$T = 199.74'$
$R = 3,000.00'$	$R = 1,185.00'$
$SE = 0.04$	$SE = 0.04$
$DS > 60$ MPH	$DS = 50$ MPH




MATCH LINE STA. -L- 24+00.00  
MATCH TO SHEET NO. 5

MATCH LINE STA. -L- 38+00.00  
MATCH TO SHEET NO. 7




Place Matting for Erosion Control  
 on Slope as Work Allows.  
 -L- Sta. 23+00 to 27+50 RT

Place Matting for Erosion Control  
 on Slopes Adjacent to Permitted  
 Wetlands as Work Allows.

PROJECT REFERENCE NO. U-5833	SHEET NO. EC-11/CONST.7
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
<b>DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED</b>	
 <b>TGS ENGINEERS</b> 804 C N. LAFAYETTE ST SHELBY, NC 28150 PH: (704) 476-0003 CORP. LICENSE NO.: C-0275	

NAD '83/2011

MATCH LINE STA. -L- 38 + 00.00  
MATCH TO SHEET NO. 6



**END PROJECT U-5833**  
-L- STA. 44+10.98

-L-POT 44+10.98

NOTE 1:  
THE CONTRACTOR SHALL REPLACE CONTROL OF ACCESS 60" CHAIN LINK FENCE AS DIRECTED BY THE ENGINEER.