

**SEE SHEET 3 FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION**

**STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5742	1	107

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N.C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N.C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 - BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

J. RACZYNSKI

M. SNYDER

F&R Personnel

INVESTIGATED BY RK&K, LLP

DRAWN BY M. SNYDER

CHECKED BY G. GOINS

SUBMITTED BY RK&K, LLP

DATE SEPTEMBER 2018

Prepared in the Office of:



DocuSigned by:
Matthew Snyder 9/18/2018
9822EB64E80842E
SIGNATURE DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

**ROADWAY
SUBSURFACE INVESTIGATION**

COUNTY CLAY
PROJECT DESCRIPTION NC 175 WIDENING FROM
GEORGIA STATE LINE TO US 64

INVENTORY

CONTENTS

LINE	STATION	PLAN
-L-	10+75 - 172+00	4 - 15
-L-	183+76 - 229+76	16 - 19
-Y1-	10+00 - 11+06	18
-Y2-	10+75 - 11+96	18
-Y3-	10+00 - 11+25	6
-Y4-	10+55 - 11+72	6
-Y5-	10+00 - 14+30	13
-DET-	10+00 - 28+04	12 - 14
-DR1-	10+00 - 11+46	4
-DR2-	10+26 - 11+17	6
-DR3-	10+50 - 11+15	6
-DR5-	10+82 - 11+21	9
-DR6-	10+50 - 11+20	9
-DR7-	10+50 - 11+92	9
-DR8-	10+55 - 11+30	11
-DR9-	10+00 - 10+55	11
-DR10-	10+25 - 11+30	13
-DR11-	10+00 - 13+00	13
-DR13-	10+00 - 10+70	13
-DR14-	10+00 - 10+60	14
-DR16-	10+00 - 10+79	15
-DR16A-	10+00 - 11+07	14
-DR20-	10+00 - 11+11	15
-DR21-	10+00 - 10+75	18

CROSS SECTIONS

LINE	STATION	SHEETS
-L-	10+75-229+76	20-98

APPENDICES

APPENDIX	TITLE	SHEETS
A	LABORATORY RESULTS	99-107































REFERENCE: R-5742

PROJECT: 46325

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS																																																																																											
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i>										WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.										HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:										ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLOGGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROQ) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS IN OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SRC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (T.S.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.																																																																																											
SOIL LEGEND AND AASHTO CLASSIFICATION										ANGULARITY OF GRAINS THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.										WEATHERED ROCK (WR)  NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.										CRYSTALLINE ROCK (CR)  FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.																																																																																											
MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.										NON-CRYSTALLINE ROCK (NCR)  FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.										COASTAL PLAIN SEDIMENTARY ROCK (CP)  COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.																																																																																																					
COMPRESSION SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50										PERCENTAGE OF MATERIAL										WEATHERING																																																																																																					
<table border="1"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY	<table border="1"> <tr> <th>ORGANIC MATERIAL</th> <th>GRANULAR SOILS</th> <th>SILT - CLAY SOILS</th> <th>OTHER MATERIAL</th> </tr> <tr> <td>TRACE OF ORGANIC MATTER</td> <td>2 - 3%</td> <td>3 - 5%</td> <td>TRACE</td> </tr> <tr> <td>LITTLE ORGANIC MATTER</td> <td>3 - 5%</td> <td>5 - 12%</td> <td>LITTLE</td> </tr> <tr> <td>MODERATELY ORGANIC</td> <td>5 - 10%</td> <td>12 - 20%</td> <td>SOME</td> </tr> <tr> <td>HIGHLY ORGANIC</td> <td>> 10%</td> <td>> 20%</td> <td>HIGHLY</td> </tr> </table>										ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL	TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE	LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE	MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME	HIGHLY ORGANIC	> 10%	> 20%	HIGHLY	<table border="1"> <tr> <th>ROCK FRESH</th> <th>VERY SLIGHT (V SLI.)</th> <th>SLIGHT (SLI.)</th> <th>MODERATE (MOD.)</th> <th>MODERATELY SEVERE (MOD. SEV.)</th> <th>SEVERE (SEV.)</th> <th>VERY SEVERE (V SEV.)</th> <th>COMPLETE</th> </tr> <tr> <td>ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</td> <td>ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</td> <td>ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</td> <td>SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</td> <td>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL</td> <td>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF</td> <td>ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</td> <td>ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</td> </tr> </table>										ROCK FRESH	VERY SLIGHT (V SLI.)	SLIGHT (SLI.)	MODERATE (MOD.)	MODERATELY SEVERE (MOD. SEV.)	SEVERE (SEV.)	VERY SEVERE (V SEV.)	COMPLETE	ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.	ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.	ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.																																				
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																						
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																						
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																						
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																						
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY																																																																																																																						
ORGANIC MATERIAL	GRANULAR SOILS	SILT - CLAY SOILS	OTHER MATERIAL																																																																																																																						
TRACE OF ORGANIC MATTER	2 - 3%	3 - 5%	TRACE																																																																																																																						
LITTLE ORGANIC MATTER	3 - 5%	5 - 12%	LITTLE																																																																																																																						
MODERATELY ORGANIC	5 - 10%	12 - 20%	SOME																																																																																																																						
HIGHLY ORGANIC	> 10%	> 20%	HIGHLY																																																																																																																						
ROCK FRESH	VERY SLIGHT (V SLI.)	SLIGHT (SLI.)	MODERATE (MOD.)	MODERATELY SEVERE (MOD. SEV.)	SEVERE (SEV.)	VERY SEVERE (V SEV.)	COMPLETE																																																																																																																		
ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.	ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.	ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF	ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF	ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.																																																																																																																		
GROUND WATER  WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING  STATIC WATER LEVEL AFTER 24 HOURS  PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA  SPRING OR SEEP										MISCELLANEOUS SYMBOLS  ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION  SOIL SYMBOL  ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT  INFERRED SOIL BOUNDARY  INFERRED ROCK LINE  ALLUVIAL SOIL BOUNDARY  DIP & DIP DIRECTION OF ROCK STRUCTURES  SPT TEST BORING  AUGER BORING  CORE BORING  MONITORING WELL  PIEZOMETER INSTALLATION  SLOPE INDICATOR INSTALLATION  CONE PENETROMETER TEST  SOUNDING ROD  TEST BORING WITH CORE  SPT N-VALUE																																																																																																															
CONSISTENCY OR DENSENESS										RECOMMENDATION SYMBOLS  UNDERCUT  SHALLOW UNDERCUT  UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE  UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK  UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE USED IN THE TOP 3 FEET OF EMBANKMENT OR BACKFILL										ROCK HARDNESS VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK. HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN. MODERATELY HARD CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS. MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK. HARD CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE. SOFT CAN BE GROOVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE. VERY SOFT CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.																																																																																																					
TEXTURE OR GRAIN SIZE										ABBREVIATIONS AR - AUGER REFUSAL BT - BORING TERMINATED CL - CLAY CPT - CONE PENETRATION TEST CSE - COARSE DMT - DILATOMETER TEST DPT - DYNAMIC PENETRATION TEST e - VOID RATIO F - FINE FOSS - FOSSILIFEROUS FRAC. - FRACTURED, FRACTURES FRAGS. - FRAGMENTS HL - HIGHLY MED. - MEDIUM MICA - MICACEOUS MOD. - MODERATELY NP - NON PLASTIC ORG. - ORGANIC PMT - PRESSUREMETER TEST SAP. - SAPROLITIC SD. - SAND, SANDY SL. - SILT, SILTY SIL. - SLIGHTLY TCR - TRICONE REFUSAL w - MOISTURE CONTENT V - VERY VST - VANE SHEAR TEST WEA. - WEATHERED % - UNIT WEIGHT % - DRY UNIT WEIGHT SAMPLE ABBREVIATIONS S - BULK SS - SPLIT SPOON ST - SHELBY TUBE RS - ROCK RT - RECOMPACTED TRIAXIAL CBR - CALIFORNIA BEARING RATIO																																																																																																															
<table border="1"> <tr> <th>U.S. STD. SIEVE SIZE</th> <th>4</th> <th>10</th> <th>40</th> <th>60</th> <th>200</th> <th>270</th> </tr> <tr> <th>OPENING (MM)</th> <td>4.75</td> <td>2.00</td> <td>0.42</td> <td>0.25</td> <td>0.075</td> <td>0.053</td> </tr> </table>										U.S. STD. SIEVE SIZE	4	10	40	60	200	270	OPENING (MM)	4.75	2.00	0.42	0.25	0.075	0.053	<table border="1"> <tr> <th>BOULDER (BLDR.)</th> <th>COBBLE (COB.)</th> <th>GRAVEL (GR.)</th> <th>COARSE SAND (CSE. SD.)</th> <th>FINE SAND (F. SD.)</th> <th>SILT (SL.)</th> <th>CLAY (CL.)</th> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)								<table border="1"> <tr> <th>GRAIN SIZE</th> <th>MM</th> <th>305</th> <th>75</th> <th>2.0</th> <th>0.25</th> <th>0.05</th> <th>0.005</th> </tr> <tr> <th>IN.</th> <td>12</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>										GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005	IN.	12	3																																																					
U.S. STD. SIEVE SIZE	4	10	40	60	200	270																																																																																																																			
OPENING (MM)	4.75	2.00	0.42	0.25	0.075	0.053																																																																																																																			
BOULDER (BLDR.)	COBBLE (COB.)	GRAVEL (GR.)	COARSE SAND (CSE. SD.)	FINE SAND (F. SD.)	SILT (SL.)	CLAY (CL.)																																																																																																																			
GRAIN SIZE	MM	305	75	2.0	0.25	0.05	0.005																																																																																																																		
IN.	12	3																																																																																																																							
SOIL MOISTURE - CORRELATION OF TERMS										EQUIPMENT USED ON SUBJECT PROJECT										FRACTURE SPACING										BEDDING																																																																																											
<table border="1"> <tr> <th>SOIL MOISTURE SCALE (ATTERBERG LIMITS)</th> <th>FIELD MOISTURE DESCRIPTION</th> <th>GUIDE FOR FIELD MOISTURE DESCRIPTION</th> </tr> <tr> <td>LL - LIQUID LIMIT</td> <td>- SATURATED - (SAT.)</td> <td>USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE</td> </tr> <tr> <td>PL - PLASTIC LIMIT</td> <td>- WET - (W)</td> <td>SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE</td> </tr> <tr> <td>OM - OPTIMUM MOISTURE</td> <td>- MOIST - (M)</td> <td>SOLID; AT OR NEAR OPTIMUM MOISTURE</td> </tr> <tr> <td>SL - SHRINKAGE LIMIT</td> <td>- DRY - (D)</td> <td>REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</td> </tr> </table>										SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION	LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE	PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE	OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE	SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	<table border="1"> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> B _____ <input type="checkbox"/> H _____</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> N _____</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td>HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE _____ * STEEL TEETH</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE _____ * TUNG-CARB.</td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input checked="" type="checkbox"/> 3-1/4" HOLLOW STEM AUGERS</td> <td><input checked="" type="checkbox"/> PROBE ROD</td> </tr> </table>										DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input checked="" type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:	<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> B _____ <input type="checkbox"/> H _____	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> N _____	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:	<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER	<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER	<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD	<input type="checkbox"/>	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/>	<input checked="" type="checkbox"/> 3-1/4" HOLLOW STEM AUGERS	<input checked="" type="checkbox"/> PROBE ROD	<table border="1"> <tr> <th>TERM</th> <th>SPACING</th> <th>TERM</th> <th>THICKNESS</th> </tr> <tr> <td>VERY WIDE</td> <td>MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED</td> <td>4 FEET</td> </tr> <tr> <td>WIDE</td> <td>3 TO 10 FEET</td> <td>THICKLY BEDDED</td> <td>1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE</td> <td>1 TO 3 FEET</td> <td>THINLY BEDDED</td> <td>0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE</td> <td>0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED</td> <td>0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE</td> <td>LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED</td> <td>0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td></td> <td>THINLY LAMINATED</td> <td>< 0.008 FEET</td> </tr> </table>										TERM	SPACING	TERM	THICKNESS	VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET	WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET	MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET	CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET	VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET			THINLY LAMINATED	< 0.008 FEET	<table border="1"> <tr> <th>INDURATION</th> </tr> <tr> <td>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</td> </tr> <tr> <td>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										INDURATION	FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.
SOIL MOISTURE SCALE (ATTERBERG LIMITS)	FIELD MOISTURE DESCRIPTION	GUIDE FOR FIELD MOISTURE DESCRIPTION																																																																																																																							
LL - LIQUID LIMIT	- SATURATED - (SAT.)	USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE																																																																																																																							
PL - PLASTIC LIMIT	- WET - (W)	SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE																																																																																																																							
OM - OPTIMUM MOISTURE	- MOIST - (M)	SOLID; AT OR NEAR OPTIMUM MOISTURE																																																																																																																							
SL - SHRINKAGE LIMIT	- DRY - (D)	REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE																																																																																																																							
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																							
<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																							
<input checked="" type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																																																																							
<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> B _____ <input type="checkbox"/> H _____																																																																																																																							
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> N _____																																																																																																																							
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																							
<input type="checkbox"/>	<input checked="" type="checkbox"/> 3-1/4" HOLLOW STEM AUGERS	<input checked="" type="checkbox"/> PROBE ROD																																																																																																																							
TERM	SPACING	TERM	THICKNESS																																																																																																																						
VERY WIDE	MORE THAN 10 FEET	VERY THICKLY BEDDED	4 FEET																																																																																																																						
WIDE	3 TO 10 FEET	THICKLY BEDDED	1.5 - 4 FEET																																																																																																																						
MODERATELY CLOSE	1 TO 3 FEET	THINLY BEDDED	0.16 - 1.5 FEET																																																																																																																						
CLOSE	0.16 TO 1 FOOT	VERY THINLY BEDDED	0.03 - 0.16 FEET																																																																																																																						
VERY CLOSE	LESS THAN 0.16 FEET	THICKLY LAMINATED	0.008 - 0.03 FEET																																																																																																																						
		THINLY LAMINATED	< 0.008 FEET																																																																																																																						
INDURATION																																																																																																																									
FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.																																																																																																																									
FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																									
MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																									
INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																									
EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																									
PLASTICITY										<table border="1"> <tr> <th>DRILL UNITS:</th> <th>ADVANCING TOOLS:</th> <th>HAMMER TYPE:</th> </tr> <tr> <td><input type="checkbox"/> CME-45C</td> <td><input type="checkbox"/> CLAY BITS</td> <td><input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL</td> </tr> <tr> <td><input checked="" type="checkbox"/> CME-55</td> <td><input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER</td> <td>CORE SIZE:</td> </tr> <tr> <td><input type="checkbox"/> CME-550</td> <td><input type="checkbox"/> 8" HOLLOW AUGERS</td> <td><input type="checkbox"/> B _____ <input type="checkbox"/> H _____</td> </tr> <tr> <td><input type="checkbox"/> VANE SHEAR TEST</td> <td><input type="checkbox"/> HARD FACED FINGER BITS</td> <td><input type="checkbox"/> N _____</td> </tr> <tr> <td><input type="checkbox"/> PORTABLE HOIST</td> <td><input type="checkbox"/> TUNG-CARBIDE INSERTS</td> <td>HAND TOOLS:</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER</td> <td><input type="checkbox"/> POST HOLE DIGGER</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE _____ * STEEL TEETH</td> <td><input type="checkbox"/> HAND AUGER</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> TRICONE _____ * TUNG-CARB.</td> <td><input type="checkbox"/> SOUNDING ROD</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/> CORE BIT</td> <td><input type="checkbox"/> VANE SHEAR TEST</td> </tr> <tr> <td><input type="checkbox"/></td> <td><input checked="" type="checkbox"/> 3-1/4" HOLLOW STEM AUGERS</td> <td><input checked="" type="checkbox"/> PROBE ROD</td> </tr> </table>										DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:	<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL	<input checked="" type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:	<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> B _____ <input type="checkbox"/> H _____	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> N _____	<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:	<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER	<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER	<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD	<input type="checkbox"/>	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/>	<input checked="" type="checkbox"/> 3-1/4" HOLLOW STEM AUGERS	<input checked="" type="checkbox"/> PROBE ROD	<table border="1"> <tr> <th>PLASTICITY INDEX (PI)</th> <th>DRY STRENGTH</th> </tr> <tr> <td>NON PLASTIC 0-5</td> <td>VERY LOW</td> </tr> <tr> <td>SLIGHTLY PLASTIC 6-15</td> <td>SLIGHT</td> </tr> <tr> <td>MODERATELY PLASTIC 16-25</td> <td>MEDIUM</td> </tr> <tr> <td>HIGHLY PLASTIC 26 OR MORE</td> <td>HIGH</td> </tr> </table>										PLASTICITY INDEX (PI)	DRY STRENGTH	NON PLASTIC 0-5	VERY LOW	SLIGHTLY PLASTIC 6-15	SLIGHT	MODERATELY PLASTIC 16-25	MEDIUM	HIGHLY PLASTIC 26 OR MORE	HIGH	<table border="1"> <tr> <th>FRACTURE SPACING</th> <th>BEDDING</th> </tr> <tr> <td>VERY WIDE MORE THAN 10 FEET</td> <td>VERY THICKLY BEDDED 4 FEET</td> </tr> <tr> <td>WIDE 3 TO 10 FEET</td> <td>THICKLY BEDDED 1.5 - 4 FEET</td> </tr> <tr> <td>MODERATELY CLOSE 1 TO 3 FEET</td> <td>THINLY BEDDED 0.16 - 1.5 FEET</td> </tr> <tr> <td>CLOSE 0.16 TO 1 FOOT</td> <td>VERY THINLY BEDDED 0.03 - 0.16 FEET</td> </tr> <tr> <td>VERY CLOSE LESS THAN 0.16 FEET</td> <td>THICKLY LAMINATED 0.008 - 0.03 FEET</td> </tr> <tr> <td></td> <td>THINLY LAMINATED < 0.008 FEET</td> </tr> </table>										FRACTURE SPACING	BEDDING	VERY WIDE MORE THAN 10 FEET	VERY THICKLY BEDDED 4 FEET	WIDE 3 TO 10 FEET	THICKLY BEDDED 1.5 - 4 FEET	MODERATELY CLOSE 1 TO 3 FEET	THINLY BEDDED 0.16 - 1.5 FEET	CLOSE 0.16 TO 1 FOOT	VERY THINLY BEDDED 0.03 - 0.16 FEET	VERY CLOSE LESS THAN 0.16 FEET	THICKLY LAMINATED 0.008 - 0.03 FEET		THINLY LAMINATED < 0.008 FEET																									
DRILL UNITS:	ADVANCING TOOLS:	HAMMER TYPE:																																																																																																																							
<input type="checkbox"/> CME-45C	<input type="checkbox"/> CLAY BITS	<input checked="" type="checkbox"/> AUTOMATIC <input type="checkbox"/> MANUAL																																																																																																																							
<input checked="" type="checkbox"/> CME-55	<input type="checkbox"/> 6" CONTINUOUS FLIGHT AUGER	CORE SIZE:																																																																																																																							
<input type="checkbox"/> CME-550	<input type="checkbox"/> 8" HOLLOW AUGERS	<input type="checkbox"/> B _____ <input type="checkbox"/> H _____																																																																																																																							
<input type="checkbox"/> VANE SHEAR TEST	<input type="checkbox"/> HARD FACED FINGER BITS	<input type="checkbox"/> N _____																																																																																																																							
<input type="checkbox"/> PORTABLE HOIST	<input type="checkbox"/> TUNG-CARBIDE INSERTS	HAND TOOLS:																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> CASING <input type="checkbox"/> W/ ADVANCER	<input type="checkbox"/> POST HOLE DIGGER																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * STEEL TEETH	<input type="checkbox"/> HAND AUGER																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> TRICONE _____ * TUNG-CARB.	<input type="checkbox"/> SOUNDING ROD																																																																																																																							
<input type="checkbox"/>	<input type="checkbox"/> CORE BIT	<input type="checkbox"/> VANE SHEAR TEST																																																																																																																							
<input type="checkbox"/>	<input checked="" type="checkbox"/> 3-1/4" HOLLOW STEM AUGERS	<input checked="" type="checkbox"/> PROBE ROD																																																																																																																							
PLASTICITY INDEX (PI)	DRY STRENGTH																																																																																																																								
NON PLASTIC 0-5	VERY LOW																																																																																																																								
SLIGHTLY PLASTIC 6-15	SLIGHT																																																																																																																								
MODERATELY PLASTIC 16-25	MEDIUM																																																																																																																								
HIGHLY PLASTIC 26 OR MORE	HIGH																																																																																																																								
FRACTURE SPACING	BEDDING																																																																																																																								
VERY WIDE MORE THAN 10 FEET	VERY THICKLY BEDDED 4 FEET																																																																																																																								
WIDE 3 TO 10 FEET	THICKLY BEDDED 1.5 - 4 FEET																																																																																																																								
MODERATELY CLOSE 1 TO 3 FEET	THINLY BEDDED 0.16 - 1.5 FEET																																																																																																																								
CLOSE 0.16 TO 1 FOOT	VERY THINLY BEDDED 0.03 - 0.16 FEET																																																																																																																								
VERY CLOSE LESS THAN 0.16 FEET	THICKLY LAMINATED 0.008 - 0.03 FEET																																																																																																																								
	THINLY LAMINATED < 0.008 FEET																																																																																																																								
COLOR										<table border="1"> <tr> <th>INDURATION</th> </tr> <tr> <td>FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.</td> </tr> <tr> <td>FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.</td> </tr> <tr> <td>MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.</td> </tr> <tr> <td>INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.</td> </tr> <tr> <td>EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</td> </tr> </table>										INDURATION	FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.	EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	BENCH MARK; ELEVATIONS FROM PROVIDED ELECTRONIC FILE "R5742_merged.tin"										NOTES: F.I.A.D. - FILLED IMMEDIATELY AFTER DRILLING																																																																																					
INDURATION																																																																																																																									
FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.																																																																																																																									
FRIABLE RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.																																																																																																																									
MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.																																																																																																																									
INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.																																																																																																																									
EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.																																																																																																																									
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.																																																																																																																									

09/08/19

See Sheet 1-A For Index of Sheets
See Sheet 1-B For Conventional Symbols



VICINITY MAP

N.T.S.

STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

CLAY COUNTY

LOCATION: NC 175 FROM GEORGIA STATE LINE
TO US 64

TYPE OF WORK: IMPROVEMENT - ALIGNMENT, LANE WIDENING,
SHOULDER WIDENING, CULVERT & DRAINAGE


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5742	3	107
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
46325.1.D.1	STP-0175(8)	PE	
46325.2.1		RW	



R/W PLANS SUBMITTAL
DATE: 6-05-17

TIP PROJECT: R-5742

CONTRACT:



BEGIN TIP PROJECT R-5742
-L- Sta. 10 + 75.00

END TIP PROJECT R-5742
-L- Sta. 229 + 76.39

BEGIN CONSTRUCTION
TIP PROJECT R-5742
-L- STA. 183 + 76.08

END CONSTRUCTION
TIP PROJECT R-5742
-L- STA. 172 + 00.00

BEGIN -DET- STA. 10+00.00


END -DET- STA. 27+76.73

NOTES:

- CLEARING AND GRUBBING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD II.
- THIS PROJECT IS NOT WITHIN ANY MUNICIPAL BOUNDARIES.

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

GRAPHIC SCALES



DESIGN DATA

ADT 2012 = 2,100
ADT 2030 = 3,950
DHV = %
D = %
T = 6.4 % *
V = 50 MPH
* (TTST 5.2% + DUALS 1.2%)
CLASSIFICATION:
RURAL MAJOR COLLECTOR

PROJECT LENGTH

ROADWAY LENGTH TIP PROJECT R-5742.....3.925 MILES
TOTAL LENGTH TIP PROJECT R-5742.....3.925 MILES



RUMMEL, KLEPPER & KAHL, LLP
900 RIDGEFIELD DRIVE, SUITE 350
RALEIGH, NORTH CAROLINA 27609
NC LICENSE NO. E-0112
1-888-521-4455 OR 919-878-9560

FOR
DIVISION OF HIGHWAYS

2012 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE:
MAY 22, 2017

LETTING DATE:
JANUARY 15, 2019

B. KEITH SKINNER, P.E.
PROJECT ENGINEER

BRANDON McINNIS, P.E.
PROJECT DESIGN ENGINEER


HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.

ROADWAY DESIGN
ENGINEER

SIGNATURE: _____ P.E.

DIVISION OF HIGHWAYS
STATE OF NORTH CAROLINA



STATE HIGHWAY DESIGN ENGINEER

9/18/2018 R:\Geotech\CADD_Geotech\PlanPr of R5742_GEO_inv_003.dgn msnyder



September 18, 2018

WBS Number: 46325.1.D.1

TIP Number: R-5742

F.A. Number: STP-0175(8)

County: Clay

Description: NC 175 Widening from Georgia State Line to US 64

Subject: Roadway Subsurface Inventory Report

PROJECT DESCRIPTION

The project begins at the North Carolina-Georgia state line and extends approximately 4.2 miles north to US 64 in Clay County, North Carolina. The project consists of realigning/widening and improvements of existing NC 175. An approximately 0.22-mile portion of the project corridor was previously upgraded with the replacement of Bridge #11 over Chatuge Lake on NC 175 (TIP No. B-4733).

Seven retaining walls are proposed along the project corridor and are located as follows:

- Retaining Wall #1: -L- Sta. 111+50, 22' LT to -L- Sta. 115+00, 22' LT (fill wall)
- Retaining Wall #2: -L- Sta. 111+64, 22' RT to -L- Sta. 114+10, 22' RT (fill wall)
- Retaining Wall #3: -L- Sta. 116+17, 22' LT to -L- Sta. 117+00, 22' LT (fill wall)
- Retaining Wall #4: -L- Sta. 119+00, 22' LT to -L- Sta. 126+00, 22' LT (fill wall)
- Retaining Wall #5: -L- Sta. 160+00, 19' LT to -L- Sta. 160+50, 19' LT (fill wall)
- Retaining Wall #6: -L- Sta. 163+72, 63' RT to -L- Sta. 165+99, 25' RT (cut wall)
- Retaining Wall #7: -L- Sta. 168+25, 25' RT to -L- Sta. 170+82, 25' RT (cut wall)

A CME 55 drill rig with an automatic hammer was used for the geotechnical investigation during June and July of 2017. Standard Penetration Tests (SPT) were performed and soil samples were collected for visual classification and laboratory testing. Bulk samples were collected from select proposed excavation areas for laboratory testing.

The following alignments were investigated. Selected cross sections of these alignments are included in this report.

<u>Line</u>	<u>Stations (±)</u>
-L-	10+75 – 172+00
-L-	183+76 – 229+76
-DET-	11+04 – 26+75

AREAS OF SPECIAL GEOTECHNICAL INTEREST

Alluvial Soils: The following areas contain alluvial soils:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	33+75 – 34+50	LT & RT
-L-	111+75 – 114+35	LT & RT
-L-	155+50 – 157+25	LT & RT
-L-	208+60 – 211+25	LT & RT

Soft, Loose and/or Wet Soils: The following areas contain relatively soft or loose and/or wet soils:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	23+00 – 25+00	LT & RT
-L-	27+00 – 34+50	LT & RT
-L-	42+00 – 46+00	LT & RT
-L-	48+00 – 60+00	LT & RT
-L-	72+50 – 95+00	LT & RT
-L-	116+50 – 126+00	LT & RT
-L-	142+00 – 145+00	LT & RT
-L-	155+00 – 161+00	LT & RT
-L-	167+00 – 171+00	LT & RT
-L-	209+00 – 212+00	LT & RT

Highly Plastic Soils: The following areas contain highly plastic soils with plasticity indices (PI) greater than 25 within proposed cut sections or greater than 35 within 3-ft of subgrade:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	12+00 – 16+25	LT & RT
-L-	24+75 – 31+75	LT & RT
-L-	72+25 – 81+00	LT & RT

Weathered Rock: The following areas contain weathered rock above or within six (6) feet of proposed grade:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	110+00 – 111+50	RT
-L-	169+00 – 171+00	RT
-L-	185+00 – 189+75	LT & RT
-L-	190+25 – 193+75	RT
-L-	201+75 – 202+75	RT



Crystalline Rock: The following areas contain crystalline rock above or within six (6) feet of proposed grade:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	185+00 – 189+75	LT & RT
-L-	190+25 – 192+75	RT
-L-	202+75 – 205+00	LT & RT

Groundwater: The following areas contain groundwater within six (6) feet of the proposed grade:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	30+00 – 32+50	LT & RT
-L-	43+00 – 45+00	LT & RT
-L-	51+00 – 53+00	LT & RT
-L-	72+50 – 75+00	LT & RT
-L-	82+00 – 84+00	LT & RT
-L-	87+00 – 90+00	LT & RT
-L-	214+00 – 217+00	LT & RT

The following areas contain groundwater within three (3) feet of the existing grade:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	30+00 – 32+50	LT
-L-	43+00 – 45+00	LT & RT
-L-	51+00 – 53+00	LT & RT
-L-	72+50 – 75+00	LT & RT
-L-	116+50 – 118+00	LT & RT
-L-	120+00 – 121+00	LT
-L-	155+50 – 159+00	LT & RT

PHYSIOGRAPHY AND GEOLOGY

The project is located within the Blue Ridge Physiographic Province. The project corridor is comprised of a rural to subdivision setting. Portions of the project are adjacent to Chatuge Lake. A portion of the existing alignment consists of a causeway built over Lake Chatuge from approximately -L- 111+50 to 116+50. The general topography of the site consists of mountainous to rolling terrain with moderately to steeply sloping hillsides.

The project is located within the Blue Ridge Belt Litho-Tectonic Unit, specifically the Ocoee Supergroup and Great Smokey Group of Middle to Late Proterozoic Era (Geologic Map of North Carolina, 1985). The overlying residual soils are a result of physical and chemical weathering of the underlying parent bedrock.

SOIL PROPERTIES

Soils encountered during the geotechnical investigation are separated into three (3) categories based on origin. The origins consist of roadway embankment, alluvial soils and residual soils.

Roadway Embankment: Materials interpreted as roadway embankment were encountered within the limits of the existing NC 175 alignment. The roadway embankment generally consisted of loose to dense, silty fine to coarse SAND (A-1-b, A-2-4) and soft to stiff, sandy SILT (A-4) and silty CLAY (A-6). The thickness of the encountered roadway embankment varied up to 13.5 feet.

Alluvial Soils: Alluvial soils were typically associated with drainage features or areas where creeks previously crossed the proposed alignment. Alluvial soils were also encountered in areas within the floodplain of Lake Chatuge. Alluvial soils generally consisted of very soft to medium stiff, silty and sandy slightly to highly plastic CLAY (A-6, A-7-5 and A-7-6).

Residual Soils: Soils classified as residual soils generally consisted of loose to very dense, clayey and silty fine to coarse SAND (A-1-b, A-2-4, A-2-5, A-2-6) and soft to hard, sandy SILT (A-4, A-5) and slightly to highly plastic silty CLAY (A-6, A-7-5, A-7-6). Varying amounts of mica and rock fragments were noted within soils interpreted as residual soils.

ROCK PROPERTIES

Weathered Rock: Weathered rock was encountered in ten (10) borings at elevations ranging from 1912.2 to 2011.0. Weathered rock was generally encountered within the northern portion of the project site.

Crystalline Rock: Crystalline rock is defined as auger refusal or SPT refusal with penetration by split spoon of less than or equal to 0.1 feet per 60 blows. Crystalline rock was encountered in eight (8) borings at elevations ranging from 1919.9 to 1962.1. Crystalline rock was generally encountered within the northern portion of the project site. Parent bedrock encountered at the project site is Biotite Gneiss and Amphibolite. Scattered exposed crystalline rock in existing cut slopes is present within the following areas:

<u>Line</u>	<u>Stations (±)</u>	<u>Offset</u>
-L-	186+50 – 191+25	LT & RT

GROUNDWATER

Groundwater was encountered during drilling operations (0-hr reading) within twenty-nine (29) borings at elevations ranging from 1913.2 to 1964.6. Static (24-hr reading) measurements were recorded within twenty-eight (28) borings at elevations ranging from 1925.2 to 1985.3.



Prepared by,

Matthew R. Snyder, P.E.
Project Engineer, Geotechnical
Registered, North Carolina 044566


Appendix A

Bulk Samples


The following bulk samples were collected from cut sections for laboratory testing:

Sample No.	Line	Station	Offset	Depth (ft)	Test(s) Performed
S-1	-L-	104+35	49' RT	0.0 – 10.0	Standard Proctor, California Bearing Ratio
S-2	-L-	137+65	62' LT	0.0 – 10.0	Standard Proctor, California Bearing Ratio
S-3	-L-	170+00	37' RT	0.0 – 10.0	Standard Proctor, California Bearing Ratio

8/17/09



PROJECT REFERENCE NO. <i>R-5742</i>		SHEET NO. 4	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER		
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



MATCHLINE -L- STA. 22+50 SEE SHEET 5

APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :

RK&K



RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEBLVD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

9/18/2018 R:\Geotech\CADD_GEO\TECH\PlanProf\AR5742_GEO_inv_004.dgn

8/17/09

R:\Geotech\CADD_GEO\TECH\P1onProf\AR5742_GEO_rv_005.dgn
msander

PROJECT REFERENCE NO. R-5742		SHEET NO. 5	
R/W SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



MATCHLINE
-L- STA. 22 + 50
SEE SHEET 4



MATCHLINE -L- STA. 36 + 50
SEE SHEET 6

PAVEMENT REMOVAL

PLANS PREPARED BY :
RK&K
RUMMEL, KLEPPER & KAHL, LLP
900 RIDGEFIELD DRIVE SUITE 350
RALEIGH, NORTH CAROLINA 27609-3960
NC LICENSE NO. F-0112 • (919) 878-9560

8/17/09

PROJECT REFERENCE NO. <i>R-5742</i>		SHEET NO. 7	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			




9/18/2018
 R:\Geotech\CADD_GEO\TECH\PionProf\AR5742_GEO.rvt_007.dgn
 asunder

PLANS PREPARED BY :
RK&K
 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

8/17/09

PROJECT REFERENCE NO. <i>R-5742</i>		SHEET NO. <i>8</i>	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



MATCHLINE -L- STA. 64+50 SEE SHEET 7

-L- STA. 78+50 MATCHLINE SEE SHEET 9

FLOYD R. SHOOK
FAYE I. SHOOK
AB LIVING TRUST
PARCEL # 4465
DB 334 PG 53

PHILLIP HOLLIFIELD
MAYBELLE HOLLIFIELD
PARCEL # 2251
DB 49 PG 130

EMERALD BAY CAPITAL
PARCEL # 2429
DB 376 PG 220

EMERALD BAY CAPITAL
PARCEL # 2158
DB 376 PG 220

SCOTT NEWTON
PARCEL # 2437
DB 382 PG 64

JAMES ALLEN
PARCEL # 1933
DB 393 PG 236

JAMES MITCHELL NICHOLS
PARCEL # 17099
DB 205 PG 29

JAMES MITCHELL NICHOLS
PARCEL # 2638
DB 205 PG 29

JAMES MITCHELL NICHOLS
SUSAN W. NICHOLS
PARCEL # 16062
DB 283 PG 193

ROBERT HOLLIFIELD
RUTH HOLLIFIELD
PARCEL # 2253
DB 100 PG II

GARY NICHOLS
PARCEL # 4311
DB 205 PG 298

JERRY L. MORGAN
PHYLLIS J. MORGAN
PARCEL # 4677
DB 344 PG 63

ROBERT HOLLIFIELD
PARCEL # 2252
PLAT 4 SLIDE I238
DB 354 PG 232

RICHARD LEE CLINE & JENNIFER
SUTHERLAND
PARCEL # 2254
DB III PG 110

APPROXIMATE LOCATION OF EXISTING
STRUCTURE BASED ON AERIAL IMAGERY.



PLANS PREPARED BY :

RUMMEL, KLEPPER & KAHL, LLP
900 RIDGEFIELD DRIVE SUITE 350
RALEIGH, NORTH CAROLINA 27609-3960
NC LICENSE NO. F-0112 • (919) 878-9560

9/18/2018
R:\Geotech\CADD_GEO\TECH\PlanProf\AR5742_GEO_inv_008.dgn

8/17/09

PROJECT REFERENCE NO. R-5742		SHEET NO. 9	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			





9/18/2018
 R:\Geotech\CADD_GEO\TECH\Plan\Prof\AR5742_GEO.rvt_009.dgn
 msauder

PLANS PREPARED BY :

RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

8/17/09

PROJECT REFERENCE NO. R-5742		SHEET NO. 10	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



MATCHLINE -L- STA. 92+50 SEE SHEET 9

MATCHLINE -L- STA. 106+50 SEE SHEET 11



APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :
RK&K
 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

9/18/2018 R:\Geotech\CADD_GEO\TECH\Plan\Prof\AR5742_GEO_inv_010.dgn

8/17/09

PROJECT REFERENCE NO. R-5742		SHEET NO. II	
R/W SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



MARVIN HOWELL
MCCRACKEN
PARCEL # 7345
DB 211 PG 13

DONALD E. MOORE
LINDA K. MOORE
PARCEL # 2118
DB 193 PG 269

BEGIN PROPOED
RETAINING WALL
-L- STA. 113+64.00

HAROLD R. WEST
PARCEL # 5737
DB 141 PG 9

HUGH WILLIAMS
PATSY WILLIAMS
PARCEL # 5345
DB 139 PG 73

ROBERT S. PENLAND
PARCEL # 4348
DB 64 PG 227

MARGARET
DELENIA
P. SEWELL
PARCEL # 4455
DB 380 PG 1

APPROXIMATE LOCATION OF EXISTING
STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :



RK&K

RUMMEL, KLEPPER & KAHL, LLP
900 RIDGEFIELD DRIVE SUITE 350
RALEIGH, NORTH CAROLINA 27609-3960
NC LICENSE NO. F-0112 • (919) 878-9560

9/18/2018
R:\Geotech\CADD_GEO\TECH\PionProf\AR5742_GEO.in\011.dgn
msunder

8/17/08

PROJECT REFERENCE NO. R-5742		SHEET NO. 12	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



MATCHLINE -L- STA. 121+00
SEE SHEET 11

MATCHLINE -L- STA. 135+25
SEE SHEET 13


APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :
RK&K
 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

9/18/2018
 R:\Geotech\CADD_GEO\TECH\PlanProf\AR5742_GEO_inv_012.dgn
 msander

8/17/09

PROJECT REFERENCE NO. R-5742		SHEET NO. 13	
R/W SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			





9/18/2018
 R:\Geotech\CADD_Geotech\PlanProf\AR5742_GEO_inv_013.dgn
 msauder

PLANS PREPARED BY :
RK&K
 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

8/17/09

PROJECT REFERENCE NO. R-5742		SHEET NO. 14	
R/W SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



9/18/2018
 R:\Geotech\CADD_GEO\TECH\PionProf\AR5742_GEO_inv_014.dgn
 asunder


APPROXIMATE LOCATION OF EXISTING
 STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :


 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

8/17/09

PROJECT REFERENCE NO. R-5742		SHEET NO. 15	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



LAKE CHATUGE



APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :



RK&K

RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

9/18/2018
 R:\Geotech\CADD_GEO\TECH\Plan\Prof\AR5742_GEO_inv_015.dgn
 mander

8/17/09

PROJECT REFERENCE NO. <i>R-5742</i>		SHEET NO. <i>16</i>	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			





9/18/2018
 R:\Geotech\CADD_Geotech\Plan\Prof\15742_GEO_inv_016.dgn
 asunder

APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :
RK&K
 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560

8/17/09

PROJECT REFERENCE NO. R-5742		SHEET NO. 17	
R/W SHEET NO.			
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER		
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			




9/18/2018
 R:\Geotech\CADD_GEO\TECH\PionProf\AR5742_GEO_mv_017.dgn
 asunder

APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :
RK&K
 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560


8/17/08



PROJECT REFERENCE NO. R-5742		SHEET NO. 18	
RW SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			

MATCHLINE -L- STA. 203+00 SEE SHEET 17

MATCHLINE -L- STA. 217+00 SEE SHEET 19



APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :


RK&K

RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560


9/18/2018 R:\Geotech\CADD_Geotech\P1onProf\AR5742_GEO Inv_018.dgn

8/17/09

PROJECT REFERENCE NO. <i>R-5742</i>		SHEET NO. <i>19</i>	
R/W SHEET NO.			
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION			
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			



MATCHLINE -L- STA. 217 + 00 SEE SHEET 18





9/18/2018
 R:\Geotech\CADD_GEO\TECH\PlanProf\AR5742_GEO_rvw_019.dgn
 msander

APPROXIMATE LOCATION OF EXISTING STRUCTURE BASED ON AERIAL IMAGERY.

PLANS PREPARED BY :


 RUMMEL, KLEPPER & KAHL, LLP
 900 RIDGEFIELD DRIVE SUITE 350
 RALEIGH, NORTH CAROLINA 27609-3960
 NC LICENSE NO. F-0112 • (919) 878-9560




11 + 50.00

SOIL TEST RESULTS


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-24	12 LT	10+71	3.5-5.0	A-2-4(0)	29	3	32.2	35.5	9.0	23.3	64.3	52.2	23.7	14.3	-




10 + 50.00




9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO_xsi.L.dgn
msjgdr







SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	- 10 -	- 40 -	- 200 -		
SS-19	6 LT.	13+70	0.5-2.0	A-7-5(34)	76	26	3.3	5.6	45.8	45.3	98.4	96.3	91.4	42.2	-




9/18/2018
 R:\Geotech\CADD\CADD\CADD\R5742_050_xsi_L.dgn
 msjgder





9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_050_xsi.L.dgn
msnyder




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-17	7 LT.	16+50	8.5-10.0	A-5(1)	50	3	16.2	47.1	23.8	12.9	99.6	91.8	47.8	34.1	-






24 + 50.00


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-125	59 RT	18+27	3.5-5.0	A-5(0)	48	NP	23.6	48.2	17.6	10.6	96.3	83.9	36.6	9.1	-
SS-12	15 LT	22+75	6.5-8.0	A-5(0)	42	NP	23.5	48.1	17.9	10.5	95.7	82.9	36.3	27.6	-



23 + 00.00



18 + 50.00




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-122	15 LT	25+73	6.5-8.0	A-7-5(38)	86	31	4.2	11.3	24.4	60.1	100	97.8	87.5	58.6	-

1970
1960
1950

- (A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, FINE TO COARSE SAND, MOIST
- (B) RESIDUAL: BROWN, LOOSE, SILTY FINE TO COARSE SAND, TRACE ROCK FRAGMENTS, MOIST
- (C) RESIDUAL: ORANGE-TAN, STIFF, CLAYEY, FINE TO COARSE SANDY SILT, MOIST

EXISTING GROUND SURFACE



RESIDUAL: ORANGE-TAN, SOFT TO MEDIUM STIFF, FINE SANDY, HIGHLY PLASTIC SILTY CLAY, MICACEOUS, SAPROLITIC, MOIST

26 + 00.00


1980
1970
1960
1950

- (A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, FINE TO COARSE SAND, MOIST
- (B) RESIDUAL: BROWN, LOOSE, SILTY FINE TO COARSE SAND, TRACE ROCK FRAGMENTS, MOIST
- (C) RESIDUAL: ORANGE-TAN, STIFF, CLAYEY, FINE TO COARSE SANDY SILT, MOIST

L: 25+75 LT
25+73
15' LT

SS-122

EXISTING GROUND SURFACE



RESIDUAL: ORANGE-TAN, SOFT TO MEDIUM STIFF, FINE SANDY, HIGHLY PLASTIC SILTY CLAY, MICACEOUS, SAPROLITIC, MOIST

DRY (6/17)


FIAD

25 + 50.00

1970
1960
1950

- (A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, FINE TO COARSE SAND, MOIST
- (B) RESIDUAL: BROWN, LOOSE, SILTY FINE TO COARSE SAND, TRACE ROCK FRAGMENTS, MOIST
- (C) RESIDUAL: ORANGE-TAN, STIFF, CLAYEY, FINE TO COARSE SANDY SILT, MOIST

EXISTING GROUND SURFACE



RESIDUAL: ORANGE-TAN, SOFT TO MEDIUM STIFF, FINE SANDY, HIGHLY PLASTIC SILTY CLAY, MICACEOUS, SAPROLITIC, MOIST





25 + 00.00



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


(A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, FINE TO COARSE SAND, MOIST
 (B) RESIDUAL: BROWN, MEDIUM STIFF, FINE SANDY SILT, TRACE ROCK FRAGMENTS, MOIST



RESIDUAL: ORANGE-TAN, SOFT TO MEDIUM STIFF, FINE TO COARSE SANDY, HIGHLY PLASTIC SILTY CLAY, SAPROLITIC, MOIST TO WET

30 + 00.00

(A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, FINE TO COARSE SAND, MOIST
 (B) RESIDUAL: BROWN, MEDIUM STIFF, FINE SANDY SILT, TRACE ROCK FRAGMENTS, MOIST




RESIDUAL: TAN, GRAY, ORANGE, SOFT TO MEDIUM STIFF, FINE TO COARSE SANDY, HIGHLY PLASTIC CLAY, TRACE ROCK FRAGMENTS, MOIST

29 + 50.00

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-117	19 LT	28+76	3.5-5.0	A-7-5(18)	81	41	12.9	24.1	6.9	56.1	77.8	73.4	51.6	52.1	-


(A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, FINE TO COARSE SAND, MOIST
 (B) RESIDUAL: BROWN, MEDIUM STIFF, FINE SANDY SILT, TRACE ROCK FRAGMENTS, MOIST



29 + 00.00


(A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, FINE TO COARSE SAND, MOIST
 (B) RESIDUAL: BROWN, MEDIUM STIFF, FINE SANDY SILT, TRACE ROCK FRAGMENTS, MOIST

EXISTING GROUND SURFACE




RESIDUAL: TAN, GRAY, ORANGE, SOFT TO MEDIUM STIFF, FINE TO COARSE SANDY, HIGHLY PLASTIC CLAY, TRACE ROCK FRAGMENTS, MOIST


28 + 50.00




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-134	1 RT	31+73	6.5-8.0	A-7-5(53)	99	49	3	15	33.3	48.7	99.7	98.7	86.3	80.9	-






SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-3	48 RT	33+37	6.0-7.5	A-7-5(40)	83	40	6.1	16.4	40	37.5	99.9	97.5	82.3	68.9	-



9/18/2018 R:\Geotech\CADD\CADD_GEOTECH\SSC\R5742_050_xsi_L.dgn msjgdr

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-8	53 RT	34+20	6.5-8.0	A-2-7(0)	44	11	34.5	34.4	12.2	18.9	79.7	61.8	29.7	47.9	-
SS-139	1 RT	34+18	8.5-10.0	A-4(0)	25	NP	8.3	53.7	20.5	17.5	99.8	98.0	46.9	33.5	-
SS-142	19 LT	37+73	0.0-1.5	A-7-5(16)	53	22	9.6	25	16.8	48.6	99.4	95.6	69.2	30.5	-



(A) RESIDUAL: RED-BROWN, MEDIUM STIFF, FINE SANDY, MODERATELY PLASTIC SILTY CLAY, MOIST

L 37+75 LT
37+73
19' LT
SS-142

RESIDUAL: RED, ORANGE, BROWN, STIFF, FINE TO COARSE SANDY SILT, MICACEOUS, SAPROLITIC, MOIST

37 + 50.00

(A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM STIFF, FINE SANDY SILT, TRACE FINE GRAVEL, MOIST

(B) ALLUVIAL: BROWN, VERY SOFT TO SOFT, FINE SANDY, SLIGHTLY TO HIGHLY PLASTIC SILTY CLAY AND LOOSE, SILTY, CLAYEY FINE TO COARSE SAND, MOIST TO WET


L 34+21 LT
34+18
1' RT
SS-139

L 34+21 RT
34+20
53' RT
SS-8


RESIDUAL: BROWN, ORANGE, WHITE, SOFT TO HARD, FINE SANDY SILTY, SAPROLITIC, MOIST

CRYSTALLINE ROCK: AMPHIBOLITE



34 + 00.00




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10"	40"	200"		
SS-29	8 RT	40+75	6.5-8.0	A-7-5(13)	50	18	9.9	20.6	21.1	48.4	92.7	87.7	68.5	35.2	-
SS-206	15 LT	46+75	8.5-10.0	A-6(5)	40	17	19.7	31.4	16	32.9	89.4	79.9	48.0	28	-
SS-199	16 LT	48+50	8.5-10.0	A-7-5(15)	68	20	9.6	32.4	28.7	29.3	99.7	95.8	65.5	87.3	-




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-192	25 LT	51+75	3.5-5.0	A-7-6(8)	49	21	14.3	32.9	22.2	30.6	87.8	82.2	51.6	40.1	-
SS-32	6 RT	54+73	3.5-5.0	A-7-5(17)	59	15	6.5	11.2	48.1	34.2	94	89.6	80.6	66	-





- (A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM STIFF, FINE TO COARSE SANDY SILT, TRACE FINE TO MEDIUM GRAVEL, MOIST
- (B) RESIDUAL: ORANGE-TAN, VERY SOFT, FINE TO COARSE SANDY, MODERATELY PLASTIC CLAY, MOIST TO WET
- (C) RESIDUAL: ORANGE, VERY LOOSE, CLAYEY FINE TO COARSE SAND, WET






9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_0E0_xsi.L.dgn
msjgdr




SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							G-SAND	F-SAND	SILT	CLAY	-10	-40	-200		
SS-36	1 RT	57+73	3.5-5.0	A-5(2)	63	8	13.6	49.3	14.6	22.5	99.8	94.3	43.2	84.2	-

6/23/16
 9/18/2018
 R:\Geotech\CADD_GEOTECH\SSC\R5742_050_xsi_L.dgn
 mshgder




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-40	5 LT	61+75	3.5-5.0	A-7-5(11)	63	18	16.9	30.2	23.1	29.8	99.3	88.0	59.0	92.5	-



9/18/2018
 R:\Geotech\CADD_GEOTECH\XSEC\R5742_050_XSI.L.dgn
 msjgder


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-44	9 LT	64+79	3.5-5.0	A-4(0)	40	NP	34.2	25.8	22.3	17.7	100.0	76.7	45.2	55.1	-
SS-52	16 LT	70+73	3.5-5.0	A-4(0)	36	NP	22.5	38.9	25.3	13.3	100	88.0	46.3	34.4	-




9/18/2018
R:\Geotech\CADD\CADD_GEO\TECH\SSC\R5742_GEO_xsi_L.dgn
msjgder




6/23/16



9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_050_xsi.L.dgn
msjgder






SOIL TEST RESULTS



SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-211	10 RT	73+75	0.0-1.5	A-7-5(44)	95	40	4.5	14.2	32.7	48.6	97.5	95.6	83.2	72.3	-

6/23/16
 9/18/2018
 R:\Geotech\CADD_GEOTECH\SSC\R5742_050_xsi_L.dgn
 msjgdr



6/23/16
9/18/2018
R:\Geotech\CADD\CADD_GEO\TECH\SSC\R5742_GEO_xsi_L.dgn
msjgdr






77 + 50.00

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C SAND	F SAND	SILT	CLAY	10	40	200		
SS-56	4 RT	77+17	3.5-5.0	A-7-5(17)	65	22	13	19.5	20.5	47	96.1	88.6	68.5	40	-

77 + 00.00


76 + 50.00




6/23/16

9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO_XSI_L.dgn
msjgder

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	-10	-40	-200		
SS-61	7 LT	79+70	6.5-8.0	A-7-5(43)	90	38	3.8	13.8	31	51.4	100	98.7	86.6	69.6	-



9/18/2018
 R:\Geotech\CADD\CADD_GEO\TECH\SSC\R5742_GEO_xsi_L.dgn
 msjgdr



6/23/16


9/18/2018
R:\Geotech\CADD\CADD_GEOTECH\XSEC\R5742_050_XSI.L.dgn
msjgder







SOIL TEST RESULTS


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	.10	.40	.200		
SS-216	31 RT	82+70	3.5-5.0	A-7-6(6)	41	12	10.8	26	30.2	33	88.7	84.2	60.4	23.4	-
SS-67	8 LT	85+69	13.5-15.0	A-5(1)	50	NP	24.2	32.6	30.8	12.4	100	84.5	52.0	44.9	-







SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	-10	-40	-200		
SS-342	30 RT	87+50	6.5-8.0	A-5(1)	50	NP	25	27.2	29.4	18.4	99.3	83.8	53.8	50.3	-
SS-347	20 RT	90+75	0.0-1.5	A-7-6(10)	41	14	9	21	24.8	45.2	97.9	93.3	72.6	24.4	-
SS-348	20 RT	90+75	3.5-5.0	A-7-5(14)	85	19	19.4	28	26.6	26	100	91.1	58.5	71.8	-






SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-69	7 RT	97+38	3.5-5.0	A-4(0)	31	NP	19.8	41.4	24.2	14.6	100.0	91.0	45.6	26.3	-




SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-74	10' LT	100+75	6.5-8.0	A-2-4(0)	35	NP	28.6	40.3	16.3	14.8	73.7	58.9	29.1	7.3	-
S-1	49' RT	104+35	0.0-10.0	A-4(0)	32	NP	16.4	51.5	19.4	12.7	96.8	88.3	40.6	21.5	-




104 + 50.00




101 + 00.00

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-375	45 RT	111+39	3.5-5.0	A-4(0)	36	NP	9.3	57.7	16.2	16.8	100	97.7	42.8	30	-




9/18/2018
 R:\Geotech\CADD_Geotech\SSC\R5742_050_xsi_L.dgn
 msjgdr


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-79	1 RT	113+00	8.5-10.0	A-6(6)	36	12	12.7	30.1	24.8	32.4	98.1	91.5	61.5	20.7	-
SS-83	1 RT	113+00	28.5-30.0	A-5(0)	49	7	19.5	42.7	13.2	24.6	87.9	80.2	39.1	43.3	-




- (A) ROADWAY EMBANKMENT: RED-BROWN, LOOSE, SILTY FINE SAND, TRACE FINE GRAVEL, TRACE MICA, MOIST
- (B) ROADWAY EMBANKMENT: RED-BROWN, MEDIUM STIFF, FINE SANDY SILT, LITTLE MICA, TRACE FINE TO COARSE GRAVEL, MOIST
- (C) ROADWAY EMBANKMENT: BROWN, TAN, MEDIUM STIFF, FINE TO COARSE SANDY, SLIGHTLY PLASTIC SILTY CLAY, TRACE MICA, TRACE FINE GRAVEL, MOIST



9/18/2018 R:\Geotech\CADD_GEOTECH\SSC\R5742_050_xsi_L.dgn msjgder




9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_0E0_xsi_L.dgn
msjgder



SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-379	62 LT	117+07	0.0-1.5	A-6(3)	35	13	12.6	36.8	18.1	32.5	84.4	78.3	48.3	13.9	-



6/23/16
 9/18/2018
 R:\Geotech\CADD\CADD_GEO\TECH\SSC\R5742_050_xsi_L.dgn
 mshgder



6/23/16

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

1980 1980

1970 1970

1960 1960

1950 1950

1940 1940

1930 1930

1980 1980

1970 1970

1960 1960

1950 1950

1940 1940

1930 1930

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

EXISTING GROUND SURFACE

- (A) ROADWAY EMBANKMENT: RED-BROWN, STIFF, FINE SANDY SILT, TRACE FINE GRAVEL, MOIST
- (B) RESIDUAL: ORANGE-BROWN, MEDIUM STIFF, SLIGHTLY PLASTIC SILTY CLAY, MOIST

RESIDUAL: ORANGE-BROWN, STIFF, FINE SANDY SILT, TRACE ROCK FRAGMENTS, MICACEOUS, SAPROLITIC, MOIST

119 + 00.00

EXISTING GROUND SURFACE



- (A) RESIDUAL: ORANGE-BROWN, MEDIUM STIFF, SLIGHTLY PLASTIC SILTY CLAY, MOIST

RESIDUAL: ORANGE-BROWN, STIFF, FINE SANDY SILT, TRACE ROCK FRAGMENTS, MICACEOUS, SAPROLITIC, MOIST

118 + 50.00






9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO_XSI_L.dgn
msjgder



SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-87	8 LT	119+25	3.5-5.0	A-7-5(7)	45	14	8.5	34.7	16.7	40.1	93.9	89.2	59.5	22.7	-







121 + 00.00

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-392	38 LT	120+33	3.5-5.0	A-4(0)	38	NP	14.4	50.5	20.2	14.9	92.5	86.2	41.2	35.4	-




120 + 50.00




SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-399	22 LT	121+25	6.5-8.0	A-5(5)	56	7	7.1	49.2	24.7	19.0	99.7	95.8	56.7	38.9	-




9/18/2018
 R:\Geotech\CADD\CADD_GEOTECH\SSC\R5742_050_xsi_L.dgn
 mshqder




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-94	7 LT.	122+40	6.5-8.0	A-2-4(0)	34	NP	3.5	73.6	14.2	8.7	98.3	97.3	34.1	15.6	-
SS-96	7 LT.	122+40	13.5-15.0	A-2-5(0)	55	NP	20.1	60.5	12.5	6.9	100	93.8	26.9	30	-




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



SOIL TEST RESULTS


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-403	32' LT	123+13	0.0-1.5'	A-7.6(9)	42	16	10.5	29	18.6	41.9	96.7	90.9	62.5	28.5	-





150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150


2020 2010 2000 1990 1980 1970 1960 1950 1940

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-411	28 LT	124+06	6.5-8.0	A-7-5(10)	73	11	9.3	36.8	27.7	26.2	100	98.1	60.6	74.3	-




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150






SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-416	19 LT	125+25	3.5-5.0	A-4(1)	30	6	17.8	40.1	16.1	26	96.4	88.4	46.6	31.7	




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-100	6 LT.	126+39	6.5-8.0	A-4(2)	38	4	10.5	36.7	22.1	30.7	100.0	95.0	60.3	38.1	-
SS-106	7 RT.	130+19	8.5-10.0	A-4(0)	34	2	23.2	37.4	11.2	28.2	99.2	84.1	46.6	21.8	-




6/23/16
9/18/2018
R:\Geotech\CADD_GEOTECH\SSC\R5742_060_xsi_L.dgn
msjgder

6/23/16




135 + 00.00




133 + 00.00

9/18/2018
R:\Geotech\CADD_GEOTECH\ssc\R5742_060_xsi_L.dgn
msjgdr





SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-2	62 LT	137+65	0.0-10.0	A-4(0)	28	NP	18	41.2	16.3	24.5	92.4	82.7	44.8	28	-
SS-110	10 RT	140+00	6.5-8.0	A-4(0)	39	NP	18.7	52	20.5	8.8	95.4	86.6	38.2	12.1	-




(A) ROADWAY EMBANKMENT-BROWN, LOOSE, SILTY FINE SAND, TRACE FINE GRAVEL, MOIST

RESIDUAL: ORANGE-BROWN, RED-BROWN, STIFF TO VERY STIFF, FINE SANDY SILT, TRACE ROCK FRAGMENTS, MICACEOUS, SAPROLITIC, MOIST


(A) RESIDUAL: ORANGE-BROWN, SOFT, FINE SANDY, SLIGHTLY PLASTIC SILTY CLAY, MOIST

RESIDUAL: ORANGE-BROWN, RED-BROWN, WHITE, STIFF TO HARD, FINE SANDY SILT, TRACE ROCK FRAGMENTS, SAPROLITIC, MICACEOUS, MOIST



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-338	57 LT	142+26	23.5-25.0	A-5(0)	46	NP	12.7	50.3	27.4	9.6	100	97.0	48.8	32.7	-




9/18/2018
R:\Geotech\CADD\CADD_GEOTECH\SSC\R5742_0E0_xsi_L.dgn
msjgdr



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	- 10 -	- 40 -	- 200 -		
SS-113	5 LT	146+00	3.5-5.0	A-4(0)	35	NP	18.1	55	15.5	11.4	100	94.6	36.0	25.4	-
SS-309	20 RT	149+00	0.0-1.5	A-6(5)	30	11	8	36.2	19.2	36.6	97.9	94.3	60.8	19.4	-




9/18/2018
 R:\Geotech\CADD_GEO\TECH\SSC\R5742_0E0_xsi_L.dgn
 msjgder




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	-10	-40	-200		
SS-305	15 RT.	152+00	0.0-1.5	A-7-6(5)	43	18	14.8	22.7	27.4	35.1	71.7	65.2	47.4	25.4	-
SS-155	6 RT.	156+00	6.5-8.0	A-4(3)	32	8	11.6	28.1	20.8	39.5	94.4	89.5	61.0	47.3	-



9/18/2018 R:\Geotech\CADD_GEOTECH\SSC\R5742_050_xsi_L.dgn




6/23/16



9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_0E0_xsi_L.dgn
msjgder

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-302	25 LT	158+00	3.5-5.0	A-4(0)	27	NP	19.8	45.2	12.1	22.9	96.9	88.3	40.0	26.7	-
SS-293	20 LT	160+00	6.5-8.0	A-6(4)	31	11	8.3	41.6	15.7	34.4	98.8	96.4	56.9	22	-




9/18/2018
 R:\Geotech\CADD_GEOTECH\SSC\R5742_GEO_xsi_L.dgn
 msjgdr




161 + 00.00

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-297	22' LT	160+50	3.5-5.0'	A-4(0)	24	NP	14.1	44.4	14.9	26.6	97	90.3	47.7	28.3	-



160 + 50.00



(A) ROADWAY EMBANKMENT: ORANGE-BROWN, MEDIUM DENSE, SILTY FINE TO COARSE SAND, TRACE FINE TO COARSE GRAVEL, MICACEOUS, MOIST

L 164+00 .RT.
164+28
1' .RT

(18)
(58)
(26)
(70)

DRY (6/17)
FIAD

RESIDUAL: ORANGE-TAN, ORANGE-BROWN, MEDIUM DENSE TO VERY DENSE, SILTY FINE TO COARSE SAND, TRACE ROCK FRAGMENTS, MICACEOUS, SAPROLITIC, MOIST

164 + 50.00


EXISTING GROUND SURFACE

EXISTING GROUND SURFACE

RESIDUAL: ORANGE-TAN, ORANGE-BROWN, MEDIUM DENSE TO VERY DENSE, SILTY FINE TO COARSE SAND, TRACE ROCK FRAGMENTS, MICACEOUS, SAPROLITIC, MOIST


164 + 00.00

4:1 2:1




6/23/16


9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO_XSI_L.dgn
msjgder




6/23/16
9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO_XSI.L.dgn
msjgder




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-167	1 RT	166+96	6.5-8.0	A-4(6)	34	10	9	29.6	24.2	37.2	100	95.9	67.4	24.8	-




6/23/16
9/18/2018
R:\Geotech\CADD_GEOTECH\SSC\R5742_0E0_xsi_L.dgn
msjgder





9/18/2018
R:\Geotech\CADD_GEO\CADD_GEO\168+00-168+50.dgn







9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO.XSI.L.dgn
msjgder





9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO.XSI.L.DGN
msjgdb





150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-3	37 RT	170+00	0.0-10.0	A-2-4(0)	35	NP	28.3	46.1	17	8.6	98.2	79.1	33.6	24.7	-
SS-288	37 RT	170+00	8.5-10.0	A-4(0)	36	NP	21.4	41.8	12.9	23.9	100	86.6	45.4	22.6	-

2000 2000

1990 1990

1980 1980

1970 1970

1960 1960

1950 1950

1940 1940

1930 1930

1920 1920

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

EXISTING GROUND SURFACE


- (A) RESIDUAL BROWN-ORANGE, SOFT, FINE TO COARSE SANDY SILT, MOIST
- (B) RESIDUAL ORANGE-TAN, DENSE SILTY FINE TO COARSE SAND, MICACEOUS, SAPROLITIC, MOIST

RESIDUAL RED-BROWN, MEDIUM STIFF, FINE TO COARSE SANDY SILT, MOIST

WEATHERED ROCK: BIOTITE GNEISS

L 170+00. RT
170+00
37' RT.


S-3
SS-288




DRY (6/17)


170+00.00







9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_0E0_xsi_L.dgn
msjgdb






9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_050_xsi_L.dgn
msnyder







9/18/2018
R:\Geotech\CADD_GEOTECH\SSC\R5742_GEO_xsi_L.dgn
msjgdr






9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_050_xsi_L.dgn
msjgdr





6/23/16
 9/18/2018
 R:\Geotech\CADD_GEOTECH\ssc\R5742_0E0_xsi_L.dgn
 msjgdr



- (A) ROADWAY EMBANKMENT: BROWN, LOOSE, SILTY FINE TO COARSE SAND, TRACE FINE TO COARSE GRAVEL, MOIST
- (B) RESIDUAL: ORANGE-TAN, GREY, WHITE, MEDIUM DENSE TO VERY DENSE, SILTY FINE TO COARSE SAND, MICACEOUS, SAPROLITIC, MOIST
- (C) WEATHERED ROCK: AMPHIBOLITE

EXISTING GROUND SURFACE

L 189+00 RT
189+00
5' RT


2.0:1 4:1 4:1 2:1


100/0.8
60/0.1

DRY (6.1%) CRYSTALLINE ROCK: AMPHIBOLITE



FIAD

189 + 00.00






9/18/2018
R:\Geotech\CADD\CADD_GEOTECH\XSEC\R5742_050_XSI.L.dgn
msjgder




SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-175	2 LT.	190+00	3.5-5.0	A-2-4(0)	32	NP	22.3	54.6	15.8	7.3	100.0	89.0	33.2	12.3	-
SS-176	2 LT.	190+00	6.5-8.0	A-2-4(0)	39	NP	29	47.7	12.8	10.5	96	79.7	30.2	26.7	-


6/23/16



9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_050_xsi_L.dgn
msjgdr



9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_GEO_XSI.L.dgn
msjgdr



- (A) RESIDUAL: ORANGE-BROWN, MEDIUM STIFF TO VERY STIFF, FINE TO COARSE SANDY SILT, TRACE ROCK FRAGMENTS, MOIST
- (B) RESIDUAL: DARK BROWN, MEDIUM DENSE, SILTY FINE TO COARSE SAND, MOIST
- (C) WEATHERED ROCK: BIOTITE GNEISS
- (D) RESIDUAL: TAN, ORANGE-TAN, VERY DENSE, SILTY FINE TO COARSE SAND, MOIST

ROADWAY EMBANKMENT: BROWN, ORANGE-BROWN, MEDIUM DENSE, SILTY FINE TO COARSE SAND, TRACE FINE TO COARSE GRAVEL, TRACE MICA, MOIST

RESIDUAL: TAN, ORANGE-TAN, VERY DENSE, SILTY FINE TO COARSE SAND, MOIST

EXISTING GROUND SURFACE

L 192+00 RT
19+46
112' RT

6

19

15

20

100/0.8


51

60/0.1


DRY, (6/17)

CRYSTALLINE ROCK: BIOTITE GNEISS

191 + 50.00




6/23/18
9/18/2018
R:\Geotech\CADD_GEOTECH\ssr\5742_050_xsi_L.dgn
msjgdr




9/18/2018
R:\Geotech\CADD_GEOTECH\ssc\R5742_GEO_xsi.L.dgn
msjgdr



6/23/16



9/18/2018
R:\Geotech\CADD_GEOTECH\sscc\R5742_050_xsi.L.dgn
msjgdr




9/18/2018
R:\Geotech\CADD\CADD_GEOTECH\XSEC\R5742_GEO_XSI.L.dgn
msjgder




202 + 00.00

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-244	7 LT	199+50	8.5-10.0	A-4(0)	33	NP	24.9	38.9	14.8	21.4	97.9	82.8	42.7	23.2	-
SS-239	13 LT	201+17	13.5-15.0	A-4(2)	35	9	21.8	32.1	13.5	32.6	87.5	75.4	45.8	29.3	-




201 + 00.00





199 + 50.00

6/23/16




9/18/2018
R:\Geotech\CADD\CADD\CADD\R5742_050_xsi_L.dgn
msjgder




SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-264	40 LT	209+00	3.5-5.0	A-7-6(4)	42	20	22.9	31.6	9.7	35.8	82.2	71.2	40.8	32.3	-




9/18/2018 R:\Geotech\CADD_GEOTECH\SSC\R5742_050_xsi_L.dgn msj



6/23/18
9/18/2018
R:\Geotech\CADD_GEOTECH\XSEC\R5742_0E0_xsi_L.dgn
msjgder





6/23/16





9/18/2018
R:\Geotech\CADD_GEOTECH\ssc\R5742_050_xsi_L.dgn
msjgdr

SOIL TEST RESULTS


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-228	10 RT	218+00	3.5-5.0	A-5(0)	52	NP	14	49.5	25.4	11.1	100	93.2	46.9	69.2	-
SS-232	13 LT	221+00	3.5-5.0	A-5(0)	46	3	27.1	41	20.1	11.8	99.9	88.8	39.1	25.6	-



9/18/2018
R:\Geotech\CADD\CADD\SSC\R5742_050_xsi_L.dgn
msjgder



SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-187	30 RT	224+00	6.5-8.0	A-7-5(22)	75	15	2.9	20.4	36.6	40.1	100	98.8	84.1	62.5	-



9/18/2018 R:\Geotech\CADD_GEOTECH\SSC\R5742_060_xsi_L.dgn mshgder

*NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT*

SUBSURFACE INVESTIGATION

***APPENDIX A
LABORATORY RESULTS***

REFERENCE: R-5742

PROJECT: 46325

Prepared in the Office of:

RK&K RUMMEL, KLEPPER & KAHL, LLP
900 RIDGEFIELD DRIVE, SUITE 350
RALEIGH, NORTH CAROLINA 27609
NC LICENSE NO. F-0112

100

**North Carolina Department of Transportation
Division of Highways
Materials and Test Unit
Soils Laboratory**

T.I.P. ID NO.: R-5742
DESCRIPTION: NC-175 Widening

REPORT ON SAMPLES OF: SOIL FOR QUALITY

WBS No.: 46325.1.D.1
DATE SAMPLED: 6/17
SAMPLED FROM: -L-
SUBMITTED BY: M. Snyder

COUNTY: Clay
RECEIVED: 7/3/17
REPORTED: 7/17
BY: D. Jenks
Cert No. 101-02-0603

TEST RESULTS

PROJ. SAMPLE NO.	SS-3	SS-8	SS-12	SS-17	SS-19	SS-24	SS-29	SS-32	SS-36	SS-40	SS-44	SS-52	SS-56	SS-61
BORING NO.	L33+00 RT	L34+21 RT	L22+75 LT	L16+50 LT	L13+75 LT	L10+75 LT	L40+75 RT	L54+75 RT	L57+75 RT	L61+75 RT	L64+75 RT	L70+75 RT	L76+75 RT	L79+75 LT
Retained #4 Sieve %	0.0	12.4	0.3	0.0	0.3	28.5	5.9	2.6	0.0	0.0	0.0	0.0	3.1	0.0
Passing #10 Sieve %	99.9	79.7	95.7	99.6	98.4	64.3	92.7	94.0	99.8	99.3	100.0	100.0	96.1	100.0
Passing #40 Sieve %	97.5	61.8	82.9	91.8	96.3	52.2	87.7	89.6	94.3	88.0	76.7	88.0	88.6	98.7
Passing #200 Sieve %	82.3	29.7	36.3	47.8	91.4	23.7	68.5	80.6	43.2	59.0	45.2	46.3	68.5	86.6

SOIL MORTAR - 100%														
Coarse Sand Ret - #60 %	6.1	34.5	23.5	16.2	3.3	32.2	9.9	6.5	13.6	16.9	34.2	22.5	13.0	3.8
Fine Sand Ret - #270 %	16.4	34.4	48.1	47.1	5.6	35.5	20.6	11.2	49.3	30.2	25.8	38.9	19.5	13.8
Silt 0.053 - 0.010 mm %	40.0	12.2	17.9	23.8	45.8	9.0	21.1	48.1	14.6	23.1	22.3	25.3	20.5	31.0
Clay < 0.010 mm %	37.5	18.9	10.5	12.9	45.3	23.3	48.4	34.2	22.5	29.8	17.7	13.3	47.0	51.4
L.L.	83	44	42	50	76	29	50	59	63	63	40	36	65	90
P.L.	43	33	NP	47	50	26	32	44	55	45	NP	NP	43	52
P.I.	40	11	NP	3	26	3	18	15	8	18	NP	NP	22	38
AASHTO Classification	A-7-5(40)	A-2-7(0)	A-5(0)	A-5(1)	A-7-5(34)	A-2-4(0)	A-7-5(13)	A-7-5(17)	A-5(2)	A-7-5(11)	A-4(0)	A-4(0)	A-7-5(17)	A-7-5(43)
Station	33+37	34+20	22+75	16+50	13+70	10+71	40+75	54+73	57+73	61+75	64+79	70+73	77+17	79+70
Offset	48' RT	53' RT	15' LT	7' LT	6' LT	12' LT	8' RT	6' RT	1' RT	5' LT	9' LT	16' LT	4' RT	7' LT
Depth (ft)	6.0	6.5	6.5	8.5	0.5	3.5	6.5	3.5	3.5	3.5	3.5	3.5	3.5	6.5
to	7.5	8.0	8.0	10.0	2.0	5.0	8.0	5.0	5.0	5.0	5.0	5.0	5.0	8.0
Alignment	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-
Moisture Content (%)	68.9	47.9	27.6	34.1	42.2	14.3	35.2	66.0	84.2	92.5	55.1	34.4	40.0	69.6
Organic Content (%)	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT

NP = Not plastic
NT = Not tested
ND = Not Determined
CL = Centerline

Soils Engineer

101

**North Carolina Department of Transportation
Division of Highways
Materials and Test Unit
Soils Laboratory**

T.I.P. ID NO.: R-5742
DESCRIPTION: NC-175 Widening

REPORT ON SAMPLES OF: SOIL FOR QUALITY

WBS No.: 46325.1.D.1
DATE SAMPLED: 6/17
SAMPLED FROM: -L-
SUBMITTED BY: M. Snyder

COUNTY: Clay
RECEIVED: 7/3/17
REPORTED: 7/17
BY: D. Jenks
Cert No. 101-02-0603

TEST RESULTS

PROJ. SAMPLE NO.	SS-67	SS-69	SS-74	SS-79	SS-87	SS-94	SS-96	SS-100	SS-106	SS-113	SS-122	SS-125	SS-134	SS-139
BORING NO.	L85+75 LT	L97+75 RT	L100+75 LT	L113+00 RT	L119+25 LT	L122+25 LT	L122+25 LT	L126+00 LT	L130+00 RT	L146+00 LT	L25+75 LT	L18+50 LT	L31+75 LT	L34+21 LT
Retained #4 Sieve %	0.0	0.0	22.3	0.8	4.4	1.2	0.0	0.0	0.8	0.0	0.0	0.3	0.2	0.0
Passing #10 Sieve %	100.0	100.0	73.7	98.1	93.9	98.3	100.0	100.0	99.2	100.0	100.0	96.3	99.7	99.8
Passing #40 Sieve %	84.5	91.0	58.9	91.5	89.2	97.3	93.8	95.0	84.1	94.6	97.8	83.9	98.7	98.0
Passing #200 Sieve %	52.0	45.6	29.1	61.5	59.5	34.1	26.9	60.3	46.6	36.0	87.5	36.6	86.3	46.9

SOIL MORTAR - 100%														
Coarse Sand Ret - #60 %	24.2	19.8	28.6	12.7	8.5	3.5	20.1	10.5	23.2	18.1	4.2	23.6	3.0	8.3
Fine Sand Ret - #270 %	32.6	41.4	40.3	30.1	34.7	73.6	60.5	36.7	37.4	55.0	11.3	48.2	15.0	53.7
Silt 0.053 - 0.010 mm %	30.8	24.2	16.3	24.8	16.7	14.2	12.5	22.1	11.2	15.5	24.4	17.6	33.3	20.5
Clay < 0.010 mm %	12.4	14.6	14.8	32.4	40.1	8.7	6.9	30.7	28.2	11.4	60.1	10.6	48.7	17.5
L.L.	50	31	35	36	45	34	55	38	34	35	86	48	99	25
P.L.	NP	NP	NP	24	31	NP	NP	34	32	NP	55	NP	50	NP
P.I.	NP	NP	NP	12	14	NP	NP	4	2	NP	31	NP	49	NP
AASHTO Classification	A-5(1)	A-4(0)	A-2-4(0)	A-6(6)	A-7-5(7)	A-2-4(0)	A-2-5(0)	A-4(2)	A-4(0)	A-4(0)	A-7-5(38)	A-5(0)	A-7-5(53)	A-4(0)
Station	85+69	97+38	100+75	113+00	119+25	122+40	122+40	126+39	130+19	146+00	25+73	18+27	31+73	34+18
Offset	8' LT	7' RT	10' LT	1' RT	8' LT	7' LT	7' LT	6' LT	7' RT	5' LT	15' LT	59' RT	1' RT	1' RT
Depth (ft)	13.5	3.5	6.5	8.5	3.5	6.5	13.5	6.5	8.5	3.5	6.5	3.5	6.5	8.5
to	15.0	5.0	8.0	10.0	5.0	8.0	15.0	8.0	10.0	5.0	8.0	5.0	8.0	10.0
Alignment	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-
Moisture Content (%)	44.9	26.3	7.3	20.7	22.7	15.6	30.0	38.1	21.8	25.4	58.6	9.1	80.9	33.5
Organic Content (%)	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT

NP = Not plastic
NT = Not tested
ND = Not Determined
CL = Centerline

Soils Engineer

102

**North Carolina Department of Transportation
Division of Highways
Materials and Test Unit
Soils Laboratory**

T.I.P. ID NO.: R-5742
DESCRIPTION: NC-175 Widening

REPORT ON SAMPLES OF: SOIL FOR QUALITY

WBS No.: 46325.1.D.1
DATE SAMPLED: 6/17
SAMPLED FROM: -L-
SUBMITTED BY: M. Snyder

COUNTY: Clay
RECEIVED: 7/3/17
REPORTED: 7/17
BY: D. Jenks
Cert No. 101-02-0603

TEST RESULTS

PROJ. SAMPLE NO.	SS-142	SS-175	SS-176	SS-416	S-1	SS-187	SS-216	SS-239	SS-305	SS-342	SS-392	SS-399	SS-403	S-2
BORING NO.	L37+75 LT	L190+00 RT	L190+00 RT	L125+25 LT	L104+00 RT	L224+00 RT	L82+75 RT	L201+50 LT	L152+00 RT	L87+50 RT	L120+25 LT	L121+25 LT	L123+25 LT	L137+00 RT
Retained #4 Sieve %	0.2	0.0	2.8	1.8	0.6	0.0	10.2	7.9	26.8	0.1	6.8	0.1	1.6	6.3
Passing #10 Sieve %	99.4	100.0	96.0	96.4	96.8	100.0	88.7	87.5	71.7	99.3	92.5	99.7	96.7	92.4
Passing #40 Sieve %	95.6	89.0	79.7	88.4	88.3	98.8	84.2	75.4	65.2	83.8	86.2	95.8	90.9	82.7
Passing #200 Sieve %	69.2	33.2	30.2	46.6	40.6	84.1	60.4	45.8	47.4	53.8	41.2	56.7	62.5	44.8

SOIL MORTAR - 100%														
Coarse Sand Ret - #60 %	9.6	22.3	29.0	17.8	16.4	2.9	10.8	21.8	14.8	25.0	14.4	7.1	10.5	18.0
Fine Sand Ret - #270 %	25.0	54.6	47.7	40.1	51.5	20.4	26.0	32.1	22.7	27.2	50.5	49.2	29.0	41.2
Silt 0.053 - 0.010 mm %	16.8	15.8	12.8	16.1	19.4	36.6	30.2	13.5	27.4	29.4	20.2	24.7	18.6	16.3
Clay < 0.010 mm %	48.6	7.3	10.5	26.0	12.7	40.1	33.0	32.6	35.1	18.4	14.9	19.0	41.9	24.5
L.L.	53	32	39	30	32	75	41	35	43	50	38	56	42	28
P.L.	31	NP	NP	24	NP	60	29	26	25	NP	NP	49	26	NP
P.I.	22	NP	NP	6	NP	15	12	9	18	NP	NP	7	16	NP
AASHTO Classification	A-7-5(16)	A-2-4(0)	A-2-4(0)	A-4(1)	A-4(0)	A-7-5(22)	A-7-6(6)	A-4(2)	A-7-6(5)	A-5(1)	A-4(0)	A-5(5)	A-7-6(9)	A-4(0)
Station	37+73	190+00	190+00	125+25	104+35	224+00	82+70	201+17	152+00	87+50	120+33	121+25	123+13	137+65
Offset	19' LT	2' LT	2' LT	19' LT	49' RT	30' RT	31' RT	13' LT	15' RT	30' RT	38' LT	22' LT	32' LT	62' LT
Depth (ft)	0.0	3.5	6.5	3.5	0.0	6.5	3.5	13.5	0.0	6.5	3.5	6.5	0.0	0.0
to	1.5	5.0	8.0	5.0	10.0	8.0	5.0	15.0	1.5	8.0	5.0	8.0	1.5	10.0
Alignment	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-
Moisture Content (%)	30.5	12.3	26.7	31.7	21.5	62.5	23.4	29.3	25.4	50.3	35.4	38.9	28.5	28.0
Organic Content (%)	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT

NP = Not plastic
NT = Not tested
ND = Not Determined
CL = Centerline

Soils Engineer

103

**North Carolina Department of Transportation
Division of Highways
Materials and Test Unit
Soils Laboratory**

T.I.P. ID NO.: R-5742
DESCRIPTION: NC-175 Widening

REPORT ON SAMPLES OF: SOIL FOR QUALITY

WBS No.: 46325.1.D.1
DATE SAMPLED: 6/17
SAMPLED FROM: -L-
SUBMITTED BY: M. Snyder

COUNTY: Clay
RECEIVED: 7/3/17
REPORTED: 7/17
BY: D. Jenks
Cert No. 101-02-0603

TEST RESULTS

PROJ. SAMPLE NO.	SS-83	SS-110	SS-117	SS-155	SS-167	SS-199	SS-206	SS-211	SS-228	SS-232	SS-244	SS-264	SS-288	SS-293
BORING NO.	L113+00 RT	L140+00 RT	L28+75 LT	L156+00 RT	L167+00 RT	L48+50 LT	L46+75 LT	L73+75 RT	L218+00 RT	L221+00 LT	L199+50 LT	L209+00 LT	L170+00 RT	L160+00 LT
Retained #4 Sieve %	11.0	3.6	21.1	5.3	0.0	0.2	5.6	2.4	0.0	0.0	0.2	11.6	0.0	0.9
Passing #10 Sieve %	87.9	95.4	77.8	94.4	100.0	99.7	89.4	97.5	100.0	99.9	97.9	82.2	100.0	98.8
Passing #40 Sieve %	80.2	86.6	73.4	89.5	95.9	95.8	79.9	95.6	93.2	88.8	82.8	71.2	86.6	96.4
Passing #200 Sieve %	39.1	38.2	51.6	61.0	67.4	65.5	48.0	83.2	46.9	39.1	42.7	40.8	45.4	56.9

SOIL MORTAR - 100%														
Coarse Sand Ret - #60 %	19.5	18.7	12.9	11.6	9.0	9.6	19.7	4.5	14.0	27.1	24.9	22.9	21.4	8.3
Fine Sand Ret - #270 %	42.7	52.0	24.1	28.1	29.6	32.4	31.4	14.2	49.5	41.0	38.9	31.6	41.8	41.6
Silt 0.053 - 0.010 mm %	13.2	20.5	6.9	20.8	24.2	28.7	16.0	32.7	25.4	20.1	14.8	9.7	12.9	15.7
Clay < 0.010 mm %	24.6	8.8	56.1	39.5	37.2	29.3	32.9	48.6	11.1	11.8	21.4	35.8	23.9	34.4
L.L.	49	39	81	32	34	68	40	95	52	46	33	42	36	31
P.L.	42	NP	40	24	24	48	23	55	NP	43	NP	22	NP	20
P.I.	7	NP	41	8	10	20	17	40	NP	3	NP	20	NP	11
AASHTO Classification	A-5(0)	A-4(0)	A-7-5(18)	A-4(3)	A-4(6)	A-7-5(15)	A-6(5)	A-7-5(44)	A-5(0)	A-5(0)	A-4(0)	A-7-6(4)	A-4(0)	A-6(4)
Station	113+00	140+00	28+76	156+00	166+96	48+50	46+75	73+75	218+00	221+00	199+50	209+00	170+00	160+00
Offset	1' RT	10' RT	19' LT	6' RT	1' RT	16' LT	15' LT	10' RT	10' RT	13' LT	7' LT	40' LT	37' RT	20' LT
Depth (ft)	28.5	6.5	3.5	6.5	6.5	8.5	8.5	0.0	3.5	3.5	8.5	3.5	8.5	6.5
to	30.0	8.0	5.0	8.0	8.0	10.0	10.0	1.5	5.0	5.0	10.0	5.0	10.0	8.0
Alignment	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-
Moisture Content (%)	43.3	12.1	52.1	47.3	24.8	87.3	28.0	72.3	69.2	25.6	23.2	32.3	22.6	22.0
Organic Content (%)	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT

NP = Not plastic
NT = Not tested
ND = Not Determined
CL = Centerline

Soils Engineer

104

**North Carolina Department of Transportation
Division of Highways
Materials and Test Unit
Soils Laboratory**

T.I.P. ID NO.: R-5742
DESCRIPTION: NC-175 Widening

REPORT ON SAMPLES OF: SOIL FOR QUALITY

WBS No.: 46325.1.D.1
DATE SAMPLED: 6/17
SAMPLED FROM: -L-
SUBMITTED BY: M. Snyder

COUNTY: Clay
RECEIVED: 7/3/17
REPORTED: 7/17
BY: D. Jenks
Cert No. 101-02-0603

TEST RESULTS

PROJ. SAMPLE NO.	SS-302	SS-347	SS-375	SS-411	S-3	SS-192	SS-348	SS-379	SS-297	SS-309	SS-338			
BORING NO.	L158+00 LT	L90+75 RT	L111+00 RT	L124+25 LT	L170+00 RT	L51+75 LT	L90+75 RT	L117+00 LT	L160+50 LT	L149+00 RT	L143+00 LT			
Retained #4 Sieve %	2.4	0.8	0.0	0.0	0.8	11.9	0.0	13.9	2.7	1.6	0.0			
Passing #10 Sieve %	96.9	97.9	100.0	100.0	98.2	87.8	100.0	84.4	97.0	97.9	100.0			
Passing #40 Sieve %	88.3	93.3	97.7	98.1	79.1	82.2	91.1	78.3	90.3	94.3	97.0			
Passing #200 Sieve %	40.0	72.6	42.8	60.6	33.6	51.6	58.5	48.3	47.7	60.8	48.8			

SOIL MORTAR - 100%														
Coarse Sand Ret - #60 %	19.8	9.0	9.3	9.3	28.3	14.3	19.4	12.6	14.1	8.0	12.7			
Fine Sand Ret - #270 %	45.2	21.0	57.7	36.8	46.1	32.9	28.0	36.8	44.4	36.2	50.3			
Silt 0.053 - 0.010 mm %	12.1	24.8	16.2	27.7	17.0	22.2	26.6	18.1	14.9	19.2	27.4			
Clay < 0.010 mm %	22.9	45.2	16.8	26.2	8.6	30.6	26.0	32.5	26.6	36.6	9.6			
L.L.	27	41	36	73	35	49	85	35	24	30	46			
P.L.	NP	27	NP	62	NP	28	66	22	NP	19	NP			
P.I.	NP	14	NP	11	NP	21	19	13	NP	11	NP			
AASHTO Classification	A-4(0)	A-7-6(10)	A-4(0)	A-7-5(10)	A-2-4(0)	A-7-6(8)	A-7-5(14)	A-6(3)	A-4(0)	A-6(5)	A-5(0)			
Station	158+00	90+75	111+39	124+06	170+00	51+75	90+75	117+07	160+50	149+00	142+26			
Offset	25' LT	20' RT	45' RT	28' LT	37' RT	25' LT	20' RT	62' LT	22' LT	20' RT	57' LT			
Depth (ft)	3.5	0.0	3.5	6.5	0.0	3.5	3.5	0.0	3.5	0.0	23.5			
to	5.0	1.5	5.0	8.0	10.0	5.0	5.0	1.5	5.0	1.5	25.0			
Alignment	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-	-L-			
Moisture Content (%)	26.7	24.4	30.0	74.3	24.7	40.1	71.8	13.9	28.3	19.4	32.7			
Organic Content (%)	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT	NT			

NP = Not plastic
NT = Not tested
ND = Not Determined
CL = Centerline


Soils Engineer



FROEHLING & ROBERTSON, INC.

California Bearing Ratio Test Report

Load Penetration Curve




SOAKED CBR TEST RESULTS					
Results	S-1 (A)	S-1 (B)	S-2 (A)	S-2 (B)	
0.1 in Pen.	2.2	2.4	2.4	2.7	
0.2 in Pen.	3.4	3.8	3.2	3.4	
Moisture (%)	21.5	21.7	22.4	21.9	
Density (pcf)	101.6	99.0	100.3	100.9	
Final Moisture (%)	24.7	23.8	22.9	23.9	
Final Density (pcf)	99.7	101.4	100.6	99.9	
Project Information			Natural Moisture (%)		
Project Name:	R-5742 Clay County		CBR (S-1)	21.5	
Client Name:	RK&K		CBR (S-2)	28.1	
Project Number:	66V-0041		Percent Swell		
Date Received:	07/24/2017		CBR (S-1)	A	B
Project Location:	Hayesville, North Carolina		CBR (S-2)	0.500	0.350
				0.150	0.130
Sample Information			Proctor Value (AASHTO T-99)		
Sample Number	Classification		Max. Dry Density (pcf)	Optimum Moisture %	
CBR (S-1)	Dark Brown, Fine to Coarse sandy Silt with little clay		104.2	19.3	
CBR (S-2)	Dark Brown, Fine to Coarse Sandy Silt with some clay		102.4	20.4	
Sample Number	Sample Location		AASHTO	% - #200	
CBR (S-1)	L104+00 RT		A-4 (5)	40.6	
CBR (S-2)	L137+00 RT		A-4 (0)	44.8	




FROEHLING & ROBERTSON, INC.

California Bearing Ratio Test Report

Load Penetration Curve



SOAKED CBR TEST RESULTS			
Results	S-3 (A)	S-3 (B)	
0.1 in Pen.	3.8	3.8	
0.2 in Pen.	4.5	4.6	
Moisture (%)	21.1	21.1	
Density (pcf)	101.1	101.2	
Final Moisture (%)	23.0	23.4	
Final Density (pcf)	99.8	99.8	
Project Information		Natural Moisture (%)	
Project Name:	R-5742 Clay County	CBR (S-3)	24.7
Client Name:	RK&K		
Project Number:	66V-0041	Percent Swell	
Date Received:	07/26/2017	CBR (S-3)	A B
Project Location:	Hayesville, North Carolina		0.070 0.070
Sample Information		Proctor Value (AASHTO T-99)	
Sample Number	Classification	Max. Dry Density (pcf)	Optimum Moisture %
CBR (S-3)	Dark Brown, Silty Fine to Coarse SAND with trace clay	102.5	18.8
Sample Number	Sample Location	AASHTO	% - #200
CBR (S-3)	L170+00 RT	A-2-4 (0)	33.6



No.	LOCATION AND DESCRIPTION	REMARKS
○ S-1	Loc.: L104+00 RT Depth: 0.0 - 25.0 Sample No.: S-1 Dark Brown, Fine to Coarse Sandy Silt, with little clay	Sample Received on 07/03/2017. 5.5 lb Hammer 12" Drop
□ S-2	Location: L137+00 RT Sample Number: S-2 Dark Brown, Fine to Coarse Sandy SILT with some clay	Sample Received on 07/03/2017. 5.5 lb Hammer 12" Drop
△ S-3	Location: L170+00 RT Sample Number: S-3 Dark Brown, Silty Fine to Coarse SAND, with trace clay	Sample Received on 07/03/2017. 5.5 lb. Hammer 12" Drop

No.	AASHTO	LL	PI	NAT. MOIST.	OVERSIZE	%<#4=200	MAX. DRY DEN.	OPT. MOIST.
○ S-1	A-4 (5)	32	NP	21.5	%>#4=0.6	40.6 %	104.2	19.3 %
□ S-2	A-4 (0)	28	NP	28.0	%>#4=6.3	44.8 %	102.4	20.4 %
△ S-3	A-2-4 (0)	35	NP	24.7	%>#4=0.8	33.6 %	102.5	18.8 %

Sp. gr. for ZAV is an assumed value.