# This electronic collection of documents is provided for the convenience of the user and is Not a Certified Document –

The documents contained herein were originally issued and sealed by the individuals whose names and license numbers appear on each page, on the dates appearing with their signature on that page.

This file or an individual page shall not be considered a certified document.

36

INSTALL CCTV CAMERA ASSEMBLY


					I FCENID PROJECT REFERENCE NO. SHEET NO.
$\bigwedge$	INICIALL 2 WIRE CORRED CERVICE ENTRANCE CONDUCTORS	37	INSTALL CCTV CAMERA WOOD POLE —	<b>—</b> F0 <b>——</b>	LEGEND  NEW FIBER OPTIC COMMUNICATIONS CABLE  PROJECT REFERENCE NO. SHEET NO.  R-1015 SCP. 1
	INSTALL 3-WIRE COPPER SERVICE ENTRANCE CONDUCTORS		<del>-</del> -	EXI — EXI —	EXISTING COMMUNICATIONS CABLE
$\sqrt{2}$	INSTALL 4-WIRE COPPER FEEDER CONDUCTORS	38	INSTALL CCTV CAMERA METAL POLE AND FOUNDATION	REM ——REM ——	EXISTING COMMUNICATIONS CABLE TO BE REMOVED
$\overline{\bigcirc}$	INSTALL 3-WIRE COPPER FEEDER CONDUCTORS	39	INSTALL STANDARD (ELECTRICAL) JUNCTION BOX		NEW CONDUIT  EXISTING CONDUIT
\(\frac{1}{3}\)	INSTALL 3-WIKE COTTER TELDER CONDUCTORS	40	INSTALL OVERSIZED JUNCTION BOX —	— DD ——— DD ——	NEW DIRECTIONAL DRILLED CONDUIT
4	INSTALL SMFO CABLE	41	INSTALL SPECIAL OVERSIZED JUNCTION BOX	<del></del>	NEW GUARDRAIL
5	INSTALL CAT5e CABLE				NEW CHAIN LINK FENCE  EXISTING METAL POLE WITH MASTARM
$\wedge$	INSTALL FIBER OPTIC DROP CABLE	42	INSTALL WOOD POLE		NEW METAL POLE WITH MASTARM
<u> </u>	INSTALL FIBER OF TIC BROT CABLE	43	REMOVE EXISTING WOOD POLE —		EXISTING RIGHT OF WAY
<u></u>	INSTALL TRACER WIRE	44	INSTALL AERIAL GUY ASSEMBLY		NEW JUNCTION BOX EXISTING JUNCTION BOX
8	TRENCH	45	INSTALL STANDARD GUY ASSEMBLY		NEW OVERSIZED HEAVY DUTY JUNCTION BOX WITH SPLICE ENCLOSURE
	INSTALL PVC CONDUIT	$\vdash$		<u>s</u>	EXISTING OVERSIZED HEAVY DUTY JUNCTION BOX WITH NEW SPLICE ENCLOSURE
		46	INSTALL SIDEWALK GUY ASSEMBLY		NEW SPECIAL OVERSIZED JUNCTION BOX WITH SPLICE ENCLOSURE
(10)	INSTALL RIGID, GALVANIZED STEEL CONDUIT	47	INSTALL MESSENGER CABLE	8	EXISTING SPECIAL OVERSIZED JUNCTION BOX WITH NEW SPLICE ENCLOSURE
(11)	INSTALL RIGID, GALVANIZED STEEL RISER WITH WEATHERHEAD	48	REMOVE EXISTING COMMUNICATIONS CABLE AND MESSENGER CABLE		EXISTING SPECIAL OVERSIZED JUNCTION BOX WITHOUT SPLICE ENCLOSURE  SNOW SHOE
(12)	INSTALL RIGID, GALVANIZED STEEL RISER WITH HEAT-SHRINK TUBING	49	REMOVE EXISTING COMMUNICATIONS CABLE	$\circ$	NEW WOOD POLE
(13)	INSTALL HEAT-SHRINK TUBING RETROFIT KIT			•	EXISTING WOOD POLE
$\sim$		50	INSTALL CELL MODEM INSTALL CABLE STORAGE RACKS (SNOW SHOES) AND STORE	(S)	NEW SPLICE ENCLOSURE  EXISTING SPLICE ENCLOSURE
(14)	INSTALL POLYETHYLENE CONDUIT	51	100 FEET OF CABLE		NEW METAL POLE
(15)	DIRECTIONAL DRILL CONDUIT	52	INSTALL DELINEATOR MARKER		EXISTING METAL POLE
16	BORE AND JACK CONDUIT	53	STORE 30 FEET OF COMMUNICATIONS CABLE (EACH CABLE), EXCEPT AS NOTED ON PLANS		NEW DMS  EXISTING DMS
17	INSTALL CABLE(S) IN EXISTING CONDUIT	54	LASH CABLE(S) TO EXISTING MESSENGER CABLE		NEW CCTV CAMERA ASSEMBLY EXISTING CCTV CAMERA ASSEMBLY
18	INSTALL CABLE(S) IN NEW CONDUIT	55	LASH CABLE(S) TO EXISTING SIGNAL / COMMUNICATION CABLE	<u> </u>	NEW STANDARD GUY ASSEMBLY
19	INSTALL CABLE(S) IN EXISTING RISER	56	LASH CABLES TO NEW MESSENGER CABLE		EXISTING STANDARD GUY ASSEMBLY NEW SIGNAL CABINET
20	INSTALL CABLE(S) IN NEW RISER	57	MODIFY EXISTING ELECTRICAL SERVICE	<u> </u>	EXISTING SIGNAL CABINET  NEW MASTER SIGNAL CABINET  ATTACHMENT POINT.
21	INSTALL CABLE(S) IN EXISTING CONDUIT ENTRANCE	58	INSTALL NEW ELECTRICAL SERVICE		EXISTING MASTER SIGNAL CABINET
22	INSTALL NEW CONDUIT INTO NEW CABINET BASE (USE EXISTING CONDUIT STUBOUTS WHEN AVAILABLE)	59	BOND TRACER WIRE TO EQUIPMENT GROUND BUS ON ONE END	<del>   -</del> _	NEW YAGI ANTENNA (SINGLE)  XXX  DISTANCE ABOVE INCHES  REFERENCE POINT
(23)	INSTALL NEW RISER INTO EXISTING CABINET BASE (USE EXISTING CONDUIT STUBOUTS WHEN AVAILABLE)	60	BOND MESSENGER TO POLE GROUND	7	NEW ELECTRICAL SERVICE  EXISTING ELECTRICAL SERVICE  YYYY  REFERENCE POINT  PLOTA NAME OF THE COMMENT OF THE CO
(24)	INSTALL NEW CONDUIT INTO POLE MOUNTED CABINET			SP	SIGNAL POLE XXX DISTANCE BELOW INCHES
$\sim$		61	BOND RISER TO POLE GROUND	XXX-# XX-XXXX	CCTV/DMS NUMBER  SIGNAL INVENTORY NUMBER
(25)	INSTALL NEW RISER INTO POLE MOUNTED CABINET	62	INSTALL DMS ASSEMBLY		
26	TERMINATE FIBER-OPTIC CABLE ON INTERCONNECT CENTER IN CCTV EQUIPMENT CABINET	63	INSTALL POLE MOUNTED CCTV CABINET	<u>CO1</u>	NUMBER OF TO A NUMBER OF FIBERS /
27	INSTALL NEW ETHERNET EDGE SWITCH IN CABINET	64	INSTALL NEW EQUIPMENT CABINET DISCONNECT	CABLE(S	NUMBER OFXX XX TWISTED PAIRS PER CABLE, ETC.
28	INSTALL INTERCONNECT CENTER, PATCH PANEL, JUMPERS, AND FUSION SPLICE CABLE IN CABINET	65	INSTALL JUNCTION BOX MARKERS	DICED/C	NUMBER OF XX XX DIAMETER OF RISER(S) / CONDUIT(S) (INCH)
29>	INSTALL UNDERGROUND SPLICE ENCLOSURE	66	INTERCEPT EXISTING JUNCTION BOX	KI3EK(3	,,, e e :
30>	INSTALL AERIAL SPLICE ENCLOSURE				NUMBER OF ———————————————————————————————————
$\times$		67	INSTALL CCTV CAMERA EXTENSION POLE		NUMBER OF XX
31	INSTALL SPLICE CABINET	68	INSTALL 6X6 WOOD PEDESTAL		CABLES  CABLE  DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED
32	MODIFY EXISTING SPLICE ENCLOSURE	69	INSTALL 2070E CONTROLLER		Plans Prepared for:  US 70
33	REMOVE EXISTING SPLICE CABINET				HAVELOCK BYPASS JORGESS OF THE CARROLLES OF THE SERVICE SERVIC
34	INSTALL CABINET FOUNDATION				CONSTRUCTION NOTES AND LEGEND  Division 02 Craven Co. Havelock  O31464  CONSTRUCTION NOTES AND LEGEND  Division 02 Craven Co. Havelock  CONSTRUCTION NOTES AND LEGEND
35	REMOVE EXISTING CABINET FOUNDATION		HNTB NORTH CAROLINA, P.C. 343 E. Six Forks Road, Su Raleigh, North Carolina 2	uite 200	PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell  Greenfield Pkwy., Garner, NC 27529 PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons  SCALE  REVISIONS  INIT. DATE  Docusigned by: 12/7/2018
124	INICTALL CCTV CARACDA ACCERADIV		Raleigh, North Carolina 2	27609	nevisions INIT. DATE Natasha R Simmons 12/7/2018


343 E. Six Forks Road, Suite 200 Raleigh, North Carolina 27609 NC License No: C-1554 (919) 546-8997

ES AND LEGEND 031464 viewed by: T.R. Terrell viewed by: N.R. Simmons -Natasha R Simmons 12/7/2018

NONE

CADD Filename: R1015\_scp\_01.dgn





CADD Filename: R1015 scp 03.dgn

PROJECT REFERENCE NO. DRAWING 1 DRAWING 2 R-1015 NEW ELECTRICAL SERVICE EQUIPMENT NEW ELECTRICAL CABINET DISCONNECT NEW NEW METER BASE/ **EQUIPMENT** CCTV-1 / DMS-1 GPS COORDINATES DISCONNECT CABINET COMBO PANEL DISCONNECT INSTALL 3-WIRE #3 COPPER SERVICE ENTRANCE CONDUCTORS - INSTALL 1 DOUBLE POLE, 50 AMP CIRCUIT BREAKER FOR DMS AND 1 SINGLE POLE, 15 AMP CIRCUIT BREAKER FOR CCTV 34° 58.065′ 76° 58.020′ IN NEW  $1\frac{1}{4}$ " RIGID GALVANIZED RISER WITH WEATHERHEAD. INSTALL 11/4" RAINPROOF CONDUIT HUB ON TOP OF NEW SERVICE METER BASE/DISCONNECT COMBO PANEL INSTALL ONE 1" CONDUIT WITH THREE #12 COPPER FEEDER CONDUCTORS TO POLE-MOUNTED CCTV CABINET ELECTRICAL SERVICE LOCATION TO BE INSTALL NEW DMS SERVICE DISCONNECT WITH 1 DOUBLE POLE. DETERMINED BY DUKE ENERGY IN FIELD. 70 AMP CIRCUIT BREAKER INSTALL ONE 2" CONDUIT WITH FOUR #3 COPPER FEEDER CONDUCTORS FROM POLE-MOUNTED METER BASE/DISCONNECT INSTALL ONE 2" CONDUIT WITH FOUR #3 COPPER FEEDER CONDUCTORS TO DMS EQUIPMENT CABINET DISCONNECT INSTALL ONE 1" CONDUIT WITH FOUR #8 COPPER FEEDER CONDUCTORS TO POLE-MOUNTED DMS CABINET DRAWING S SR 1100 (Catfish Lake Rd) Approx. 11,700' to TL-3 DMS-1 SEE 64 SEE DRAWING 2

> HNTB NORTH CAROLINA, P.C. 343 E. Six Forks Road, Suite 200 Raleigh, North Carolina 27609 NC License No: C-1554 (919) 546-8997

# NOTES:

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.

7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.


9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. NCDOT DIVISION 2 WILL FURNISH AND INSTALL THE CCTV AND DMS CELL MODEM. CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 SIX (6) WEEKS PRIOR TO BEGINNING WORK.


12. INSTALL A NEW DMS WALKWAY, LADDER, AND POLE-MOUNTED CABINET ON THE NEW DMS STRUCTURE.


13. INSTALL CCTV ON CCTV EXTENSION POLE.




**GUARDRAIL DESIGN** 

CADD Filename: R1015 scp 04.dqr





PROJECT REFERENCE NO. R-1015




- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439-2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

HNTB NORTH CAROLINA, P.C.
343 E. Six Forks Road, Suite 200
Raleigh, North Carolina 27609
NC License No: C-1554
(919) 546-8997

**UNLESS ALL SIGNATURES COMPLETED** US 70 HAVELOCK BYPASS CABLE ROUTING PLAN Division 02 Craven Co. Havelock August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons REVISIONS

031464 Natasha R Simmons 12/7/2018 CADD Filename: R1015 scp 06.dqn

**DOCUMENT NOT CONSIDERED FINAL** 



# NOTES:

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.


10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





CADD Filename: R1015 scp 07.dqn

PROJECT REFERENCE NO. SHEET NO. R-1015 SCP. 8



# NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.

7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.


10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.





Division 02 Craven Co. Havelock
PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell
PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons
REVISIONS INIT. DATE



TH CARO

**DOCUMENT NOT CONSIDERED FINAL** 


**UNLESS ALL SIGNATURES COMPLETED** 

DocuSign Envelope ID: 24C208E4-40EE-4780-B2B5-E2C4A8C09490

R-1015 SCP. 9

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

# NO WORK ON THIS SHEET



HAVELOCK BYPASS

CABLE ROUTING PLAN


Division 02 Craven Co. Haveloce


Plan Date: August 2018 Reviewed By: T.R. Terrell

750 N. Greenfield Pkwy., Garner, NC 27529 PREPARED BY: N.K. Vlanich Reviewed By: N.R. Simmons


Revisions Init. Date

US 70





PROJECT REFERENCE NO. R-1015



1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.

7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.

12. BACK PULL EXISTING FIBER TO EXISTING SPLICE ENCLOSURE AT SIGNAL 02-0672.

US 70 HAVELOCK BYPASS CABLE ROUTING PLAN

Division 02 Craven Co. Havelock PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons REVISIONS INIT. DATE

031464 Natasha R Simmons 12/7/2018


TH CARO

CFESSION.

**DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED** 

CADD Filename: R1015 scp 12.dgr

PROJECT REFERENCE NO. R - 1015



WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE. 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN


CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER. 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.






INIT. DATE Natasha R Simmons 12/7/2018 CADD Filename: R1015 scp 13.dqn

CESSION.

031464



# **NOTES**

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.
- 12. NCDOT DIVISION 2 WILL FURNISH AND INSTALL THE CCTV AND DMS CELL MODEM. CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 SIX (6) WEEKS PRIOR TO BEGINNING WORK.

Plans Prepared for:

US 70

HAVELOCK BYPASS

CABLE ROUTING PLAN

Division 02 Craven Co. Haveloce

Plan Date: August 2018 Reviewed By: T.R. Terrell

N. Greenfield Pkwy., Garner, NC 27529 PREPARED BY: N.K. Vlanich Reviewed By: N.R. Simmons

SCALE

O 50

AN

Havelock

R. Terrell

I.R. Simmons

INIT. DATE

MOCUMENT NOT CONSIDERED FINAL CAROL

SEAL


O31464

R. Simmons

Docusigned by:

Natasha R Simmons 12/7/2018

CADD Filename: R1015 scp 14.dqn



# NOTES:

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

HNTB NORTH CAROLINA, P.C.
343 E. Six Forks Road, Suite 200
Raleigh, North Carolina 27609
NC License No: C-1554
(919) 546-8997





# NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







# NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







# **NOTES:**

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN


CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







# NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







# **NOTES**

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.


4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.

- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.





CADD Filename: R1015 scp 20.dqn



1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.

7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.



US 70 HAVELOCK BYPASS CABLE ROUTING PLAN

Division 02 Craven Co. Havelock PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons REVISIONS INIT. DATE

Natasha R Simmons 12/7/2018 CADD Filename: R1015 scp 21.dqn

DOCUMENT NOT CONSIDERED FINAL

**UNLESS ALL SIGNATURES COMPLETED** 

TH CAROL

COFESSION !

031464

PROJECT REFERENCE NO. DRAWING 1 DRAWING 2 R-1015 NEW ELECTRICAL SERVICE EQUIPMENT NEW EQUIPMENT CABINET DISCONNECT METER BASE/ DISCONNECT COMBO PANEL INSTALL 3-WIRE #3 COPPER SERVICE **EQUIPMENT** ENTRANCE CONDUCTORS IN NEW CABINET INSTALL 1 DOUBLE POLE, 50 AMP CIRCUIT  $1\frac{1}{4}$ " RIGID GALVANIZED RISER WITH DISCONNECT BREAKER FOR DMS WEATHERHEAD. INSTALL 11/4" INSTALL ONE 2" CONDUIT WITH RAINPROOF CONDUIT HUB ON TOP FOUR #4 COPPER FEEDER OF NEW SERVICE METER/DISCONNECT CONDUCTORS FROM POLE-MOUNTED COMBO PANEL METER BASE/DISCONNECT COMBO PANEL INSTALL NEW SERVICE DISCONNECT WITH 1 DOUBLE POLE, 50 AMP NSTALL ONE 1" CONDUIT WITH FOUR CIRCUIT BREAKER #8 COPPER FEEDER CONDUCTORS TO DMS EQUIPMENT CABINET INSTALL ONE 2" CONDUIT WITH FOUR #4 COPPER FEEDER CONDUCTORS TO DMS EQUIPMENT CABINET DISCONNECT **REMOVE EXISTING 12** FIBER-OPTIC CABLE FROM CONTROLLER CABINET TO TOP OF SIGNAL POLE. (19) NOTE 36 SR 1776 SR 1776 (MIMOSA DR) (MIMOSA DR) Ш Approx. 610' To Approx. 770' To Jackson Dr Trader Ave / Holly Dr CAT - 1 US 70 BUSINESS DMS-4 02-0225 39 Z MATCHL ATC ТҮРЕ В 62 SR 1775 SR 1775 53 53 **ELECTRICAL SERVICE** LOCATION TO BE DETERMINED BY DUKE ENERGY IN FIELD. 59 **GUARDRAIL DESIGN** 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY. 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES. |58 | DRAWING 1 64 SEE DRAWING 2 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT 042542 GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL. 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE 12/7/2018 CCTV CAMERAS OR DMS. 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL. 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE. **DOCUMENT NOT CONSIDERED FINAL** 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN **UNLESS ALL SIGNATURES COMPLETED** CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER. 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE US 70 IN THE SAME JUNCTION BOX. HAVELOCK BYPASS 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE CABLE ROUTING PLAN DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER. 031464 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND Division 02 Craven Co. Havelock August 2018 REVIEWED BY: T.R. Terrell DMS CONSTRUCTION WORK HAS BEEN PERFORMED. 11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE. REVIEWED BY: N.R. Simmons PREPARED BY: N.K. Vlanich HNTB NORTH CAROLINA, P.C. 343 E. Six Forks Road, Suite 200 Raleigh, North Carolina 27609 NC License No: C-1554 (919) 546-8997 12. NCDOT DIVISION 2 WILL FURNISH AND INSTALL THE CCTV AND DMS CELL MODEM. CONTACT THE DIVISION 2 TRAFFIC REVISIONS INIT. DATE Natasha R Simmons 12/7/2018 ENGINEER, STEVE HAMILTON, AT (252) 439–2816 SIX (6) WEEKS PRIOR TO BEGINNING WORK.

CADD Filename: R1015 scp 22.dg

031464

Natasha R Simmons 12/7/2018

CADD Filename: R1015 scp 23.dgn

Havelock

INIT. DATE

Division 02


REVISIONS

PLAN DATE:

Craven Co.

PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons

August 2018 REVIEWED BY: T.R. Terrell



HNTB NORTH CAROLINA, P.C.
343 E. Six Forks Road, Suite 200
Raleigh, North Carolina 27609
NC License No: C-1554
(919) 546-8997

 $\bigcirc$ 


DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

ENGINEER, STEVE HAMILTON, AT (252) 439–2816 SIX (6) WEEKS PRIOR TO BEGINNING WORK.

DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND


11. NCDOT DIVISION 2 WILL FURNISH AND INSTALL THE SIGNAL CELL MODEM. CONTACT THE DIVISION 2 TRAFFIC



PROJECT REFERENCE NO. R-1015

FESSION ...

031464





HNTB NORTH CAROLINA, P.C.
343 E. Six Forks Road, Suite 200
Raleigh, North Carolina 27609
NC License No: C-1554
(919) 546-8997

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES. 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL

SYSTEM IS BACK UP AND FUNCTIONAL. 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.
- 12. INSTALL TWO (2) INCH CONDUITS IN SIX (6) INCH CONDUIT UNDER RAILROAD TRACKS AT A DEPTH OF FIFTEEN (15) FEET BELOW BASE OF RAIL.





# NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







# NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







# **NOTES**

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







# **NOTES**

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.


3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.

- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.



US 70 HAVELOCK BYPASS CABLE ROUTING PLAN

CABLE ROUIING PLAN

Division 02 Craven Co. Havelock

PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell

PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons

REVISIONS INIT. DATE

SEAL
031464

K

Docusigned by:


Notasha R Simmons 12/7/2018

F6DA88DF3AD445A...
SIGNATURE


CADD Filenome: R1015 scp 29.dgn

**DOCUMENT NOT CONSIDERED FINAL** 

**UNLESS ALL SIGNATURES COMPLETED** 



PROJECT REFERENCE NO. R-1015



1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.





US 70 HAVELOCK BYPASS CABLE ROUTING PLAN


Craven Co. PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons

031464 Havelock Natasha R Simmons 12/7/2018 CADD Filename: R1015 scp 31.dqn

GUARDRAIL DESIGN

CESSION !

PROJECT REFERENCE NO. R-1015



1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NÉTWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.


10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.



US 70 HAVELOCK BYPASS CABLE ROUTING PLAN


Division 02 Craven Co. Havelock August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons REVISIONS INIT. DATE




**DOCUMENT NOT CONSIDERED FINAL** 

**UNLESS ALL SIGNATURES COMPLETED** 


Natasha R Simmons 12/7/2018 CADD Filename: R1015 scp 32.dqn






# NOTES

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.



PROJECT REFERENCE NO.



1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.


HNTB NORTH CAROLINA, P.C.
343 E. Six Forks Road, Suite 200
Raleigh, North Carolina 27609
NC License No: C-1554
(919) 546-8997



031464 Natasha R Simmons 12/7/2018

CADD Filename: R1015 scp 35.dqn

PROJECT REFERENCE NO. R - 1015



# **NOTES:**


1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.


2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.






REVISIONS

Natasha R Simmons 12/7/2018 CADD Filename: R1015 scp 36.dqn

DOCUMENT NOT CONSIDERED FINAL

031464



### NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





PROJECT REFERENCE NO. R - 1015 CABLE CABLE 12" CABLE -L- US 70 BUSINESS CARTERET COUNTY CRAVEN COUNTY

### NOTES


1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.


2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.


- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





**DOCUMENT NOT CONSIDERED FINAL** 

CADD Filename: R1015 scp 38.dqn



PROJECT REFERENCE NO. R-1015 34° 51.660′ 76° 56.869 ELECTRICAL SERVICE LOCATION TO BE DETERMINED BY CARTERET-CRAVEN ELECTRICAL COOPERATIVE IN FIELD. 58 DRAWING **GUARDRAIL DESIGN** 042542

DRAWING 2


NEW ELECTRICAL SERVICE EQUIPMENT METER BASE/ DISCONNECT COMBO PANEL INSTALL 3-WIRE #3 COPPER SERVICE ENTRANCE CONDUCTORS IN NEW 11/4" RIGID GALVANIZED RISER WITH WEATHERHEAD. INSTALL  $1\frac{1}{4}$ " RAINPROOF CONDUIT HUB ON TOP OF NEW SERVICE METER/DISCONNECT COMBO PANEL INSTALL NEW SERVICE DISCONNECT WITH 1 DOUBLE POLE, 50 AMP CIRCUIT BREAKER INSTALL ONE 2" CONDUIT WITH FOUR

#6 COPPER FEEDER CONDUCTORS TO DMS EQUIPMENT CABINET DISCONNECT

DRAWING 1

NEW EQUIPMENT CABINET DISCONNECT **EQUIPMENT** CABINET INSTALL 1 DOUBLE POLE, 50 AMP CIRCUIT DISCONNECT BREAKER FOR DMS - INSTALL ONE 2" CONDUIT WITH FOUR #6 COPPER FEEDER CONDUCTORS FROM POLE-MOUNTED METER BASE/DISCONNECT COMBO PANEL - INSTALL ONE 1" CONDUIT WITH FOUR #8 COPPER FEEDER CONDUCTORS TO DMS EQUIPMENT CABINET

DMS-8 GPS COORDINATES



1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. NCDOT DIVISION 2 WILL FURNISH AND INSTALL THE CCTV AND DMS CELL MODEM. CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 SIX (6) WEEKS PRIOR TO BEGINNING WORK.





### NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.


9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.






CADD Filename: R1015 scp 41.dqn



### NOTES

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
  3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER,
- STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





CADD Filename: R1015 scp 42.dqn

DRAWING 1

EXISTING METER BASE/ DISCONNECT

COMBO PEDESTAL

MODIFY ELECTRICAL SERVICE EQUIPMENT

EXISTING SINGLE POLE, EXISTING

INSTALL NEW SERVICE DISCONNECT

- INSTALL NEW 1½" RIGID GALVANIZED

CONDUIT FOR SERVICE ENTRANCE

CONDUCTORS BY UTILITY PROVIDER

INSTALL ONE 1" CONDUIT WITH THREE #6 COPPER FEEDER CONDUCTORS TO

BREAKER FOR TRAFFIC SIGNAL

WITH 1 SINGLE POLE, 15 AMP

CIRCUIT BREAKER


PROJECT REFERENCE NO. SHEET NO. R-1015 SCP. 43

# CCTV-7 GPS COORDINATES

N 34° 52.062′ W 76° 56.192′

INSTALL 1 SINGLE POLE, 15 AMP CIRCUIT
BREAKER FOR CCTV

INSTALL ONE 1" CONDUIT WITH
THREE #4 COPPER FEEDER
CONDUCTORS FROM METER BASE/
DISCONNECT COMBO PEDESTAL



## NOTES:

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

DRAWING 2

**EQUIPMENT** 

CABINET


DISCONNECT

NEW EQUIPMENT CABINET DISCONNECT


INSTALL ONE 1" CONDUIT WITH THREE

#12 COPPER FEEDER CONDUCTORS TO POLE-MOUNTED CCTV EQUIPMENT

- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. NCDOT DIVISION 2 WILL FURNISH AND INSTALL THE CCTV AND DMS CELL MODEM. CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 SIX (6) WEEKS PRIOR TO BEGINNING WORK.




PROJECT REFERENCE NO. R-1015



STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.


- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.



**DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED** US 70 HAVELOCK BYPASS FESSION ... CABLE ROUTING PLAN 031464 Division 02 Craven Co. Havelock August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons REVISIONS Natasha R Simmons 12/7/2018

CADD Filename: R1015 scp 44.dgn

PROJECT REFERENCE NO. R - 1015



- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
  3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER,
- STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE
- DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER. 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. NCDOT DIVISION 2 WILL FURNISH AND INSTALL THE CCTV AND DMS CELL MODEM. CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439-2816 SIX (6) WEEKS PRIOR TO BEGINNING WORK.



US 70 HAVELOCK BYPASS CABLE ROUTING PLAN

Division 02 Craven Co. Havelock PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons REVISIONS

Natasha R Simmons 12/7/2018 CADD Filename: R1015 scp 45.dqn


**DOCUMENT NOT CONSIDERED FINAL** 

**UNLESS ALL SIGNATURES COMPLETED** 

TH CARO

CESSION .

031464



### NOTES

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

HNTB NORTH CAROLINA, P.C.

343 E. Six Forks Road, Suite 200
Raleigh, North Carolina 27609
NC License No: C-1554
(919) 546-8997

US 70
HAVELOCK BYPASS
CABLE ROUTING PLAN

Division 02 Craven Co. Haveloc

PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell

PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons

REVISIONS INIT. DATE

SEAL
031464

18

Docusigned by:

Natasha R Simmons 12/7/2018

**DOCUMENT NOT CONSIDERED FINAL** 

**UNLESS ALL SIGNATURES COMPLETED** 

PREVISIONS

PREVISIONS

INIT. DATE

O 50

1"=50'


PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons

Adgust 2010 REVIEWED BY: N.R. Simmons

INIT. DATE

O 50

CADD Filename: R1015 scp 46.dgm



### NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.







### NOTES

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE
- DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

  10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. INSTALL TWO (2) INCH CONDUITS IN SIX (6) INCH CONDUIT UNDER RAILROAD TRACKS AT A DEPTH OF FIFTEEN (15) FEET BELOW BASE OF RAIL.



1"=50'

US 70 HAVELOCK BYPASS CABLE ROUTING PLAN

Division 02 Craven Co. Havelock
PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell
PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons
REVISIONS INIT. DATE

R. Terrell

R. Simmons

INIT. DATE

Matasha R Simmons 12/7/2018

F6DA88DF3AD445A...
SIGNATURE

CADD Filename: R1015 scp 48.dgn

**DOCUMENT NOT CONSIDERED FINAL** 

**UNLESS ALL SIGNATURES COMPLETED** 


ESSION ...

031464

PROJECT REFERENCE NO. R - 1015

ESSION ...

031464



1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439-2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





### NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.


6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.


9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





PROJECT REFERENCE NO. R-1015



# **NOTES:**

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439-2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.



US 70 HAVELOCK BYPASS CABLE ROUTING PLAN


Division 02 Craven Co. Havelock PLAN DATE: August 2018 REVIEWED BY: T.R. Terrell PREPARED BY: N.K. Vlanich REVIEWED BY: N.R. Simmons

031464 Natasha R Simmons 12/7/2018


CADD Filename: R1015 scp 51.dqn

**DOCUMENT NOT CONSIDERED FINAL** 

**UNLESS ALL SIGNATURES COMPLETED** 




- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.
- 12. INSTALL TWO (2) INCH CONDUITS IN SIX (6) INCH CONDUIT UNDER RAILROAD TRACKS AT A DEPTH OF FIFTEEN (15) FEET BELOW BASE OF RAIL.



PROJECT REFERENCE NO. R-1015






1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.


2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.


3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE. 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN
- CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER. 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE
- DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER. 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.
- 11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.







### NOTES

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.

7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.


8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.


9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.

11. REMOVE EXISTING FIBER OPTIC CABLE AND PULL IN NEW FIBER OPTIC CABLE.









### NOTES

- 1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.
- 2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.
- 3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.
- 4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.
- 5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.
- 6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.
- 7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.
- 8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.
- 9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.
- 10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





CADD Filename: R1015 scp 55.dqn



### NOTES:

1. MAINTAIN A MINIMUM OF SIX (6) FEET FROM THE EDGE OF PAVEMENT WHEN TRENCHING PARALLEL TO THE ROADWAY.

2. SEAL ALL CONDUIT ENTRANCES WITH DUCT AND CONDUIT SEALER AT ALL JUNCTION BOX/CABINET ENTRANCES.

3. FIVE (5) DAYS PRIOR TO BEGINNING WORK ON THE SIGNAL SYSTEM, CONTACT THE DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO ARRANGE FOR THE DIVISION TO PROGRAM THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE SENIOR SIGNAL SYSTEM OPERATOR AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SIGNAL SYSTEM IS BACK UP AND FUNCTIONAL.

4. CONTACT DIVISION 2 TRAFFIC ENGINEER, STEVE HAMILTON, AT (252) 439–2816 TO CONFIRM THE LOCATION OF THE CCTV CAMERAS OR DMS.

5. DO NOT INSTALL CCTV POLE ANY CLOSER THAN SIX (6) FEET FROM THE FACE OF GUARDRAIL.

6. MOUNT THE CCTV CAMERA 5 FEET BELOW THE TOP OF THE POLE.


7. DO NOT INSTALL CONDUIT OR JUNCTION BOXES UNTIL THE LOCATION OF THE CCTV CAMERA OR DMS HAS BEEN CONFIRMED BY THE DIVISION 2 TRAFFIC ENGINEER.

8. INSTALL CONDUITS IN THE SAME TRENCH. DO NOT INSTALL ELECTRICAL POWER CONDUCTORS AND FIBER-OPTIC CABLE IN THE SAME JUNCTION BOX.

9. IT IS THE CONTRACTOR'S RESPONSIBILITY TO OBTAIN THE MAXIMUM FAULT CURRENT INFORMATION FROM THE POWER COMPANY FOR THE REQUIRED ELECTRICAL SERVICE AND PLACE A "FAULT CURRENT" STICKER INSIDE THE SERVICE DISCONNECT PANEL WITH THE DATE AND MAXIMUM FAULT CURRENT ON THE STICKER.

10. AT THE DIRECTION OF THE ENGINEER, PERFORM GRADING AS NEEDED WHERE GUARDRAIL, POLE INSTALLATION AND DMS CONSTRUCTION WORK HAS BEEN PERFORMED.





CADD Filename: R1015 scp 56.dqn