COMPUTED BY: <u>Neil Roberson</u> DATE:<u>June 5, 2019</u> CHECKED BY: <u>cmkr</u> DATE: <u>July 3, 2019</u>

## SUMMARY OF SUBSURFACE DRAINAGE

LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
	CONTIN	SD	1500		
				TOTAL LF:	1500

\*UD = Underdrain

\*BD = Blind Drain

\*SD = Subsurface Drain

## STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

## SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Soil Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
0	CONTINGENC	Y	ASU Type 1		200	400	600		
			TOTAL	CY/TONS/SY:	200	400**	600**	0	0

\*ASU(1/2) = Aggregate Subgrade (Type 1 or 2) \*AST = Aggregate Stabilization

\*\*Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Soil Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.

PROJECT NO.	SHEET NO.
U-5827	3G-1