
	DIAGRAM			TABLE OF OPERATION		
					PHAS	ЭE
				SIGNAL	Ø Ø 2 4	F
				FACE	Ø Ø 2 4 + 6	F L A S H
		► )				
				21	F → F → R	
Ø2+6	Ø4	1		22, 23	G R R G	Y R
				41, 42	G R	Γ Υ
PHASING DIAGRAM		GEND		01, 02		
	TED MOVEMENT ECTED MOVEMEN	IT (OVERI	_AP)			
	NALIZED MOVEM		,	SIGNAL F	ACE :	Ι.[
<> PEDES	TRIAN MOVEMEN	IT		All Head	is L.E.D	).
					(R)	
				12	′ ( <u>Y</u> )	12′
				$\left( \begin{array}{c} F \\ Y \end{array} \right)$	G	
					22, 23	
				21	41, 42	2
					61, 62	-
						¥
		T	-			•
						-
						- 0
				•	•	-
		•			•	-
		•		•	•	-
	•••				•	• - •
	•••	•	E		•	-
	•••		E		•	-
	•••		E			-
	•••		E	•		-
	•••				•	-
<u>e</u> a • • •		• • •				-
<u>e</u> a • • •	•••	CHA PHASE				-
<u>e</u> a • • •						-
<u>P</u> E ASC/5	• • • • • • • • • • • • • • • • • • •	PHASE	RT			-
EATURE Min Green * Walk *	• • • 3 TIMINO 2	PHASE 4	RT6			-
EATURE Min Green * Walk * Ped Clear	3 TIMINO 2 14 	<b>PHASE</b> 4 7	<b>RT</b> 6 14			-
EATURE Min Green * Walk * Ped Clear Veh. Extension *	<b>3 TIMINO</b> <b>2</b> 14 	PHASE 4 7 - - 2.0	<b>RT</b> 6 14 - 6 6.0			-
EATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 *	<b>3 TIMINO</b> <b>2</b> 14 - 6.0 90	PHASE 4 7 - 2.0 30	<b>RT</b>			-
EATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow	<b>3 TIMINO</b> <b>2</b> 14 	PHASE 4 7 - 2.0 30 3.0	<b>RT</b>			-
EATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 *	<b>3 TIMINO</b> <b>2</b> 14 - 6.0 90	PHASE 4 7 - 2.0 30	<b>RT</b>			-
EATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow Red Clear	<b>3 TIMINO</b> <b>2</b> 14 - - 6.0 90 5.3 1.2	PHASE 4 7 - 2.0 30 3.0 2.1	<b>RT</b>			-
EATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow Red Clear Actuations B4 Add *	<b>3 TIMINO</b> <b>2</b> 14 - 6.0 90 5.3 1.2 -	PHASE 4 7 - 2.0 30 3.0 2.1	<b>BT</b> 6 14 - 6.0 90 5.2 1.0 -			-
EATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow Red Clear Actuations B4 Add * Seconds /Actuation * Max Initial * Time Before Reduction *	<b>3 TIMINO</b> <b>2</b> 14 	PHASE 4 7 - 2.0 30 3.0 2.1	<b>RT</b> 6 14 - 6.0 90 5.2 1.0 5.2 1.0 2.5 46 15			-
ASC/ FEATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow Red Clear Actuations B4 Add * Seconds / Actuation * Max Initial * Time Before Reduction * Time To Reduce *	<b>3 TIMINO</b> <b>2</b> 14 	PHASE 4 7 2.0 30 3.0 2.1	<b>RT</b> 6 14 - 6.0 90 5.2 1.0 5.2 1.0 2.5 46 15 30			-
ASC/ FEATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow Red Clear Actuations B4 Add * Seconds /Actuation * Max Initial * Time Before Reduction * Time To Reduce * Minimum Gap	<b>3 TIMINO</b> <b>2</b> 14 - - 6.0 90 5.3 1.2 - 2.5 46 15 30 3.4	PHASE 4 7 7 - 2.0 30 3.0 2.1	<b>RT</b> 6 14 - 6.0 90 5.2 1.0 - 2.5 46 15 30 3.4			-
ASC/ FEATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow Red Clear Actuations B4 Add * Seconds /Actuation * Max Initial * Time Before Reduction * Time To Reduce * Minimum Gap Locking Detector	<b>3 TIMINO</b> <b>2</b> 14 - - 6.0 90 5.3 1.2 - 2.5 46 15 30 3.4 X	PHASE 4 7 7 - 2.0 30 3.0 2.1	<b>BT</b> 6 14 - 6.0 90 5.2 1.0 5.2 1.0 5.2 1.0 5.2 1.0 30 3.4 X			-
ASC/ FEATURE Min Green * Walk * Ped Clear Veh. Extension * Max 1 * Yellow Red Clear Actuations B4 Add * Seconds /Actuation * Max Initial * Time Before Reduction * Time To Reduce * Minimum Gap	<b>3 TIMINO</b> <b>2</b> 14 - - 6.0 90 5.3 1.2 - 2.5 46 15 30 3.4	PHASE 4 7 7 - 2.0 30 3.0 2.1	<b>RT</b> 6 14 - 6.0 90 5.2 1.0 - 2.5 46 15 30 3.4			-

ASC/3 DETECTOR INSTALLATION CHART												
	DETECTOR				PROGRAMMING							
ZONE	SIZE (FT)	DISTANCE FROM STOPBAR (FT)	TURNS	NEW LOOP	PHASE	CALLING	EXTEND TIME	DELAY TIME	USE ADDED INITIAL	ТҮРЕ	SYSTEM LOOP	
2A <b>*</b>	6X6	420	*	*	2	Yes	-	-	Х	Ν	-	
4A <del>*</del>	6X40	0	*	*	4	Yes	-	5	-	S	-	
6A*	6X6	420	*	*	6	Yes	-	_	Х	Ν	-	

\* Video Detection Zone




0


PROJECT REFERENCE NO. SHEET NO. Sig 7.0 U-2581BA

## 2 Phase Fully Actuated (Isolated)

## NOTES

- 1. Refer to "Roadway Standard Drawings NCDOT" dated January 2018 and "Standard Specifications for Roads and Structures" dated January 2018.
- 2. Do not program signal for late night flashing operation unless otherwise directed by the Engineer.
- 3. Set all detector units to presence mode.
- 4. Reposition all existing signal heads. 5. Incorporate Video Detection system for vehicle detection.
- 6. Provide the Engineer with the Manufacturer's approved Video Detection locations and mounting heights to obtain detection zones as shown.





KNGINEE

9/9/2019

DATE