

**STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS**

SUMMARY OF SUBSURFACE DRAINAGE

| LINE | Station | Station | Location LT/RT/CL | Drain Type* UD/BD/SD | LF |
|-------------|---------|---------|----------------------|-------------------------|-----|
| | | | | | |
| CONTINGENCY | | | | SD | 200 |
| | | | | TOTAL LF: | 200 |

*UD = Underdrain
 *BD = Blind Drain
 *SD = Subsurface Drain

SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

| LINE | Station | Station | Aggregate Type* ASU(1/2)/ AST | Aggregate Thickness INCHES [8" for ASU(2)] | Shallow Undercut CY | Class IV Subgrade Stabilization TONS | Geotextile for Soil Stabilization SY | Stabilizer Aggregate TONS | Class IV Aggregate Stabilization TONS |
|--------------------------|---------|---------|--|--|---------------------------|---|---|---------------------------------|--|
| | | | | | | | | | |
| CONTINGENCY | | | ASU | 18 | 100 | 200 | 200 | | |
| TOTAL CY/TONS/SY: | | | | | 100 | 200** | 200** | 0 | 0 |

*ASU(1/2) = Aggregate Subgrade (Type 1 or 2)

*AST = Aggregate Stabilization

**Total tons of "Class IV Subgrade Stabilization" and total square yards of "Geotextile for Soil Stabilization" are only the estimated quantities for ASU(1/2)/AST and may only represent a portion of the subgrade stabilization and geotextile quantities shown in the Item Sheets of the Proposal.