



**NOTES**

1. BOND CLASS II, 28 STRAND (MINIMUM), 15 AWG (MINIMUM) ROPE-LAY BARE COPPER CONDUCTOR TO THE MAIN GROUND ROD BY AN IRREVERSIBLE MECHANICAL CRIMP. MAINTAIN MAXIMUM HORIZONTAL SEPARATION BETWEEN COPPER CONDUCTOR AND RISER.
2. ALL CONNECTIONS TO GROUND RODS SHOULD BE MADE WITH AN IRREVERSIBLE MECHANICAL CRIMP METHOD.
3. REFER TO STANDARD DRAWING 1700-2 FOR ALTERNATE GROUND ROD INSTALLATION METHOD AS APPROVED BY THE ENGINEER.
4. INSTALL MARKER TAPE DIRECTLY ABOVE ALL GROUNDING ELECTRODES AND CONDUCTORS AT A DEPTH OF 12 INCHES.
5. REMOVE BONDING JUMPER BETWEEN EQUIPMENT CABINET GROUND BUSS AND NEUTRAL BUSS.

	<p>CCTV CAMERA INSTALLATION FOR WOOD POLES WITH SOLAR POWERED ELECTRICAL SERVICE TYPICAL DETAIL</p>	
	<p>PLAN DATE: December 2020</p>	<p>REVIEWED BY: F. A. Campbell</p>
<p>PREPARED BY: S. W. Cox</p>	<p>REVIEWED BY:</p>	<p>DATE:</p>
<p>REVISIONS</p>	<p>INIT.</p>	<p>DATE</p>
<p>NTS</p>	<p>DocuSigned by: Francis A. Campbell 12/8/2020</p>	<p>CADD Filename:</p>