

FOUNDATION NOTES

FOR PILES, SEE SECTION 450 OF THE STANDARD SPECIFICATIONS.

PILES AT END BENT NO.1 AND END BENT NO.2 ARE DESIGNED FOR A FACTORED RESISTANCE OF 137.5 TONS PER PILE.

DRIVE PILES AT END BENT NO.1 AND END BENT NO.2 TO A REQUIRED DRIVING RESISTANCE OF 230 TONS PER PILE.

FOR DRILLED PIERS, SEE SECTION 411 OF THE STANDARD SPECIFICATIONS.

SID INSPECTIONS MAY BE REQUIRED FOR DRILLED PIERS. THE ENGINEER WILL DETERMINE THE NEED FOR SID INSPECTIONS. FOR SID INSPECTIONS, SEE SECTION 411 OF THE STANDARD SPECIFICATIONS.

CSL TUBES ARE REQUIRED AND CSL TESTING MAY BE REQUIRED FOR DRILLED PIERS. THE ENGINEER WILL DETERMINE THE NEED FOR CSL TESTING. FOR CSL TESTING, SEE SECTION 411 OF THE STANDARD SPECIFICATIONS.

DRILLED PIERS AT BENT NO.1 ARE DESIGNED FOR A FACTORED RESISTANCE OF 515 TONS PER PIER. CHECK FIELD CONDITIONS FOR THE REQUIRED TIP RESISTANCE OF 20 TSF.

INSTALL DRILLED PIERS AT BENT NO.1 TO A TIP ELEVATION NO HIGHER THAN 175 FT (LT), 164.0 FT (CT) AND 164 FT (RT) WITH THE REQUIRED TIP RESISTANCE AND A PENETRATION OF AT LEAST 15 FT INTO WEATHERED ROCK AND ROCK AS DEFINED BY ARTICLE 411-1 OF THE STANDARD SPECIFICATIONS.

THE SCOUR CRITICAL ELEVATION FOR BENT NO.1 IS ELEVATION 187 FT (LT), 180 FT (CT), AND 180 FT (RT). SCOUR CRITICAL ELEVATIONS ARE USED TO MONITOR POSSIBLE SCOUR PROBLEMS DURING THE LIFE OF THE STRUCTURE.

DRILLED PIERS AT BENT NO.2 ARE DESIGNED FOR A FACTORED RESISTANCE OF 505 TONS PER PIER.

INSTALL DRILLED PIERS AT BENT NO.2 TO A TIP ELEVATION NO HIGHER THAN 171.5 FT WITH THE REQUIRED TIP RESISTANCE AND A PENETRATION OF AT LEAST 13 FT INTO WEATHERED ROCK AND ROCK AS DEFINED BY ARTICLE 411-1 OF THE STANDARD SPECIFICATIONS.

PERMANENT STEEL CASINGS ARE REQUIRED FOR DRILLED PIERS AT BENT NO.2. DO NOT EXTEND PERMANENT CASINGS BELOW ELEVATION 184.5 FT WITHOUT PRIOR APPROVAL FROM THE ENGINEER.

THE SCOUR CRITICAL ELEVATION FOR BENT NO.2 IS ELEVATION 182.0 FT. SCOUR CRITICAL ELEVATIONS ARE USED TO MONITOR POSSIBLE SCOUR PROBLEMS DURING THE LIFE OF THE STRUCTURE.

DRILLED PIERS AT BENT NO.3 ARE DESIGNED FOR A FACTORED RESISTANCE OF 470 TONS PER PIER. CHECK FIELD CONDITIONS FOR THE REQUIRED TIP RESISTANCE OF 20 TSF.

INSTALL DRILLED PIERS AT BENT NO.3 TO A TIP ELEVATION NO HIGHER THAN 172.5 FT WITH THE REQUIRED TIP RESISTANCE AND A PENETRATION OF AT LEAST 15 FT INTO WEATHERED ROCK AND ROCK AS DEFINED BY ARTICLE 411-1 OF THE STANDARD SPECIFICATIONS.


PERMANENT STEEL CASINGS ARE REQUIRED FOR DRILLED PIERS AT BENT NO.3. DO NOT EXTEND PERMANENT CASINGS BELOW ELEVATION 187.5 FT WITHOUT PRIOR APPROVAL FROM THE ENGINEER.

THE SCOUR CRITICAL ELEVATION FOR BENT NO.3 IS ELEVATION 182.0 FT. SCOUR CRITICAL ELEVATIONS ARE USED TO MONITOR POSSIBLE SCOUR PROBLEMS DURING THE LIFE OF THE STRUCTURE.


DRILLED PIERS AT BENT NO.4 ARE DESIGNED FOR A FACTORED RESISTANCE OF 520 TONS PER PIER. CHECK FIELD CONDITIONS FOR THE REQUIRED TIP RESISTANCE OF 35 TSF.

INSTALL DRILLED PIERS AT BENT NO.4 TO A TIP ELEVATION NO HIGHER THAN 163 FT WITH THE REQUIRED TIP RESISTANCE AND A PENETRATION OF AT LEAST 18 FT INTO WEATHERED ROCK AND ROCK AS DEFINED BY ARTICLE 411-1 OF THE STANDARD SPECIFICATIONS.


THE SCOUR CRITICAL ELEVATION FOR BENT NO.4 IS ELEVATION 183.0 FT. (LT), 179.0 FT. (CT), AND 179.0 FT. (RT). SCOUR CRITICAL ELEVATIONS ARE USED TO MONITOR POSSIBLE SCOUR PROBLEMS DURING THE LIFE OF THE STRUCTURE.




END BENT NO. 1




BENT NO. 1




BENT NO. 2



BENT NO. 3




BENT NO. 4



END BENT NO. 2

FOUNDATION LAYOUT



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

V&M
Vaughn & Melton
Consulting Engineers

Asheville, North Carolina
828-253-2796

Boone, NC 828-355-9933
Tri-Cities, TN 423-467-8401
Knoxville, TN 865-546-5800
Spartanburg, SC 864-514-4775
Charleston, SC 843-974-5650
Middlesboro, KY 606-248-6600
Raleigh, NC 919-977-9455
Charlotte, NC 704-357-0488
Atlanta, GA 770-627-3590

Copyright © 2006 Vaughn & Melton, Inc. All Rights Reserved

PROJECT NO. B-4407

ANSON/STANLY COUNTY

STATION: 32+31.61 -L-

SHEET 4 OF 5

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
RALEIGH

GENERAL DRAWING
BRIDGE ON US-52
OVER ROCKY RIVER
BETWEEN SR-1627 (OLD US-52)
AND SR-1934 (RIVERVIEW RD.)

REVISIONS						SHEET NO.
NO.	BY:	DATE:	NO.	BY:	DATE:	S-4
1		10/2020	3			TOTAL SHEETS
2		10/2020	4			45

WDC/PRG
 2/26/21 11:53 AM
 C:\Users\wdc\Documents\Projects\B-4407\Structures\Final Plans\DOT_B-4407_SML_FLD3_S04.dgn
 TIME: 09:48 AM on Tuesday, January 12, 2021