


GEOTECHNICAL ENGINEER



SIGNATURE DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

NOTES:

- SEE EROSION CONTROL AND ROADWAY PLANS AND SUMMARY SHEETS FOR REINFORCED SOIL SLOPE (RSS) AND SLOPE EROSION CONTROL LOCATIONS.
- FOR NON-STANDARD REINFORCED SOIL SLOPES,SEE REINFORCED SOIL SLOPES PROVISION.FOR STEEL BEAM GUARDRAIL,SEE SECTION 862 OF THE STANDARD SPECIFICATIONS.
- FOR SHOULDER AND SLOPE BORROW,SEE ARTICLE 1019-2 OF THE STANDARD SPECIFICATIONS.FOR GEOCELLS,SEE CELLULAR CONFINEMENT SYSTEMS PROVISION.FOR COIR FIBER MAT,MATting FOR EROSION CONTROL AND COMPOST BLANKET,SEE EROSION CONTROL PROVISIONS,SECTION 1631 OF THE STANDARD SPECIFICATIONS AND ROADWAY STANDARD DRAWING NO.1631.01.
- WHEN VERY LOOSE OR SOFT SOIL OR MUCK IS BELOW RSS,AT-GRADE STABILIZATION WILL BE REQUIRED.
- GEOGRIDS ARE TYPICALLY APPROVED FOR ULTIMATE TENSILE STRENGTHS IN THE MACHINE DIRECTION (MD) AND CROSS-MACHINE DIRECTION (CD)OR LONG-TERM DESIGN STRENGTHS FOR A 75-YEAR DESIGN LIFE IN THE MD BASED ON MATERIAL TYPE.THE LIST OF APPROVED GEOGRIDS WITH DESIGN STRENGTHS IS AVAILABLE FROM:
connect.ncdot.gov/resources/Materials/Pages/Materials-Manual-by-Material.aspx
DEFINE MATERIAL TYPE FROM THE WEBSITE ABOVE FOR SELECT MATERIAL AS FOLLOWS:

| MATERIAL TYPE | SELECT MATERIAL |
|----------------|---------------------------------|
| BORROW | CLASS I SELECT MATERIAL |
| FINE AGGREGATE | CLASS II OR III SELECT MATERIAL |

IF THE WEBSITE DOES NOT LIST A LONG-TERM DESIGN STRENGTH FOR AN APPROVED GEOGRID IN THE MD,DO NOT USE THE GEOGRID FOR PRIMARY GEOGRID.IF THE WEBSITE DOES NOT LIST A LONG-TERM DESIGN STRENGTH FOR AN APPROVED GEOGRID IN THE CD,USE A LONG-TERM DESIGN STRENGTH EQUAL TO THE ULTIMATE TENSILE STRENGTH DIVIDED BY 7 FOR THE SECONDARY GEOGRID.

- DO NOT OVERLAP PRIMARY GEOGRIDS IN THE MD SO OVERLAPS ARE PARALLEL TO THE TOE OF RSS. POLYOLEFIN (e.g.,HDPE OR PP)GEOGRIDS MAY BE SPLICED ONCE PER PRIMARY GEOGRID LENGTH IN ACCORDANCE WITH THE GEOGRID MANUFACTURER'S INSTRUCTIONS.USE POLYOLEFIN GEOGRID PIECES AT LEAST 4' LONG.DO NOT SPLICE POLYESTER TYPE (PET)GEOGRIDS.
- FOR PRIMARY GEOGRIDS WITH 100% COVERAGE,PLACE PRIMARY GEOGRIDS SO GEOGRIDS ARE ADJACENT TO EACH OTHER IN THE CD.FOR PRIMARY GEOGRIDS WITH 75% TO LESS THAN 100% COVERAGE,

$$\text{MINIMUM REQUIRED LONG-TERM DESIGN STRENGTH} = \text{LTDS BASED ON 100\% COVERAGE} \times (W + S) / W$$

SEE TABLE FOR LTDS BASED ON 100% COVERAGE AND GEOGRID PLACEMENT DETAILS FOR PRIMARY GEOGRID ROLL WIDTH (W) AND SPACING (S).FOR PRIMARY GEOGRIDS WITH LESS THAN 100% COVERAGE,STAGGER PRIMARY GEOGRIDS SO GEOGRIDS ARE CENTERED OVER GAPS IN THE PRIMARY GEOGRID LAYER BELOW.DO NOT USE LESS THAN 75% COVERAGE FOR PRIMARY GEOGRIDS.

- DO NOT PLACE ANY GEOGRIDS UNTIL EXCAVATION DIMENSIONS AND IN-SITU MATERIAL ARE APPROVED.
- FOR SLOPE EROSION CONTROL,USE GEOCELLS OR MATting ON SLOPE FACES OF RSS AS FOLLOWS:

| RSS ANGLE | SLOPE EROSION CONTROL |
|----------------------|---|
| 1:1 TO < 1.5:1 (H:V) | GEOCELLS WITH COMPOST BLANKET |
| 1.5:1 TO < 2:1 (H:V) | GEOCELLS WITH COMPOST BLANKET OR COIR FIBER MAT WITH SHOULDER AND SLOPE BORROW* |
| 2:1 (H:V) OR FLATTER | MATting FOR EROSION CONTROL WITH SHOULDER AND SLOPE BORROW |

*SEE REINFORCED SOIL SLOPES AND SLOPE EROSION CONTROL SUMMARY TABLE IN THE ROADWAY SUMMARY SHEETS FOR SLOPE EROSION CONTROL ON SLOPE FACES OF RSS 1.5:1 (H:V) TO STEEPER THAN 2:1.

NON-STANDARD RSS LOCATIONS

| LINE | SIDE | BEGIN STATION | END STATION | L/H RATIO | PRIMARY GEOGRID,MD MINIMUM REQUIRED LTDS (LB/FT) |
|------|------|---------------|-------------|-----------|--|
| -L- | LT | 1253+50 | 1256+50 | 2.3 | 1200 |

NOTE: FOR SECONDARY GEOGRID,MINIMUM REQUIRED LTDS IN THE CROSS-MACHINE DIRECTION IS 185 LB/FT.

NON-STANDARD DETAIL

NON-STANDARD REINFORCED SOIL SLOPE (RSS) WITH HIGH GROUNDWATER SHEET 2 OF 2