



DOCUMENT NOT CONSIDERED FINAL  
UNLESS ALL SIGNATURES COMPLETED

**Michael Baker**  
INTERNATIONAL

|  |   |
|--|---|
| TEMPORARY SHORING LOCATION NO. <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">1-5</span> | SEE SHEET TMP-4E<br>ESTIMATED QUANTITY = 835.7 SF |
|--|---|

-LREV- STA. 1003+39, 7' LT TO -LREV- STA. 1004+00, 18' LT  
LENGTH=61.0' AVERAGE HEIGHT = 13.7 FT MAXIMUM HEIGHT = 20.4 FT

**SHORING LOCATION NO. 1-5**

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS

DESIGN TEMPORARY SHORING FROM STATION -LREV- 1003+39 ±, 18 FT LEFT TO STATION -LREV- 1004+00 ±, 18 FT LEFT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 PCF  
FRICTION ANGLE (φ) = 30 DEGREES  
COHESION (c) = 0 PSF  
GROUNDWATER ELEVATION = 187.5 FT

DO NOT USE A TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -LREV- 1003+39 ±, 18 FT LEFT TO STATION -LREV- 1004+00 ±, 18 FT LEFT.

IT MAY BE PREFERRED TO USE A TEMPORARY SOIL NAIL WALL FOR TEMPORARY SOIL NAIL WALL FOR TEMPORARY SHORING FROM STATION -LREV- 1003+39 ±, 18 FT LEFT TO STATION -LREV- 1004+00 ±, 18 FT LEFT FOR TEMPORARY SOIL NAIL WALLS, SEE TEMPORARY SOIL NAIL WALLS PROVISION.

|  |  |
|--|--|
| TEMPORARY SHORING LOCATION NO. <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">1-7</span> | SEE SHEET TMP-4E<br>ESTIMATED QUANTITY = 1864.8 SF |
|--|--|

-LREV- STA. 1003+28, 10.0' LT TO -LREV- STA. 1004+00, 10.0' LT  
LENGTH=72.00' AVERAGE HEIGHT = 25.9 FT MAXIMUM HEIGHT = 27.9 FT

**SHORING LOCATION NO. 1-7**

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -LREV- 1003+28 ±, 10 FT LEFT, TO STATION -LREV- 1004+00 ±, 10 FT LEFT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 PCF  
FRICTION ANGLE (φ) = 30 DEGREES  
COHESION (c) = 0 PSF  
GROUNDWATER ELEVATION = 187.5 FT

DO NOT USE CANTILEVER, BRACED OR ANCHORED SHORING FOR TEMPORARY SHORING FROM STATION LREV- 1003+28 ±, 10 FT LEFT, TO STATION -LREV- 1004+00 ±, 10 FT LEFT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -LREV- 1003+28 ±, 10 FT LEFT, TO STATION -LREV- 1004+00 ±, 10 FT LEFT. SEE STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY WALLS.

WHEN BACKFILL FOR BRIDGE APPROACH FILLS OVERLAPS WITH THE REINFORCED ZONE OF TEMPORARY WALLS, USE SHORING BACKFILL OR BACKFILL MATERIAL REQUIRED FOR BRIDGE APPROACH FILLS, WHICHEVER IS BETTER, IN THE REINFORCED ZONE OF TEMPORARY WALLS.

|  |  |
|--|--|
| TEMPORARY SHORING LOCATION NO. <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">1-6</span> | SEE SHEET TMP-4E<br>ESTIMATED QUANTITY = 1113.4 SF |
|--|--|

-LREV- STA. 1002+00, 13.0' LT TO -LREV- STA. 1002+28, 13.0' LT  
LENGTH=38.00' AVERAGE HEIGHT = 29.3 FT MAXIMUM HEIGHT = 31.3 FT

**SHORING LOCATION NO. 1-6**

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -LREV- 1002+00 ±, 13 FT LEFT TO STATION -LREV- 1002+38 ±, 13 FT LEFT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 PCF  
FRICTION ANGLE (φ) = 30 DEGREES  
COHESION (c) = 0 PSF  
GROUNDWATER ELEVATION = 187.5 FT

DO NOT USE A CANTILEVER, BRACED OR ANCHORED SHORING FOR TEMPORARY SHORING FROM STATION -LREV- 1002+00 ±, 13 FT LEFT, TO STATION -LREV- 1002+38 ±, 13 FT LEFT.

WHEN BACKFILL FOR BRIDGE APPROACH FILLS OVERLAPS WITH THE REINFORCED ZONE OF TEMPORARY WALLS, USE SHORING BACKFILL OR BACKFILL MATERIAL REQUIRED FOR BRIDGE APPROACH FILLS, WHICHEVER IS BETTER, IN THE REINFORCED ZONE OF TEMPORARY WALLS.

|  |   |
|--|---|
| TEMPORARY SHORING LOCATION NO. <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">1-8</span> | SEE SHEET TMP-5C<br>ESTIMATED QUANTITY = 318 SF |
|--|---|

-L- STA. 973+00, 77.0' LT TO -L- STA. 973+00, 97.0' LT  
LENGTH=20.00' AVERAGE HEIGHT = 15.9 FT MAXIMUM HEIGHT = 16.5 FT

**SHORING LOCATION NO. 1-8**

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

LIMITED SUBSURFACE INFORMATION IS AVAILABLE IN THE VICINITY OF TEMPORARY SHORING FROM STATION -L- 973+00 ±, 77 FT LEFT, TO STATION -L- 973+00 ±, 97 FT LEFT. THE INFORMATION PROVIDED FOR TEMPORARY SHORING DESIGN WAS ASSUMED AND MAY NOT BE APPLICABLE TO THE ACTUAL SITE CONDITIONS ENCOUNTERED DURING CONSTRUCTION.

DESIGN TEMPORARY SHORING FROM STATION -L- 973+00 ±, 77 FT LEFT, TO STATION -L- 973+00 ±, 97 FT LEFT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:

UNIT WEIGHT (γ) = 120 PCF  
FRICTION ANGLE (φ) = 30 DEGREES  
COHESION (c) = 0 PSF  
GROUNDWATER ELEVATION = 181.5 FT

DO NOT USE CANTILEVER, BRACED OR ANCHORED SHORING FOR TEMPORARY SHORING FROM STATION -L- 973+00 ±, 77 FT LEFT, TO STATION -L- 973+00 ±, 97 FT LEFT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -L- 973+00 ±, 77 FT LEFT, TO STATION -L- 973+00 ±, 97 FT LEFT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.02.

THE TEMPORARY SHORING NOTES SHOWN ON THIS SHEET WERE PROVIDED THROUGH A SEALED DOCUMENT FROM THE GEOTECHNICAL ENGINEER. THE DOCUMENT WAS SUBMITTED TO THE WZTC SECTION MICHAEL BAKER INTERNATIONAL ON SEPTEMBER 4, 2020 AND SEALED BY A PROFESSIONAL ENGINEER, STACIE E. MITCHELL, LICENSE #032125.

AREA 1

TEMPORARY SHORING  
NOTES/LOCATIONS

4/2/2021  
 R:\Traffic\Transportation Management\PLAN SHEETS\I-5986B TMP 02GI.A1-2 TEMPORARY SHORING NOTES LOCATIONS.dgn  
 Caroline.Owings