

January 9, 2020

North Carolina Department of Transportation Geotechnical Unit Mail Service Center 1592 Raleigh, North Carolina 27699-1592

Attention: Mr. Craig Haden

email: <u>cehaden@ncdot.gov</u>

Reference: Preliminary Site Assessment Report NCDOT Project I-5878, WBS Element 53078.1.1 Parcel 78 - BP I Mart 501-503 Spring Branch Road Dunn, Harnett County, North Carolina S&ME Project 4305-19-161

Dear Mr. Haden:

S&ME, Inc. (S&ME) is submitting this Preliminary Site Assessment (PSA) Report to the North Carolina Department of Transportation (NCDOT). This report presents the background/project information, field activities, findings, conclusions, and recommendations. These services were performed in general accordance with S&ME Proposal No. 43-1900576 REV-01 dated August 9, 2019, and Contract Number 7000018853 dated April 12, 2018 between NCDOT and S&ME, Inc., authorized by NCDOT in its September 5,2019 Notice to Proceed Letter.

Background/Project Information

Based on NCDOT's July 24, 2019, Request for Technical and Cost Proposal, the PSA was conducted within the NCDOT right-of-way (ROW) and/or easement as indicated on the preliminary plan sheets provided by NCDOT at the following property:

NCDOT Parcel No.	Property Owner	Site Address
78	I – Mart, LLC	(BP I-Mart)
		501-503 Spring Branch (aka Pope Road), Dunn, NC



The property is developed with an active gasoline/convenience store identified as BP I-Mart. The petroleum underground storage tanks (USTs) that the BP I-Mart operate are located on the southern end of the property adjoining Parcel 200 (Former T-Mart). The western end of the USTs extend across the ROW. The BP I-Mart and the former T-Mart are both listed with the same UST Facility ID No. of 0-00-000017633. Information regarding the UST system listed for the BP I-Mart is provided in the following table:

UST Facility ID No. 0-00-000017633

Number of Tanks	Contents	Capacity (gallons)	Date Installed	Date Removed
1	Gasoline	10,000	8/15/1999	Active USTs
2	Gasoline	10,000	8/15/1999	Active USTs
3	Gasoline	8,000	8/15/1999	Active USTs

The BP I-Mart property is not listed with a North Carolina Department of Environmental Quality (NCDEQ) Incident associated with petroleum releases from USTs or aboveground storage tanks. However, the location of the existing USTs for the BP I-Mart are located near the former UST area for the adjoining Former T-Mart. In addition, a well identified as RW-2 (previously MW-4) associated with the Former T-Mart release is located on the BP I-Mart property within the ROW. The BP I-Mart site is located downgradient of the Former T-Mart. However, free product has previously been measured in RW-2. In 2017, several petroleum constituents were reported in RW-2 at concentrations exceeding their respective15A NCAC 2L Groundwater Quality Standards (2L Standards) *AFVR and Groundwater Monitoring Report* prepared by Geologic Resources, Inc dated May 25, 2017).

The PSA included a geophysical survey and subsequent limited soil sampling (11 soil borings up to 10 feet below ground surface (ft.-bgs)) and limited groundwater sampling (one groundwater sample), within accessible areas of the proposed ROW/easement in preparation for construction activities. **Figure 1** shows the vicinity and site location, and **Figure 2** shows the site and boring locations. Soil and groundwater sampling results are shown on **Figure 3**.

Field Services

Prior to field activities, a site specific Health and Safety Plan was prepared as required by the Occupational Health and Safety Act (OSHA). Underground utilities were located and marked by the North Carolina One-Call Service. A private utility locator (East Coast Underground, LLC) was also used to locate and mark underground utilities.

Geophysical Survey

On July 25, 2019, S&ME completed Time Domain Electromagnetic (TDEM) and Ground Penetrating Radar (GPR) surveys within accessible areas of the proposed ROW/easement at Parcel 78. Brief descriptions of these complementary geophysical techniques are presented in the following paragraphs.



Time Domain Electromagnetics (TDEM)

TDEM measures the electrical conductivity of subsurface materials and discriminates between moderately conductive earth materials and very conductive metallic targets within the shallow subsurface. The conductivity is determined by transmitting a time-varying magnetic pulse into the subsurface and measuring the amplitude and phase shift of the secondary magnetic field. The secondary magnetic field is created when the conductive materials become an inductor as the primary magnetic field is passed through them. TDEM data are acquired continuously at a walking pace typically along a series of parallel or perpendicular lines. The system generates audible and visual indications when metallic targets are encountered. These measurements can also be supported with a global positioning system (GPS) which is output directly into the TDEM data file.

We used a Geonics Limited EM-61 MK2 TDEM system in general accordance with ASTM D6820 "Standard Guide for Use of the Time Domain Electromagnetic Method for Subsurface Investigation." Data was collected along lines spaced at approximately five feet using a Juniper[®] Systems Geode[™] sub-meter GPS as positioning support. The presence of landscaping/vegetations within the survey area, however, prevented TDEM data collection in a small area at the northeastern corner of the site. The approximate TDEM data collection paths are presented in **Figure 4.** Golden Software's Surfer[®] program was used to grid and plot the data (**Figures 5 and 6**). The TDEM data has been presented as Plots A and B in order to provide both opaque and semi-transparent views, respectively.

Ground Penetrating Radar (GPR)

GPR transmits electromagnetic waves into the subsurface from an antenna at a specific frequency and measures the time for wave reflections to be received by interfaces between materials with differing material properties (e.g. soil/metal, etc.). The intensity of the reflected GPR wave is a function of the contrast in the material properties (i.e. dielectric permittivity) at the interface, the conductivity of the material that the wave is traveling through, and the frequency of the signal.

We used a Geophysical Survey Systems, Inc. (GSSI) SIR[®] 4000 GPR system equipped with a 350 MHz antenna in general accordance with ASTM D6432 "*Standard Guide for Using the Surface Ground Penetrating Radar Method for Subsurface Investigation*" to further characterize anomalies/features identified during the TDEM survey.

A total of three GPR profiles (Lines 1 through 3) were collected for documentation (**Figure 7**). The data was post-processed using the GSSI Radan[®] 7 GPR software program for additional analysis.

Geophysical Findings

Anomalous features unrelated to known surficial targets were not identified in the geophysical data sets. However, the locations of the current three existing USTs, extending into the survey area, were confirmed by the GPR survey **(Figures 6 and 7).** The identified USTs are characterized by high amplitude GPR responses located about 2.5 ft.-bgs. An example GPR profile is presented in **Figure 8.**

Soil Sampling

On October 28, 2019, Troxler Geologic, Inc. (Troxler's) drill crew utilized a track mounted Geoprobe® rig to advance 11 soil borings (B-1 through B-11) and to collect soil samples within accessible areas of the proposed ROW/easement at Parcel 78. The approximate location of the soil borings are shown in **Figure 2**. A photographic



log is included in **Appendix I.** Troxler's drill crew advanced the Geoprobe® borings up to a depth of approximately 10 ft.-bgs. During the advancement of the soil borings, groundwater was encountered at a depth of approximately seven ft.-bgs. Soil samples were continuously collected in four-foot long disposable acetate-plastic sleeves that line the hollow stainless-steel sample probes. Soil recovered from the sleeves was classified on-site by S&ME personnel and screened with a Photoionization Detector (PID) at approximately two foot depth intervals to measure relative headspace concentrations of volatile organic compounds (VOCs).

VOC headspace readings were obtained from an aliquot of each soil sample that was placed in a re-sealable bag. Another portion of the sample was placed in a separate re-sealable bag and stored in an insulated container with ice for possible laboratory analyses. After waiting approximately 15 minutes to allow the sample to reach ambient temperature and headspace equilibrium, the PID probe was inserted into the bag to obtain a headspace reading. A summary of the PID readings and logs of the soil borings are included in **Appendix II**.

Petroleum odors and slightly elevated PID readings were noted at borings B-5 through B-10, which were located near the existing USTs and former UST basin areas. Petroleum odors were noted at borings B-5 and B-6 starting at a depth of approximately two ft.-bgs and extending to approximately four ft.-bgs. Petroleum odors were noted at a depth of approximately 0.5 ft.-bgs at borings B-7 and B-8 and extending to approximately four ft.-bgs to seven ft.-bgs, respectively. Petroleum odors were noted at borings B-9 from approximately two ft.-bgs to seven ft.-bgs. Petroleum odors were noted at boring B-10 from approximately 4 ft.-bgs to eight ft.-bgs. Groundwater was encountered at a depth of approximately seven ft.-bgs. Therefore, a soil sample was selected from these borings at the two to four foot depth interval or the four to six foot depth. Various soil samples at varying depth intervals were selected from the remaining borings. The soil samples were placed into laboratory supplied containers and transported to RED Lab, LLC (Red Lab) in an insulated cooler with ice for analysis. A total of 11 soil samples (one soil sample per boring) were analyzed by RED Lab for TPH-GRO and TPH-DRO using ultra-violet fluorescence (UVF) spectroscopy with product (fuel) identification.

Soil Analytical Results

Based upon analytical results of soil samples analyzed by RED Lab using UVP spectroscopy, TPH-GRO and TPH-DRO were not reported at concentrations exceeding their respective North Carolina TPH Action Levels. TPH-GRO and TPH-DRO were reported in borings B-2 and B-3 at the two to four foot depth interval at concentrations above the laboratory reporting limits but well below their North Carolina TPH Action Levels. TPH-DRO was also reported in borings B-1, B-4, B-5, and B-8 at the two to four foot depth interval and borings B-9 and B-11 at the four to six foot depth interval at concentrations well below its North Carolina TPH Action Level. TPH-GRO and TPH-DRO were not reported at concentrations exceeding the laboratory method reporting limits at the remaining soil samples. A summary of the soil analytical results is presented in **Table 1** and shown on **Figure 3**. A copy of the laboratory analytical report provided by RED Lab is presented in **Appendix III**.

Groundwater Sampling

During the advancement of the soil borings, groundwater was encountered at a depth of approximately seven ft.bgs. The vault for the existing well identified as RW-2 located within the ROW on the property was filled with rain water and was not gauged or sampled. Therefore, the Geoprobe® was used to advance one of the soil borings into the groundwater table for the collection of a groundwater sample. Based on petroleum odors, apparent downgradient location from the existing USTs and location near the former USTs, boring B-7, was selected for



collection of a groundwater sample. A temporary monitor well (TW-1) was installed at boring B-7 to a depth of approximately 11.5 ft.-bgs using a ten foot section of one-inch diameter, Schedule 40 PVC well riser attached to a five foot section of 0.01-inch slotted screen that intersected the groundwater table. Groundwater within the temporary monitor well at boring B-7 was measured at 6.78 ft.-bgs. Groundwater was purged from the temporary well until relatively clear using disposable tubing attached to a peristaltic pump. The flow rate was reduced and laboratory supplied containers were filled directly from the tubing, labeled as TW-1 and placed in an insulated cooler with ice for transport to Con-Test Laboratories (Con-Test) for analysis of VOCs by EPA Method 8260 and polycyclic aromatic compounds (PAHs) by EPA Method 8270.

Upon completion of the soil and groundwater sampling, the well materials were removed and the soil borings backfilled with bentonite pellets and soil cuttings. Investigative derived wastes (IDW), such as soil cuttings generated during the soil boring advancement and decontamination water, were spread on the ground in accordance with the procedures specified by NCDEQ. Used gloves and tubing were bagged and disposed offsite.

Groundwater Analytical Results

Based upon analytical results of the groundwater sample analyzed by Con-Test, numerous petroleum related target constituents were reported at concentrations exceeding their 2L Standards. Benzene was the highest constituent reported above its 2L Standard at a concentration of 330 micrograms per liter (μ g/L), which exceeds its 2L Standard of 1 μ g/L. A summary of the groundwater analytical results is presented in **Table 2** and shown on **Figure 3**. A copy of the laboratory analytical report provided by Con-Test is presented in **Appendix III**.

Conclusion and Recommendations

Existing groundwater monitoring well identified as RW-2 (previously MW-4) is located on the property within the ROW. The well is associated with a UST release from the Former T-Mart (NCDEQ Incident # 18955), which adjoins the property to the south. Free product has previously been measured in RW-2. In 2017, several petroleum constituents were reported in RW-2 at concentrations exceeding their respective 2L Standards.

The geophysical survey confirmed the locations of the current three existing, active, USTs associated with the BP I-Mart. The western ends of the two 10,000-gallon gasoline and one 8,000-gallon gasoline USTs extend across the ROW. The location of the existing USTs for the BP I-Mart are located near the former UST area for the adjoining Former T-Mart.

S&ME advanced 11 soil borings (B-1 through B-11) to a depth of up to approximately 10 ft.-bgs at the site. Petroleum odors and elevated PID readings were noted at borings B-5 through B-10, which were located near the existing USTs and former UST basin areas. Petroleum odors were noted starting at depths ranging from 0.5 ft.bgs and extending to up to boring termination at eight ft.-bgs. Groundwater was encountered at a depth of approximately seven ft.-bgs. Selected soil samples from the soil borings were analyzed for TPH-GRO and TPH-DRO using UVF spectroscopy.

TPH-GRO and TPH-DRO were not reported at concentrations exceeding their respective North Carolina TPH Action Levels. TPH-GRO and TPH-DRO were reported in borings B-2 and B-3 at the two to four foot depth interval. TPH-DRO was also reported in borings B-1, B-4, B-5, and B-8 at the two to four foot depth interval.



However, TPH-GRO and TPH-DRO were reported in these borings at concentrations well below their North Carolina TPH Action Levels. TPH-GRO and TPH-DRO were not reported at concentrations exceeding the laboratory method reporting limits at the remaining soil samples.

During the soil boring advancement, groundwater was encountered at a depth of approximately seven ft.-bgs. One temporary well (TW-1) was installed at soil boring B-7 located at an apparent downgradient location from the existing USTs and near the former UST area. Groundwater at TW-1 was measured at 6.78 ft.-bgs and analyzed by Con-Test for VOCs by EPA Method 8260 and PAHs by EPA Method 8270. Several petroleum related target constituents were reported at concentrations exceeding their 2L Standards.

Based on the findings of the geophysical survey, the western end of three existing, active, USTs extend across the ROW. Based on the analytical results of soil and groundwater samples, it is likely that during construction, NCDOT may encounter marginally impacted soil (below TPH Action Levels) and groundwater impacted with petroleum at the site. Petroleum odors were noted in soil samples at depths ranging from 0.5 ft.-bgs to boring termination at eight ft.-bgs, which extends into the groundwater encountered at approximately seven ft.-bgs. However, TPH-GRO and TPH-DRO were not reported at concentration exceeding their TPH Action Levels.

It should also be assumed that saturated petroleum impacted soil will be encountered if construction excavations extend deeper than seven ft.-bgs on the site. If construction dewatering is required, petroleum impacted groundwater must be properly disposed or treated at a licensed facility. If petroleum stained or odorous soils are encountered during construction, these soils should be properly handled and disposed at a licensed facility.

S&ME recommends maintaining an awareness level for the presence of marginally impacted petroleum in the soil (below TPH Action Levels) and groundwater at the site for the safety of workers and the public.

Limitations

The results of this preliminary investigation are limited to the boring locations presented herein. The results of this Preliminary Site Assessment are not all inclusive and may not represent existing conditions across the entire property. These results only reflect the current conditions at the locations sampled on the date this Preliminary Site Assessment was performed. This report has been prepared in accordance with generally accepted environmental engineering and geophysical practice for specific application to this project. The conclusions and recommendations contained in this report are based upon applicable standards of our practice in this geographic area at the time this report was prepared. No other warranty, expressed or implied, is made.

The geophysical methods used for this survey have inherent limitations. Site metallic features (e.g., reinforced concrete, utilities, etc.) and overhead transmission lines can produce a false electromagnetic response and may mask subsurface features. The depth of exploration of the GPR signal is highly site specific and is greatly limited by signal attenuation (absorption) of the subsurface materials. Signal attenuation is dependent upon the electrical conductivity of the subsurface materials. Signal attenuation is greatest in materials with relatively high electrical conductivities such as clay soils, and lowest in relatively low conductivity materials such as unsaturated sand. For this project location, the GPR data sets appear to have a maximum depth of penetration of about six ft.-bgs.

Regardless of the thoroughness of a geophysical study, there is always a possibility that actual conditions may not match the interpretations. The results should be considered accurate only to the degree implied by the methods



used and the method's limitations and data coverage. Accordingly, the possibility exists that not all features at a project site will be located due to either subsurface soil conditions or the occurrence of features outside the lateral limits and below the depth of penetration of the methods used. As with most surface geophysical methods, resolution of the subsurface will also decrease with depth. As such, the size and/or contrast of features compared to the imaged subsurface media must be significant enough to produce the anticipated response. The location and/or determination (or the lack thereof) of potential buried features is based on our review of the provided information and of the geophysical survey. Under no circumstances does S&ME assume any responsibility for damages resulting from the presence of subsurface features that may exist but were not identified by our survey.

This Preliminary Site Assessment was performed solely for NCDOT regarding the above-referenced site and assessment area. This report is provided for the sole use of NCDOT. Use of this report by any other parties will be at such party's sole risk. S&ME disclaims liability for any such use or reliance by third parties. The observations presented in this report are indicative of conditions during the time of the assessment and of the specific areas referenced.

Closing ٠

S&ME appreciates the opportunity to provide these services to you. If you have any questions or comments regarding this report, please contact us at your convenience.

Sincerely,

S&ME, Inc. DocuSigned by: Amie Honeycutt 4C890EAEC25F488. Jamie T Honeycutt **Environmental Professional** ihoneycutt@smeinc.com



DocuSigned by: Iom Kaymond D4B9FB5F636F4BB

DocuSigned by: Michael Phi 861E52DDEFAF4C7

Michael W. Pfeifer Senior Project Manager mpfeifer@smeinc.com

Thomas P. Raymond, P.E., P.M.P. Senior Consultant traymond@smeinc.com



Attachments:

Table 1: Summary of Soil Sampling Results**Table 2**: Summary of Groundwater Sampling Results

Figure 1: Vicinity Map
Figure 2: Site Map
Figure 3: Soil and Groundwater Constituent Map
Figure 4: TDEM Path Location Plan
Figure 5: TDEM Data Plot A
Figure 6: TDEM Data Plot B
Figure 7: Geophysical Anomaly Location Plan
Figure 8: Example GPR Data – Line 3

Appendix I:PhotographsAppendix II:Boring LogsAppendix III:Laboratory Analytical Reports and Chain of Custody

Tables



TABLE 1 SUMMARY OF SOIL SAMPLING RESULTS NCDOT Project I-5878 Parcel 78 - (BP I-Mart) 501 - 503 Spring Branch Road Dunn, Harnett County, North Carolina S&ME Project No. 4305-19-161

Ar	nalytical Metho	d→	Range Organics (GR Organics (DRO) by UI	carbons (TPH) Gasoline RO) and Diesel Range traviolet Fluorescence ectrometry
Sample ID	Date	Contaminant of Concern→ Sample Depth (ftbgs)	TPH-GRO	TPH-DRO
B-1	10/28/2019	2 to 4	<0.52	1.2
B-2	10/28/2019	2 to 4	2.6	25
B-3	10/28/2019	2 to 4	3.7	27.6
B-4	10/28/2019	2 to 4	<0.49	1.4
B-5	10/28/2019	2 to 4	<0.53	3.8
B-6	10/28/2019	2 to 4	<0.27	<0.27
B-7	10/28/2019	2 to 4	<0.5	<0.5
B-8	10/28/2019	2 to 4	<0.26	0.26
B-9	10/28/2019	4 to 6	<0.29	11
B-10	10/28/2019	4 to 6	<0.29	<0.29
B-11	10/28/2019	4 to 6	<0.28	5.7
Notes:	orth Carolina T	PH Action Levels	50	100

Notes:

1. UVF analysis performed by RED Lab, LLC

2. Concentrations are reported in milligrams per kilogram (mg/Kg).

3. ft.-bgs:- feet below ground surface.

4. Concentrations exceeding the laboratory's reporting limits are shown in **BOLD** fields.

5. Concentrations exceeding the North Carolina TPH Action Levels are shown in Shaded and **BOLD** fields.

TABLE 2SUMMARY OF GROUNDWATER SAMPLING RESULTSNCDOT Project I-5878Parcel 78 - (BP I-Mart)501 - 503 Spring Branch RoadDunn, Harnett County, North CarolinaS&ME Project No. 4305-19-161

Analytical	Method→		Volatile Organic Compounds by EPA Method 8260							Polycyclic Aromatic Compounds (PAHs) by EPA Meth 8270						lethod							
Sample ID	Contaminant of Concern→ Date	Benzene	Diisopropyl Ether	Ethylbenzene	lsopropylbenzene	MTBE	Naphthalene	n-Butylbenzene	sec-Butylbenzene	tert-Butyl Alcohol	n-Propylbenzene	Toluene	1,2,4- Trimethylbenzene	1,3,5- Trimethylbenzene	Total Xylenes	Acenaphthene	Acenaphthylene	Fluoranthene	Fluorene	Naphthalene	Phenanthrene	Pyrene	2-Methylnaphthalene
B-7/TW-1	10/28/2019	330	2.0 J	19	3.2 J	11	37	3.8 J	1.2 J	480	3.9 J	12	8.3	1.0 J	43	0.13 J	0.079 J	0.052 J	0.14 J	25	0.13	0.049 J	21
2L S	Standard (µg/L)	1	70	600	70	20	6	70	70	10	70	600	400	400	500	80	200	300	300	6	200	200	30
	GCL (µg/L)	5,000	70,000	84,500	25,000	20,000	6,000	6,900	8,500	10,000	30,000	260,000	28,500	25,000	85,500	2,120	1,965	300	990	6,000	410	200	12,500

Notes:

1. Analytes that are not shown for the method were not detected.

2. Concentrations are reported in micrograms per liter (µg/L).

3. 2L Standard: North Carolina Groundwater Quality Standards: 15A NCAC 2L.0202


4. Concentrations exceeding the laboratory's reporting limits are shown in **BOLD** fields.


5. Concentrations exceeding the 2L Standards are shown in Shaded and BOLD fields.

6. GCL: Gross Contamination Level.

7. J: Estimated concentration detected below the reporting limit.

Figures





LEGEND Geoenvironmental Boring: Underground Storage Tank (UST): UST Map Source: NCDOT Project I-5986B Image Source: NC ONEMAP, Dated 2016

8


ΞM

Known Soil Contamination: 淡 Possible Soil Contamination: 淡ーsー ぷ Existing Contamination Known - Water: 涼 ーwー 淡 Existing Monitoring Well: O

SITE MAP

NCDOT Project: I-5878 PARCEL 78 - BP I-MART 501-503 Spring Branch Road, Dunn, Harnett County, North Carolina

0	40	80
G	GRAPHIC SCALE	(IN FEET)
	SCALE:	FIGURE NO.
	1" = 40'	
	DATE:	
	JAN. 2020	2
	PROJECT NUMBER	
	4305-19-161	





ΞM


SOIL AND GROUNDWATER CONSTITUENT MAP


NCDOT Project: I-5878 PARCEL 78 - BP I-MART 501-503 Spring Branch Road, Dunn, Harnett County, North Carolina


SCALE:	FIGURE NO.
1" = 40'	
DATE:	
NOV. 2019	3
PROJECT NUMBER	
4305-19-161	ノノ
	1" = 40' DATE: NOV. 2019 PROJECT NUMBER












Appendix I – Photographs








i







Appendix II – Boring Logs

PROJECT:	NCDOT I-5878									
	Parcel 78-501-503 Spring Branch Rd (BP - I-Mart S&ME Project No. 4305-19-161	:), Dunn, NC			BORIN	IG LOG:	B-1			
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appli	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:								
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:	-							
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
5	alt, Gravel, ly Clay, Orange, Sand, Orange, Red, ng Terminated at 8 Ft-BGS		•		0.0 0.2 0.5	No Yes No	1210			

PROJECT:	NCDOT I-5878									
	Parcel 78-501-503 Spring Branch Rd (BP - I-Mart S&ME Project No. 4305-19-161), Dunn, NC			BORIN	IG LOG:	B-2			
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appl	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:	J. Honeyc	cutt						
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:								
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
Asph	alt, Gravel, y Clay, Orange,				0.0 0.6	No Yes	1220			
5 Silty	Sand, Orange, Red,				0.7	No				
Borir	ig Terminated at 8 Ft-BGS		▼							
10										
 15										
20 —										
25 —										
30				I					I	

PROJECT:	NCDOT I-5878				PODIA	IG LOG:	D 2			
	Parcel 78-501-503 Spring Branch Rd (BP - I-Mart S&ME Project No. 4305-19-161	i), Dunn, NC			DUKI		D-2			
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:								
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:		icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:								
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:								
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
Aspt Sanc	alt, Gravel, y Clay, Orange,				1.3	No Yes	1230			
5					0.6	No				
	Sand, Orange, Red, ng Terminated at 8 Ft-BGS		•							
10										
 15										
20										
 25										
30										

PROJECT:	NCDOT I-5878									
	Parcel 78-501-503 Spring Branch Rd (BP - I-Ma S&ME Project No. 4305-19-161	art), Dunn, NC		BORING LOG: B-4						
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appl	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:								
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:	,							
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
	···· · · · · · · · · · · · · · · · · ·									
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
San	halt, Gravel, dy Clay, Orange,				0.9 2.3	No Yes	1245			
5	dy Clay, Red, Orange, Gray,				3.4	No				
Bor	ing Terminated at 8 Ft-BGS		▼							
10										
 15										
20 —										
 25										
30										

PROJECT:	NCDOT I-5878									
	Parcel 78-501-503 Spring Branch Rd (BP - I-Ma S&ME Project No. 4305-19-161	art), Dunn, NC		BORING LOG: B-5						
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appli	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:	J. Honeyc	utt						
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:								
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	n value
Aspl	halt, Gravel, dy Clay, Orange, Red, Gray,									
					39.7	No				
Sand	dy Clay, Orange, Red, Gray, Slight Petroleum Odors									
and the second sec	dy Clay, Orange, Red, Gray,				66.9	Yes	1430			
5					23.8	No				
	Sand, Red, Orange,		▼							
	ng Terminated at 8 Ft-BGS									
10 —										
15 —										
20 —										
25 —										
							1		I	1

PROJECT:	NCDOT I-5878									
	Parcel 78-501-503 Spring Branch Rd (BP - I-Maı S&ME Project No. 4305-19-161	rt), Dunn, NC			BORIN	IG LOG:	B-6			
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appli	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:	J. Honeyc	utt						
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:								
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
	ioil, ly Clay, Orange, ly Clay, Orange, Slight Petroleum Odors				0.0	No				
	iy Clay, Orange, Red, Gray,				13.8	Yes	1445			
5	Sand, Red, Orange,				13.1	No				
	ng Terminated at 8 Ft-BGS		▼							
 10										
15										
20										
 25										
30										

PROJECT:	NCDOT I-5878									
	Parcel 78-501-503 Spring Branch Rd (BP - I-Mart), Dunn, NC S&ME Project No. 4305-19-161				BORIN	ig log:	B-7/	TW-1		
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	12							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	EVEL: 6.78							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appl	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:	J. Honeyo	cutt						
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:								
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
				1		~	~			
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
Asp San	halt, Gravel, dy Clay, Orange, Slight Petroleum Odors				2.1	No				
	dy Clay, Orange,				9.4	Yes	1500			
5					2.3	No				
San	d, Tan, Orange,		▼							
10										
Bori	ing Terminated at 12 Ft-BGS									
15 —										
20 —										
25 —										

PROJECT:	NCDOT I-5878 Parcel 78-501-503 Spring Branch Rd (BP - I-Mart), Dunn, NC				PODIA		ро			
	S&ME Project No. 4305-19-161	u, duini, NC			DUKIN	IG LOG	D-Q			
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appl	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:	J. Honeyo	cutt						
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:								
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:		-	-					
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
Clay	nalt, Gravel, ey Sand, Tan, Slight Petroleum Odors				21.5	No				
5					10.3	Yes	1530			
Silty	Sand, Orange, Red, Slight Petroleum Odors		_		8.2	No				
Bori	ng Terminated at 8 Ft-BGS		•							
10										
15 —										
_										
20 —										
25 —										
30										

PROJECT:	NCDOT I-5878 Parcel 78-501-503 Spring Branch Rd (BP - I-Mart), Dunn, NC			BORING LOG: B-9										
	S&ME Project No. 4305-19-161	,, Dunn, NC			Denin		55							
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8											
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:												
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appl	icable										
HAMMER TYPE:	Not Applicable	LOGGED BY:												
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:												
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:												
DEPTH (feet) (feet) CAAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	n value				
Clay	rey Sand, Tan, Red,				15.4	No								
5					21.2	No								
	r Sand, Tan, Red,		▼		28.4	Yes	1545							
	ing Terminated at 8 Ft-BGS													
10														
 15														
20 —														
25 —														
30				1		l	1		<u> </u>					

PROJECT:	NCDOT I-5878									
	Parcel 78-501-503 Spring Branch Rd (BP - I-Ma S&ME Project No. 4305-19-161	rt), Dunn, NC			BORIN	IG LOG:	B-10			
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8							-
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7							
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appl	icable						
HAMMER TYPE:	Not Applicable	LOGGED BY:								
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:								
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:								
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE
Clay Clay	ey Sand, Tan, Red, ey Sand, Tan, Red,				1.3 4.0	No				
5 — Clay	ey Sand, Tan, Red, Petroleum Odors				6.2	Yes	1600			
	Sand, Tan, Red, Petroleum Odors ng Terminated at 8 Ft-BGS		•							
10										
15										
20 —										
25 —										
30										

PROJECT:	CT: NCDOT I-5878 Parcel 78-501-503 Spring Branch Rd (BP - I-Mart), Dunn, NC		BORING LOG: B-11											
	S&ME Project No. 4305-19-161	, Dunn, NC			DOKI		D-11							
DATE DRILLED:	Monday, October 28, 2019	BORING DEPTH (FT):	8											
DRILL RIG:	Geoprobe 54DT	WATER LEVEL:	7											
DRILLER:	Troxler Geologic, Inc.	CAVE-IN DEPTH:	Not Appli	icable										
HAMMER TYPE:	Not Applicable	LOGGED BY:	J. Honeyc	utt										
SAMPLING METHOD:	Macro-Core Sampler	NORTHING:												
DRILLING METHOD:	Macro-Core Sampler (3-in. OD)	EASTING:												
DEPTH (feet) GRAPHIC LOG	MATERIAL DESCRIPTION		WATER LEVEL	SAMPLE	PID READING (PPM)	LABORATORY ANALYSES	Sample Time / 1st 6in	2nd 6in	3rd 6in	N VALUE				
	ihalt, Gravel, yey Sand, Orange,		•		1.4 1.2 2.7	No No Yes	1615							
10	ing Terminated at 8 Ft-BGS													
25														

Appendix III – Laboratory Analytical Reports and Chain of Custody

	REDLAB APID ENVIRONMENTAL DIAGNOSTICS
--	---



Hydrocarbon Analysis Results

Client: S&ME Address: 3201 SPRING FOREST RD RALEIGH NC

Samples taken Samples extracted Samples analysed

Monday, October 28, 2019 Monday, October 28, 2019 Tuesday, October 29, 2019

Operator

MAX MOYER

Contact: JAMIE HONEYCUTT


Project: NCDOT I-5878 PARCEL 78

														U00902
Matrix	Sample ID	Dilution used	BTEX (C6 - C9)	GRO (C5 - C10)	DRO (C10 - C35)	TPH (C5 - C35)	Total Aromatics (C10-C35)	16 EPA PAHs	BaP	%	% Ratios		HC Fingerprint Match	I
										C5 - C10	C10 - C18	C18		
S	B-1 (2-4')	20.6	<0.52	<0.52	1.2	1.2	0.83	<0.17	<0.021	0	62.8	37.2	V.Deg.PHC 76.3%,(FCM),(P)	
S	B-2 (2-4')	22.8	<0.57	2.6	25	27.6	9.5	0.42	<0.023	31.5	45.9	22.7	Deg.PHC 78.4%,(FCM),(P)	
S	B-3 (2-4')	19.5	<0.49	3.7	27.6	31.3	22.9	0.77	<0.02	30.1	52.8	17.1	Deg Fuel 76.7%,(FCM),(P)	
s	B-4 (2-4')	19.4	<0.49	<0.49	1.4	1.4	0.66	<0.16	<0.019	89	8.3	2.7	Deg Fuel 89.1%,(FCM),(P)	
S	B-5 (2-4')	21.1	<0.53	<0.53	3.8	3.8	1.7	<0.17	<0.021	0	73.9	26.1	Deg Fuel 89.2%,(FCM)	
S	B-6 (2-4')	10.8	<0.27	<0.27	<0.27	0.2	0.2	<0.09	<0.011	0	67.3	32.7	Residual HC,(BO),(P)	
S	B-7 (2-4')	20.0	<0.5	<0.5	<0.5	<0.5	<0.1	<0.16	<0.02	0	0	0	Residual HC,(P)	
S	B-8 (2-4')	10.3	<0.26	<0.26	0.26	0.26	0.16	<0.08	<0.01	0	75.4	24.6	Deg Fuel 75.1%,(FCM),(P)	
S	B-9 (4-6')	11.8	<0.29	<0.29	11	11	10.5	0.41	<0.012	0	80.9	19.1	Deg.Fuel 82.2%,(FCM)	
S	B-10 (4-6')	11.8	<0.29	<0.29	<0.29	0.14	0.14	<0.09	<0.012	0	58.9	41.1	Residual HC	
	Initial C	alibrator	QC check	OK					Final FC	CM QC	Check	OK		100.8 %

Concentration values in mg/kg for soil samples and mg/L for water samples. Soil values uncorrected for moisture or stone content. Fingerprints provide a tentative hydrocarbon identification.

Abbreviations :- FCM = Results calculated using Fundamental Calibration Mode : % = confidence of hydrocarbon identification : (PFM) = Poor Fingerprint Match : (T) = Turbid : (P) = Particulate detected


B = Blank Drift : (SBS)/(LBS) = Site Specific or Library Background Subtraction applied to result : (BO) = Background Organics detected : (OCR) = Outside cal range : (M) = Modifed Result. % Ratios estimated aromatic carbon number proportions : HC = Hydrocarbon : PHC = Petroleum HC : FP = Fingerprint only. Data generated by HC-1 Analyser



Q	ED			E	RAPI			B TICS			_	\int	<u>QROS</u>
				Hydroca	arbon An	alysis R	esults						
Address:	S&ME 3201 SPRING FOREST RD RALEIGH NC								Sa Sample Sampl		acted		Monday, October 28, 2019 Monday, October 28, 2019 Tuesday, October 29, 2019
Contact:	JAMIE HONEYCUTT									Ор	erator		MAX MOYER
Project:	NCDOT I-5878 PARCEL 78												
													U00902
Matrix	Sample ID	Dilution used	BTEX (C6 - C9)	GRO (C5 - C10)	DRO (C10 - C35)	TPH (C5 - C35)	Total Aromatics (C10-C35)	16 EPA PAHs	BaP	a	% Ratios	;	HC Fingerprint Match
										C5 - C10	C10 - C18	C18	
S	B-11 (4-6')	11.0	<0.28	<0.28	5.7	5.7	3.3	0.12	<0.011	0	78.3	21.7	Deg Fuel 92.2%,(FCM)
	Initial C	alibrator	QC check	OK					Final F	CM QC	Check	OK	99.3 %
Concentratio	on values in mg/kg for soil samples and mg	/L for water	samples So	il values unco	prrected for m	oisture or sto	ne content. Fin	gernrints pr	ovide a tent	ative hvd	rocarbor	identifi	cation
	is :- FCM = Results calculated using Funda												
B = Blank D	rift : (SBS)/(LBS) = Site Specific or Library	Background	Subtraction	applied to res	sult : (BO) = B	ackground O	rganics detecte	ed : (OCR) =	= Outside ca	I range :	(M) = M		
70 Ratios es	timated aromatic carbon number proportion	IS : HC = HY	ulocarbon :	Pric = Petrol		= Fingerprint	only. Data	a generated	d by HC-1 A	maiyser			

QED Hydrocarbon Fingerprints

Project: NCDOT I-5878 PARCEL 78



NODOT I JETS POLLED 78	Ferende R.B. Dumme, NC	I and a second and	RAPID ENVIRONMENTAL DIAGNOSTICS	CHAIN OF CUSTODY AND ANALYTICAL		┝	Jr Initials Sample ID Sample ID	ATU R.1 1.41	202	56.2 44.8 11	53.2 43.9	57.7 UU.3	7 44.4	5.4.1 S.7.5 HH.5	27.6 44.6 1	0 0 -4 43.8 (1 26 July 11 6	56.7 44.8 H	1 4-10 J.						1 by	5	
StMF.S	NON NO	Harry with 7	1/20101 - I-5878 1 Parce 0-18	3	Tomie 7 Honer 21	equested	1											*							128/19 10/28/18	Date/	
Client Name:	Address:	Contact: Proiect Ref ·	Email:	Phone #:	Collected by:	Sample Collection	Date/Time	10 28-10 1210	1 1200	1 1230	Iarr	02111	i luus	1500	Č 1530	1545	(leno	1 I Rece				ш.	Comments:	Relinauished hv	and have	/ Relinquished by	



November 11, 2019

Jamie Honeycutt S&ME, Inc - Raleigh, NC 3201 Spring Forest Rd. Raleigh, NC 27616

Project Location: Dunn, NC Client Job Number: Project Number: 4305-19-161 Laboratory Work Order Number: 19J1775

Enclosed are results of analyses for samples received by the laboratory on October 28, 2019. If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Beny K. Millee

Kerry K. McGee Project Manager

Table of Contents

Sample Summary	3
Hits Only Report	4
Case Narrative	5
Sample Results	7
19J1775-01	7
Sample Preparation Information	10
QC Data	11
Volatile Organic Compounds by GC/MS	11
B244975	11
Semivolatile Organic Compounds by GC/MS	16
B244837	16
Flag/Qualifier Summary	18
Certifications	19
Chain of Custody/Sample Receipt	22



39 Spruce Street * East Longmeadow, MA 01028 * FAX 413/525-6405 * TEL. 413/525-2332 S&ME, Inc - Raleigh, NC 3201 Spring Forest Rd. REPORT DATE: 11/11/2019 Raleigh, NC 27616 PURCHASE ORDER NUMBER: ATTN: Jamie Honeycutt PROJECT NUMBER: 4305-19-161 ANALYTICAL SUMMARY 19J1775 WORK ORDER NUMBER: The results of analyses performed on the following samples submitted to the CON-TEST Analytical Laboratory are found in this report. PROJECT LOCATION: Dunn, NC FIELD SAMPLE # LAB ID: MATRIX TEST SUB LAB SAMPLE DESCRIPTION TW-1 19J1775-01 Ground Water SW-846 8260D

SW-846 8270E



EXECUTIVE SUMMARY

Client	ID.	TW-1
Chent	112.	1 22-1

Lab ID: 19J1775-01

Analyte	Results/Qua	1	DL	RL	Units	Method
1,2,4-Trimethylbenzene	8.3		0.90	5.0	μg/L	SW-846 8260D
1,3,5-Trimethylbenzene	1.0	J	0.70	5.0	μg/L	SW-846 8260D
Benzene	330		0.90	5.0	μg/L	SW-846 8260D
Diisopropyl Ether (DIPE)	2.0	J	0.85	2.5	μg/L	SW-846 8260D
Ethylbenzene	19		0.65	5.0	μg/L	SW-846 8260D
Isopropylbenzene (Cumene)	3.2	J	0.85	5.0	μg/L	SW-846 8260D
m+p Xylene	33		1.5	10	μg/L	SW-846 8260D
Methyl tert-Butyl Ether (MTBE)	11		1.2	5.0	μg/L	SW-846 8260D
Naphthalene	37		1.6	25	μg/L	SW-846 8260D
n-Butylbenzene	3.8	J	1.0	5.0	μg/L	SW-846 8260D
n-Propylbenzene	3.9	J	0.65	5.0	μg/L	SW-846 8260D
o-Xylene	10		0.85	5.0	μg/L	SW-846 8260D
sec-Butylbenzene	1.2	J	0.80	5.0	μg/L	SW-846 8260D
tert-Butyl Alcohol (TBA)	480		21	100	μg/L	SW-846 8260D
Toluene	12		0.70	5.0	μg/L	SW-846 8260D
2-Methylnaphthalene (SIM)	21		0.65	10	μg/L	SW-846 8270E
Acenaphthene (SIM)	0.13	J	0.034	0.31	μg/L	SW-846 8270E
Acenaphthylene (SIM)	0.079	J	0.036	0.21	μg/L	SW-846 8270E
Fluoranthene (SIM)	0.052	J	0.026	0.52	μg/L	SW-846 8270E
Fluorene (SIM)	0.14	J	0.035	1.0	μg/L	SW-846 8270E
Naphthalene (SIM)	25		2.7	10	μg/L	SW-846 8270E
Phenanthrene (SIM)	0.13		0.031	0.052	μg/L	SW-846 8270E
Pyrene (SIM)	0.049	J	0.024	1.0	$\mu g/L$	SW-846 8270E



CASE NARRATIVE SUMMARY

All reported results are within defined laboratory quality control objectives unless listed below or otherwise qualified in this report.

For method 8270, only PAHs were requested and reported.

SW-846 8260D

Qualifications:

L-02

Laboratory fortified blank/laboratory control sample recovery and duplicate recoveries outside of control limits. Data validation is not affected since all results are "not detected" for associated samples in this batch and bias is on the high side. Analyte & Samples(s) Qualified:

trans-1,4-Dichloro-2-butene

B244975-BS1, B244975-BSD1, S042201-CCV1

Vinyl Chloride

B244975-BS1, B244975-BSD1, S042201-CCV1

RL-11

Elevated reporting limit due to high concentration of target compounds.

Analyte & Samples(s) Qualified:

19J1775-01[TW-1]

V-05

Continuing calibration verification (CCV) did not meet method specifications and was biased on the low side for this compound.

Analyte & Samples(s) Qualified:

tert-Amyl Methyl Ether (TAME)

19J1775-01[TW-1], B244975-BLK1, B244975-BS1, B244975-BSD1, S042201-CCV1

V-20

Continuing calibration verification (CCV) did not meet method specifications and was biased on the high side. Data validation is not affected since sample result was "not detected" for this compound. Analyte & Samples(s) Qualified:

2-Hexanone (MBK)

B244975-BS1, B244975-BSD1, S042201-CCV1

4-Methyl-2-pentanone (MIBK)

B244975-BS1, B244975-BSD1, S042201-CCV1

Acetone

B244975-BS1, B244975-BSD1, S042201-CCV1

trans-1,4-Dichloro-2-butene

B244975-BS1, B244975-BSD1, S042201-CCV1

Vinyl Chloride

B244975-BS1, B244975-BSD1, S042201-CCV1



The results of analyses reported only relate to samples submitted to the Con-Test Analytical Laboratory for testing.

I certify that the analyses listed above, unless specifically listed as subcontracted, if any, were performed under my direction according to the approved methodologies listed in this document, and that based upon my inquiry of those individuals immediately responsible for obtaining the information, the material contained in this report is, to the best of my knowledge and belief, accurate and complete.

fra Watshington

Lisa A. Worthington Technical Representative



Volatile Organic Compounds by GC/MS

Sample Description:

Sampled: 10/28/2019 17:00

Project Location: Dunn, NC Date Received: 10/28/2019

Field Sample #: TW-1

Sample ID: 19J1775-01 Sample Matrix: Ground Water

Sample Flags: RL-11

Sample Flags: RL-11 Analyte	Results	RL	DL	Units	mpounds by G Dilution	Flag/Qual	Method	Date Prepared	Date/Time Analyzed	Analyst
Acetone	ND	250	19	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Acrylonitrile	ND	25	2.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
tert-Amyl Methyl Ether (TAME)	ND	5.0	0.70	μg/L	5	V-05	SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Benzene	330	5.0	0.90	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Bromobenzene	ND	5.0	0.75	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Bromochloromethane	ND	5.0	1.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Bromodichloromethane	ND	2.5	0.80	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Bromoform	ND	5.0	2.3	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Bromomethane	ND	10	3.9	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
2-Butanone (MEK)	ND	100	9.7	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
tert-Butyl Alcohol (TBA)	480	100	21	μg/L μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
n-Butylbenzene	3.8	5.0	1.0	μg/L	5	J	SW-846 8260D	11/4/19	11/4/19 15:46	EEH
sec-Butylbenzene	1.2	5.0	0.80		5	J	SW-846 8260D	11/4/19	11/4/19 15:46	EEH
tert-Butylbenzene	ND			μg/L ug/I	5	J				EEH
tert-Butyl Ethyl Ether (TBEE)		5.0	0.85	μg/L ug/I	5		SW-846 8260D	11/4/19	11/4/19 15:46	
Carbon Disulfide	ND	2.5	0.80	μg/L			SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Carbon Tetrachloride	ND	25	22	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Chlorobenzene	ND	5.0	0.55	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Chlorodibromomethane	ND	5.0	0.75	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
	ND	2.5	1.0	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Chloroethane	ND	10	1.8	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Chloroform	ND	10	0.85	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Chloromethane	ND	10	2.2	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
2-Chlorotoluene	ND	5.0	0.60	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
4-Chlorotoluene	ND	5.0	0.70	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2-Dibromo-3-chloropropane (DBCP)	ND	25	2.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2-Dibromoethane (EDB)	ND	2.5	0.95	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Dibromomethane	ND	5.0	1.8	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2-Dichlorobenzene	ND	5.0	0.80	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,3-Dichlorobenzene	ND	5.0	0.60	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,4-Dichlorobenzene	ND	5.0	0.65	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
trans-1,4-Dichloro-2-butene	ND	10	1.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Dichlorodifluoromethane (Freon 12)	ND	10	1.3	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1-Dichloroethane	ND	5.0	0.80	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2-Dichloroethane	ND	5.0	2.0	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1-Dichloroethylene	ND	5.0	1.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
cis-1,2-Dichloroethylene	ND	5.0	0.65	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
trans-1,2-Dichloroethylene	ND	5.0	1.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2-Dichloropropane	ND	5.0	1.0	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,3-Dichloropropane	ND	2.5	0.55	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
2,2-Dichloropropane	ND	5.0	1.0	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1-Dichloropropene	ND	10	0.80	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
cis-1,3-Dichloropropene	ND	2.5	0.65	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
trans-1,3-Dichloropropene	ND	2.5	1.2	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Diethyl Ether	ND	10	1.7	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH

Work Order: 19J1775

Page 7 of 24



Sample Description:

Sampled: 10/28/2019 17:00

Table of Contents

Work Order: 19J1775

Date Received: 10/28/2019

Project Location: Dunn, NC

Field Sample #: TW-1

Sample ID: 19J1775-01

Sample Matrix: Ground Water

Sample Flags: RL-11			Vola	tile Organic Com	pounds by G	C/MS				
Analyte	Results	RL	DL	Units	Dilution	Flag/Qual	Method	Date Prepared	Date/Time Analyzed	Analyst
Diisopropyl Ether (DIPE)	2.0	2.5	0.85	μg/L	5	J	SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,4-Dioxane	ND	250	110	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Ethylbenzene	19	5.0	0.65	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Hexachlorobutadiene	ND	3.0	2.4	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
2-Hexanone (MBK)	ND	50	7.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Isopropylbenzene (Cumene)	3.2	5.0	0.85	μg/L	5	J	SW-846 8260D	11/4/19	11/4/19 15:46	EEH
p-Isopropyltoluene (p-Cymene)	ND	5.0	1.0	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Methyl tert-Butyl Ether (MTBE)	11	5.0	1.2	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Methylene Chloride	ND	25	1.7	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
4-Methyl-2-pentanone (MIBK)	ND	50	8.4	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Naphthalene	37	25	1.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
n-Propylbenzene	3.9	5.0	0.65	μg/L	5	J	SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Styrene	ND	5.0	0.55	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1,1,2-Tetrachloroethane	ND	5.0	1.4	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1,2,2-Tetrachloroethane	ND	2.5	1.1	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Tetrachloroethylene	ND	5.0	0.90	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Tetrahydrofuran	ND	50	2.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Toluene	12	5.0	0.70	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2,3-Trichlorobenzene	ND	25	2.8	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2,4-Trichlorobenzene	ND	5.0	2.0	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,3,5-Trichlorobenzene	ND	5.0	1.5	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1,1-Trichloroethane	ND	5.0	1.0	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1,2-Trichloroethane	ND	5.0	0.80	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Trichloroethylene	ND	5.0	1.2	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Trichlorofluoromethane (Freon 11)	ND	10	1.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2,3-Trichloropropane	ND	10	1.2	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,1,2-Trichloro-1,2,2-trifluoroethane (Freon 113)	ND	5.0	1.6	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,2,4-Trimethylbenzene	8.3	5.0	0.90	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
1,3,5-Trimethylbenzene	1.0	5.0	0.70	μg/L	5	J	SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Vinyl Chloride	ND	10	2.2	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
m+p Xylene	33	10	1.5	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
o-Xylene	10	5.0	0.85	μg/L	5		SW-846 8260D	11/4/19	11/4/19 15:46	EEH
Surrogates		% Reco	very	Recovery Limits	\$	Flag/Qual				
1,2-Dichloroethane-d4		104		70-130					11/4/19 15:46	
Toluene-d8 4-Bromofluorobenzene		100 102		70-130 70-130					11/4/19 15:46 11/4/19 15:46	



Work Order: 19J1775

Project Location: Dunn, NC Date Received: 10/28/2019

Field Sample #: TW-1

p-Terphenyl-d14

Sample ID: 19J1775-01

Sample Matrix: Ground Water

Sampled: 10/28/2019 17:00

Sample Description:

			Semivo	olatile Organic Co	ompounds by	GC/MS				
								Date	Date/Time	
Analyte	Results	RL	DL	Units	Dilution	Flag/Qual	Method	Prepared	Analyzed	Analyst
Acenaphthene (SIM)	0.13	0.31	0.034	μg/L	1	J	SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Acenaphthylene (SIM)	0.079	0.21	0.036	μg/L	1	J	SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Anthracene (SIM)	ND	0.21	0.033	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Benzo(a)anthracene (SIM)	ND	0.052	0.017	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Benzo(a)pyrene (SIM)	ND	0.10	0.012	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Benzo(b)fluoranthene (SIM)	ND	0.052	0.016	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Benzo(g,h,i)perylene (SIM)	ND	0.52	0.019	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Benzo(k)fluoranthene (SIM)	ND	0.21	0.012	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Chrysene (SIM)	ND	0.21	0.016	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Dibenz(a,h)anthracene (SIM)	ND	0.10	0.018	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Fluoranthene (SIM)	0.052	0.52	0.026	μg/L	1	J	SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Fluorene (SIM)	0.14	1.0	0.035	μg/L	1	J	SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Indeno(1,2,3-cd)pyrene (SIM)	ND	0.10	0.019	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
2-Methylnaphthalene (SIM)	21	10	0.65	μg/L	10		SW-846 8270E	10/30/19	11/4/19 10:34	IMR
Naphthalene (SIM)	25	10	2.7	μg/L	10		SW-846 8270E	10/30/19	11/4/19 10:34	IMR
Phenanthrene (SIM)	0.13	0.052	0.031	μg/L	1		SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Pyrene (SIM)	0.049	1.0	0.024	μg/L	1	J	SW-846 8270E	10/30/19	11/1/19 20:51	IMR
Surrogates		% Reco	very	Recovery Limit	s	Flag/Qual				
Nitrobenzene-d5		72.6		30-130					11/1/19 20:51	
Nitrobenzene-d5		73.1		30-130					11/4/19 10:34	
2-Fluorobiphenyl		47.7		30-130					11/1/19 20:51	
2-Fluorobiphenyl		53.5		30-130					11/4/19 10:34	
p-Terphenyl-d14		54.6		30-130					11/1/19 20:51	

30-130

49.6

11/4/19 10:34



Sample Extraction Data

Prep Method: SW-846 5030B-SW-846 8260D

Lab Number [Field ID]	Batch	Initial [mL]	Final [mL]	Date	
19J1775-01 [TW-1]	B244975	1	5.00	11/04/19	
Prep Method: SW-846 3510C-SW-846 8270	١F				
rrep Method: 5 w-640 5510C-5 w-640 6270	JE.				
Lab Number [Field ID]	Batch	Initial [mL]	Final [mL]	Date	
19J1775-01 [TW-1]	B244837	960	1.00	10/30/19	



QUALITY CONTROL

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch B244975 - SW-846 5030B	roour	Linit	50	20101	-cosurt					
Blank (B244975-BLK1)				Prenared &	Analyzed: 11	/04/19				
Acetone	ND	50	μg/L	riepaieu &	Allalyzeu. 11	/04/19				
Acrylonitrile	ND ND	5.0	μg/L μg/L							
ert-Amyl Methyl Ether (TAME)	ND	0.50	μg/L							V-05
Benzene	ND	1.0	μg/L							¥-05
Bromobenzene	ND	1.0	μg/L							
romochloromethane	ND	1.0	μg/L							
romodichloromethane	ND	0.50	μg/L							
romoform	ND	1.0	μg/L							
romomethane	ND	2.0	μg/L							
Butanone (MEK)	ND	20	μg/L							
rt-Butyl Alcohol (TBA)	ND	20	μg/L							
Butylbenzene	ND	1.0	μg/L							
cc-Butylbenzene	ND	1.0	μg/L							
rt-Butylbenzene	ND	1.0	μg/L							
rt-Butyl Ethyl Ether (TBEE)	ND	0.50	μg/L							
arbon Disulfide	ND	5.0	μg/L							
arbon Tetrachloride	ND	1.0	μg/L							
hlorobenzene	ND	1.0	μg/L							
hlorodibromomethane	ND	0.50	μg/L							
hloroethane	ND	2.0	μg/L							
hloroform	ND	2.0	μg/L							
hloromethane	ND	2.0	μg/L							
Chlorotoluene	ND	1.0	μg/L							
Chlorotoluene	ND	1.0	μg/L							
2-Dibromo-3-chloropropane (DBCP)	ND	5.0	μg/L							
2-Dibromoethane (EDB)	ND	0.50	μg/L							
ibromomethane	ND	1.0	μg/L							
2-Dichlorobenzene	ND	1.0	μg/L							
3-Dichlorobenzene	ND	1.0	μg/L							
,4-Dichlorobenzene	ND	1.0	μg/L							
ans-1,4-Dichloro-2-butene	ND	2.0	μg/L							
ichlorodifluoromethane (Freon 12)	ND	2.0	μg/L							
1-Dichloroethane	ND	1.0	$\mu g/L$							
2-Dichloroethane	ND	1.0	$\mu g/L$							
1-Dichloroethylene	ND	1.0	$\mu g/L$							
is-1,2-Dichloroethylene	ND	1.0	$\mu g/L$							
ans-1,2-Dichloroethylene	ND	1.0	μg/L							
2-Dichloropropane	ND	1.0	μg/L							
3-Dichloropropane	ND	0.50	μg/L							
2-Dichloropropane	ND	1.0	μg/L							
1-Dichloropropene	ND	2.0	μg/L							
s-1,3-Dichloropropene	ND	0.50	μg/L							
ans-1,3-Dichloropropene	ND	0.50	μg/L							
iethyl Ether	ND	2.0	μg/L							
iisopropyl Ether (DIPE)	ND	0.50	μg/L							
4-Dioxane	ND	50	μg/L							
hylbenzene	ND	1.0	μg/L							
exachlorobutadiene	ND	0.60	μg/L							
Hexanone (MBK)	ND	10	μg/L							
opropylbenzene (Cumene)	ND	1.0	μg/L							
Isopropyltoluene (p-Cymene)	ND	1.0	μg/L							
lethyl tert-Butyl Ether (MTBE)	ND	1.0	μg/L							



QUALITY CONTROL

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch B244975 - SW-846 5030B										
Blank (B244975-BLK1)				Prepared & A	Analyzed: 11/	/04/19				
1ethylene Chloride	ND	5.0	μg/L							
-Methyl-2-pentanone (MIBK)	ND	10	μg/L							
aphthalene	ND	2.0	μg/L							
Propylbenzene	ND	1.0	μg/L							
tyrene	ND	1.0	μg/L							
1,1,2-Tetrachloroethane	ND	1.0	μg/L							
1,2,2-Tetrachloroethane	ND	0.50	μg/L							
etrachloroethylene	ND	1.0	μg/L							
trahydrofuran	ND	10	μg/L							
bluene	ND	1.0	μg/L							
2,3-Trichlorobenzene	ND	5.0	μg/L							
2,4-Trichlorobenzene	ND	1.0	μg/L							
3,5-Trichlorobenzene	ND	1.0	μg/L							
1,1-Trichloroethane	ND	1.0	μg/L							
1,2-Trichloroethane	ND	1.0	μg/L							
richloroethylene	ND	1.0	μg/L							
ichlorofluoromethane (Freon 11)	ND	2.0	μg/L							
2,3-Trichloropropane	ND	2.0	μg/L							
1,2-Trichloro-1,2,2-trifluoroethane (Freon	ND ND	1.0	μg/L μg/L							
3)	ND	1.0	μg/L							
2,4-Trimethylbenzene	ND	1.0	μg/L							
3,5-Trimethylbenzene	ND	1.0	μg/L							
nyl Chloride	ND	2.0	μg/L							
+p Xylene	ND	2.0	μg/L							
Xylene	ND	1.0	μg/L							
urrogate: 1,2-Dichloroethane-d4	25.8		μg/L	25.0		103	70-130			
irrogate: Toluene-d8	25.2		μg/L	25.0		101	70-130			
irrogate: 4-Bromofluorobenzene	24.3		μg/L	25.0		97.4	70-130			
CS (B244975-BS1)			10		Analyzed: 11/					
cetone	140	50	μg/L	100	Anaryzea. 11/	140	70-160			V-20
crylonitrile	140	5.0	μg/L	10.0		123	70-130			V-20
rt-Amyl Methyl Ether (TAME)	7.90	0.50	μg/L	10.0		79.0	70-130			V-05
enzene		1.0	μg/L	10.0		96.0				v- 05
romobenzene	9.60	1.0	μg/L μg/L			96.0 110	70-130 70-130			
romochloromethane	11.0	1.0		10.0						
romotichloromethane	11.3	0.50	μg/L μg/L	10.0		113	70-130			
romoform	11.2			10.0		112	70-130			
	10.0	1.0	μg/L ug/I	10.0		100	70-130			
romomethane	5.87	2.0	μg/L	10.0		58.7	40-160			
Butanone (MEK)	114	20	μg/L ug/I	100		114	40-160			
rt-Butyl Alcohol (TBA)	96.7	20	μg/L	100		96.7	40-160			
Butylbenzene	11.6	1.0	μg/L	10.0		116	70-130			
c-Butylbenzene	11.3	1.0	μg/L	10.0		113	70-130			
t-Butylbenzene	10.8	1.0	μg/L	10.0		108	70-130			
rt-Butyl Ethyl Ether (TBEE)	7.42	0.50	μg/L	10.0		74.2	70-130			
arbon Disulfide	11.2	5.0	μg/L	10.0		112	70-130			
rbon Tetrachloride	11.2	1.0	μg/L	10.0		112	70-130			
hlorobenzene	10.6	1.0	μg/L	10.0		106	70-130			
nlorodibromomethane	10.8	0.50	μg/L	10.0		108	70-130			
nloroethane	9.65	2.0	μg/L	10.0		96.5	70-130			
hloroform	9.93	2.0	μg/L	10.0		99.3	70-130			
hloromethane	7.98	2.0	μg/L	10.0		79.8	40-160			
Chlorotoluene	10.4	1.0	μg/L	10.0		104	70-130			
									P	age 12 of



QUALITY CONTROL

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes	
Batch B244975 - SW-846 5030B											
LCS (B244975-BS1)				Prepared &	Analyzed: 11	/04/19					
4-Chlorotoluene	11.3	1.0	μg/L	10.0		113	70-130				
1,2-Dibromo-3-chloropropane (DBCP)	10.4	5.0	μg/L	10.0		104	70-130				
1,2-Dibromoethane (EDB)	10.7	0.50	μg/L	10.0		107	70-130				
Dibromomethane	10.5	1.0	μg/L	10.0		105	70-130				
1,2-Dichlorobenzene	10.8	1.0	μg/L	10.0		108	70-130				
1,3-Dichlorobenzene	11.0	1.0	μg/L	10.0		110	70-130				
1,4-Dichlorobenzene	10.7	1.0	μg/L	10.0		107	70-130				
trans-1,4-Dichloro-2-butene	13.2	2.0	μg/L	10.0		132 *	70-130			L-02, V-20	
Dichlorodifluoromethane (Freon 12)	6.19	2.0	μg/L	10.0		61.9	40-160				•
1,1-Dichloroethane	10.6	1.0	μg/L	10.0		106	70-130				
1,2-Dichloroethane	11.7	1.0	μg/L	10.0		117	70-130				
1,1-Dichloroethylene	11.7	1.0	μg/L	10.0		117	70-130				
cis-1,2-Dichloroethylene	10.8	1.0	μg/L	10.0		108	70-130				
trans-1,2-Dichloroethylene	11.4	1.0	μg/L	10.0		114	70-130				
1,2-Dichloropropane	10.9	1.0	μg/L	10.0		109	70-130				
1,3-Dichloropropane	10.5	0.50	μg/L	10.0		105	70-130				
2,2-Dichloropropane	11.8	1.0	μg/L	10.0		118	40-130				•
1,1-Dichloropropene	10.5	2.0	μg/L	10.0		105	70-130				
cis-1,3-Dichloropropene	11.3	0.50	μg/L	10.0		113	70-130				
trans-1,3-Dichloropropene	10.9	0.50	μg/L	10.0		109	70-130				
Diethyl Ether	10.8	2.0	μg/L	10.0		108	70-130				
Diisopropyl Ether (DIPE)	12.1	0.50	μg/L	10.0		121	70-130				
1,4-Dioxane	116	50	μg/L	100		116	40-130				1
Ethylbenzene	10.7	1.0	μg/L	10.0		107	70-130				
Hexachlorobutadiene	11.8	0.60	μg/L	10.0		118	70-130				
2-Hexanone (MBK)	132	10	μg/L	100		132	70-160			V-20	1
Isopropylbenzene (Cumene)	11.0	1.0	μg/L	10.0		110	70-130				
p-Isopropyltoluene (p-Cymene)	10.5	1.0	μg/L	10.0		105	70-130				
Methyl tert-Butyl Ether (MTBE)	9.41	1.0	μg/L	10.0		94.1	70-130				
Methylene Chloride	11.6	5.0	μg/L	10.0		116	70-130				
4-Methyl-2-pentanone (MIBK)	137	10	μg/L	100		137	70-160			V-20	i
Naphthalene	9.20	2.0	μg/L	10.0		92.0	40-130				i
n-Propylbenzene	11.3	1.0	μg/L	10.0		113	70-130				
Styrene	9.10	1.0	μg/L	10.0		91.0	70-130				
1,1,1,2-Tetrachloroethane	11.2	1.0	μg/L	10.0		112	70-130				
1,1,2,2-Tetrachloroethane	11.4	0.50	μg/L	10.0		114	70-130				
Tetrachloroethylene	11.4	1.0	μg/L	10.0		114	70-130				
Tetrahydrofuran	10.3	10	μg/L	10.0		103	70-130				
Toluene	10.7	1.0	μg/L	10.0		107	70-130				
1,2,3-Trichlorobenzene	8.52	5.0	μg/L	10.0		85.2	70-130				
1,2,4-Trichlorobenzene	10.4	1.0	μg/L	10.0		104	70-130				
1,3,5-Trichlorobenzene	10.5	1.0	μg/L	10.0		105	70-130				
1,1,1-Trichloroethane	11.1	1.0	μg/L	10.0		111	70-130				
1,1,2-Trichloroethane	10.6	1.0	μg/L	10.0		106	70-130				
Trichloroethylene	10.7	1.0	μg/L	10.0		107	70-130				
Trichlorofluoromethane (Freon 11)	10.0	2.0	μg/L	10.0		100	70-130				
1,2,3-Trichloropropane	11.1	2.0	μg/L	10.0		111	70-130				
1,1,2-Trichloro-1,2,2-trifluoroethane (Freon 113)	10.9	1.0	μg/L	10.0		109	70-130				
1,2,4-Trimethylbenzene	9.65	1.0	μg/L	10.0		96.5	70-130				
1,3,5-Trimethylbenzene	10.7	1.0	μg/L	10.0		107	70-130				
Vinyl Chloride	26.4	2.0	μg/L	10.0		264 *	40-160			L-02, V-20	İ



QUALITY CONTROL

Volatile Organic Compounds by GC/MS - Quality Control

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes	
Batch B244975 - SW-846 5030B											
LCS (B244975-BS1)				Prepared &	Analyzed: 11/	04/19					
m+p Xylene	21.6	2.0	μg/L	20.0		108	70-130				
o-Xylene	11.1	1.0	μg/L	10.0		111	70-130				
Surrogate: 1,2-Dichloroethane-d4	26.2		μg/L	25.0		105	70-130				
Surrogate: Toluene-d8	24.7		μg/L	25.0		98.8	70-130				
Surrogate: 4-Bromofluorobenzene	25.5		$\mu g/L$	25.0		102	70-130				
LCS Dup (B244975-BSD1)				Prepared &	Analyzed: 11/	04/19					
Acetone	145	50	μg/L	100		145	70-160	3.73	25	V-20	†
Acrylonitrile	12.0	5.0	μg/L	10.0		120	70-130	3.21	25		
tert-Amyl Methyl Ether (TAME)	7.77	0.50	μg/L	10.0		77.7	70-130	1.66	25	V-05	
Benzene	9.68	1.0	μg/L	10.0		96.8	70-130	0.830	25		
Bromobenzene	10.6	1.0	μg/L	10.0		106	70-130	3.90	25		
Bromochloromethane	11.1	1.0	μg/L	10.0		111	70-130	1.43	25		
Bromodichloromethane	10.6	0.50	μg/L	10.0		106	70-130	4.86	25		
Bromoform	10.3	1.0	μg/L	10.0		103	70-130	2.46	25		
Bromomethane	6.68	2.0	μg/L	10.0		66.8	40-160	12.9	25		Ť
2-Butanone (MEK)	117	20	μg/L	100		117	40-160	2.32	25		†
tert-Butyl Alcohol (TBA)	90.2	20	μg/L	100		90.2	40-160	7.03	25		Ť
n-Butylbenzene	11.6	1.0	μg/L	10.0		116	70-130	0.172	25		
sec-Butylbenzene	11.4	1.0	μg/L	10.0		114	70-130	0.440	25		
tert-Butylbenzene	10.9	1.0	μg/L	10.0		109	70-130	0.368	25		
tert-Butyl Ethyl Ether (TBEE)	7.38	0.50	μg/L	10.0		73.8	70-130	0.541	25		
Carbon Disulfide	10.4	5.0	μg/L	10.0		104	70-130	6.66	25		
Carbon Tetrachloride	11.1	1.0	μg/L	10.0		111	70-130	0.809	25		
Chlorobenzene	10.1	1.0	μg/L	10.0		101	70-130	5.02	25		
Chlorodibromomethane	10.5	0.50	μg/L α	10.0		105	70-130	2.73	25		
Chloroethane	9.87	2.0	μg/L α	10.0		98.7	70-130	2.25	25		
Chloroform	9.64	2.0	μg/L α	10.0		96.4	70-130	2.96	25		
Chloromethane	7.89	2.0	μg/L π	10.0		78.9	40-160	1.13	25		Ť
2-Chlorotoluene	10.2	1.0	μg/L	10.0		102	70-130	1.17	25		
4-Chlorotoluene	10.8	1.0	μg/L ug/I	10.0		108	70-130	4.70	25		
1,2-Dibromo-3-chloropropane (DBCP) 1,2-Dibromoethane (EDB)	10.5	5.0 0.50	μg/L ug/I	10.0		105	70-130	0.573	25 25		
Dibromomethane	10.6	1.0	μg/L μg/L	10.0 10.0		106 107	70-130 70-130	1.31 1.60	25 25		
1,2-Dichlorobenzene	10.7	1.0	μg/L μg/L	10.0		107	70-130	2.54	23 25		
1,3-Dichlorobenzene	10.5	1.0	μg/L μg/L	10.0		103	70-130	0.542	23 25		
1,4-Dichlorobenzene	11.1 10.5	1.0	μg/L μg/L	10.0		105	70-130	1.60	25 25		
trans-1,4-Dichloro-2-butene	10.5	2.0	μg/L μg/L	10.0		134 *	70-130	1.13	25	L-02, V-20	
Dichlorodifluoromethane (Freon 12)	6.16	2.0	μg/L μg/L	10.0		61.6	40-160	0.486	25	L-02, v- 20	†
1,1-Dichloroethane	10.6	1.0	μg/L μg/L	10.0		106	70-130	0.00	25		1
1,2-Dichloroethane	11.7	1.0	μg/L	10.0		117	70-130	0.0856	25		
1,1-Dichloroethylene	11.7	1.0	μg/L	10.0		117	70-130	0.428	25		
cis-1,2-Dichloroethylene	10.6	1.0	μg/L	10.0		106	70-130	1.68	25		
trans-1,2-Dichloroethylene	11.2	1.0	μg/L	10.0		112	70-130	1.95	25		
1,2-Dichloropropane	11.2	1.0	μg/L	10.0		110	70-130	0.183	25		
1,3-Dichloropropane	10.7	0.50	μg/L	10.0		107	70-130	1.70	25		
2,2-Dichloropropane	11.3	1.0	μg/L	10.0		113	40-130	4.17	25		Ť
1,1-Dichloropropene	10.4	2.0	μg/L	10.0		104	70-130	1.24	25		1
cis-1,3-Dichloropropene	10.1	0.50	μg/L	10.0		108	70-130	4.34	25		
trans-1,3-Dichloropropene	11.0	0.50	μg/L	10.0		110	70-130	0.915	25		
Diethyl Ether	10.7	2.0	μg/L	10.0		107	70-130	1.39	25		
Diisopropyl Ether (DIPE)	11.6	0.50	μg/L	10.0		116	70-130	3.96	25		

Page 14 of 24



QUALITY CONTROL

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes	
Batch B244975 - SW-846 5030B											_
LCS Dup (B244975-BSD1)				Prepared & A	Analyzed: 11	/04/19					
1,4-Dioxane	122	50	μg/L	100		122	40-130	4.65	50		† :
Ethylbenzene	10.7	1.0	μg/L	10.0		107	70-130	0.561	25		
Hexachlorobutadiene	11.8	0.60	μg/L	10.0		118	70-130	0.508	25		
2-Hexanone (MBK)	132	10	μg/L	100		132	70-160	0.137	25	V-20	t
Isopropylbenzene (Cumene)	10.8	1.0	μg/L	10.0		108	70-130	2.57	25		
p-Isopropyltoluene (p-Cymene)	10.6	1.0	μg/L	10.0		106	70-130	0.190	25		
Methyl tert-Butyl Ether (MTBE)	9.24	1.0	μg/L	10.0		92.4	70-130	1.82	25		
Methylene Chloride	11.1	5.0	μg/L	10.0		111	70-130	4.22	25		
4-Methyl-2-pentanone (MIBK)	140	10	μg/L	100		140	70-160	2.14	25	V-20	†
Naphthalene	9.12	2.0	μg/L	10.0		91.2	40-130	0.873	25		t
n-Propylbenzene	10.8	1.0	μg/L	10.0		108	70-130	4.24	25		
Styrene	9.13	1.0	μg/L	10.0		91.3	70-130	0.329	25		
1,1,1,2-Tetrachloroethane	11.2	1.0	μg/L	10.0		112	70-130	0.0890	25		
1,1,2,2-Tetrachloroethane	11.2	0.50	μg/L	10.0		112	70-130	1.41	25		
Tetrachloroethylene	10.9	1.0	μg/L	10.0		109	70-130	3.94	25		
Tetrahydrofuran	10.7	10	μg/L	10.0		107	70-130	4.28	25		
Toluene	10.5	1.0	μg/L	10.0		105	70-130	2.45	25		
1,2,3-Trichlorobenzene	8.47	5.0	μg/L	10.0		84.7	70-130	0.589	25		
1,2,4-Trichlorobenzene	10.1	1.0	μg/L	10.0		101	70-130	3.42	25		
1,3,5-Trichlorobenzene	10.5	1.0	μg/L	10.0		105	70-130	0.0954	25		
1,1,1-Trichloroethane	11.0	1.0	μg/L	10.0		110	70-130	1.63	25		
1,1,2-Trichloroethane	10.6	1.0	μg/L	10.0		106	70-130	0.661	25		
Trichloroethylene	10.3	1.0	μg/L	10.0		103	70-130	4.29	25		
Trichlorofluoromethane (Freon 11)	10.0	2.0	μg/L	10.0		100	70-130	0.399	25		
1,2,3-Trichloropropane	11.3	2.0	μg/L	10.0		113	70-130	1.16	25		
1,1,2-Trichloro-1,2,2-trifluoroethane (Freon 113)	10.7	1.0	μg/L	10.0		107	70-130	1.86	25		
1,2,4-Trimethylbenzene	9.50	1.0	μg/L	10.0		95.0	70-130	1.57	25		
1,3,5-Trimethylbenzene	10.4	1.0	μg/L	10.0		104	70-130	2.93	25		
Vinyl Chloride	25.0	2.0	μg/L	10.0		250 *	40-160	5.64	25	L-02, V-20	†
m+p Xylene	21.3	2.0	μg/L	20.0		107	70-130	1.44	25		
o-Xylene	10.9	1.0	μg/L	10.0		109	70-130	1.82	25		
Surrogate: 1,2-Dichloroethane-d4	25.2		μg/L	25.0		101	70-130				_
Surrogate: Toluene-d8	25.1		μg/L	25.0		100	70-130				
Surrogate: 4-Bromofluorobenzene	25.1		μg/L	25.0		100	70-130				



QUALITY CONTROL

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch B244837 - SW-846 3510C										
Blank (B244837-BLK1)				Prepared: 10)/30/19 Anal	yzed: 11/01/1	9			
Acenaphthene (SIM)	ND	0.30	μg/L							
Acenaphthylene (SIM)	ND	0.20	μg/L							
Anthracene (SIM)	ND	0.20	μg/L							
Benzo(a)anthracene (SIM)	ND	0.050	μg/L							
Benzo(a)pyrene (SIM)	ND	0.10	μg/L							
Benzo(b)fluoranthene (SIM)	ND	0.050	μg/L							
Benzo(g,h,i)perylene (SIM)	ND	0.50	μg/L							
Benzo(k)fluoranthene (SIM)	ND	0.20	μg/L							
Chrysene (SIM)	ND	0.20	μg/L							
Dibenz(a,h)anthracene (SIM)	ND	0.10	μg/L							
Fluoranthene (SIM)	ND	0.50	μg/L							
Fluorene (SIM)	ND	1.0	μg/L							
ndeno(1,2,3-cd)pyrene (SIM)	ND	0.10	μg/L							
2-Methylnaphthalene (SIM)	ND	1.0	μg/L							
Japhthalene (SIM)	ND	1.0	μg/L							
Phenanthrene (SIM)	ND	0.050	μg/L							
Pyrene (SIM)	ND	1.0	μg/L							
Surrogate: Nitrobenzene-d5	83.8		μg/L	100		83.8	30-130			
Surrogate: 2-Fluorobiphenyl	54.8		μg/L	100		54.8	30-130			
Surrogate: p-Terphenyl-d14	73.4		μg/L	100		73.4	30-130			
LCS (B244837-BS1)				Prepared: 10)/30/19 Anal	zed: 11/01/1	9			
Acenaphthene (SIM)	37.1	6.0	μg/L	50.0		74.1	40-140			
Acenaphthylene (SIM)	38.1	4.0	μg/L	50.0		76.2	40-140			
Anthracene (SIM)	41.5	4.0	μg/L	50.0		83.1	40-140			
Benzo(a)anthracene (SIM)	42.4	1.0	μg/L	50.0		84.9	40-140			
Benzo(a)pyrene (SIM)	40.2	2.0	μg/L	50.0		80.4	40-140			
Benzo(b)fluoranthene (SIM)	44.2	1.0	μg/L	50.0		88.4	40-140			
Benzo(g,h,i)perylene (SIM)	41.9	10	μg/L	50.0		83.9	40-140			
Benzo(k)fluoranthene (SIM)	43.5	4.0	μg/L	50.0		87.0	40-140			
Chrysene (SIM)	32.8	4.0	μg/L	50.0		65.5	40-140			
Dibenz(a,h)anthracene (SIM)	46.1	2.0	μg/L	50.0		92.1	40-140			
Fluoranthene (SIM)	40.0	10	μg/L	50.0		80.0	40-140			
Fluorene (SIM)	38.6	20	μg/L	50.0		77.3	40-140			
ndeno(1,2,3-cd)pyrene (SIM)	52.7	2.0	μg/L	50.0		105	40-140			
2-Methylnaphthalene (SIM)	37.6	20	μg/L	50.0		75.2	40-140			
Naphthalene (SIM)	34.8	20	μg/L	50.0		69.6	40-140			
Phenanthrene (SIM)	38.1	1.0	μg/L	50.0		76.2	40-140			
Pyrene (SIM)	35.8	20	μg/L	50.0		71.6	40-140			
Surrogate: Nitrobenzene-d5	84.0		μg/L	100		84.0	30-130			
Surrogate: 2-Fluorobiphenyl	58.3		μg/L	100		58.3	30-130			
Surrogate: p-Terphenyl-d14	56.1		μg/L	100		56.1	30-130			



‡

39 Spruce Street * East Longmeadow, MA 01028 * FAX 413/525-6405 * TEL. 413/525-2332

QUALITY CONTROL

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch B244837 - SW-846 3510C										
LCS Dup (B244837-BSD1)				Prepared: 10)/30/19 Anal	yzed: 11/01/1	19			
Acenaphthene (SIM)	36.6	6.0	μg/L	50.0		73.3	40-140	1.14	20	
Acenaphthylene (SIM)	37.7	4.0	μg/L	50.0		75.4	40-140	1.16	20	
Anthracene (SIM)	40.8	4.0	μg/L	50.0		81.6	40-140	1.85	20	
Benzo(a)anthracene (SIM)	41.9	1.0	μg/L	50.0		83.7	40-140	1.38	20	
Benzo(a)pyrene (SIM)	38.8	2.0	μg/L	50.0		77.5	40-140	3.65	20	
Benzo(b)fluoranthene (SIM)	43.3	1.0	μg/L	50.0		86.5	40-140	2.15	20	
Benzo(g,h,i)perylene (SIM)	41.4	10	μg/L	50.0		82.8	40-140	1.34	20	
Benzo(k)fluoranthene (SIM)	43.9	4.0	μg/L	50.0		87.9	40-140	1.05	20	
Chrysene (SIM)	32.3	4.0	μg/L	50.0		64.5	40-140	1.54	20	
Dibenz(a,h)anthracene (SIM)	45.7	2.0	μg/L	50.0		91.3	40-140	0.872	20	
Fluoranthene (SIM)	38.8	10	μg/L	50.0		77.6	40-140	3.04	20	
Fluorene (SIM)	38.3	20	μg/L	50.0		76.6	40-140	0.884	20	
Indeno(1,2,3-cd)pyrene (SIM)	51.0	2.0	μg/L	50.0		102	40-140	3.28	20	
2-Methylnaphthalene (SIM)	37.3	20	μg/L	50.0		74.6	40-140	0.854	20	
Naphthalene (SIM)	34.4	20	μg/L	50.0		68.8	40-140	1.21	20	
Phenanthrene (SIM)	37.5	1.0	μg/L	50.0		74.9	40-140	1.69	20	
Pyrene (SIM)	34.9	20	$\mu g/L$	50.0		69.8	40-140	2.55	20	
Surrogate: Nitrobenzene-d5	78.5		μg/L	100		78.5	30-130			
Surrogate: 2-Fluorobiphenyl	55.7		μg/L	100		55.7	30-130			
Surrogate: p-Terphenyl-d14	58.0		μg/L	100		58.0	30-130			



FLAG/QUALIFIER SUMMARY

- * QC result is outside of established limits.
- † Wide recovery limits established for difficult compound.
- ‡ Wide RPD limits established for difficult compound.
- # Data exceeded client recommended or regulatory level

Percent recoveries and relative percent differences (RPDs) are determined by the software using values in the calculation which have not been rounded.

No results have been blank subtracted unless specified in the case narrative section.

- J Detected but below the Reporting Limit (lowest calibration standard); therefore, result is an estimated concentration (CLP J-Flag).
- L-02 Laboratory fortified blank/laboratory control sample recovery and duplicate recoveries outside of control limits. Data validation is not affected since all results are "not detected" for associated samples in this batch and bias is on the high side.
- RL-11 Elevated reporting limit due to high concentration of target compounds.
- V-05 Continuing calibration verification (CCV) did not meet method specifications and was biased on the low side for this compound.
- V-20 Continuing calibration verification (CCV) did not meet method specifications and was biased on the high side. Data validation is not affected since sample result was "not detected" for this compound.



CERTIFICATIONS

Certified Analyses included in this Report

Analyte	Certifications	
SW-846 8260D in Water		
Acetone	NC	
Acrylonitrile	NC	
tert-Amyl Methyl Ether (TAME)	NC	
Benzene	NC	
Bromobenzene	NC	
Bromochloromethane	NC	
Bromodichloromethane	NC	
Bromoform	NC	
Bromomethane	NC	
2-Butanone (MEK)	NC	
tert-Butyl Alcohol (TBA)	NC	
n-Butylbenzene	NC	
sec-Butylbenzene	NC	
tert-Butylbenzene	NC	
tert-Butyl Ethyl Ether (TBEE)	NC	
Carbon Disulfide	NC	
Carbon Tetrachloride	NC	
Chlorobenzene	NC	
Chlorodibromomethane	NC	
Chloroethane	NC	
Chloroform	NC	
Chloromethane	NC	
2-Chlorotoluene	NC	
4-Chlorotoluene	NC	
1,2-Dibromo-3-chloropropane (DBCP)	NC	
1,2-Dibromoethane (EDB)	NC	
Dibromomethane	NC	
1,2-Dichlorobenzene	NC	
1,3-Dichlorobenzene	NC	
1,4-Dichlorobenzene	NC	
trans-1,4-Dichloro-2-butene	NC	
Dichlorodifluoromethane (Freon 12)	NC	
1,1-Dichloroethane	NC	
1,2-Dichloroethane	NC	
1,1-Dichloroethylene	NC	
cis-1,2-Dichloroethylene	NC	
trans-1,2-Dichloroethylene	NC	
1,2-Dichloropropane	NC	
1,3-Dichloropropane	NC	
2,2-Dichloropropane	NC	
1,1-Dichloropropene	NC	
cis-1,3-Dichloropropene	NC	
trans-1,3-Dichloropropene	NC	
Diethyl Ether	NC	
Diisopropyl Ether (DIPE)	NC	
1,4-Dioxane	NC	
Ethylbenzene	NC	



CERTIFICATIONS

Certified Analyses included in this Report

eer tineu Analyses menueu in tins report	
Analyte	Certifications
SW-846 8260D in Water	
Hexachlorobutadiene	NC
2-Hexanone (MBK)	NC
Isopropylbenzene (Cumene)	NC
p-Isopropyltoluene (p-Cymene)	NC
Methyl tert-Butyl Ether (MTBE)	NC
Methylene Chloride	NC
4-Methyl-2-pentanone (MIBK)	NC
Naphthalene	NC
n-Propylbenzene	NC
Styrene	NC
1,1,1,2-Tetrachloroethane	NC
1,1,2,2-Tetrachloroethane	NC
Tetrachloroethylene	NC
Tetrahydrofuran	NC
Toluene	NC
1,2,3-Trichlorobenzene	NC
1,2,4-Trichlorobenzene	NC
1,3,5-Trichlorobenzene	NC
1,1,1-Trichloroethane	NC
1,1,2-Trichloroethane	NC
Trichloroethylene	NC
Trichlorofluoromethane (Freon 11)	NC
1,2,3-Trichloropropane	NC
1,1,2-Trichloro-1,2,2-trifluoroethane (Freon 113)	NC
1,2,4-Trimethylbenzene	NC
1,3,5-Trimethylbenzene	NC
Vinyl Chloride	NC
m+p Xylene	NC
o-Xylene	NC



The CON-TEST Environmental Laboratory operates under the following certifications and accreditations:

Code	Description	Number	Expires
AIHA	AIHA-LAP, LLC - ISO17025:2017	100033	03/1/2020
MA	Massachusetts DEP	M-MA100	06/30/2020
СТ	Connecticut Department of Publilc Health	PH-0567	09/30/2021
NY	New York State Department of Health	10899 NELAP	04/1/2020
NH-S	New Hampshire Environmental Lab	2516 NELAP	02/5/2020
RI	Rhode Island Department of Health	LAO00112	12/30/2019
NC	North Carolina Div. of Water Quality	652	12/31/2019
NJ	New Jersey DEP	MA007 NELAP	06/30/2020
FL	Florida Department of Health	E871027 NELAP	06/30/2020
VT	Vermont Department of Health Lead Laboratory	LL015036	07/30/2020
ME	State of Maine	2011028	06/9/2021
VA	Commonwealth of Virginia	460217	12/14/2019
NH-P	New Hampshire Environmental Lab	2557 NELAP	09/6/2020
VT-DW	Vermont Department of Health Drinking Water	VT-255716	06/12/2020
NC-DW	North Carolina Department of Health	25703	07/31/2020
PA	Commonwealth of Pennsylvania DEP	68-05812	06/30/2020

Table Table <thtable< th=""> <thtable< th=""> <thta< th=""><th>IIIII con-test</th><th>1011++S</th><th><u>ettan of cus</u></th><th>http://www.contestiabs.com (AIAIN.0)F_CLISTODY_RFCORD_(North_Carolina)</th><th><u>bs.com</u> Vorth Carolina)</th><th>Doc # 379</th><th>Doc # 379 Rev 1_03242017 39 5</th><th>t2017 39 Spruce Street</th><th>Street</th><th>-</th><th></th><th></th></thta<></thtable<></thtable<>	IIIII con-test	1011++S	<u>ettan of cus</u>	http://www.contestiabs.com (AIAIN.0)F_CLISTODY_RFCORD_(North_Carolina)	<u>bs.com</u> Vorth Carolina)	Doc # 379	Doc # 379 Rev 1_03242017 39 5	t2017 39 Spruce Street	Street	-		
Tentil inference (105, cm) Totals	ANALYTICAL LARORATORY	Prone: 413-525-232 Fax: 413-525-6405	Requi	n concount pesse	ol time			East Long	meadow, MA 0		Page of	
Reference Due Data Due		Email: info@contestlabs.com									# of Containers	
The Terch 780 Zabri 4 Day Day <thday< th=""> <thday< th=""> Day</thday<></thday<>	SAAS		Due Date:								² Preservation Code	—
Mill (M, M) Total Total Total Total MM-VSS REQUESTED P M M Anti- T-Law Dom: Pf Exx1 Dom: Pf Exx1 Anti- T-Law Dim<	3301 Sprike	لمنغلمة	Rus	ih Approval Reg	Jired						³ Container Code	1
2.20% 2.20% 4.0% 4.0% Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell Format: Part Hell Format: Part Hell Ant: Hell Format: Part Hell <	વૃંહ વનુ ગુ		1-Day] 3-Day			ANA	YSIS REQ	UESTED		Dissolved Wetals Samples	84878
Line Contract. File Contract. File Contract. File Contract. File Contract. File	TUCON m	-5878 DUNN BUCh] 4-Day							Field Filtered	10,000
And C - (2-1da) Homat: Def Exc. And C - (2-1da) Other Constrained Constrained And C - (2-1da) Constrained Constrained Constrained And (1-1da) Constra	B			Data Delivery		, 					Lab to Filter	(14) (14)
Other Other Other Other Other Other Ref The construction of the c		1-161				2						Second
Other Current of the totate hay flaquents: Current of the totate hay flaquents: Current of the totate hay flaquents: Current of the totate has have to the totate have totate have to the totate have totate have to the totate have h	t Manager: Tome	THOUSE AT	Other:			28					səjdineş ənendsandanın:O	1966-1979
Miltor T Hanse, M Interline Tirthene, e.M. Sayinth Jack lot. Tirthene, e.M. Sayinth Jack lot. Interline, e.M. Sayinth Jack lot. Interline, e.M. Sayinth Jack lot. Interline, e.M. Jack lot. H Interline, e.M. Jack lot. Jack lot. Interetail Matterline Jack lot.	st Quote Name/Number:		CLP Like Data	Pkg Required:		ہ ج					Field Filtered	<u> </u>
The Hardweight H		Honered	Email To:			9 78					Lab to Filter	(24) X
Construction Description Description Description Description Description Description Description Description 1 T.UT Idi/36/01 Idi/3	15	- Kina	Fax To #:									
TU-1 Luterine Laterine Costs Costs <thcosts< th=""> Costs Costs</thcosts<>		ent Samole (0 / Description	Ending								1 Matrix Codoc.	100
TU-T leitzikal (rt.coc 66u/ H 1 1 1 1 </td <td>Work Order#</td> <td></td> <td>DaterTime</td> <td></td> <td></td> <td>, ,</td> <td></td> <td></td> <td></td> <td></td> <td>GW = Ground Water</td> <td>202</td>	Work Order#		DaterTime			, ,					GW = Ground Water	202
1 Date / Time: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1											WW = Waste Water	
Image: state of the state o					 						A = Air	segme.
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		×									S = Soil SL = Sludge	5.1.1
0 Date/Time: 0 Date/Time: 0											SOL = Solid	s je
e Image: Section and the state of the st					_						u = Uuter (prease define)	10.1
Image: Second control of the second control of th												
e) Date/Time: Prease use the following codes to indicate possible sample concentration e) Date/Time: Prease use the following codes to indicate possible sample concentration e) Date/Time: Prease use the following codes to indicate possible sample concentration e) Date/Time: Program Information c) Date/Time: Program Information bate/Time: Program Information Program Information c) Date/Time: Program Information c) <td></td> <td>² Preservation Codes:</td> <td></td>											² Preservation Codes:	
Please use the following codes to indicate possible sample concentration within the Conc Code oclum above: Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Please use the following codes to indicate possible sample concentration Program Information Plate/Time: Program Information Program Information											H = HCL	
0 Please use the following codes to indicate possible sample concentration within the Cone Code column above: nithin the Cone Code column above: nithies above: n											M = Methanol	
Program Program Information Program Program Information Program Program Information Program Program Information Program Information State Lead Profile Information State Lead Profile Information State Lead Profile Information State Lead Date/Time: Project Entry Other: Date/Time: Onter: Other:											N = Nitric Acid S = Sulfuric Acid	
e) Please use the following codes to indicate possible sample concentration within the Conc Code column above: h - High; M - Medium: L - Low; C - Clean: U - Unknown e) Date/Time: A Id/33/j/d/rss A L(j) [U U - U) Bate/Time: Date/Time: C Id/33/j/d/rss C C - Clean: U - Unknown Bate/Time: Id/33/j/d/rss A L(j) [U U - U) Bate/Time: Date/Time: C Id/33/j/d/rss C Date/Time: Program Information State Lead Bate/Time: Instate Date/Time: Project Entity Date/Time: Project Entity											B = Sodium Bisulfate V = Codium Hudrooldo	11 M N
Please use the following codes to indicate possible sample concentration within the Conc Code column above: H - High; M - Medium; L - Low; C - Clean; U - Uhknown Program Information Date/Time: Program Information INFXTrust Fund Date/Time: No surf Careforn Intercenterates Program Information Date/Time: Program Information INFXTrust Fund Date/Time: Cup/C Date/Time: Cup/C Date/Time: Cup/C Date/Time: Onter											T = Sodium	<u>.</u>
Please use the following codes to indicate possible sample concentration within the Conc Code column above: H - High; M - Medium; L - Low; C - Clean; U - Uhknown Month Carolina Iberection Imit Requirements H - High; M - Medium; L - Low; C - Clean; U - Uhknown M - A2K/Hd / Soc M - A2K/Hd / Soc M - Month Carolina Iberection Imit Requirements M - Month Carolina Iberection Imit Requirements M - Month Carolina Iberection Imit Requirements M - Month Carolina Iberection M - Montherection M - Month Carolina Iberectio	nts:									-	0 = Other (please	<u>-</u>
e) Date/Time: H - High; M - Medium; L - Low; C - Clean; U - Unknown 2) Ul/3%/19/15% 21 3) Date/Time: No rst carolina besention time Requirements 2) Ul/2%/19/15% 21 3) Date/Time: Low; C - Clean; U - Unknown 3) Date/Time: No rst carolina besention time Requirements 3) Date/Time: Componing to the requirements 3) Date/Time: Componing to the requirements 3) Date/Time: Componing to the requirements 4) Date/Time: Componing to the requirements 1) Date/Time: Other: 2) Date/Time: Other: 1) Date/Time: 1) Dat					Please use the	e following within	codes to it the Conc (dicate poss	ible sample cor 1 above:	ncentration	define)	N (
(e) Date/Time: No of the Constituent of the Automation 7.4 (u) (u) <th< td=""><td></td><td></td><td></td><td></td><td>Ξ́, Η</td><td>gh; M - Mec</td><td>dium; L - L</td><td>ow; C - Cle</td><td>ean; U - Unkno</td><td>um</td><td>³ Container Codes:</td><td></td></th<>					Ξ́, Η	gh; M - Mec	dium; L - L	ow; C - Cle	ean; U - Unkno	um	³ Container Codes:	
$ \begin{array}{ c c c c c } \hline	iished by (signature)	Date/Time;		Bestsearer himi	aReguirement		4	ogram I	nformatio	c	A = Amber Glass G = Glass	
Junction Mate/Time: Gwpc Sws Landfill REC e) Date/Time: Insurance Insurance Insurance Insurance e) Date/Time: Other: Insurance Insurance Insurance e) Date/Time: Other: Insurance Insurance Insurance footer Insurance Insurance Insurance Insurance footer Insurance Insurance Insurance Insurance footer Insurance Insurance Insurance Insurance	Zllon	9	🗌 2L		1	8		, ,		/Trust Fund	P = Plastic	d je s
e) total times integration e) bate/Times integration bate/Times integration bate/Times 0ther bate/Times 0ther bate/Times 0ther bate/Times 0ther constraint Net acreation bate/Times 0ther bate/Times 0ther constraint Net acreatited bate/Times federal bate/Times federal city 5chool	(fure)		GWPC			28,029	SW I	Landfill		REC	V = Vial	5 N. 2 S
e) Date/Time: Other: Other Other: Oth	·	U U U Date/Time:	- SWSL	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				. Urphaned	Landtil		5 = Summa Canister T = Tedlar Bao	
Date/Time: Other e) Date/Time: Project Entity bate/Time: Project Entity Date/Time: Chromatogram Date/Time: Date/Time:			MSCC		NORTH CARO	IX T		a rean			0 = Other (please	en e
e) Date/Time: Project Entity Other O	ed by: (signature)	Date/Time:	(D'Unair:				NEL	IC BRO AR	ALAR, LLC AC	medited		Iat
Date/Time: Federal Brownfield City School	uished by: (signature)		1.00		slitu			Othe	r Chromat	aran Miran	PCB ONLY Souther	ble of
	ed by: (signature)	Date/Time:	Federal City		ield				AIHA-LA	5777'd	Non Soxhlet	Conte

IMPORTANT! The wildfires are causing hazardous conditions in California. Learn More



411359783313 🖄

(?)32

Delivered Tuesday 10/29/2019 at 9:06 am

Ø-----Ø-----Ø

DELIVERED Signed for by: B.BECCA

GET STATUS UPDATES OBTAIN PROOF OF DELIVERY

TO EAST LONGMEADOW, MA US

Shipment Facts

TRACKING NUMBER 411359783313

DELIVERED TO Shipping/Receiving

PACKAGING

Your Packaging

SHIP DATE
(?)
Mon 10/28/2019

SERVICE FedEx Priority Overnight

TOTAL PIECES

ACTUAL DELIVERY Tue 10/29/2019 9:06 am

SPECIAL HANDLING SECTION STANDARD TRANSIT

WEIGHT

34.8 lbs / 15.79 kgs

34.8 lbs / 15.79 kgs

TOTAL SHIPMENT WEIGHT

⑦ 10/29/2019 by 10.30 am

Travel History			Local Scan Time	\sim
Tuesday, 10/29/2019	· .	and the second		
9:06 am		Delivered		
7:46 am	WINDSOR LOCKS, CT	On FedEx vehicle for delivery		
7:35 am	WINDSOR LOCKS, CT	At local FedEx facility		
6:23 am	EAST GRANBY, CT	At destination sort facility		

	onfirmed Sample Co Lab Staff Before Reli Imples				ANALY Doc# 2	TICAL L		SC ® TORY
	e Receipt Checklist						ny False	
Client S+	tatement will be broເ ທີ£	ight to the a	ttention of	the Client	- State Tru	e or False		
Received By	140		Date	10/20	10	Time	906	
How were the sam	ples In Cooler	T	No Cooler	T	On Ice	T	No Ice	
received?	Direct from Sam	pling			- Ambient		Melted Ice	,
Were samples wit	thin	By Gun #	2	-	Actual Terr	np- 3.4		
Temperature? 2-6		By Blank #			Actual Terr			
Was Custo	dy Seal Intact?	M	We	ere Sample	s Tampered	with?	$\Lambda 4$	
	Relinquished ?	T	-	s Chain Ag	ree With Sa	imples?	<u> </u>	
	ken/leaking/loose cap	s on any sam	•	F	-		,	
Is COC in ink/ Legi		-		-		olding time?		
Did COC include			Analysis ID's		- '	ler Name Dates/Times	<u> </u>	-
pertinent Informati	on? Project filled out and legible?		. 108		- Conection	Dates/ Times		
Are there Lab to Fil	-	 	-	M/bo wa	s notified?			
Are there Rushes?	(613 :		-		s notified?			
Are there Short Hol	ds?	F	-		s notified?			
Is there enough Vol			-		-			_
Is there Headspace		F	-	MS/MSD?	F		C	
Proper Media/Conta	••	+	-	Is splitting	samples red	- quired?	4	
Were trip blanks re	ceived?	F		On COC?	F	_		_
Do all samples have	e the proper pH?	N-	Acid		-	Base		
Vials #	Containers:	#			#			#
Unp-	1 Liter Amb.	2	1 Liter			16 oz		
HCL- 3	500 mL Amb.		500 mL			8oz Am		
Meoh-	250 mL Amb.		250 mL			4oz Am		
Bisulfate-	Flashpoint		Col./Ba			2oz Am		
DI- Thiosulfate-	Other Glass		Other I Plasti			Enc Frozen:	ore	
Sulfuric-	Perchlorate			ock		1102.011.		
			Unused I	a an				Contract of the second second
Vials #	Containera:	Constant Providence	Gilused	megia	#	and second and second		
Unp-	1 Liter Amb.		1 Liter	Plastic		16 oz	Amb.	
HCL-	500 mL Amb.		500 mL		1 a m 1	8oz Am		
Meoh-	250 mL Amb.		250 mL		····· ··· · · · · · · · · · · · · · ·	4oz Am		
Bisulfate-	Col./Bacteria		Flash	point		2oz Am		
DI-	Other Plastic		Other			Enc	ore	
Thiosulfate-	SOC Kit		Plastic			Frozen:		
Sulfuric-	Perchlorate		Zipl	ock				
Comments:	·							