

STATE OF NORTH CAROLINA DIVISION OF HIGHWAYS

SUMMARY OF SUBSURFACE DRAINAGE

LINE	Station	Station	Location (LT/RT/CL)	Drain Type* (UD/BD/SD)	LF
-L-	40+00.00	107+00.00		SD	6700
-L-	159+00.00	173+00.00		SD	1400
-L-	189+00.00	225+00.00		SD	3600
-L1-	63+73.00	70+00.00		SD	650
-Y4-	10+00.00	15+00.00		SD	500
CONTINGENCY				SD	1000
				TOTAL LF:	13850

*UD = Underdrain
 *BD = Blind Drain
 *SD = Subsurface Drain

SUMMARY OF AGGREGATE SUBGRADE/STABILIZATION

LINE	Station	Station	Aggregate Type* ASU(1/2)/ AST	Aggregate Thickness INCHES [8" for ASU(2)]	Shallow Undercut CY	Class IV Subgrade Stabilization TONS	Geotextile for Soil Stabilization SY	Stabilizer Aggregate TONS	Class IV Aggregate Stabilization TONS
-Y4-	10+50.00	15+75.00	ASU	12	500	950	1500		
CONTINGENCY					500	950	3300		
					TOTAL CY/TONS/SY:				
					1000	1900	4800*		

ASU = Aggregate Subgrade, AST = Aggregate Stabilization

*Total square yards of Geotextile for Soil Stabilization is only the estimated quantity for ASU/AST and may only represent a portion of the geotextile quantity shown in the Item Sheets of the Proposal.