

REFERENCE: R-5014

PROJECT: 41162

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

RETAINING WALL
SUBSURFACE INVESTIGATION

COUNTY DARE
PROJECT DESCRIPTION STRUCTURE NO.1 AND NO.2
ON SR 1217 (COLINGTON ROAD) FROM END TO
US 158 (CROATAN HIGHWAY)
SITE DESCRIPTION RETAINING WALL NO.1 AND
RETAINING WALL NO.2

CONTENTS

SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	LEGEND (SOIL & ROCK)
3	SITE PLAN
4	WALL ENVELOPES

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5014	1	4

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT 1919 TOTTENHAM. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:
1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
 2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

C. TANG, EI
CATLIN
B. MILLER
T. SPENCEL

INVESTIGATED BY C. TANG, EI
DRAWN BY D. BROWN, PEC. TANG, EI
CHECKED BY C. TANG, EI
SUBMITTED BY D. BROWN, PE
DATE NOVEMBER 2017



DocuSigned by:
Donald W. Brown, Jr.
C06817F5F77656 SIGNATURE DATE 1/2/2019

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

**NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION
SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS**

SOIL DESCRIPTION										GRADATION										ROCK DESCRIPTION										TERMS AND DEFINITIONS									
<p>SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, <i>VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6</i></p>										<p>WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.</p>										<p>HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:</p>										<p>ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE. CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK. DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM. RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE. STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (IN OR BPF) OF A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.</p>									
SOIL LEGEND AND AASHTO CLASSIFICATION										MINERALOGICAL COMPOSITION										WEATHERING										ROCK HARDNESS									
<p>GENERAL CLASS. GRANULAR MATERIALS ($\leq 35\%$ PASSING #200) SILT-CLAY MATERIALS ($> 35\%$ PASSING #200) ORGANIC MATERIALS</p> <p>GROUP CLASS. A-1, A-2, A-3, A-4, A-5, A-6, A-7, A-1, A-2, A-3, A-4, A-5, A-6, A-7</p> <p>SYMBOL</p> <p>% PASSING #10, #40, #200</p> <p>MATERIAL PASSING #40 LL, PI</p> <p>GROUP INDEX</p> <p>USUAL TYPES OF MAJOR MATERIALS STONE FRAGS. GRAVEL, AND SAND; FINE SAND; SILTY OR CLAYEY GRAVEL AND SAND; SILTY SOILS; CLAYEY SOILS</p> <p>GEN. RATING AS SUBGRADE EXCELLENT TO GOOD; FAIR TO POOR; FAIR TO POOR; POOR; UNSUITABLE</p> <p>PI OF A-7-5 SUBGROUP IS \leq LL - 30; PI OF A-7-6 SUBGROUP IS $>$ LL - 30</p>										<p>ANGULARITY OF GRAINS THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.</p> <p>MINERALOGICAL COMPOSITION MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.</p> <p>COMPRESSIBILITY SLIGHTLY COMPRESSIBLE (LL $<$ 31) MODERATELY COMPRESSIBLE (LL = 31 - 50) HIGHLY COMPRESSIBLE (LL $>$ 50)</p> <p>PERCENTAGE OF MATERIAL ORGANIC MATERIAL: TRACE OF ORGANIC MATTER (2 - 3%), LITTLE ORGANIC MATTER (3 - 5%), MODERATELY ORGANIC (5 - 10%), HIGHLY ORGANIC ($>$ 10%) GRANULAR SOILS: 2 - 3%, 3 - 5%, 5 - 12%, $>$ 12% SILT - CLAY SOILS: 3 - 5%, 5 - 12%, $>$ 12% OTHER MATERIAL: TRACE (1 - 10%), LITTLE (10 - 20%), SOME (20 - 35%), HIGHLY (35% AND ABOVE)</p> <p>GROUND WATER WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING STATIC WATER LEVEL AFTER 24 HOURS PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA SPRING OR SEEP</p>										<p>FRESH - ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING. ROCK RINGS UNDER HAMMER IF CRYSTALLINE.</p> <p>VERY SLIGHT (IV SL.) - ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.</p> <p>SLIGHT (SL.) - ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.</p> <p>MODERATE (MOD.) - SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.</p> <p>MODERATELY SEVERE (MOD. SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. IF TESTED, WOULD YIELD SPT REFUSAL</p> <p>SEVERE (SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. IF TESTED, WOULD YIELD SPT N VALUES $>$ 100 BPF</p> <p>VERY SEVERE (IV SEV.) - ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. IF TESTED, WOULD YIELD SPT N VALUES $<$ 100 BPF</p> <p>COMPLETE - ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.</p>										<p>UNDERCUT (diagonal hatching) SHALLOW UNDERCUT (horizontal hatching)</p> <p>UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE (cross-hatching) UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK (diagonal hatching)</p> <p>ABBREVIATIONS AR - AUGER REFUSAL; BT - BORING TERMINATED; CL - CLAY; CPT - CONE PENETRATION TEST; CSE - COARSE; DMT - DILATOMETER TEST; DPT - DYNAMIC PENETRATION TEST; e - VOID RATIO; F - FINE; FOSS. - FOSSILIFEROUS; FRAC. - FRACTURED, FRACTURES; FRAGS. - FRAGMENTS; HI. - HIGHLY; MED. - MEDIUM; MICA. - MICACEOUS; MOD. - MODERATELY; NP - NON PLASTIC; ORG. - ORGANIC; PMT - PRESSUREMETER TEST; SAP. - SAPROLITIC; SD. - SAND, SANDY; SL. - SILT, SILTY; SLI. - SLIGHTLY; TCR - TRICONE REFUSAL; w - MOISTURE CONTENT; V - VERY; VST - VANE SHEAR TEST; WEA. - WEATHERED; UG - UNIT WEIGHT; UG - DRY UNIT WEIGHT; S - BULK; SS - SPLIT SPOON; ST - SHELBY TUBE; RS - ROCK; RT - RECOMPACTED TRIAXIAL; CBR - CALIFORNIA BEARING RATIO</p>									
TEXTURE OR GRAIN SIZE										MISCELLANEOUS SYMBOLS										RECOMMENDATION SYMBOLS										SOIL MOISTURE - CORRELATION OF TERMS									
<p>U.S. STD. SIEVE SIZE OPENING (MM): 4, 10, 40, 60, 200, 270; 4.75, 2.00, 0.42, 0.25, 0.075, 0.053</p> <p>BOULDER (BLDR.), COBBLE (COB.), GRAVEL (GR.), COARSE SAND (CSE, SD.), FINE SAND (F SD.), SILT (SL.), CLAY (CL.)</p> <p>GRAIN SIZE: MM 305, 75, 2.0, 0.25, 0.05, 0.005; IN. 12, 3</p>										<p>ROADWAY EMBANKMENT (RE) WITH SOIL DESCRIPTION; SOIL SYMBOL; ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT; INFERRED SOIL BOUNDARY; INFERRED ROCK LINE; ALLUVIAL SOIL BOUNDARY</p> <p>DIP & DIP DIRECTION OF ROCK STRUCTURES; SPT TEST BORING; AUGER BORING; CORE BORING; MONITORING WELL; PIEZOMETER INSTALLATION; SLOPE INDICATOR INSTALLATION; CONE PENETROMETER TEST; SOUNDING ROD; TEST BORING WITH CORE; SPT N-VALUE</p>										<p>UNDERCUT; SHALLOW UNDERCUT; UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE; UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK</p>										<p>SOIL MOISTURE SCALE (ATTERBERG LIMITS); FIELD MOISTURE DESCRIPTION; GUIDE FOR FIELD MOISTURE DESCRIPTION</p> <p>LL - LIQUID LIMIT; PL - PLASTIC LIMIT; OM - OPTIMUM MOISTURE; SL - SHRINKAGE LIMIT</p> <p>- SATURATED - (SAT.) - USUALLY LIQUID; VERY WET, USUALLY FROM BELOW THE GROUND WATER TABLE - WET - (W) - SEMISOLID; REQUIRES DRYING TO ATTAIN OPTIMUM MOISTURE - MOIST - (M) - SOLID; AT OR NEAR OPTIMUM MOISTURE - DRY - (D) - REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE</p>									
PLASTICITY										EQUIPMENT USED ON SUBJECT PROJECT										FRACTURE SPACING										BEDDING									
<p>PLASTICITY INDEX (PI) vs DRY STRENGTH</p> <p>NON PLASTIC (PI $<$ 4); SLIGHTLY PLASTIC (PI 4-7); MODERATELY PLASTIC (PI 7-17); HIGHLY PLASTIC (PI $>$ 17)</p> <p>VERY LOW (PI $<$ 4); SLIGHT (PI 4-7); MEDIUM (PI 7-17); HIGH (PI $>$ 17)</p>										<p>DRILL UNITS: CME-45C, CME-55, CME-550, VANE SHEAR TEST, PORTABLE HOIST, DIEDRICH D-50</p> <p>ADVANCING TOOLS: CLAY BITS, 6" CONTINUOUS FLIGHT AUGER, 8" HOLLOW AUGERS, HARD FACED FINGER BITS, TUNG-CARBIDE INSERTS, CASING w/ ADVANCER, TRICONE *STEEL TEETH, TRICONE *TUNG-CARB., CORE BIT</p> <p>HAMMER TYPE: AUTOMATIC, MANUAL</p> <p>CORE SIZE: -B, -H, -N</p> <p>HAND TOOLS: POST HOLE DIGGER, HAND AUGER, SOUNDING ROD, VANE SHEAR TEST</p>										<p>VERY WIDE - MORE THAN 10 FEET WIDE - 3 TO 10 FEET MODERATELY CLOSE - 1 TO 3 FEET CLOSE - 0.16 TO 1 FOOT VERY CLOSE - LESS THAN 0.16 FEET</p>										<p>VERY THICKLY BEDDED - 4 FEET THICKLY BEDDED - 1.5 - 4 FEET THINLY BEDDED - 0.16 - 1.5 FEET VERY THINLY BEDDED - 0.03 - 0.16 FEET THICKLY LAMINATED - 0.008 - 0.03 FEET THINLY LAMINATED - $<$ 0.008 FEET</p>									
COLOR										INDURATION										FRAC. SPACING										BEDDING									
<p>DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-BROWN). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.</p>										<p>FRAGILE - RUBBING WITH FINGER FREES NUMEROUS GRAINS; GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE. MODERATELY INDURATED - GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. INDURATED - GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER. EXTREMELY INDURATED - SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.</p>										<p>VERY WIDE - MORE THAN 10 FEET WIDE - 3 TO 10 FEET MODERATELY CLOSE - 1 TO 3 FEET CLOSE - 0.16 TO 1 FOOT VERY CLOSE - LESS THAN 0.16 FEET</p>										<p>VERY THICKLY BEDDED - 4 FEET THICKLY BEDDED - 1.5 - 4 FEET THINLY BEDDED - 0.16 - 1.5 FEET VERY THINLY BEDDED - 0.03 - 0.16 FEET THICKLY LAMINATED - 0.008 - 0.03 FEET THINLY LAMINATED - $<$ 0.008 FEET</p>									
																				BENCH MARK: GPS STATION R-5014-GPS-13										ELEVATION: 2.43 FEET									
																				NOTES:																			




BEGIN RETAINING WALL #1
 -WALL1- POT STA. 10+00.00
 -Y3C- STA. 10+67.06 (16.00' LT)

BEGIN RETAINING WALL #2
 -WALL2- PC STA. 10+00.00
 -Y3C- STA. 10+69.88 (41.66' RT)

END RETAINING WALL #1
 -WALL1- PC STA. 10+42.18
 -Y3C- STA. 10+28.84 (21.33' LT)


END RETAINING WALL #2
 -WALL2- POT STA. 10+99.90
 -L- STA. 107+38.88 (35.00' LT)

-L- STA. 106+69.43
 -Y3C- STA. 10+00.00



(A) ARTIFICIAL FILL
 BROWN, BLACK AND GRAY, VERY LOOSE TO
 MEDIUM DENSE, MOIST, SILTY SAND, WITH
 TRACE ROOTS

PROFILE ALONG CENTERLINE OF -WALL1-



NOTE: EXISTING GROUND SURFACE CROSS SECTION AT RETAINING WALL NO. 1 TAKEN FROM ELECTRONIC TIN FILE (DATED 03-13-17). INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE ENVELOPE.

HORIZ. SCALE 0 20 40 (FEET)

VE = 5:1


RETAINING WALL ENVELOPE NO. 1

(A) ALLUVIAL
 GRAY AND BROWN, LOOSE,
 WET, SILTY SAND, WITH
 TRACE SHELL FRAGMENTS
 AND WOOD FRAGMENTS

(B) ARTIFICIAL FILL
 GRAY, BLACK AND
 BROWN, VERY LOOSE TO
 MEDIUM DENSE, MOIST
 TO WET SILTY SAND,
 WITH TRACE ROOTS

PROJECT REFERENCE NO.	SHEET NO.
R-5014	4

PROFILE ALONG CENTERLINE OF -WALL2-



NOTE: EXISTING GROUND SURFACE CROSS SECTION AT RETAINING WALL NO. 2 TAKEN FROM ELECTRONIC TIN FILE (DATED 03-13-17). INFERRED STRATIGRAPHY IS DRAWN THROUGH THE BORINGS WITH BOTH PROJECTED ONTO THE ENVELOPE.

HORIZ. SCALE 0 20 40 (FEET)

VE = 5:1

RETAINING WALL ENVELOPE NO. 2