

+

+

1									
AS-BUILT REPAIR QUANTITY TABLE									
	QUANTITIES								
BENT 1 SPAN B FACE	ESTI	ΜΑΤΕ	ACTUAL						
SHOTCRETE REPAIRS	AREA SQ.FT.	VOLUME CU.FT.	AREA SQ.FT.	VOLUME CU.FT.					
САР	1.9	1.0							
COLUMN	3.4	1.7							
CONCRETE REPAIRS	AREA SQ.FT.	VOLUME CU.FT.	AREA SQ.FT.	VOLUME CU.FT.					
CAP	0.0	0.0							
COLUMN	0.0	0.0							
EPOXY RESIN INJECTION		LIN.FT.	LIN.FT.						
САР	8.0								
COLUMN	0.0								
EPOXY COATING		SQ.FT.	SO. FT.						
TOP OF BENT CAP	0.0								

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1"BEHIND REBAR AND MINIMUM 2"CLEARANCE TO SAWCUT. SEE ``TYPICAL CAP AND COLUMN REPAIR DETAILS'' SHEET.

NOTES

BENT INFORMATION IS TAKEN FROM THE ROUTINE INSPECTION REPORT DATED 05/06/2020.

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE GIVEN BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP AND APPLY EPOXY PROTECTIVE COATING. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

CONCRETE REPAIRS MAYBE SUBSTITUTED IN LIEU OF SHOTCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR CAP REPAIRS, SEE TYPICAL CAP AND COLUMN REPAIR DETAILS SHEET.

	PROJECT NO. <u>I-5746C</u> <u>MECKLENBURG</u> COUNTY BRIDGE NO. <u>590138</u>					
OZEE938FAB674C5 02EE938FAB674C5 02EE938FAB674C5 00FESSION 00FESS	REVISIONS SHEET NO.					
8/23/2021						
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	№. вү: 1 2	DATE:	№. вү: З 4	DATE:	S3-11 TOTAL SHEETS 274	