

AS-BUILT REPAIR QUANTITY TABLE				
END BENT 2	QUANTITIES			
	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SQ.FT.	VOLUME CU.FT.	AREA SQ.FT.	VOLUME CU.FT.
CAP & CURTAIN WALL	0.0	0.0		
CONCRETE REPAIRS	AREA SQ.FT.	VOLUME CU.FT.	AREA SQ.FT.	VOLUME CU.FT.
CAP	0.0	0.0		
EPOXY RESIN INJECTION		LIN. FT.		LIN. FT.
CAP & CURTAIN WALL		11.5		
EPOXY COATING		SQ. FT.		SQ. FT.
TOP OF BENT CAP		150		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1"BEHIND REBAR AND MINIMUM 2"CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

NOTES

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

CONCRETE REPAIRS MAY BE SUBSTITUTED IN LIEU OF SHOTCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISION.

FOR CONCRETE REPAIR, SEE SPECIAL PROVISION.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISION.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP.EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.



CONCRETE REPAIR AREA

SHOTCRETE REPAIR AREA

----- EPOXY RESIN INJECTION (ERI)

∽ 1.5 LF ERI	PROJECT NO. <u>I-5746C</u> <u>MECKLENBURG</u> county BRIDGE NO.: <u>590328</u>				
DocuSigned by:	SHEET 1 OF 2				
DZEE938FAB674C5	STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH				
SEAL SEAL SEAL STOREER SEAL STOREER SEAL	END BENT 2				
THE TO AN A. COLUMN	NORTHBOUND				
8/23/2021					
	REVISIONS SHEET NO				
DOCUMENT NOT CONSIDERED	NO. BY: DATE: NO. BY: DATE: S8-19				
FINAL UNLESS ALL SIGNATURES COMPLETED	1 3 TOTAL SHEETS 2 4 274				