

+

+

AS-BUILT REPA	IR QI	UANT]	ΤΥ Τ	ABLE
BENT 2 NORTHBOUND	QUANTITIES			
DEINI Z NORIHDUUND	ESTIMATE		ACTUAL	
SHOTCRETE REPAIRS	AREA SQ.FT.	VOLUME CU.FT.	AREA SQ.FT.	VOLUME CU.FT.
САР	4.2	2.1		
COLUMNS	8.9	4.5		
CONCRETE REPAIRS	AREA SQ.FT.	VOLUME CU.FT.	AREA SQ.FT.	VOLUME CU.FT.
САР	38.6	19.3		
EPOXY RESIN INJECTION		LIN. FT		LIN. FT
САР		0.0		
COLUMNS		0.0		
EPOXY COATING		SQ. FT.		SQ. FT.
TOP OF BENT CAP		202		

VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MINIMUM OF 1"BEHIND REBAR AND MINIMUM 2"CLEARANCE TO SAWCUT. FOR REPAIR DETAILS, SEE ``TYPICAL CAP AND COLUMN REPAIR DETAILS'' SHEET.

NOTES

REPAIR LOCATIONS AND ESTIMATE OF QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

CONCRETE REPAIRS MAY BE SUBSTITUTED IN LIEU OF SHOTCRETE REPAIRS WITH THE APPROVAL OF THE ENGINEER.

FOR SHOTCRETE REPAIR, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIR, SEE SPECIAL PROVISIONS.

CLEAN AND REMOVE DEBRIS FROM THE TOP OF THE CAP. EPOXY COATING SHALL BE APPLIED TO THE TOP SURFACE OF THE CAP. THE CONTRACTOR SHALL NOT COAT THE AREA OF THE CAP BENEATH THE MASONRY PLATES. FOR EPOXY COATING, SEE SPECIAL PROVISIONS.

FOR PEDESTAL WALL REPAIR, SEE "TYPICAL CAP AND COLUMN REPAIR DETAILS" SHEET.

SHOTCRETE REPAIR AREA

CONCRETE REPAIR AREA

----- EPOXY RESIN INJECTION (ERI)

	PROJECT NO.	<u> </u>	·		
N	MECKLEN				
	BRIDGE No	590330			
DocuSigned by:	SHEET 1 OF 2				
02EE938FAB674C5	STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION RALEIGH				
OFESSION A. COLUMNIA	BENT 2 NORTHBOUND SPAN B FACE				
8/23/2021	SFAN	I D FACE			
	REVISIONS SHEET NO.				
DOCUMENT NOT CONSIDERED		IO. BY: DATE:	S9-17		
FINAL UNLESS ALL SIGNATURES COMPLETED	1 4	3 A	TOTAL SHEETS 274		