

AS-BUILT REPAIR QUANTITY TABLE TOP OF DECK REPAIRS ESTIMATE ACTUAL 1680 SQ. YDS. SCARIFYING BRIDGE DECK 0.0 SQ. YDS. CLASS II SURFACE PREPARATION CONCRETE DECK REPAIR FOR PC OVERLAY 0.0 SQ. YDS. SHOTBLASTING BRIDGE DECK 1680 SQ. YDS. 151.6 CU. YDS. PLACING AND FINISHING PC OVERLAY 1680 SQ. YDS. 14400 SQ.FT. GROOVING BRIDGE FLOORS

TOP OF DECK REPAIR QUANTITIES REPRESENT ESTIMATED VALUES OF CLASS II SURFACE PREPARATION AND CONCRETE DECK REPAIR FOR PC OVERLAY AFTER REMOVAL OF UNSOUND CONCRETE. (MIN. 2" CLEAR TO SAWCUT). SEE OVERLAY SURFACE PREPARATION FOR POLYMER CONCRETE SPECIAL

REPAIR LOCATIONS AND ESTIMATED QUANTITIES ARE BASED ON THE BEST INFORMATION AVAILABLE. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATIONS AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE AS-BUILT REPAIR QUANTITY TABLE.

FOR SECTION B-B, SEE "JOINT DETAILS" SHEET.

FOR CONCRETE DECK REPAIR FOR PC OVERLAY, SEE SPECIAL PROVISIONS. FOR PC MATERIALS, SEE SPECIAL PROVISIONS.

APPROX. CLASS II SURFACE PREPARATION

EPOXY RESIN INJECTION (ERI)

PROJECT NO. I-5746C MECKLENBURG COUNTY 590332 STATION:__

SHEET 9 OF 11

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
RALEIGH

DECK SURFACE REPAIR SPAN R

SHEET NO

REVISIONS DATE:

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED