



**TYPICAL SECTION NO. 4**

NOTE: USE FOR MAP NO. 3 WIDENING EXISTING PAVEMENT TO MINIMUM 18' WIDTH

PAVEMENT SCHEDULE	
C1	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5B, AT AN AVERAGE RATE OF 165 LBS. PER SQ. YD.
C2	PROP. APPROX. 1.5" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168 LBS. PER SQ. YD.
E1	PROP. APPROX. 5.5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 627 LBS. PER SQ. YD.
F1	PROPOSED ASPHALT SURFACE TREATMENT, MAT COAT WITH #67 STONE
S	AGGREGATE SHOULDER BORROW
U	EXISTING PAVEMENT.
V1	MILLING 0" TO 1.5" IN DEPTH
V2	TRENCHING FOR BASE COURSE (SEE S.P.)

g:\AUG-2021\100-2021-Submittal\Randolph-October2021-Maps-1.dgn  
 August 2021  
 10/18/2021