

NOTE: PAVEMENT EDGE SLOPES ARE 1:1 UNLESS SHOWN OTHERWISE.




TO BE USED WITH TYPICAL SECTION NO.1 & 2
-L- STA. 15+00.00 TO STA. 20+00.00 RT.




INSET B

TO BE USED WITH TYPICAL SECTION NO. 1


-L- STA. 30+10.00 TO STA. 32+25.00 LT.



Detail Showing Method of Wedging



TYPICAL SECTION NO. 1



PROJECT REFERENCE NO.

BR-0002

ROADWAY DESIGN
ENGINEER

PAVEMENT DESIGN
ENGINEER

PROJECT REFERENCE NO.

PAVEMENT DESIGN
ENGINEER

PAVEMENT DESIGN
ENGINEER

7/15/2021 SEAL
024641
022896

O22896

Clark S. Morrison

BOATHOUSTEOUTCH.

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

USE TYPICAL SECTION NO. 1

TRANSITION FROM EXISTING AT -L- STA. 15 + 25.00 TO TYPICAL NO. 1 AT -L- STA. 15 + 75.00 -L- STA. 15 + 75.00 TO STA. 17 + 50.00


-L- STA. 29 + 50.00 TO STA. 31 + 75.00 TRANSITION FROM TYPICAL NO. 1 AT -L- STA. 31 + 75.00 TO EXISTING AT -L- STA. 32 + 25.00

* PAVE TO THE FACE OF GUARDRAIL

USE TYPICAL SECTION NO. 2

-L- STA. 17 + 50.00 TO STA. 22 + 40.00 (BEGIN BRIDGE) -L- STA. 25 + 20.00 (END BRIDGE) TO STA. 29 + 50.00

* PAVE TO THE FACE OF GUARDRAIL



TO BE USED WITH TYPICAL SECTION NO. 2
-L- STA. 28+70.00 TO STA. 32+00.00 RT.