

NAD 83/NSRS 2007

-YI-		
Pls Sta 12+89.27	PI Sta 17+57.89	Pls Sta 22+18.60
Os = 5' 58" 05.9"	Δ = 21' 37" 27.0" (LT)	Os = 5' 58" 05.9"
Ls = 375.00'	D = 3' 10" 59.2"	Ls = 375.00'
LT = 250.14'	L = 679.34'	LT = 250.14'
ST = 125.13'	T = 343.76'	ST = 125.13'
	R = 1,800.00'	
	DS = 60 MPH	
	SE = EXIST	

PROJECT REFERENCE NO.	SHEET NO.
U-5754	EC-04/CONST.04
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER

CLEARING AND GRUBBING
EROSION CONTROL FOR
CONSTRUCTION SHEET 04

-YI- SC Sta. 14+14.13

-YI- ST Sta. 24+68.47

754-1

-BL- GPS U5754-2

-YI- CS Sta. 20+93.47

NOTE:
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT
DRAINAGE OUTLETS.

