


STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION

SIGNING PLAN
GUILFORD COUNTY

LOCATION: RAMP EXTENSIONS FROM I-40/I-85 BUSINESS TO US 29/70/220

TIP NO. U-5754	SHEET NO. SIGN-1
APPROVED: _____	
DATE: _____	
SEAL 	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

T.I.P.: U-5754

CONTRACT: C204295

ROADWAY STANDARD DRAWING

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" - PROJECT SERVICES UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2018 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:

STD. NO.	TITLE
901.10	TYPE 'A' SIGNS
901.20	TYPE 'B' SIGNS
901.50	ARROWS AND SHIELDS
901.60	RIVET SPACING FOR OVERLAYED SIGNS
901.70	SIGN STRINGERS AND SUPPORT SPACING
901.80	SIGN MOUNTING DETAILS - FOR TYPE A AND TYPE B SIGNS
903.10	GROUND MOUNTED SIGN SUPPORTS
904.10	ORIENTATION OF GROUND MOUNTED SIGNS
904.20	SECONDARY SIGN MOUNTING
904.30	SUPPLEMENTAL SIGN MOUNTING
904.50	MOUNTING OF TYPE 'D', 'E' AND 'F' SIGNS ON 'U' CHANNEL POSTS

SUMMARY OF QUANTITIES

ITEM NO.	ITEM DESCRIPTION	QUANTITY	UNIT
DESC. NO.	SECT. NO.		
4048000000	902	REINFORCED CONCRETE SIGN FOUNDATION.....	1 C.Y.
4054000000	902	PLAIN CONCRETE SIGN FOUNDATION.....	1 C.Y.
4057000000	SP	OVERHEAD FOOTING.....	57 C.Y.
4060000000	903	SUPPORTS, BREAKAWAY STEEL BEAM.....	415 LB
4066000000	903	SUPPORTS, SIMPLE STEEL BEAM.....	444 LB
4072000000	903	SUPPORTS, 3 LB STEEL U-CHANNEL.....	225 L.F.
4082100000	906	SUPPORTS, OVERHEAD SIGN STRUCTURE @ -Y2- Sta. 12+69.....	1 LS
4082100000	906	SUPPORTS, OVERHEAD SIGN STRUCTURE @ -Y2- Sta. 23+61.....	1 LS
4082100000	906	SUPPORTS, OVERHEAD SIGN STRUCTURE @ -Y2- Sta. 49+43.....	1 LS
4082100000	906	SUPPORTS, OVERHEAD SIGN STRUCTURE @ -Y1RP- Sta.16+86.....	1 LS
4102000000	904	SIGN ERECTION, TYPE E.....	11 EA.
4108000000	904	SIGN ERECTION, TYPE F.....	3 EA.
4109000000	904	SIGN ERECTION, TYPE A (OVERHEAD).....	13 EA.
4109000000	904	SIGN ERECTION, TYPE B (OVERHEAD).....	7 EA.
4110000000	904	SIGN ERECTION, TYPE A (GROUND MOUNTED).....	3 EA.
4115000000	904	SIGN ERECTION, OVERLAY (OVERHEAD).....	7 EA.
4149000000	907	DISPOSAL OF SIGN SYSTEM, OVERHEAD.....	2 EA.
4152000000	907	DISPOSAL OF SIGN SYSTEM, STEEL BEAM.....	6 EA.
4155000000	907	DISPOSAL OF SIGN SYSTEM, U-CHANNEL.....	11 EA.
4234000000	907	DISPOSAL OF SIGN, A OR B (OVERHEAD).....	15 EA.
4238000000	907	DISPOSAL OF SIGN, D, E OR F.....	1 EA.
4241000000	907	DISPOSAL OF SIGN, OVERLAY (OVERHEAD).....	3 EA.
4251000000	907	DISPOSAL OF LIGHTING SYSTEM.....	1 EA.
4263000000	907	DISPOSAL OF WALKWAY.....	4 EA.
4360000000	SP	CUTTING OF SIGN HANGERS, OVERHEAD.....	4 EA.

GENERAL NOTES


- SIGNS FURNISHED BY STATE
- CONFIRM IN WRITING AT LEAST 4 MONTHS IN ADVANCE, THE ACTUAL DATE THE DEPARTMENT FURNISHED SIGNS WILL BE REQUIRED.
- ALL TYPE 'D' SIGNS SHALL BE MOUNTED ON TWO U-CHANNEL POSTS UNLESS OTHERWISE INDICATED ON THE PLANS.
- IF REMOVAL OR RELOCATION OF SIGNS ON PRIVATE STREET (NON-STATE MAINTAINED) IS REQUIRED DUE TO CONSTRUCTION, THE CONTRACTOR SHALL INFORM THE ENGINEER. THE WORK WILL BE COMPLETED BY OTHERS.
- WHEN NOT STATIONED OR DIMENSIONED ON PLANS, ALL 'E' AND 'F' SIGNS SHALL BE FIELD LOCATED BY THE ENGINEER
- WHEN EXISTING SIGNS ARE REMOVED AND INSTALLED ON NEW SUPPORTS, THE RE-ERECTION SHALL IMMEDIATELY FOLLOW THE REMOVAL.
- THE BACKGROUND FOR TYPE E & F SIGNS SHALL BE TYPE C REFLECTIVE SHEETING.
- DO NOT BEGIN FABRICATION FOR TYPES A & B SIGNS MOUNTED ON OVERHEAD STRUCTURES OR STEEL SUPPORTS UNTIL "S" DIMENSIONS HAVE BEEN FIELD VERIFIED.
- SEE ROADWAY PLANS FOR GUARD/GUIDE RAIL DETAILS.

INDEX

SHEET NO.	DESCRIPTION
SIGN-1	TITLE SHEET
SIGN-1A	PLAN SHEET INDEX
SIGN-2	GROUND MOUNTED SIGN SUPPORTS
SIGN-3-3C	STRUCTURE LINE DRAWINGS (EXISTING)
SIGN-3D-3G	STRUCTURE LINE DRAWINGS (PROPOSED)
SIGN-4-4F	SIGN DESIGNS & "E" & "F" SIGNS
SIGN-5-14	SIGNING PLAN SHEETS

PLAN PREPARED FOR THE N.C.D.O.T. SIGNING AND DELINEATION UNIT

Kelvin L. Jordan Signing and Delineation Regional Engineer
Ashley K. Mathews Signing and Delineation Design Engineer






Stantec Consulting Services Inc.
801 Jones Franklin Road
Suite 300
Raleigh, NC 27606
Tel. (919) 851-6866
Fax. (919) 851-7024
www.stantec.com
License No. F-0672

PLAN PREPARED BY: Stantec Consulting Services, Inc.

Betsy L. Watson, PE Senior Principal
Jay Woolard, PE Senior Transportation Engineer
James Hambricht Senior Transportation Technician



TIP NO.	SHEET NO.
U-5754	SIGN - 1A
APPROVED: _____	
DATE: _____	
SEAL	
	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	



\$\$\$\$\$SYTIME\$\$\$\$\$
 \$\$\$\$DDGN\$\$\$\$\$
 \$\$\$USERNAM\$\$\$\$\$

SIGNING PLAN SHEET INDEX



TIP NO. U-5754	SHEET NO. SIGN-2
APPROVED: _____	
DATE: _____	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

Version: 3.1 Posted: 6/2/2017



NUMBER	TYPE	SIGN SIZE (in.)			ROADWAY STATION	NUMBER OF SUPPORTS	BEAM SECTION	SUPPORT TYPE BA or S	OMNI COUPLER	ATTACHMENT METHOD	MOUNTING METHOD	HORIZONTAL CLEARANCE* (ft.)	SUPPORT SPACING	LENGTH (ft)			LEFT SUPPORT (ft)			CENTER SUPPORT (ft)			RIGHT SUPPORT (ft)			SUPPORT WEIGHTS		FOOTINGS				FIELD VERIFIED SEE NOTE 2 (mm/dd/yy)																			
		w	x	h										SNS HT "H"	MTG HT "C"	EMBED-MENT	S	L	LENGTH	S	L	LENGTH	S	L	LENGTH	B/A (lbs.)	SIMPLE (lbs.)	DIAMETER (ft.)	DEPTH (ft.)	REINFORCED (c.y.)	PLAIN (c.y.)																				
101	A	216	x	66	-Y1- Sta. 88+06	2	W6x12	S	N/A	N/A	N/A	11.50	10.55	5.50	7.00	3.5	2.12	14.62	18.12	0.00	0.00	0.00	2.85	15.35	18.85	0.00	443.64	1.5	4	0.52	0.00	_____																			
201	A	96	x	60	-Y2- Sta. 16+84	2	S3x5.7	BA	N/A	N/A	N/A	Δ	4.69	5.00	7.00	2.5	0.50	12.50	15.00	0.00	0.00	0.00	0.50	12.50	15.00	207.00	0	1.0	3	0.00	0.17	_____																			
202	A	72	x	60	-Y1- Sta. 57+33	2	S3x5.7	BA	N/A	N/A	N/A	Δ	3.52	5.00	7.00	2.5	0.50	12.50	15.00	0.00	0.00	0.00	0.50	12.50	15.00	207.00	0	1.0	3	0.00	0.17	_____																			
																								TOTAL	TOTAL	TOTAL	TOTAL																								
																								414.00	443.64	0.52	0.35																								
																								USE:	415.00	444.00	1.00	1.00																							

NOTES


- DIMENSION "S" REPRESENTS AN INCREASE (+), OR A DECREASE (-) IN POLE LENGTH, RELATIVE TO THE ELEVATION OF THE EDGE OF TRAVEL LANE.
- FIELD VERIFICATIONS SHALL BE REQUIRED FOR ALL SUPPORTS, SEE (*) ARTICLE 903-3. FABRICATORS SHALL BE AISC CERTIFIED IN CATEGORY 1, SEE (*) ARTICLE 1072-1. (*) = N.C.D.O.T. STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES
- PLAN LOCATIONS FOR EXISTING UTILITIES ARE BASED ON THE BEST AVAILABLE INFORMATION AND, THEREFORE MAY NOT BE PRECISELY ACCURATE. THEREFORE, IT IS INCUMBENT UPON THE CONTRACTOR TO DETERMINE THE EXACT LOCATION OF UTILITIES BEFORE BEGINNING WORK IN A LOCATION.



TYPE "A" AND TYPE "B" GROUND MOUNTED SIGNS

TIP NO. U-5754	SHEET NO. SIGN-3
APPROVED: _____	
DATE: _____	
SEAL  1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	

EXISTING OVERHEAD SIGN STRUCTURE #1 (Outside Construction Limits)





NOTES:


1. THIS IS A SCHEMATIC REPRESENTATION OF AN EXISTING STRUCTURE BASED ON RECORD DATA AND NOT A FIELD SURVEY. THIS INFORMATION IS SHOWN FOR THE PURPOSE OF ALIGNING THE NEW SIGNS OVER THE APPROPRIATE TRAVEL LANES.
2. REPLACEMENT SIGNS FOR THIS EXISTING STRUCTURE ARE INTENDED TO RESULT IN LESS SIGN SQUARE FOOTAGE, AND THEREFORE LESS WIND LOAD, THAN CURRENTLY EXISTS ON THIS STRUCTURE. THE CONTRACTOR SHALL FIELD VERIFY THE SQUARE FOOTAGE OF THE EXISTING SIGNS AND VERIFY THAT THE REPLACEMENT SIGNS RESULT IN LESS SQUARE FOOTAGE. THIS INFORMATION SHALL BE VERIFIED BEFORE FABRICATION OF THE REPLACEMENT SIGNS.
3. SEE STANDARD 904-3(B)(3) FOR REQUIREMENTS OF NEW STRUCTURAL MEMBERS, MOUNTING HARDWARE FOR NEW SIGNS, SHOP DRAWINGS, BRACING AND ACCESSORY HARDWARE FOR ATTACHMENTS.
4. SEE NCDOT STANDARD SPECIFICATIONS, SECTION 1076-6, FOR REPAIR OF GALVANIZING.
5. WHERE POSSIBLE, MOUNT NEW SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE AND MAINTAIN A MINIMUM CLEARANCE OF 17 FEET (18 FEET MAXIMUM) BETWEEN THE HIGH POINT OF THE ROADWAY AND THE BOTTOM OF THE SIGN.
6. REMOVE ALL EXISTING WALKWAY STRUCTURES.

**EXISTING OVERHEAD SIGN
STRUCTURE #1
(See Sheet SIGN-5)**

\$\$\$SYTIME\$\$\$\$
 \$\$\$DGN\$\$\$\$
 \$\$\$USERNAM\$\$\$\$

EXISTING OVERHEAD SIGN STRUCTURE #2 (Outside Construction Limits)

TIP NO. U-5754	SHEET NO. SIGN-3A
APPROVED: _____	
DATE: _____	
	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	





NOTES:


1. THIS IS A SCHEMATIC REPRESENTATION OF AN EXISTING STRUCTURE BASED ON RECORD DATA AND NOT A FIELD SURVEY. THIS INFORMATION IS SHOWN FOR THE PURPOSE OF ALIGNING THE NEW SIGNS OVER THE APPROPRIATE TRAVEL LANES.
2. REPLACEMENT SIGNS FOR THIS EXISTING STRUCTURE ARE INTENDED TO RESULT IN LESS SIGN SQUARE FOOTAGE, AND THEREFORE LESS WIND LOAD, THAN CURRENTLY EXISTS ON THIS STRUCTURE. THE CONTRACTOR SHALL FIELD VERIFY THE SQUARE FOOTAGE OF THE EXISTING SIGNS AND VERIFY THAT THE REPLACEMENT SIGNS RESULT IN LESS SQUARE FOOTAGE. THIS INFORMATION SHALL BE VERIFIED BEFORE FABRICATION OF THE REPLACEMENT SIGNS.
3. SEE STANDARD 904-3(B)(3) FOR REQUIREMENTS OF NEW STRUCTURAL MEMBERS, MOUNTING HARDWARE FOR NEW SIGNS, SHOP DRAWINGS, BRACING AND ACCESSORY HARDWARE FOR ATTACHMENTS.
4. SEE NCDOT STANDARD SPECIFICATIONS, SECTION 1076-6, FOR REPAIR OF GALVANIZING.
5. WHERE POSSIBLE, MOUNT NEW SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE AND MAINTAIN A MINIMUM CLEARANCE OF 17 FEET (18 FEET MAXIMUM) BETWEEN THE HIGH POINT OF THE ROADWAY AND THE BOTTOM OF THE SIGN.
6. REMOVE ALL EXISTING WALKWAY STRUCTURES.

**EXISTING OVERHEAD SIGN
STRUCTURE #2
(See Sheet SIGN-7)**

\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$DGN\$\$\$\$\$
\$\$\$\$\$USERNAME\$\$\$\$\$

EXISTING OVERHEAD SIGN STRUCTURE #3 (Outside Construction Limits)

TIP NO. U-5754	SHEET NO. SIGN-3B
APPROVED: _____	
DATE: _____	
	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	



Note:
Remove All Existing Walkways on Existing Overhead Structure



NOTES:


1. THIS IS A SCHEMATIC REPRESENTATION OF AN EXISTING STRUCTURE BASED ON RECORD DATA AND NOT A FIELD SURVEY. THIS INFORMATION IS SHOWN FOR THE PURPOSE OF ALIGNING THE NEW SIGNS OVER THE APPROPRIATE TRAVEL LANES.
2. REPLACEMENT SIGNS FOR THIS EXISTING STRUCTURE ARE INTENDED TO RESULT IN LESS SIGN SQUARE FOOTAGE, AND THEREFORE LESS WIND LOAD, THAN CURRENTLY EXISTS ON THIS STRUCTURE. THE CONTRACTOR SHALL FIELD VERIFY THE SQUARE FOOTAGE OF THE EXISTING SIGNS AND VERIFY THAT THE REPLACEMENT SIGNS RESULT IN LESS SQUARE FOOTAGE. THIS INFORMATION SHALL BE VERIFIED BEFORE FABRICATION OF THE REPLACEMENT SIGNS.
3. SEE STANDARD 904-3(B)(3) FOR REQUIREMENTS OF NEW STRUCTURAL MEMBERS, MOUNTING HARDWARE FOR NEW SIGNS, SHOP DRAWINGS, BRACING AND ACCESSORY HARDWARE FOR ATTACHMENTS.
4. SEE NCDOT STANDARD SPECIFICATIONS, SECTION 1076-6, FOR REPAIR OF GALVANIZING.
5. WHERE POSSIBLE, MOUNT NEW SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE AND MAINTAIN A MINIMUM CLEARANCE OF 17 FEET (18 FEET MAXIMUM) BETWEEN THE HIGH POINT OF THE ROADWAY AND THE BOTTOM OF THE SIGN.
6. REMOVE ALL EXISTING WALKWAY STRUCTURES.

**EXISTING OVERHEAD SIGN
STRUCTURE #3
(See Sheet SIGN-7)**

\$\$\$SYTIME\$\$\$\$
 \$\$\$DCN\$\$\$\$
 \$\$\$USERNAME\$\$\$\$

EXISTING OVERHEAD SIGN STRUCTURE #5 (-Y2RP- Sta. 11+55 +/-)

TIP NO. U-5754	SHEET NO. SIGN-3C
APPROVED: _____	
DATE: _____	
	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	



Note:
Remove All Existing Walkways &
Lights on Existing Overhead Structure

NOTES:



1. THIS IS A SCHEMATIC REPRESENTATION OF AN EXISTING STRUCTURE BASED ON RECORD DATA AND NOT A FIELD SURVEY. THIS INFORMATION IS SHOWN FOR THE PURPOSE OF ALIGNING THE NEW SIGNS OVER THE APPROPRIATE TRAVEL LANES.
2. REPLACEMENT SIGNS FOR THIS EXISTING STRUCTURE ARE INTENDED TO RESULT IN LESS SIGN SQUARE FOOTAGE, AND THEREFORE LESS WIND LOAD, THAN CURRENTLY EXISTS ON THIS STRUCTURE. THE CONTRACTOR SHALL FIELD VERIFY THE SQUARE FOOTAGE OF THE EXISTING SIGNS AND VERIFY THAT THE REPLACEMENT SIGNS RESULT IN LESS SQUARE FOOTAGE. THIS INFORMATION SHALL BE VERIFIED BEFORE FABRICATION OF THE REPLACEMENT SIGNS.
3. SEE STANDARD 904-3(B)(3) FOR REQUIREMENTS OF NEW STRUCTURAL MEMBERS, MOUNTING HARDWARE FOR NEW SIGNS, SHOP DRAWINGS, BRACING AND ACCESSORY HARDWARE FOR ATTACHMENTS.
4. SEE NCDOT STANDARD SPECIFICATIONS, SECTION 1076-6, FOR REPAIR OF GALVANIZING.
5. WHERE POSSIBLE, MOUNT NEW SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE AND MAINTAIN A MINIMUM CLEARANCE OF 17 FEET (18 FEET MAXIMUM) BETWEEN THE HIGH POINT OF THE ROADWAY AND THE BOTTOM OF THE SIGN.
6. REMOVE ALL EXISTING WALKWAY STRUCTURES AND LIGHTING FIXTURES.


**EXISTING OVERHEAD SIGN
STRUCTURE #5
(See Sheet SIGN-8)**

\$\$\$SYTIME\$\$\$\$
 \$\$\$DCN\$\$\$\$
 \$\$\$USERNAME\$\$\$\$

OVERHEAD SIGN STRUCTURE 'A'

I-40 EBL @ Exit 223
 -Y2- STA. 12+69
 (Crossection @ -Y2- Sta. 12+50)

TIP NO. U-5754	SHEET NO. SIGN-3D
APPROVED: _____	
DATE: _____	
SEAL  1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	



NOTES:

- IF THE CONTRACTOR BIDS ALUMINUM SIGN STRUCTURE, EACH SHALL BE PROVIDED WITH AN APPROVED HIGHWAY TRUSS DAMPER DEVICE IN ACCORDANCE WITH AASHTO SPECIFICATIONS.
- MOUNT SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE.
- FIELD VERIFICATION SHALL BE REQUIRED FOR ALL FOOTING ELEVATIONS, PER THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES. PROVIDE FIELD VERIFICATION TO THE SIGNING SECTION.
- THE TOP OF THE FOOTING SHALL EXTEND AT LEAST 4 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING.
- SIGN HANGERS AND ATTACHMENT HARDWARE SHALL BE PROVIDED AND INSTALLED ON THE ASSEMBLY TO ACCOMMODATE ALL SIGNS SHOWN IN THIS PLAN SHEET.
- DESIGN AND CONSTRUCTION REQUIREMENTS FOR SIGN STRUCTURES SHALL ACCOMMODATE WIND VELOCITY OF 90 M.P.H.



* THESE DIMENSIONS SHALL BE USED FOR WIND LOAD AND DEAD LOAD COMPUTATIONS IN DESIGN OF STRUCTURE AND FOOTINGS. DESIGN AND CONSTRUCTION REQUIREMENTS FOR SIGN STRUCTURES SHALL ACCOMMODATE WIND VELOCITY OF 90 M.P.H.


OVERHEAD SIGN STRUCTURE 'A'
(I-40 EBL @ EXIT 223)
-Y2- STA. 12+69

\$\$\$SYSTEMTIME\$\$\$
 \$\$\$DGN\$\$\$
 \$\$\$USERNAM\$\$\$

OVERHEAD SIGN STRUCTURE 'C'

US 29/70/220 NBL
 -Y2- STA. 49+43
 (Crossection @ -Y2- Sta. 49+40)

TIP NO. U-5754	SHEET NO. SIGN-3F
APPROVED: _____	
DATE: _____	
SEAL  1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
	



NOTES:

- IF THE CONTRACTOR BIDS ALUMINUM SIGN STRUCTURE, EACH SHALL BE PROVIDED WITH AN APPROVED HIGHWAY TRUSS DAMPER DEVICE IN ACCORDANCE WITH AASHTO SPECIFICATIONS.
- MOUNT SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE.
- FIELD VERIFICATION SHALL BE REQUIRED FOR ALL FOOTING ELEVATIONS, PER THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES. PROVIDE FIELD VERIFICATION TO THE SIGNING SECTION.
- THE TOP OF THE FOOTING SHALL EXTEND AT LEAST 4 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING.
- SIGN HANGERS AND ATTACHMENT HARDWARE SHALL BE PROVIDED AND INSTALLED ON THE ASSEMBLY TO ACCOMMODATE ALL SIGNS SHOWN IN THIS PLAN SHEET.
- DESIGN AND CONSTRUCTION REQUIREMENTS FOR SIGN STRUCTURES SHALL ACCOMMODATE WIND VELOCITY OF 90 M.P.H.



*THESE DIMENSIONS SHALL BE USED FOR WIND LOAD AND DEAD LOAD COMPUTATIONS IN DESIGN OF STRUCTURE AND FOOTINGS. DESIGN AND CONSTRUCTION REQUIREMENTS FOR SIGN STRUCTURES SHALL ACCOMMODATE WIND VELOCITY OF 90 M.P.H.


OVERHEAD SIGN STRUCTURE 'C'
(US 29/70/220 NBL)
-Y2- STA. 49+43

\$\$\$\$\$SYTIME\$\$\$\$\$
 \$\$\$DDGN\$\$\$\$\$
 \$\$\$USERNAM\$\$\$\$\$

OVERHEAD SIGN STRUCTURE 'D'

US 29/70/220 SB Ramp
 -Y1RP- STA. 16+86
 (Crossection @ -Y1RP- Sta. 17+00)

TIP NO. U-5754	SHEET NO. SIGN-3G
APPROVED: _____	
DATE: _____	
SEAL  1/16/2019 DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED 	



NOTES:

- IF THE CONTRACTOR BIDS ALUMINUM SIGN STRUCTURE, EACH SHALL BE PROVIDED WITH AN APPROVED HIGHWAY TRUSS DAMPER DEVICE IN ACCORDANCE WITH AASHTO SPECIFICATIONS.
- MOUNT SIGNS VERTICALLY CENTERED ON HORIZONTAL MEMBER OF STRUCTURE.
- FIELD VERIFICATION SHALL BE REQUIRED FOR ALL FOOTING ELEVATIONS, PER THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES. PROVIDE FIELD VERIFICATION TO THE SIGNING SECTION.
- THE TOP OF THE FOOTING SHALL EXTEND AT LEAST 4 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING.
- SIGN HANGERS AND ATTACHMENT HARDWARE SHALL BE PROVIDED AND INSTALLED ON THE ASSEMBLY TO ACCOMMODATE ALL SIGNS SHOWN IN THIS PLAN SHEET.
- DESIGN AND CONSTRUCTION REQUIREMENTS FOR SIGN STRUCTURES SHALL ACCOMMODATE WIND VELOCITY OF 90 M.P.H.

*THESE DIMENSIONS SHALL BE USED FOR WIND LOAD AND DEAD LOAD COMPUTATIONS IN DESIGN OF STRUCTURE AND FOOTINGS. DESIGN AND CONSTRUCTION REQUIREMENTS FOR SIGN STRUCTURES SHALL ACCOMMODATE WIND VELOCITY OF 90 M.P.H.

OVERHEAD SIGN STRUCTURE 'D'
(US 29/70/220 SB Ramp)
-Y1RP- STA. 16+86

\$\$\$\$\$SYTIME\$\$\$\$\$
 \$\$\$DDGN\$\$\$\$\$
 \$\$\$USERNAME\$\$\$\$\$

SIGN NUMBER: 3B **BACKG COLOR: Green** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: A **COPY COLOR: White** **DESIGN BY: James Hambricht** **DATE: Dec 11, 2018**
QUANTITY: 1 **LOCATION: Existing Overhead Sign Structure #2**

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 18'-0"
 HEIGHT: 6'-6"
 TOTAL AREA: 117.0 Sq.Ft.

BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 10"

Panel Style: guide_fw_overhead.ssi
 M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
EM 2000	178.4
E 2000	65.1

FILENAME: U-5754 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 4B **BACKG COLOR: Green** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: A **COPY COLOR: White** **DESIGN BY: James Hambricht** **DATE: Oct 18, 2018**
QUANTITY: 1 **LOCATION: Existing Overhead Sign Structure #3**

SYMBOL	X	Y	WID	HT
M1_4	30.8	100	36	36
M1_4	99	100	36	36
M1_4	162.7	100	45	36
ARDOWN	101	12	32	22

SIGN WIDTH: 19'-6"
 HEIGHT: 15'-0"
 TOTAL AREA: 292.5 Sq.Ft.

BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 12"

Panel Style: guide_fw_overhead.ssi
 M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
E 2000	59.9
E 2000	46.4
E 2000	59.9
EM 2000	123.4
E 2000	65.1

FILENAME: U-5754 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 5B **BACKG COLOR: Green** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: A **COPY COLOR: White** **DESIGN BY: James Hambricht** **DATE: Dec 11, 2018**
QUANTITY: 1 **LOCATION: Existing Overhead Sign Structure #3**

SYMBOL	X	Y	WID	HT
AR_Type A	212.4	19.2	22.2	35

SIGN WIDTH: 21'-6"
 HEIGHT: 5'-6"
 TOTAL AREA: 118.3 Sq.Ft.

BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 9"

Panel Style: guide_fw_overhead.ssi
 M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
EM 2000	178.4

FILENAME: U-5754 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 6B **BACKG COLOR: Green** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: A **COPY COLOR: White** **DESIGN BY: James Hambricht** **DATE: Oct 18, 2018**
QUANTITY: 1 **LOCATION: Proposed Overhead Sign Structure "A" (-Y2- Sta. 12+69)**

SYMBOL	X	Y	WID	HT
M1_4	30.8	87.9	36	36
M1_4	99	87.9	36	36
M1_4	162.7	87.9	45	36
AR_Type A	29.5	20.3	22.2	35
AR_Type A	177	20.3	22.2	35

SIGN WIDTH: 19'-6"
 HEIGHT: 14'-0"
 TOTAL AREA: 273.0 Sq.Ft.

BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 12"

Panel Style: guide_fw_overhead.ssi
 M.U.T.C.D.: 2009 Edition

Spacing Factor is 1 unless specified otherwise


LETTER POSITIONS

Letter spacings are to start of next letter

Series/Size	Text Length
E 2000	59.9
E 2000	46.4
E 2000	59.9
EM 2000	123.4

FILENAME: U-5754 Sign Designs NORTH CAROLINA D.O.T. SIGN DETAIL

APPROVED: _____
 DATE: _____



1/16/2019
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



\$\$\$\$\$SYTIME\$\$\$\$\$
 \$\$\$\$DDGN\$\$\$\$\$
 \$\$\$\$USERNAM\$\$\$\$\$

SIGN DESIGNS

SIGN NUMBER: 7

TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_4	71.6	89.7	36	36
M1_4	139.7	89.6	36	36
AR_Type A	17.1	70.2	22.2	35
M1_4	67.1	16.1	45	36

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be direct applied, Grade "A" sheeting (except those that are colored black).
- Background shall be Grade "C" reflective sheeting.
- Shields and Type "A", "B", and "C" Arrows shall be demountable and made from 0.032" (0.8mm) aluminum.

PROJECT ID: U-5754
DESIGN BY: James Hambright
LOCATION: Existing Overhead Sign Structure #5

CHECKED BY: Name
DIVISION: 7
DATE: Oct 18, 2019

Panel Style: guide_fw_overhead.ssi
M.U.T.C.D.: 2009 Edition
Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

	N	O	R	T	H	Series/Size
59.6	12.2	3.1	12.8	11	9.7	78.5
	E	A	S	T		
134.5	11.3	1.5	13.6	11	9	17.1
	N	O <td>R</td> <td>T</td> <td>H</td> <td></td>	R	T	H	
59.6	12.2	3.1	12.8	11	9.7	78.5

FILENAME: U-5754 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 8

TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
M1_1	51	75.9	36	36
ARDOWN	5.3	13.9	32	22

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be direct applied, Grade "A" sheeting (except those that are colored black).
- Background shall be Grade "C" reflective sheeting.
- Shields and Type "A", "B", and "C" Arrows shall be demountable and made from 0.032" (0.8mm) aluminum.

PROJECT ID: U-5754
DESIGN BY: James Hambright
LOCATION: Existing Overhead Sign Structure #5

CHECKED BY: Name
DIVISION: 7
DATE: Oct 18, 2019

Panel Style: guide_fw_overhead.ssi
M.U.T.C.D.: 2009 Edition
Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

	E	A	S	T	Series/Size		
45.8	11.3	1.5	13.6	11	9	45.8	
	D	u	r	h	o	m	
20.7	17.8	17	11.8	15.5	17	17.6	20.7

FILENAME: U-5754 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 9

TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
ARDOWN	68.4	8	32	22

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be direct applied, Grade "A" sheeting (except those that are colored black).
- Background shall be Grade "C" reflective sheeting.
- Shields and Type "A", "B", and "C" Arrows shall be demountable and made from 0.032" (0.8mm) aluminum.
- Bottom panel shall be yellow, Grade "C" sheeting. Legend shall be direct applied, non-reflective, black sheeting. Yellow panel is 174" X 36".
- "NO TRUCKS" panel shall be yellow, Grade "C" sheeting. Legend shall be black, direct applied, non-reflective sheeting. Panel size shall be 120" X 18".

PROJECT ID: U-5754
DESIGN BY: James Hambright
LOCATION: Proposed Overhead Sign Structure "B" (-Y2- Sta. 23+61)

CHECKED BY: Name
DIVISION: 7
DATE: Oct 18, 2019

Panel Style: guide_fw_intermediate.ssi
M.U.T.C.D.: 2009 Edition
Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

	F	l	o	r	i	d	a	S	t	Series/Size	
23.6	16.2	8.2	15.8	11.8	8.2	15.5	10.6	16	16.3	8.3	23.6
	1/2	M	I	L	E						
54.5	22	10	12	4.4	9.2	7.5	54.5				
	N	O	T	R	U	C	K	S			
35.2	12.5	10.1	12	11	12.1	12.5	11.2	9.7	35.2		
	E	X	I	T							
13.8	11.4	13.9	5.1	9	120.6						
	O	N	L	Y							
112.4	12.8	12.8	9.9	12.2	13.8						

FILENAME: U-5754 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL

SIGN NUMBER: 10

TYPE: A
QUANTITY: 1

BACKG COLOR: Green
COPY COLOR: White

SYMBOL	X	Y	WID	HT
AR_Type A	69.1	4.7	22.2	35

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be direct applied, Grade "A" sheeting (except those that are colored black).
- Background shall be Grade "C" reflective sheeting.
- Shields and Type "A", "B", and "C" Arrows shall be demountable and made from 0.032" (0.8mm) aluminum.
- Bottom panel shall be yellow, Grade "C" sheeting. Legend shall be direct applied, non-reflective, black sheeting. Yellow panel is 174" X 36".
- "NO TRUCKS" panel shall be yellow, Grade "C" sheeting. Legend shall be black, direct applied, non-reflective sheeting. Panel size shall be 120" X 18".

PROJECT ID: U-5754
DESIGN BY: James Hambright
LOCATION: Proposed Overhead Sign Structure "C" (-Y2- Sta. 49+43)

CHECKED BY: Name
DIVISION: 7
DATE: Oct 18, 2019

Panel Style: guide_fw_intermediate.ssi
M.U.T.C.D.: 2009 Edition
Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

	F	l	o	r	i	d	a	S	t	Series/Size	
23.6	16.2	8.2	15.8	11.8	8.2	15.5	10.6	16	16.3	8.3	23.6
	N	O	T	R	U	C	K	S			
35.2	12.5	10.1	12	11	12.1	12.5	11.2	9.7	35.2		
	E	X	I	T							
17.6	11.4	13.9	5.1	9	116.9						
	O	N	L	Y							
108.6	12.8	12.8	9.9	12.2	17.6						

FILENAME: U-5754 Sign Designs
NORTH CAROLINA D.O.T. SIGN DETAIL

APPROVED: _____
DATE: _____

SEAL

1/16/2019

DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED

\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$DDCN\$\$\$\$\$
\$\$\$\$\$USERNAM\$\$\$\$\$

SIGN NUMBER: 11A **BACKG COLOR: Yellow** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: D **COPY COLOR: Black** **DESIGN BY: James Hambricht** **LOCATION: Proposed Overhead Sign Structure "D" (-Y1- Sta. 63+92)** **DATE: Oct 18, 2018**
QUANTITY: 1

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 6'-0"
HEIGHT: 2'-6"
TOTAL AREA: 15.0 Sq.Ft.

BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADII: 3.25"

No. Z BARS: 1
LENGTH: 250.0

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be black, direct applied, non-reflective sheeting.
- Background shall be Grade "C" reflective sheeting.

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Letter	Series/Size	Text Length
L	E 2000	41.4
E	E 2000	20.8
F	E 2000	46.4
T	EM 2000	178.4

FILENAME: U-5754 Sign Designs **NORTH CAROLINA D.O.T. SIGN DETAIL**

SIGN NUMBER: 11B **BACKG COLOR: Green** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: A **COPY COLOR: White** **DESIGN BY: James Hambricht** **LOCATION: Proposed Overhead Sign Structure "D" (-Y1- Sta. 63+92)** **DATE: Dec 11, 2018**
QUANTITY: 1

SYMBOL	X	Y	WID	HT
M1_1	132.8	51.7	36	36
AR_Type A	18	18	22.2	35

SIGN WIDTH: 21'-6"
HEIGHT: 12'-6"
TOTAL AREA: 268.8 Sq.Ft.

BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADII: 12"

No. Z BARS: 4
LENGTH: 250.0

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be direct applied, Grade "A" sheeting (except those that are colored black).
- Background shall be Grade "C" reflective sheeting.
- Shields and Type "A", "B", and "C" Arrows shall be demountable and made from 0.032" (0.8mm) aluminum.

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Letter	Series/Size	Text Length
T	E 2000	20.8
O	E 2000	46.4
A	EM 2000	178.4
S	E 2000	46.4
T	E 2000	20.8

FILENAME: U-5754 Sign Designs **NORTH CAROLINA D.O.T. SIGN DETAIL**

SIGN NUMBER: 12 **BACKG COLOR: Green** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: A **COPY COLOR: White** **DESIGN BY: James Hambricht** **LOCATION: Proposed Overhead Sign Structure "D" (-Y1- Sta. 63+92)** **DATE: Dec 10, 2018**
QUANTITY: 1

SYMBOL	X	Y	WID	HT
M1_1	53.1	179	36	36
M1_4	122.4	179	36	36
M1_4	53.1	104.7	36	36
M1_4	117.9	104.7	45	36
ARDOWN	20	12.8	32	22
ARDOWN	164	12.8	32	22

SIGN WIDTH: 18'-0"
HEIGHT: 21'-6"
TOTAL AREA: 387.0 Sq.Ft.

BORDER TYPE: FLUSH
RECESS: 0"
WIDTH: 2"
RADII: 12"

No. Z BARS: 6
LENGTH: 208.0

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be direct applied, Grade "A" sheeting (except those that are colored black).
- Background shall be Grade "C" reflective sheeting.
- Shields and Type "A", "B", and "C" Arrows shall be demountable and made from 0.032" (0.8mm) aluminum.

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Letter	Series/Size	Text Length
W	E 2000	48.8
E	E 2000	20.8
S	E 2000	59.8
T	E 2000	20.8
H	EM 2000	134.6
P	E 2000	48.8
O	E 2000	20.8
I	E 2000	20.8
N	E 2000	20.8
T	E 2000	20.8

FILENAME: U-5754 Sign Designs **NORTH CAROLINA D.O.T. SIGN DETAIL**

SIGN NUMBER: 13 **BACKG COLOR: Yellow** **PROJECT ID: U-5754** **CHECKED BY: Name** **DIVISION: 7**
TYPE: A **COPY COLOR: Black** **DESIGN BY: James Hambricht** **LOCATION: Proposed Overhead Sign Structure "D" (-Y1- Sta. 63+92)** **DATE: Oct 18, 2018**
QUANTITY: 1

SYMBOL	X	Y	WID	HT

SIGN WIDTH: 10'-0"
HEIGHT: 10'-0"
TOTAL AREA: 100.0 Sq.Ft.

BORDER TYPE: FLUSH
RECESS: 0.5"
WIDTH: 1.5"
RADII: 12"

No. Z BARS: 3
LENGTH: 112.0

MAT'L: 0.125" (3.2 mm) ALUMINUM

NOTES:

- Legend and border shall be black, direct applied, non-reflective sheeting.
- Background shall be Grade "C" reflective sheeting.

Spacing Factor is 1 unless specified otherwise

LETTER POSITIONS

Letter spacings are to start of next letter

Letter	Series/Size	Text Length
R	E 2000	62.9
L	E 2000	57.6
A	E 2000	48.8
N	E 2000	20.8
E	E 2000	20.8
M	E 2000	33.1
I	E 2000	20.8
L	E 2000	20.8
E	E 2000	20.8

FILENAME: U-5754 Sign Designs **NORTH CAROLINA D.O.T. SIGN DETAIL**

APPROVED: _____
 DATE: _____

SEAL

1/16/2019


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



\$\$\$\$\$SYTIME\$\$\$\$\$
 \$\$\$\$DGN\$\$\$\$\$
 \$\$\$\$USERNAME\$\$\$\$\$

SIGN DESIGNS


401 QUANTITY REQ'D 1_



W4-3(R)
48" X 48"

TWO "U" POSTS PER SIGN


402 QUANTITY REQ'D 1_



W4-3(L)
48" X 48"

TWO "U" POSTS PER SIGN


403 QUANTITY REQ'D 1_



W1-2
48" X 48"

TWO "U" POSTS PER SIGN

404 QUANTITY REQ'D 8_




W1-8(L)
30" X 36"

ONE "U" POST PER SIGN

501 QUANTITY REQ'D 1_


REMOVE I-85 BUSINESS SHIELD AND CARDINAL DIRECTION PANEL FROM EXISTING ASSEMBLY



NOTE:
EXISTING SIGN ASSEMBLY IS MOUNTED ON TWO WOODEN POSTS WITH U-CHANNEL SUPPORT BRACING

502 QUANTITY REQ'D 1_


(2 "U" POSTS PER ASSMBLY)



TWO "U" POSTS PER SIGN

503 QUANTITY REQ'D 1_

(2 "U" POSTS PER ASSMBLY)



TWO "U" POSTS PER SIGN


TIP NO. SHEET NO.

U-5754 SIGN-4F

APPROVED: _____

DATE: _____

SEAL




1/16/2019

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




TYPE "E" & "F" SIGNS

TIP NO. U-5754	SHEET NO. SIGN-5
APPROVED: _____	
DATE: _____	
SEAL	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



To Winston-Salem

MATCHLINE SHEET SIGN-6



Overlay Placement Detail
Overlay Panel #706 & #707
(66" x 20")


PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, OVERHEAD
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 4 DISPOSAL OF SIGN, A OR B (OVERHEAD)
- 5 DISPOSAL OF SIGN, D, E OR F
- 6 DISPOSAL OF LIGHTING SYSTEM
- 7 DISPOSAL OF WALKWAY
- 8 SIGN ERECTION, TYPE A (OVERHEAD)
- 9 SIGN ERECTION, TYPE B (OVERHEAD)
- 10 SIGN ERECTION, TYPE A (GROUND MOUNTED)
- 11 SIGN ERECTION, TYPE D, E, AND F
- 12 SIGN ERECTION, OVERLAY (OVERHEAD)
- 13 DISPOSAL OF OVERLAY (OVERHEAD)
- 14 CUTTING OF SIGN HANGERS (OVERHEAD)

EXISTING/PROPOSED SIGNING
EXISTING OVERHEAD SIGN STRUCTURE #1

\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$DDGN\$\$\$\$\$
\$\$\$\$\$USERNAM\$\$\$\$\$

TIP NO. U-5754	SHEET NO. SIGN-6
APPROVED: _____	
DATE: _____	
SEAL	
1/16/2019	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	



MATCHLINE SHEET SIGN-5

MATCHLINE -X1- STA. 11+00 SEE SHEET SIGN-7

PROJECT NOTES

- 1 DISPOSAL OF SIGN SYSTEM, OVERHEAD
- 2 DISPOSAL OF SIGN SYSTEM, STEEL BEAM
- 3 DISPOSAL OF SIGN SYSTEM, U-CHANNEL
- 4 DISPOSAL OF SIGN, A OR B (OVERHEAD)
- 5 DISPOSAL OF SIGN, D, E OR F
- 6 DISPOSAL OF LIGHTING SYSTEM
- 7 DISPOSAL OF WALKWAY

- 8 SIGN ERECTION, TYPE A (OVERHEAD)
- 9 SIGN ERECTION, TYPE B (OVERHEAD)
- 10 SIGN ERECTION, TYPE A (GROUND MOUNTED)
- 11 SIGN ERECTION, TYPE D, E, AND F
- 12 SIGN ERECTION, OVERLAY (OVERHEAD)
- 13 DISPOSAL OF OVERLAY (OVERHEAD)
- 14 CUTTING OF SIGN HANGERS (OVERHEAD)

EXISTING/PROPOSED SIGNING

\$\$\$\$\$SYTIME\$\$\$\$\$
\$\$\$\$\$USERNAME\$\$\$\$\$

