



CLEARING AND GRUBBING  
EROSION CONTROL FOR  
CONSTRUCTION SHEET 12

NOTE:  
PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B  
AND TEMPORARY ROCK SILT CHECKS TYPE - A AT  
DRAINAGE OUTLETS.

<p>PI Sta 128+73.26 Δ = 38° 27' 26.2" (RT) D = 8' 11" 06.4" L = 469.84' T = 244.16' R = 700.00' SE = 6% RO = 126' V = 45 MPH</p>	<p>PI Sta 132+79.59 Δ = 48° 44' 46.4" (RT) D = 21' 00" 00.0" L = 232.12' T = 123.61' R = 272.84' SE = 6% RO = 126' * V = 30 MPH</p>
<p>PI Sta 135+62.16 Δ = 48° 11' 11.3" (RT) D = 15' 24" 00.0" L = 312.90' T = 166.37' R = 372.05' SE = 6% RO = 126' * V = 35 MPH</p>	<p>PI Sta 138+87.14 Δ = 73° 15' 56.1" (LT) D = 23' 52" 23.7" L = 306.89' T = 178.45' R = 240.00' SE = 4% RO = 73' * V = 30 MPH</p>

NOTES:  
\* DESIGN EXCEPTION REQUIRED FOR MINIMUM  
HORIZONTAL CURVE RADII.  
\*\* SEE SHEET 26-F FOR GEOTECHNICAL DETAILS  
DRIVEWAY RADII ARE 10' UNLESS OTHERWISE NOTED  
SEE SHEET 25 FOR -L- PROFILE

REVISIONS

I:\5208\Projects\Commentary\Design\RE014\_hyd\_EC\_psh\_12.dgn