



UTILIZE FABRIC INSERT INLET PROTECTION DEVICES IN LIEU OF TEMPORARY ROCK INLET SEDIMENT TRAPS TYPE-C WHERE PONDING MAY OCCUR ON ROADWAY OPEN TO TRAFFIC.

-L-		-RPA-	
PI Sta 13+40.63	PI Sta 16+63.75	PI Sta 28+53.50	PI Sta 11+52.12
Δ = 6' 15" 49.2" (RT)	Δ = 1' 11" 31.5" (RT)	Δ = 14' 26" 10.3" (RT)	Δ = 3' 01" 54.5" (LT)
D = 4' 08" 02.3"	D = 1' 16" 23.7"	D = 3' 54" 30.9"	D = 6' 46" 21.2"
L = 151.52'	L = 93.63'	L = 369.35'	L = 44.77'
T = 75.83'	T = 46.81'	T = 185.66'	T = 22.39'
R = 1,385.97'	R = 4,499.99'	R = 1,465.90'	R = 846.00'
			SE = 04
			Runoff = 110'
			DS = 40MPH

ALL DRIVE RADII 10' UNLESS OTHERWISE NOTED  
 FOR DETOUR, SEE SHEET NO. 2B-1  
 FOR STRUCTURE PLANS SEE S-1 THRU S-28  
 FOR PROFILE, SEE SHEET NO. 5

51469 15/2/2021 10:01-10:03 B5737.dwg Sheets B5737\_REU\_ECO6\_PSH04\_2\_FINAL.dgn