

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**


09_08/2019

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	B-5694	1	
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
45648.1.1		P.E.	
45648.2.1		ROW & UTIL.	
45648.3.1		CONSTR.	

STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS
BLADEN COUNTY


LOCATION: REPLACE BRIDGE NO. 080051 OVER WHITE OAK CANAL ON NC 11

TYPE OF WORK: GRADING, DRAINAGE, PAVING AND STRUCTURE




TIP PROJECT: B-5694

CONTRACT: C204362



DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED



DESIGN DATA

ADT 2022 =	3326
ADT 2042 =	4075
K =	10 %
D =	55 %
T =	13 % *
V =	60 MPH
V (DET) =	45 MPH
* TTST =	11% DUAL 2%
FUNC CLASS =	MAJOR COLLECTOR REGIONAL TIER

PROJECT LENGTH

LENGTH OF ROADWAY TIP PROJECT B-5694	= .219 MILES
LENGTH OF STRUCTURE TIP PROJECT B-5694	= .066 MILES
TOTAL LENGTH OF TIP PROJECT B-5694	= .285 MILES

Prepared in the Office of: KCI Associates of N.C., P.A. 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609 Phone (919) 783-9214 Fax (919) 783-9266 http://www.kci.com	Plans Prepared For: DIVISION OF HIGHWAYS 1000 Birch Ridge Dr. Raleigh NC, 27610
2018 STANDARD SPECIFICATIONS RIGHT OF WAY DATE: MAY 31, 2019	DEWAYNE L. SYKES, P.E. PROJECT ENGINEER
LETTING DATE: JUNE 21, 2022	BRYAN E. HOUGH, P.E. PROJECT DESIGN ENGINEER
NC DOT CONTACT:	KRISTY ALFORD, P.E. STRUCTURES MANAGEMENT UNIT

HYDRAULICS ENGINEER

DocuSigned by:

 CA0C89016E8C437...
 P.E. 4/7/2022


ROADWAY DESIGN ENGINEER

DocuSigned by:

 398761E1FEF93446...
 P.E. 4/4/2022



25-MAR-2022 06:46
 M:\2018\20180945\12 B-5694\Roadway\Proj\B-5694_Rdy_t.sh.dgn
 \$\$\$SERVNAME\$\$\$



EFF. 01-16-2018

SHEET NUMBER	SHEET
1	TITLE SHEET
1A	INDEX OF SHEETS, GENERAL NOTES, AND STANDARD DRAWINGS
1B	CONVENTIONAL SYMBOLS
2A-1	TYPICAL SECTIONS, PAVEMENT SCHEDULE, WEDGING DETAIL, AND INCIDENTAL MILLING DETAIL
2C-1	TEMPORARY GUARDRAIL ANCHOR UNIT TYPE B-77
2C-2	GUARDRAIL INSTALLATION
2C-1	STANDARD TEMPORARY SHORING
3B-1	SUMMARY OF EARTHWORK, SUMMARY OF SHOULDER BERM GUTTER, SUMMARY OF PAVEMENT REMOVAL, SUMMARY OF BREAKING OF EXISTING PAVEMENT, SUMMARY OF PORTABLE CONCRETE BARRIER AND SUMMARY OF GUARDRAIL
3D-1	SUMMARY OF DRAINAGE QUANTITIES
3G-1	SUMMARY OF SUBSURFACE DRAINAGE
4 TO 5	-L- PLAN SHEETS
6 TO 7	-DET- PLAN SHEETS
8	-L- PROFILE SHEET
9	-DET- PROFILE SHEET
RW01 TO RW05	RIGHT OF WAY SHEETS
TMP-1 TO TMP-5B	TRANSPORTATION MANAGEMENT PLANS
PMP-1 TO PMP-3	PAVEMENT MARKING PLANS
EC-1 TO EC-9	EROSION CONTROL PLANS
U0-1 TO U0-3	UTILITIES BY OTHERS PLANS
X-1	CROSS SECTION INDEX
X-1A	CROSS SECTION SUMMARY
X-2 TO X-28	CROSS-SECTIONS
S-1 TO S-37	STRUCTURE PLANS

GENERAL NOTES: 2018 SPECIFICATIONS EFFECTIVE: 01-16-2018

GRADING AND SURFACING OR RESURFACING AND WIDENING:
 THE GRADE LINES SHOWN DENOTE THE FINISHED ELEVATION OF THE PROPOSED SURFACING AT GRADE POINTS SHOWN ON THE TYPICAL SECTIONS. WHERE NO GRADE LINES ARE SHOWN, THE PROFILES SHOWN DENOTE THE TOP ELEVATION OF THE EXISTING PAVEMENT ALONG THE CENTER LINE OF SURVEY ON WHICH THE PROPOSED RESURFACING WILL BE PLACED. GRADE LINES MAY BE ADJUSTED BY THE ENGINEER IN ORDER TO SECURE A PROPER TIE-IN.

CLEARING:
 CLEARING ON THIS PROJECT SHALL BE PERFORMED TO THE LIMITS ESTABLISHED BY METHOD III.

SUPERELEVATION:
 ALL CURVES ON THIS PROJECT SHALL BE SUPERELEVATED IN ACCORDANCE WITH STD. NO. 225.04 USING THE RATE OF SUPERELEVATION AND RUNDFF SHOWN ON THE PLANS. SUPERELEVATION IS TO BE REVOLVED ABOUT THE GRADE POINTS SHOWN ON THE TYPICAL SECTIONS.

SHOULDER CONSTRUCTION:
 ASPHALT, EARTH, AND CONCRETE SHOULDER CONSTRUCTION ON THE HIGH SIDE OF SUPERELEVATED CURVES SHALL BE IN ACCORDANCE WITH STD. NO. 560.01

SUBSURFACE DRAINS:
 SUBSURFACE DRAINS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. NO.815.02 AT LOCATIONS DIRECTED BY THE ENGINEER.

DRIVEWAYS:
 DRIVEWAYS SHALL BE CONSTRUCTED IN ACCORDANCE WITH STD. 848.02 USING 3 FOOT RADII OR RADII AS SHOWN ON THE PLANS. LOCATIONS OF DRIVES WILL BE AS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.

GUARDRAIL:
 THE GUARDRAIL LOCATIONS SHOWN ON THE PLANS MAY BE ADJUSTED DURING CONSTRUCTION AS DIRECTED BY THE ENGINEER. THE CONTRACTOR SHOULD CONSULT WITH THE ENGINEER PRIOR TO ORDERING GUARDRAIL MATERIAL.

TEMPORARY SHORING:
 SHORING REQUIRED FOR THE MAINTENANCE OF TRAFFIC NOT SHOWN ON THE PLANS WILL BE PAID FOR AT THE CONTRACT PRICE FOR "TEMPORARY SHORING".

END BENTS:
 THE ENGINEER SHALL CHECK THE STRUCTURE END BENT PLANS, DETAILS, AND CROSS-SECTION PRIOR TO SETTING OF THE SLOPE STAKES FOR THE EMBANKMENT OR EXCAVATION APPROACHING A BRIDGE.

UTILITIES:
 UTILITY OWNERS ON THIS PROJECT ARE FOUR COUNTY EMC (OVERHEAD ELECTRIC), WINDSTREAM (BURIED COMMUNICATION), AND STAR COMMUNICATIONS (BURIED COMMUNICATION) ANY RELOCATION OF EXISTING UTILITIES WILL BE ACCOMPLISHED BY OTHERS.

RIGHT-OF-WAY MARKERS:
 ALL RIGHT-OF-WAY MARKERS ON THIS PROJECT SHALL BE PLACED BY OTHERS.

2018 ROADWAY ENGLISH STANDARD DRAWINGS

The following Roadway Standards as appear in "Roadway Standard Drawings" Highway Design Branch - N. C. Department of Transportation - Raleigh, N. C., Dated January, 2018 are applicable to this project and by reference hereby are considered a part of these plans:

STD. NO.	TITLE
DIVISION 2 - EARTHWORK	
200.03	Method of Clearing - Method III
225.02	Guide for Grading Subgrade - Secondary and Local
225.04	Method of Obtaining Superelevation - Two Lane Pavement
DIVISION 3 - PIPE CULVERTS	
300.01	Method of Pipe Installation
DIVISION 4 - MAJOR STRUCTURES	
422.01	Bridge Approach Fills - Type I Standard Approach Fill
422.03	Reinforced Bridge Approach Fills - Type A Alternate Approach Fill For Integral Abutment
DIVISION 5 - SUBGRADE, BASES AND SHOULDERS	
560.01	Method of Shoulder Construction - High Side of Superelevated Curve - Method I
DIVISION 8 - INCIDENTALS	
815.02	Subsurface Drain
840.00	Concrete Base Pad for Drainage Structures
840.25	Anchorage for Frames - Brick or Concrete or Precast
840.29	Frames and Narrow Slot Flow Grates
840.35	Traffic Bearing Grated Drop Inlet - for Cast iron Double Frame and Grates
840.46	Traffic Bearing Precast Drainage Structure
840.66	Drainage Structure Steps
846.01	Concrete Curb, Gutter and Curb & Gutter
846.04	Drop Inlet Installation in Shoulder Berm Gutter
848.02	Driveway Turnout - Radius Type
862.01	Guardrail Placement
862.02	Guardrail Installation
862.03	Structure Anchor Units
862.04	Anchoring End of Guardrail - B-77 and B-83 Anchor Units
876.01	Rip Rap in Channels
876.02	Guide for Riprap in Channels

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

STATE OF NORTH CAROLINA, DIVISION OF HIGHWAYS

CONVENTIONAL PLAN SHEET SYMBOLS

12/2/2016

Note: Not to Scale

BOUNDARIES AND PROPERTY:

State Line	-----
County Line	-----
Township Line	-----
City Line	-----
Reservation Line	-----
Property Line	-----
Existing Iron Pin (EIP)	○
Computed Property Corner	×
Existing Concrete Monument (ECM)	□
Parcel/Sequence Number	(123)
Existing Fence Line	-x-x-x-
Proposed Woven Wire Fence	○
Proposed Chain Link Fence	□
Proposed Barbed Wire Fence	◇
Existing Wetland Boundary	-WLB-
Proposed Wetland Boundary	-WLB-
Existing Endangered Animal Boundary	-EAB-
Existing Endangered Plant Boundary	-EPB-
Existing Historic Property Boundary	-HPB-
Known Contamination Area: Soil	-S-S-
Potential Contamination Area: Soil	-S-S-
Known Contamination Area: Water	-W-W-
Potential Contamination Area: Water	-W-W-
Contaminated Site: Known or Potential	☠ ?

BUILDINGS AND OTHER CULTURE:

Gas Pump Vent or U/G Tank Cap	○
Sign	○
Well	○
Small Mine	×
Foundation	□
Area Outline	□
Cemetery	□
Building	□
School	□
Church	□
Dam	□

HYDROLOGY:

Stream or Body of Water	-----
Hydro, Pool or Reservoir	-----
Jurisdictional Stream	-JS-
Buffer Zone 1	-BZ 1-
Buffer Zone 2	-BZ 2-
Flow Arrow	←
Disappearing Stream	→
Spring	○
Wetland	▽
Proposed Lateral, Tail, Head Ditch	-----
False Sump	▽

RAILROADS:

Standard Gauge	-----
RR Signal Milepost	○
Switch	□
RR Abandoned	-----
RR Dismantled	-----

RIGHT OF WAY & PROJECT CONTROL:

Primary Horiz Control Point	○
Primary Horiz and Vert Control Point	●
Secondary Horiz and Vert Control Point	◆
Vertical Benchmark	⊕
Existing Right of Way Monument	△
Proposed Right of Way Monument (Rebar and Cap)	▲
Proposed Right of Way Monument (Concrete)	⊙
Existing Permanent Easement Monument	◇
Proposed Permanent Easement Monument (Rebar and Cap)	◆
Existing C/A Monument	△
Proposed C/A Monument (Rebar and Cap)	▲
Proposed C/A Monument (Concrete)	⊙
Existing Right of Way Line	-----
Proposed Right of Way Line	-----
Existing Control of Access Line	-----
Proposed Control of Access Line	-----
Proposed ROW and CA Line	-----
Existing Easement Line	-----
Proposed Temporary Construction Easement	-----
Proposed Temporary Drainage Easement	-----
Proposed Permanent Drainage Easement	-----
Proposed Permanent Drainage/Utility Easement	-----
Proposed Permanent Utility Easement	-----
Proposed Temporary Utility Easement	-----
Proposed Aerial Utility Easement	-----

ROADS AND RELATED FEATURES:

Existing Edge of Pavement	-----
Existing Curb	-----
Proposed Slope Stakes Cut	-C-
Proposed Slope Stakes Fill	-F-
Proposed Curb Ramp	-----
Existing Metal Guardrail	-----
Proposed Guardrail	-----
Existing Cable Guiderail	-----
Proposed Cable Guiderail	-----
Equality Symbol	⊕
Pavement Removal	-----
VEGETATION:	
Single Tree	○
Single Shrub	○
Hedge	-----

Woods Line	-----
Orchard	-----
Vineyard	-----

EXISTING STRUCTURES:

MAJOR:	
Bridge, Tunnel or Box Culvert	-----
Bridge Wing Wall, Head Wall and End Wall	-----
MINOR:	
Head and End Wall	-----
Pipe Culvert	-----
Footbridge	-----
Drainage Box: Catch Basin, DI or JB	-----
Paved Ditch Gutter	-----
Storm Sewer Manhole	-----
Storm Sewer	-----

UTILITIES:

* SUE - Subsurface Utility Engineering
LOS - Level of Service - A, B, C or D (Accuracy)

POWER:	
Existing Power Pole	●
Proposed Power Pole	○
Existing Joint Use Pole	●
Proposed Joint Use Pole	○
Power Manhole	⊕
Power Line Tower	⊕
Power Transformer	⊕
U/G Power Cable Hand Hole	⊕
H-Frame Pole	●
U/G Power Line Test Hole (SUE - LOS A)*	⊕
U/G Power Line (SUE - LOS B)*	-----
U/G Power Line (SUE - LOS C)*	-----
U/G Power Line (SUE - LOS D)*	-----

TELEPHONE:

Existing Telephone Pole	●
Proposed Telephone Pole	○
Telephone Manhole	⊕
Telephone Pedestal	⊕
Telephone Cell Tower	⊕
U/G Telephone Cable Hand Hole	⊕
U/G Telephone Test Hole (SUE - LOS A)*	⊕
U/G Telephone Cable (SUE - LOS B)*	-----
U/G Telephone Cable (SUE - LOS C)*	-----
U/G Telephone Cable (SUE - LOS D)*	-----
U/G Telephone Conduit (SUE - LOS B)*	-----
U/G Telephone Conduit (SUE - LOS C)*	-----
U/G Telephone Conduit (SUE - LOS D)*	-----
U/G Fiber Optics Cable (SUE - LOS B)*	-----
U/G Fiber Optics Cable (SUE - LOS C)*	-----
U/G Fiber Optics Cable (SUE - LOS D)*	-----

WATER:

Water Manhole	⊕
Water Meter	○
Water Valve	⊗
Water Hydrant	⊕
U/G Water Line Test Hole (SUE - LOS A)*	⊕
U/G Water Line (SUE - LOS B)*	-----
U/G Water Line (SUE - LOS C)*	-----
U/G Water Line (SUE - LOS D)*	-----
Above Ground Water Line	-----

TV:

TV Pedestal	⊕
TV Tower	⊗
U/G TV Cable Hand Hole	⊕
U/G TV Test Hole (SUE - LOS A)*	⊕
U/G TV Cable (SUE - LOS B)*	-----
U/G TV Cable (SUE - LOS C)*	-----
U/G TV Cable (SUE - LOS D)*	-----
U/G Fiber Optic Cable (SUE - LOS B)*	-----
U/G Fiber Optic Cable (SUE - LOS C)*	-----
U/G Fiber Optic Cable (SUE - LOS D)*	-----

GAS:

Gas Valve	◇
Gas Meter	⊕
U/G Gas Line Test Hole (SUE - LOS A)*	⊕
U/G Gas Line (SUE - LOS B)*	-----
U/G Gas Line (SUE - LOS C)*	-----
U/G Gas Line (SUE - LOS D)*	-----
Above Ground Gas Line	-----

SANITARY SEWER:

Sanitary Sewer Manhole	⊕
Sanitary Sewer Cleanout	⊕
U/G Sanitary Sewer Line	-----
Above Ground Sanitary Sewer	-----
SS Force Main Line Test Hole (SUE - LOS A)*	⊕
SS Force Main Line (SUE - LOS B)*	-----
SS Force Main Line (SUE - LOS C)*	-----
SS Force Main Line (SUE - LOS D)*	-----


MISCELLANEOUS:

Utility Pole	●
Utility Pole with Base	□
Utility Located Object	○
Utility Traffic Signal Box	⊕
Utility Unknown U/G Line (SUE - LOS B)*	-----
U/G Tank; Water, Gas, Oil	-----
Underground Storage Tank, Approx. Loc.	-----
A/G Tank; Water, Gas, Oil	-----
Geoenvironmental Boring	⊕
Abandoned According to Utility Records	AATUR
End of Information	E.O.I.


6/2/2019

FINAL PAVEMENT SCHEDULE
ALL PAVEMENT EDGE SLOPES ARE 1:1 UNLESS OTHERWISE NOTED.

C1	PROP. APPROX. 3" ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 168.0 LBS. PER SQ. YD. IN EACH OF TWO LAYERS.
C2	PROP. VAR. DEPTH ASPHALT CONCRETE SURFACE COURSE, TYPE S9.5C, AT AN AVERAGE RATE OF 112 LBS. PER SQ. YD. PER 1" DEPTH TO BE PLACED IN LAYERS NOT TO EXCEED 2.0" IN DEPTH.
D1	PROP. APPROX. 4" ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 456 LBS. PER SQ. YD.
D2	PROP. VAR. DEPTH ASPHALT CONCRETE INTERMEDIATE COURSE, TYPE I19.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 2 1/2" IN DEPTH OR GREATER THAN 4" IN DEPTH.
E1	PROP. APPROX. 5" ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 570 LBS. PER SQ. YD.
E2	PROP. VAR. DEPTH ASPHALT CONCRETE BASE COURSE, TYPE B25.0C, AT AN AVERAGE RATE OF 114 LBS. PER SQ. YD. PER 1" DEPTH TO BE PLACED IN LAYERS NOT LESS THAN 3" IN DEPTH OR GREATER THAN 5 1/2" IN DEPTH.
J1	PROP. 6" AGGREGATE BASE COURSE.
P	PRIME COAT. (APPLY THE PRIME COAT AT A RATE OF .35 GAL/SY)
R1	SHOULDER BERM GUTTER.
T	EARTH MATERIAL.
U	EXISTING PAVEMENT.
W	VARIABLE DEPTH ASPHALT PAVEMENT (SEE DETAIL SHOWING METHOD OF WEDGING).




USE WITH TYPICAL 1 OR 2 WHERE SHOULDER BERM GUTTER IS REQUIRED
-L- STA. 19+85.00 TO 19+95.68 LT
-L- STA. 19+85.00 TO 19+95.68 RT




USE WITH TYPICAL 3 WHERE SHOULDER BERM GUTTER IS REQUIRED
-DET- 19+70.00 TO 19+80.60 RT

DETAIL SHOWING SHOULDER BERM GUTTER (SBG) ON TOP OF SUBGRADE




Detail Showing Method of Wedging




INCIDENTAL MILLING DETAIL

MILL 0" TO 1.5" AS DIRECTED BY THE ENGINEER (50 LF PER 1" OF DEPTH)
TEMPORARY ASPHALT WEDGING AS DIRECTED BY THE ENGINEER
* MILL DEPTH AS SHOWN ON PLANS OR AS DIRECTED BY THE ENGINEER
** SEE TYPICALS FOR MIX TYPE




ROADWAY TYPICAL SECTION NO. 1

ROADWAY TYPICAL SECTION NO. 1
-L- STA. 15+00.00 TO STA. 17+18.00
-L- STA. 28+14.00 TO STA. 30+05.22




ROADWAY TYPICAL SECTION NO. 2

ROADWAY TYPICAL SECTION NO. 2
-L- STA. 17+18.00 TO STA. 20+09.85 (BEGIN BRIDGE)
-L- STA. 23+60.35 (END BRIDGE) TO STA. 28+14.00




ROADWAY TYPICAL SECTION NO. 3

ROADWAY TYPICAL SECTION NO. 3
-DET- STA. 16+83.99 TO STA. 20+40.09 (BEGIN BRIDGE)
-DET- STA. 21+35.09 (END BRIDGE) TO STA. 28+52.00




ROADWAY TYPICAL SECTION NO. 4


ROADWAY TYPICAL SECTION NO. 4
-DET- STA. 15+00.00 TO STA. 16+83.99
-DET- STA. 28+52.00 TO STA. 30+20.00



INSET A
USE IN GUARDRAIL LOCATIONS




INSET B
USE IN GUARDRAIL LOCATIONS






BRIDGE TYPICAL SECTION

BRIDGE TYPICAL SECTION
-L- STA. 20+09.85 TO STA. 23+60.35










BRIDGE TYPICAL SECTION

BRIDGE TYPICAL SECTION
-DET- STA. 20+40.09 TO STA. 21+35.09

PROJECT REFERENCE NO. B-5694	SHEET NO. 2A-1
ROADWAY DESIGN ENGINEER  BRIAN E. HOLSINGER 036853 4/4/2022	PAVEMENT DESIGN ENGINEER  CLARK S. MORRISON 022896 4/4/2022
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
 KCI Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609 Phone (919) 783-9214 • Fax (919) 783-9266	

01-APR-2022 07:48
M:\2018\18-0015\18-0015-12 B-5694-Roadway\Proj\B-5694-Rdwy_tjpc.dgn











POST	THICKNESS	BOLT LENGTH
①	4 1/4"	9"
②	3 1/4"	5" *
③	2"	6"
④	1"	3" *

* BOLTS FOR POSTS 2 AND 4 ARE USED TO ATTACH BLOCK TO POST. RUBRAIL NOT ATTACHED TO BLOCK.

**DETAIL C
RUBRAIL BLOCKOUT**

- GENERAL NOTES:**
- POSTS 1 THROUGH 5 REQUIRE AN ADDITIONAL HOLE TO ATTACH LOWER BLOCKOUTS AND/OR RUBRAIL.
 - RUBRAIL BLOCKOUTS LOCATED ON POSTS 1 THROUGH 4 ARE OFFSET DRILLED AND SECURED WITH 5/8" BUTTONHEAD BOLTS (SEE CHART FOR BOLT LENGTHS). SECURE BLOCKS ONLY TO POSTS 2 AND 4. SECURE RUBRAIL AND BLOCKOUTS TO POSTS 1 AND 3. RUBRAIL IS SECURED TO POST 5 WITH A 5/8" x 4 1/2" BUTTONHEAD BOLT. RUBRAIL IS FLARED TO BACK OF POST 6 AND NOT SECURED.
 - STEEL SPACER TUBE IS A SCHEDULE 40 GALVANIZED PIPE 6" INSIDE DIAMETER x 9" LONG. ATTACH TUBE TO GUARDRAIL ONLY WITH 5/8" x 1 1/4" LONG BUTTONHEAD BOLT AND RECTANGULAR PLATE WASHER.
 - SEE DETAIL D FOR SLOPED RUBRAIL BLOCKOUT. BLOCKOUT IS ATTACHED TO RAIL ELEMENT ONLY. USE 3/8" x 3" LAG BOLT WITH FLAT WASHER.
 - SHOP FABRICATE THE C6 x 8.2 RUBRAIL END TO BE CONSISTENT WITH THE SLOPE OF THE JERSEY SHAPE AND ATTACH FLUSH WITH THE SLOPED TOE OF THE BARRIER OR BRIDGE RAIL.
 - ANCHORAGE:
 - AT PORTABLE CONCRETE BARRIER, ANCHOR RUBRAIL USING THREE 5/8" x 6" CHEMICALLY ANCHORED BOLTS WITH WASHERS.
 - AT PORTABLE CONCRETE BARRIER, ANCHOR THE W-BEAM END SHOE USING A 4 BOLT HOLD-DOWN PLATE AS SHOWN. INSTALL THE W-BEAM END SHOE BEHIND THE NESTED W-BEAM ELEMENTS.
 - POSTS 1 AND 2 ARE W8 x 13, 7'-6" LONG. ALL OTHER POSTS IN THE ANCHOR UNIT ARE W6 x 8.5.

- NOTES FOR 4 BOLT HOLD DOWN PLATE**
- THE GUARDRAIL ANCHOR ASSEMBLY SHALL CONSIST OF A 1/4" HOLD DOWN PLATE AND 4 - 7/8" DIA. BOLTS WITH NUTS AND WASHERS.
 - THE HOLD-DOWN PLATE SHALL CONFORM TO AASHTO M270 GRADE 36. AFTER FABRICATION, THE HOLD-DOWN PLATE SHALL BE HOT-DIP GALVANIZED IN ACCORDANCE WITH AASHTO M111.
 - AFTER INSTALLATION, THE EXPOSED THREAD OF THE BOLT SHALL BE BURRED WITH A SHARP POINTED TOOL. THE 1/4" DIA. HOLES SHALL BE FORMED OR DRILLED WITH A CORE BIT. IMPACT TOOLS WILL NOT BE PERMITTED. ANY CONCRETE DAMAGED BY THIS WORK SHALL BE REPAIRED TO THE SATISFACTION OF THE ENGINEER.



4/4/2022

CONTRACT STANDARDS AND DEVELOPMENT UNIT
Office 919-707-6950 FAX 919-250-4119

TEMPORARY GUARDRAIL ANCHOR UNIT TYPE B-77

ORIGINAL BY: E.E. WARD DATE: 04-07-04
 MODIFIED BY: J.S. Howerton DATE: 10-02-18
 CHECKED BY: _____ DATE: _____
 FILE SPEC.: _____


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

02-OCT-2018 14:39 S:\Contracts\Contractors\Special Details\Howerton\Temporary B-77 to PCB.dgn Jhowerton AT CSD-292595


STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ROADWAY DETAIL DRAWING FOR
GUARDRAIL INSTALLATION


SHEET 6 OF 8
862D02



STANDARD W-BEAM GUARDRAIL




PLAN




WOOD OFFSET BLOCK
(FOR WOOD POSTS)

STANDARD LINE POST

SHORT WOOD BREAKAWAY POST




STEEL TUBE
TS 6"x8"x0.1875"



SIDE

FRONT

ROUTED OFFSET BLOCK



SIDE

FRONT

"W6" STEEL POST

SYSTEM PARTS

STATE OF NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

ROADWAY DETAIL DRAWING FOR
GUARDRAIL INSTALLATION

SHEET 6 OF 8
862D02



4/4/2022

CONTRACTS STANDARDS AND DEVELOPMENT UNIT
Office 919-707-6950 FAX 919-250-4119

SEE TITLE BLOCK

ORIGINAL BY: J. HOWERTON DATE: 3-7-2018
MODIFIED BY: DATE: _____
CHECKED BY: DATE: _____
FILE SPEC.: _____


GROUNDWATER CONDITION (SEE NOTE 6)	H SHORING HEIGHT (FT)	SLOPE OR SURCHARGE CASE WITH NO TRAFFIC IMPACT					SURCHARGE CASE WITH TRAFFIC IMPACT				
		SHEET PILES		H-PILES WITH TIMBER LAGGING			SHEET PILES		H-PILES WITH TIMBER LAGGING		
		MINIMUM REQUIRED EMBEDMENT (FT)	MINIMUM REQUIRED SECTION MODULUS (IN ³ /FT)	MINIMUM REQUIRED EMBEDMENT* (FT) (SEE NOTE 10)			MINIMUM REQUIRED EMBEDMENT (FT)	MINIMUM REQUIRED SECTION MODULUS (IN ³ /FT)	MINIMUM REQUIRED EMBEDMENT* (FT) (SEE NOTE 10)		
				HP 10x42	HP 12x53	HP 14x73			HP 10x42	HP 12x53	HP 14x73
GROUNDWATER ELEVATION BETWEEN BOTTOM OF SHORING AND PILE TIP	< 6	11.5	4.5	11.5	11.5	11.5	16.0	12.0	13.0	13.0	13.0
	7	13.0	7.0	13.0	13.0	13.0	17.0	14.5	14.5	14.5	14.5
	8	15.0	10.0	--	15.0	15.0	18.0	17.0	--	15.5	15.5
	9	17.0	14.0	--	17.0	17.0	19.0	20.0	--	17.0	17.0
	10	18.5	19.5	--	--	18.5	20.0	23.5	--	--	18.5
	11	20.5	26.0	--	--	--	21.0	28.0	--	--	20.0
GROUNDWATER ELEVATION BELOW PILE TIP	< 6	7.5	3.0	8.0	8.0	8.0	11.0	10.0	9.5	9.5	9.5
	7	8.5	4.5	9.5	9.5	9.5	12.0	12.0	10.5	10.5	10.5
	8	10.0	6.5	10.5	10.5	10.5	12.5	14.0	11.5	11.5	11.5
	9	11.0	9.5	--	12.0	12.0	13.5	16.5	--	12.5	12.5
	10	12.5	13.0	--	--	13.5	14.0	19.5	--	13.5	13.5
	11	13.5	17.0	--	--	14.5	15.0	22.5	--	--	14.5
12	15.0	21.5	--	--	16.0	16.0	25.5	--	--	15.5	

MINIMUM REQUIRED EMBEDMENT AND SECTION MODULUS


*DO NOT USE H-PILES WITH TIMBER LAGGING FOR GROUNDWATER CONDITION, SHORING HEIGHT AND H-PILE SIZE SHOWN IF MINIMUM REQUIRED EMBEDMENT IS "--".

NOTES:


- AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY SHORING AS NOTED IN THE PLANS.
- FOR STANDARD TEMPORARY SHORING, SEE STANDARD SHORING PROVISION.
- STANDARD TEMPORARY SHORING IS BASED ON THE FOLLOWING IN-SITU ASSUMED SOIL PARAMETERS:
UNIT WEIGHT, $\gamma = 120$ PCF
FRICTION ANGLE, $\phi = 30$ DEGREES
COHESION, $c = 0$ PSF
- DO NOT USE STANDARD TEMPORARY SHORING IF ASSUMED SOIL PARAMETERS ARE NOT APPLICABLE.
- DO NOT USE STANDARD TEMPORARY SHORING WHEN VERY LOOSE OR SOFT SOIL OR MUCK IS WITHIN THE EMBEDMENT DEPTH.
- USE GROUNDWATER ELEVATION NOTED IN THE PLANS. IF NO GROUNDWATER ELEVATION IS SHOWN IN THE PLANS, USE "GROUNDWATER ELEVATION BETWEEN BOTTOM OF SHORING AND PILE TIP" FOR GROUNDWATER CONDITION. DO NOT USE STANDARD TEMPORARY SHORING IF GROUNDWATER IS ABOVE BOTTOM OF SHORING.
- AT THE CONTRACTOR'S OPTION OR IF AVAILABLE CLEAR DISTANCE IS LESS THAN THE MINIMUM REQUIRED FOR CONCRETE BARRIER, SET BARRIER NEXT TO AND UP AGAINST TRAFFIC SIDE OF PILES AND USE "SURCHARGE CASE WITH TRAFFIC IMPACT".
- AT THE CONTRACTOR'S OPTION OR IF AVAILABLE CLEAR DISTANCE IS LESS THAN 4' FOR TEMPORARY GUARDRAIL, ATTACH GUARDRAIL TO TRAFFIC SIDE OF PILES AS SHOWN IN THE PLANS AND USE "SURCHARGE CASE WITH TRAFFIC IMPACT".
- MINIMUM REQUIRED EXTENSION IS 6' FOR "SLOPE OR SURCHARGE CASE WITH NO TRAFFIC IMPACT" AND 32' FOR "SURCHARGE CASE WITH TRAFFIC IMPACT".
- MINIMUM REQUIRED EMBEDMENT FOR H-PILES WITH TIMBER LAGGING IS BASED ON DRIVEN H-PILES AT MAXIMUM 6' SPACING. AT THE CONTRACTOR'S OPTION, EMBEDMENT DEPTHS MAY BE REDUCED BY 25% FOR DRILLED-IN H-PILES.
- SUBMIT A "STANDARD TEMPORARY SHORING SELECTION FORM" AT LEAST 7 DAYS BEFORE STARTING TEMPORARY SHORING CONSTRUCTION. UP TO 3 SHORING LOCATIONS MAY BE INCLUDED ON EACH FORM. STANDARD SHORING SELECTION FORMS ARE AVAILABLE FROM:
connect.ncdot.gov/resources/Geological/Pages/Geotech_Forms_Details.aspx
- CONTACT THE ENGINEER IF PILES DO NOT ATTAIN THE MINIMUM REQUIRED EMBEDMENT.



CONCRETE BARRIER
**TOP OF SHORING =
EDGE OF PAVEMENT




TEMPORARY GUARDRAIL
**GUARDRAIL FACE =
EDGE OF PAVEMENT



STANDARD TEMPORARY SHORING
(SLOPE CASE)
*SEE TABLE ABOVE.

STANDARD TEMPORARY SHORING
(SURCHARGE CASE)
*SEE TABLE ABOVE.



NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

**GEOTECHNICAL
ENGINEERING UNIT**

STANDARD DETAIL NO. 1801.01

STANDARD
TEMPORARY SHORING

12-3700BHZ

COMPUTED BY: SAW DATE: 6/13/2019
CHECKED BY: LMY DATE: 6/13/2019

PROJECT NO. B-5694 SHEET NO. 3D-1

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS

Note: Invert Elevations indicated are for Bid Purposes only and shall not be used for project construction stakeout.
See "Standard Specifications For Roads and Structures, Section 300-5".

LIST OF PIPES, ENDWALLS, ETC. (FOR PIPES 48 INCHES & UNDER)

Main data table with columns: LINE & STATION, OFFSET, STRUCTURE NUMBER, TOP ELEVATION, INVERT ELEVATION, MINIMUM REQUIRED SLOPE, QUANTITIES FOR DRAINAGE STRUCTURES, and various material codes.

ABBREVIATIONS table listing codes like C.A.A., C.B., C.S., D.I., G.D.I., H.D.P.E., J.B., M.H., N.S., P.V.C., R.C., T.B.D.I., T.B.J.B., W.S. and their corresponding material names.

SHEET TOTALS and PROJECT TOTALS summary rows at the bottom of the table.

COMPUTED BY: Tyler C. Bottoms DATE: 6/11/19
 CHECKED BY: Jinyoung Park DATE: 7/11/19

(5-15-18)

PROJECT NO.	SHEET NO.
B-5694	3G-1




**STATE OF NORTH CAROLINA
 DIVISION OF HIGHWAYS**

SUMMARY OF SUBSURFACE DRAINAGE


LINE	Station	Station	Location LT/RT/CL	Drain Type* UD/BD/SD	LF
				SD	200
				TOTAL LF:	200

*UD = Underdrain
 *BD = Blind Drain
 *SD = Subsurface Drain







8/17/99

PROJECT REFERENCE NO. B-5694		SHEET NO. 4	
ROADWAY DESIGN ENGINEER		HYDRAULICS ENGINEER	
 036853 BRYAN E. HORD 4/4/2022		 033860 KCI 4/4/2022	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED			
 KCI <small>Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609 Phone (919) 783-9214 • Fax (919) 783-9266</small>			

REVISIONS



MATCH LINE STA. 24+00.0 - SEE SHEET 5



FOR -L- PROFILE SEE SHEET 8
FOR DETOUR SEE SHEETS 6/7
FOR STRUCTURES SEE SHEETS S-1 TO S-37


23-MAR-2022 13:18
M:\2018\180194512 B-5694\Roadway\Proj\B-5694_Rdy_pah.dgn
BRYAN E. HORD

8/17/99



REVISIONS

08-FEB-2022 14:00
MS-DWG
B-5694-Roadway\Proj\B-5694-Rdy_psh_1.dgn
\$\$\$\$\$

MATCH LINE STA. 24+00.0 - SEE SHEET 4



END CONSTRUCTION
 -DET- STA. 30+20.00
 = -L- STA. 30+05.22




PROJECT REFERENCE NO. B-5694	SHEET NO. 5
RW SHEET NO.	
ROADWAY DESIGN ENGINEER BRYAN E. HOGAN 036653 4/4/2022	HYDRAULICS ENGINEER LEAH M. YOUNG 033860 4/4/2022
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
KCI Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609 Phone (919) 783-9214 • Fax (919) 783-9266	

FOR -L- PROFILE SEE SHEET 8
 FOR DETOUR SEE SHEETS 6/7

-DET-

PI Sta 16+06.52 Δ = 18° 36' 49.2" (LT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 132' DS = 45 MPH	PI Sta 18+17.69 Δ = 18° 36' 49.2" (RT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 120' DS = 45 MPH	PI Sta 27+18.97 Δ = 18° 36' 49.2" (RT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 120' DS = 45 MPH	PI Sta 29+30.14 Δ = 18° 36' 49.2" (LT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 132' DS = 45 MPH
--	--	--	--






PROJECT REFERENCE NO. B-5694	SHEET NO. 6
ROADWAY DESIGN ENGINEER 	HYDRAULICS ENGINEER
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
KCI Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609 Phone (919) 783-9214 • Fax (919) 783-9266	



BEGIN CONSTRUCTION
-DET- STA. 15+00.00
= -L- STA. 15+00.00

BEGIN BRIDGE
-DET- STA. 20+40.09

END BRIDGE
-DET- STA. 21+35.09



FOR -DET- PROFILE SEE SHEET 9
FOR -L- SEE SHEETS 4/5
FOR STRUCTURES SEE SHEETS S-1 TO S-37

REVISIONS


MATCH LINE STA. 23+00.00 - SEE SHEET 7

11-MAY-2022 10:14
 M:\2018\5694\Roadway\Proj\B-5694_Rdy_det.psh.dgn
 8/17/99

8/17/99

-DET-

PI Sta 16+06.52 Δ = 18° 36' 49.2" (LT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 132' DS = 45 MPH	PI Sta 18+17.69 Δ = 18° 36' 49.2" (RT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 120' DS = 45 MPH	PI Sta 27+18.97 Δ = 18° 36' 49.2" (RT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 120' DS = 45 MPH	PI Sta 29+30.14 Δ = 18° 36' 49.2" (LT) D = 8' 48' 53.0" L = 211.7' T = 106.52' R = 650.00' e = .06 RO = 132' DS = 45 MPH
--	--	--	--






PROJECT REFERENCE NO. B-5694	SHEET NO. 7
ROADWAY DESIGN ENGINEER BRYAN E. HODGINS Professional Engineer No. 036853 4/4/2022	HYDRAULICS ENGINEER Professional Engineer No. 033860 4/4/2022
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
 <small>Engineers • Planners • Scientists • Construction Managers 4505 Falls of Neuse Road, Suite 400 Raleigh, NC 27609 Phone (919) 783-9214 • Fax (919) 783-9266</small>	

REVISIONS

MATCH LINE STA. 23+00.00 - SEE SHEET 6



END CONSTRUCTION
-DET- STA. 30+20.00
-L- STA. 30+05.22



FOR -DET- PROFILE SEE SHEET 9
FOR -L- SEE SHEETS 4/5

23-MAR-2022 13:17
 M:\2018\1801945\12 B-5694\Roadway\Proj\B-5694_Rdy_det.psh.1.dgn
 USER:BAW

5/28/2022

PROJECT REFERENCE NO. B-5694	SHEET NO. 8
ROADWAY DESIGN ENGINEER 	HYDRAULICS ENGINEER 
4/4/2022	4/4/2022



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

BM #1 - WOODED AREA
-L- STA. 16+00.71, 95.36' RT
EL = 18.15'

BRIDGE HYDRAULIC DATA

DESIGN DISCHARGE	= 950	CFS
DESIGN FREQUENCY	= 50	YRS
DESIGN HW ELEVATION	= 12.8	FT
BASE DISCHARGE	= 1200	CFS
BASE FREQUENCY	= 100	YRS
BASE HW ELEVATION	= 13.7	FT
OVERTOPPING DISCHARGE	= 17000	CFS
OVERTOPPING FREQUENCY	= >500+	YRS
OVERTOPPING ELEVATION	= 22.8	FT



DATE OF SURVEY	= 08/16/2017
W.S. ELEVATION AT DATE OF SURVEY	= 5.3 FT



FOR -L- ALIGNMENT SEE SHEETS 4/5

D:\FEB-2022\1406\12 B-5694\Roadway\Proj\B-5694_Rdy_pfl_psh.dgn

5/28/24



PROJECT REFERENCE NO. B-5694	SHEET NO. 9
ROADWAY DESIGN ENGINEER 	HYDRAULICS ENGINEER 
4/4/2022	4/4/2022

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

-DET-

BM #1 - WOODED AREA
 -L- STA. 16+00.71, 95.36' RT
 EL = 18.15'

DETOUR BRIDGE HYDRAULIC DATA		
DESIGN DISCHARGE	= 550	CFS
DESIGN FREQUENCY	= 10	YRS
DESIGN HW ELEVATION	= 10.8	FT
BASE DISCHARGE	= 1200	CFS
BASE FREQUENCY	= 100	YRS
BASE HW ELEVATION	= 13.8	FT
OVERTOPPING DISCHARGE	= 17000	CFS
OVERTOPPING FREQUENCY	= >500+	YRS
OVERTOPPING ELEVATION	= 24.7	FT
DATE OF SURVEY	= 08/16/2017	
W.S. ELEVATION AT DATE OF SURVEY	= 5.3	FT



FOR -DET- ALIGNMENT SEE SHEETS 6/7

D:\FEB-2022\1407... B-5694\Roadway\Proj\B-5694_Rdy_det.plt.psh.dgn