

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**

09_205/299

TIP PROJECT: R-5819/R-5820

CONTRACT:


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

COLUMBUS COUNTY

**LOCATION: SR 1740 (OLD LAKE ROAD) CONVERT AT-GRADE INTERSECTION TO GRADE SEPARATION (R-5819)
SR 1735 (CHAUNCEY TOWN ROAD) CONVERT AT-GRADE INTERSECTION TO INTERCHANGE (R-5820)**



TYPE OF WORK: WET UTILITY PLANS

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	R-5819/R-5820	UC-1	
STATE WBS NO.	F.A. PROJ. NO.	DESCRIPTION	
47091.1.147092.1.1		PE	



BEGIN TIP PROJECT R-5819/R-5820
-LWB- POC STA. 18+50.00
-LEB- POC STA. 18+50.00

END TIP PROJECT R-5819/R-5820
-L- POC STA. 105+30.00



INDEX OF SHEETS

UC-1	TITLE SHEET
UC-2 TO UC-5	PLAN & PROFILE SHEETS
UC-DT1 TO UC-DT2	DETAIL SHEETS

PROJECT LENGTH

LENGTH OF 2" WATERLINE	= 26 FT.
LENGTH OF 6" WATERLINE	= 1790 FT.
LENGTH OF 8" WATERLINE	= 712 FT.
TOTAL LENGTH OF WATERLINE	= 2528 FT.
LENGTH OF 6" FORCEMAIN	= 28 FT.
LENGTH OF 8" FORCEMAIN	= 1760 FT.
LENGTH OF 10" FORCEMAIN	= 600 FT.
TOTAL LENGTH OF FORCEMAIN	= 2388 FT.

Prepared in the Office of:
VHB Engineering NC, P.C. (C-3705)
940 Main Campus Drive, Suite 500
Raleigh, NC 27606

FOR THE NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
2018 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: MARCH 31, 2021

LETTING DATE: JUNE 21, 2022

NCDOT CONTACT:

BRANDON BARHAM, PE
PROJECT MANAGER

JOHN M. KAMPRATH, PE
PROJECT DESIGN ENGINEER

ALEX HENDERSON
NCDOT PROJECT MANAGER

UTILITIES ENGINEER

DocuSigned by:
John M. Kamprath
-SIGNATURE-

P.E. 4/12/2022



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Tuesday, April 12, 2022 ANSI A (8.50 X 11.00 Inches)


LEGEND

	EX. WATERLINE TO REMAIN
	EX. WATERLINE TO BE REMOVED/ABANDONED
	PROPOSED WATERLINE
	EX. SANITARY FORCEMAIN TO REMAIN
	EX. SANITARY FORCEMAIN TO BE REMOVED/ABANDONED
	PROPOSED 8" C900 FORCEMAIN

- ### NOTES KEYED TO PLAN
- RELOCATE EX. FIRE HYDRANT ASSEMBLY.
 - INSTALL RELOCATED FIRE HYDRANT ASSEMBLY AND CONNECT TO MAIN WITH 6" X 6" TEE.

- ### Notes
- ALL WORK ASSOCIATED WITH THE RELOCATION OF WATERMAINS OR SANITARY SEWER FORCEMAINS SHALL BE COMPLETED AS PER THE NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES, LATEST EDITION, SUPPLEMENTED (AS REQUIRED) WITH THE FACILITIES OWNER STANDARD SPECIFICATIONS AS DESCRIBED IN THE PROJECT SPECIFIC SPECIAL PROVISIONS.
 - ALL MAINS SHALL BE INSTALLED WITH A MINIMUM OF 36 INCHES OF COVER.
 - WATER MAINS SHALL BE AT LEAST 10 FEET LATERALLY FROM EXISTING OR PROPOSED SEWERS. WHERE LOCAL CONDITIONS PREVENT A SEPARATION OF 10 FEET, THE WATER MAIN MAY BE LAID CLOSER, PROVIDED THAT THE ELEVATION OF THE BOTTOM OF THE WATER MAIN IS AT LEAST 18 INCHES ABOVE THE TOP OF THE SEWER WITH A HORIZONTAL SEPARATION OF AT LEAST 3 FEET.
 - WATER MAINS SHALL MAINTAIN A MINIMUM 24" HORIZONTAL AND 18" VERTICAL SEPARATION BETWEEN THE WATER MAIN AND STORM SEWER OR OTHER DRY UTILITIES.
 - WHEN A PROPOSED WATER MAIN CROSSES UNDER A PROPOSED OR EXISTING SANITARY SEWER, CONSTRUCT BOTH THE WATER MAIN AND THE SEWER OF FERROUS MATERIALS WITH JOINTS THAT ARE EQUIVALENT TO WATER MAIN STANDARDS FOR A DISTANCE OF 10 FEET ON EACH SIDE OF THE POINT OF CROSSING. CENTER THE SECTION OF WATER PIPE AT THE POINT OF CROSSING.
 - VERIFY ALL ILLUSTRATED UTILITY CROSSINGS PRIOR TO CONSTRUCTION AND NOTIFY THE ENGINEER IF CONFLICTS ARE ENCOUNTERED.
 - CONTRACTOR SHALL COORDINATE UTILITY RELOCATION OR ABANDONMENT WITH LOCAL UTILITY COMPANIES AS REQUIRED.
 - ALL CONNECTIONS TO EXISTING WATER MAINS OR FORCE MAINS TO BE MADE WITH THRUST COLLAR AS PER THE DETAIL OF THESE PLANS.
 - CONTRACTOR SHALL PROVIDE A VACUUM TRUCK ON-SITE TO CLEAN UP WASTEWATER SPILLAGE DURING CONNECTIONS TO EXISTING FORCE MAIN.
 - CONTRACTOR SHALL COORDINATE CONNECTIONS TO EXISTING WATER MAINS AND FORCE MAINS WITH THE UTILITY OWNER SO AS TO MINIMIZE SERVICE INTERRUPTIONS.

GENERAL NOTES:
 1. EX. TOPOGRAPHIC SURVEY AND SUE BY OTHERS. CONTRACTOR TO CONFIRM FINAL CONNECTION POINTS IN FIELD.
 2. EX. WATER MAIN AND FORCE MAIN DEPTHS SHOWN ARE APPROXIMATE BASED ON BEST AVAILABLE INFORMATION. ACTUAL DEPTH IS TO BE CONFIRMED IN FIELD.
 3. EX. WATER MAIN AND FORCE MAIN MATERIALS SHOWN ARE BASED ON BEST AVAILABLE INFORMATION. CONTRACTOR IS RESPONSIBLE TO PROVIDE ADEQUATE PIPE MATERIAL TRANSITION AT ALL CONNECTIONS.








PROJECT REFERENCE NO. R5819/R5820	SHEET NO. UC-2
REVISION NO.	UTILITIES ENGINEER
90% DESIGN - 11/30/21	
100% DESIGN - 3/02/22	
100% DESIGN - 4/11/22	

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared by

 VHB Engineering NC, P.C. (C-3705)
 940 Main Campus Drive, Suite 500
 Raleigh, NC 27606









- PROFILES NOTES:
- MINIMUM COVER OF 36" TO BE MAINTAINED WITH WATER AND SANITARY FORCEMAIN INSTALLATION.
 - A SECTION OF DIP MAIN LINE SHALL BE CENTERED AT EVERY POINT OF CROSSING BELOW STORM SEWER.
 - THRUST COLLARS TO BE INSTALLED AT EVERY DEFLECTION POINT.
 - MAINS SHALL BE INSTALLED WITHOUT INTERMEDIATE HIGH POINTS. WHERE HIGH POINTS CAN NOT BE AVOIDED CONTRACTOR TO COORDINATE WITH UTILITY OWNER FOR AIR RELEASE REQUIREMENTS.
 - PROJECT GEOTECHNICAL ENGINEER TO VERIFY NATIVE OR PLACED SITE SOIL BEARING STRENGTH AND RESISTANCE AT EACH BEND AND TEE LOCATION TO ENSURE CONCRETE THRUST BLOCK MINIMUM DESIGNS AS PER PROJECT SPECIFICATIONS ARE SUFFICIENT. WHERE MAINS ARE PLACED IN FILL ADDITIONAL CONCRETE AND REINFORCEMENT MAY BE WARRANTED.

4/12/2022
 \\vhb.com\gbl\proj\Raleigh\38564.19 NCDOT R5819 R5820 US74\NCDOT\Utilities\Ray_Ut\Proj\Plan Sheets\R5819_UC_PLAN.dwg
 Mark Edwards

Tuesday, April 12, 2022 ANSI A (8.50 X 11.00 Inches)

4/12/2022 \\vhb.com\gbl\proj\Raleigh\38564.19 NCDOT Utilities\Ray_Ut\Proj\Plan Sheets\R5819_UC_PLAN.dwg Mark Edwards



PROJECT REFERENCE NO. R5819/R5820	SHEET NO. UC-3
REVISION NO. 90% DESIGN - 11/30/21 100% DESIGN - 3/02/22	UTILITIES ENGINEER [Signature] SEAL 14101 [Signature]

Vert. 0 5 10 20 Feet
Horiz. 0 25 50 100 Feet

GENERAL NOTES:
1. EX. TOPOGRAPHIC SURVEY AND SUE BY OTHERS. CONTRACTOR TO CONFIRM FINAL CONNECTION POINTS IN FIELD.
2. EX. WATER MAIN AND FORCE MAIN DEPTHS SHOWN ARE APPROXIMATE BASED ON BEST AVAILABLE INFORMATION. ACTUAL DEPTH IS TO BE CONFIRMED IN FIELD.
3. EX. WATER MAIN AND FORCE MAIN MATERIALS SHOWN ARE BASED ON BEST AVAILABLE INFORMATION. CONTRACTOR IS RESPONSIBLE TO PROVIDE ADEQUATE PIPE MATERIAL TRANSITION AT ALL CONNECTIONS.




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

Prepared by
vhb
VHB Engineering NC, P.C. (C-3705)
940 Main Campus Drive, Suite 500
Raleigh, NC 27606

LEGEND

- EX. WATERLINE TO REMAIN
- EX. WATERLINE TO BE REMOVED/ABANDONED
- 6" WL PROPOSED WATERLINE
- EX. SANITARY FORCEMAIN TO REMAIN
- EX. SANITARY FORCEMAIN TO BE REMOVED/ABANDONED
- 8" PVC FM PROPOSED 8" C900 FORCEMAIN

- ### Notes
- ALL WORK ASSOCIATED WITH THE RELOCATION OF WATERMAINS OR SANITARY SEWER FORCEMAINS SHALL BE COMPLETED AS PER THE NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES, LATEST EDITION, SUPPLEMENTED (AS REQUIRED) WITH THE FACILITIES OWNER STANDARD SPECIFICATIONS AS DESCRIBED IN THE PROJECT SPECIFIC SPECIAL PROVISIONS.
 - ALL MAINS SHALL BE INSTALLED WITH A MINIMUM OF 36 INCHES OF COVER.
 - WATER MAINS SHALL BE AT LEAST 10 FEET LATERALLY FROM EXISTING OR PROPOSED SEWERS. WHERE LOCAL CONDITIONS PREVENT A SEPARATION OF 10 FEET, THE WATER MAIN MAY BE LAID CLOSER, PROVIDED THAT THE ELEVATION OF THE BOTTOM OF THE WATER MAIN IS AT LEAST 18 INCHES ABOVE THE TOP OF THE SEWER WITH A HORIZONTAL SEPARATION OF AT LEAST 3 FEET.
 - WATER MAINS SHALL MAINTAIN A MINIMUM 24" HORIZONTAL AND 18" VERTICAL SEPARATION BETWEEN THE WATER MAIN AND STORM SEWER OR OTHER DRY UTILITIES.
 - WHEN A PROPOSED WATER MAIN CROSSES UNDER A PROPOSED OR EXISTING SANITARY SEWER, CONSTRUCT BOTH THE WATER MAIN AND THE SEWER OF FERROUS MATERIALS WITH JOINTS THAT ARE EQUIVALENT TO WATER MAIN STANDARDS FOR A DISTANCE OF 10 FEET ON EACH SIDE OF THE POINT OF CROSSING. CENTER THE SECTION OF WATER PIPE AT THE POINT OF CROSSING.
 - VERIFY ALL ILLUSTRATED UTILITY CROSSINGS PRIOR TO CONSTRUCTION AND NOTIFY THE ENGINEER IF CONFLICTS ARE ENCOUNTERED.
 - CONTRACTOR SHALL COORDINATE UTILITY RELOCATION OR ABANDONMENT WITH LOCAL UTILITY COMPANIES AS REQUIRED.
 - ALL CONNECTIONS TO EXISTING WATER MAINS OR FORCE MAINS TO BE MADE WITH THRUST COLLAR AS PER THE DETAIL OF THESE PLANS.
 - CONTRACTOR SHALL PROVIDE A VACUUM TRUCK ON-SITE TO CLEAN UP WASTEWATER SPILLAGE DURING CONNECTIONS TO EXISTING FORCE MAIN.
 - CONTRACTOR SHALL COORDINATE CONNECTIONS TO EXISTING WATER MAINS AND FORCE MAINS WITH THE UTILITY OWNER SO AS TO MINIMIZE SERVICE INTERRUPTIONS.




- ### PROFILES NOTES:
- MINIMUM COVER OF 36" TO BE MAINTAINED WITH WATER AND SANITARY FORCEMAIN INSTALLATION.
 - A SECTION OF DIP MAIN LINE SHALL BE CENTERED AT EVERY POINT OF CROSSING BELOW STORM SEWER.
 - THRUST COLLARS TO BE INSTALLED AT EVERY DEFLECTION POINT.
 - MAINS SHALL BE INSTALLED WITHOUT INTERMEDIATE HIGH POINTS. WHERE HIGH POINTS CAN NOT BE AVOIDED CONTRACTOR TO COORDINATE WITH UTILITY OWNER FOR AIR RELEASE REQUIREMENTS.
 - PROJECT GEOTECHNICAL ENGINEER TO VERIFY NATIVE OR PLACED SITE SOIL BEARING STRENGTH AND RESISTANCE AT EACH BEND AND THE LOCATION TO ENSURE CONCRETE THRUST BLOCK MINIMUM DESIGNS AS PER PROJECT SPECIFICATIONS ARE SUFFICIENT. WHERE MAINS ARE PLACED IN FILL ADDITIONAL CONCRETE AND REINFORCEMENT MAY BE WARRANTED.



Tuesday, April 12, 2022 ANSI A (8.50 X 11.00 Inches)

LEGEND	
	EX. WATERLINE TO REMAIN
	EX. WATERLINE TO BE REMOVED/ABANDONED
	PROPOSED WATERLINE
	EX. SANITARY FORCEMAIN TO REMAIN
	EX. SANITARY FORCEMAIN TO BE REMOVED/ABANDONED
	PROPOSED 8" PVC FORCEMAIN



- ### Notes
1. ALL WORK ASSOCIATED WITH THE RELOCATION OF WATERMANS OR SANITARY SEWER FORCEMANS SHALL BE COMPLETED AS PER THE NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES, LATEST EDITION, SUPPLEMENTED (AS REQUIRED) WITH THE FACILITIES OWNER STANDARD SPECIFICATIONS AS DESCRIBED IN THE PROJECT SPECIFIC SPECIAL PROVISIONS.
 2. ALL MAINS SHALL BE INSTALLED WITH A MINIMUM OF 36 INCHES OF COVER.
 3. WATER MAINS SHALL BE AT LEAST 10 FEET Laterally FROM EXISTING OR PROPOSED SEWERS, WHERE LOCAL CONDITIONS PREVENT A SEPARATION OF 10 FEET, THE WATER MAIN MAY BE LAID CLOSER, PROVIDED THAT THE ELEVATION OF THE BOTTOM OF THE WATER MAIN IS AT LEAST 18 INCHES ABOVE THE TOP OF THE SEWER WITH A HORIZONTAL SEPARATION OF AT LEAST 3 FEET.
 4. WATER MAINS SHALL MAINTAIN A MINIMUM 24" HORIZONTAL AND 18" VERTICAL SEPARATION BETWEEN THE WATER MAIN AND STORM SEWER OR OTHER DRY UTILITIES.
 5. WHEN A PROPOSED WATER MAIN CROSSES UNDER A PROPOSED OR EXISTING SANITARY SEWER, CONSTRUCT BOTH THE WATER MAIN AND THE SEWER OF FERROUS MATERIALS WITH JOINTS THAT ARE EQUIVALENT TO WATER MAIN STANDARDS FOR A DISTANCE OF 10 FEET ON EACH SIDE OF THE POINT OF CROSSING. CENTER THE SECTION OF WATER PIPE AT THE POINT OF CROSSING.
 6. VERIFY ALL ILLUSTRATED UTILITY CROSSINGS PRIOR TO CONSTRUCTION AND NOTIFY THE ENGINEER IF CONFLICTS ARE ENCOUNTERED.
 7. CONTRACTOR SHALL COORDINATE UTILITY RELOCATION OR ABANDONMENT WITH LOCAL UTILITY COMPANIES AS REQUIRED.
 8. ALL CONNECTIONS TO EXISTING WATER MAINS OR FORCE MAINS TO BE MADE WITH THRUST COLLAR AS PER THE DETAIL OF THESE PLANS.
 9. CONTRACTOR SHALL PROVIDE A VACUUM TRUCK ON-SITE TO CLEAN UP WASTEWATER SPILLAGE DURING CONNECTIONS TO EXISTING FORCE MAIN.
 10. CONTRACTOR SHALL COORDINATE CONNECTIONS TO EXISTING WATER MAINS AND FORCE MAINS WITH THE UTILITY OWNER SO AS TO MINIMIZE SERVICE INTERRUPTIONS.



GENERAL NOTES:
 1. EX. TOPOGRAPHIC SURVEY AND SUE BY OTHERS. CONTRACTOR TO CONFIRM FINAL CONNECTION POINTS IN FIELD.
 2. EX. WATER MAIN AND FORCE MAIN DEPTHS SHOWN ARE APPROXIMATE BASED ON BEST AVAILABLE INFORMATION. ACTUAL DEPTH IS TO BE CONFIRMED IN FIELD.
 3. EX. WATER MAIN AND FORCE MAIN MATERIALS SHOWN ARE BASED ON BEST AVAILABLE INFORMATION. CONTRACTOR IS RESPONSIBLE TO PROVIDE ADEQUATE PIPE MATERIAL TRANSITION AT ALL CONNECTIONS.



PROFILES NOTES:
 1. MINIMUM COVER OF 36" TO BE MAINTAINED WITH WATER AND SANITARY FORCEMAIN INSTALLATION.
 2. A SECTION OF DIP MAIN LINE SHALL BE CENTERED AT EVERY POINT OF CROSSING BELOW STORM SEWER.
 3. THRUST COLLARS TO BE INSTALLED AT EVERY DEFLECTION POINT.
 4. MAINS SHALL BE INSTALLED WITHOUT INTERMEDIATE HIGH POINTS. WHERE HIGH POINTS CAN NOT BE AVOIDED CONTRACTOR TO COORDINATE WITH UTILITY OWNER FOR AIR RELEASE REQUIREMENTS.
 5. PROJECT GEOTECHNICAL ENGINEER TO VERIFY NATIVE OR PLACED SITE SOIL BEARING STRENGTH AND RESISTANCE AT EACH BEND AND TEE LOCATION TO ENSURE CONCRETE THRUST BLOCK MINIMUM DESIGNS AS PER PROJECT SPECIFICATIONS ARE SUFFICIENT. WHERE MAINS ARE PLACED IN FILL ADDITIONAL CONCRETE AND REINFORCEMENT MAY BE WARRANTED.




PROJECT REFERENCE NO. R5819/R5820	SHEET NO. UC-4
REVISION NO.	UTILITIES ENGINEER
90% DESIGN - 11/30/21	
100% DESIGN - 3/02/22	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared by VHB Engineering NC, P.C. (C-3705) 940 Main Campus Drive, Suite 500 Raleigh, NC 27606	

4/12/2022 \\vhb.com\gbl\proj\Raleigh\38564.19 NCDOT R5819 R5820 U574 NCDOT Utilities\Rdy_Ut\Proj\Plan Sheets\R5819_UC_PLAN.dwg Mark Edwards


Tuesday, April 12, 2022 ANSI A (8.50 X 11.00 Inches)

LEGEND	
	EX. WATERLINE TO REMAIN
	EX. WATERLINE TO BE REMOVED/ABANDONED
	PROPOSED WATERLINE
	EX. SANITARY FORCEMAIN TO REMAIN
	EX. SANITARY FORCEMAIN TO BE REMOVED/ABANDONED
	PROPOSED 8" C900 FORCEMAIN


- ### Notes
- ALL WORK ASSOCIATED WITH THE RELOCATION OF WATERMANS OR SANITARY SEWER FORCEMANS SHALL BE COMPLETED AS PER THE NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES, LATEST EDITION, SUPPLEMENTED (AS REQUIRED) WITH THE FACILITIES OWNER STANDARD SPECIFICATIONS AS DESCRIBED IN THE PROJECT SPECIFIC SPECIAL PROVISIONS.
 - ALL MAINS SHALL BE INSTALLED WITH A MINIMUM OF 36 INCHES OF COVER.
 - WATER MAINS SHALL BE AT LEAST 10 FEET LATERALLY FROM EXISTING OR PROPOSED SEWERS. WHERE LOCAL CONDITIONS PREVENT A SEPARATION OF 10 FEET, THE WATER MAIN MAY BE LAID CLOSER, PROVIDED THAT THE ELEVATION OF THE BOTTOM OF THE WATER MAIN IS AT LEAST 18 INCHES ABOVE THE TOP OF THE SEWER WITH A HORIZONTAL SEPARATION OF AT LEAST 3 FEET.
 - WATER MAINS SHALL MAINTAIN A MINIMUM 24" HORIZONTAL AND 18" VERTICAL SEPARATION BETWEEN THE WATER MAIN AND STORM SEWER OR OTHER DRY UTILITIES.
 - WHEN A PROPOSED WATER MAIN CROSSES UNDER A PROPOSED OR EXISTING SANITARY SEWER, CONSTRUCT BOTH THE WATER MAIN AND THE SEWER OF FERROUS MATERIALS WITH JOINTS THAT ARE EQUIVALENT TO WATER MAIN STANDARDS FOR A DISTANCE OF 10 FEET ON EACH SIDE OF THE POINT OF CROSSING. CENTER THE SECTION OF WATER PIPE AT THE POINT OF CROSSING.
 - VERIFY ALL ILLUSTRATED UTILITY CROSSINGS PRIOR TO CONSTRUCTION AND NOTIFY THE ENGINEER IF CONFLICTS ARE ENCOUNTERED.
 - CONTRACTOR SHALL COORDINATE UTILITY RELOCATION OR ABANDONMENT WITH LOCAL UTILITY COMPANIES AS REQUIRED.
 - ALL CONNECTIONS TO EXISTING WATER MAINS OR FORCE MAINS TO BE MADE WITH THRUST COLLAR AS PER THE DETAIL OF THESE PLANS.
 - CONTRACTOR SHALL PROVIDE A VACUUM TRUCK ON-SITE TO CLEAN UP WASTEWATER SPILLAGE DURING CONNECTIONS TO EXISTING FORCE MAIN.
 - CONTRACTOR SHALL COORDINATE CONNECTIONS TO EXISTING WATER MAINS AND FORCE MAINS WITH THE UTILITY OWNER SO AS TO MINIMIZE SERVICE INTERRUPTIONS.




- #### GENERAL NOTES:
- EX. TOPOGRAPHIC SURVEY AND SUE BY OTHERS. CONTRACTOR TO CONFIRM FINAL CONNECTION POINTS IN FIELD.
 - EX. WATER MAIN AND FORCE MAIN DEPTHS SHOWN ARE APPROXIMATE BASED ON BEST AVAILABLE INFORMATION. ACTUAL DEPTH IS TO BE CONFIRMED IN FIELD.
 - EX. WATER MAIN AND FORCE MAIN MATERIALS SHOWN ARE BASED ON BEST AVAILABLE INFORMATION. CONTRACTOR IS RESPONSIBLE TO PROVIDE ADEQUATE PIPE MATERIAL TRANSITION AT ALL CONNECTIONS.




TYPICAL SECTION NO.15
-DET2- (ONSITE DETOUR FOR SR 1740 OLD LAKE RD)



- #### PROFILES NOTES:
- MINIMUM COVER OF 36" TO BE MAINTAINED WITH WATER AND SANITARY FORCEMAIN INSTALLATION.
 - A SECTION OF DIP MAIN LINE SHALL BE CENTERED AT EVERY POINT OF CROSSING BELOW STORM SEWER.
 - THRUST COLLARS TO BE INSTALLED AT EVERY DEFLECTION POINT.
 - MAINS SHALL BE INSTALLED WITHOUT INTERMEDIATE HIGH POINTS. WHERE HIGH POINTS CAN NOT BE AVOIDED CONTRACTOR TO COORDINATE WITH UTILITY OWNER FOR AIR RELEASE REQUIREMENTS.
 - PROJECT GEOTECHNICAL ENGINEER TO VERIFY NATIVE OR PLACED SITE SOIL BEARING STRENGTH AND RESISTANCE AT EACH BEND AND TEE LOCATION TO ENSURE CONCRETE THRUST BLOCK MINIMUM DESIGNS AS PER PROJECT SPECIFICATIONS ARE SUFFICIENT. WHERE MAINS ARE PLACED IN FILL ADDITIONAL CONCRETE AND REINFORCEMENT MAY BE WARRANTED.



6" WATER MAIN




8" FORCE MAIN

4/12/2022
 \\vhb.com\gbl\proj\Raleigh\38564.19 NCDOT Utilities\Ray_Ut\Proj\Plan Sheets\R5819_UC_PLAN.dwg
 Mark Edwards

PROJECT REFERENCE NO. R5819/R5820	SHEET NO. UC-5
REVISION NO. 90% DESIGN - 11/30/21 100% DESIGN - 3/02/22	UTILITIES ENGINEER
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared by VHB Engineering NC, P.C. (C-3705) 940 Main Campus Drive, Suite 500 Raleigh, NC 27606	

Tuesday, April 12, 2022 ANSI A (8.50 X 11.00 inches)
 4/12/2022
 \\hvb.com\gbl\proj\Raleigh_38564.19 NCDOT\Utilities\Rdy_Ut\Proj\Plan Sheets\R5819_UC_PLAN.dwg
 Mark Edwards



GENERAL NOTES (DRY):

- BEDDING FOR PRESSURE AND GRAVITY PIPE IN DRY CONDITIONS.
- PROVIDE TRENCH SAFETY SYSTEM FOR TRENCH DEPTHS GREATER THAN 5 FEET.
- IF THE NATIVE MATERIAL EXCAVATED FROM THE TRENCH IS UNSUITABLE AS BACKFILL MATERIAL, OR THE REQUIRED COMPACTION IS UNATTAINABLE, THE CONTRACTOR SHALL, AT HIS EXPENSE, IMPORT SELECT MATERIAL TO BE MIXED WITH OR USED IN PLACE OF THE NATIVE MATERIAL. SELECT MATERIAL MUST BE APPROVED BY ENGINEER. SUBSTITUTE SOIL CEMENT SLURRY (1-SACK) IF REQUIRED IN SPECS.


CONSTRUCTION KEY NOTES (DRY):

- APPROVED MARKING TAPE
- UNDISTURBED STABLE MATERIAL
- NATIVE MATERIAL BACKFILL
PAVED CONDITION: COMPACT TO 90% DENSITY PER ASTM D-1557 MODIFIED PROCTOR.
UNPAVED CONDITION: COMPACT TO 85% DENSITY PER ASTM D-1557 MODIFIED PROCTOR.
(*SEE NOTE #3 IF THESE PREVIOUS CONDITIONS CANNOT BE MET.)
- SLOPE TRENCH IN SANDY SOIL CONDITIONS.
- USE CLASS II OR CLASS III SAND PER ASTM D-2487. NATIVE MATERIAL OR IMPORTED SELECT MATERIAL MEETING OR EXCEEDING THIS REQUIREMENT MAY BE USED. COMPACT TO 85% DENSITY PER ASTM D-1557 MODIFIED PROCTOR (OR 90% D-698 STANDARD PROCTOR).
- APPROVED PIPE.
- TRENCH DIMENSIONS AS FOLLOWS:

PIPE DIAMETER	"H"
6" - 30"	4"
GREATER THAN 30"	6"

PIPE DIAMETER	"W"
6" - 30"	8"
GREATER THAN 30"	12"

I. TRACER WIRE TO BE INSTALLED OVER NON-FERROUS (PVC, HDPE, ETC.) PIPES.



GENERAL NOTES (WET):

- BEDDING FOR PRESSURE PIPE IN WET CONDITIONS.
- PROVIDE TRENCH SAFETY SYSTEM FOR TRENCH DEPTHS GREATER THAN 5 FEET.
- A DRY TRENCH MUST BE MAINTAINED WHILE PLACING BEDDING.
- IF THE NATIVE MATERIAL EXCAVATED FROM THE TRENCH IS UNSUITABLE AS BACKFILL MATERIAL, OR THE REQUIRED COMPACTION IS UNATTAINABLE, THE CONTRACTOR SHALL, AT HIS EXPENSE, IMPORT SELECT MATERIAL TO BE MIXED WITH OR USED IN PLACE OF THE NATIVE MATERIAL. SELECT MATERIAL MUST BE APPROVED BY ENGINEER. SUBSTITUTE SOIL CEMENT SLURRY (1-SACK) IF REQUIRED IN SPECS.


CONSTRUCTION KEY NOTES (WET):

- APPROVED MARKING TAPE
- UNDISTURBED STABLE MATERIAL
- NATIVE MATERIAL BACKFILL
PAVED CONDITION: COMPACT TO 90% DENSITY PER ASTM D-1557 MODIFIED PROCTOR.
UNPAVED CONDITION: COMPACT TO 85% DENSITY PER ASTM D-1557 MODIFIED PROCTOR.
(*SEE NOTE #4 IF THESE PREVIOUS CONDITIONS CANNOT BE MET.)
- USE CLASS II OR CLASS III SAND PER ASTM D-2487. NATIVE MATERIAL OR IMPORTED SELECT MATERIAL MEETING OR EXCEEDING THIS REQUIREMENT MAY BE USED. COMPACT TO 85% DENSITY PER ASTM D-1557 MODIFIED PROCTOR (OR 90% D-698 STANDARD PROCTOR).
- APPROVED PIPE (WRAP DUCTILE IRON OR STEEL PIPE IN APPROVED POLYETHYLENE SHEETING, MINIMUM 6 MIL THICKNESS).
- USE CLASS I GRAVEL PER ASTM D-2321 AND D-2487. NO COMPACTION REQUIRED. USE MINIMAL TAMPING, RODDING OR HAUNCH SLICING CAREFULLY IN THE EMBEDMENT ZONE. IF REQUIRED BY THE ENGINEER, TEST PER ASTM D-4254 PERCENT OF RELATIVE DENSITY.
- 18" MINIMUM UNLESS OTHERWISE SPECIFIED.
- TRENCH DIMENSIONS AS FOLLOWS:


PIPE DIAMETER	"H"
6" - 30"	4"
GREATER THAN 30"	6"

PIPE DIAMETER	"W"
6" - 30"	8"
GREATER THAN 30"	12"

I. TRACER WIRE TO BE INSTALLED OVER NON-FERROUS (PVC, HDPE, ETC.) PIPES.




Horizontal Directional Drill (HDD) HDPE
N.T.S. Source: VHB



Standard Thrust Block Views
N.T.S. Source: VHB

Utility Trench
N.T.S. Source: VHB




REINFORCING REQUIREMENTS

I.D. PIPE	REBAR SIZE	"X" BAR LENGTH	"X" BAR WEIGHT	"Y" BAR LENGTH	"Y" BAR WEIGHT	NO. REQUIRED
6" - 36"	#5	2'-2" + O.D. PIPE	1.043 LBS/FT	1'-1"	1.1 LBS EACH	X-24, Y-12
36" & GREATER	#6	3'-0" + O.D. PIPE	1.502 LBS/FT	1'-3"	1.9 LBS EACH	X-24, Y-12

THRUST COLLAR, AND THRUST SCHEDULE

I.D. PIPE	"A"	"B"	"C"	"D"
6" - 16"	1'-4"	1'-7"	0'-2"	3/8"
20" - 24"	1'-4"	1'-7"	0'-3"	1/2"
30" - 36"	1'-4"	1'-7"	0'-4"	5/8"
48" & GREATER	1'-8"	1'-9"	0'-6"	7/8"

Thrust Collar Detail
N.T.S. Source: VHB



HDPE/DIP Transition Assembly
N.T.S. Source: VHB

SIZE AND DEGREE OF BEND	REACTION BEARING AREAS FOR HORIZONTAL WATER PIPE BENDS BASED ON TEST PRESSURE OF 200 P.S.I.							REACTION BEARING AREAS FOR HORIZONTAL WATER PIPE BENDS BASED ON TEST PRESSURE OF 200 P.S.I.														
	STATIC THRUST IN POUNDS	MODERATELY DRY CLAY 4000 LBS/FT ²	SOFT CLAY 2000 LBS/FT ²	GRAVEL / COARSE SAND 1800 LBS/FT ²	8000 LBS/FT ² ALLWAY'S DRY	SAND, COMPACT FIRM 8000 LBS/FT ²	SAND, CLEAN DRY 1000 LBS/FT ²	SOIL 1000 LBS/FT ² QUICKSAND - VERY POOR 10,000 LBS/FT ²	ROCK - POOR 10,000 LBS/FT ²	ROCK - POOR 10,000 LBS/FT ²	ROCK - POOR 10,000 LBS/FT ²	ROCK - POOR 10,000 LBS/FT ²										
6"	11 1/4"	1,108	1	1	1	1	1	2	1													
	22 1/2"	2,207	1	2	2	1	1	3	1													
	45°	4,328	2	3	3	1	1	2	5	1												
	90°	7,996	2	4	5	1	1	2	8	1												
	PLUG	5,655	2	3	4	1	1	2	6	1												
8"	11 1/4"	1,970	1	1	2	1	1	1	2	1												
	22 1/2"	3,922	1	2	3	1	1	1	4	1												
	45°	7,694	2	4	5	1	1	2	8	1												
	90°	14,215	4	8	9	2	2	4	15	2												
	PLUG	10,053	3	5	6	2	2	3	10	1												
12"	11 1/4"	4,433	2	3	3	1	1	2	5	1												
	22 1/2"	8,826	3	5	6	2	2	3	9	1												
	45°	17,312	5	9	11	3	3	5	18	2												
	90°	31,983	8	16	19	4	4	8	32	4												
	PLUG	22,619	6	12	14	3	3	6	23	3												
16"	11 1/4"	7,881	2	4	5	1	1	2	8	1												
	22 1/2"	15,691	4	8	10	2	2	4	16	2												
	45°	30,779	8	16	19	4	4	8	31	4												
	90°	56,861	15	29	35	8	8	15	57	6												
	PLUG	40,213	10	21	25	5	5	10	41	5												
	24"	11 1/4"	17,734	5	9	11	3	3	5	18	2											
	22 1/2"	35,305	9	18	22	5	5	9	36	4												
	45°	69,252	18	35	42	9	9	18	70	7												
	90°	127,936	32	64	77	16	16	32	128	13												
	PLUG	90,478	23	46	55	12	12	23	91	10												
	30"	11 1/4"	27,709	7	14	17	4	4	7	2	3											
	22 1/2"	55,163	14	28	34	7	7	14	56	6												
	45°	108,206	28	55	65	14	14	28	109	11												
	90°	199,900	50	100	120	25	25	50	200	20												
	PLUG	141,372	36	71	85	18	18	36	142	15												
	36"	11 1/4"	39,901	10	20	24	5	5	10	40	4											
	22 1/2"	79,439	20	40	48	10	10	20	30	8												
	45°	155,816	39	78	94	20	20	39	156	16												
	90°	287,855	72	144	172	36	36	72	288	29												
	PLUG	203,575	51	102	122	26	26	51	204	21												
	48"	11 1/4"	70,935	18	36	43	9	9	18	71	8											
	22 1/2"	141,218	36	71	85	18	18	36	142	15												
	45°	277,007	70	139	166	35	35	70	277	28												
	90°	511,742	128	256	320	64	64	128	512	52												
	PLUG	361,911	91	181	217	46	46	91	362	37												


REACTION BEARING AREAS ARE IN SQUARE FEET MEASURED IN A VERTICAL PLANE IN THE TRENCH SIDE AT AN ANGLE OF 90° TO THE THRUST VECTOR.

REACTION BEARING AREAS ARE IN SQUARE FEET MEASURED IN A VERTICAL PLANE IN THE TRENCH SIDE AT AN ANGLE OF 90° TO THE THRUST VECTOR.


THRUST BLOCKING DESIGN QUANTITY TABLE				THRUST BLOCKING DESIGN QUANTITY TABLE			
REVISIONS	DATE	REVISIONS	DATE	REVISIONS	DATE	REVISIONS	DATE

USE 6" - 90 BEND VALUE FOR HYDRANTS FOR ADDITIONAL SAFETY FACTOR.


Tuesday, April 12, 2022 ANSI A (8.50 X 11.00 Inches)
 4/12/2022
 \\vhb.com\gbl\proj\Raleigh\38564.19 NCDOT\Utilities\R5819 UC_PLAN.dwg
 Mark Edwards



DIMENSIONS IN INCHES	
TOP	BOTTOM
10	15
10	24
16	24
20	36
26	48
26	60



NOTES:
 1. CONCRETE PROTECTOR RING SHALL BE 3000 P.S.I. PRECAST REINFORCED CONCRETE.




NOTES:
 1. ONLY MANUFACTURED VALVE BOX EXTENSIONS SHALL BE ALLOWED.
 2. VALVE OPERATING NUT MUST BE EXTENDED SO THAT THE DEPTH IS NO GREATER THAN 4" (ft) FROM THE SURFACE USING A MANUFACTURER APPROVED EXTENSION KIT.
 3. PRECAST CONCRETE ENCASEMENT IS REQUIRED OUTSIDE OF PAVED AREAS.
 4. CONCRETE PROTECTOR RING MAY BE USED IN LIEU OF ENCASEMENT IN UNPAVED AREAS.
 5. ALL VALVES SHALL BE PLACED ON 4" THICK 8"x12" CONCRETE BLOCKS.

Valve Box

N.T.S.

Source: VHB



NOTES

- CONCRETE THRUST BLOCKS TO BE USED ONLY WHERE THEY CAN BEAR ON UNDISTURBED EARTH AS SHOWN. USE CLAMPS AND TIE RODS OR OTHER ACCEPTABLE METHOD OF JOINT RESTRAINT WHERE SOIL CONDITIONS PROHIBIT THE USE OF THRUST BLOCKS.
- HYDRANT IN SIDEWALK AREAS TO BE LOCATED TO PROVIDE MINIMUM CLEAR SIDEWALK PASSAGE WIDTH OF 3 FEET AT HYDRANT.
- A 36-INCH CLEAR SPACE SHALL BE MAINTAINED AROUND THE CIRCUMFERENCE OF THE HYDRANT UNLESS OTHERWISE APPROVED BY AUTHORITY HAVING JURISDICTION.

Hydrant Construction

N.T.S.

Source: VHB



12/18

LD_250

Concrete Protector Ring

N.T.S.

Source: VHB



NOTES:
 1. TAPPING SLEEVE SHALL BE FABRICATED OF TYPE 304 S.S. AND PROVIDE A 360° SEAL AROUND EXISTING PIPE WITH FULL CIRCUMFERENTIAL GASKET.

Tapping Sleeve & Valve Assembly


N.T.S.

Source: VHB

Valve and Valve Box Installation

N.T.S.

Source: VHB




NOTES:
 1. VALVE MARKERS SHALL BE PLACED AT R/W.
 2. LETTERS SHALL FACE TOWARDS VALVE.
 3. MARKER SHALL HAVE BRASS OR BRONZE EMBED ON TOP OR SIDE.
 4. CONTRACTOR SHALL STAMP DISTANCE TO CENTER OF VALVE INTO EMBED.
 5. MAIN LINE VALVES SHALL HAVE MARKER WITH "MV" CASTED IN IT.
 6. BLOW-OFF ASSEMBLY SHALL INCLUDE MARKER W/ "BO" CASTED IN IT.

Valve Marker

N.T.S.


Source: VHB



Concrete Cradle Protection for Water and Force Main Crossings

N.T.S.

Source: VHB



GENERAL NOTES:
 1. STEEL RODS AND BOLTS SHALL BE 3/4" HOT DIPPED GALVANIZED.
 2. CONCRETE SHALL NOT CONTACT BOLTS OR ENDS OF MECHANICAL JOINT BENDS.
 3. RESTRAINED MECHANICAL GLANDS TO BE USED AT ALL FITTINGS.
 4. MUST USE DUCTILE IRON EYE BOLTS WHERE NECESSARY.
 5. 3' MINIMUM COVER MUST BE MAINTAINED ON ALL WATER MAINS

Standard Vertical Bend

N.T.S.

Source: VHB

ROD REQUIREMENTS		
SIZE OF 45 BEND	STATIC THRUST IN POUNDS	NO. OF RODS REQUIRED
6"	4,328	2
8"	7,694	4
12"	17,312	4
16"	30,779	8
24"	69,252	8

PROJECT REFERENCE NO. R5819/R5820	SHEET NO. UC- DT2
REVISION NO.	UTILITIES ENGINEER
90% DESIGN - 11/30/21	DocuSigned by: John M. Edwards SEAL 14101 ENGINEER 10/11/2022
100% DESIGN - 3/02/22	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	
Prepared by vhb VHB Engineering NC, P.C. (C-3705) 940 Main Campus Drive, Suite 500 Raleigh, NC 27606	