

8/23/99



PROJ. REFERENCE NO.
U-2519BB

SHEET NO.
X-96

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

240

240

230

230

220

220

210

210

200

200

220

220

210

210

220

220

210

210

200

200

210

210

200

200

210

210

200

200

210

210

200

200

INTERSECTION SHEAR LINE
0.003 0.003
213.70
26 + 50.00
INTERSECTION SHEAR LINE

4:1 6:1 0.005 0.005 6:1
SP 213.19 212.50
26 + 00.00

4:1 4:1 0.020 0.020 6:1
SP 212.80 213.07
25 + 50.00

4:1 4:1 0.020 0.020 4:1 4:1
SP 212.28 214.19 212.59
25 + 00.00

4:1 4:1 0.020 0.020 4:1 4:1
SP 211.98 214.97 212.44
24 + 50.00

4:1 4:1 0.020 0.020 4:1 4:1
SP 211.68 215.50 212.29
24 + 00.00

-SRI-

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

2/3/2022
E:\Projects\XSC\U2519BB.rdy-XPL_SRI.dgn
Erica.Martin