

CLEARING AND GRUBBING EROSION CONTROL FOR CONSTRUCTION SHEET 17

NOTE: PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.

INSTALL PIPE(S) IN JURISDICTIONAL AREAS WITHOUT IMPACTING STREAM UNTIL AREA STABILIZED AND ACCORDING TO NCDOT BEST MANAGEMENT PRACTICES FOR CONSTRUCTION AND MAINTENANCE ACTIVITIES MANUAL.

 ENVIRONMENTALLY SENSITIVE AREA SEE PROJECT SPECIAL PROVISIONS

95 x 36 x 3
2.0 inch Skimmer
with 1.625 inch
Orifice Diameter
13 ft. weir
ID 17.7 B

Modified Silt Basin
Type 'B'
58 x 36 x 3
15 ft. weir
(See Tiered Skimmer
Basin Detail)
ID 17.3 B

58 x 36 x 3
2.0 inch Skimmer
with 1.625 inch
Orifice Diameter
15 ft. weir
(See Tiered Skimmer
Basin Detail)
ID 17.3 B

90 x 35 x 3
2.0 inch Skimmer
with 1.625 inch
Orifice Diameter
12 ft. weir
ID 17.1 CG

65 x 30 x 3
1.5 inch Skimmer
with 1.25 inch
Orifice Diameter
7 ft. weir
ID 17.2 B

45 x 22 x 3
1.5 inch Skimmer
with 0.875 inch
Orifice Diameter
4 ft. weir
ID 17.5 B

60 x 15 x 3
1.5 inch Skimmer
with 0.75 inch
Orifice Diameter
4 ft. weir
ID 17.6 B

46 x 23 x 3
1.5 inch Skimmer
with 0.875 inch
Orifice Diameter
4 ft. weir
ID 17.4 CG

MATCHLINE -L- STA. 180+00.00 SEE SHEET NO. 16

MATCHLINE -L- STA. 193+00.00 SEE SHEET NO. 18

