

HDR Engineering, Inc. of the Carolinas 555 Fayetteville St, Suite 900 Raleigh, N.C. 27601 N.C.B.E.L.S. License Number: F-0116

| Lister E-1989 115-20 1. CONTRACTOR IS RESPONSIBLE FOR FURNISHING ELEVATION DRAWINGS FOR ENGINEER'S APPROVAL. 1. CONTRACTOR IS RESPONSIBLE FOR FURNISHING ELEVATION DRAWINGS FOR ENGINEER'S APPROVAL. 2. PROVIDE A FIXED LADDER LEADING TO THE ACCESS PLATEFORM FOR THE DMS AS INDICATED IN THE PROJECT SPECIAL PROVISIONS. 3. EQUIP THE LADDER WITH A SECURITY COVER (LADDER GUARD). START THE FIRST LADDER RUNG NO MORE THAN 18 INCHES ABOVE A CONCRETE LANDING PAD, dESIGN RUNGS ON 12 INCH CENTER-TO-CENTER TYPICAL SPACING. 4. INSTALL A CONCRETE LANDING PAD MEASURING A MINIMUM 4 INCHES DEEP, 24 INCHES WIDE, AND 36 INCHES LONG DIRECTLY BENEATH THE LADDER. 5. USE ACTUAL DIMENSIONS AND WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE. 6. FIELD VERFY ALL FOOTING ELEVATIONS AND SECIFICATIONS FOR ROADS AND STRUCTURES 7. INSURE THAT THE TOP OF THE FOOTING ELEVATIONS AND SECIFICATIONS FOR ROADS AND SURFACE AT THE FOOTING THE PEDESTAL STRUCTURES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINTO'S THE EGOUND SURFACE AT THE FOOTING ENTOY 24 INCHES ABOVE THE HIGHEST POINTO'S ENCLOSURE TO WITHSTAND WIND VELOCTIES OF 120 MPH 9. DESIGN AND CONSTRUCT THE PEDESTAL STRUCTURES AND DOT DAMAGE ANY UND EXISTING UNTERSEAND THE HIGHEST POINT OF THE GROUND WORK, DO NOT DAMAGE ANY UND EXISTING ANY UND EXISTING UNTERSEAND ENCLOSURE TO THE PROJECT SPECIAL PROVESIONS CABLE DURING ANY UND EXISTING UNTERSEANED ED ROAD CONSTRUCTION 10. DEFER TO THE PROJECT SPECIAL PROVESIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTUETES AND AND MAND BANDING 11. OTHER PROJECT SPECIAL PROVESIONS AND ARM AND BANDING STATEMENT </th <th></th> <th></th> <th>PROJECT REFERENCE</th> <th>NO I</th> <th>SHEET NO.</th> | | | PROJECT REFERENCE | NO I | SHEET NO. | |
|---|--|---|---------------------------------------|-----------------------|---------------------------------------|--|
| <text></text> | | | | | | |
| <list-item> 1. PROVIDE A FIXED LADDER LEADING TO THE ACCESS PLATEFORM FOR THE DMS AS INDICATED IN THE PROJECT SPECIAL DYNCH AND AND AND AND AND AND AND AND AND AND</list-item> | FURNIS | HING ELEVATION | | FOR | | |
| <text></text> | 2. PRO ACCES | VIDE A FIXED LADE S PLATEFORM FOR | THE DMS A | | THE | |
| COVER (LADDER GUARD). START THE FIRST LADDER RUNG NO MORE THAN 18 INCHES ABOVE A CONCRETE LANDING PAD. dESIGN RUNGS ON 12 INCH CENTER-TO-CENTER TYPICAL SPACING. 4. INSTALL A CONCRETE LANDING PAD MEASURING A MINIMUM 4 INCHES DEEP, 24 INCHES WIDE, AND 36 INCHES LONG DIRECTLY BENEATH THE LADDER. 5. USE ACTUAL DIMENSIONS AND WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE. 6. FIELD VERIFY ALL FOOTING ELEVATIONS AND GROUND SLOPES AT THE FOOTING SPECIFICATIONS FOR ROADS AND STRUCTURES 7. ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS AT LEAST 5 INCHES AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 120 MPH 9. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK, DO NOT DAMAGE ANY EXISTING UTILITIES OF NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT ANY EXISTING UTILITIES OF NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT EXTENSISTING UTILITIES OF NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION FOR INFORMATION ABOUT EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION FOR INFORMATION ABOUT EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION FOR INFORMATION ABOUT EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION FOR INFORMATION ABOUT EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION FOR INFORMATION ABOUT EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION FOR INFORMATION ABOUT EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISION FOR INFORMATION ABOUT EXTENSION ARM AND BANDING | PROVIS | IONS. | | ΊΤΥ | | |
| MEASURING A MINIMUM 4 INCHES DEEP, 24 INCHES WIDE, AND 36 INCHES LONG DIRECTLY BENEATH THE LADDER. 5. USE ACTUAL DIMENSIONS AND WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE. 6. FIELD VERIFY ALL FOOTING ELEVATIONS AND GROUND SLOPES AT THE FOOTINGS USING THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES 7. ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS OF 120 MPH 9. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING VERIFY ALL MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING | COVER LADDE ABOVE RUNGS | (LADDER GUARD). R RUNG NO MOR A CONCRETE LAN 6 ON 12 INCH CE | START THE F E THAN 18 DING PAD. | IRST INCH dESIG | | |
| WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE. 6. FIELD VERIFY ALL FOOTING ELEVATIONS AND GROUND SLOPES AT THE FOOTINGS USING THE LATEST NOCOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES 7. ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS AT LEAST 6 INCHES AND MIND VELOCITIES OF 120 MPH 9. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING INSTALLATION DETAILS MUSICING MINS INSTALLATION DETAILS MUSICING MINS INSTALLATION DETAILS MUSICING MINS INSTALLATION DETAILS MUSICING | MEASU DEEP, 2 INCHES LADDEF | RING A MINIMUM 4 INCHES WIDE, AI 5 LONG DIRECTLY 8. | 4 INCHES ND 36 BENEATH TH | | | |
| AND GROUND SLOPES AT THE FOOTINGS USING THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES 7. ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING 8. DESIGN AND CONSTRUCT THE PEDESTAL-STRUCTURES AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 120 MPH 9. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK, DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING NOT MALE AND BANDING NET INSTALLATION DETAIL NET INSTALLATION DETAIL NET INSTALLATION DETAIL NET INSTALLATION DETAIL NET INSTALLATION DETAIL NET INSTALLATION DETAIL NET INSTALLATION NET INSTALLATI | WEIGH ⁻ The de | F OF THE DMS TO SIGN OF THE DMS | COMPLETE S STRUCTURE | | | |
| EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING 8. DESIGN AND CONSTRUCT THE PEDESTAL STRUCTURES AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 120 MPH 9. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING VOLUMENT NOT CONSIDERED FOR THE CCTV EXTENSION ARM AND BANDING VERTIFIED TO SECOND MARK AND BANDING | AND GROUND SLOPES AT THE FOOTINGS USING THE LATEST NCDOT STANDARD SPECIFICATIONS FOR | | | | | |
| PEDESTAL-STRUCTURES AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 120 MPH 9. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING MIS INSTALLATION DETAIL MIS INSTALLATION DETAIL MIS INSTALLATION DETAIL MIS INSTALLATION DETAIL MIS INSTALLATION DETAIL MIS INSTALLATION DETAIL MIS INSTALLATION MIS INSTA | EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT | | | | | |
| LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT COMMUNICATIONS CABLE DURING CONSTRUCTION 10. REFER TO THE PROJECT SPECIAL PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING DUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED DUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED DUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED DIMS INSTALLATION DETAIL DIMS INSTALLATION DIMS INSTALLAT | PEDESTAL STRUCTURES AND DMS ENCLOSURE TO WITHSTAND WIND | | | | | |
| PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV EXTENSION ARM AND BANDING DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED red in the Offices of: DIVISION 14 DIVISION 14 HAVING COUNTY PLAN DATE: APPRIL 13, 2022 REVISIONS INIT: DIVISION 14 HAVING COUNTY PREPARED BY: T. MCHENRY INIT: DIVISIONS MULTING | LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT COMMUNICATIONS CABLE DURING | | | | | |
| Final UNLESS ALL Signatures completed DMS INSTALLATION DETAIL Division 14 Haywood County Plan Date: APRIL 13, 2022 Reviewed BY: C. BEARD Verture Odo50 INIT. Date Matthew q. Mathew q. Matthew q. Matthew q. Mathew q. Mathe | PROVISIONS FOR INFORMATION ABOUT THE MATERIALS NEEDED FOR THE CCTV | | | | | |
| Final UNLESS ALL Signatures completed DMS INSTALLATION DETAIL Division 14 Haywood County Plan Date: APRIL 13, 2022 Reviewed BY: C. BEARD Verture Odo50 INIT. Date Matthew q. Mathew q. Matthew q. Matthew q. Mathew q. Mathe | | | | | | |
| DETAIL Division 14 Haywood County Plan Date: APRIL 13, 2022 Revision By: C. BEARD PREPARED BY: T. MCHENRY APPROVED BY: M. VOLZ Scale Revisions INIT. Date Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. Matthew a. | red in the Offices of: | | [| FINA | AL UNLESS ALL URES COMPLETED | |
| Scale REVISIONS INIT. DATE 0 50 | AND HORF AND SCORE AND SCO | DETAIL <u>Division_14Haywood_County</u> | | MAR WAR | A CARO FESSION SEAL P 046589 | |
| | | PREPARED BY: T. MCHENRY APPROVED | BY: M. VOLZ | | YEW A MININ | |
| | | | | SIGNATI | JRE DATE | |