

STEEL REPAIR LOCATIONS											
TYPE	SPAN	BEAM	LOCATION	DIM. ``A''	DIM.``B''	DIM.``C''	DIM.``D''				
(SEE SHEETS S3-22 THRU S3-24 FOR BEAM REPATE DETATUS AND DIMENSIONS.)											

	REPAIR QUANTITY TABLE								
	UNDERSIDE OF DECK	QUANTITIES							
	REPAIRS - SPAN C	ESTIMATE		ACTUAL					
	SHOTCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF				
	UNDERSIDE OF DECK	0.0	0.0						
	CONCRETE BENT DIAPHRAGM	11.3	5.7						
	OVERHANG	8.8	3.0						
PAIR	CONCRETE REPAIRS	AREA SF	VOLUME CF	AREA SF	VOLUME CF				
	UNDERSIDE OF DECK	0.0	0.0						
R	CONCRETE BENT DIAPHRAGM	0.0	0.0						
	OVERHANG	0.0	0.0						
VALUES IN CHART REPRESENT ESTIMATED REPAIR TOTALS AFTER REMOVAL OF UNSOUND CONCRETE, MIN. OF 1"BEHIND REBAR AND									

MIN. 2"CL TO SAWCUT. SEE REPAIR DETAILS.

NOTES:

THE LOCATIONS AND DIMENSIONS OF THE AREAS FOR REPAIR ARE BASED ON THE BEST INFORMATION AVAILABLE. THE CONTRACTOR, IN CONJUNCTION WITH THE ENGINEER, SHALL VERIFY THE LOCATION AND EXTENT OF REPAIR AREAS PRIOR TO STEEL FABRICATION. IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER WILL NOTE ON THE DRAWINGS THE APPROXIMATE LOCATION AND DESCRIPTION OF THE REPAIRS AND ENTER THE ACTUAL QUANTITIES INTO THE REPAIR QUANTITY TABLE. FOR ADDITIONAL NOTES, SEE SHEET 1 OF 5.