

PROJ. REFERENCE NO.	SHEET NO.
I-5987B	TMP-2TS8

SEE SHEETS TMP-146, 147
TEMPORARY SHORING LOCATION NO. (B2-01) ESTIMATED QUANTITY = 3510 SF

-L- STA. 797+00±, 33.0' RT TO -L- STA. 802+40±, 33.0' RT
 LENGTH = 540' AVERAGE HEIGHT = 6.5 FT MAXIMUM HEIGHT = 7.8 FT

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -L- 797+00±, 33 FT RT, TO STATION -L- 802+40±, 33 FT RT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
 UNIT WEIGHT (γ) = 120 PCF
 FRICTION ANGLE (ϕ) = 30 DEGREES
 COHESION (C) = 0 PSF
 GROUNDWATER ELEVATION = 144 FT±

DO NOT USE CANTILEVER, BRACED AND/OR ANCHORED SHORING FOR TEMPORARY SHORING FROM STATION -L- 797+00±, 33 FT RT, TO STATION -L- 802+40±, 33 FT RT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -L- 797+00±, 33 FT RT, TO STATION -L- 802+40±, 33 FT RT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY WALLS.

WHEN BACKFILL FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS OVERLAPS WITH THE REINFORCED ZONE OF TEMPORARY WALLS, USE SHORING BACKFILL OR BACKFILL MATERIAL REQUIRED FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS, WHICHEVER IS BETTER, IN THE REINFORCED ZONE OF TEMPORARY WALLS.

SEE SHEET TMP-147
TEMPORARY SHORING LOCATION NO. (B2-02) ESTIMATED QUANTITY = 3791 SF

-L- STA. 803+92±, 33.0' RT TO -L- STA. 808+60±, 33.0' RT
 LENGTH = 468' AVERAGE HEIGHT = 8.1 FT MAXIMUM HEIGHT = 8.5 FT

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -L- 803+92±, 33 FT RT, TO STATION -L- 808+60±, 33 FT RT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
 UNIT WEIGHT (γ) = 120 PCF
 FRICTION ANGLE (ϕ) = 30 DEGREES
 COHESION (C) = 0 PSF
 GROUNDWATER ELEVATION = 144 FT±

DO NOT USE CANTILEVER, BRACED AND/OR ANCHORED SHORING FOR TEMPORARY SHORING FROM STATION -L- 803+92±, 33 FT RT, TO STATION -L- 808+60±, 33 FT RT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -L- 803+92±, 33 FT RT, TO STATION -L- 808+60±, 33 FT RT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY WALLS.

WHEN BACKFILL FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS OVERLAPS WITH THE REINFORCED ZONE OF TEMPORARY WALLS, USE SHORING BACKFILL OR BACKFILL MATERIAL REQUIRED FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS, WHICHEVER IS BETTER, IN THE REINFORCED ZONE OF TEMPORARY WALLS.

SEE SHEET TMP-157
TEMPORARY SHORING LOCATION NO. (B2-03) ESTIMATED QUANTITY = 732 SF

-Y1B- STA. 27+50±, 32.0' LT TO -Y1B- STA. 28+09±, 32.0' LT
 LENGTH = 59' AVERAGE HEIGHT = 12.4 FT MAXIMUM HEIGHT = 17.0 FT

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -Y1B- 27+50±, 32 FT LT, TO STATION -Y1B- 28+09±, 32 FT LT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
 UNIT WEIGHT (γ) = 120 PCF
 FRICTION ANGLE (ϕ) = 30 DEGREES
 COHESION (C) = 0 PSF
 GROUNDWATER ELEVATION = 161 FT±

DO NOT USE A TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -Y1B- 27+50±, 32 FT LT, TO STATION -Y1B- 28+09±, 32 FT LT.

IT MAY BE PREFERRED TO USE A TEMPORARY SOIL NAIL WALL FOR TEMPORARY SHORING FROM STATION -Y1B- 27+50±, 32 FT LT, TO STATION -Y1B- 28+09±, 32 FT LT. FOR TEMPORARY SOIL NAIL WALLS, SEE TEMPORARY SOIL NAIL WALLS PROVISION.

SEE SHEET TMP-157
TEMPORARY SHORING LOCATION NO. (B2-04) ESTIMATED QUANTITY = 1701 SF

-Y1B- STA. 26+20±, 27.0' LT TO -Y1B- STA. 28+09±, 27.0' LT
 LENGTH = 189' AVERAGE HEIGHT = 9.0 FT MAXIMUM HEIGHT = 22.0 FT

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -Y1B- 26+20±, 27 FT LT, TO STATION -Y1B- 28+09±, 27 FT LT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
 UNIT WEIGHT (γ) = 120 PCF
 FRICTION ANGLE (ϕ) = 30 DEGREES
 COHESION (C) = 0 PSF
 GROUNDWATER ELEVATION = 161 FT±

DO NOT USE CANTILEVER, BRACED AND/OR ANCHORED SHORING FOR TEMPORARY SHORING FROM STATION -Y1B- 26+20±, 27 FT LT, TO STATION -Y1B- 28+09±, 27 FT LT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -Y1B- 26+20±, 27 FT LT, TO STATION -Y1B- 28+09±, 27 FT LT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY WALLS.

WHEN BACKFILL FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS OVERLAPS WITH THE REINFORCED ZONE OF TEMPORARY WALLS, USE SHORING BACKFILL OR BACKFILL MATERIAL REQUIRED FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS, WHICHEVER IS BETTER, IN THE REINFORCED ZONE OF TEMPORARY WALLS.

SEE SHEET TMP-158
TEMPORARY SHORING LOCATION NO. (B2-05) ESTIMATED QUANTITY = 656 SF

-Y1B- STA. 30+28±, 32.0' LT TO -Y1B- STA. 30+85±, 32.0' LT
 LENGTH = 57' AVERAGE HEIGHT = 11.5 FT MAXIMUM HEIGHT = 16.0 FT

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -Y1B- 30+28±, 32 FT LT, TO STATION -Y1B- 30+85±, 32 FT LT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
 UNIT WEIGHT (γ) = 120 PCF
 FRICTION ANGLE (ϕ) = 30 DEGREES
 COHESION (C) = 0 PSF
 GROUNDWATER ELEVATION = 162 FT±

DO NOT USE A TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -Y1B- 30+28±, 32 FT LT, TO STATION -Y1B- 30+85±, 32 FT LT.

IT MAY BE PREFERRED TO USE A TEMPORARY SOIL NAIL WALL FOR TEMPORARY SHORING FROM STATION -Y1B- 30+28±, 32 FT LT, TO STATION -Y1B- 30+85±, 32 FT LT. FOR TEMPORARY SOIL NAIL WALLS, SEE TEMPORARY SOIL NAIL WALLS PROVISION.

SEE SHEET TMP-158
TEMPORARY SHORING LOCATION NO. (B2-06) ESTIMATED QUANTITY = 4273 SF

-Y1B- STA. 30+28±, 27.0' LT TO -Y1B- STA. 32+75±, 27.0' LT
 LENGTH = 247' AVERAGE HEIGHT = 17.3 FT MAXIMUM HEIGHT = 23.0 FT

FOR TEMPORARY SHORING AND POSITIVE PROTECTION FOR TEMPORARY SHORING, SEE PLANS AND TEMPORARY SHORING PROVISION.

BEFORE BEGINNING TEMPORARY SHORING DESIGN OR CONSTRUCTION, SURVEY EXISTING GROUND ELEVATIONS IN THE VICINITY OF SHORING LOCATIONS TO DETERMINE ACTUAL SHORING HEIGHTS.

DESIGN TEMPORARY SHORING FROM STATION -Y1B- 30+28±, 27 FT LT, TO STATION -Y1B- 32+75±, 27 FT LT, FOR THE FOLLOWING ASSUMED SOIL PARAMETERS AND GROUNDWATER ELEVATION:
 UNIT WEIGHT (γ) = 120 PCF
 FRICTION ANGLE (ϕ) = 30 DEGREES
 COHESION (C) = 0 PSF
 GROUNDWATER ELEVATION = 162 FT±

DO NOT USE CANTILEVER, BRACED AND/OR ANCHORED SHORING FOR TEMPORARY SHORING FROM STATION -Y1B- 30+28±, 27 FT LT, TO STATION -Y1B- 32+75±, 27 FT LT.

AT THE CONTRACTOR'S OPTION, USE STANDARD TEMPORARY WALL FOR TEMPORARY SHORING FROM STATION -Y1B- 30+28±, 27 FT LT, TO STATION -Y1B- 32+75±, 27 FT LT. SEE GEOTECHNICAL STANDARD DETAIL NO. 1801.02 FOR STANDARD TEMPORARY WALLS.


WHEN BACKFILL FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS OVERLAPS WITH THE REINFORCED ZONE OF TEMPORARY WALLS, USE SHORING BACKFILL OR BACKFILL MATERIAL REQUIRED FOR RETAINING WALLS AND/OR BRIDGE APPROACH FILLS, WHICHEVER IS BETTER, IN THE REINFORCED ZONE OF TEMPORARY WALLS.

3/15/2022
 U:\Traffic\Transportation Management\Plan\TCP\PLAN SHEETS\I-5987B_TMP-2TS8_TEMPORARY_SHORING_NOTES.dgn
 angood


THE TEMPORARY SHORING NOTES SHOWN ON THIS SHEET WERE PROVIDED THROUGH A SEALED DOCUMENT FROM THE GEOTECHNICAL ENGINEER. THE DOCUMENT WAS SUBMITTED TO STANTEC CONSULTING ON (FEB 10, 2022) AND SEALED BY A PROFESSIONAL ENGINEER, (JINYOUNG PARK, Ph.D., P.E.), LICENSE #032171.



Stantec Consulting Services Inc.
 801 Jones Franklin Road
 Suite 300
 Raleigh, NC 27606
 Tel. 919.851.6866
 Fax. 919.851.7024
 www.stantec.com
 License No. F-0672



4/29/2022
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



SECTION 2
TEMPORARY SHORING NOTES
SECTION 2
LOCATIONS B2-01
THRU B2-06