



DMS-3
AT
I-95 (NB)
-L- STA 881+50

NOTES

1. FIELD VERIFY ALL FOOTING ELEVATIONS AND GROUND SLOPES AT THE FOOTING USING THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES. CONTRACTOR IS RESPONSIBLE FOR FURNISHING ELEVATION DRAWINGS FOR ENGINEER'S APPROVAL.
2. USE ACTUAL DIMENSIONS AND WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE.
3. ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING.
4. DESIGN AND CONSTRUCT THE PEDESTAL STRUCTURE AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 110 MPH.
5. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT CABLES DURING CONSTRUCTION.

3/11/2022 8:36:32 AM R:\ITS\665\gmp\plan_sheets\I-5987B\ITS_pch_14_DMS-3_of_MM_36_xsc.dgn

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



Prepared for the Offices of:		I-95 Northbound DMS-3 Elevation (Mile-Marker 36)		SEAL NORTH CAROLINA PROFESSIONAL ENGINEER SEVEN G. HAYNIE
Division 6 Robeson County Lumberton		PLAN DATE: March 2022 REVIEWED BY: S.G. Haynie		
PREPARED BY: O. Drobny		REVIEWED BY: J. S. Cole		DocuSigned by: Steven G. Haynie 3/18/2022
REVISIONS		INIT. DATE		
SIGNATURE		DATE		CADD File name: [unclear]