## SUMMARY OF PILE INFORMATION/INSTALLATION

(Blank entries indicate item is not applicable to structure)

Ful Put					Driven Piles			Predrilling for Piles*			Drilled-In Piles		
End Bent/ Bent No, Pile(s) #-# (e.g., "Bent 1, Piles 1-5")	Factored Resistance per Pile TONS	Pile Cut-Off (Top of Pile) Elevation FT	Estimated Pile Length per Pile FT	Scour Critical Elevation FT	Min Pile Tip (Tip No Higher Than) Elev FT	Required Driving Resistance (RDR)** per Pile TONS	Total Pile Redrives Quantity EACH	Predrilling Length per Pile Lin FT	Predrilling Elevation (Elev Not To Predrill Below) FT	Maximum Predrilling Dia INCHES	Pile Excavation (Bottom of Hole) Elev FT	Pile Exc Not In Soil per Pile Lin FT	Pile Exc In Soil per Pile Lin FT
End Bent No. 1, Piles 1-9	120	188.45	95			200							
End Bent No. 2, Piles 1-9	120	188.40	90			200	1						
Bent No. 1, Piles 1-28	140	168.57	65			235	23						
							_						

<sup>\*</sup>Predrilling for Piles is required for end bents/bents with a predrilling length and at the Contractor's option for end bents/bents with predrilling information but no predrilling length.

## PILE DESIGN INFORMATION

(Blank entries indicate item is not applicable to structure)

End Bent/ Bent No, Pile(s) #-# (e.g., "Bent 1, Piles 1-5")	Factored Axial Load per Pile TONS	Factored Downdrag Load per Pile TONS	Factored Dead Load* per Pile TONS	Dynamic Resistance Factor	Nominal Downdrag Resistance per Pile TONS	Nominal Scour Resistance per Pile TONS	Scour Resistance Factor (Default = 1.00)
End Bent No. 1, Piles 1-9	120			0.60			
End Bent No. 2, Piles 1-9	120			0.60			
Bent No. 1, Piles 1-28	139			0.60			

<sup>\*</sup>Factored Dead Load is factored weight of pile above the ground line.

## NOTES:

- 1. The Pile Foundation Tables are based on the bridge substructure design and foundation recommendations sealed by a North Carolina Professional Engineer (Stephen C. Crockett, 048207) on 12/16/21.
- 2. Total Pile Driving Equipment Setup quantity (not shown in Pile Foundation Tables) equals the number of driven piles, i.e., the number of piles with a Required Driving Resistance.
- 3. The Engineer will determine the need for PDA Testing when PDAs may be required.


## SUIMMARY OF PDA/PILE ORDER LENGTHS

(Blank entries indicate item is not applicable to structure)

PDA Test Pile Length FT	Total PDA Testing Quantity	End Bent/ Bent No(s)	Pile Order Length Basis*
	EACH		EST or PDA
100			
95	2		
70	1		
	95	95 2	95 2

\*EST = Pile order lengths from estimated pile lengths; PDA = Pile order lengths based on PDA testing. For groups of end bents/bents with pile order lengths based on PDA testing, the first end bent/bent no. listed for each group is the representative end bent/bent with the PDA.

> PROJECT NO. <u>I-5987B</u> ROBESON \_COUNTY STATION: <u>-Y1B- 29+51.04/-L- 702+75.43</u>



STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

> PILE FOUNDATION **TABLES**

> > SHEET NO.

SIGNATURE	DATE	REVISIONS				
OCUMENT NOT	CONSIDERED	NO.	BY:	DATE:	NO.	BY:

TOTAL **FINAL UNLESS ALL** SHEETS SIGNATURES COMPLETED

Factored Resistance + Factored Downdrag Load + Factored Dead Load Nominal Scour Resistance  $\frac{1}{-}$  + Nominal Downdrag Resistance +  $\frac{1}{-}$  Scour Resistance Factor Dynamic Resistance Factor