

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**



STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION




ROY COOPER
GOVERNOR

JAMES H. TROGDON, III
SECRETARY

October 15, 2019

MEMORANDUM TO: Brian Hanks, P.E.
State Structures Engineer

ATTENTION: Jacquelyn Bowles, P.E.
Project Engineer

FROM:   John L. Pilipchuk, L.G., P.E.
State Geotechnical Engineer 
52C44B94B8BE444...

STATE PROJECT: 67044.1.1 (BR-0044)
COUNTY: ROCKINGHAM

DESCRIPTION: Replace Bridge No 780168 over Smith River on NC14/NC78

SUBJECT: Geotechnical Recommendations

The Geotechnical Engineering Unit has reviewed and presents the subsurface investigation and foundation recommendations prepared by Summit Design and Engineering Services, PLLC for the above referenced project.

- Roadway Subsurface Investigation (48) pages
- Geotechnical Report - Recommendations (5) pages

Please call John McCray at (919) 707-6890 or David Teague, PE at (919) 707-6877 if there are any questions concerning this memorandum.

Attachment

REFERENCE: BR-0044

PROJECT: 67044

SEE SHEET 2A FOR PLAN SHEET LAYOUT
AT TIME OF INVESTIGATION

CONTENTS

<u>LINE</u>	<u>STATION</u>	<u>PLAN</u>	<u>PROFILE</u>
-L-	10+75 - 33+30	4-6	

CROSS SECTIONS

<u>LINE</u>	<u>STATION</u>	<u>SHEETS</u>
-L-	10+75 - 19+00	7-22
-L-	25+00 - 33+30	23-39

APPENDICES

<u>APPENDIX</u>	<u>TITLE</u>	<u>SHEETS</u>
A	CBR RESULTS	40-44

STATE OF NORTH CAROLINA
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

ROADWAY

SUBSURFACE INVESTIGATION

COUNTY ROCKINGHAM
PROJECT DESCRIPTION BRIDGE NO. 168 ON
NC 14/NC 87 (N. VAN BUREN ROAD) OVER
SMITH RIVER

INVENTORY

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BR-0044	1	48

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (919) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

- THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.
- BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

PERSONNEL

B. SMITH, PG

A. GROSS, PG

A. RULEY, GIT

M. SHIPMAN, EI

L. GONZALEZ

O. STANLEY

INVESTIGATED BY B. SMITH, PG

DRAWN BY B. SMITH, PG

CHECKED BY B. WORLEY, PG


SUBMITTED BY B. SMITH, PG

DATE OCTOBER, 2019

Prepared in the
Office of:



NC FIRM LICENSE No: P-0339 and C-487
504 Meadowlands Drive
Hillsborough, NC 27278
(919) 732-3883
(919) 732-6676 (FAX)



DocuSigned by:

BE61A49304C542E...

10/16/2019

SIGNATURE

DATE

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION GRADATION ROCK DESCRIPTION TERMS AND DEFINITIONS
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT...
GRADATION WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.
ROCK DESCRIPTION HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED, AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL...
TERMS AND DEFINITIONS ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.

09_08/99

C:\Users\brgett\OneDrive\Desktop\BR0044_GEO_RDWY_Inventory\REV\Summit\CADD_GEO\TECH\Plan\Pr of BR0044_GEO_inv_2A.dgn
30-SEP-2019 14:50
C:\Users\brgett\OneDrive\Desktop\BR0044_GEO_RDWY_Inventory\REV\Summit\CADD_GEO\TECH\Plan\Pr of BR0044_GEO_inv_2A.dgn
\$\$\$\$\$SERVNAME\$\$\$\$

TIP PROJECT: BR-0044

CONTRACT:


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

ROCKINGHAM COUNTY

**LOCATION: BRIDGE NO. 168 ON NC 14/NC 87
(N. VAN BUREN ROAD) OVER
SMITH RIVER**

**TYPE OF WORK: GRADING, DRAINAGE, PAVING,
AND STRUCTURE**


STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	BR-0044	2A	48
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION	
67044.1.1		PE	



VICINITY MAP


See Sheet 1A For Index of Sheets
See Sheet 1B For Conventional Symbols

25% ROADWAY PLANS
JANUARY 30, 2019



CLEARING ON THE PROJECT SHALL BE TO THE LIMITS
ESTABLISHED USING METHOD _____
THIS PROJECT IS NOT WITHIN ANY MUNICIPAL BOUNDARIES

INCOMPLETE PLANS
DO NOT USE FOR R/W ACQUISITION
DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED



DESIGN DATA

ADT 2020 =	8,080
ADT 2040 =	8,400
K =	9 %
D =	55 %
T =	12 % *
V =	60 MPH
* (TTST 10%+DUAL 2%)	
FUNC CLASS=PRINCIPAL ARTERIAL	
REGIONAL TIER	

PROJECT LENGTH

LENGTH ROADWAY TIP PROJECT BR-0044 =	0.328 MI
LENGTH STRUCTURE TIP PROJECT BR-0044 =	0.099 MI
TOTAL LENGTH TIP PROJECT BR-0044 =	0.427 MI

AECOM
NC FIRM LICENSE No: F-0342
701 Corporate Center Drive, Suite 475
Raleigh, NC 27607
(919) 854-6200 - (919) 854-6259(FAX)

2018 STANDARD SPECIFICATIONS

RIGHT OF WAY DATE: APRIL 16, 2019

LETTING DATE: JANUARY 21, 2020

NEIL J. DEAN, P.E.
PROJECT ENGINEER

RADHA ATTALURI, P.E.
PROJECT DESIGN ENGINEER


DAVID STUTTS, P.E.
NCDOT PROJECT MANAGER


HYDRAULICS ENGINEER

SIGNATURE: _____ P.E.

ROADWAY DESIGN ENGINEER

SIGNATURE: _____ P.E.





919.732.3883 SUMMIT-ENGINEER.COM
504 Meadowland Drive, Hillsborough, NC 27278

October 9, 2019

WBS Number: 67044.1.1
 TIP Number: BR-0044
 Project ID: 34624
 County: Rockingham
 Description: Bridge No. 168 on NC 14/NC 87 (N. Van Buren Road) over Smith River

SUBJECT: Geotechnical Report - Roadway Subsurface Inventory

Project Description

The proposed 0.427-mile project is located just outside the municipal boundaries of Eden. The project will involve the replacement of Bridge No. 168 on NC 14/NC 87. The new bridge is currently proposed to be constructed approximately 45 feet north of the existing bridge. To accommodate the new bridge location, 0.328-miles of new roadway alignment and widening is proposed on NC 14/NC 87. The proposed earthworks are significant in some areas of the project corridor with some cut and fill sections exceeding 25 feet.

The geotechnical investigation was conducted from May 20, 2019 to June 13, 2019. Borings were advanced using a CME-550X drill machine equipped with an automatic hammer. Drill tooling was advanced using 3.25-inch hollow-stem augers. One hand auger was advanced at a boring location deemed to be inaccessible for the drill rig. Standard Penetration Tests (SPT) were performed at all other planned boring locations to provide subsurface information for roadway foundation and slope design/construction. Undisturbed samples were obtained in areas of significant proposed fill placement. No rock coring was performed during the roadway investigation. All investigations and reporting were performed in accordance with the NCDOT Geotechnical Engineering Unit’s 2016 “Geotechnical Investigation and Recommendations Manual.”

At the time of this report, 10 of the proposed 12 structure borings have been drilled as part of the geotechnical investigation for the new bridge. One structure boring, EB2-B, was determined to be useful to the roadway investigation and is included within this report. The remainder of the structure boring data will be available in the Structure Subsurface Investigation Report which will be turned in by Summit under a separate cover and at a later date.

The following alignments were investigated for this project:

<u>Alignment</u>	<u>Station(±)</u>
-L-	10+75.00 - 33+30.00

Physiography, Geography, and Geology

The project is located in far north-central North Carolina within the Piedmont Physiographic Province. Topography in the project area is characterized by gently rolling, well rounded hills and long low ridges with a couple hundred feet of elevation difference between the hills and valleys. In general, the topography within the project corridor would fit this description. Elevations along the project range from approximately 690 feet to approximately 540 feet above sea level. The topographic high occurs near the top of the first cut on the project at approximately 11+00, 100’LT. The topographic low occurs within the floodplain of the Smith River.

The project corridor is located within the Roanoke River Basin and it intersects the Smith River. River flow is now mostly controlled by an upstream dam near Martinsville, Virginia. Previous flooding events have led to the formation of a floodplain that is believed to reach approximately 600 feet in width where it intersects the centerline of the project. The river flows south from the project where it eventually merges with the Dan River. One unnamed tributary was observed within the project corridor at 15+29, 78’LT. It flows north where it eventually merges into the Smith River.

Geologically, the project corridor is located within the Sauratown Mountains Anticlinorium. The underlying bedrock consists of a complex mixture of metamorphic rock that has repeatedly been compressed, fractured, faulted, and folded. The rocks within this area are believed to be of a similar origin and age to the rocks found within the Western Blue Ridge. The eastern end of the project corridor falls within a mile of the western boundary of the Dan River Triassic Basin.

Soil Properties

Residual soils, soils derived from the weathering of rock, are the dominant soil origin within the project corridor. In general, the Residual soils underlying the project follow the typical weathering profile observed throughout the piedmont. The clays, when present, are usually found closer to the ground surface. The silts and sands are typically found deeper and closer to the parent rock source. However, much like the parent rocks that they weather from, the Residual soils can vary significantly in some areas in both composition and vertical/horizontal distribution. The compositional boundaries (also known as contacts) within the Residual soils are shown in the graphical section of this report as dashed lines. However, in reality, the contacts are much more likely gradational in nature. Meaning that the compositional changes between clay, silt, and sand occur gradually and over some vertical/horizontal distance. Highly plastic Residual clays (Plasticity Index value greater than 26) can be problematic during construction. They can negatively affect embankment stability, embankment settlement, subgrade stability, and may not be suitable for use as embankment material on the project.

Residual silty and sandy clays are prevalent throughout the project corridor and are typically present within 6 feet of the ground surface. They are generally not saprolitic and contain less visible mica than the silts and sands. SPT results in the Residual clays showed soil densities typically range from medium

stiff to stiff. No highly plastic clays were encountered during the investigation. Below is a summary of the results of laboratory testing conducted on the Residual clays present within the project corridor:

<u>Sample No.</u>	<u>Liquid Limit (L.L.)</u>	<u>Plasticity Index (P.I.)</u>	<u>Natural Moisture</u>	<u>Passing # 200 Sieve</u>	<u>AASHTO Classification</u>
SS-1	43	18	20.0%	58%	A-7-6
SS-2	47	15	21.2%	49%	A-7-5
SS-11	47	21	17.3%	72%	A-7-6
SS-20	45	18	37.5%	53%	A-7-6
SS-21	59	23	41.6%	77%	A-7-5
SS-34	41	21	15.6%	54%	A-7-6
SS-35	28	12	15.7%	51%	A-6
SS-90	34	16	12.9%	44%	A-6
SS-62	34	15	18.7%	51%	A-6
AVERAGES	42	18	22.3%	57%	

Residual clayey and sandy silts are common throughout the project corridor and typically underlie the clays. These soils can be saprolitic and are usually micaceous. SPT results in the Residual silts showed soil densities that typically ranged from medium stiff to stiff with some soft and very stiff areas. Softer areas typically corresponded with areas of higher moisture content. Below is a summary of the results of laboratory testing conducted on the Residual silts present within the project corridor:

<u>Sample No.</u>	<u>Liquid Limit (L.L.)</u>	<u>Plasticity Index (P.I.)</u>	<u>Natural Moisture</u>	<u>Passing # 200 Sieve</u>	<u>AASHTO Classification</u>
SS-12	36	2	18.0%	52%	A-4
SS-13	29	0	14.8%	43%	A-4
SS-24	25	2	13.2%	51%	A-4
SS-66	25	8	17.2%	48%	A-4
SS-91	48	8	22.9%	72%	A-5
AVERAGES	33	4	17.2%	53%	

Residual silty sands are also common throughout the project corridor and typically underlie the clays and/or silts. The sands are generally saprolitic and micaceous with trace to little amounts of gravel-sized crystalline rock fragments. SPT results in the Residual sands showed soil densities that typically ranged from loose to dense with some very loose and very dense areas. Below is a summary of the results of laboratory testing conducted on the Residual sands:

<u>Sample No.</u>	<u>Liquid Limit (L.L.)</u>	<u>Plasticity Index (P.I.)</u>	<u>Natural Moisture</u>	<u>Passing # 200 Sieve</u>	<u>AASHTO Classification</u>
SS-3	38	0	12.5%	33%	A-2-4
SS-28	30	2	8.4%	25%	A-2-4
AVERAGES	34	1	10.5%	29%	

Alluvial soils, soils that have been transported and deposited by water, were encountered within the project corridor. Alluvial deposition typically occurs in topographically low areas. These soils are often very near or even below the water table and are typically wet to saturated. As a consequence of their high moisture content and nature of deposition, alluvial soils typically exhibit very soft to soft/very loose to loose soil densities. They also can contain highly plastic clays and sometimes significant amounts of organic matter. Depending on their characteristics, Alluvial soils can be problematic during and after construction. They can negatively impact embankment stability, embankment settlement, and subgrade stability.

Alluvial silty and sandy clays were commonly encountered within the floodplain of the Smith River. SPT results in the Alluvial clays showed soil densities that typically ranged from medium stiff to stiff. Below is a summary of the results of laboratory testing conducted on the Alluvial clays present within the project corridor:

<u>Sample No.</u>	<u>Liquid Limit (L.L.)</u>	<u>Plasticity Index (P.I.)</u>	<u>Natural Moisture</u>	<u>Passing # 200 Sieve</u>	<u>AASHTO Classification</u>
SS-31	41	14	25.0%	73%	A-7-6
SS-38	41	14	28.6%	57%	A-7-6
SS-42	44	17	21.1%	45%	A-7-6
AVERAGES	42	15	24.9%	58%	

Alluvial sandy silts are also present within the floodplain. SPT results in the Alluvial silts showed soil densities that typically ranged from medium stiff to stiff. Below is a summary of the results of the laboratory testing conducted on the Alluvial silts present within the project corridor:

<u>Sample No.</u>	<u>Liquid Limit (L.L.)</u>	<u>Plasticity Index (P.I.)</u>	<u>Natural Moisture</u>	<u>Passing # 200 Sieve</u>	<u>AASHTO Classification</u>
SS-33	30	9	20.5%	53%	A-4
SS-39	32	8	20.9%	48%	A-4
AVERAGES	31	9	20.7%	51%	

Alluvial silty sands were also encountered within the floodplain but were not laboratory tested. These sands were typically field classified as moist to wet and SPT results showed soil densities were typically loose. Approximate locations where Alluvial soils are believed to be present within the project corridor will be highlighted in the “Areas of Special Geotechnical Interest” section of this text report.

Roadway Embankment soils from the construction of existing NC 14/NC 87 are present throughout the project corridor. Roadway Embankment soils are often quite similar to the local Residual soils that they are typically sourced from. However, they often have a “reworked” appearance, with a large variation in grain size. They can contain little to trace amounts of organic material, gravel, cobbles, boulders and/or other types of debris. If properly constructed, Roadway Embankment soils typically do not present major issues during future construction projects. However, some older Roadway Embankment fills across the state can be poorly compacted, contain highly plastic clays, perched water, and even miscellaneous debris such as tree trunks.

Roadway Embankment sandy and clayey silts were the predominate soil type found within the existing embankment fills of NC 14/NC 87. SPT results in the Roadway Embankment silts showed soil densities that typically range from medium stiff to stiff. Below is a summary of the results of the laboratory testing conducted on the Roadway Embankment silts present within the project corridor:

Sample No.	Liquid Limit (L.L.)	Plasticity Index (P.I.)	Natural Moisture	Passing # 200 Sieve	AASHTO Classification
S-1	35	0	18.6%	40%	A-4
SS-81	32	3	22.2%	43%	A-4
SS-70	32	0	20.3%	41%	A-4
AVERAGES	33	1	20.4%	41%	

Silty sands were also encountered within the Roadway Embankment but were not laboratory tested. They were typically found immediately below the existing pavement structure. These sands were typically field classified as dry and SPT results indicated densities ranging from medium dense to dense.

Rock Properties

Crystalline and Weathered Rock were encountered in several areas within the project corridor. Analysis of rock fragments retrieved from SPT testing seemed to indicate that the underlying bedrock mostly consists of a Biotite Gneiss and/or Schist. This schist may be interlayered with metagraywacke in some areas.

Crystalline Rock was not encountered within 6 feet of proposed grade during the investigation and is not anticipated to be a major factor during the construction of the roadway. However, this does not guarantee that it won't be encountered in some small areas during construction. The interlayering of compositionally different rock types and repeated past deformation events have caused fracturing, faulting, and folding of these rock units. This combined with differential weathering occurring over millions of years could cause the Crystalline Rock "line" to be quite erratic and unpredictable in some areas.

Weathered Rock was encountered within 6 feet of proposed grade in a few areas. It is in these areas that the chances of encountering small areas of Crystalline Rock are greatest. Because of this, approximate locations where Weathered Rock is believed to be present within six feet of proposed grade will be highlighted in the "Areas of Special Geotechnical Interest" section of this text report. Along that same line of thinking, small areas of Weathered Rock could be encountered within cuts that are believed to primarily be through Residual soil.

Groundwater Properties

The field investigation was conducted during a period of average rainfall. Groundwater was only encountered in 3 of the 17 total borings. Top of water table elevations varied from 594.6 feet to 542.9 feet above sea level. An average water table elevation of 571.5 feet above sea was calculated within the project corridor. Below is a summary of the locations and elevations groundwater was encountered within the project corridor:

Boring ID	Station(±)	Offset	Elevation(ft)
L_1400LT	14+00	50'LT	594.6
L_1478LT	14+78	81'LT	577.0
L_2500LT	25+00	40'LT	542.9

On the western side of the Smith River, groundwater was encountered in two borings (L_1400LT & L_1478LT). Both borings were down in a low area near the headwaters of a small tributary that flows north and eventually empties into the Smith River. In the floodplain on the east side of the river, groundwater was encountered within one boring (L_2500LT). While it was only encountered in only one boring, groundwater is believed to be present throughout most of the floodplain. This is mostly due to the numerous borings within the floodplain that caved immediately after drilling. The caving was likely the result of wet and unstable soils that could not handle the tripping out of the drill tooling. Groundwater was not encountered within six feet of proposed grade is not anticipated to be a factor during construction of the roadway. However, it could be a factor for any potential undercut for embankment stability in the floodplain or the low area from 14+00 - 15+00 left.

A visual reconnaissance for water wells was conducted throughout the project corridor. This was used in conjunction with the final survey file to attempt to identify water wells within or adjacent to the proposed right of way of the project. Properly abandoned wells are not included in the following list. Some water well locations are well hidden, and it is possible that some wells were missed or misidentified by the final survey and/or visual reconnaissance. The following water wells were identified within the project corridor:

Alignment	Station(±)	Offset
-L-	17+16	38'LT

Areas of Special Geotechnical Interest

Alluvial Soils - During the geotechnical investigation, areas of Alluvial soils were observed and encountered. Alluvial soils can be problematic during and after construction. They can negatively impact embankment stability, embankment settlement, and subgrade stability. More detailed information on these soils can be found in the "Soil Properties" section of this text report. The following approximate locations listed below show areas where Alluvial soils are believed to be present within the project corridor:

Alignment	Station(±)	Offset
-L-	18+89- 29+32	Left & Right

Weathered Rock - During the geotechnical investigation, Weathered Rock was encountered in several areas. Weathered Rock could present issues with excavation during construction, especially if unanticipated areas of Crystalline Rock are present within these zones. More detailed information on the rocks underlying the project corridor can be found in the "Rock Properties" section of this text report. The following approximate locations listed below show areas where Weathered Rock is believed to be present within six feet of proposed grade:

<u>Alignment</u>	<u>Station(±)</u>	<u>Offset</u>
-L-	10+75 - 11+25	Left & Right
-L-	16+75 - 18+50	Left

Appendix A

Bulk Samples – California Bearing Ratio (CBR)

L_1100LT
 (-L-) 11+00, 100'LT
 0.0 – 15.0 ft.
 S – 1


L_1800LT
 (-L-) 18+00, 20'LT
 0.0 – 15.0 ft.
 S – 2

References

North Carolina Geological Survey, 1985, Geologic map of North Carolina: North Carolina Geological Survey, General Geologic Map, scale 1:500000.

The Geology of the Carolinas, J. Wright Horton, Jr., and Victor A. Zullo

Groundwater Science, Charles R. Fitts



DocuSigned by:

 BE61A49304C542E...

Respectfully Submitted,



Brett Smith, PG
 Project Geologist
 Summit Design and Engineering Services, PLLC

PROJECT REFERENCE NO. <i>BR-0044</i>	SHEET NO. <i>4</i>
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
Prepared in the Office of: AECOM NC FIRM LICENSE No F-0342 101 Corporate Center Drive, Suite 475 Raleigh, NC 27607 (919) 854-6200 • (919) 854-6259(FAX)	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	




REVISIONS
 20-SEP-2019 14:53
 2044_GEOLOGY-2019-1453-REV1_Summ.t\CADD_GEOTECH.PlanPrOf\BR0044_GEO.inv.04.dgn

5/14/99

PROJECT REFERENCE NO. BR-0044	SHEET NO. 5
RW SHEET NO.	HYDRAULICS ENGINEER
ROADWAY DESIGN ENGINEER	ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
Prepared in the Office of: AECOM 101 Corporate Center Drive, Suite 4175 Raleigh, NC 27607 (919) 854-6200 • (919) 854-6259 FAX	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	

5/14/99
 REVISIONS
 05-OCT-2019 09:46
 .GEO_Plan_V2_SUMMIT_CADD_GEO_V2.dgn
 BR0044_GEO_Plan_V2_SUMMIT_CADD_GEO_V2.dgn





REVISIONS

MATCHLINE -L- STA 15+00
SEE SHEET 4

MATCHLINE -S- STA 29+00
SEE SHEET 6

PAVEMENT REMOVAL

PROJECT REFERENCE NO. BR-0044	SHEET NO. 6
RW SHEET NO.	
ROADWAY DESIGN ENGINEER	HYDRAULICS ENGINEER
INCOMPLETE PLANS DO NOT USE FOR R/W ACQUISITION	
Prepared in the Office of: AECOM <small>NC FIRM LICENSE No F-0342 101 Corporate Center Drive, Suite 475 Raleigh, NC 27607 (919) 854-6200 • (919) 854-6259(FAX)</small>	
DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED	




REVISIONS
 5/14/99
 02-OCT-2019 15:36
 2044_GEO-CONV-CADD-REV1_Summ.t\CADD_GEO-CONV-06.dgn

02-OCT-2019 15:36
 2044_GEO-CONV-CADD-REV1_Summ.t\CADD_GEO-CONV-06.dgn




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



09-OCT-2019 14:31
 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_Inventor\REV2_Summit\CADD_GEO\TECH\ssc_BR0044_GEO_xsi.L(7-22).dgn
 6/23/16


- (A) ROADWAY EMBANKMENT: brown and white, moist, medium dense, silty SAND (A-2-4) with little mica
- (B) RESIDUAL: red to red-brown, moist, stiff, slightly to moderately plastic, highly sandy, silty CLAY (A-7-5/A-7-6)
- (D) RESIDUAL: brown, tan, and white, dry, loose to very dense, saprolitic, silty SAND (A-2-4) with trace to some mica
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-1	100'LT	11+00	0.0' - 1.5'	A-7-6(8)	43	18	19.0	23.5	14.0	43.5	92	82	58	20.0	N/A
SS-2	100'LT	11+00	3.8' - 5.3'	A-7-5(5)	47	15	23.9	28.1	16.6	31.4	87	74	49	21.2	N/A
SS-3	100'LT	11+00	8.8' - 10.3'	A-2-4(0)	38	0	31.6	42.9	15.7	9.8	89	73	33	12.5	N/A
S-1	100'LT	11+00	0.0' - 15.0'	A-4(0)	32	3	27.4	33.4	23.9	15.3	93	78	45	N/A	N/A



SS-1
 SS-2
 SS-3
 S-1
 L 1100'LT
 11+00
 100'LT
 100/0.9
 100/0.6
 100/0.8
 B.T
 DRY
 (05/19)


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



09-OCT-2019 14:33
 L:\USERS\j\j\Projects\BR0044\Desk_top\BR0044_GEO_PD\W\Inventory\REV2_Summit\CADD_GEO\TECH\ssc_BR0044_GEO_xsi.L (7-22).dgn
 6/23/16

- (A) ROADWAY EMBANKMENT: brown and white, moist, medium dense, silty SAND (A-2-4) with little mica
- (B) RESIDUAL: red-brown, moist, stiff, moderately plastic, silty CLAY (A-7-6) with some sand
- (C) RESIDUAL: orange, moist, medium stiff to stiff, saprolitic, sandy SILT (A-4) with little to some clay
- (D) RESIDUAL: tan and white, dry to wet, loose to very dense, saprolitic, silty SAND (A-2-4) with trace to little mica
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-11	100'LT	12+00	0.0' - 1.5'	A-7-6(15)	47	21	12.1	19.2	16.1	52.5	98	93	72	17.3	N/A
SS-12	100'LT	12+00	4.0' - 5.5'	A-4(0)	36	2	17.3	33.4	20.6	28.6	88	80	52	18.0	N/A
SS-13	100'LT	12+00	9.0' - 10.5'	A-4(0)	29	0	26.5	40.3	19.2	14.0	98	84	43	14.8	N/A



SS-11
 SS-12
 SS-13
 L 1200LT
 12+00
 100'LT

B:T
 DRY
 (05/19)

12 + 00.00
 -L-




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

(F) ROADWAY EMBANKMENT: brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay


(B) RESIDUAL: brown, wet to saturated, stiff to very stiff, moderately plastic, highly sandy, silty CLAY (A-7-6)

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
S-1	50'LT	14+00	0.0' - 1.0'	A-4(0)	35	0	30.2	34.1	20.2	15.5	90	74	40	18.6	N/A




(A) ROADWAY EMBANKMENT: brown and white, moist, medium dense, silty SAND (A-2-4) with little mica

(C) RESIDUAL: orange, moist, medium stiff to stiff, saprolitic, sandy SILT (A-4) with little to some clay






150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



- (F) ROADWAY EMBANKMENT: brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay
- (B) RESIDUAL: brown to red-brown, moist to wet, medium stiff to stiff, moderately plastic, silty CLAY (A-7-5/A-7-6) with some sand
- (C) RESIDUAL: brown and gray, wet to saturated, soft, saprolitic, sandy SILT (A-4)

09-OCT-2019 14:37
 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_Inventor\REV2_Summit\CADD_GEO\TECH\ssc\BR0044_GEO_xsi.L (7-22).dgn
 6/23/16




- (F) ROADWAY EMBANKMENT: brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay
- (B) RESIDUAL: brown to red-brown, moist to wet, medium stiff to stiff, moderately plastic, silty CLAY (A-7-5/A-7-6) with some sand
- (C) RESIDUAL: brown and gray, wet to saturated, soft, saprolitic, sandy SILT (A-4)
- (G) CRYSTALLINE ROCK: (Biotite Gneiss/Schist)

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-20	8'LT	14+78	0.0' - 1.5'	A-7-6(7)	45	18	19.1	18.8	21.7	40.4	79	71	53	37.5	N/A
SS-21	8'LT	14+78	3.2' - 4.7'	A-7-5(20)	59	23	9.7	20.6	24.5	45.3	100	95	77	41.6	N/A

Note: Due to the elevation difference, stratigraphy could not be drawn through the offset boring. Boring data was projected onto the cross section.

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




- (F) ROADWAY EMBANKMENT: brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay
- (B) RESIDUAL: brown to red-brown, moist, medium stiff to stiff, moderately plastic, silty CLAY (A-7-5/A-7-6) with some sand
- (C) RESIDUAL: brown, red-tan, and gray, dry, soft to very stiff, saprolitic, sandy SILT (A-4) with some clay
- (D) RESIDUAL: tan, dry, medium dense to very dense, highly micaceous, saprolitic, silty SAND (A-2-4)

09-OCT-2019 14:39
C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_Inventory\REV2_Summit\CADD_GEO\TECH\ssc_BR0044_GEO_xsi.L (7-22).dgn

15 + 50.00
— L —

6/23/16




PROJ. REFERENCE NO.

BR-0044

SHEET NO.


16




- (F) **ROADWAY EMBANKMENT:** brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay
- (C) **RESIDUAL:** red-tan, dry, very stiff, saprolitic, sandy SILT (A-4) with some clay
- (D) **RESIDUAL:** tan, dry, medium dense to very dense, highly micaceous, saprolitic, silty SAND (A-2-4)

09-OCT-2019 14:40
G:\Users\lupic\Documents\2016\Projects\BR0044\GEO\REV2_Summit\CADD\GEO\TECH\sec_BR0044_GEO_xsi.L(7-22).dgn
300SUBSERIAL#16


16 + 00.00



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



09-OCT-2019 14:41
 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_Inventor\REV2_Summit\CADD_GEO\TECH\SSC\BR0044_GEO_xsi.L (7-22).dgn
 SSUBSERNAME\$33



- (F) ROADWAY EMBANKMENT: brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay.
- (C) RESIDUAL: red-tan, dry, very stiff, saprolitic, sandy SILT (A-4) with some clay
- (D) RESIDUAL: tan, dry, medium dense to very dense, highly micaceous, saprolitic, silty SAND (A-2-4)
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-28	10'LT	17+00	4.0' - 5.5'	A-2-4(0)	30	2	23.3	55.9	13.7	7.1	71	64	25	8.4	N/A

SS-28

L_1700LT
17+00
10'LT


BT
DRY
(05/19)

17 + 00.00

— L —




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



- (F) **ROADWAY EMBANKMENT:** brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay
- (C) **RESIDUAL:** red-tan, dry to moist, medium stiff to very stiff, sandy SILT (A-4) with some clay
- (D) **RESIDUAL:** red-white and tan, dry, medium dense to very dense, highly micaceous, saprolitic, silty SAND (A-2-4)
- (E) **WEATHERED ROCK:** (Biotite Gneiss/Schist)


17 + 50.00




09-OCT-2019 14:47
 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO\PDWY\Inventory\REV2_Summit\CADD_GEO\TECH\ssc_BR0044_GEO_xsi.L (7-22).dgn
 6/23/16


- (F) ROADWAY EMBANKMENT: brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay
- (C) RESIDUAL: tan, moist, medium stiff, sandy SILT (A-4) with some clay
- (D) RESIDUAL: red-white, dry, medium dense, silty SAND (A-2-4)
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-24	20'LT	18+00	0.0' - 1.5'	A-4(0)	25	2	17.8	41.4	17.0	23.8	98	91	51	13.2	NA
S-2	20'LT	18+00	0.0' - 8.9'	A-4(0)	27	1	23.7	44.4	18.3	13.6	90	78	38	NA	NA






150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



- (F) ROADWAY EMBANKMENT: brown, moist, medium stiff to stiff, sandy SILT (A-4) with little clay
- (C) RESIDUAL: tan, moist, medium stiff, sandy SILT (A-4) with some clay
- (D) RESIDUAL: red-white, dry, medium dense, silty SAND (A-2-4)
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)

18+50.00



09-OCT-2019 14:48
C:\Users\jgarcia\OneDrive\Documents\18+50.00\18+50.00.dwg
C:\Users\jgarcia\OneDrive\Documents\18+50.00\18+50.00.dwg


09-OCT-2019 14:49
 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_Inventor\REV2_Summit\CADD_GEO\TECH\ssc\BR0044_GEO_xsi.L (7-22).dgn
 33 SUBSTRATE



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

- (F) **ROADWAY EMBANKMENT:** tan to red-brown, moist to wet, soft to stiff, sandy SILT (A-4) with little to some mica
- (H) **ALLUVIAL:** brown, dry, loose, micaceous, silty SAND (A-2-4)
- (I) **ALLUVIAL:** brown, moist to wet, medium stiff to stiff, slightly plastic, highly sandy, silty CLAY (A-7-6)
- (D) **RESIDUAL:** tan, moist, dense to very dense, saprolitic, silty SAND (A-2-4) with little to some mica
- (E) **WEATHERED ROCK:** (Biotite Gneiss/Schist)
- (G) **CRYSTALLINE ROCK:** (Biotite Gneiss/Schist)

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-31	100'LT	19+00	3.5' - 5.0'	A-7-6(10)	41	14	1.6	36.2	25.6	36.7	97	96	73	25.0	NA




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

- (F) ROADWAY EMBANKMENT: red, brown, and tan, moist to wet, soft to very stiff, sandy SILT (A-4) with little clay, trace mica and gravel
- (H) ALLUVIAL: brown, moist to wet, loose, silty SAND (A-2-4) with little mica
- (J) ALLUVIAL: brown, moist to wet, medium stiff, sandy SILT (A-4) with some clay and trace organics
- (I) ALLUVIAL: gray, wet, medium stiff, sandy CLAY (A-6) with some mica and trace organics
- (D) RESIDUAL: brown and white, saturated, dense to very dense, saprolitic, silty SAND (A-2-4) with little mica and gravel-sized rock fragments
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)
- (G) CRYSTALLINE ROCK: (Biotite Gneiss/Schist)

SOIL TEST RESULTS

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-33	40'LT	25+00	3.9' - 5.4'	A-4(2)	30	9	14.2	39.0	14.0	32.9	99	96	53	20.5	NA




Note: EB2-B was drilled during the bridge investigation.

6/23/16
09-OCT-2019 14:52
C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY\Inventory\REV2_Summit\CADD_GEO\TECH\ssc_BR0044_GEO_xsi_L(23-39).dgn
SUBSEQUENT



PROJ. REFERENCE NO.	SHEET NO.
BR-0044	24




- (F) ROADWAY EMBANKMENT: red, brown, and tan, moist to wet, soft to very stiff, sandy SILT (A-4) with little clay, trace mica and gravel
- (H) ALLUVIAL: brown, moist to wet, loose, silty SAND (A-2-4) with little mica
- (J) ALLUVIAL: brown, moist to wet, medium stiff, sandy SILT (A-4) with some clay and trace organics
- (I) ALLUVIAL: gray, wet, medium stiff, sandy CLAY (A-6) with some mica and trace organics
- (D) RESIDUAL: brown and white, saturated, dense to very dense, saprolitic, silty SAND (A-2-4) with little mica and gravel-sized rock fragments
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)
- (G) CRYSTALLINE ROCK: (Biotite Gneiss/Schist)

25 + 50.00


-L-

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



- (A) ROADWAY EMBANKMENT: black, gray, and red-brown, dry, dense, silty SAND (A-2-4) with little gravel
- (F) ROADWAY EMBANKMENT: red, brown, and tan, moist to wet, soft to stiff, sandy SILT (A-4) with little clay and trace mica
- (I) ALLUVIAL: red-brown, brown, and gray, moist to wet, medium stiff, slightly plastic, highly sandy, silty CLAY (A-7-6) with trace mica
- (J) ALLUVIAL: brown, moist to wet, medium stiff to stiff, sandy SILT (A-4) with some clay
- (D) RESIDUAL: brown, gray, and white, wet to saturated, very loose to very dense, highly micaceous, saprolitic, silty SAND (A-2-4) with little mica and gravel-sized rock fragments
- (E) WEATHERED ROCK: (Biotite Schist)


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



09-OCT-2019 14:56
 L:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_InventoryREV2_Summit\CADD_GEO\TECH\ssc\BR0044_GEO_xsi.L (23-39).dgn
 33 SUBSEQUENT

- (A) ROADWAY EMBANKMENT: black, gray, and red-brown, dry, dense, silty SAND (A-2-4) with little gravel
- (F) ROADWAY EMBANKMENT: red, brown, and tan, moist to wet, soft to stiff, sandy SILT (A-4) with little clay and trace mica
- (I) ALLUVIAL: red-brown, brown, and gray, moist to wet, medium stiff, slightly plastic, highly sandy, silty CLAY (A-7-6) with trace mica
- (J) ALLUVIAL: brown, moist to wet, stiff, sandy SILT (A-4) with some clay
- (D) RESIDUAL: brown to gray, wet, very loose, highly micaceous, silty SAND (A-2-4)
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)
- (G) CRYSTALLINE ROCK: (Biotite Gneiss/Schist)


SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-38	30'LT	26+94	0.0' - 1.5'	A-7-6(6)	41	14	16.0	27.2	14.9	42.0	89	82	57	28.6	NA
SS-39	30'LT	26+94	4.3' - 5.8'	A-4(2)	32	8	13.8	45.2	10.0	31.0	98	96	48	20.9	NA
SS-81	30'RT	27+00	3.9' - 5.4'	A-4(0)	32	3	28.4	31.4	20.8	19.4	92	77	43	22.2	NA



27 + 00.00

-L-

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




- (A) ROADWAY EMBANKMENT: black, gray, and red-brown, dry, dense, silty SAND (A-2-4) with little gravel
- (F) ROADWAY EMBANKMENT: red, brown, and tan, moist to wet, soft to stiff, sandy SILT (A-4) with little clay and trace mica
- (I) ALLUVIAL: red-brown, brown, and gray, moist to wet, medium stiff, slightly plastic, highly sandy, silty CLAY (A-7-6) with trace mica
- (J) ALLUVIAL: brown, moist to wet, stiff, sandy SILT (A-4) with some clay
- (D) RESIDUAL: brown to gray, wet, very loose, highly micaceous, silty SAND (A-2-4)
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)
- (G) CRYSTALLINE ROCK: (Biotite Gneiss/Schist)

27 + 50.00


-L-

6/23/16
09-OCT-2019 14:57
L:\Users\jg\Documents\2019\Projects\BR0044\GEO_PDWY\Inventory\REV2_Summit\CADD_GEO\TECH\sec_BR0044_GEO_xsi.L (23-39).dgn
SUBSEQUENT




- (A) ROADWAY EMBANKMENT: brown, white, black, gray, and red-brown, dry, medium dense to dense, silty SAND (A-2-4) with little gravel
- (F) ROADWAY EMBANKMENT: red-brown, tan, and gray, moist to wet, soft to stiff, sandy SILT (A-4) and clayey SILT (A-5) with little to trace mica, gravel, and organics
- (I) ALLUVIAL: red-brown, brown, and gray, moist to wet, medium stiff to stiff, slightly to moderately plastic, highly sandy, silty CLAY (A-7-6) with trace mica
- (J) ALLUVIAL: brown, moist to wet, stiff, sandy SILT (A-4) with some clay
- (D) RESIDUAL: brown to gray, wet, very loose, highly micaceous, silty SAND (A-2-4)
- (E) WEATHERED ROCK: (Biotite Gneiss/Schist)



28 + 00.00



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




09-OCT-2019 14:59
 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_Inventory\REV2_Summit\CADD_GEO\TECH\SSO\BR0044_GEO_xsi.L (23-39).dgn
 33 SUBSTRATE





- (A) ROADWAY EMBANKMENT: gray, white, and brown, dry, medium dense, silty SAND (A-2-4) with little gravel
- (F) ROADWAY EMBANKMENT: red-brown, tan, and gray, moist to wet, medium stiff, sandy SILT (A-4) and clayey SILT (A-5) with little to trace mica, gravel, and organics
- (I) ALLUVIAL: red-brown, moist to wet, medium stiff to stiff, moderately plastic, highly sandy, silty CLAY (A-7-6) with trace mica
- (H) ALLUVIAL: white and red-brown, moist, medium dense, silty SAND (A-2-4) with little gravel
- (B) RESIDUAL: red-brown, wet, medium stiff, moderately plastic, highly sandy, silty CLAY (A-7-6) with trace gravel-sized rock fragments

SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-42	25'LT	29+00	0.0' - 1.5'	A-7-6(4)	44	17	22.7	24.3	21.1	31.9	78	69	45	21.1	NA
SS-70	18'RT	29+00	3.7' - 5.2'	A-4(0)	32	0	24.6	33.6	22.8	19.0	86	75	41	20.3	NA




29 + 00.00

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




-L-

09-OCT-2019 15:03
 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY_Inventory\REV2_Summit\CADD_GEO\TECH\ssc_BR0044_GEO_xsi.L (23-39).dgn
 33




- (A) ROADWAY EMBANKMENT: black and gray, moist, dense, silty SAND (A-2-4) with some gravel
- (F) ROADWAY EMBANKMENT: red-brown, moist, medium stiff, sandy SILT (A-4) with some mica
- (B) RESIDUAL: red, moist, medium stiff, slightly to moderately plastic, highly sandy, silty CLAY (A-7-6) and sandy CLAY (A-6) with trace mica
- (C) RESIDUAL: red-orange, moist, medium stiff to very stiff, sandy SILT (A-4) with some clay and little to some mica

SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	LL.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-34	40'LT	30+50	0.0' - 1.5'	A-7-6(8)	41	21	15.7	28.7	14.0	41.6	89	82	54	15.6	NA
SS-35	40'LT	30+50	4.0' - 5.5'	A-6(3)	28	12	19.2	33.5	14.3	32.9	96	89	51	15.7	NA



30 + 50.00
 -L-

09-OCT-2019 15:04 C:\Users\jgarcia\OneDrive\Documents\Projects\BR0044\GEO_PDWY\Inventory\REV2_Summit\CADD_GEO\TECH\SS-66\BR0044_GEO_xsl-L(23-39).dgn




- (A) ROADWAY EMBANKMENT: black and gray, moist, dense, silty SAND (A-2-4) with some gravel
- (F) ROADWAY EMBANKMENT: red-brown, moist, medium stiff, sandy SILT (A-4) with some mica
- (B) RESIDUAL: red, moist, medium stiff, slightly to moderately plastic, highly sandy, silty CLAY (A-7-6) and sandy CLAY (A-6) with trace mica
- (C) RESIDUAL: red-orange, red-brown, and brown, moist to wet, medium stiff to very stiff, sandy SILT (A-4) with some clay and little to some mica
- (D) RESIDUAL: red-brown and white, moist, medium dense, silty SAND (A-2-4) with some gravel-sized rock fragments and trace mica


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-66	13'RT	31+00	8.7' - 10.2'	A-4(1)	25	8	21.6	33.3	18.0	27.1	95	86	48	17.2	N/A

31 + 00.00

150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150




150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

09-OCT-2019 15:09
 L:\USERS\jg\Projects\BR0044_GEO_PDWY_Inventory\REV2_Summit\CADD_GEO\TECH\ssc\BR0044_GEO_xsi.L (23-39).dgn
 6/23/16


150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150

- (A) ROADWAY EMBANKMENT: brown to gray, moist, medium dense, silty SAND (A-2-4) with some gravel
- (F) ROADWAY EMBANKMENT: red-brown, moist, medium stiff, sandy SILT (A-4) with some mica
- (B) RESIDUAL: red-brown to brown, moist, medium stiff to stiff, slightly to moderately plastic, sandy CLAY (A-6) with trace mica
- (C) RESIDUAL: orange-white and red-brown, moist, medium stiff to stiff, saprolitic, clayey SILT (A-5) and sandy SILT (A-4) with trace to some mica and trace cobble-sized rock fragments
- (D) RESIDUAL: white-brown, moist, medium dense, saprolitic, silty SAND (A-2-4) with some mica


SOIL TEST RESULTS															
SAMPLE NO.	OFFSET	STATION	DEPTH INTERVAL	AASHTO CLASS.	L.L.	P.I.	% BY WEIGHT				% PASSING (SIEVES)			% MOISTURE	% ORGANIC
							C. SAND	F. SAND	SILT	CLAY	10	40	200		
SS-90	45'LT	32+50	0.0' - 1.5'	A-6(3)	34	16	23.0	31.8	16.3	29.0	87	78	44	12.9	N/A
SS-91	45'LT	32+50	4.7' - 6.2'	A-5(8)	48	8	9.9	22.4	27.8	39.9	96	92	72	22.9	NA
SS-62	13'RT	32+50	8.7' - 10.2'	A-6(5)	34	15	17.3	31.1	10.1	41.4	89	83	51	18.7	NA



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150



NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
GEOTECHNICAL ENGINEERING UNIT
SUBSURFACE INVESTIGATION

APPENDIX A
LABORATORY RESULTS (CALIFORNIA BEARING RATIO TESTING)

REFERENCE: BR-0044

PROJECT: 67044

Prepared in the
Office of:



NC FIRM LICENSE No: P-0339 and C-487
504 Meadowlands Drive
Hillsborough, NC 27278
(919) 732-3883
(919) 732-6676 (FAX)

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
 DIVISION OF HIGHWAY
 MATERIALS & TESTS UNIT
 SOILS LABORATORY



504 Meadowlands Drive, Hillsborough, NC 27278
 Phone // 919.732.3883 Web // www.summitde.net

Standard Moisture-Density Relationship Report

ASTM D698

T. I. P. No. BR-0044
 REPORT ON SAMPLES OF Replace Bridge No. 780168 over the Smith River
 Project 67044.1.1 County Rockingham Owner Geotech
 Date: Sampled May, 2019 Received _____ Reported 7/5/19
 Sampled from Roadway Investigation By Geotech
 Submitted by Brett Smith _____ 2008 Standard Specifications

Project Number **18-0173.I55** Date **6/27/2019**
 Project Name **BR-0044** Sample Number **S-1**
 Client **NCDOT**
 Sample Description _____ Maximum Dry Density **114.3 pcf**
 Sample Location **L_1100LT** Optimum Moisture **13.8%**

7/5/19


TEST RESULTS

Proj. Sample No.	S-1	S-2				
Boring No.	L 1100LT	L 1800LT				
Retained #4 Sieve %	0	0				
Passing #10 Sieve %	93	90				
Passing #40 Sieve %	78	78				
Passing #200 Sieve %	45	38				

MINUS NO. 10 FRACTION

SOIL MORTAR - 100%						
Coarse Sand Ret - #60 %	27.4	23.7				
Fine Sand Ret - #270 %	33.4	44.4				
Silt 0.05 - 0.005 mm %	23.9	18.3				
Clay < 0.005 mm %	15.3	13.6				
Passing #40 Sieve %	83.8	87.0				
Passing #200 Sieve %	48.4	42.8				

L. L.	32	27				
P. I.	3	1				
AASHTO Classification	A-4	A-4				
Group Index	0	0				
pH	N/A	N/A				
Station	11+00	18+00				
OFFSET	100'LT	20'LT				
ALIGNMENT	-L-	-L-				
Depth (Ft)	0.0	0.0				
to	15.0	8.9				
Natural Moisture %	N/A	N/A				



Natural Moisture:
 Specific Gravity: **2.60 (Assumed)**
 Liquid Limit:
 Plasticity Index:
 % Fines:
 % Sand:
 % Gravel:

Rammer Type: **Manual**
 Preparation Method: **Dry**
 Method: **A**
 Oversize Correction: **Not Required**

Aaron Hackett
 Soils Engineer

Aaron Hackett, EI
 Lab Manager

Jeff Elliott, PE
 CMT & SI Department Manager




504 Meadowlands Drive, Hillsborough, NC 27278
 Phone // 919.732.3883 Web // www.summitde.net

Standard Moisture-Density Relationship Report

ASTM D698

Project Number	18-0173.I55	Date	6/27/2019
Project Name	BR-0044	Sample Number	S-2
Client	NCDOT		

Sample Description	Maximum Dry Density 112.1 pcf
Sample Location L_1800LT	Optimum Moisture 14.2%



Natural Moisture:		Rammer Type:	Manual
Specific Gravity:	2.60 (Assumed)	Preparation Method:	Dry
Liquid Limit:		Method:	A
Plasticity Index:		Oversize Correction:	Not Required
% Fines:			
% Sand:			
% Gravel:			

Aaron Hackett, EI
 Lab Manager

Jeff Elliott, PE
 CMT & SI Department Manager




Report on California Bearing Ratio (ASTM D 1883/AASHTO T 193)

Date	6/27/2019	Project Name	BR-0044
Sample No.	CBR Run #1	Project No.	18-0173.I55
Sample Location	L_1100LT	Client	NCDOT

Proctor and Classification Data	
Sample Description	0
Classification	0
Max. Dry Density	114.3
Optimum Moisture	13.8%

CBR Preparation Data	
Rammer Used	5.5 lbs
Compaction Method	3 Layers, 56 Blows
Surcharge Amount	10 lbs
Soaked/Unsoaked	Soaked

CBR Results			
Compaction Moisture Content	13.5%	Dry unit weight (lbs/cu.ft)	112.8
Moisture Content of Top 1"		Percent of Max. Dry Density	98.7%
After Soaking	21.3%		
		CBR Values	
Swell	N/A	Penetration (in)	0.171 0.271
		Stress (psi)	39.00 81.00
		CBR	3.9 5.4



Remarks: Zero-point correction applied. All material passed the 3/4" sieve.

Aaron Hackett
 Lab Manager

Jeff Elliott, P.E.
 CMT & SI Dept. Manager



Report on California Bearing Ratio (ASTM D 1883/AASHTO T 193)

Date	<u>6/27/2019</u>	Project Name	<u>BR-0044</u>
Sample No.	<u>CBR Run #2</u>	Project No.	<u>18-0173.I55</u>
Sample Location	<u>L_1100LT</u>	Client	<u>NCDOT</u>



Report on California Bearing Ratio (ASTM D 1883/AASHTO T 193)

Date	<u>6/27/2019</u>	Project Name	<u>BR-0044</u>
Sample No.	<u>CBR Run #1</u>	Project No.	<u>18-0173.I55</u>
Sample Location	<u>L_1800LT</u>	Client	<u>NCDOT</u>

Proctor and Classification Data

Sample Description	<u>0</u>
Classification	<u>0</u>
Max. Dry Density	<u>114.3</u>
Optimum Moisture	<u>13.8%</u>

CBR Preparation Data

Rammer Used	<u>5.5 lbs</u>
Compaction Method	<u>3 Layers, 56 Blows</u>
Surcharge Amount	<u>10 lbs</u>
Soaked/Unsoaked	<u>Soaked</u>

Proctor and Classification Data

Sample Description	<u>0</u>
Classification	<u>0</u>
Max. Dry Density	<u>112.1</u>
Optimum Moisture	<u>14.2%</u>

CBR Preparation Data



Rammer Used	<u>5.5 lbs</u>
Compaction Method	<u>3 Layers, 56 Blows</u>
Surcharge Amount	<u>10 lbs</u>
Soaked/Unsoaked	<u>Soaked</u>

CBR Results

Compaction Moisture Content	<u>13.5%</u>	Dry unit weight (lbs/cu.ft)	<u>114.1</u>
Moisture Content of Top 1"		Percent of Max. Dry Density	<u>99.8%</u>
After Soaking	<u>21.0%</u>		
		CBR Values	
Swell	<u>2.9%</u>	Penetration (in)	<u>0.167</u> <u>0.267</u>
		Stress (psi)	<u>39.00</u> <u>85.00</u>
		CBR	<u>3.9</u> <u>5.7</u>

CBR Results

Compaction Moisture Content	<u>16.4%</u>	Dry unit weight (lbs/cu.ft)	<u>108.5</u>
Moisture Content of Top 1"		Percent of Max. Dry Density	<u>96.8%</u>
After Soaking	<u>17.6%</u>		
		CBR Values	
Swell	<u>N/A</u>	Penetration (in)	<u>0.135</u> <u>0.235</u>
		Stress (psi)	<u>16.00</u> <u>34.60</u>
		CBR	<u>1.6</u> <u>2.3</u>



Remarks: Zero-point correction applied. All material passed the 3/4" sieve.

Remarks: Zero-point correction applied. All material passed the 3/4" sieve.

Aaron Hackett
Lab Manager

Jeff Elliott, P.E.
CMT & SI Dept. Manager

Aaron Hackett
Lab Manager

Jeff Elliott, P.E.
CMT & SI Dept. Manager




Report on California Bearing Ratio (ASTM D 1883/AASHTO T 193)

Date	<u>6/27/2019</u>	Project Name	<u>BR-0044</u>
Sample No.	<u>CBR Run #2</u>	Project No.	<u>18-0173.I55</u>
Sample Location	<u>L_1800LT</u>	Client	<u>NCDOT</u>

Proctor and Classification Data		CBR Preparation Data	
Sample Description	<u>0</u>	Rammer Used	<u>5.5 lbs</u>
Classification	<u>0</u>	Compaction Method	<u>3 Layers, 56 Blows</u>
Max. Dry Density	<u>112.1</u>	Surcharge Amount	<u>10 lbs</u>
Optimum Moisture	<u>14.2%</u>	Soaked/Unsoaked	<u>Soaked</u>

CBR Results			
Compaction Moisture Content	<u>16.4%</u>	Dry unit weight (lbs/cu.ft)	<u>108.9</u>
Moisture Content of Top 1"		Percent of Max. Dry Density	<u>97.1%</u>
After Soaking	<u>17.8%</u>		
		CBR Values	
Swell	<u>0.0%</u>	Penetration (in)	<u>0.147</u> <u>0.247</u>
		Stress (psi)	<u>23.00</u> <u>47.00</u>
		CBR	<u>2.3</u> <u>3.1</u>



Remarks: Zero-point correction applied. All material passed the 3/4" sieve.

Aaron Hackett
Lab Manager

Jeff Elliott, P.E.
CMT & SI Dept. Manager



October 8, 2019

WBS Number: 67044.1.1
TIP Number: BR-0044
Project ID: 34624
County: Rockingham
Description: Bridge No. 168 on NC 14/NC 87 (N. Van Buren Road) over Smith River

Subject: Geotechnical Report – Design and Construction Recommendations

Summit Design and Engineering Services, PLLC has completed a subsurface investigation for this project and presents the following recommendations.

I. Slope / Embankment Stability

A. Slope Design

We recommend that all roadway slopes be constructed at a ratio of 2:1 (H:V) or flatter.

B. Undercut for Embankment Stability

Recommend 2,000 cubic yards of Undercut for Embankment Stability to be included in the project contract as a contingency item to be used at the discretion of the Engineer. All undercut should be computed as material to be wasted. However, some material may be used outside of the pavement section at the discretion of the Engineer.

C. Geotextile for Soil Stabilization

Recommend 2,000 square yards of Geotextile for Soil Stabilization be included in the project contract, as follows:

1. 2,000 square yards for contingency areas of Undercut for Embankment Stability to be placed prior to the placement of Select Granular Material as noted in **Section I.B.**

II. Subgrade Stability

A. Subsurface Drainage

Recommend 300 linear feet of Subdrain pipe used for Underdrain (Roadway Standard Drawing 815.03) be included in the project contract as a contingency item to be used at the discretion of the Engineer.

B. Grade Point Undercut

Recommend 100 cubic yards be included in the project contract for Grade Point Undercut.

C. Undercut for Subgrade Stability

Recommend 200 cubic yards of Undercut for Subgrade Stability be included in the project contract as a contingency item to be used at the discretion of the Engineer.

D. Aggregate Subgrade

Recommend 100 cubic yards of 12-inch Shallow Undercut for Aggregate Subgrade be included in the project contract as a contingency item to be used at the discretion of the Engineer.

E. Geotextile for Soil Stabilization

Recommend 500 square yards of Geotextile for Soil Stabilization to be included in the project contract, as follows:

1. 200 square yards for contingency areas of Undercut for Subgrade Stability to be placed prior to placement of Select Granular Material as noted in **Section II.C.**
2. 300 square yards for contingency areas of Aggregate Subgrade to be placed prior to the placement of Class IV Subgrade Stabilization Material as noted in **Section II.D.**

III. Borrow Specifications

A. Borrow Criteria

Common borrow for slope/embankment construction to subgrade shall meet Statewide Criteria for acceptance of Borrow Material (Section 1018-2 A).

B. Class IV Subgrade Stabilization Material

Recommend 200 tons of Class IV Subgrade Stabilization Material to be used as backfill for Shallow Undercut on Geotextile for Soil Stabilization, as follows:

1. 200 tons on Geotextile for Soil Stabilization for contingency areas of Aggregate Subgrade as noted in **Section II.D.**

C. Select Granular Material

Recommend 2,200 cubic yards of Select Granular Material for embankment stability and subgrade stability on Geotextile for Soil Stabilization, as follows:

1. 2,000 cubic yards on Geotextile for Soil Stabilization for contingency areas of Undercut for Embankment Stability as noted in **Section I.B.**
2. 200 cubic yards on Geotextile for Soil Stabilization for contingency areas of Undercut for Subgrade Stability as noted in **Section II.C.**

Select Material for embankment construction on Geotextile for Soil Stabilization shall meet the criteria outlined in Standard Specifications, Article 1016-3 Class II or III. Construction utilizing Select Granular Material should follow section 265-3 of the Standard Specifications.

D. Shrinkage Factor

A shrinkage factor of 20 percent is recommended for calculation of earthwork on this project.

IV. Miscellaneous

A. Reduction of Unclassified Excavation - Clearing and Grubbing

A loss of 1,000 cubic yards of unclassified excavation is estimated on this project due to clearing and grubbing.

B. Water Wells

Water wells were identified within the proposed right-of-way at the following locations:

<u>Line</u>	<u>Station (±)</u>	<u>Offset</u>
-L-	17+16	38'LT

Water wells should be abandoned per Standard Specification 205.


Sincerely,

SUMMIT DESIGN AND ENGINEERING SERVICES, PLLC
Firm's NC License No. P-0339

Brett Smith, P.G.
Project Geologist

DocuSigned by:

BE61A49304C542E...
10/16/2019



Harold D. Pruitt, P.E.
Senior Design Engineer

DocuSigned by:

Harold D. Pruitt

BAE9676E0BE04DA...

10/16/2019



Don Dewey, P.E.
Vice President – Geotechnical Engineering

DocuSigned by:

Don Dewey

49A5BA9969D5485...



NORTH CAROLINA DEPARTMENT OF TRANSPORTATION
GEOTECHNICAL ENGINEERING UNIT

Summary of Quantities

WBS No.: 67044.1.1

County: Rockingham

Project Engineer: Harold Pruitt, P.E.

TIP No.: BR-0044

Field Office: Summit

Project Geologist: Brett Smith, P.G.

Description: Bridge No. 168 on NC 14/NC 87 (N. Van Buren Road) over Smith River

Pay Item No.	Pay Item/ Quantity Adjustment	Spec Book Section No. or Special Provision (SP) Reference	Report Section	Alignment	Begin Station	End Station	Quantity	Units
0015000000-N	Sealing Abandoned Wells	205 - Sealing Abandoned Wells	IV. B	Varies	N/A	N/A	1	EA
Total Quantity of Sealing Abandoned Wells =							1	EA
0036000000-E	Undercut Excavation	225 - Roadway Excavation	I. B	Contingency	N/A	N/A	2,000	CY
0036000000-E	Undercut Excavation	225 - Roadway Excavation	II. B	Varies	N/A	N/A	100	CY
0036000000-E	Undercut Excavation	225 - Roadway Excavation	II. C	Contingency	N/A	N/A	200	CY
Total Quantity of Undercut Excavation =							2,300	CY
0195000000-E	Select Granular Material	265 - Select Granular Material	III. C	Contingency	N/A	N/A	2,000	CY
0195000000-E	Select Granular Material	265 - Select Granular Material	III. C	Contingency	N/A	N/A	200	CY
Total Quantity of Select Granular Material =							2,200	CY
0196000000-E	Geotextile for Soil Stabilization	270 - Geotextile for Soil Stabilization	I. C	Contingency	N/A	N/A	2,000	SY
0196000000-E	Geotextile for Soil Stabilization	270 - Geotextile for Soil Stabilization	II. E	Contingency	N/A	N/A	200	SY
0196000000-E	Geotextile for Soil Stabilization	270 - Geotextile for Soil Stabilization	II. E	Contingency	N/A	N/A	300	SY
Total Quantity of Geotextile for Soil Stabilization =							2,500	SY
1099500000-E	Shallow Undercut	505 - Aggregate Subgrade	II. D	Contingency	N/A	N/A	100	CY
Total Quantity of Shallow Undercut =							100	CY
1099700000-E	Class IV Subgrade Stabilization	505 - Aggregate Subgrade	III. B	Contingency	N/A	N/A	200	TON
Total Quantity of Class IV Subgrade Stabilization =							200	TON
2044000000-E	6" Perforated Subdrain Pipe	815 - Subsurface Drainage	II. A	Contingency	N/A	N/A	300	LF
Total Quantity of 6" Perforated Subdrain Pipe =							300	LF

These Items Only Impact Earthwork Totals

N/A	Loss Due to Clearing & Grubbing	200 - Clearing and Grubbing	IV. A	N/A	N/A	N/A	1,000	CY
N/A	Shrinkage Factor	235 - Embankments	III. D	N/A	N/A	N/A	20	%