This electronic collection of documents is provided for the convenience of the user and is Not a Certified Document –

The documents contained herein were originally issued and sealed by the individuals whose names and license numbers appear on each page, on the dates appearing with their signature on that page.

This file or an individual page shall not be considered a certified document.

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	A-0009CB	1	5

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION STRUCTURE ON NC 143 OVER SWEETWATER CREEK AT -L- STATION 278+68

CONTENTS

SHEET NO. **DESCRIPTION**

2. 2A 3 4-5

TITLE SHEET LEGEND (SOIL & ROCK) SITE PLAN BORE LOGS

PERSONNEL **BRECCIA**

D. GOODNIGHT

INVESTIGATED BY \underline{CG}_2

DRAWN BY __M. BREWER, P.E.

CHECKED BY R. KRAL, P.E.

SUBMITTED BY CG2

DATE _DECEMBER 2021

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT 1(99) 707-850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

CENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (INP-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION, THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEM NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED TO THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:

 I. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

 BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.





V. Matthew Brewer 386129C0A4C1462. SIGNATURE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

1/20/22

PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	2

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS (PAGE 1 OF 2)

											(1-7	1GE	(OF 2)					
				SOIL	DES	CRI	PTI	ON					GRADATION					
BE PENE ACCORD IS I CONSISTI	CONSIDERED TRATED WITH ING TO THE BASED ON T ENCY, COLOR S MINERALO	H A CI STANI HE AA TEXTI	ONTINUOUS DARD PENET SHTO SYSTE URE, MOISTL COMPOSITI	P. SEMI- FLIGHT RATION M. BAS RE, AAS ON, ANGL	CONSOLI POWER TEST (IC DESC HTO CLI JLARITY	IDATE AUGE (AASH (RIPTI ASSIF	D. OR R AND TO T ONS C ICATIO	WEATHE YIELD 206, AS ENERAL DN, AND E, PLAS	LESS M DIS Y IN OTHER ICITY	THAN 100 586). SOIL CLUDE THE PERTINE ETC. FOR	BLOWS PECLASSIFING FOLLOWING FACTOR	ER FOOT CATION NG: RS SUCH	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES. ANGULARITY OF GRAINS THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:					
	VERY STIFF,		LEGEN										ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.					
GENERAL		GRANUL	AR MATERIAL	s	<u> </u>	SILT	-CLAY P	1ATERIAL			GANIC MATERI	1Δι ς	MINERALOGICAL COMPOSITION					
CLASS. GROUP	A-1	≤ 35% A-3	PASSING *200	8) 4-2		(> 3! A-4	5% PASS A-5		-7	A-1, A-2	A-4, A-5		MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.					
CLASS.	A-1-a A-1-b	,,,,,,,,,,,	A-2-4 A-2-5	A-2-6	A-2-7	0380300			7-5. 7-6	A-3	A-6, A-7	***********	COMPRESSIBILITY SLIGHTLY COMPRESSIBLE LL < 31					
	000000000000000000000000000000000000000			×			1.7.1						MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50					
% PASSING *10	50 MX									GRANULAR	SILT- CLAY	MUCK,	PERCENTAGE OF MATERIAL					
	30 MX 50 MX 15 MX 25 MX		35 MX 35 MX	35 MX	35 MX 36	6 MN :	36 MN	36 MN 3	MN	SOILS	SOILS	PEAT	GRANULAR SILT - CLAY ORGANIC MATERIAL SOILS OTHER MATERIAL					
MATERIAL													TRACE OF ORGANIC MATTER 2 - 3%, 3 - 5%, TRACE 1 - 10%, LITTLE ORGANIC MATTER 3 - 5%, 5 - 12%, LITTLE 10 - 20%,					
PASSING *40 LL	_	_	40 MX 41 MN					40 MX 4	MN	SOILS			MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35%					
PI	6 MX	NP	10 MX 10 MX	11 MN	_	-	_	11 MN 1		LITTL	RATE	HIGHLY ORGANIC	HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE					
GROUP INDEX	O CTONE EDACE	0	0	4 N	1X 8	3 MX	12 MX	16 MX N	MX	amoun Orga		SOILS	GROUND WATER ✓ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING					
USUAL TYPES OF MAJOR MATERIALS	STONE FRAGS. GRAVEL, AND SAND	FINE SAND		r Clayey and Sani		SILT SOIL		CLAYE SOILS		MAT	TER		✓ water level in bore hole immediately after drilling ✓ static water level after 24 hours ✓ order ✓ ord					
GEN. RATING		FXCFLL	ENT TO GOOD			-	AIR TO	PNNR		FAIR TO	POOR	UNSUITABLE						
AS SUBGRADE			-7-5 SUBGROU		11 - 30	• P1 NE	Δ-7-6	SURCEO	P IS >	P00R			SPRING OR SEEP					
		1,01	CONS							- 11 30			MISCELLANEOUS SYMBOLS					
PRIMARY	SOIL TYPE	(COMPACTNE CONSISTE		PE			STANDAI RESIST LUE)			E OF UNC RESSIVE S (TONS/F1	TRENGTH	ROADWAY EMBANKMENT (RE) 25/025 WITH SOIL DESCRIPTION DP & DIP DIRECTION OF ROCK STRUCTURES					
GENERA	LLY		VERY LO				< 4 TO						SOIL SYMBOL SOIL SYMBOL SPT DMT TEST BORING SLOPE INDICATOR INSTALLATION					
GRANUL MATERI (NON-CO			MEDIUM DI DENSE VERY DEI	ENSE			10 TC 30 TC > 5	30 50			N/A		ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT AUGER BORING CONE PENETROMETER					
			VERY SC								< 0.25	ı	— INFERRED SOIL BOUNDARY — CORE BORING ■ SOUNDING ROD					
GENERA SILT-CI			SOFT MEDIUM S	TIEE			2 TO	4			0.25 TO 0.5 TO 1	0.5	TEST BORING MONITORING WELL TEST BORING					
MATERI	4L		STIFF				8 TO	15			1 TO 2	!	DIE ZOME TED					
(COHES)	VE)		VERY ST HARD	11-1-			15 TC				2 TO 4 > 4	,	***** ALLUVIAL SOIL BOUNDARY \(\triangle \) FIEZUMETER INSTALLATION \(\triangle \) SPT N-VALUE					
			TE	KTURI	E OR	GR	AIN	SIZE					RECOMMENDATION SYMBOLS					
U.S. STD. SI OPENING (M			4 4.7		10 .00	40 0. 42		60 .25	200 .075	270 0.053			UNCLASSIFIED EXCAVATION - UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE					
BOULDE (BLDR.	R CO	BBLE	GRAV (GF	/EL	С	OARS SAND	E		INE	9	SILT SL.)	CLAY (CL.)	SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - USED IN THE TUP 3 FEET OF EMBANKMENT OR BACKFILL					
GRAIN MN			75		2.0	SE. SI		.25	SD.)	0.05	0.005		ABBREVIATIONS AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST					
SIZE IN	. 12		3								0.000	,	BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED					
con	MOISTURE		MOIST		- COI		<u>LAT</u>	ION I)F	IERMS			CL CLAY MODERATELY γ - UNIT WEIGHT CPT - CONE PENETRATION TEST NP - NON PLASTIC γ_d - DRY UNIT WEIGHT CSE COARSE ORG ORGANIC					
	TERBERG LI				CRIPTIO		(GUIDE F	OR F	IELD MOIS	STURE DES	SCRIPTION	DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST <u>SAMPLE ABBREVIATIONS</u>					
LL _	LIQUID		_		URATEC AT.)) -					WET, USU		OPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE					
PLASTIC RANGE (PI) PL				- WET	- (W)					EQUIRES (DRYING TO)	FOSS. FOSSILIFEROUS SLI SLIGHTLY RS - ROCK FRACI FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL FRAGS FRAGMENTS W - MOISTURE CONTENT CBR - CALIFORNIA BEARING HI HIGHLY V - YERY RATIO					
PLL	_ PLASTI	IC LIM	ш										EQUIPMENT USED ON SUBJECT PROJECT					
	OPTIML SHRINK			- MOI	ST - (N	4)		50L ID; 4	TOR	NEAR OP	TIMUM MO	DISTURE	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE: CME-45C CLAY BITS X AUTOMATIC MANUAL					
				- DRY	- (D)					DITIONAL MUM MOIS	WATER TO TURE)	CMF-55 6* CONTINUOUS FLIGHT AUGER CORE SIZE:					
	<u>'</u>			Р	LAST	ICI	ΤY						X 8' HOLLOW AUGERS					
				PLA	STICIT		DEX (F	<u>(I)</u>			Y STRENG		X CME-550X HARD FACED FINGER BITS					
SLI	I PLASTIC GHTLY PLAS				6	7-5 3-15					VERY LOW SLIGHT	'	VANE SHEAR TEST TUNGCARBIDE INSERTS HAND TOOLS:					
	ERATELY P		С			8-25 R MOI	RE				MEDIUM HIGH		CASING W/ ADVANCER POST HOLE DIGGER					
						OR							PORTABLE HOIST TRICONE STEEL TEETH HAND AUGER TRICONE TUNGCARB. SQUINDING RDD					
DECCRIS	DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY).							· /T ^ L ·	DED .	VELLOW CO	OUNT DITT	- CDAY'	CORE BIT SOUNDING ROD VANE SHEAR TEST					
	TIONS MAY ODIFIERS SU												The stream less					

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS (PAGE 2 OF 2)

ROCK DESCRIPTION TERMS AND DEFINITIONS HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN I.FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.

ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS: ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES 3 100 BLOWS PER FOOT IF TESTED. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.

FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.

COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC. CRYSTALLINE ROCK (CR) CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. NON-CRYSTALLINE ROCK (NCR) COASTAL PLAIN SEDIMENTARY ROCK (CP) CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT WEATHERING ROCKS OR CUTS MASSIVE ROCK. FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, $\underline{\text{DIP DIRECTION (DIP AZIMUTH)}}$ - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE. (V SLI.) FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO SLIGHT SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. 1 INCH, OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. (SLI.) FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN $\frac{\text{FLOAT}}{\text{PARENT}} - \text{ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.}$ GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. WITH FRESH ROCK. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH MODERATELY SEVERE (MOD, SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. IF TESTED, WOULD YIELD SPT REFUSAL $\underline{\text{LEDGE}}$ - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT SEVERE REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. (SEV.) LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVINIS STRATIM VERY SEVERE AN INTERVENING IMPERVIOUS STRATUM. (V SEV.) VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</u> RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND COMPLETE ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <u>SAPROLITE (SAP.)</u> - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. ROCK HARDNESS CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES VERY HARD <u>SILL</u> - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK. CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED HARD TO DETACH HAND SPECIMEN. SLICKENSIDE - I - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB, HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS PENETRATION EQUAL BY MODERATE BLOWS. CAN BE GROOVED OR GOLIGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFF OR PICK POINT. MEDILIM CAN BE EXCAVATED IN SMALL CHIPS TO PEICES I INCH MAXIMUM SIZE BY HARD BLOWS OF THE HARD TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. POINT OF A GEOLOGIST'S PICK. CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. SOFT STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. VERY CAN BE CARVED WITH KNIFE, CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE, CAN BE SCRATCHED READILY B FINGERNAIL. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. FRACTURE SPACING BEDDING BENCH MARK: N/A TERM TERM THICKNESS SPACING VERY WIDE MORE THAN 10 FEET 3 TO 10 FEET VERY THICKLY BEDDED THICKLY BEDDED 4 FEET 1.5 - 4 FEET 0.16 - 1.5 FEET **ELEVATION:** FEET WIDE THINLY BEDDED
VERY THINLY BEDDED
THICKLY LAMINATED MODERATELY CLOSE 1 TO 3 FEET 0.03 - 0.16 FEET 0.008 - 0.03 FEET VERY CLOSE LESS THAN 0.16 FEET ROADWAY DESIGN FILES DATED 7/11/2021 PROVIDED BY TGS ENGINEERS THINLY LAMINATED < 0.008 FEET FIAD = FILLED IMMEDIATELY AFTER DRILLING INDURATION

FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.


RUBBING WITH FINGER EREES NUMEROUS GRAINS. GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.


GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. MODERATELY INDURATED


GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE: INDURATED DIFFICULT TO BREAK WITH HAMMER.

SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE: EXTREMELY INDURATED SAMPLE BREAKS ACROSS GRAINS.

DATE: 8-15-14







$oldsymbol{REFERENCE}: A-0009CB$

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	A-0009CB	1	7

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION STRUCTURE ON SR 1282 OVER SWEETWATER CREEK AT -Y4- STATION 12+13

CONTENTS

SHEET NO.

2. 2A

3 4-7 **DESCRIPTION**

TITLE SHEET LEGEND (SOIL & ROCK)

SITE PLAN BORE LOGS PERSONNEL

CG2 EXPLORATION

S. BRAUN

INVESTIGATED BY CG2

DRAWN BY S. N. PATTERSON, G.I.T.

CHECKED BY M. BREWER, P.E.

SUBMITTED BY CG2

DATE JANUARY 2022

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT 1(99) 707-850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

CENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BOREHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (INP-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE OF INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION, THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERPRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEM NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED TO THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:

 I. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

 BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.





V. Matthew Brewer -386129C0A4C1462.

SIGNATURE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

1/20/22

PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	2

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS (PAGE 1 OF 2)

												((PA	4GE	1 OF 2)
						<u>S</u> 0I	DE	SCR	<u>IPTI</u>	ON					GRADATION
BE PENE ACCORD IS CONSIST	TRATED ING TO BASED C ENCY, CC	WITH THE S ON THI OLOR,	A CC STAND E AAS TEXTU	INTINU IARD F SHTO ! JRE, M	JOUS I PENET SYSTE OISTU	, SEMI FLIGHT RATIO M. BA RE, AA	-CONSO POWE TEST SIC DE SHTO (DLIDATE R AUGE (AASH SCRIPT CLASSIE	ED, OR ER ANI ITO T TONS FICATI	WEATHER D YIELD I 206, ASTI GENERALL ION, AND (ED EARTH ESS THAN 1 D1586). Y INCLUDE THER PER	100 BL0 SOIL CL4 THE FO TINENT F	OWS PE ASSIFIC OLLOWIN FACTOR	ER FOOT CATION NG: RS SUCH	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES. ANGULARITY OF GRAINS
·	AS MINER VERY ST	IFF,GF	RAY, SIL	TY CLA	AY, MOIS	T WITI	INTER	RBEDDE	D FINE	SAND LA	CITY, ETC. ERS, HIGHLY	PLASTIC.	AMPLE. A-7-6	•	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.
GENERAL				AR MA1			ID A			LASSI MATERIALS	FICATI				MINERALOGICAL COMPOSITION
CLASS. GROUP	A-1	(1		PASSIN	G *200					SING #200)	7 A-1, A-	ORGANIC	MATERI 4. A-5	IALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.
CLASS.	A-1-a A	-1-ь	_	A-2-4		A-2-6				A-1			6. A-7		COMPRESSIBILITY
SYMBOL	0000000								777						SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50
% PASSING *10	50 MX										GRANUL		ILT-	MUCK.	HIGHLY COMPRESSIBLE LL > 50 PERCENTAGE OF MATERIAL
*40 *200	30 MX 50			35 MX	35 MX	35 MX	35 MX	36 MN	36 MN	36 MN 36	SOILS	. "	CLAY OILS	PEAT	ORGANIC MATERIAL GRANULAR SILT - CLAY ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL
MATERIAL PASSING *40 LL PI	_ 6 MX									40 MX 41 11 MN 11	MN I	OILS WITH		HIGHLY	TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 10% LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20% MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35% HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE
GROUP INDEX	0		0	(ð	4	MX	8 MX	12 MX	16 MX NO		MOUNTS OF		ORGANIC SOILS	GROUND WATER
USUAL TYPES OF MAJOR MATERIALS	STONE FR GRAVEL. SAND	AND .	FINE SAND			r Clay and sa		SIL SOI		CLAYEY SOILS		ORGANIC MATTER			▼ water level in Bore hole immediately after drilling ▼ STATIC WATER LEVEL AFTER 24 HOURS
GEN. RATING AS SUBGRADE			XCELL	ENT TO	G00D				FAIR T	0 POOR	FAIR POOR		POOR	UNSUITABLE	<u>∨pw</u> PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA ○
		Р	1 OF A							6 SUBGROUF	IS > LL -	30			MISCELLANEOUS SYMBOLS
						S OR		RAN	GE OF	STANDAR	F			ONFINED	
PRIMARY	SOIL TY	'PE		CONS	Y LO	NCY		PENETF	(N-V	RESISTE	ICE C		SIVE S INS/FT	TRENGTH	WITH SOIL DESCRIPTION OF ROCK STRUCTURES
GENERA GRANUL	.AR			L	.00SE JM DE				4 T	0 10 0 30			N/A		SUIL STMBOL TEST BURING INSTALLATION
MATERI (NON-CI	AL DHESIVE)			DENSE Y DEN					0 50			N/H		ARTIFICIAL FILL (AF) OTHER AUGER BORING CONE PENETROMETER THAN ROADWAY EMBANKMENT
GENERA	ALLY.				RY SO SOFT	FT				2			0.25 5 TO 0		── INFERRED SOIL BOUNDARY
SILT-C MATERI	LAY			MEDI	UM S'	TIFF			4 T	0 8		0.5	5 TO 1	.0	INFERRED ROCK LINE MNONITORING WELL TEST BORING WITH CORE
COHES				VER	Y STI	IFF			15 T	0 30			TO 4		TTTTT ALLUVIAL SOIL BOUNDARY A PIEZOMETER INSTALLATION - SPT N-VALUE
						(TUF	RE O	R GF		SIZE					RECOMMENDATION SYMBOLS
U.S. STD. SI OPENING (M		'E			4 4.7	6	10 2.00	40 0.42	2		00 27 075 0.0				UNDERCUT UNCLASSIFIED EXCAVATION - UNCLASSIF
BOULDE (BLDR.			BLE		GRAV (GR			COARS SANI (CSE. S	כ	s	INE AND SD.)	SILT (SL.)		CLAY (CL.)	UNDERCUT ONCEPTABLE DEGRADABLE ROCK EMBANKMENT OR BACKFILL ABBREVIATIONS
GRAIN M	м 30!	5		75			2.0	10021		0.25	0.0	15	0.005	i	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST
SIZE IN	l. 12			3											BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED CL CLAY MOD MODERATELY 7 - UNIT WEIGHT
SOTI	MOISTU		OIL SCALE		ISTU		- <u>С</u> і				F TER				CPT - CONE PENETRATION TEST NP - NON PLASTIC $\mathring{\gamma}_{d}$ - DRY UNIT WEIGHT CSE COARSE ORG ORGANIC
	TERBERO					DE	SCRIPT	TION			R FIELD				DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST SAMPLE ABBREVIATIONS DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK
LL _F	LIC	uid i	LIMIT				TURAT SAT.)	ED -			LIQUID; V LOW THE				e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK
PLASTIC RANGE < (PI) PL	PL	ASTIC	: LIM	ΙΤ	_	- WE	T - (W	n			D: REQUIRI			l	FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL FRAGS FRAGMENTS ω - MOISTURE CONTENT CBR - CALIFORNIA BEARING HI HIGHLY V - VERY RATIO
NO				STURI	E	- MC	IST -	(M)		SOLID; A	OR NEAF	OPTIMU	JM MO	ISTURE	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:
SL	. + SHI	- INKA	GE L	TIMI		- DR	Y - (D	1)			ADDITION)	CME-45C CLAY BITS X AUTOMATIC MANUAL
\vdash							ΡΙΔΟ	STICI			. 11000	.010 I UNE			CME-55 CONTINUOUS FLIGHT HOUSE CORE SIZE: -B
								ITY IN		PI)		DRY S			CME-550X HARD FACED FINGER BITS
SL	N PLAST IGHTLY	PLAS						Ø-5 6-15					Y LOW IGHT	1	VANE SHEAR TEST TUNG,-CARBIDE INSERTS HAND TOOLS:
	DERATEL GHLY PL			2				16-25 OR MC	DRE				DIUM IIGH		CASING W/ ADVANCER POST HOLE DIGGER POST HOLE DIGGER POST HOLE DIGGER
							C	OLOR	1						TRICONE TUNG, CARB. SQUINDING POD
											ED. YELLO DESCRIB				OIEDRICH D-50 CORE BIT SOUNDING ROUS
Щ_															

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS (PAGE 2 OF 2)

ROCK DESCRIPTION TERMS AND DEFINITIONS HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN I.FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.

ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS: ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER. AQUIFER - A WATER BEARING FORMATION OR STRATA. ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND. ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES 3 100 BLOWS PER FOOT IF TESTED. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.

FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.

COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC. CRYSTALLINE ROCK (CR) CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE. COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE. NON-CRYSTALLINE ROCK (NCR) COASTAL PLAIN SEDIMENTARY ROCK (CP) CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT WEATHERING ROCKS OR CUTS MASSIVE ROCK. FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL. VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, $\underline{\text{DIP DIRECTION (DIP AZIMUTH)}}$ - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH. CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE. (V SLI.) FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO SLIGHT SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE. 1 INCH, OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS. (SLI.) FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES. MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN $\frac{\text{FLOAT}}{\text{PARENT}} - \text{ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM PARENT MATERIAL.}$ GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. WITH FRESH ROCK. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD. ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH MODERATELY SEVERE (MOD, SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED. IF TESTED, WOULD YIELD SPT REFUSAL $\underline{\text{LEDGE}}$ - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT. ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT SEVERE REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN. (SEV.) LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVINIS STRATIM VERY SEVERE AN INTERVENING IMPERVIOUS STRATUM. (V SEV.) VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</u> RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK. ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND COMPLETE ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE. <u>SAPROLITE (SAP.)</u> - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK. ROCK HARDNESS CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES VERY HARD <u>SILL</u> - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS. SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK. CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED HARD TO DETACH HAND SPECIMEN. SLICKENSIDE - I - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB, HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS PENETRATION EQUAL BY MODERATE BLOWS. CAN BE GROOVED OR GOLIGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFF OR PICK POINT. MEDILIM CAN BE EXCAVATED IN SMALL CHIPS TO PEICES I INCH MAXIMUM SIZE BY HARD BLOWS OF THE HARD TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. POINT OF A GEOLOGIST'S PICK. CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE. SOFT STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE. VERY CAN BE CARVED WITH KNIFE, CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE, CAN BE SCRATCHED READILY B FINGERNAIL. TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER. FRACTURE SPACING BEDDING BENCH MARK: N/A TERM TERM THICKNESS SPACING VERY WIDE MORE THAN 10 FEET 3 TO 10 FEET VERY THICKLY BEDDED THICKLY BEDDED 4 FEET 1.5 - 4 FEET 0.16 - 1.5 FEET **ELEVATION:** FEET WIDE THINLY BEDDED
VERY THINLY BEDDED
THICKLY LAMINATED MODERATELY CLOSE 1 TO 3 FEET 0.03 - 0.16 FEET 0.008 - 0.03 FEET VERY CLOSE LESS THAN 0.16 FEET ROADWAY DESIGN FILES DATED 7/11/2021 PROVIDED BY TGS ENGINEERS THINLY LAMINATED < 0.008 FEET FIAD = FILLED IMMEDIATELY AFTER DRILLING INDURATION

FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.


RUBBING WITH FINGER EREES NUMEROUS GRAINS. GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.


GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER. MODERATELY INDURATED


GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE: INDURATED DIFFICULT TO BREAK WITH HAMMER.

SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE: EXTREMELY INDURATED SAMPLE BREAKS ACROSS GRAINS.


DATE: 8-15-14








NCDOT BORE SINGLE A-0009CB





REFERENCE

CONTENTS

DESCRIPTION

LEGEND (SOIL & ROCK)

SUPPLEMENTAL LEGEND (GSI)

LABORATORY TEST RESULTS

GEOPHYSICAL TEST RESULTS

BORE LOGS, CORE LOGS & ROCK CORE PHOTOGRAPHS

TITLE SHEET

SITE PLAN PROFILE

CROSS SECTIONS

SHEET NO.

2Α

5-16

17-32

33 34-35

S 3

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY _GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION PRECAST CONCRETE ARCH LAND BRIDGE OVER NC 143 BETWEEN SR 1282 AND NC 28 AT -L- STATION 381+40

STATE PROJECT REFERENCE NO. 35 A-0009CB

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (1991) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSUFFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BORCHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS, AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:


 1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

 2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

CG2 EXPLORATION **BRECCIA** D. GOODNIGHT S. BRAUN INVESTIGATED BY <u>CG2, PLLC</u> DRAWN BY _M. BREWER, P.E. CHECKED BY _R. KRAL, P.E. SUBMITTED BY _CG2, PLLC DATE APRIL 2022

Prepared in the Office of:

CAROLINAS



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO. SHEET NO.

A-0009CB

2

NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT

SUBSURFACE INVESTIGATION

SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED	TERMS AND DEFINITIONS
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.	ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM, BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING:	GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.	SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN	AQUIFER - A WATER BEARING FORMATION OR STRATA,
CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE,	ANGULARITY OF GRAINS	REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:	WEATHERED VISCOUSTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES >	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
SOIL LEGEND AND AASHTO CLASSIFICATION	ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	ROCK (WR) 100 BLOWS PER FOOT IF TESTED.	ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT
GENERAL GRANULAR MATERIALS SILT-CLAY MATERIALS ORGANIC MATERIALS	MINERALOGICAL COMPOSITION	CRYSTALLINE FINE TO COARSE GRAIN IGNEOUS AND METAMORPHIC ROCK THAT	WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.
LLASS. (\$ 39% PASSING *200) (> 39% PASSING *200)	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	ROCK (CR) WOOLD FIELD SPT REFUSAL IF TESTED, ROCK TYPE INCLUDES GRANTE, GNEISS, GABBRO, SCHIST, ETC.	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4 A-5 CLASS. A-1-0 A-1-0 A-1-0 A-2-4 A-2-5 A-2-6 A-2-7 A-7-5 A-6 A-7	COMPRESSIBILITY	NON-CRYSTALLINE FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YELLD SPT REFUSAL IF TESTED.	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM
SYMBOL 0000d00000	SLIGHTLY COMPRESSIBLE LL < 31	ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.	OF SLOPE.
7. PASSING	MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50	COASTAL PLAIN SEDIMENTARY ROCK COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
*10 50 MX GRANULAR SIL1-	PERCENTAGE OF MATERIAL	CCP) SHELL BEDS, ETC. WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT
*40 30 MX 50 MX 51 MN FEAT *200 15 MX 25 MX 10 MX 35 MX 35 MX 35 MX 36 MN 36 MN 36 MN 36 MN 36 MN 56 MN	GRANULAR SILT - CLAY ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER	ROCKS OR CUTS MASSIVE ROCK.
MATERIAL	TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 10%	HAMMER IF CRYSTALLINE.	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.
PASSING *40	LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20% MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35%	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN,	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE
PI 6 MX NP 10 MX 10 MX 11 MN 11 MN 10 MX 10 MX 11 MN 11 MN LITTLE UR HIGHLY	HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE	(V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF OF A CRYSTALLINE NATURE.	LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
GROUP INDEX 0 0 0 4 MX 8 MX 12 MX 16 MX NO MX AMOUNTS OF SOUS	GROUND WATER	SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
USUAL TYPES STONE FRAGS. FINE SILTY OR CLAYEY SILTY CLAYEY MATTER		(SLI.) I INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED, CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
OF MAJOR GRAVEL, AND SAND GRAVEL AND SAND SOILS SOILS	STATIC WATER LEVEL AFTER 24 HOURS	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM
GEN. RATING EXCELLENT TO GOOD FAIR TO POOR POOR UNSUITABLE		(MOD.) GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	PARENT MATERIAL.
45 SUBURADE PUUN	SPRING OR SEEP	WITH FRESH ROCK.	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30	<u> </u>	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL	FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.
CONSISTENCY OR DENSENESS RANGE OF STANDARD RANGE OF UNCONFINED	MISCELLANEOUS SYMBOLS	SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH (MOD. SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK.	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
PRIMARY SOIL TYPE COMPACTINESS OF PENETRATION RESISTENCE COMPRESSIVE STRENGTH	ROADWAY EMBANKMENT (RE) 25/025 DIP & DIP DIRECTION WITH SOIL DESCRIPTION OF ROCK STRUCTURES	<u>IF TESTED, WOULD YIELD SPT REFUSAL</u>	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO
CONSISTENCY (N-VALUE) (TONS/FT ²) VERY LOOSE < 4	SPT CLORE INDICATOR	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT (SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED	ITS LATERAL EXTENT,
GRANULAR LOOSE 4 TO 10	SOIL SYMBOL OPT DAT TEST BORING INSTALLATION SLOPE INDICATOR INSTALLATION	TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
MATERIAL MEDIUM DENSE 30 10 50 N/A	ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT AUGER BORING CONE PENETROMETER	IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE	MOTTLEO (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
(NON-COHESIVE) VERY DENSE > 5Ø	THAN RUADWAY EMBANKMENT \$\frac{1}{2}\$	SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK	PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE
VERY SOFT < 2 < 0.25 GENERALLY SOFT 2 TO 4 0.25 TO 0.5	- INFERRED SOIL BOUNDARY - CORE BORING SOUNDING ROD	(V SEV.) REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</u>	OF AN INTERVENING IMPERVIOUS STRATUM.
GENERALLY SOFT 2 TO 4 0.25 TO 0.5 SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0	INFERRED ROCK LINE MN MONITORING WELL TEST BORING WITH CORE	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK, ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF
MATERIAL STIFF 8 TO 15 1 TO 2 (COHESIVE) VERY STIFF 15 TO 30 2 TO 4	A PIEZOMETER	SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.	ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE
HARD > 30 > 4	→ → → → → → ALLUVIAL SOIL BOUNDARY \(\triangle \) INSTALLATION \(\triangle \) SPT N-VALUE	ROCK HARDNESS	RUN AND EXPRESSED AS A PERCENTAGE.
TEXTURE OR GRAIN SIZE	RECOMMENDATION SYMBOLS	VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.
U.S. STD. SIEVE SIZE 4 10 40 60 200 270	UNDERCUT UNCLASSIFIED EXCAVATION - UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE	SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND
OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	SHALLOW UNCLASSIFIED EXCAVATION - USED IN THE TOP 3 FEET OF	HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY, HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
BOULDER COBBLE GRAVEL SAND SAND SILT CLAY	ONDERCOT LESS ACCEPTABLE DEGRAPABLE NOCK	MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT
(USE, SU.) (F SU.)	ABBREVIATIONS	HARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK. HAND SPECIMENS CAN BE DETACHED	OR SLIP PLANE.
GRAIN MM 305 75 2.0 0.25 0.05 0.005 SIZE IN. 12 3	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED	BY MODERATE BLOWS. MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB, HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL
SOIL MOISTURE - CORRELATION OF TERMS	CL CLAY MOD MODERATELY γ - UNIT WEIGHT	HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
COU MOISTURE SCALE FIELD MOISTURE	CPT - CONE PENETRATION TEST NP - NON PLASTIC $\gamma_{ m d}$ - DRY UNIT WEIGHT CSE COARSE ORG ORGANIC	POINT OF A GEOLOGIST'S PICK. SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY
(ATTERBERG LIMITS) DESCRIPTION GUIDE FOR FIELD MOISTURE DESCRIPTION	DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST <u>SAMPLE ABBREVIATIONS</u>	FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN	TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY	DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON	PIECES CAN BE BROKEN BY FINGER PRESSURE. VERY CAN BE CARVED WITH KNIFE, CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH	STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY
(SAT.) FROM BELOW THE GROUND WATER TABLE	F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK	SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
PLASTIC CEMICOLID. REQUIRES DRVING TO	FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL	FINGERNAIL.	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
RANGE - WET - (W) SEMISOLITY REGULARS DATING TO ATTAIN OPTIMUM MOISTURE	FRAGS FRAGMENTS	FRACTURE SPACING BEDDING TERM SPACING TERM THICKNESS	BENCH MARK:
	EQUIPMENT USED ON SUBJECT PROJECT	VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET	ELEVATION: FEET
OM OPTIMUM MOISTURE - MOIST - (M) SOLID; AT OR NEAR OPTIMUM MOISTURE	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:	WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET	
SL _ SHRINKAGE LIMIT	CME-45C CLAY BITS X AUTOMATIC MANUAL	CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET	NOTES:
- DRY - (D) ATTAIN OPTIMUM MOISTURE	CME-55 G* CONTINUOUS FLIGHT AUGER CORE SIZE:	VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED < 0.008 FEET	ROADWAY DESIGN AND SURVEY INFORMATION PROVIDED BY TGS ENGINEERS
PLASTICITY	X 8*HOLLOW AUGERS	INDURATION]
PLASTICITY INDEX (PI) DRY STRENGTH	X CME-550X HARD FACED FINGER BITS X-N O	FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	
NON PLASTIC 0-5 VERY LOW	TUNGCARBIDE INSERTS	RUBBING WITH FINGER FREES NUMEROUS GRAINS; FRIABLE GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	
SLIGHTLY PLASTIC 6-15 SLIGHT MODERATELY PLASTIC 16-25 MEDIUM	VANE SHEAR TEST X CASING W/ ADVANCER HAND TOOLS: POST HOLE DIGGER	CRAINC CAN BE CERABATED FROM CAMBLE WITH CIFFL BRODE.	
HIGHLY PLASTIC 26 OR MORE HIGH	PORTABLE HOIST TRICONE STEEL TEETH HAND AUGER	MODERATELY INDURATED BREAKS EASILY WHEN HIT WITH HAMMER.	
COLOR	TRICONE 'TUNG,-CARB, COUNDING DOD	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE;	
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY).	X DIEDRICH D50 X CORE BIT VANE SHEAR TEST	DIFFICULT TO BREAK WITH HAMMER.	
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	DATE: 8-15-1
		L	l .

PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	2A


DATE: 8-19-16


NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION


SUPPLEMENTAL LEGEND GEOLOGICAL STRENGTH INDEX (CSI) TABLES


AASHTO LRFD Figure 10.4.6.4-1 — Determination of GSI for Joi	nted Ro	ock Mass (Marinos and Ho	ek, 2000)		AASHTO LRFD Figure 10.4.6.4-2 — Determination of GSI for Tectonically Deformed Heterogeneous Rock Masses (Marinos and Hoek, 2000)
GEOLOGICAL STRENGTH INDEX (GSI) FOR JOINTED ROCKS (Hoek and Marinos, 2000)		у Ф С		ν ψ Ψ Ο Ο Φ	GSI FOR HETEROGENEOUS ROCK MASSES SUCH AS FLYSCH (Marinos. P and Hoek E., 2000)
From the lithology, structure and surface conditions of the discontinuities, estimate the average value of GSI. Do not try to be too precise. Guoting a range from 33 to 37 is more realistic than stating that GSI = 35. Note that the table does not apply to structurally controlled failures. Where weak planar structural planes are present in an unfavorable orientation with respect to the excavation face, these will dominate the rock mass behaviour. The shear strength of surfaces in rocks that are prone to deterioration as a result of changes in moisture content will be reduced if water is present. When working with rocks in the fair to very poor categories, a shift to the right may be made for wet conditions. Water pressure is dealt with by effective stress analysis.	SURFACE CONDITIONS	VERY GOOD Very rough, fresh unweathered surface: GOOD Rough, slightly weathered, iron stained	FAIR Smooth, moderately weathered and altered surfaces	POOR Slickensided, highly weathered surface with compact coatings or fillings or angular fragments VERY POOR Slickensided, highly weathered surface with soft clay coatings or fillings	Exemplates and escription of the lithology, structure and surface conditions (particularly of the bedding planes), choose a box in the chart. Tocate the position in the pox that corresponds to the condition of the discontinuities and estimate the average value of GSI from the contours. Do not attempt to be too precise. Growing a range from the continuities are breath, these mill dominate the personne of surfaces with the strength of some rock masses is reduced by the presence of groundwater and this can be allowed for poor and very poor and very poor and very poor and the poor of things with a solution of the rock mass. **WERY GOOD - Rough
STRUCTURE		'	1	JALITY 📥	COMPOSITION AND STRUCTURE
INTACT OR MASSIVE - intact rock specimens or massive in situ rock with few widely spaced discontinuities BLOCKY - well interlocked un-	 PIECES 	90		N/A N/A	A. Thick bedded, very blocky sandstone The effect of pelitic coatings on the bedding planes is minimized by the confinement of the rock mass. In shallow tunnels or slopes these bedding planes may cause structurally controlled instability. 70 A
disturbed rock mass consisting of cubical blocks formed by three intersecting discontinuity sets	ROCK	70 60			8. Sand- stone with C. Sand- or silty shale D. Siltstone or silty shale E. Weak siltstone
VERY BLOCKY - interlocked, partially disturbed mass with multi-faceted angular blocks formed by 4 or more joint sets	OCKING OF		50		thin inter- siltstone in similar stone layers of siltstone amounts or clayey shale with sandstone layers B C D E State State State C D E State State State C D E State St
BLOCKY/DISTURBED/SEAMY - folded with angular blocks formed by many intersecting discontinuity sets. Persistence of bedding planes or schistosity	INTERL		40	30	C.O. E. and G - may be more or less folded than illustrated but this does not change the strength. Tectonic deformation, faulting and loss of continuity moves these categories to F and H.
DISINTEGRATED - poorly inter- locked, heavily broken rock mass with mixture of angular and rounded rock pieces	 			20	G. Undisturbed silty or clayey shale with or without a few very thin sandstone layers H. Tectonically deformed silty or clayey shale with or clayey shale forming a chaotic structure with pockets of clay. Thin layers of sandstone are transformed sandst
LAMINATED/SHEARED - Lack of blockiness due to close spacing of weak schistosity or shear planes	II _	N/A N/A		10	sandstone are transformed into small rock pieces. Means deformation after tectonic disturbance
























		BORE L	OG										C	ORE	LOG			
WBS 32572.1.FS10	TIP A-0009CB	COUNTY GRAHAM		GEOLOGIST S. Braun		WE	BS 32572.1.FS	S10		TIP A-	0009CB	С		Y GRAHA		GEOLOGIST S. Braun	<u> </u>	
SITE DESCRIPTION Precast Con-	crete Arch Land Bridge over N	C 143 Between SR 1	282 and NC 28		GROUND WTR (ft)	SIT	TE DESCRIPTIO	N Pred	cast Cond	crete Arch	Land Bridg	e over N	C 143	Between SI	R 1282 and NC 28		GROUN	ID WTR (ft
BORING NO. LB_EB1-A	STATION 380+73	OFFSET 4	8 ft RT	ALIGNMENT L	0 HR. 3.9	ВС	DRING NO. LB	_EB1-A		STATIO	N 380+7	3		OFFSET	48 ft RT	ALIGNMENT L	0 HR.	3.9
COLLAR ELEV. 3,129.3 ft	TOTAL DEPTH 20.1 ft	NORTHING	618,546	EASTING 593,515	24 HR. 6.0		OLLAR ELEV.				DEPTH 2			NORTHIN	IG 618,546	EASTING 593,515	24 HR.	6.0
DRILL RIG/HAMMER EFF/DATE CG20	446 Diedrich D50 83% 06/16/2020	·	DRILL METHOD SP	T Core Boring HAMIN	MER TYPE Automatic	DR	RILL RIG/HAMMER	EFF/DAT	E CG20	446 Diedrich	D50 83%06	16/2020			DRILL METHOD	SPT Core Boring	HAMMER TYPE	Automatic
DRILLER C. Odom	START DATE 03/30/21	COMP. DAT	E 03/30/21	SURFACE WATER DEPTH N	I/A	DR	RILLER C. Odd	m		START	DATE 03	3/30/21		COMP. D	ATE 03/30/21	SURFACE WATER DE	PTH N/A	
ELEV DRIVE DEPTH BLOW COU			SAMP. C	SOIL AND ROCK DES	SCRIPTION	I -	DRE SIZE NQ		1	TOTAL	RUN 10.3	3 ft	3 A T A					
(ft) (ft) (ft) 0.5ft 0.5ft	0.5ft 0 25 50	75 100	NO. MOI G	ELEV. (ft)	DEPTH (ft)	ELE (ft	EV RUN DEP	TH RUN (ft)	DRILL RATE	RUN REC. Re (ft) (QD SAMF	STF REC. (ft)	RQD	ρ		DESCRIPTION AND REMAR	KS	
						\vdash	(1-)	(1.5)	(Min/ft)) %/	% NO.	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	G _{ELEV}	/. (ft)			DEPTH
3130				-3,129.3 GROUND SURF		3119	9.5 3,119.5 9.8	5.0	N=60/0.	0 (5.0) (5 100% 10	5.0)	(10.3)	(9.5)	3,119	0.5	Begin Coring @ 9.8 ft CRYSTALLINE ROCK		•
3,128.3	5		M N	RESIDUAL Stiff, Tan-Brown, Fine Sand	dy, Clayey SILT				N=60/0. 3:58/1.0 5:42/1.0 3:09/1.0	3 100% 10	0%	100%	92%	3,119	Fresh to Slightly \ (META-SANDS	Weathered, Moderately Hard to STONE), with Very Close to Mod	Hard, Black-White- lerately Close Fract	Gray, ure
3,125.8 3.5 68 32/0.3				3,125.8 (A-5) WEATHERED R	3.5	311	15 3,114.5 14.	8	3:09/1.0 3:34/1.0 3:31/1.0		RS-3	3			`	Spacing	Ţ	
3,123.3 6.0 4 7	14	100/0.8		- 3,124.3 Gray-Brown-Tan (META-S	SANDSTONE)	'	‡	5.3	3:28/1.0 3:07/1.0	0 (5.3) (4 0 100% 8	·.5) 5%					RS-3: 13.3 - 13.9 ft Unit Weight: 171.5 pcf		
3 120 8 8 5	14 •21		M	Very Stiff, Brown-Tan, Fi - 3,120.8 Sandy SILT (A-4), with trace	ne to Coarse	311	10 ‡		3:12/1.0 3:11/1.0	ol I					Unconfine	ed Compressive Strength: 20,62	20 psi (2,969 ksf)	
3120 3,120.6 0.3 100/0.3 3,119.5 9.8 100/0.3		100/0.3		<u>−3,119.5</u> rock fragmen	ts 9.8	4	3,109.2 20.	1	4:17/1.3	3			-	3,109	0.2 Boring Ter	minated at Elevation 3,109.2 ft (META-SANDSTONE)	n Crystalline Rock	20
				WEATHERED R Gray-Brown-Tan, (META-	SANDSTONE)									l F	C	(META-SANDSTONE)		
3115			RS-3	. CRYSTALLINE F Black-White-Gray, (META-			1							[-				
				REC=100%										l E				
3110				RQD=92% GSI=70-80			<u> </u>							1 E				
+				3,109.2 Boring Terminated at Eleva	20.1 tion 3 109 2 ft In	41	1 1							<u> </u>				
				Crystalline Rock (META-S	SANDSTONE)									<u> </u>				
				· -										-				
				•										<u> </u>				
				•														
				<u>-</u>														
				•														
				-										-				
				•														
				•			‡											
				- ·														
				•			‡											
				· -														
				•			‡											
				•			‡											
				•			‡											
				<u>-</u> -														
				•			‡											
				• -			‡							 				
							‡											
] ‡				- •										F				
							‡							F				
				-			‡							F				
							‡							F				
							‡							F				
				- •			‡							F				
							‡							F				
				•														



Precast Concrete Arch Land Bridge over NC 143 Between SR 1282 and NC 28 Rock Core Photographs Boring: LB_EB1-A

9.8 to 20.1 Feet



									В	ORE L	<u>.</u> U	JG							
WBS	32572	2.1.FS10	0		TI	P A-00	09CB		COUNTY	r Grahan	/				GEOLOGI	ST S. Brau	ın		
SITE	DESCR	IPTION	Prec	ast Co	ncrete	Arch La	nd Brid	lge over	NC 143 E	setween SR	128	32 and	NC 28	3				GROUN	ND WTR (ft)
BOR	ING NO.	LB_E	B1-D		s	TATION	381+	-32		OFFSET	50	ft RT			ALIGNME	NT L		0 HR.	Dry
COL	LAR ELI	EV . 3,	130.2 f	t	TO	OTAL D	EPTH	1.7 ft		NORTHING	3 (618,54	9		EASTING	593,583		24 HR.	Dry
DRILL	RIG/HAN	MER EF	F./DATE	CG	20446 D	iedrich Da	0 83%(06/16/202	20		D	RILLM	ETHOD	H.S	S. Augers		HAMM	ER TYPE	Automatic
DRIL	LER C	. Odom			S	TART D	ATE	03/29/2	1	COMP. DA	TE	03/2	9/21		SURFACE	WATER DE	EPTH N/	A	
LEV	DRIVE ELEV	DEPTH	BLC	w co	UNT		E	BLOWS	PER FOOT		5	SAMP.	▼/	L O	<u> </u>	SOIL AND F			
(ft)	(ft)	(ft)	0.5ft	0.5ft	0.5ft	0	25		50	75 100	Ш	NO.	/MOI	G	ELEV. (ft)				DEPTH (ft
3135		1													_				
	:	‡																	
3130	:	‡													3,130.2	GROL	JND SURF	ACF	0.0
3130	3.128.5	1.7									$\dagger \dagger$						Y EMBANI	KMENT	
		‡	60/0.0				·			60/0.0			M		Vei	(A-5), w	ith trace or	ganics	- 1
		‡													_ F	Boring Term Penetration Te	est Refusal	at Elevation	on
		‡														3,128.5 ft ((META	On Crystalli -SANDST(
		‡														•		,	
	-	‡													_				
		<u> </u>																	
		ţ																	
		ł												<u> </u>					
		ŧ												E					
	-	ł													_				
		Ī																	
		Ŧ																	
	-	Ŧ												[-				
		Ŧ												F					
	_	Ŧ													-				
		Ŧ												F					
		Ŧ												F					
	-	Ŧ												F	-				
		Ŧ																	
	_	‡												Ė	_				
		‡																	
		‡																	
	-	‡													-				
	;	‡																	
	-	‡													-				
		‡																	
		‡																	
	-	‡													-				
	:	‡																	
		‡													-				
] :	‡																	
		‡																	
	-	†													-				
		ĺ												F					
	:	Ŧ																	
	-	Ŧ													-				
	:	‡																	


Sheet 19

BORING NO. LB_EB1-C STATION 381+88 OFFSET 51 ft RT ALIGNMENT L O HR. 1.4			BORE LOG			C	ORE LOG	
SCRING OL LE SELC	WBS 32572.1.FS10	TIP A-0009CB	COUNTY GRAHAM	GEOLOGIST S. Braun	WBS 32572.1.FS10	TIP A-0009CB COUNT	TY GRAHAM	GEOLOGIST S. Braun
COLLARELEY_3-33 7 # TOTAL DEPTH 4.5 E MORTHING 015-04 SASTING 303-04 MARKET Authors 10 MORTHING 303-04 MARKET MARKET MORTHING 303-04 MARKET MARKET MORTHING 303-04 MARKET MARKET MORTHING 303-04 MARKET MARK	SITE DESCRIPTION Pred		er NC 143 Between SR 1282 and NC 28					GROUND WTR (ft
DRILLER C. O. DETAIL C. STAPE TO THE COMPS DRILLER C. O. DETAIL TO THE COMPS DRILLER C. O. DETAI	BORING NO. LB_EB1-C	STATION 381+88	OFFSET 51 ft RT	ALIGNMENT L 0 HR. 1.4	BORING NO. LB_EB1-C	STATION 381+88	OFFSET 51 ft RT	
DRILLER C. Closm START DATE 03/3021 COMP, DATE 03/3021 SURFACE WATER DEPTH NA					<u> </u>		<u> </u>	
COPE SECTION STATE COPE STATE COPE STATE COPE C						1		
1315 10 10 10 10 10 10 10				SURFACE WATER DEPTH N/A		<u> </u>	COMP. DATE 03/30/21	SURFACE WATER DEPTH N/A
335	ELEV ELEV DEPTH BLC (ft) (ft) 0.5ft	 	50 75 400 7 0		CORE SIZE NQ	RUN STRATA		
335	(11)	0.511 0.511 0 25	NO. MOI G	ELEV. (ft) DEPTH (ft)	ELEV RATE Company Company	REC. RQD SAMP. REC. RQD (ft) (ft) NO. (ft) (ft)	0 6 515) (45)	
3150 3.330.7 1.0 18 77 230.1 1900.0 330.7 1.0 190	2425					96 96 96 96	ELEV. (π)	
3120 100	3135			 - -	3,127.2 4.5 5.0 N=60/0.0 6:24/1.0	(10.0) (8.0) 100% 78% (10.0) (8.0)	3,127.2 Fresh to Slightly V	CRYSTALLINE ROCK Meathered Moderately Hard to Hard Black-White Gray
3120 100	+ + + + + + + + + + + + + + + + + +			3,131.7 GROUND SURFACE 0.0	5:50/1.0 2:57/1.0	100 % 78 % 100 % 00 %	(META-SANDS	TONE), with Very Close to Moderately Close Fracture
Bisck-White-Gray, (META-SANDSTONE) RS 3 RS 3 RS 3 RS 4 RS 4 RS 4 RS 5 RS 5 RS 5 RS 5 RS 6 RS 7		77 23/0.1	100/0 6	3,130.2 RESIDUAL 1.5 Very Stiff, Brown, Fine Sandy, Clayey SILT	3,122.2 9.5 3:20/1.0 5.0 3:16/1.0	(5.0) (4.1)		. •
Bisck-White-Gray, (META-SANDSTONE) RS 3 RS 3 RS 3 RS 4 RS 4 RS 4 RS 5 RS 5 RS 5 RS 5 RS 6 RS 7	3,128.3 [†] 3.4 3,127.5 [†] 4.2 100/0.		- 100/0.2	(A-5), with trace organics 3,127.2 WEATHERED ROCK 4.5	T 12:46/1.0		Unconfine	Unit Weight: 175.6 pcf
Bisck-White-Gray, (META-SANDSTONE) RS 3 RS 3 RS 3 RS 4 RS 4 RS 4 RS 5 RS 5 RS 5 RS 5 RS 6 RS 7	3125 100/0.2		100/0.2	Gray (META-SANDSTONE) CRYSTALLINE ROCK	T 4:34/1.0		3,117.2	14
Boring Terminated at Elevation 3,117.2 ft in Crystalline Rook (META-SANDSTONE)	i I	1 1 11 1		Black-White-Gray, (META-SANDSTONE)			Boring Terr	
Boring Terminated at Elevation 3,117.2 ft in Crystalline Rook (META-SANDSTONE)	i			REC=100% RQD=80%			1 E	
Boring Terminated at Elevation 3,117.2 ft in Crystalline Rook (META-SANDSTONE)	3120			GSI=60-70			<u> </u>	
Crystalline Rock (META-SANDSTONE)	+ + -			3,117.2 14.5			-	
	ı						-	
	, ‡							
	, ‡							
	ı <u> </u>			[1 F	
	ı I						[
	ı						[-	
	, ‡			_				
	, ‡			<u>-</u> -			<u> </u>	
	, ‡			- -				
				- -				
	ı			-			-	
				-				
	ı ‡						 	
	, 			-			F	
	ılŦl			E			F	
	, <u> </u>			E			1 F	
	, 🛨						E	
	ı						 	
	,			_			1 -	
	ı						<u> </u>	
	, ‡							
	, ‡			-				
	, ‡			-			-	
	, ‡			-				
							-	
	, ‡			-				
	, <u>Ŧ</u>			E			E	
	, <u> </u>						1 F	



Precast Concrete Arch Land Bridge over NC 143 Between SR 1282 and NC 28 Rock Core Photographs Boring: LB_EB1-C

4.5 to 14.5 Feet



FEET

											<u> </u>	KE_	<u>L</u> (<u>UG</u>							
WBS	32572	2.1.FS10	0		Т	IP A	-00090	СВ		COUN	ITY (SRAH/	٩M				GEOLOGI	ST S. Brau	ın		
SITE	DESCR	IPTION	Prec	ast Co	oncrete	Arch	Land I	Bridge	over	NC 143	Betw	een SI	₹ 12	282 and	NC 28	3				GROUN	ND WTR (ft)
BORI	ING NO.	LB_E	B1-E		s	TATI	ON 3	82+51			OF	FSET	4	7 ft RT			ALIGNME	NT L		0 HR.	Dry
COLI	LAR ELI	EV . 3,	132.6	ft	Т	OTAL	DEP1	ΓH 6.	.5 ft		NC	RTHII	NG	618,59	98		EASTING	593,710		24 HR.	Dry
DRILL	RIG/HAN	/IMER EF	F./DATI	E OG	20446 [Diedrich	n D50 83	3%06/1	16/2020)	-			DRILL M	ETHOD) H.S	. Augers		HAMIV	ER TYPE	Automatic
DRIL	LER C	. Odom			S	TART	DATE	E 03/	/29/2	I	СС	MP. C	AT	E 03/2	29/21		SURFACE	WATER DE	EPTH N	A	
LEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	1	0.5ft	UNT)WS F	PER FO			00	SAMP. NO.		L O G	ELEV. (ft)	SOIL AND F			DEPTH (f
135		 - -														_	- 3,132.6	GROL	IND SURF	ACE	0
3130	3,131.6 3,129.1 3,126.1	3.5	38 65 60/0.0	35/0.1	53							100/0	- [,	D	000	V∈ 3,129.1 3,126.1	Fery Dense, Gra WEAT Gray (ME Boring Term	RESIDUAL ay, Silty GF HERED RO TA-SANDS inated with	CAVEL (A-COCK STONE)	1-a) 3.9 6.9
																		Penetration To 3,126.1 ft o (META	est Refusal On Crystall -SANDST	ne Rock	on

Sheet 22

GEOTECHNICAL BORING REPORT CORE LOG

		BURE LUG									C	ORE LUG		
WBS 32572.1.FS10	TIP A-0009CB C	COUNTY GRAHAM	GEOLOGIST S. Braun		WBS	3 32572.1.FS10		TIP /	4-0009CB		COUNT	Y GRAHAM	GEOLOGIST S. Braun	
SITE DESCRIPTION Precast Cond	crete Arch Land Bridge over NC	C 143 Between SR 1282 and NC 28	GROUND WTR (fi	(ft)	SITE	DESCRIPTION Prec	ast Cond	crete Arc	h Land Bridg	e over N	IC 143	Between SR 1282 and NC 28		GROUND WTR (ft)
BORING NO. LB_EB1-B	STATION 383+04	OFFSET 50 ft RT	ALIGNMENT L 0 HR. 8.	8.2 [BORI	RING NO. LB_EB1-B		STAT	ION 383+0	4		OFFSET 50 ft RT	ALIGNMENT L	0 HR. 8.2
COLLAR ELEV. 3,131.8 ft	TOTAL DEPTH 19.5 ft	NORTHING 618,630	EASTING 593,761 24 HR. 8.	8.0 [COLI	LAR ELEV. 3,131.8 f	ft	TOTA	L DEPTH	19.5 ft		NORTHING 618,630	EASTING 593,761	24 HR. 8.0
DRILL RIG/HAMMER EFF/DATE CG20	1446 Diedrich D50 83%06/16/2020	DRILL METHOD SE	T Core Boring HAMMER TYPE Automatic		DRILL	L RIG/HAMMER EFF./DATI	E CG204	146 Diedri	ch D50 83%06	/16/2020		DRILL METHOD SPT	Core Boring HAMM	IER TYPE Automatic
DRILLER C. Odom	START DATE 03/30/21	COMP. DATE 03/30/21	SURFACE WATER DEPTH N/A		DRIL	LLER C. Odom		STAR	T DATE 03	3/30/21		COMP. DATE 03/30/21	SURFACE WATER DEPTH N/	A
ELEV DRIVE DEPTH BLOW COU		R FOOT SAMP. V	SOIL AND ROCK DESCRIPTION		CORI	RE SIZE NQ		TOTA	L RUN 13.					
(ft) (ft) (ft) 0.5ft 0.5ft	0.5ft 0 25 50	75 100 NO. MOI G	ELEV. (ft) DEPTH	H (ft)	ELEV	RUN DEPTH RUN	DRILL RATE	REC.	N RQD (ft) % NO.	ST REC	RATA RQD (ft) %	L	ESCRIPTION AND REMARKS	
					(ft)	(ft) (ft) (ft)	(Min/ft)	(ft) %	(ft) NO.	(ft) %	(ft) %	G ELEV. (ft)	LOCKII TION AND KLIVIAKKO	DEPTH (ft)
3135			_	3	3125.8	8							Begin Coring @ 6.0 ft	
			<u>-</u> -		3123	3,125.8 6.0 3.5	N=60/0.0 4:21/1.0 5:30/1.0	0 (3.3) 94%	(2.9) 81%	(13.3 99%	6) (12.9) 5 96%	3,125.8 Fresh to Slightly Wea	CRYSTALLINE ROCK thered, Moderately Hard to Hard, Bla NE), with Very Close to Moderately C	6.0 ck-White-Gray,
3.130.8+ 1.0			3,131.8 GROUND SURFACE (RESIDUAL	0.0		3,122.3 9.5	4:39/1.0 1 2:50/0.5	(5.0)	(5.0)			(META-SANDSTON	NE), with Very Close to Moderately C Spacing	lose Fracture
	27 43	M [\frac{1}{2} \cdot \cd	 Hard, Brown-Gray, Fine to Coarse Sandy, 3.128.8 Clayey SILT (A-5), with little gravel-sized 	3.0	3120	8 3,125.8 6.0 3.5 3,122.3 9.5 5.0 3,117.3 14.5	3:02/1.0 2:06/1.0	100%	(5.0) 100% RS-4	<u>-</u> -/			RS-4: 10.1 - 10.6 ft	
3,128.3 7 3.5 22 16	13	M 000	rock fragments Medium Dense, Gray, Silty GRAVEL	_]		3 117 3 14 5	2:19/1.0					Unconfined C	Unit Weight: 174.2 pcf compressive Strength: 15,620 psi (2,2	249 ksf)
3,125.8 6.0 60/0.0		<u></u>	(A-1-a)	1 1		1 0.0		(5.0) 100%						
±			CRYSTALLINE ROCK Black-White-Gray, (META-SANDSTONE)		3115	† †	2:26/1.0 2:13/1.0) I I	100 %					
			- - REC=99%			3,112.3 19.5	2:06/1.0			_		(META-SANDSTON Unconfined C	ated at Elevation 3,112.3 ft In Crystall	19.5
3120			RQD=96% _ GSI=75-80									Borning Termina	(META-SANDSTONE)	ine Rock
±														
3115			<u>-</u>			<u> </u>								
			-			+						-		
 			Boring Terminated at Elevation 3,112.3 ft In	19.5		1 1						<u> </u>		
			Crystalline Rock (META-SANDSTONE)									E		
‡			- -			 						E		
‡			- -									<u> </u>		
			- -									[-		
‡			- -			 						[-		
‡			- -			 								
			- -									F		
			- -									[
			- -											
			- -									[
			- -											
			- -											
			- -											
1/22/22			_ -									-		
<u>i</u>			- -											
[0] †			- 											
			- -											
			- -									‡		
<u> </u>			 -											
			<u>-</u> -											
			- _											
			<u> </u>									-		
			-											
ŏ			_									<u> </u>		
			- -									 		
			- -			 						[-		
			_ -			‡						-		
			- -											
j			-			†								



Precast Concrete Arch Land Bridge over NC 143 Between SR 1282 and NC 28 Rock Core Photographs Boring: LB_EB1-B

6.0 to 19.5 Feet



GEOTECHNICAL BORING REPORT CORE LOG

	BORE LOG										COR	E LOG		
WBS 32572.1.FS10 TIP A-0009CB	COUNTY GRAHAM	GEOLOGIST D. Goodnight		WBS	\$ 32572.1.FS1	0		TIP A	-0009CB	COUN	TY GR	RAHAM	GEOLOGIST D. Good	dnight
SITE DESCRIPTION Precast Concrete Arch Land Bridge over	r NC 143 Between SR 1282 and NC 28		GROUND WTR (ft)	SITE	E DESCRIPTION	Precas	st Concr	ete Arch	Land Bridge	over NC 143	3 Betwee	en SR 1282 and NC	28	GROUND WTR (ft)
BORING NO. LB_B1-A STATION 380+54	OFFSET 11 ft RT	ALIGNMENT -L-	0 HR. 2.7	BOR	ring no. Lb_b	1-A		STATIC	ON 380+54		OFFS	SET 11 ft RT	ALIGNMENT -L-	0 HR. 2.7
COLLAR ELEV. 3,126.7 ft TOTAL DEPTH 25.1 f	ft NORTHING 618,584		24 HR. 6.0	COL	LAR ELEV. 3,	126.7 ft		TOTAL	DEPTH 2	5.1 ft	NOR	THING 618,584	EASTING 593,496	24 HR . 6.0
DRILL RIG/HAMMER EFF/DATE FME9553 CWE-550X 80% 03/12/202		PT Core Boring HAMM	ER TYPE Automatic	DRIL	L RIG/HAMMER EF	F/DATE						DRILL METHO	D SPT Core Boring	HAMMER TYPE Automatic
DRILLER J. Phillips START DATE 09/09/2		SURFACE WATER DEPTH N/.	A		LLER J. Phillips	5			DATE 09/		СОМ	IP. DATE 09/09/21	SURFACE WATER DE	PTH N/A
(ft) ELEV (ft)	PER FOOT SAMP. L O NO. MOI G	SOIL AND ROCK DESC		-	RE SIZE NQ				RUN 15.0					
(ft) (ft) (ft) 0.5ft 0.5ft 0.5ft 0	50 75 100 NO. MOI G	ELEV. (ft)	DEPTH (ft)	ELEV (ft)	RUN DEPTH	RUN (ft)	DRILL RATE (Min/ft)	RUN REC. F (ft)	ROD SAMP.	STRATA REC. RQD (ft) (ft) %	기		DESCRIPTION AND REMAR	
						()	(Min/π)	%	%	% %	G	ELEV. (ft)		DEPTH (ft)
3130		<u> </u>		3116.6 3115	2 116 6 10 1	5.0 A	V=60/0.0	(4.7)	4.0)	(14.7) (13.2 98% 88%	2)	3,116.6	Begin Coring @ 10.1 ft CRYSTALLINE ROCK	10.1
				-	1 7	0	0.36/1.0)6:20/1.0)4:34/1.0	(4.7) (4 94% 8	30%	98% 88%		Fresh to Very (META-SAND	y Slightly Weathered, Hard to Very OSTONE), with moderately close fra	Hard, Black-White-Gray, acture spacing, extremely
3125 3,125.7 1.0 9 15 11	М М	ROADWAY EMBANI Gravel (0.2 ft)) / /		3,111.6 15.1	0.0)4:12/1.0) <u>4:11/1.0</u>	(5.0)	4.2)				indurated, very thinly bedd	led
3,123.2 3.5 5 7 7		- 3,123.7 RESIDUAL Medium Dense, Brown, Silt	ty Fine SAND	3110	4 ‡	1 10	NE-26/4 O	(5.0) (4 100% 8	1					
3.120.7 + 6.0	M M	(A-2-4), with little gravel- fragments	-sized rock		3,106.6+ 20.1	000	06:16/1.0 06:03/1.0	(5.0) (5.0) (5.0)						
3 118 2		Stiff, Tan-Brown, Fine Sand	dy SILT (A-4)	3105		5.0 0	0.03/1.0 04:46/1.0 05:54/1.0	(5.0) (5	5.0)					
3,116.6 + 10.1 15 42 58/0.2 1 1 1 1 1 1 1 1 1	100/0.7	3,116.6 WEATHERED RO				0:	05:22/1.0 05:04/1.0	10070	0070					
3115	60/0.0	Tan, (META-SANDS CRYSTALLINE R	OCK		3,101.6 25.1	0.	05:04/1.0 04:53/1.0					3,101.6 Boring	Terminated at Elevation 3,101.6 ft	In Crystalline Rock
		3,117.7 3,116.6 Tan, (META-SANDS CRYSTALLINE R Black-White-Gray, (META-S REC=98% RQD=88% GSI=65-75	SANDSTONE)		‡								(META-SANDSTONE)	
3110		REC=98% RQD=88% GSI=65-75			‡									
		GSI=05-75			‡						1			
3105		 - -									F			
3103		- -			‡						F			
		3,101.6	25.1								ΙE	•		
		Boring Terminated at Elevati Crystalline Rock (META-S/	on 3,101.6 ft In ANDSTONE)		1 1						<u> </u>			
		- -									1 -			
		<u></u>			‡									
		<u> </u>			‡						<u> </u>			
					‡									
±					‡									
		_ -			‡						F			
		<u>-</u>			‡									
		<u>-</u> -			‡									
		- -			‡									
1/22/27		- -			‡						F			
		-			-						F	•		
9 +		-			1 - 1						1 E			
NO T		- -			1 ±						1 -			
		- -									1 -			
[- -			‡						1 <u>E</u>			
		<u></u>			‡									
		_			‡									
		_			‡						-	•		
		<u>-</u>			‡									
		_			‡									
		<u>-</u> -			‡									
		<u>_</u> -			‡									
8		<u>-</u> -			‡									
		 									1			



Precast Concrete Arch Land Bridge over NC 143 Between SR 1282 and NC 28 Rock Core Photographs

Boring: LB_B1-A 10.1 to 25.1 Feet



											20	$ abla \mathcal{L}$	<u></u> _	<u>UG</u>							
WBS	32572	2.1.FS1	0		TII	P A-(00090	СВ		COUN	TY (GRAH	AM				GEOLOG	IST S. Brau	n		
SITE	DESCR	IPTION	Prec	ast Cor	ncrete /	Arch L	and E	Bridge	over l	NC 143	Betw	een S	R 12	282 and	NC 28	3				GROUN	ID WTR (ft)
BOR	ING NO.	LB_B	1-D		ST	ATIO	N 38	81+22	!		OF	FSE	Γ 6	ft RT			ALIGNME	NT L		0 HR.	Dry
COL	LAR ELI	EV. 3,	127.9 f	t	тс	TAL	DEPT	H 5.	.1 ft		NC	ORTH	NG	618,5	91		EASTING	593,565		24 HR.	Dry
DRILL	_RIG/HAN	/IMER EF	F./DATE	CG2	:0446 Di	edrich I	D50 83	3%06/1	6/2020)				DRILL N	/ETHOE) H.S	6. Augers		HAMIN	MER TYPE	Automatic
DRIL	LER C	. Odom			ST	ART	DATE	04/	01/21		CC	OMP.	DAT	E 04/	01/21		SURFACE	WATER DE	PTH N	/A	
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLC 0.5ft	W COL		0	2	BLO 25	WS P	ER FOO	75	1	100	SAMP. NO.	MOI	L O G	ELEV. (ft)	SOIL AND R	OCK DES	CRIPTION	DEPTH (ft
3130	3.126.9	10						T								¥776	3,127.9		IND SURF		0.
3125	3,125.1		1	71/0.4				1				100/	1				3,125.1	Gray (ME			2.8
	3.122.8	Į.	60/0.0								-	- 60/	0.0▼				. 3,122.8	CRYS1 Gray (ME	TALLINE R		5. ⁻
			60/0.0									60/	0.0 ♥					Boring Term Penetration Te 3,122.8 ft	inated witl st Refusal	h Standard I at Elevatio ine Rock	

Sheet 27

GEOTECHNICAL BORING REPORT CORE LOG

BORE LO	OG			C	ORE LOG		
WBS 32572.1.FS10 TIP A-0009CB COUNTY GRAHAM	GEOLOGIST S. Braun		WBS 32572.1.FS10	TIP A-0009CB COUNT	Y GRAHAM	GEOLOGIST S. Braun	
SITE DESCRIPTION Precast Concrete Arch Land Bridge over NC 143 Between SR 12	282 and NC 28	GROUND WTR (ft)	SITE DESCRIPTION Precast Concr	rete Arch Land Bridge over NC 143	Between SR 1282 and NC 28		GROUND WTR (ft)
BORING NO. LB_B1-C STATION 381+90 OFFSET 5	5 ft RT ALIGNMENT L	0 HR. 8.0	BORING NO. LB_B1-C	STATION 381+90	OFFSET 5 ft RT	ALIGNMENT L	0 HR. 8.0
COLLAR ELEV. 3,129.2 ft TOTAL DEPTH 24.4 ft NORTHING		24 HR. FIAD	COLLAR ELEV. 3,129.2 ft	TOTAL DEPTH 24.4 ft	NORTHING 618,608	EASTING 593,632	24 HR. FIAD
		RTYPE Automatic	DRILL RIG/HAMMER EFF/DATE CG2044	46 Diedrich D50 83% 06/16/2020	DRILL METHOD SF	PT Core Boring HAI	MMER TYPE Automatic
	SURFACE WATER DEPTH N/A	١	DRILLER C. Odom	START DATE 04/02/21	COMP. DATE 04/02/21	SURFACE WATER DEPTH	N/A
ELEV DRIVE DEPTH BLOW COUNT BLOWS PER FOOT	SAMP. L O SOIL AND ROCK DESCRI		CORE SIZE NQ	TOTAL RUN 22.5 ft	<u> </u>		
(ii) (ft) (iii) 0.5ft 0.5ft 0.5ft 0 25 50 75 100	NO. MOI G ELEV. (ft)	DEPTH (ft)	ELEV RUN DEPTH RUN RATE (Min/ft)	RUN SAMP. STRATA REC. RQD RQD		DESCRIPTION AND REMARKS	
			(It) (IVIIII/It)	%	G ELEV. (ft)	Desire Ossis a O 4 0 ft	DEPTH (ft)
3130	3,129.2 GROUND SURFAC		3127.3 1.9 2.5 N=60/0.0	(2.5) (2.2) (22.4) (19.0	3,127.3 Fresh to Slightly We	Begin Coring @ 1.9 ft CRYSTALLINE ROCK	1.9
3,127.3 1.9 060/0.0	IVI 3,127.3 Stiff, Brown, Clayey, Fine to Co	Coarse Sandy1.9	3127.3 3,127.3 1.9 2.5 N=60/0.0 3:41/1.0 4:49/1.0 2:48/0.5 2:30/1.0 1:56/1.0 2:11/1.0 2:21/1.	100% 88% 100% 84% (5.0) (5.0)	Fresh to Slightly Wo (META-SANDST)	eathered, Moderately Hard to Hard, ONE), with Very Close to Moderately	Black-White-Gray, Close Fracture
3125	CRYSTALLINE ROC	CK	2:30/1.0 1:56/1.0 2:11/4.0	100% 100% RS-2		Spacing	
	Black-White-Gray, (META-SAN REC=100%	ANDSTONE)	3120 3,119.8 9.4 2:21/1.0 2:47/1.0			RS-2: 6.5 - 7.0 ft Unit Weight: 169.0 pcf	
3120	DOD 040/		5.0 2:38/1.0 2:30/1.0	(5.0) (4.9) 100% 98%	Unconfined	Compressive Strength: 16,160 psi (2,327 KST)
	GSI-05-75		3115 3,114.8 14.4 2:50/1.0 3:45/1.0	(5.0) (4.9) 100% 98%			
			5.0 2:45/1.0	(4.9) (3.3) 98% 66%			
3115				90% 00%			
			[3110] 3.109.8L 19.4 3.16/1 0				
3110			3:04/1.0	(5.0) (3.6) 100% 72%			
	RQD=84% GSI=65-75		3105 3,104.8 24.4 3:05/1.0 2:48/1.0		3,104.8		24.4
3105	3.104.8	24.4			Boring Termi	inated at Elevation 3,104.8 ft In Crys (META-SANDSTONE)	talline Rock
	Boring Terminated at Elevation Crystalline Rock (META-SAN	n 3.104.8 ft In					
	Crystalline Rock (WETA-SAIN	ND3TONE)			-		
					[
					E		
					-		
4/52)							
<u> </u>					F		
					[
			±		-		
<u>м</u> . — — — — — — — — — — — — — — — — — — —							
5					-		
					-		
			‡		-		
					E		
					I E		
			‡		E		



Precast Concrete Arch Land Bridge over NC 143 Between SR 1282 and NC 28 Rock Core Photographs Boring: LB_B1-C 1.9 to 24.4 Feet



			JRE LUG		
WBS 32572.1.FS10		TIP A-0009CB COUNTY	GRAHAM	GEOLOGIST S. Braun	
SITE DESCRIPTION	recast Concre	ete Arch Land Bridge over NC 143 B	etween SR 1282 and NC 28		GROUND WTR (ft)
BORING NO. LB_B1-		STATION 382+53	OFFSET 1 ft LT	ALIGNMENT L	0 HR. Dry
COLLAR ELEV. 3,12	.3 ft	TOTAL DEPTH 2.7 ft	NORTHING 618,641	EASTING 593,687	24 HR. Dry
ORILL RIG/HAMMER EFF./	ATE CG20446	16 Diedrich D50 83%06/16/2020	DRILL METHOD H.S.	Augers HAMM	ER TYPE Automatic
DRILLER C. Odom		START DATE 04/01/21	COMP. DATE 04/01/21	SURFACE WATER DEPTH N/	A
-: I FI FV -:	BLOW COUNT 5ft 0.5ft 0.5			SOIL AND ROCK DESC ELEV. (ft) 3,129.3 GROUND SURFA	DEPTH (f
3,128.3 1.0	/0.3		· · · ·	WEATHERED RO	OCK
3 126 6 7 2 7 10	70.3		1 100/03 T	Gray (META-SANDSTO	TONE) 2.3 Standard at Elevation ne Rock

Sheet 30

WBS 32572.1.FS10 **TIP** A-0009CB COUNTY GRAHAM GEOLOGIST S. Braun SITE DESCRIPTION Precast Concrete Arch Land Bridge over NC 143 Between SR 1282 and NC 28 GROUND WTR (ft) **STATION** 383+23 OFFSET 3 ft RT ALIGNMENT L BORING NO. LB B1-B 0 HR. Dry COLLAR ELEV. 3,131.0 ft TOTAL DEPTH 29.1 ft **NORTHING** 618,679 **EASTING** 593,746 24 HR. Dry DRILL RIG/HAMMER EFF./DATE CG20446 Diedrich D50 83%06/16/2020 **DRILL METHOD** SPT Core Boring HAMMER TYPE Automatic DRILLER C. Odom **START DATE** 04/01/21 COMP. DATE 04/01/21 SURFACE WATER DEPTH N/A ELEV (ft) DEPTH BLOW COUNT (ft) 0.5ft 0.5ft 0.5ft **BLOWS PER FOOT** SAMP. SOIL AND ROCK DESCRIPTION (ft) 0.5ft 0.5ft 0.5ft NO. MOI G 75 100 ELEV. (ft) DEPTH (ft) 3135 GROUND SURFACE 3,131.0 3130 3,130.0 1.0 ROADWAY EMBANKMENT M 3,129.5 3,127.8 3,101.9 Stiff, Brown, Clayey, Fine to Coarse Sandy SILT (A-4), with trace gravel 100/0.8 60/0.0 3,127.8 WEATHERED ROCK Gray (META-SANDSTONE) 3125 CRYSTALLINE ROCK Black-White-Gray, (META-SANDSTONE) RS-1 REC = 100% RQD = 86% GSI = 65-75 3120 3115 3110 3105 Boring Terminated at Elevation 3,101.9 ft In Crystalline Rock (META-SANDSTONE)

GEOTECHNICAL BORING REPORT CORE LOG

									C	01	RE L	<u>OG</u>	<u> </u>								
WBS	32572	.1.FS10)		TIP	A-000	9CB	C	OUNT	Υ (SRAHAM				C	GEOLOGI	ST S.	Braun			
				ast Concr				over NO	2 143	_				28						GROU	ND WTR (ft)
BOR	ING NO.	LB_B	1-B				383+23			OF	FSET 3	ft RT			_	ALIGNMEI				0 HR.	Dry
	LAR ELE						PTH 29.			NC	RTHING					EASTING	593,74	46	1	24 HR.	Dry
				E CG2044												ore Boring					Automatic
	LER C						TE 04/0			CC	MP. DA1	Γ E 04	4/01/21		S	SURFACE	WATE	R DEP	TH N/	A	
-	E SIZE			I DDILL		AL RUI JN	N 25.9 f		ΔΤΔ	ļ.,											
ELEV (ft)	RUN ELEV (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	REC. (ft) %	RQD (ft) %	SAMP. NO.	STR REC. (ft) %	RQD (ft) %	L O G	ELEV. (f	t)		ļ	DES	CRIPTION	AND RI	EMARK	(S		DEPTH (ft)
3127.8	3,127.8 3.126.97	3.2	0.9	N=60/0.0	(0.8)	(0.0)		(25.8)	(22.3)		3,127.8					Begin Cor CRYSTA	ing @ 3	3.2 ft			3.2
3125	3,121.9		5.0	N=60/0.0 (4:13/0.9) 3:15/1.0 5:12/1.0 4:03/1.0 4:17/1.0 3:53/1.0 2:54/1.0 2:19/1.0	(5.0) 99% (5.0)	(4.1) 81% (4.5)	RS-1	100%	`86%´				ΓÁ-SAN	DSTO	NE),	resh, Mode with Close RS-1: Unit Weignpressive S	to Mode 8.0 - 8.6 ght: 173.	erately (S ft .8 pcf	Close Fr	acture Spa	Gray,
3115	3,116.9	14.1	5.0	2:19/1.0 2:33/1.0 2:41/1.0 2:27/1.0 2:53/1.0 1:40/1.0 5:54/1.0	(5.0) 100%	(4.4)					- - - - - -										
3110] -	-	5.0	3:36/1.0 3:21/1.0 2:04/1.0 3:36/1.0 3:39/1.0 3:26/1.0	(5.0) 100%	(4.6) 92%					- - - - - -										
3105	3,106.9	-	5.0	2:38/1.0 2:40/1.0 2:49/1.0 3:27/1.0 2:27/1.0 3:07/1.0	(5.0) 100%	(4.7) 94%					3,101.9		D .	·		ed at Elevat		4061	0		29.1
																(META-S					



Precast Concrete Arch Land Bridge over NC 143 Between SR 1282 and NC 28 Rock Core Photographs Boring: LB, B1-B




PROJECT REA	FERENCE NO.	SHEET NO.
A-00	09CB	33
LAB	RESU	<i>JLTS</i>

				ROCK	TEST RESULTS		
SAMPLE	BORING	STATION	OFFSET	DEPTH	ROCK TYPE	UNIT WEIGHT	UNCONFINED COMPRESSIVE
NO.	DOMING	BIATION	OFFSET	INTERVAL	ROOK TITE	(PCF)	STRENGTH
RS-1	LB_B1-B	383+23 -L-	3'RT	8.0 - 8.6'	META-SANDSTONE	173.8	21,490 psi/3,095 ksf
RS–2	<i>LB_B1-C</i>	381+90 -L-	5'RT	6.5 - 7.0'	META-SANDSTONE	169.0	16,160 psi/2,327 ksf
RS–3	LB_EB1-A	380 + 73 -L-	48' RT	13.3 - 13.9'	META-SANDSTONE	171.5	20,620 psi/2,969 ksf
RS-4	LB_EB1-B	383+04 -L-	50' RT	10.1 - 10.6'	META-SANDSTONE	174.2	15,620 psi/2,249 ksf
RS– 5	LB_EB1-C	381+88 -L-	51' RT	10.0 - 10.6'	META-SANDSTONE	175.6	22,000 psi/3,168 ksf

LAB TESTING PERFORMED BY NCDOT LAB CERT NO. 117-1104

PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	34

GEOPHYSICAL TEST RESULTS - SEISMIC REFRACTION LINE 19.2




GEOPHYSICAL TESTING PERFORMED BY GEL SOLUTIONS. REFERENCE "SEISMIC REFRACTION SURVEY FOR EVALUATION OF ROCK" DATED 10/01/2021 CG2 ESTIMATED WAVE SPEED FOR WEATHERED ROCK: 4,500 FT/SEC

CG2 ESTIMATED WAVE SPEED FOR CRYSTALLINE ROCK: 7,500 FT/SEC

PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	35

GEOPHYSICAL TEST RESULTS - SEISMIC REFRACTION LINE 19.3



GEOPHYSICAL TESTING PERFORMED BY GEL SOLUTIONS. REFERENCE "SEISMIC REFRACTION SURVEY FOR EVALUATION OF ROCK" DATED 10/01/2021 CG2 ESTIMATED WAVE SPEED FOR WEATHERED ROCK: 4,500 FT/SEC

CG2 ESTIMATED WAVE SPEED FOR CRYSTALLINE ROCK: 7,500 FT/SEC

REFERENCE

CONTENTS

DESCRIPTION

LEGEND (SOIL & ROCK)

TITLE SHEET

WALL ENVELOPE

CROSS SECTIONS BORE LOGS

SITE PLAN

SHEET NO.

5-6

3

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY _GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION _RETAINING WALL #10: MECHANICALLY STABILIZED EARTH (MSE) WALL ON -L- FROM 316+45 RT TO 317+67 RT

STATE PROJECT REFERENCE NO. A-0009CB

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (1991) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSURFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BORCHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOD. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS INCLORDED TO CLIMATIC CONDITIONS INCLORDED TO CLIMATIC CONDITIONS INCLORDING TO CLIMATIC CONDITIONS INCLORDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS, AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

CG2 EXPLORATE	ION
C. PIERCY	
N. MCLAREN	

INVESTIGATED BY __CG2

DRAWN BY __M. BREWER, P.E.

CHECKED BY __R. KRAL, P.E.

SUBMITTED BY <u>M. Brewer</u>, P.E.

DATE _MAY 2022





D. Matthew Brewer -386129C0ASGNATURE

6/7/2022

DOCUMENT NOT CONSIDERED FINAL

UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO. SHEET NO.

A-0009CB


2


NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION


SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS

004 0500007404	201017101	Total Scool Scool Street	
SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED	TERMS AND DEFINITIONS
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.	ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586), SOIL CLASSIFICATION	GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.	SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN	<u>AQUIFER</u> - A WATER BEARING FORMATION OR STRATA.
IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH	ANGULARITY OF GRAINS	REPRESENTED BY A ZONE OF WEATHERED ROCK.	ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF.GRAY.SILTY CLAY.MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC.A-7-6	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:	ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING
SOIL LEGEND AND AASHTO CLASSIFICATION	ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED VILVA NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.	A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
CENERAL CRANIII AR MATERIALS SILT-CLAY MATERIALS	MINERALOGICAL COMPOSITION	EINE TO COARSE CRAIN ICNEOUS AND METAMORPHIC POCK THAT	ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND
CLASS. (≤ 35% PASSING *200) (> 35% PASSING *200) ORGANIC MATERIALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC.	BOOK (CB) WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE,	SURFACE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5	ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	UNEISS, CARBERO, SCHIST, ETC.	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
CLASS. A-1-0 A-1-6 A-2-4 A-2-5 A-2-6 A-2-7 A-7-6 A-3 A-6, A-7	COMPRESSIBILITY	NON-CHISTALLINE SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED.	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM
SYMBOL 000000000000000000000000000000000000	SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD	OF SLOPE.
7. PASSING	HIGHLY COMPRESSIBLE LL > 50	SEDIMENTARY ROCK SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
*10 50 MX GRANULAR SILI- MUCK,	PERCENTAGE OF MATERIAL	(CP) SHELL BEDS, ETC. WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT
*40 30 MX 50 MX 51 MN SOLLS SOLLS PEAT *200 15 MX 25 MX 10 MX 35 MX 35 MX 35 MX 36 MN	GRANULAR SILT - CLAY ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL		ROCKS OR CUTS MASSIVE ROCK.
MATERIAL	TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 10%	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER HAMMER IF CRYSTALLINE.	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE
PASSING *40 SOILS WITH	LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20%	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN,	HORIZONTAL.
LL 40 MX 41 MN	MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35% HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE	(V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF	<u>DIP DIRECTION (DIP AZIMUTH)</u> - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
GROUP INDEX 0 0 0 4 MX 8 MX 12 MX 16 MX NO MX AMOUNTS OF	GROUND WATER	OF A CRYSTALLINE NATURE.	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE
OPCANIC SULS		SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO (SLI.) 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR	SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
USUAL TYPES STONE FRAGS. FINE SILTY OR CLAYEY SILTY CLAYEY MATTER OF MAJOR GRAVEL, AND CAMP CRAYER AND CAMP COLOR	▼ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING	CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
MATERIALS SAND SAND GRAVEL AND SAND SOILS SOILS	STATIC WATER LEVEL AFTER 24 HOURS	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM
GEN. RATING EXCELLENT TO GOOD FAIR TO POOR POOR UNSUITABLE	PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA	(MOD.) GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	PARENT MATERIAL.
AS SUBURADE.	SPRING OR SEEP	WITH FRESH ROCK.	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ;PI OF A-7-6 SUBGROUP IS > LL - 30		MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL	FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.
CONSISTENCY OR DENSENESS	MISCELLANEOUS SYMBOLS	SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH (MOD. SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK, ROCK GIVES "CLUNK" SOUND WHEN STRUCK.	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
PRIMARY SOIL TYPE COMPACTNESS OR RANGE OF STANDARD RANGE OF UNCONFINED PENETRATION RESISTENCE COMPRESSIVE STRENGTH	ROADWAY EMBANKMENT (RE) 25/025 DIP & DIP DIRECTION	IF TESTED, WOULD YIELD SPT REFUSAL	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO
CONSISTENCY (N-VALUE) (TONS/FT ²)	☐ ☐ WITH SOIL DESCRIPTION → OF ROCK STRUCTURES	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT	ITS LATERAL EXTENT.
GENERALLY VERY LOOSE < 4	SOIL SYMBOL SOIL SYMBOL STATE TEST BORING SLOPE INDICATOR INSTALLATION	(SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
GRANULAR LOOSE 4 TO 10 GRANULAR MEDIUM DENSE 10 TO 30 N/A	 南	IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF	MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS
MATERIAL DENSE 30 TO 50	ARTIFICIAL FILL (AF) OTHER THAN ROADWAY EMBANKMENT AUGER BORING CONE PENETROMETER	VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE	USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
VERT DENSE 2 2 DB	4	SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK (V SEV.) REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR	PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.
VERY SOFT < 2	— INFERRED SOIL BOUNDARY — CORE BORING SOUNDING ROD	VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</u>	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0	INFERRED ROCK LINE MONITORING WELL TEST BORING WITH CORE	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND	ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF
MATERIAL STIFF 8 TO 15 1 TO 2	PIEZOMETER COT NOT NOT NOT NOT NOT NOT NOT NOT NOT N	SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS ALSO AN EXAMPLE.	ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE
HARD > 30 > 4	INSTALLATION SPT N-VALUE		RUN AND EXPRESSED AS A PERCENTAGE.
TEXTURE OR GRAIN SIZE	RECOMMENDATION SYMBOLS	ROCK HARDNESS	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.
U.S. STD. SIEVE SIZE 4 10 40 60 200 270	UNDERCUT UNCLASSIFIED EXCAVATION - UNCLASSIF	VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND
OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	UNSUITABLE WASTE	HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED	RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO
BOULDER COBBLE GRAVEL COARSE FINE SILT CLAY	SHALLOW UNCLASSIFIED EXCAVATION - UNDERCUT UNCLASSIFIED EXCAVATION - EMBANKMENT OR BACKFILL	TO DETACH HAND SPECIMEN.	THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
(BLDR.) (COB.) (GR.) (CSE. SD.) (F SD.) (SL.) (CL.)	ABBREVIATIONS	MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.
GRAIN MM 305 75 2.0 0.25 0.05 0.005	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST	HARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF
SIZE IN. 12 3	BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED	MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT.	A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL
SOIL MOISTURE - CORRELATION OF TERMS	- CL CLAY MOD MODERATELY 7 - UNIT WEIGHT	HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER, SPT REFUSAL IS PENETRATION EQUAL
SOLI MOISTURE SCALE FIELD MOISTURE	CPT - CONE PENETRATION TEST NP - NON PLASTIC 7 _d - DRY UNIT WEIGHT CSE COARSE ORG ORGANIC	POINT OF A GEOLOGIST'S PICK.	TO OR LESS THAN 0.1 FOOT PER 60 BLOWS. STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY
(ATTERBERG LIMITS) OESCRIPTION GUIDE FOR FIELD MOISTURE DESCRIPTION	DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST <u>SAMPLE ABBREVIATIONS</u>	SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK, CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN	TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY	DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON	PIECES CAN BE BROKEN BY FINGER PRESSURE.	STRATA ROCK QUALITY DESIGNATION (SROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL
(SAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE	VERY CAN BE CARVED WITH KNIFE, CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY	LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
PLASTIC PLOUID LIMIT	FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK	FINGERNAIL.	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
RANGE - WET - (W) SEMISULIDE REQUIRES DRING TO	FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL FRAGS FRAGMENTS TCR - TRICONE REFUSAL FRAGGS FRAGMENTS TCR - TRICONE REFUSAL FRAGMENTS TCR - TR	FRACTURE SPACING BEDDING	BENCH MARK: N/A
(PI) PL PLASTIC LIMITATTAIN OPTIMUM MOISTURE	HI HIGHLY V - VERY RATIO	TERM SPACING TERM THICKNESS	BENCH MARK: N/ A
	EQUIPMENT USED ON SUBJECT PROJECT	VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET	ELEVATION: FEET
OM \(\psi\) OPTIMUM MOISTURE	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:	WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET	
SL SHRINKAGE LIMIT	CME-45C CLAY BITS X AUTOMATIC MANUAL	CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET	NOTES:
- DRY - (D) REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	6 CONTINUOUS FLIGHT AUGER CORE SIZE:	VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.008 FEET THINLY LAMINATED < 0.008 FEET	SURVEY AND ROADWAY DESIGN FILES PROVIDED BY TGS ENGINEERS ON 11/15/2021
PLASTICITY	X CME-550 X 8*HOLLOW AUGERS CORE SIZE: -BH	INDURATION	
		FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	
PLASTICITY INDEX (PI) DRY STRENGTH NON PLASTIC 0-5 VERY LOW	X CME-550X	DIRDING WITH FINCED EDEER NUMEDOUG CRAING.	
SLIGHTLY PLASTIC 6-15 SLIGHT	I I VANE SHEAR TEST I □ □ I HAND TODIS•	FRIABLE GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	
MODERATELY PLASTIC 16-25 MEDIUM HIGHLY PLASTIC 26 OR MORE HIGH	CASING W/ ADVANCER POST HOLE DIGGER	MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE;	
	PORTABLE HOIST TRICONE STEEL TEETH HAND AUGER	BREAKS EASILY WHEN HIT WITH HAMMER.	
COLOR	TRICONE TUNGCARB. SOUNDING ROD	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE: DIFFICULT TO BREAK WITH HAMMER.	
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY).	CORE BIT VANE SHEAR TEST		
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	DATE: 8-15-1
		1	









	BORE LOG						
WBS 32572.1.FS10 TIP A-0009	CB COUNTY GRAHAM	GEOLOGIST N. McLaren		WBS 32572.1.FS10	TIP A-0009CB COUN	NTY GRAHAM	GEOLOGIST C. Piercy
SITE DESCRIPTION Upgrade NC 143 from SR 12	223 (Beech Creek Road) to 0.5 Miles North of Appal	achian Trail	GROUND WTR (ft)	SITE DESCRIPTION Upgrade No	C 143 from SR 1223 (Beech Creek I	Road) to 0.5 Miles North of Appal	lachian Trail GROUND WTR (ft)
BORING NO. RWAL10_B-1 STATION 3	316+56 OFFSET 26 ft RT	ALIGNMENT L	0 HR. Dry	BORING NO. RWAL10_B-2	STATION 317+60	OFFSET 35 ft RT	ALIGNMENT L 0 HR. Dry
COLLAR ELEV. 2,661.7 ft TOTAL DEP	TH 20.0 ft NORTHING 621,083	EASTING 591,668	24 HR. Dry	COLLAR ELEV. 2,672.9 ft	TOTAL DEPTH 20.0 ft	NORTHING 621,115	EASTING 591,777 24 HR. Dry
DRILL RIG/HAMMER EFF/DATE CG29473 CVE-550 79%	603/12/2021 DRILL METHOD	I.S. Augers HAMIN	MERTYPE Automatic	DRILL RIG/HAMIVIER EFF/DATE BRE	E9533 CME-550X 78% 03/12/2021	DRILL METHOD	H.S. Augers HAMINIER TYPE Automatic
DRILLER J. Estep START DAT	E 04/28/21 COMP. DATE 04/28/21	SURFACE WATER DEPTH N	/A	DRILLER J. Phillips	START DATE 04/28/21	COMP. DATE 04/28/21	SURFACE WATER DEPTH N/A
ELEV DRIVE ELEV (ft) DEPTH BLOW COUNT 0.5ft 0.5ft 0.5ft 0	BLOWS PER FOOT SAMP. 25 50 75 100 NO. MOI G	SOIL AND ROCK DES	SCRIPTION DEPTH (ft)	ELEV COLUMN (ft) DRIVE COLUMN (ft) DRIVE (ft) DEPTH BLOW COLUMN (ft) 0.5ft 0.5ft		75 100 NO. MOI G	
2665	M L		IKMENT -Brown, Fine to	2675 2,671.9 1.0 2 5 2670 2.669.4 3.5	9	- · · · · · · M L	2,672.9 GROUND SURFACE 0.0 ROADWAY EMBANKMENT Soft to Stiff, Brown, Fine to Coarse Sandy SILT (A-4(0)), with trace gravel
2,658.2 3.5 2 1 4 2,655.7 6.0 10 11 11 2,653.2 8.5	M L	Coarse Sandy SILT (Å-organics 2,656.2 RESIDUAL 2,653.7 Medium Dense, Tan-Or Clayey, Silty Fine to Coarse with trace grayel-sized re- with trace grayel-sized re-	4), with trace <u>5.5</u>	2,666.9 6.0 15 11 2665	→ → → → → → → →	55-8089 18%	2,667.4 RESIDUAL Medium Dense, Brown-Gray, Silty Fine to 2,664.4 Coarse SAND (A-2-4), with trace gravel-sized rock fragments
2,648.2 13.5 3 2 6	M		Orange-Brown, (A-4), with trace	2,659.4 13.5 26 27		ō : : : : : M	WEATHERED ROCK 2,660.9 Brown-Gray, (META-SILTSTONE) RESIDUAL Medium Dense to Very Dense, Gray-Brown, Silty Fine to Coarse SAND (A-2-4), with
2645	30 M	2,644.7 Medium Dense to Orange-Tan-Gray, Silty F 2,641.7 SAND (A-2-4), with trace g	ine to Coarse	21 12	10 22		trace gravel-sized rock fragments 2,652.9 Boring Terminated at Elevation 2,652.9 ft In
NCDOT BORE DOUBLE A-0009CB_GEO_RUY_GIM.GFJ NV_DVI.GUI 3/2/2/		Fragments Boring Terminated at Eleva Residual Silty Sance	ition 2,641.7 ft In				Residual Silty Sand (A-2-4)

REFERENCE

CONTENTS

DESCRIPTION

LEGEND (SOIL & ROCK)

TITLE SHEET

WALL ENVELOPE

CROSS SECTIONS BORE LOGS

SITE PLAN

SHEET NO.

5-8

3

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY _GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION RETAINING WALL #11: CAST-IN-PLACE CONCRETE WALL WITH ARCHITECTURAL FORM LINER FINISH ON -L-FROM 330+82 LT TO 333+24 LT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	A-0009CB	1	10

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (1991) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSUFFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BORCHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE OR INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS, AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

NOTES:

1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

CG2 EXPLORATION **BRECCIA** S. BRAUN

N. MCLAREN

C. PIERCY

INVESTIGATED BY __CG2

DRAWN BY __M. BREWER, P.E.

CHECKED BY R. KRAL, P.E.

SUBMITTED BY __M. BREWER, P.E.

DATE _MAY 2022



CAROLINAS **GEOTECHNICAL** GROUP 2400 CROWNPOINT EXECUTIVE DRIVE

SUITE 800 CHARLOTTE, NC 28227 (980) 339-8684



-386129C0A4C1462

05/06/2022

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO. SHEET NO.

A-0009CB


2


NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION


SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS


SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS	
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.	HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.	
ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM DI586). SOIL CLASSIFICATION	<u>UNIFORMLY GRADED</u> - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. <u>GAP-GRADED</u> - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.	SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL. THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN	AQUIFER - A WATER BEARING FORMATION OR STRATA.	
IS BASED ON THE AASHTO SYSTEM, BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH		ANGULARITY OF GRAINS REPRESENTED BY A ZONE OF WEATHERED ROCK.		
AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SULTY CLAY, MOIST WITH INTERBEDDED FINE SAID LAYERS, HIGHLY PLASTIC, A-7-6	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:	ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING	
SOIL LEGEND AND AASHTO CLASSIFICATION	ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > 100 BLOWS PER FOOT IF TESTED.	A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT	
CENERAL CRANIII AR MATERIALS SILT-CLAY MATERIALS	MINERALOGICAL COMPOSITION	FINE TO COARSE CRAIN IGNEOUS AND METAMORPHIC ROCK THAT	WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND	
CLASS. (≤ 35% PASSING *200) (> 35% PASSING *200) ORGANIC MATERIALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC.	WOULD YIELD SPT REFUSAL IF TESTED, ROCK TYPE INCLUDES GRANITE,	SURFACE.	
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5	ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	UNELSS, OHBERU, SCHIST, ETC.	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.	
CLASS. A-1-0 A-1-b A-2-4 A-2-5 A-2-6 A-2-7 A-7-6 A-3 A-6, A-7	COMPRESSIBILITY	NON-CRYSTALLINE ROCK (NCR) SEDIMENTARY ROCK THAT WOULD YELLD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.	
SYMBOL 0000 d00000 0000 0000 0000 0000 0000	SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED	
7. PASSING SUIT-	HIGHLY COMPRESSIBLE LL > 50	SEDIMENTARY ROCK SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED (CP) SHELL BEDS, ETC.	BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.	
*10 50 MX GRANULAR CLAY PEAT SOILS SOILS CLAY PEAT	PERCENTAGE OF MATERIAL	WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT	
*200 15 MX 25 MX 10 MX 35 MX 35 MX 35 MX 35 MX 36 MN 36 MN 36 MN 36 MN 36 MN 36 MN	GRANULAR SILT - CLAY ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER	ROCKS OR CUTS MASSIVE ROCK.	
MATERIAL	TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 10% LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20%	HAMMER IF CRYSTALLINE.	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.	
PASSING *40 40 MX 41 MN	MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35%	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, (V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE	
PI 6 MX NP 10 MX 10 MX 11 MN 11 MN 10 MX 10 MX 11 MN 11 MN 11 MN MODERATE HIGHLY	HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE	OF A CRYSTALLINE NATURE.	LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.	
GROUP INDEX 0 0 0 4 MX 8 MX 12 MX 16 MX NO MX AMOUNTS OF SOILS	GROUND WATER	SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.	
USUAL TYPES STONE FRAGS. FINE SILTY OR CLAYEY SILTY CLAYEY MATTER	✓ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING	(SLI.) 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR CRYSTALS ARE DULL AND DISCOLORED. CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.	
OF MAJOR GRAYEL, AND SAND GRAYEL AND SAND SOILS SOILS	$lacktriangle$ Static water level after $\underline{24}$ Hours	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM	
CEN RATING FAIR TO		(MOD.) GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS	PARENT MATERIAL.	
AS SUBGRADE EXCELLENT TO GOOD FAIR TO POOR POOR UNSUITABLE	SPRING OR SEEP	DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED WITH FRESH ROCK.	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.	
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ;PI OF A-7-6 SUBGROUP IS > LL - 30	-	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL	FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE	
CONSISTENCY OR DENSENESS	MISCELLANEOUS SYMBOLS	SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH (MOD. SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK, ROCK GIVES "CLUNK" SOUND WHEN STRUCK.	FIELD. JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.	
PRIMARY SOIL TYPE COMPACTNESS OR PENETRATION RESISTENCE COMPRESSIVE STRENGTH	ROADWAY EMBANKMENT (RE) 25/025 DIP & DIP DIRECTION	IF TESTED, WOULD YIELD SPT REFUSAL	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO	
CONSISTENCY CONSISTENCY (N-VALUE) (TONS/FT ²)	₩ITH SOIL DESCRIPTION → OF ROCK STRUCTURES	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT	ITS LATERAL EXTENT.	
GENERALLY VERY LOOSE < 4 LOOSE 4 TO 10	SOIL SYMBOL SOIL SYMBOL SPT DWT TEST BORING SLOPE INDICATOR INSTALLATION	(SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.	
LOOSE	RT	IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF	MOTILED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTILING IN SOILS	
MATERIAL DENSE 30 TO 50	ARTIFICIAL FILL (AF) OTHER AUGER BORING CONE PENETROMETER THAN ROADWAY EMBANKMENT AUGER BORING TEST	VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC ELEMENTS ARE DISCERNIBLE	USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.	
VERY SOFT < 2 < 0.25	INFERRED SOIL BOUNDARY - CORE BORING SOUNDING ROD	SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK (V SEV.) REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR	PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE OF AN INTERVENING IMPERVIOUS STRATUM.	
GENERALLY SOFT 2 TO 4 0.25 TO 0.5	MW - TECT DODING	VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</u>	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.	
SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0 MATERIAL STIFF 8 TO 15 1 TO 2	INFERRED ROCK LINE MONITORING WELL WITH CORE	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS	ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF	
(COHESIVE) VERY STIFF 15 TO 30 2 TO 4	→▼→→→→ ALLUVIAL SOIL BOUNDARY △ PIEZOMETER INSTALLATION ── SPT N-VALUE	ALSO AN EXAMPLE.	ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.	
HARD > 30 > 4		ROCK HARDNESS	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT	
TEXTURE OR GRAIN SIZE	RECOMMENDATION SYMBOLS	VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES	ROCK.	
U.S. STD. SIEVE SIZE 4 10 40 60 200 270 OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	UNDERCUT UNCLASSIFIED EXCAVATION - UNCLASSIFIED EXCAVATION - UNSUITABLE WASTE UNCLASSIFIED EXCAVATION - ACCEPTABLE, BUT NOT TO BE	SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO	
COARCE FINE	SHALLOW UNCLASSIFIED EXCAVATION - USED IN THE TOP 3 FEET OF	HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED TO DETACH HAND SPECIMEN.	THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.	
BOULDER COBBLE GRAVEL SAND SAND SILT CLAY		MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT	
(CSE. SD.) (F SD.)	ABBREVIATIONS	HARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED	OR SLIP PLANE.	
GRAIN MM 305 75 2.0 0.25 0.05 0.005 SIZE IN. 12 3	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED	BY MODERATE BLOWS.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB, HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL	
	CL CLAY MOD MODERATELY γ - UNIT WEIGHT	MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL	
SOIL MOISTURE - CORRELATION OF TERMS	_ CPT - CONE PENETRATION TEST NP - NON PLASTIC $\gamma_{ m d}$ - DRY UNIT WEIGHT	POINT OF A GEOLOGIST'S PICK.	TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.	
SOIL MOISTURE SCALE FIELD MOISTURE GUIDE FOR FIELD MOISTURE DESCRIPTION (ATTERBERG LIMITS) DESCRIPTION	CSE COARSE ORG ORGANIC DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST SAMPLE ABBREVIATIONS	SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK, CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.	
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY	DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK	PIECES CAN BE BROKEN BY FINGER PRESSURE.	STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL	
(SAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES 1 INCH	TENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.	
PLASTIC PLOUID LIMIT COMMISSION DEGLINES PRIVING TO	FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK	SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE, CAN BE SCRATCHED READILY BY FINGERNAIL.	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.	
RANGE / - WET - (W) SEMISULID; REQUIRES DRYING TO	FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL W - MOISTURE CONTENT CBR - CALIFORNIA BEARING	FRACTURE SPACING BEDDING	BENCH MARK: N/A	
(PI) PL PLASTIC LIMIT	HI HIGHLY V - VERY RATIO	TERM SPACING TERM THICKNESS	BENCH MARK: N/A	
- MOIST - (M) COLID. AT OR NEAR ORTIMIN MOISTURE	EQUIPMENT USED ON SUBJECT PROJECT	VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET	ELEVATION: FEET	
OM OPTIMUM MOISTURE SLL SHRINKAGE LIMIT	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:	MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET	NOTEC:	
PEOLIPES ADDITIONAL WATER TO	CME-45C CLAY BITS X AUTOMATIC MANUAL	CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET	NOTES:	
- DRY - (D) ATTAIN OPTIMUM MOISTURE	X CME-550 G* CONTINUOUS FLIGHT AUGER CORE SIZE:	THINLY LAMINATED < 0.008 FEET	SURVEY AND ROADWAY DESIGN FILES PROVIDED BY TGS ENGINEERS ON 11/15/2021	
PLASTICITY	X 8 HOLLOW AUGERS	INDURATION		
PLASTICITY INDEX (PI) DRY STRENGTH	X CME-550X HARD FACED FINGER BITS	FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.		
NON PLASTIC 0-5 VERY LOW	TUNGCARBIDE INSERTS	RUBBING WITH FINGER FREES NUMEROUS GRAINS;		
SLIGHTLY PLASTIC 6-15 SLIGHT MODERATELY PLASTIC 16-25 MEDIUM	VANE SHEAR TEST CASING W/ ADVANCER HAND TOOLS:	GENILE BLUW BY HAMMER DISINIEGRATES SAMPLE.		
HIGHLY PLASTIC 26 OR MORE HIGH	POST HOLE DIGGER	MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE; BREAKS EASILY WHEN HIT WITH HAMMER.		
COLOR	TOUGHT AUGUST	CRAINS ARE DISCIPLET TO SERVADATE WITH STEEL PROPE.		
	X DIEDRICH D50	INDURATED DIFFICULT TO BREAK WITH HAMMER.		
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY). MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.	CORE BIT VANE SHEAR TEST	EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE;		
		SAMPLE BREAKS ACROSS GRAINS.	DATE: 8-15-1	














	<i></i>	BORE LOG								
WBS 32572.1.FS10	TIP A-0009CB COUN	TY GRAHAM	GEOLOGIST N. McLaren		WBS 32572.1.FS	10	TIP A-0009CB COUN	NTY GRAHAM	GEOLOGIST S. Braun	
SITE DESCRIPTION Upgrade NO	143 from SR 1223 (Beech Creek R	Road) to 0.5 Miles North of Appalacl	nian Trail	GROUND WTR (ft)	SITE DESCRIPTION	N Upgrade N	IC 143 from SR 1223 (Beech Creek I	Road) to 0.5 Miles North of Ap	palachian Trail	GROUND WTR (ft)
BORING NO. RWAL11_B-1	STATION 330+83	OFFSET 21 ft LT	ALIGNMENT L	0 HR. 1.0	BORING NO. RW	'AL11_B-2	STATION 331+71	OFFSET 50 ft LT	ALIGNMENT L	0 HR. Dry
COLLAR ELEV. 2,780.9 ft	TOTAL DEPTH 20.0 ft	NORTHING 622,012	EASTING 592,730	24 HR. 1.0	COLLAR ELEV.	2,801.0 ft	TOTAL DEPTH 18.5 ft	NORTHING 622,083	EASTING 592,790	24 HR. Dry
DRILL RIG/HAMMER EFF/DATE CG2	9473 CME-550 79%03/12/2021	DRILL METHOD H.S	S. Augers HAM	MERTYPE Automatic	DRILL RIG/HAMMER	EFF./DATE CG	20446 Diedrich D50 83% 06/16/2020	DRILL METHOL	D H.S. Augers HA	MMER TYPE Automatic
DRILLER J. Estep	START DATE 04/28/21	COMP. DATE 04/28/21	SURFACE WATER DEPTH	N/A	DRILLER C. Odo	m	START DATE 04/30/21	COMP. DATE 04/30/21	SURFACE WATER DEPTH	N/A
ELEV DRIVE DEPTH BLOW COL		OT SAMP. V	SOIL AND ROCK DE	SCRIPTION	ELEV DRIVE DEP	H BLOW CO	DUNT BLOWS PER FO	OT SAMP.	L SOIL AND ROCK E	IESCRIPTION
(ft) (ft) (ft) 0.5ft 0.5ft	0.5ft 0 25 50	75 100 NO. MOI G		DEPTH (ft)	(ft) (ft) (ft)	0.5ft 0.5ft	0.5ft 0 25 50	75 100 NO. MOI		2001111 11011
2785			_		2805					
					‡				_	
-			2,780.9 GROUND SUR	RFACE 0.0	10000				2,801.0 GROUND SL	
2780 2,779.9 1.0 3 3	5	W N	RESIDUA Medium Stiff to Stiff, Bro	own-Gray, Fine	2800 2,800 0 1.0	4 5	6 11		RESIDU Stiff to Very Stiff, Brow	vn-Gray, Fine to
2,777.4 3.5 5 3	.[· · · · · ·	Sandy, Clayey SILT (A. organics	; i	2,797.5	4 7	3		Coarse Sandy SILT (A- little gravel-sized ro	4(0)), with trace to ock fragments
2775 2,774.9 6.0	.98		Medium Stiff to	o Stiff,	2795 2,795.0 6.0	3 11	7			
2,772.4 7 8.5	4	· · · · · · M	Tan-Orange-Gray-Brown Sandy SILT (.	(A-4)	2,792.5 8.5	1 - 1	1 1 1 1 1 1 1 1 1 1			
2770	9	: :::: w			2790	13 6	4 . 410	· · · · · · W		
+			-		+					
2,767.4 13.5 3 3	9 12 1 1 1 1 1 1 1 1	: : : : : _M			2,787.5 13.5	8 11	6			
2765			-		2785		· · · • · · · · · · · · · · · ·	"		
2,762.4 18.5					2,782.5T 18.5	5			2,782.5	18.5
4 5	8 13		2,760.9 Boring Terminated at Elev	20.0	' ‡	60/0.0		60/0.0	Boring Terminated Penetration Test Refu	ısal at Elevation
			Residual Sandy S	Silt (A-4)	‡				2,782.5 ft On Crys (META-SILTS	stalline Rock STONE)
					‡				`	,
			-		‡				-	
					‡					
					‡					
			-		‡				-	
‡					‡					
‡			-		‡				-	
					‡					
					‡				-	
			-						F	
									-	
1/56/2			-						[
									[
			_						<u> </u>	
					I					
THE TOTAL PROPERTY OF			-						[
			_		1 1 ±					
<u> </u> +			-		±				-	
			_						<u> </u>	
									E	
žL I I I					<u></u>				1 1	

GEOTECHNICAL BORING REPORT BORE LOG

		BORE LOG						
WBS 32572.1.FS10	TIP A-0009CB COUN	TY GRAHAM	GEOLOGIST S. Braun		WBS 32572.1.FS10	TIP A-0009CB COUNT	TY GRAHAM	GEOLOGIST C. Piercy
SITE DESCRIPTION Upgrade NC				GROUND WTR (ft)	SITE DESCRIPTION Upgrade N	NC 143 from SR 1223 (Beech Creek R		
BORING NO. RWAL11_B-3	STATION 332+44	OFFSET 46 ft LT	ALIGNMENT L	0 HR. 11.5	BORING NO. RWAL11_B-4	STATION 333+24	OFFSET 21 ft LT	ALIGNMENT L 0 HR. Dry
COLLAR ELEV. 2,803.5 ft	TOTAL DEPTH 30.0 ft	NORTHING 622,117		24 HR. FIAD	COLLAR ELEV. 2,799.3 ft	TOTAL DEPTH 20.0 ft	NORTHING 622,138	EASTING 592,936 24 HR. 9.0
DRILL RIG/HAMMER EFF./DATE CG204		DRILL METHOD H.S	S. Augers HAMM	TER TYPE Automatic	DRILL RIG/HAMMER EFF/DATE BR		DRILL METHOD H.	S. Augers HAMMER TYPE Automatic
DRILLER C. Odom	START DATE 04/29/21	COMP. DATE 04/29/21	SURFACE WATER DEPTH N/	′A	DRILLER J. Phillips	START DATE 04/28/21	COMP. DATE 04/28/21	SURFACE WATER DEPTH N/A
ELEV (ft) DEPTH BLOW COUNTY (ft) 0.5ft 0.5ft 0		75 100 NO. MOI G	SOIL AND ROCK DES	CRIPTION DEPTH (ft)	ELEV Cft) DRIVE CFT BLOW CC (ft) 0.5ft 0.5ft		75 100 NO. MOI G	SOIL AND ROCK DESCRIPTION
2,802.5 1.0 4 4	3	· · · · · · M	2,803.5 GROUND SURF RESIDUAL Medium Stiff to to Ve	ery Stiff,	2,798.3 1.0 3 2 2,795.8 3.5		SS-8082 22%	-2,799.3 GROUND SURFACE 0. RESIDUAL Soft to Medium Stiff, Brown-Gray, Fine to 2,796.3 Coarse Sandy SILT (A-4(4))3.
2.797.5 6.0	5		Brown-Black-Gray-Tan, F Sandy SILT (A-4), with trac gravel-sized rock fra .	e organics and	2,793.3 6.0 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	5 	M	Loose, Red-Brown, Silty Fine to Coarse 2,793.8 SAND (A-2-4) Medium Stiff, Red-Brown, Fine to Coarse Sandy SILT (A-4)
2790 2.790.0 13.5	6 • • • • • • • • • • • • • • • • • • •		-		2 785 8 13 5	90/0.4		- 2,785.3 14.
2785 2,785.0 18.5 11 10	4		:		2,780.8 18.5 2 4	6		WEATHERED ROCK Black-Red-Brown, (META-SILTSTONE) 17
2780 2,780.0 23.5 21 79/0.3 2775 2,775.0 28.5	6	· · · · · · · · · · · · · · · · · · ·	2,780.0 Gray, (META-SILTS - 2,776.5 RESIDUAL Stiff, Brown-Gray, Fine to 0	STONE) 			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Boring Terminated at Elevation 2,779.3 ft In Residual Silty Sand (A-2-4)
	<u> . </u>	Sat.	SILT (A-4), with little grave fragments Boring Terminated at Elevate Residual Sandy Siles	tion 2,773.5 ft In				
1001.65U 4/20/22			- - - - - - - - -					- - - - - - - -
HUY CIMICI O			:					- - - - - - - -
A-dunasur			- - - - - -					
HOME DAGGE								- - - - -
								<u>-</u>

REFERENCE

CONTENTS

DESCRIPTION

LEGEND (SOIL & ROCK)

GEOPHYSICAL TEST RESULTS

TITLE SHEET

WALL ENVELOPE

CROSS SECTIONS

SITE PLAN

BORE LOGS

SHEET NO.

5-8

9-10

3

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY _GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION _RETAINING WALL #12: SOIL NAIL WALL WITH ARCHITECTURAL FORM LINER FINISH ON -L- FROM 341+76 LT TO 344 + 11 LT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAL SHEETS
N.C.	A-0009CB	1	11

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (1991) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSUFFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BORCHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE OR INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS, AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:

 1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

 2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

CG2 EXPLORATION **BRECCIA** S. BRAUN N. MCLAREN C. PIERCY

GEL SOLUTIONS

INVESTIGATED BY __CG2

DRAWN BY __M. BREWER, P.E.

CHECKED BY R. KRAL, P.E.

SUBMITTED BY <u>M. Brewer</u>, P.E.

DATE _MAY 2022





D. Matthew Brewer

DATE **DOCUMENT NOT CONSIDERED FINAL**

UNLESS ALL SIGNATURES COMPLETED

6/7/2022

PROJECT REFERENCE NO. SHEET NO.

A-0009CB


2


NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION


SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS


SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT	WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE. UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.	HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM DI586). SOIL CLASSIFICATION IS BASED ON THE AASHTO SYSTEM, BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING:	GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.	SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN	AQUIFER - A WATER BEARING FORMATION OR STRATA.
CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH	ANGULARITY OF GRAINS	REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:	SI//ESI//A	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.
SOIL LEGEND AND AASHTO CLASSIFICATION	ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED VILLY NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > ROCK (WR) 100 BLOWS PER FOOT IF TESTED.	ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT
GENERAL GRANULAR MATERIALS SILT-CLAY MATERIALS ORGANIC MATERIALS	MINERALOGICAL COMPOSITION	CRYSTALLINE CRYSTA	WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND
LLASS. (\$\(\sigma\) 35/. PASSING "200) (> 35/. PASSING "200)	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC. ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	ROCK (CR) WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE, GNEISS, GABBRO, SCHIST, ETC.	SURFACE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5 CLASS. A-1-0 A-1-b A-2-4 A-2-5 A-2-6 A-2-7 A-4 A-5 A-6, A-7 A-6, A-7	COMPRESSIBILITY	NON-CRYSTALLINE - FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
000000000000000000000000000000000000000	SLIGHTLY COMPRESSIBLE LL < 31	ROCK (NCR) SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.
SYMBOL 000000000000000000000000000000000000	MODERATELY COMPRESSIBLE LL = 31 - 50 HIGHLY COMPRESSIBLE LL > 50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD SEDIMENTARY ROCK SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED
7. PASSING SILT- MUCK, GRANULAR SILT- MUCK,	PERCENTAGE OF MATERIAL	(CP) SHELL BEDS, ETC.	BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
*40 30 MX 50 MX 51 MN SOILS CLAY PEAT	GRANIII AR STIT - CLAY	- WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.
200 15 MX 25 MX 10 MX 25 MX 25 MX 25 MX 25 MX 35 MX 36 MX 36 MX 36 MX 36 MX 36 MX	ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 10%	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER HAMMER IF CRYSTALLINE.	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE
MATERIAL PASSING *40	LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20%	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN,	HORIZONTAL.
LL 40 MX 41 MN 40 MX 41 MN 40 MX 41 MN 40 MX 41 MN 50LL5 WITH	MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35% HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE	(V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.
PI 6 MX NP 10 MX 10 MX 11 MN 11 MN 10 MX 11 MN 11 MN 11 MN MODERATE ORGANIC	GROUND WATER	OF A CRYSTALLINE NATURE.	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE
GROUP INDEX W W 4 MX 8 MX 12 MX 16 MX NU MX AMUUNIS UF ORCANIC SOILS		SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO (SLI.) 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR	SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
USUAL 17PES STUNE HAUSS. FINE SILTY OR CLAYEY SILTY CLAYEY MATTER	▼ WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING	CRYSTALS ARE DULL AND DISCOLORED, CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
MATERIALS SAND SAND CRAVEL AND SAND SOILS SOILS	▼ STATIC WATER LEVEL AFTER <u>24</u> HOURS	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM
GEN. RATING EXCELLENT TO GOOD FAIR TO POOR POOR UNSUITABLE	<u> </u>	(MOD.) GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	PARENT MATERIAL.
AS SUBURALLE PUUR	SPRING OR SEEP	WITH FRESH ROCK.	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.
P! OF A-7-5 SUBGROUP IS ≤ LL - 30 ;P! OF A-7-6 SUBGROUP IS > LL - 30 CONSISTENCY OR DENSENESS	MISCELLANEOUS SYMBOLS	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, IN GRANITOID ROCKS, ALL FELDSPARS DULL SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH	FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE FIELD.
PANCE OF STANDARD PANCE OF LINCONFINED		(MOD. SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK, ROCK GIVES "CLUNK" SOUND WHEN STRUCK,	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
PRIMARY SOIL TYPE COMPACTINESS OF PENETRATION RESISTENCE COMPRESSIVE STRENGTH	ROADWAY EMBANKMENT (RE) 25/025 DIP & DIP DIRECTION	<u>IF TESTED, WOULD YIELD SPT REFUSAL</u>	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO
IN-VALUE) (TUNS/FT-)	WITH SOIL DESCRIPTION → OF ROCK STRUCTURES	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC CLEAR AND EVIDENT BUT (SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED	ITS LATERAL EXTENT.
GENERALLY VERY LOOSE < 4 CONTROL LOOSE	SOIL SYMBOL SOIL SYMBOL SLOPE INDICATOR INSTALLATION	TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.
GRANULAR MEDIUM DENSE 10 TO 30 N/A MATERIAL DENSE 30 TO 50	ARTIFICIAL FILL (AF) OTHER AUGER BORING CONE PENETROMETER	IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF	MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
DENSE 30 TO 50	THAN ROADWAY EMBANKMENT	VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK	PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE
VERY SOFT < 2 < 0.25	──── INFERRED SOIL BOUNDARY — CORE BORING SOUNDING ROD	(V SEV.) REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR	OF AN INTERVENING IMPERVIOUS STRATUM.
GENERALLY SOFT 2 TO 4 0.25 TO 0.5 SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0	INFERRED ROCK LINE MN MONITORING WELL TEST BORING	VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BFF</u> COMPLETE ROCK REDUCED TO SOIL, ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
MATERIAL STIFF 8 TO 15 1 TO 2	WITH CORE	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS	ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE
(COHESIVE) VERY STIFF 15 TO 30 2 TO 4 HARD > 30 > 4	→ PIEZOMETER INSTALLATION → SPT N-VALUE	ALSO AN EXAMPLE.	RUN AND EXPRESSED AS A PERCENTAGE.
TEXTURE OR GRAIN SIZE	RECOMMENDATION SYMBOLS	ROCK HARDNESS	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT
		VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES	ROCK.
U.S. STD. SIEVE SIZE 4 10 40 60 200 270 OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	UNDERCUT UNSUITABLE WASTE UNSUITABLE WASTE UNSUITABLE WASTE USED IN THE TOP 3 FEET OF	SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK. HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY, HARD HAMMER BLOWS REQUIRED	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO
BOULDER COBBLE GRAVEL COARSE FINE SILT CLAY	SHALLOW UNDERCUT UNDE	TO DETACH HAND SPECIMEN.	THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
(BLDR.) (COB.) (GR.) (CSE. SD.) (F SD.) (SL.) (CL.)	ABBREVIATIONS	MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT OR SLIP PLANE.
GRAIN MM 305 75 2.0 0.25 0.05 0.005	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST	HARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED BY MODERATE BLOWS.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF
SIZE IN. 12 3	BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED	MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT.	A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL
SOIL MOISTURE - CORRELATION OF TERMS	CL CLAY MOD MODERATELY γ - UNIT WEIGHT CPT - CONE PENETRATION TEST NP - NON PLASTIC γ_d - DRY UNIT WEIGHT	HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE POINT OF A GEOLOGIST'S PICK.	WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
SOIL MOISTURE SCALE FIELD MOISTURE CHIDE FOR FIELD MOISTURE DESCRIPTION	CSE COARSE ORG ORGANIC	SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK, CAN BE EXCAVATED IN FRAGMENTS	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY
(ATTERBERG LIMITS) DESCRIPTION GUIDE FOR FIELD MOISTURE DESCRIPTION	DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST SAMPLE ABBREVIATIONS DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK	FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN	TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY	DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON	PIECES CAN BE BROKEN BY FINGER PRESSURE. VERY CAN BE CARVED WITH KNIFE, CAN BE EXCAVATED READILY WITH POINT OF PICK, PIECES I INCH	STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY
(SAT.) FROM BELOW THE GROUND WATER TABLE	F - FINE SL SILT, SILTY ST - SHELBY TUBE FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK	SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
PLASTIC CEMICOLIDA DECULIDES ORVING TO	FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL	FINGERNAIL.	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
(P) ATTAIN OPTIMUM MOISTURE	FRAGS FRAGMENTS W - MOISTURE CONTENT CBR - CALIFORNIA BEARING	FRACTURE SPACING BEDDING	BENCH MARK: N/A
"" PL L PLASTIC LIMIT	1	TERM SPACING TERM THICKNESS VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET	
OM OPTIMUM MOISTURE - MOIST - (M) SOLID; AT OR NEAR OPTIMUM MOISTURE	EQUIPMENT USED ON SUBJECT PROJECT DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:	■ WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET	ELEVATION: FEET
SL SHRINKAGE LIMIT	CME-45C CLAY BITS X AUTOMATIC MANUAL	MODERATELY CLOSE	NOTES:
- DRY - (D) REQUIRES ADDITIONAL WATER TO	CI CONTINUOUS FLICHT AUGED	VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET	SURVEY AND ROADWAY DESIGN FILES PROVIDED BY TGS ENGINEERS ON 11/15/2021
ATTAIN OPTIMUM MOISTURE	X CME-550	THINLY LAMINATED < 0.008 FEET INDURATION	VIN / 3/2U2
PLASTICITY	.	INDUMH I ION FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	1
PLASTICITY INDEX (PI) DRY STRENGTH NON PLASTIC 0-5 VERY LOW	X CME-550X HARD FACED FINGER BITS -N -N	DIBRING WITH FINGED EDEES NUMEROUS CRAINS.	
SLIGHTLY PLASTIC 6-15 SLIGHT	VANE SHEAR TEST TUNGCARBIDE INSERTS HAND TOOLS:	FRIABLE GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	
MODERATELY PLASTIC 16-25 MEDIUM	CASING W/ ADVANCER POST HOLE DIGGER	MODERATELY INDURATED GRAINS CAN BE SEPARATED FROM SAMPLE WITH STEEL PROBE;	
	PORTABLE HOIST TRICONE STEEL TEETH HAND AUGER	BREAKS EASILY WHEN HIT WITH HAMMER.	
COLOR	X DIEDRICH D50	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; OFFICULT TO BREAK WITH HAMMER.	
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY).	CORE BIT VANE SHEAR TEST		
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	DATE: 8-15-1
		I .	1
















	BORE L						
WBS 32572.1.FS10 TIP	A-0009CB COUNTY GRAHAM	GEOLOGIST S. Braun		WBS 32572.1.FS10	TIP A-0009CB COUN	ITY GRAHAM	GEOLOGIST C. Piercy
SITE DESCRIPTION Upgrade NC 143 fro	om SR 1223 (Beech Creek Road) to 0.5 Mil	iles North of Appalachian Trail	GROUND WTR (ft)	SITE DESCRIPTION Upgrade NO	C 143 from SR 1223 (Beech Creek F	Road) to 0.5 Miles North of Appala	achian Trail GROUND WTR (ft)
BORING NO. RWAL12_B-1 STA	ATION 342+16 OFFSET 2	28 ft LT ALIGNMENT L	0 HR. Dry	BORING NO. RWAL12_B-2	STATION 343+24	OFFSET CL	ALIGNMENT L 0 HR. Dry
COLLAR ELEV. 2,879.9 ft TOT	TAL DEPTH 30.0 ft NORTHING	EASTING 593,757	24 HR . Dry	COLLAR ELEV. 2,872.6 ft	TOTAL DEPTH 23.6 ft	NORTHING 622,043	EASTING 593,788 24 HR. Dry
DRILL RIG/HAMMER EFF/DATE CG20446 Died	drich D50 83%06/16/2020	DRILL METHOD H.S. Augers HAN	MMER TYPE Automatic	DRILL RIG/HAMMER EFF/DATE BRES	E9533 CME-550X 78% 03/12/2021	DRILL METHOD	H.S. Augers HAMMER TYPE Automatic
DRILLER C. Odom STA	ART DATE 05/03/21 COMP. DA	SURFACE WATER DEPTH	N/A	DRILLER J. Phillips	START DATE 04/28/21	COMP. DATE 04/28/21	SURFACE WATER DEPTH N/A
		SAMP. SOIL AND ROCK DE	N/A ESCRIPTION DEPTH (ft) RFACE 0.0 AL to Coarse Sandy, race organics and fragments Brown, Fine to A-4), with trace fragments Fine to Coarse 5(3)), with trace oxide to Coarse Sandy 4) Tan, Silty Fine to	DRILLER J. Phillips ELEV (ft) DRIVE ELEV (ft) DEPTH (ft) 0.5ft 0.5ft 2875 2,871.6 1.0 4 9 2,869.1 3.5 100/0.4 2,866.6 6.0 100/0.3 2865 2,864.1 8.5 100/0.2 2855 2,859.1 13.5 100/0.2 2855 2,854.1 18.5 100/0.2	START DATE 04/28/21 UNT BLOWS PER FOO	OT SAMP. L O NO. MOI G	SURFACE WATER DEPTH N/A SOIL AND ROCK DESCRIPTION 2,872.6 GROUND SURFACE RESIDUAL Medium Dense to Dense, Red-Brown, Silty Fine to Coarse SAND (A-2-4), with little gravel-sized rock fragments WEATHERED ROCK Gray-Brown, (META-SANDSTONE)
2,851.4 28.5	46	M 2,849.9 Boring Terminated at Elev Residual Silty Sar	30.0 vation 2,849.9 ft In nd (A-2-4)	2.849.1 23.5 60/0.1		60/0.1	2.849.1 2.849.0 CRYSTALLINE ROCK Gray-Brown, (META-SANDSTONE) Boring Terminated with Standard Penetration Test Refusal at Elevation 2,849.0 ft in Crystalline Rock (META-SANDSTONE)



PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	11

GEOPHYSICAL TEST RESULTS - SEISMIC REFRACTION LINE 12.1



GEOPHYSICAL TESTING PERFORMED BY GEL SOLUTIONS. REFERENCE "SEISMIC REFRACTION SURVEY FOR EVALUATION OF ROCK" DATED 10/01/2021 CG2 ESTIMATED WAVE SPEED FOR WEATHERED ROCK: 4,500 FT/SEC

CG2 ESTIMATED WAVE SPEED FOR CRYSTALLINE ROCK: 7,500 FT/SEC

REFERENCE

CONTENTS

DESCRIPTION

LEGEND (SOIL & ROCK)

GEOPHYSICAL TEST RESULTS

TITLE SHEET

WALL ENVELOPE

CROSS SECTIONS

SITE PLAN

BORE LOGS

SHEET NO.

5-10

11-12

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY _GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION _RETAINING WALL #13: SOIL NAIL WALL WITH ARCHITECTURAL FORM LINER FINISH ON -L- FROM 344+69 LT TO 346 + 76 LT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAI SHEET
N.C.	A-0009CB	1	13

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (1991) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSUFFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BORCHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE OR INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS, AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:

 1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

 2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

CG2 EXPLORATION **BRECCIA**

S. BRAUN

D. GOODNIGHT C. PIERCY

GEL SOLUTIONS

INVESTIGATED BY __CG2

DRAWN BY __M. BREWER, P.E.

CHECKED BY R. KRAL, P.E.

SUBMITTED BY <u>M. Brewer</u>, P.E.

DATE _MAY 2022





D. Matthew Brewer

DOCUMENT NOT CONSIDERED FINAL

DATE

UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO. SHEET NO.

A-0009CB


2


NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION


SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS


COLL DECEDIBIION	CDADATION	T DOCK DECEDIBIION	TEDMC AND DEFINITIONS		
SOIL DESCRIPTION SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN	GRADATION WELL GRADED - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.	ROCK DESCRIPTION HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED	TERMS AND DEFINITIONS ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.		
BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION	UNIFORMLY GRADED - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE.	ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL. SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60	AQUIFER - A WATER BEARING FORMATION OR STRATA.		
IS BASED ON THE AASHTO SYSTEM, BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING:	GAP-GRADED - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.	BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN	ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.		
CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE,	ANGULARITY OF GRAINS	REPRESENTED BY A ZONE OF WEATHERED ROCK. ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING		
VERY STIFF,GRAY,SILTY CLAY,MOIST WITH INTERBEDDED FINE SAND LAYERS,HIGHLY PLASTIC,A-7-6	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS: ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES >	A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC.		
SOIL LEGEND AND AASHTO CLASSIFICATION	MINERALOGICAL COMPOSITION	ROCK (WR) 100 BLOWS PER FOOT IF TESTED.	ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT		
GENERAL GRANULAR MATERIALS SILT-CLAY MATERIALS CLASS. (≤35% PASSING *200) (>35% PASSING *200) ORGANIC MATERIALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC.	CRYSTALLINE CRYSTALLINE WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE,	WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND SURFACE.		
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5	ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	GNEISS, GABBRO, SCHIST, ETC.	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.		
CLASS. A-1-0 A-1-6 A-2-4 A-2-5 A-2-6 A-2-7 A-7-5 A-3 A-6, A-7	COMPRESSIBILITY	NON-CRYSTALLINE ROCK (NCR) FINE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN SEDIMENTARY ROCK THAT WOULD YELLD SPT REFUSAL IF TESTED.	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM		
SYMBOL 000000000000000000000000000000000000	SLIGHTLY COMPRESSIBLE LL < 31 MODERATELY COMPRESSIBLE LL = 31 - 50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD	OF SLOPE.		
% PASSING	HIGHLY COMPRESSIBLE LL > 50	SEDIMENTARY ROCK SPIT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.		
*10 50 MX GRANULAR GRANULAR GRANULAR CLAY PEAT COLOR CLAY PEAT COLOR COLOR	PERCENTAGE OF MATERIAL	WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT		
■200 15 MX 25 MX 10 MX 35 MX 35 MX 35 MX 35 MX 36 MN 36 MN 36 MN 36 MN 36 MN 36 MN	GRANULAR SILT - CLAY ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER	ROCKS OR CUTS MASSIVE ROCK.		
MATERIAL CONTROL OF THE CONTROL OF T	TRACE OF ORGANIC MATTER 2 - 3%, 3 - 5%, TRACE 1 - 10%, LITTLE ORGANIC MATTER 3 - 5%, 5 - 12%, LITTLE 10 - 20%	HAMMER IF CRYSTALLINE.	<u>DIP</u> - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE HORIZONTAL.		
PASSING *40 48 MX 41 MN LITTLE OR	MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35%	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, (V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE		
PI 6 MX NP 10 MX 10 MX 11 MN 11 MN 10 MX 10 MX 11 MN 11 MN 11 MN MODERATE ORGANIC	HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE	OF A CRYSTALLINE NATURE.	LINE OF DIP, MEASURED CLOCKWISE FROM NORTH.		
GROUP INJEX U U U 4 MX 8 MX 12 MX 16 MX NU MX AMUUNTS UF SOILS	GROUND WATER	SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR	FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.		
OF MA IOR GRAVEL AND FINE SILTY OR CLAYEY SILTY CLAYEY MATTER	WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING	CRYSTALS ARE DULL AND DISCOLORED, CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.		
MATERIALS SAND SAND GRAVEL AND SAND SOILS SOILS	STATIC WATER LEVEL AFTER 24 HOURS	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY. ROCK HAS	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM		
GEN. RATING AS SUBGRADE EXCELLENT TO GOOD FAIR TO POOR POOR UNSUITABLE		DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	PARENT MATERIAL. FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM.		
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30	SPRING OR SEEP	WITH FRESH ROCK.	FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE		
CONSISTENCY OR DENSENESS	MISCELLANEOUS SYMBOLS	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH	FIELD.		
RANGE OF STANDARD RANGE OF UNCONFINED	T ROADWAY EMBANKMENT (RE) 25/025 DIP & DIP DIRECTION	(MOD. SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK, ROCK GIVES "CLUNK" SOUND WHEN STRUCK, IF TESTED, WOULD YIELD SPT REFUSAL	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.		
PRIMARY SOIL TYPE CONTINUESS OF PENETRATION RESISTENCE COMPRESSIVE STRENGTH (N-VALUE) (TONS/FT ²)	ROADWAY EMBANKMENT (RE) ROADWAY EMBANKMENT (RE) DIP & DIP DIRECTION OF ROCK STRUCTURES	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO ITS LATERAL EXTENT.		
GENERALLY VERY LOOSE < 4	SOIL SYMBOL SPT ONT TEST BORING SLOPE INDICATOR INSTALLATION	(SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS.		
GRANULAR LUUSE 4 10 10	M	IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF	MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS. MOTTLING IN SOILS		
MATERIAL DENSE 30 TO 50 (NON-COHESIVE) VERY DENSE > 50	ARTIFICIAL FILL (AF) OTHER AUGER BORING CONE PENETROMETER THAN ROADWAY EMBANKMENT AUGER BORING CONE PENETROMETER	VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC ELEMENTS ARE DISCERNIBLE	USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE. PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE		
VERY 50FT < 2 < 0.25	INFERRED SOIL BOUNDARY CORE BORING SOUNDING ROD	SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK (V SEV.) REMAINING. SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR	OF AN INTERVENING IMPERVIOUS STRATUM.		
GENERALLY SOFT 2 TO 4 0.25 TO 0.5	TEST BORING	VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</u>	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.		
SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0 MATERIAL STIFF 8 TO 15 1 TO 2	INFERRED ROCK LINE MONITORING WELL WITH CORE	COMPLETE ROCK REDUCED TO SOIL. ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND SCATTERED CONCENTRATIONS. QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS. SAPROLITE IS	ROCK QUALITY DESIGNATION (RQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE		
(COHESIVE) VERY STIFF 15 TO 30 2 TO 4 HARD > 30 > 4	TTT ALLUVIAL SOIL BOUNDARY A PIEZOMETER INSTALLATION - SPT N-VALUE	ALSO AN EXAMPLE.	RUN AND EXPRESSED AS A PERCENTAGE.		
TEXTURE OR GRAIN SIZE	RECOMMENDATION SYMBOLS	- ROCK HARDNESS	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.		
U.S. STD. SIEVE SIZE 4 10 40 60 200 270	UNCLASSIFIED EXCAVATION - UNCLASSIFIED EXCAV	VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK. BREAKING OF HAND SPECIMENS REQUIRES SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND		
OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	1000 IV TUE TOD O SEET OF	HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED	RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.		
BOULDER COBBLE GRAVEL SAND SAND SILT CLAY	SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - UNCLASSIFIED EXCAVATION - EMBANKMENT OR BACKFILL	TO DETACH HAND SPECIMEN.	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT		
(BLDR.) (COB.) (GR.) (CSE. SD.) (F SD.) (SL.) (CL.)	ABBREVIATIONS	MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK, GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED	OR SLIP PLANE.		
GRAIN MM 305 75 2.0 0.25 0.05 0.005	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED	BY MODERATE BLOWS.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF A 140 LB, HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL		
SIZE IN. 12 3	CL CLAY MOD MODERATELY 7 - UNIT WEIGHT	MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL		
SOIL MOISTURE - CORRELATION OF TERMS SOIL MOISTURE SCALE FIELD MOISTURE COURS FOR PETER MOISTURE SCALES OF THE PROPERTY OF TH	CPT - CONE PENETRATION TEST NP - NON PLASTIC γ_d - DRY UNIT WEIGHT CSE COARSE ORG ORGANIC	POINT OF A GEOLOGIST'S PICK.	TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.		
(ATTERBERG LIMITS) OESCRIPTION GUIDE FOR FIELD MOISTURE DESCRIPTION	DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST <u>SAMPLE ABBREVIATIONS</u>	SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK. CAN BE EXCAVATED IN FRAGMENTS FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.		
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY	DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON	PIECES CAN BE BROKEN BY FINGER PRESSURE.	STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY		
(SAT.) FROM BELOW THE GROUND WATER TABLE	F - FINE SL SILT, SILTY ST - SHELBY TUBE	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY	THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.		
PLASTIC CEMICOLID. DECILIDES DRVING TO	FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL	FINGERNAIL.	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.		
(PI) ATTAIN OPTIMUM MOISTURE	FRAGS FRAGMENTS	FRACTURE SPACING BEDDING	BENCH MARK: N/A		
	EQUIPMENT USED ON SUBJECT PROJECT	TERM SPACING TERM THICKNESS VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET	ELEVATION: FEET		
OM _ OPTIMUM MOISTURE - MOIST - (M) SOLID; AT OR NEAR OPTIMUM MOISTURE	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:	WIDE 3 TO 10 FEET THICKLY BEDDED 1.5 - 4 FEET MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET			
SL SHRINKAGE LIMIT	CME-45C CLAY BITS X AUTOMATIC MANUAL	CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET	NOTES:		
- DRY - (D) REQUIRES ADDITIONAL WATER TO ATTAIN OPTIMUM MOISTURE	6. CONTINUOUS FLIGHT AUGER CORE SIZE:	VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET THINLY LAMINATED < 0.008 FEET	SURVEY AND ROADWAY DESIGN FILES PROVIDED BY TGS ENGINEERS ON 11/15/2021		
PLASTICITY	CME-550 X 8' HOLLOW AUGERS CORE SIZE:	INDURATION			
PLASTICITY INDEX (PI) DRY STRENGTH	X CME-550X HARD FACED FINGER BITS N-N	FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.			
NON PLASTIC 0-5 VERY LOW	TUNGCARBIDE INSERTS	RUBBING WITH FINGER FREES NUMEROUS GRAINS; FRIABLE GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.			
SLIGHTLY PLASTIC 6-15 SLIGHT MODERATELY PLASTIC 16-25 MEDIUM	VANE SHEAR TEST CASING W/ ADVANCER HAND TOOLS: POST HOLE DIGGER	CRAING CAN BE CEDARATED FROM CAMPLE WITH CIFFL PROPE			
HIGHLY PLASTIC 26 OR MORE HIGH	PORTABLE HOIST TRICONE STEEL TEETH HAND AUGER	MODERATELY INDURATED ORALINS CHIN DE SCHAMHED FROM SHIFTE WITH STEEL FROBE; BREAKS EASILY WHEN HIT WITH HAMMER.			
COLOR	X DIEDRICH D50 TRICONE TUNGCARB. SOUNDING ROD	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE; DIFFICULT TO BREAK WITH HAMMER.			
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY).	CORE BIT VANE SHEAR TEST	CHARP HAMMER BLOWS REQUIRED TO RREAK SAMPLE.			
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		EXTREMELY INDURATED SHARP HAMMER BLOWS REDUITED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	DATE: 8-15-1		
		•			
























										D	ORE I	L	JG			
WBS	325	72.1.F	FS10)			TIP	A-0009CE	3	COUNT	Y GRAHA	М				GEOLOGIST D. Goodnight
SITE	DES	CRIPT	ION	Upgı	ade N	IC 14	3 fr	rom SR 1223	3 (Beech 0	Creek Ro	ad) to 0.5 N	/lile	s North	of Ap	palach	nian Trail GROUND WTR (ft
BOR	ING N	0 . R	RWAL	_13_B	-3		ST	STATION 346+28 OFFSET 9 ft RT ALIGNMENT L 0 F				ALIGNMENT L 0 HR. Dry				
COL	LAR E	LEV.	2,8	393.9	ft		то	TAL DEPTH	23.9 ft		NORTHIN	G	621,74	18		EASTING 593,792 24 HR. Dry
						E9553	3 CI \	/IE-550X 80%	03/12/2021				DRILL M	ETHO	H.S.	. Augers HAMMER TYPE Automatic
DRIL	LER	J. Ph	illips				ST	ART DATE	08/11/21		COMP. D	AT	E 08/1	1/21		SURFACE WATER DEPTH N/A
ELEV (ft)	DD1	E DE	PTH	BLC	0.5ft	TNUC			BLOWS P	ER FOOT			SAMP. NO.	MOI	L O G	SOIL AND ROCK DESCRIPTION ELEV. (ft) DEPTH (
2 895 2890	2,892	0.4 3		4	13	12		· · · · · •	25 · · · 1- · · ·					M M	L::F	Case SAND (A-2-4), with trace gravel RESIDUAL Very Stiff to Hard, Tan-Gray, Fine to
2885	2,885	5.4 8	3.5 3.5	10	10	11			30			_		M M		Coarse Sandy SILT (A-4), with trace gravel-sized rock fragments
		1.4 1; 		7	14	15	5		29					М		-
	2,870	14 2	3.5	14	12	23			<u>-35</u>		100/0.			M		2,873.4 WEATHERED ROCK Tan, (META-SANDSTONE) 2,870.0 Boring Terminated at Elevation 2,870.0 ft In Weathered Rock (META-SANDSTONE) Note -Hard Drilling encountered at 20.5 ft

SHEET 12

PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	13

GEOPHYSICAL TEST RESULTS - SEISMIC REFRACTION LINE 13.1



GEOPHYSICAL TESTING PERFORMED BY GEL SOLUTIONS. REFERENCE "SEISMIC REFRACTION SURVEY FOR EVALUATION OF ROCK" DATED 10/01/2021 CG2 ESTIMATED WAVE SPEED FOR WEATHERED ROCK: 4,500 FT/SEC

CG2 ESTIMATED WAVE SPEED FOR CRYSTALLINE ROCK: 7,500 FT/SEC

REFERENCE

CONTENTS

DESCRIPTION

LEGEND (SOIL & ROCK)

GEOPHYSICAL TEST RESULTS

TITLE SHEET

WALL ENVELOPE

CROSS SECTIONS

SITE PLAN

BORE LOGS

SHEET NO.

5-10

11-12

STATE OF NORTH CAROLINA

DEPARTMENT OF TRANSPORTATION **DIVISION OF HIGHWAYS** GEOTECHNICAL ENGINEERING UNIT

STRUCTURE SUBSURFACE INVESTIGATION

COUNTY _GRAHAM

PROJECT DESCRIPTION UPGRADE NC 143 FROM SR 1223 (BEECH CREEK ROAD) TO 0.5 MILES NORTH OF APPALACHIAN TRAIL

SITE DESCRIPTION RETAINING WALL #14: SOIL NAIL WALL WITH ARCHITECTURAL FORM LINER FINISH ON -L- FROM 347+95 LT TO 350 + 64 LT

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.	TOTAI SHEET
N.C.	A-0009CB	1	13

CAUTION NOTICE

THE SUBSURFACE INFORMATION AND THE SUBSURFACE INVESTIGATION ON WHICH IT IS BASED WERE MADE FOR THE PURPOSE OF STUDY, PLANNING AND DESIGN, AND NOT FOR CONSTRUCTION OR PAY PURPOSES. THE VARIOUS FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA AVAILABLE MAY BE REVIEWED OR INSPECTED IN RALEIGH BY CONTACTING THE N. C. DEPARTMENT OF TRANSPORTATION, GEOTECHNICAL ENGINEERING UNIT AT (1991) 707-6850. THE SUBSURFACE PLANS AND REPORTS, FIELD BORING LOGS, ROCK CORES AND SOIL TEST DATA ARE NOT PART OF THE CONTRACT.

GENERAL SOIL AND ROCK STRATA DESCRIPTIONS AND INDICATED BOUNDARIES ARE BASED ON A GEOTECHNICAL INTERPRETATION OF ALL AVAILABLE SUBSUFFACE DATA AND MAY NOT NECESSARILY REFLECT THE ACTUAL SUBSURFACE CONDITIONS BETWEEN BORINGS OR BETWEEN SAMPLED STRATA WITHIN THE BORCHOLE. THE LABORATORY SAMPLE DATA AND THE IN SITU (IN-PLACE) TEST DATA CAN BE RELIED ON ONLY TO THE DEGREE OF RELIABILITY INHERENT IN THE STANDARD TEST METHOL. THE OBSERVED WATER LEVELS OR SOIL MOISTURE CONDITIONS INDICATED IN THE SUBSURFACE OR INVESTIGATIONS ARE AS RECORDED AT THE TIME OF THE INVESTIGATION. THESE WATER LEVELS OR SOIL MOISTURE CONDITIONS MAY VARY CONSIDERABLY WITH TIME ACCORDING TO CLIMATIC CONDITIONS INCLUDING TEMPERATURES, PRECIPITATION AND WIND, AS WELL AS OTHER NON-CLIMATIC FACTORS.

THE BIDDER OR CONTRACTOR IS CAUTIONED THAT DETAILS SHOWN ON THE SUBSURFACE PLANS ARE PRELIMINARY ONLY AND IN MANY CASES THE FINAL DESIGN DETAILS ARE DIFFERENT. FOR BIDDING AND CONSTRUCTION PURPOSES, REFER TO THE CONSTRUCTION PLANS AND DOCUMENTS FOR FINAL DESIGN INFORMATION ON THIS PROJECT. THE DEPARTMENT DOES NOT WARRANT OR GUARANTEE THE SUFFICIENCY OR ACCURACY OF THE INVESTIGATION MADE, NOR THE INTERRETATIONS MADE, OR OPINION OF THE DEPARTMENT AS TO THE TYPE OF MATERIALS, AND CONDITIONS TO BE ENCOUNTERED. THE BIDDER OR CONTRACTOR IS CAUTIONED TO MAKE SUCH INDEPENDENT SUBSURFACE INVESTIGATIONS AS HE DEEMS NECESSARY TO SATISFY HIMSELF AS TO CONDITIONS TO BE ENCOUNTERED ON THE PROJECT. THE CONTRACTOR SHALL HAVE NO CLAIM FOR ADDITIONAL COMPENSATION OR FOR AN EXTENSION OF TIME FOR ANY REASON RESULTING FROM THE ACTUAL CONDITIONS ENCOUNTERED AT THE SITE DIFFERING FROM THOSE INDICATED IN THE SUBSURFACE INFORMATION.

- NOTES:

 1. THE INFORMATION CONTAINED HEREIN IS NOT IMPLIED OR GUARANTEED BY THE N. C. DEPARTMENT OF TRANSPORTATION AS ACCURATE NOR IS IT CONSIDERED PART OF THE PLANS, SPECIFICATIONS OR CONTRACT FOR THE PROJECT.

 2. BY HAVING REQUESTED THIS INFORMATION, THE CONTRACTOR SPECIFICALLY WAIVES ANY CLAIMS FOR INCREASED COMPENSATION OR EXTENSION OF TIME BASED ON DIFFERENCES BETWEEN THE CONDITIONS INDICATED HEREIN AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

CG2 EXPLORATION **BRECCIA** N. MCLAREN D. GOODNIGHT **GEL SOLUTIONS**

INVESTIGATED BY __CG2

DRAWN BY __M. BREWER, P.E.

CHECKED BY R. KRAL, P.E.

SUBMITTED BY <u>M. Brewer</u>, P.E.

DATE _MAY 2022



D. Matthew Brewer

6/7/2022 DATE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

PROJECT REFERENCE NO. SHEET NO.

A-0009CB


2


NORTH CAROLINA DEPARTMENT OF TRANSPORTATION DIVISION OF HIGHWAYS GEOTECHNICAL ENGINEERING UNIT


SUBSURFACE INVESTIGATION


SOIL AND ROCK LEGEND, TERMS, SYMBOLS, AND ABBREVIATIONS


SOIL DESCRIPTION	GRADATION	ROCK DESCRIPTION	TERMS AND DEFINITIONS
SOIL IS CONSIDERED UNCONSOLIDATED, SEMI-CONSOLIDATED, OR WEATHERED EARTH MATERIALS THAT CAN BE PENETRATED WITH A CONTINUOUS FLIGHT POWER AUGER AND YIELD LESS THAN 100 BLOWS PER FOOT	<u>WELL GRADED</u> - INDICATES A GOOD REPRESENTATION OF PARTICLE SIZES FROM FINE TO COARSE.	HARD ROCK IS NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT REFUSAL IF TESTED. AN INFERRED ROCK LINE INDICATES THE LEVEL AT WHICH NON-COASTAL PLAIN MATERIAL WOULD YIELD SPT REFUSAL.	ALLUVIUM (ALLUV.) - SOILS THAT HAVE BEEN TRANSPORTED BY WATER.
ACCORDING TO THE STANDARD PENETRATION TEST (AASHTO T 206, ASTM D1586). SOIL CLASSIFICATION	<u>UNIFORMLY GRADED</u> - INDICATES THAT SOIL PARTICLES ARE ALL APPROXIMATELY THE SAME SIZE. <u>GAP-GRADED</u> - INDICATES A MIXTURE OF UNIFORM PARTICLE SIZES OF TWO OR MORE SIZES.	SPT REFUSAL IS PENETRATION BY A SPLIT SPOON SAMPLER EQUAL TO OR LESS THAN 0.1 FOOT PER 60	AQUIFER - A WATER BEARING FORMATION OR STRATA.
IS BASED ON THE AASHTO SYSTEM. BASIC DESCRIPTIONS GENERALLY INCLUDE THE FOLLOWING: CONSISTENCY, COLOR, TEXTURE, MOISTURE, AASHTO CLASSIFICATION, AND OTHER PERTINENT FACTORS SUCH	ANGULARITY OF GRAINS	BLOWS IN NON-COASTAL PLAIN MATERIAL, THE TRANSITION BETWEEN SOIL AND ROCK IS OFTEN REPRESENTED BY A ZONE OF WEATHERED ROCK.	ARENACEOUS - APPLIED TO ROCKS THAT HAVE BEEN DERIVED FROM SAND OR THAT CONTAIN SAND.
AS MINERALOGICAL COMPOSITION, ANGULARITY, STRUCTURE, PLASTICITY, ETC. FOR EXAMPLE, VERY STIFF, GRAY, SILTY CLAY, MOIST WITH INTERBEDDED FINE SAND LAYERS, HIGHLY PLASTIC, A-7-6	THE ANGULARITY OR ROUNDNESS OF SOIL GRAINS IS DESIGNATED BY THE TERMS:	ROCK MATERIALS ARE TYPICALLY DIVIDED AS FOLLOWS:	ARGILLACEOUS - APPLIED TO ALL ROCKS OR SUBSTANCES COMPOSED OF CLAY MINERALS, OR HAVING
SOIL LEGEND AND AASHTO CLASSIFICATION	ANGULAR, SUBANGULAR, SUBROUNDED, OR ROUNDED.	WEATHERED NON-COASTAL PLAIN MATERIAL THAT WOULD YIELD SPT N VALUES > ROCK (WR) 100 BLOWS PER FOOT IF TESTED.	A NOTABLE PROPORTION OF CLAY IN THEIR COMPOSITION, SUCH AS SHALE, SLATE, ETC. ARTESIAN - GROUND WATER THAT IS UNDER SUFFICIENT PRESSURE TO RISE ABOVE THE LEVEL AT
CENERAL CRANIII AR MATERIALS SILT-CLAY MATERIALS	MINERALOGICAL COMPOSITION	FINE TO COARSE CRAIN IGNEOUS AND METAMORPHIC ROCK THAT	WHICH IT IS ENCOUNTERED, BUT WHICH DOES NOT NECESSARILY RISE TO OR ABOVE THE GROUND
CLASS. (≤ 35% PASSING *200) (> 35% PASSING *200) ORGANIC MATERIALS	MINERAL NAMES SUCH AS QUARTZ, FELDSPAR, MICA, TALC, KAOLIN, ETC.	WOULD YIELD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES GRANITE,	SURFACE.
GROUP A-1 A-3 A-2 A-4 A-5 A-6 A-7 A-1, A-2 A-4, A-5	ARE USED IN DESCRIPTIONS WHEN THEY ARE CONSIDERED OF SIGNIFICANCE.	NON-CRYSTALLINE NON-CRYSTALLINE FIRE TO COARSE GRAIN METAMORPHIC AND NON-COASTAL PLAIN	CALCAREOUS (CALC.) - SOILS THAT CONTAIN APPRECIABLE AMOUNTS OF CALCIUM CARBONATE.
CLASS. A-1-a A-1-b A-2-4 A-2-5 A-2-6 A-2-7 A-7-6 A-3 A-6, A-7	COMPRESSIBILITY SLIGHTLY COMPRESSIBLE LL < 31	ROCK (NCR) SEDIMENTARY ROCK THAT WOULD YEILD SPT REFUSAL IF TESTED. ROCK TYPE INCLUDES PHYLLITE, SLATE, SANDSTONE, ETC.	COLLUVIUM - ROCK FRAGMENTS MIXED WITH SOIL DEPOSITED BY GRAVITY ON SLOPE OR AT BOTTOM OF SLOPE.
SYMBOL 0000 d00000 coood	MODERATELY COMPRESSIBLE LL = 31 - 50	COASTAL PLAIN COASTAL PLAIN SEDIMENTS CEMENTED INTO ROCK, BUT MAY NOT YIELD	CORE RECOVERY (REC.) - TOTAL LENGTH OF ALL MATERIAL RECOVERED IN THE CORE BARREL DIVIDED
7. PASSING SILT-	HIGHLY COMPRESSIBLE LL > 50 PERCENTAGE OF MATERIAL	SEDIMENTARY ROCK SPT REFUSAL. ROCK TYPE INCLUDES LIMESTONE, SANDSTONE, CEMENTED SHELL BEDS, ETC.	BY TOTAL LENGTH OF CORE RUN AND EXPRESSED AS A PERCENTAGE.
*10 59 MX GRANULAR CLAY PEAT MUCK, SOILS	GRANULAR SILT - CLAY	WEATHERING	DIKE - A TABULAR BODY OF IGNEOUS ROCK THAT CUTS ACROSS THE STRUCTURE OF ADJACENT ROCKS OR CUTS MASSIVE ROCK.
"200 I I XM C2 XM UI XM C2 XM C2 XM C2 XM UI XM C3 XM	ORGANIC MATERIAL SOILS SOILS OTHER MATERIAL	FRESH ROCK FRESH, CRYSTALS BRIGHT, FEW JOINTS MAY SHOW SLIGHT STAINING, ROCK RINGS UNDER	DIP - THE ANGLE AT WHICH A STRATUM OR ANY PLANAR FEATURE IS INCLINED FROM THE
MATERIAL PASSING *40	TRACE OF ORGANIC MATTER 2 - 3% 3 - 5% TRACE 1 - 10% LITTLE ORGANIC MATTER 3 - 5% 5 - 12% LITTLE 10 - 20%	HAMMER IF CRYSTALLINE. VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN.	HORIZONTAL.
LL 40 MX 41 MN 40 MX 41 MN 40 MX 41 MN 40 MX 41 MN SUILS WITH	MODERATELY ORGANIC 5 - 10% 12 - 20% SOME 20 - 35% HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE	VERY SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED, SOME JOINTS MAY SHOW THIN CLAY COATINGS IF OPEN, (V SLI.) CRYSTALS ON A BROKEN SPECIMEN FACE SHINE BRIGHTLY. ROCK RINGS UNDER HAMMER BLOWS IF	DIP DIRECTION (DIP AZIMUTH) - THE DIRECTION OR BEARING OF THE HORIZONTAL TRACE OF THE
PI 6 MX NP IW MX IW MX II MN II MN IW MX II MN II MN II MN MODERATE ORGANIC	HIGHLY ORGANIC > 10% > 20% HIGHLY 35% AND ABOVE GROUND WATER	OF A CRYSTALLINE NATURE.	LINE OF DIP, MEASURED CLOCKWISE FROM NORTH, FAULT - A FRACTURE OR FRACTURE ZONE ALONG WHICH THERE HAS BEEN DISPLACEMENT OF THE
GROUP INDEX W W 4 MX 8 MX 12 MX 16 MX NU MX AMUNTS OF SOILS		SLIGHT ROCK GENERALLY FRESH, JOINTS STAINED AND DISCOLORATION EXTENDS INTO ROCK UP TO (SLI.) 1 INCH. OPEN JOINTS MAY CONTAIN CLAY. IN GRANITOID ROCKS SOME OCCASIONAL FELDSPAR	SIDES RELATIVE TO ONE ANOTHER PARALLEL TO THE FRACTURE.
USUAL TITES STUNE FRAUS. FINE SILTY OR CLAYEY SILTY CLAYEY MATTER	WATER LEVEL IN BORE HOLE IMMEDIATELY AFTER DRILLING	CRYSTALS ARE DULL AND DISCOLORED, CRYSTALLINE ROCKS RING UNDER HAMMER BLOWS.	FISSILE - A PROPERTY OF SPLITTING ALONG CLOSELY SPACED PARALLEL PLANES.
MATERIALS SAND SAND GRAVEL AND SAND SOILS SOILS	▼ STATIC WATER LEVEL AFTER <u>24</u> HOURS	MODERATE SIGNIFICANT PORTIONS OF ROCK SHOW DISCOLORATION AND WEATHERING EFFECTS. IN	FLOAT - ROCK FRAGMENTS ON SURFACE NEAR THEIR ORIGINAL POSITION AND DISLODGED FROM
GEN. RATING EXCELLENT TO GOOD FAIR TO POOR POOR POOR UNSUITABLE	<u>∨PW</u> PERCHED WATER, SATURATED ZONE, OR WATER BEARING STRATA	(MOD.) GRANITOID ROCKS, MOST FELDSPARS ARE DULL AND DISCOLORED, SOME SHOW CLAY, ROCK HAS DULL SOUND UNDER HAMMER BLOWS AND SHOWS SIGNIFICANT LOSS OF STRENGTH AS COMPARED	PARENT MATERIAL.
HS SUBURHUE FUUR	SPRING OR SEEP	WITH FRESH ROCK.	FLOOD PLAIN (FP) - LAND BORDERING A STREAM, BUILT OF SEDIMENTS DEPOSITED BY THE STREAM. FORMATION (FM.) - A MAPPABLE GEOLOGIC UNIT THAT CAN BE RECOGNIZED AND TRACED IN THE
PI OF A-7-5 SUBGROUP IS ≤ LL - 30 ; PI OF A-7-6 SUBGROUP IS > LL - 30 CONSISTENCY OR DENSENESS	MISCELLANEOUS SYMBOLS	MODERATELY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. IN GRANITOID ROCKS, ALL FELDSPARS DULL SEVERE AND DISCOLORED AND A MAJORITY SHOW KAOLINIZATION. ROCK SHOWS SEVERE LOSS OF STRENGTH	FIELD.
DANCE OF CTANDARD DANCE OF UNICONSTITUT	TI SOCCEPHICOUS STILLOUS	(MOD.SEV.) AND CAN BE EXCAVATED WITH A GEOLOGIST'S PICK. ROCK GIVES "CLUNK" SOUND WHEN STRUCK.	JOINT - FRACTURE IN ROCK ALONG WHICH NO APPRECIABLE MOVEMENT HAS OCCURRED.
PRIMARY SOIL TYPE COMPACTNESS OR CONSISTENCY PENETRATION RESISTENCE COMPRESSIVE STRENGTH (IN-VALUE) (TONS/FT ²)	ROADWAY EMBANKMENT (RE) 25/025 DIP & DIP DIRECTION WITH SOIL DESCRIPTION OF ROCK STRUCTURES	IF TESTED, WOULD YIELD SPT REFUSAL	LEDGE - A SHELF-LIKE RIDGE OR PROJECTION OF ROCK WHOSE THICKNESS IS SMALL COMPARED TO
VERY LOOSE < 4	T SPT C SLOPE INDICATOR	SEVERE ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED, ROCK FABRIC CLEAR AND EVIDENT BUT (SEV.) REDUCED IN STRENGTH TO STRONG SOIL. IN GRANITOID ROCKS ALL FELDSPARS ARE KAOLINIZED	ITS LATERAL EXTENT.
GENERALLY LOOSE 4 TO 10	SOIL SYMBOL OPT DAT TEST BORING INSTALLATION	TO SOME EXTENT. SOME FRAGMENTS OF STRONG ROCK USUALLY REMAIN.	LENS - A BODY OF SOIL OR ROCK THAT THINS OUT IN ONE OR MORE DIRECTIONS. MOTTLED (MOT.) - IRREGULARLY MARKED WITH SPOTS OF DIFFERENT COLORS, MOTTLING IN SOILS
MATERIAL MEDIUM DENSE 10 10 30 N/A	ARTIFICIAL FILL (AF) OTHER AUGER BORING CONE PENETROMETER THAN ROADWAY EMBANKMENT TEST	IF TESTED, WOULD YIELD SPT N VALUES > 100 BPF VERY ALL ROCK EXCEPT QUARTZ DISCOLORED OR STAINED. ROCK FABRIC ELEMENTS ARE DISCERNIBLE	USUALLY INDICATES POOR AERATION AND LACK OF GOOD DRAINAGE.
(NON-COHESIVE) VERY DENSE > 50	T IUMIA VOHDAMI EMBHAKAMENI T	SEVERE BUT MASS IS EFFECTIVELY REDUCED TO SOIL STATUS, WITH ONLY FRAGMENTS OF STRONG ROCK	PERCHED WATER - WATER MAINTAINED ABOVE THE NORMAL GROUND WATER LEVEL BY THE PRESENCE
VERY SOFT < 2 < 0.25	— INFERRED SOIL BOUNDARY ← CORE BORING • SOUNDING ROD	(V SEV.) REMAINING, SAPROLITE IS AN EXAMPLE OF ROCK WEATHERED TO A DEGREE THAT ONLY MINOR VESTIGES OF ORIGINAL ROCK FABRIC REMAIN. <u>IF TESTED, WOULD YIELD SPT N VALUES < 100 BPF</u>	OF AN INTERVENING IMPERVIOUS STRATUM.
GENERALLY SOFT 2 TO 4 0.25 TO 0.5 SILT-CLAY MEDIUM STIFF 4 TO 8 0.5 TO 1.0	INFERRED ROCK LINE MONITORING WELL TEST BORING WITH CORE	COMPLETE ROCK REDUCED TO SOIL, ROCK FABRIC NOT DISCERNIBLE, OR DISCERNIBLE ONLY IN SMALL AND	RESIDUAL (RES.) SOIL - SOIL FORMED IN PLACE BY THE WEATHERING OF ROCK.
MATERIAL STIFF 8 TO 15 1 TO 2 COHESIVE) VERY STIFF 15 TO 30 2 TO 4	A RIEZOMETER	SCATTERED CONCENTRATIONS, QUARTZ MAY BE PRESENT AS DIKES OR STRINGERS, SAPROLITE IS	ROCK QUALITY DESIGNATION (ROD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL LENGTH OF ROCK SEGMENTS EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF CORE
HARD > 30 > 4	TTTT ALLUVIAL SOIL BOUNDARY ALLUVIAL SOIL BOUNDARY INSTALLATION SPT N-VALUE	ALSO AN EXAMPLE.	RUN AND EXPRESSED AS A PERCENTAGE.
TEXTURE OR GRAIN SIZE	RECOMMENDATION SYMBOLS	ROCK HARDNESS VERY HARD CANNOT BE SCRATCHED BY KNIFE OR SHARP PICK, BREAKING OF HAND SPECIMENS REQUIRES	SAPROLITE (SAP.) - RESIDUAL SOIL THAT RETAINS THE RELIC STRUCTURE OR FABRIC OF THE PARENT ROCK.
U.S. STD. SIEVE SIZE 4 10 40 60 200 270	UNDERCUT UNCLASSIFIED EXCAVATION - UNCLASSIF	SEVERAL HARD BLOWS OF THE GEOLOGIST'S PICK.	SILL - AN INTRUSIVE BODY OF IGNEOUS ROCK OF APPROXIMATELY UNIFORM THICKNESS AND
OPENING (MM) 4.76 2.00 0.42 0.25 0.075 0.053	HIGED IN THE TOP 2 FEET OF	HARD CAN BE SCRATCHED BY KNIFE OR PICK ONLY WITH DIFFICULTY. HARD HAMMER BLOWS REQUIRED	RELATIVELY THIN COMPARED WITH ITS LATERAL EXTENT, THAT HAS BEEN EMPLACED PARALLEL TO THE BEDDING OR SCHISTOSITY OF THE INTRUDED ROCKS.
BOULDER COBBLE GRAVEL COARSE FINE SILT CLAY	SHALLOW UNDERCUT UNCLASSIFIED EXCAVATION - ACCEPTABLE DEGRADABLE ROCK EMBANKMENT OR BACKFILL	TO DETACH HAND SPECIMEN.	SLICKENSIDE - POLISHED AND STRIATED SURFACE THAT RESULTS FROM FRICTION ALONG A FAULT
(BLDR,) (COB,) (GR,) (CSE, SD,) (F SD,) (SL,) (CL,)	ABBREVIATIONS	MODERATELY CAN BE SCRATCHED BY KNIFE OR PICK. GOUGES OR GROOVES TO 0.25 INCHES DEEP CAN BE HARD EXCAVATED BY HARD BLOW OF A GEOLOGIST'S PICK, HAND SPECIMENS CAN BE DETACHED	OR SLIP PLANE.
GRAIN MM 305 75 2.0 0.25 0.05 0.005	AR - AUGER REFUSAL MED MEDIUM VST - VANE SHEAR TEST	BY MODERATE BLOWS.	STANDARD PENETRATION TEST (PENETRATION RESISTANCE) (SPT) - NUMBER OF BLOWS (N OR BPF) OF
SIZE IN. 12 3	BT - BORING TERMINATED MICA MICACEOUS WEA WEATHERED CL CLAY MOD MODERATELY 7 - UNIT WEIGHT	MEDIUM CAN BE GROOVED OR GOUGED 0.05 INCHES DEEP BY FIRM PRESSURE OF KNIFE OR PICK POINT. HARD CAN BE EXCAVATED IN SMALL CHIPS TO PEICES 1 INCH MAXIMUM SIZE BY HARD BLOWS OF THE	A 140 LB. HAMMER FALLING 30 INCHES REQUIRED TO PRODUCE A PENETRATION OF 1 FOOT INTO SOIL WITH A 2 INCH OUTSIDE DIAMETER SPLIT SPOON SAMPLER. SPT REFUSAL IS PENETRATION EQUAL
SOIL MOISTURE - CORRELATION OF TERMS	$ullet$ CPT - CONE PENETRATION TEST NP - NON PLASTIC $\gamma_{ extsf{d}}$ - DRY UNIT WEIGHT	POINT OF A GEOLOGIST'S PICK.	TO OR LESS THAN 0.1 FOOT PER 60 BLOWS.
SOIL MOISTURE SCALE FIELD MOISTURE (ATTERBERG LIMITS) DESCRIPTION GUIDE FOR FIELD MOISTURE DESCRIPTION	CSE COARSE ORG ORGANIC DMT - DILATOMETER TEST PMT - PRESSUREMETER TEST SAMPLE ABBREVIATIONS	SOFT CAN BE GROVED OR GOUGED READILY BY KNIFE OR PICK, CAN BE EXCAVATED IN FRAGMENTS	STRATA CORE RECOVERY (SREC.) - TOTAL LENGTH OF STRATA MATERIAL RECOVERED DIVIDED BY TOTAL LENGTH OF STRATUM AND EXPRESSED AS A PERCENTAGE.
	DPT - DYNAMIC PENETRATION TEST SAP SAPROLITIC S - BULK	FROM CHIPS TO SEVERAL INCHES IN SIZE BY MODERATE BLOWS OF A PICK POINT. SMALL, THIN PIECES CAN BE BROKEN BY FINGER PRESSURE.	STRATA ROCK QUALITY DESIGNATION (SRQD) - A MEASURE OF ROCK QUALITY DESCRIBED BY TOTAL
- SATURATED - USUALLY LIQUID; VERY WET, USUALLY (SAT.) FROM BELOW THE GROUND WATER TABLE	e - VOID RATIO SD SAND, SANDY SS - SPLIT SPOON F - FINE SL SILT, SILTY ST - SHELBY TUBE	VERY CAN BE CARVED WITH KNIFE. CAN BE EXCAVATED READILY WITH POINT OF PICK. PIECES 1 INCH	LENGTH OF ROCK SEGMENTS WITHIN A STRATUM EQUAL TO OR GREATER THAN 4 INCHES DIVIDED BY THE TOTAL LENGTH OF STRATA AND EXPRESSED AS A PERCENTAGE.
	FOSS FOSSILIFEROUS SLI SLIGHTLY RS - ROCK	SOFT OR MORE IN THICKNESS CAN BE BROKEN BY FINGER PRESSURE. CAN BE SCRATCHED READILY BY FINGERNAIL.	TOPSOIL (TS.) - SURFACE SOILS USUALLY CONTAINING ORGANIC MATTER.
PLASTIC SEMISOLID; REQUIRES DRYING TO	FRAC FRACTURED, FRACTURES TCR - TRICONE REFUSAL RT - RECOMPACTED TRIAXIAL W - MOISTURE CONTENT CBR - CALIFORNIA BEARING	FRACTURE SPACING BEDDING	
(PI) PLASTIC LIMIT	HI HIGHLY V - VERY RATIO	TERM SPACING TERM THICKNESS	BENCH MARK: N/A
- MOIST - (M) COLID. AT OR NEAR ORTIMIN MOISTURE	EQUIPMENT USED ON SUBJECT PROJECT	VERY WIDE MORE THAN 10 FEET VERY THICKLY BEDDED 4 FEET	ELEVATION: FEET
OM OPTIMUM MOISTURE	DRILL UNITS: ADVANCING TOOLS: HAMMER TYPE:	MODERATELY CLOSE 1 TO 3 FEET THINLY BEDDED 0.16 - 1.5 FEET	NOTES:
PENLIPES ANDITIONAL WATER TO	CME-45C CLAY BITS X AUTOMATIC MANUAL	CLOSE 0.16 TO 1 FOOT VERY THINLY BEDDED 0.03 - 0.16 FEET VERY CLOSE LESS THAN 0.16 FEET THICKLY LAMINATED 0.008 - 0.03 FEET	
- DRY - (D) ATTAIN OPTIMUM MOISTURE	X CME-550 CORE SIZE:	THINLY LAMINATED (0.008 FEET	SURVEY AND ROADWAY DESIGN FILES PROVIDED BY TGS ENGINEERS ON 11/15/2021
PLASTICITY	X 8* HOLLOW AUGERS	INDURATION	1
PLASTICITY INDEX (PI) DRY STRENGTH	X CME-550X HARD FACED FINGER BITS	FOR SEDIMENTARY ROCKS, INDURATION IS THE HARDENING OF MATERIAL BY CEMENTING, HEAT, PRESSURE, ETC.	
NON PLASTIC 0-5 VERY LOW	TUNGCARBIDE INSERTS	RUBBING WITH FINGER FREES NUMEROUS GRAINS; FRIABLE GENTLE BLOW BY HAMMER DISINTEGRATES SAMPLE.	
SLIGHTLY PLASTIC 6-15 SLIGHT MODERATELY PLASTIC 16-25 MEDIUM	VANE SHEAR TEST CASING W/ ADVANCER HAND TOOLS: CASING POST HOLE DIGGER	CRAINC CAN BE CERABATED FROM CAMBLE WITH CIFFL BRORE.	
HIGHLY PLASTIC 26 OR MORE HIGH	POST HOLE DIGGER POST HOLE DIGGER STEEL TEETH HAND AUGER	MODERATELY INDURATED MODERATELY INDURATED MODERATELY INDURATED BREAKS EASILY WHEN HIT WITH HAMMER.	
COLOR	TRICONE TRICONE SOUNDING ROD	INDURATED GRAINS ARE DIFFICULT TO SEPARATE WITH STEEL PROBE:	
DESCRIPTIONS MAY INCLUDE COLOR OR COLOR COMBINATIONS (TAN, RED, YELLOW-BROWN, BLUE-GRAY).	CORE BIT VANE SHEAR TEST	DIFFICULT TO BREAK WITH HAMMER.	
MODIFIERS SUCH AS LIGHT, DARK, STREAKED, ETC. ARE USED TO DESCRIBE APPEARANCE.		EXTREMELY INDURATED SHARP HAMMER BLOWS REQUIRED TO BREAK SAMPLE; SAMPLE BREAKS ACROSS GRAINS.	DATE: 8-15-1-
		ORDITE DIRECT MOTORS OTHERS.	DHIE: 8-10-14
























							D	ORE L	UG					
WBS	32572	2.1.FS1	0		TII	P A-0009CB	COUNT	Y GRAHAM				GEOLOGIST N. McLaren		
SITE	DESCR	IPTION	Upgr	ade N	C 143 1	from SR 1223 (B	eech Creek Ro	ad) to 0.5 Mil	es North	of Ap	palach	ian Trail	GROUN	D WTR (ft)
BORII	NG NO.	RWA	L14_B	-2	Sī	TATION 349+90 OFFSET 6 ft LT ALIGNMENT L			STATION 349+90 OFFSET			0 HR.	Dry	
COLL	AR EL	EV. 2,	917.1 f	ft	т	OTAL DEPTH 2	23.6 ft	NORTHING	621,40	04		EASTING 593,680	24 HR.	Dry
DRILL	RIG/HAI	VIMER EF	F/DATI	E CG2	29473 C	ME-550 79% 03/12/	2021		DRILL IV	IETHO E) HS	. Augers HA	MMER TYPE	Automatic
DRILL	ER J	. Estep			ST	TART DATE 04	/28/21	COMP. DAT	ΓE 04/2	28/21		SURFACE WATER DEPTH	N/A	
ELEV (ft)	DRIVE ELEV (ft)	DEPTH (ft)	BLC 0.5ft	0.5ft		0 25	DWS PER FOOT	75 100	SAMP.	MOI	L O G	SOIL AND ROCK [ESCRIPTION	DEPTH (f
2920										Z 101.01	_ - -	2,917.1 GROUND SU		0.
2915	2,916.1 - 2,913.6	Į.	24	35 24	45 39			80		D D		Hard, Tan-Gray-Orang Sandy SILT (A-4), wit gravel-sized roc	e, Fine to Coa h trace mica ar	rse nd
2910	2,911.1	Į.	17	21	25		46			D		-	J	
2905	2,908.6	8.5	15	14	17	9 3				D				
	2,903.6	13.5	32	58	42/0.3	:::::)_		100/0.8				- 2,903.1 WEATHERE I Gray-Tan, (META-S		14.
2900	2,898.6	18.5	51	49/0.3				100/0.8	,			-		
2895	2.893.6	23.5	60/0.1									- 2,893.6 -2,893.5/\ CRYSTALLIN		23. \23.
												Gray-Tan, (META-Soring Terminated Penetration Test Ref 2,893.5 ft In Crys (META-SAND)	with Standard usal at Elevatio talline Rock	n

SHEET 12

PROJECT REFERENCE NO.	SHEET NO.
A-0009CB	13

GEOPHYSICAL TEST RESULTS - SEISMIC REFRACTION LINE 14.1



GEOPHYSICAL TESTING PERFORMED BY GEL SOLUTIONS. REFERENCE "SEISMIC REFRACTION SURVEY FOR EVALUATION OF ROCK" DATED 10/01/2021 CG2 ESTIMATED WAVE SPEED FOR WEATHERED ROCK: 4,500 FT/SEC

CG2 ESTIMATED WAVE SPEED FOR CRYSTALLINE ROCK: 7,500 FT/SEC

14000 -

15000 -