



- NOTE: PLACE TEMPORARY ROCK SEDIMENT DAMS TYPE - B AND TEMPORARY ROCK SILT CHECKS TYPE - A AT DRAINAGE OUTLETS.
- NOTE: ALL EROSION CONTROL DEVICES SHOWN ARE LOCATED WITHIN EXISTING RW OR EASEMENT.
- NOTE: PERIMETER EROSION CONTROL MEASURES SHALL BE INSTALLED DURING CLEARING AND GRUBBING PHASE.
- NOTE: CONTRACTOR SHALL PROVIDE GROUND COVER ON EXPOSED SLOPES IN ACCORDANCE WITH THE "SOIL STABILIZATION TIMEFRAMES," SEE EC-3.
- NOTE: PRIOR TO INSTALLATION OF EROSION CONTROL DEVICES, CONTRACTOR SHALL VERIFY BOUNDARIES OF JURISDICTIONAL AREAS AND DELINEATE WITH SAFETY FENCE OR FLAGGING.

ALL DRIVEWAY RADII ARE 20' UNLESS OTHERWISE NOTED.
 UNIFORMLY TRANSITION DRIVEWAY SLOPES AS SHOWN.
 PROPOSED PAVEMENT REMOVAL
 FOR -Y2- PROFILE SEE SHEET 72, 73
 FOR -DR4- PROFILE SEE SHEET 92
 FOR DITCH DETAILS SEE SHEETS 2D-1 AND 2D-2

REVISIONS
 ROW REVISION - 11/23/2021 - CHANGED DRIVEWAY AND EASEMENT ON PARCELS 52, 131, & 133 - CDA

4/7/2022
 R:\E:\Environmental\Design\15987A_EC_PSH_034.dwg
 samuel.skelton