B.M. #9: BENCH NAIL SET IN BASE OF 18"SWEET GUM; 124.27' RIGHT OF STA. 212+40.74 -L-, EL. 146.42 (I-95)--MSE WALL MSE WALL -PROPOSED GUARDRAIL (TYP.) (ROADWAY DETAIL & PAY ITEM)— BRIDGE ID STA. 29+75.79 -Y2-STA. 210+10.00 -L-TO SR 1005 TO US 301 31+00 29+00 30+00 (SR 1529)— ∕-95°-00′-00″ 95°-00′-00″ (TYP.) EXISTING/ BRIDGE— 10 (EX NOTE: FOR UTILITY INFORMATION, SEE UTILITY PLANS AND SPECIAL PROVISIONS. LOCATION SKETCH

TOTAL BILL OF MATERIAL											
	REMOVAL OF EXISTING STRUCTURE AT STA. 29+75.79 -Y2-	ASBESTOS ASSESSMENT	FOUNDATION EXCAVATION FOR BENT 1	PDA TESTING	REINFORCED CONCRETE DECK SLAB	GROOVING BRIDGE FLOORS	CLASS A CONCRETE	BRIDGE APPROACH SLABS	REINFORCING STEEL	SPIRAL COLUMN REINFORCING STEEL	
	LUMP SUM	LUMP SUM	LUMP SUM	EACH	SQ.FT.	SQ.FT.	CU. YDS.	LUMP SUM	LBS.	LBS.	
SUPERSTRUCTURE	LUMP SUM				6,988	6,759					
END BENT 1							27.0	LUMP SUM	3,504		
BENT 1			LUMP SUM				56.2		10,348	1,749	
END BENT 2							27.1	LUMP SUM	3,524		
TOTAL	LUMP SUM	LUMP SUM	LUMP SUM	2	6,988	6,759	110.3	LUMP SUM	17,376	1,749	

			TOTAL B	ΙL	L OF	М	ATER	CIAL				
	54" PRESTRESSED CONCRETE GIRDERS	PILE DRIVING EQUIPMENT SETUP FOR HP 12 X 53 STEEL PILES	PILE DRIVING EQUIPMENT SETUP FOR HP 14 X 73 STEEL PILES	HP STE	12 X 53 EL PILES	HP STE	14 X 73 EL PILES	PILE REDRIVES	TWO BAR METAL RAIL	1'-2" X 2'-6" CONCRETE PARAPET	4"SLOPE PROTECTION	ELASTOMERIO BEARINGS
	LIN.FT.	EACH	EACH	NO.	LIN.FT.	NO.	LIN.FT.	EACH	LIN.FT.	LIN.FT.	SQ. YDS.	LUMP SUM
SUPERSTRUCTURE	754.24								363.44	378.65		LUMP SUM
END BENT 1		6		6	600.0			3			12	
BENT 1			18			18	1170.0	9				
END BENT 2		6		6	510.0			3			12	
TOTAL	754.24	12	18	12	1110.0	18	1170.0	15	363.44	378.65	24	LUMP SUM

DATE: 06/2021 DRAWN BY : B.E. LANNING _ DATE : 06/2021 CHECKED BY : A.K. ORR DATE: 03/2022 DESIGN ENGINEER OF RECORD : A.K. ORR

NOTES:

ASSUMED LIVE LOAD = HL 93 OR ALTERNATE LOADING.

THIS BRIDGE HAS BEEN DESIGNED IN ACCORDANCE WITH THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS.

THIS BRIDGE IS LOCATED IN SEISMIC ZONE 2.

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

FOR EROSION CONTROL MEASURES, SEE EROSION CONTROL PLANS.

NEEDLE BEAMS WILL NOT BE ALLOWED UNLESS OTHERWISE CALLED FOR ON THE PLANS OR APPROVED BY THE ENGINEER.

REMOVABLE FORMS MAY BE USED IN LIEU OF METAL STAY-IN-PLACE FORMS IN ACCORDANCE WITH ARTICLE 420-3 OF THE STANDARD SPECIFICATIONS.

ALL FALSEWORK AND FORMS SHALL REMAIN IN PLACE UNTIL THE ENTIRE UNIT IS CAST AND CURED. CONTRACTOR SHALL BE RESPONSIBLE FOR MODIFICATIONS IN THE LINK SLAB REGION.

FOR MAINTENANCE AND PROTECTION OF TRAFFIC BENEATH PROPOSED STRUCTURE, SEE SPECIAL PROVISIONS.

FOR LIMITS OF TEMPORARY SHORING FOR MAINTENANCE OF TRAFFIC, SEE TRAFFIC CONTROL PLANS. FOR PAY ITEM FOR TEMPORARY SHORING FOR MAINTENANCE OF TRAFFIC, SEE ROADWAY PLANS.

THE SUBSTRUCTURE OF THE EXISTING BRIDGE INDICATED ON THE PLANS IS FROM THE BEST INFORMATION AVAILABLE. THIS INFORMATION IS SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR. THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER AGAINST THE DEPARTMENT OF TRANSPORTATION FOR ANY DELAYS OR ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN THE EXISTING BRIDGE SUBSTRUCTURE SHOWN ON THE PLANS AND THE ACTUAL CONDITIONS AT THE PROJECT SITE.

AFTER SERVING AS A TEMPORARY STRUCTURE, THE EXISTING STRUCTURE CONSISTING OF 5 SPANS UNITS; ON REINFORCED CONCRETE END BENTS AND BENTS AND LOCATED AT 47 FT. SOUTH OF THE PROPOSED STRUCTURE SHALL BE REMOVED. THE EXISTING BRIDGE IS PRESENTLY NOT POSTED FOR LOAD LIMIT. SHOULD THE STRUCTURAL INTEGRITY OF THE BRIDGE DETERIORATE DURING THE CONSTRUCTION OF THE PROPOSED BRIDGE, A LOAD LIMIT MAY BE POSTED AND MAY BE REDUCED AS FOUND NECESSARY DURING THE LIFE OF THE PROJECT.

FOR ASBESTOS ASSESSMENT FOR BRIDGE DEMOLITION AND RENOVATION ACTIVITIES, SEE SPECIAL PROVISIONS.

FOR SUBMITTAL OF WORKING DRAWINGS. SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK, SEE SPECIAL PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIONS.

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR FOUNDATION NOTES, SEE "PILE FOUNDATION TABLES" SHEET.

THE ELEVATIONS AND CLEARANCES SHOWN ON THE PLANS AT THE POINTS OF MINIMUM VERTICAL CLEARANCE ARE FROM THE BEST INFORMATION AVAILABLE. PRIOR TO BEGINNING BRIDGE CONSTRUCTION, VERIFY THE ELEVATIONS ON THE EXISTING PAVEMENT AND CHECK THE CLEARANCE. REPORT ANY VARIATIONS TO THE ENGINEER. ANY PLAN REVISIONS NECESSARY TO ACHIEVE THE REQUIRED MINIMUM VERTICAL CLEARANCE WILL BE PROVIDED BY THE DEPARTMENT.

FOR MSE RETAINING WALLS, SEE GEOTECHNICAL SPECIAL PROVISIONS.

PROJECT NO. I-5987A ROBESON COUNTY

29+75.79 -Y2-STATION: 210+10.00 -L-

SHEET 2 OF 2

STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTATION

GENERAL DRAWING

FOR BRIDGE ON SR 1529 (POWERSVILLE ROAD) OVER I-95 BETWEEN US 301 & SR 1005



MI ENGINEERING 11 SCHAUB DRIVE, SUITE 100 No. RALEIGH, NC 27606 (919) 851-6606 FIRM PE NUMBER : P-0671

REVISIONS S1-2 NO. BY: BY: DATE: TOTAL SHEETS 36