

**This electronic collection of documents is provided
for the convenience of the user
and is Not a Certified Document –**

**The documents contained herein were originally issued
and sealed by the individuals whose names and license
numbers appear on each page, on the dates appearing
with their signature on that page.**

**This file or an individual page
shall not be considered a certified document.**

TIP PROJECT: U-2579AA


STATE OF NORTH CAROLINA
DIVISION OF HIGHWAYS

FORSYTH COUNTY

**LOCATION: WINSTON-SALEM NORTHERN BELTWAY
EASTERN SECTION (FUTURE I-74)
FROM US 311 TO I-40**

**TYPE OF WORK: COMMUNICATIONS CABLE AND CONDUIT ROUTING, CCTV
CAMERA, DYNAMIC MESSAGE SIGN AND HUB CABINET INSTALLATION**

STATE	STATE PROJECT REFERENCE NO.	SHEET NO.
N.C.	U-2579AA	ITS-1
STATE PROJ. NO.	F.A. PROJ. NO.	DESCRIPTION
34839.3.13	0074226	CONST.
34839.1.7	0074226	PE



2018 STANDARD SPECIFICATIONS

PROJECT LENGTH
PROJECT LENGTH = 1.60 MILES

LETTING DATE:
OCTOBER 18, 2022

INDEX OF SHEETS

SHEET ITS 1.....	TITLE SHEET
SHEET ITS 2.....	CONSTRUCTION NOTES AND LEGEND
SHEET ITS 3.....	SYSTEM BLOCK DIAGRAM
SHEET ITS 4-17.....	CABLE ROUTING PLANS
SHEET ITS 18-23.....	SPLICE DETAILS
SHEET ITS 24-28.....	TYPICAL DETAILS
SHEET ITS 29-31.....	DMS S-DIMENSIONS

ROADWAY STANDARD DRAWINGS

THE FOLLOWING ROADWAY STANDARDS AS APPEAR IN "ROADWAY STANDARD DRAWINGS" ROADWAY DESIGN UNIT - N.C. DEPARTMENT OF TRANSPORTATION - RALEIGH, N.C., DATED JANUARY 2018 ARE APPLICABLE TO THIS PROJECT AND BY REFERENCE HEREBY ARE CONSIDERED A PART OF THESE PLANS:


STD. NO.	TITLE
1700.01.....	ELECTRICAL SERVICE OPTIONS
1700.02.....	ELECTRICAL SERVICE GROUNDING
1715.01.....	UNDERGROUND CONDUIT-TRENCHING
1716.01.....	JUNCTION BOXES
1720.01.....	WOOD POLES
1730.01.....	FIBER OPTIC CABLE

2018 STANDARD SPECIFICATION


NCDOT CONTACT:
TRANSPORTATION MOBILITY AND SAFETY

M. M. MCDIARMID, P.E., CPM
STATE TRANSPORTATION SYSTEMS
MANAGEMENT & OPERATIONS ENGINEER


Prepared in the Offices of:



750 N. Greenfield Pkwy., Garner, NC 27529



ALL DIMENSIONS IN THESE PLANS ARE IN FEET UNLESS OTHERWISE NOTED



Designed by: Andrew J. Skuce
DATE: 06/22/2022

- 1 INSTALL COAX CABLE
- 2 INSTALL 4-WIRE COPPER FEEDER CONDUCTORS
- 3 INSTALL 3-WIRE COPPER FEEDER CONDUCTORS
- 4 INSTALL SMFO CABLE
- 5 EXISTING SMFO CABLE
- 6 INSTALL FIBER OPTIC DROP CABLE
- 7 INSTALL TRACER WIRE
- 8 TRENCH
- 9 INSTALL PVC CONDUIT
- 10 INSTALL RIGID, GALVANIZED STEEL CONDUIT
- 11 INSTALL RIGID, GALVANIZED STEEL RISER WITH WEATHERHEAD
- 12 INSTALL RIGID, GALVANIZED STEEL RISER WITH FIBER OPTIC CABLE SEAL
- 13 INSTALL OUTER-DUCT POLYETHYLENE CONDUIT
- 14 INSTALL POLYETHYLENE CONDUIT
- 15 DIRECTIONAL DRILL CONDUIT
- 16 BORE AND JACK CONDUIT
- 17 INSTALL CABLE(S) IN EXISTING CONDUIT
- 18 INSTALL CABLE(S) IN NEW CONDUIT
- 19 INSTALL CABLE(S) IN EXISTING RISER
- 20 INSTALL CABLE(S) IN NEW RISER
- 21 INSTALL CABLE(S) IN EXISTING CONDUIT STUB-OUTS
- 22 INSTALL NEW CONDUIT INTO CABINET BASE (USE EXISTING CONDUIT STUB-OUTS WHEN AVAILABLE)
- 23 INSTALL NEW RISER INTO EXISTING CABINET BASE (USE EXISTING CONDUIT STUB-OUTS WHEN AVAILABLE)
- 24 INSTALL NEW CONDUIT INTO POLE MOUNTED CABINET
- 25 INSTALL NEW RISER INTO EXISTING POLE MOUNTED CABINET
- 26 INSTALL NEW ETHERNET EDGE SWITCH
- 27 INSTALL NEW FIBER OPTIC TRANSCEIVER
- 28 INSTALL INTERCONNECT CENTER, PATCH PANEL, JUMPERS AND FUSION SPlice CABLE IN CABINET
- 29 INSTALL UNDERGROUND SPlice ENCLOSURE
- 30 INSTALL AERIAL SPlice ENCLOSURE
- 31 MODIFY EXISTING INTERCONNECT CENTER /SPlice ENCLOSURE
- 32 INSTALL POLE MOUNTED SPlice CABINET
- 33 INSTALL BASE MOUNTED HUB CABINET

- 34 INSTALL CABINET FOUNDATION
- 35 INSTALL CCTV CAMERA POLE MOUNTED CABINET
- 36 INSTALL CCTV CAMERA ASSEMBLY
- 37 INSTALL CCTV CAMERA WOOD POLE
- 38 INSTALL CCTV CAMERA METAL POLE AND FOUNDATION
- 39 INSTALL JUNCTION BOX
- 40A INSTALL OVERSIZED JUNCTION BOX
- 40B INSTALL SPECIAL OVERSIZED JUNCTION BOX (36" x 24" x 24")
- 41 REMOVE EXISTING JUNCTION BOX
- 42 INSTALL WOOD POLE
- 43 REMOVE EXISTING WOOD POLE
- 44 INSTALL DMS ASSEMBLY
- 45 INSTALL DMS PEDESTAL STRUCTURE
- 46 INSTALL SIDEWALK GUY ASSEMBLY
- 47 INSTALL MESSENGER CABLE
- 48A REMOVE EXISTING COMMUNICATIONS AND MESSENGER CABLE
- 48B REMOVE EXISTING COMMUNICATIONS CABLE
- 49 BACK PULL EXISTING COMMUNICATIONS CABLE
- 50 INSTALL CELL MODEM AND ANTENNA
- 51 INSTALL CABLE STORAGE RACKS (SNOW SHOES) AND STORE 100 FEET OF CABLE
- 52A INSTALL DELINEATOR MARKER
- 52B INSTALL JUNCTION BOX MARKER
- 53A STORE 20 FEET OF COMMUNICATIONS CABLE
- 53B STORE 50 FEET OF EACH COMMUNICATIONS CABLE
- 54 LASH CABLE(S) TO EXISTING COMMUNICATIONS CABLE
- 55 LASH CABLE(S) TO EXISTING MESSENGER CABLE
- 56 INSTALL NEW SOLAR ASSEMBLY
- 57 INSTALL 10KVA SINGLE PHASE TRANSFORMER
- 58 INSTALL NEW ELECTRICAL SERVICE
- 59 INSTALL NEW EQUIPMENT CABINET DISCONNECT
- 60 BOND TRACER WIRE TO EQUIPMENT GROUND BUS
DO NOT BOND TRACER WIRE TO EQUIPMENT GROUND BUS
- 61 BOND RISER AND MESSENGER CABLE TO POLE GROUND
- 62 BOND RISER TO POLE GROUND
- 63 BOND MESSENGER CABLE TO POLE GROUND
- 64 INSTALL HEAT SHRINK TUBING RETROFIT KIT
- 65 INSTALL MOLDABLE DUCT SEAL
- 66 INSTALL CCTV EXTENSION POLE

LEGEND

	NEW FIBER OPTIC COMMUNICATIONS CABLE
	EXISTING COMMUNICATIONS CABLE
	EXISTING COMMUNICATIONS CABLE TO BE REMOVED
	NEW AERIAL GUY ASSEMBLY
	NEW CONDUIT
	EXISTING CONDUIT
	NEW DIRECTIONAL DRILLED CONDUIT

NEW

- OVERSIZED JUNCTION BOX
- WOOD POLE
- AERIAL SPlice ENCLOSURE
- UNDERGROUND SPlice ENCLOSURE
- METAL POLE
- CCTV ASSEMBLY
- STANDARD GUY ASSEMBLY
- SIDEWALK GUY ASSEMBLY
- CABLE STORAGE RACKS (SNOW SHOES)
- SIGNAL/EQUIPMENT CABINET
- SPlice CABINET
- FLAT PANEL ANTENNA (SINGLE)
- YAGI ANTENNA (DOUBLE) FOR REPEATER OPERATION
- YAGI ANTENNA (SINGLE)
- OMNI ANTENNA
- SIGNAL POLE
- SIGNAL INVENTORY NUMBER
- ELECTRICAL SERVICE

EXISTING

-
-
-
-
-
-
-
-
-
-
-
-
-

CONSTRUCTION NOTE SYMBOLOGY KEY



- INDICATES NUMBER OF CABLES, LOOPS, ETC.
 - INDICATES NUMBER OF FIBERS PER CABLE, TWISTED PAIRS PER CABLE, ETC.
 - INDICATES NUMBER OF RISER(S)/CONDUIT(S)
 - INDICATES DIAMETER OF RISER(S)/CONDUIT(S) (INCH)
-

ATTACHMENT POINT:

- 'SS' DISTANCE ABOVE (IN)/ATTACHMENT POINT REFERENCE POINT
 - REFERENCE POINT DISTANCE BELOW (IN)/ATTACHMENT POINT
- "SS" REFERENCE LOCATION**
 FS = FRONT SIDE OF POLE
 BS = BACK SIDE OF POLE

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



	CONSTRUCTION NOTES		
	DIVISION 09 FORSYTH CO. WINSTON-SALEM	PLAN DATE: MARCH 2022	
250 N. Greenfield Place, Garner, NC 27529	PREPARED BY: J. WALDEN	DocuSigned by: Andrew J. Skuce DATE: 03/31/2022	
REVISIONS		INIT.	DATE





NOTES

1. DEVICE NUMBERING IS FOR THE PURPOSES OF THIS PROJECT ONLY.
2. INSTALL DEPARTMENT SUPPLIED CELL MODEMS IN DMS CABINETS FOR BACKUP COMMUNICATIONS. ALLOW 8 WEEK LEAD TIME AFTER REQUESTING THE MODEMS FROM THE DEPARTMENT.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

 Prepared in the Offices of: 750 N. Greenfield Pkwy., Garner, NC 27529	DEVICE CONNECTION DIAGRAM		 SEAL 050152 ENGINEER ANDREW J. SKUCE
	DIVISION 09 FORSYTH CO., WINSTON-SALEM PLAN DATE: MARCH 2022 REVIEWED BY: A. SKUCE PREPARED BY: J. WALDEN REVIEWED BY:		
	REVISIONS	INIT.	DATE
DocuSigned by: Andrew J. Skuce			03/31/2022 DATE



NOTES

1. OBTAIN FINAL DMS LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.
2. CONTACT ENGINEER TO REQUEST NCDOT SUPPLIED MODEM AT LEAST SIX WEEKS PRIOR TO INSTALLATION.



SEE DRAWING 2

INSTALL 6"X6" PEDESTAL WITH A 10KVA SINGLE PHASE TRANSFORMER

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

<p>750 N. Greenfield Pkwy., Garner, NC 27529</p>	<p>COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS</p>		
	<p>DIVISION 09 FORSYTH CO. WINSTON-SALEM</p>		
<p>PLAN DATE: MARCH 2022</p>	<p>REVIEWED BY: A. SKUCE</p>	<p>PREPARED BY: J. WALDEN</p>	<p>REVIEWED BY:</p>
<p>REVISIONS</p>	<p>INIT.</p>	<p>DATE</p>	<p>DocuSigned by: Andrew J. Skuce DATE: 03/31/2022</p>

DRAWING 1



MATCHLINE - SEE ITS-4

MATCHLINE - SEE ITS-6


US 311 WB


US 311 EB

SEE DRAWING 1


DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

<p>750 N. Greenfield Pkwy., Garner, NC 27529</p>	COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS		
	DIVISION 09 FORSYTH CO., WINSTON-SALEM		
PLAN DATE: MARCH 2022	PREPARED BY: J. WALDEN	REVIEWED BY: A. SKUCE	SEAL 050152 ENGINEER ANDREW J. SKUCE 03/31/2022
REVISIONS		INIT. DATE	







**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
DIVISION 09	FORSYTH CO. WINSTON-SALEM
PLAN DATE: MARCH 2022	REVIEWED BY: A. SKUCE
PREPARED BY: J. WALDEN	REVIEWED BY:
REVISIONS	INIT. DATE




DocuSigned by:
Andrew J. Skuce
03/31/2022



NOTES

- OBTAIN FINAL CCTV LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.

DRAWING 1




DRAWING 2




DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	<p>COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS</p>	
	<p>DIVISION 09 FORSYTH CO. WINSTON-SALEM</p>	<p>SEAL 050152 ENGINEER ANDREW J. SKUCE</p>
<p>750 N. Greenfield Pkwy., Garner, NC 27529</p>	<p>PLAN DATE: MARCH 2022</p>	<p>REVIEWED BY: A. SKUCE</p>
<p>SCALE 0 50' 1" = 50'</p>	<p>PREPARED BY: J. WALDEN</p>	<p>REVIEWED BY:</p>
<p>REVISIONS</p>	<p>INIT.</p>	<p>DATE</p>
<p>DocuSigned by: Andrew J. Skuce</p>	<p>03/31/2022</p>	<p>DATE</p>





**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
DIVISION 09	FORSYTH CO., WINSTON-SALEM
PLAN DATE: MARCH 2022	REVIEWED BY: A. SKUCE
PREPARED BY: J. WALDEN	REVIEWED BY:
REVISIONS	INIT. DATE

SEAL
NORTH CAROLINA
PROFESSIONAL
ENGINEER
ANDREW J. SKUCE
050152
3/31/2022
DATE





**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

Prepared in the Offices of:


750 N. Greenfield Pkwy., Garner, NC 27529

SCALE
0 50'
1" = 50'

COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
DIVISION 09 FORSYTH CO. WINSTON-SALEM	
PLAN DATE: MARCH 2022	REVIEWED BY: A. SKUCE
PREPARED BY: J. WALDEN	REVIEWED BY:
REVISIONS	INIT. DATE

SEAL



Andrew J. Skuce
03/31/2022



SEE DRAWING 1

DRAWING 1


DRAWING 2



SEE DRAWING 2

MATCHLINE - SEE ITS-9


MATCHLINE - SEE ITS-11





NOTES

- OBTAIN FINAL CCTV LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED





COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
DIVISION 09	FORSYTH CO. WINSTON-SALEM
PLAN DATE: MARCH 2022	REVIEWED BY: A. SKUCE
PREPARED BY: J. WALDEN	REVIEWED BY:
REVISIONS	INIT. DATE



DRAWING 1



SEE DRAWING 2




SEE DRAWING 1


MATCHLINE - SEE ITS-10

MATCHLINE - SEE ITS-20

MATCHLINE - SEE ITS-12




DRAWING 2





NOTES

- OBTAIN FINAL CCTV LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS		DIVISION 09 FORSYTH CO. WINSTON-SALEM	
PLAN DATE: MARCH 2022	PREPARED BY: J. WALDEN	REVIEWED BY: A. SKUCE	DATE: 03/31/2022
REVISIONS	INIT.	DATE	



DRAWING 2




NOTES

- OBTAIN FINAL HUB CABINET LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.
- INSTALL HUB CABINET A MINIMUM OF 30 FEET OFF THE EDGE OF TRAVEL.
- DIT TO SUPPLY HUB ETHERNET SWITCH. ALLOW MINIMUM 12 WEEK LEAD TIME AFTER REQUESTING THE HUB ETHERNET SWITCH FROM DIT.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
	DIVISION 09 FORSYTH CO. WINSTON-SALEM PLAN DATE: MARCH 2022 REVIEWED BY: A. SKUCE PREPARED BY: J. WALDEN REVIEWED BY:	REVISIONS INIT. DATE
Prepared in the Offices of: 750 N. Greenfield Pkwy., Garner, NC 27529	SCALE 0 50' 1" = 50'	SEAL NORTH CAROLINA PROFESSIONAL ENGINEER ANDREW J. SKUCE 03/31/2022 Andrew J. Skuce



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**


Prepared in the Offices of:

750 N. Greenfield Pkwy., Garner, NC 27529

COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
DIVISION 09 FORSYTH CO. WINSTON-SALEM	
PLAN DATE: MARCH 2022	REVIEWED BY: A. SKUCE
PREPARED BY: J. WALDEN	REVIEWED BY:
REVISIONS	INIT. DATE

SEAL


DocuSigned by:
Andrew J. Skuce
DATE: 03/31/2022




MATCHLINE - SEE ITS-13

SEE DRAWING 2


SEE DRAWING 1



DRAWING 1



DRAWING 2








NOTES


- OBTAIN FINAL DMS AND CCTV LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.
- CONTACT ENGINEER TO REQUEST NCDOT SUPPLIED MODEM AT LEAST SIX WEEKS PRIOR TO INSTALLATION.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



	Prepared in the Offices of: 		COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
	750 N. Greenfield Pkwy., Garner, NC 27529		DIVISION 09 FORSYTH CO., WINSTON-SALEM	SEAL NORTH CAROLINA PROFESSIONAL ENGINEER ANDREW J. SKUCE 03/31/2022
SCALE 0 50' 1" = 50'	PLAN DATE: MARCH 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. SKUCE	REVISIONS INIT. DATE	DATE



**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**




COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
DIVISION 09	FORSYTH CO., WINSTON-SALEM
PLAN DATE: MARCH 2022	REVIEWED BY: A. SKUCE
PREPARED BY: J. WALDEN	REVIEWED BY:
REVISIONS	INIT. DATE



DocuSigned by:
Andrew J. Skuce
03/31/2022

SEE DRAWING 2




MATCHLINE - SEE ITS-15


MATCHLINE - SEE ITS-17

I-74 - NORTHERN BELTWAY

DRAWING 2



DRAWING 1




SEE DRAWING 1



NOTES

- OBTAIN FINAL CCTV LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.





DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED



COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS	
DIVISION 09	FORSYTH CO., WINSTON-SALEM
PLAN DATE: MARCH 2022	REVIEWED BY: A. SKUCE
PREPARED BY: J. WALDEN	REVIEWED BY:
REVISIONS	INIT. DATE




SEE DRAWING 3



NOTES

- OBTAIN FINAL CCTV AND DMS LOCATION APPROVAL FROM THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) BEFORE INITIATING ANY WORK AT THIS LOCATION.
- CONTACT ENGINEER TO REQUEST NCDOT SUPPLIED MODEM AT LEAST SIX WEEKS PRIOR TO INSTALLATION.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED





COMMUNICATIONS CABLING AND CONDUIT ROUTING PLANS



DIVISION 09 FORSYTH CO. WINSTON-SALEM

PLAN DATE: MARCH 2022 REVIEWED BY: A. SKUCE

PREPARED BY: J. WALDEN REVIEWED BY:

REVISIONS	INIT.	DATE





1) FIVE (5) DAYS PRIOR TO BEGINNING WORK CONTACT THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) TO ARRANGE FOR PROGRAMING OF THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SYSTEM IS OPERATIONAL

2) ETHERNET SWITCH TERMINATION CONFIGURATIONS ARE GENERIC. CONTRACTOR IS RESPONSIBLE FOR DETERMINING \ ENSURING PROPER TERMINATIONS.


3) INCLUDE ON THE COVER OF EACH SPLICE TRAY THE FOLLOWING: REFERENCE SECTION 1731 "FIBER OPTIC SPLICE ENCLOSURE"

- 1) SPLICE LOCATION
- 2) DATE
- 3) COMPANY NAME
- 4) NAME OF INDIVIDUAL PERFORMING THE SPLICING

PRIOR TO INSTALLING THE COVER ON THE SPLICE TRAY TAKE A DIGITAL PHOTOGRAPH SHOWING THE SPLICE TRAY AND INFORMATION SHOWN ABOVE (1-4) AND SUBMIT PHOTOGRAPH ALONG WITH OTDR TEST RESULTS.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	SPLICE DETAIL		
	DIVISION 09 FORSYTH CO.		
PLAN DATE: MARCH 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, PE REVIEWED BY:		SEAL 050152 ENGINEER ANDREW J. SKUCE
REVISIONS _____ _____	INIT. _____ _____	DATE _____ _____	DocuSigned by: Andrew J. Skuce 03/31/2022 DATE





- 1) FIVE (5) DAYS PRIOR TO BEGINNING WORK CONTACT THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) TO ARRANGE FOR PROGRAMING OF THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SYSTEM IS OPERATIONAL
 - 2) ETHERNET SWITCH TERMINATION CONFIGURATIONS ARE GENERIC. CONTRACTOR IS RESPONSIBLE FOR DETERMINING \ ENSURING PROPER TERMINATIONS.
 - 3) INCLUDE ON THE COVER OF EACH SPLICE TRAY THE FOLLOWING: REFERENCE SECTION 1731 "FIBER OPTIC SPLICE ENCLOSURE"
- 1) SPLICE LOCATION
 - 2) DATE
 - 3) COMPANY NAME
 - 4) NAME OF INDIVIDUAL PERFORMING THE SPLICING

PRIOR TO INSTALLING THE COVER ON THE SPLICE TRAY TAKE A DIGITAL PHOTOGRAPH SHOWING THE SPLICE TRAY AND INFORMATION SHOWN ABOVE (1-4) AND SUBMIT PHOTOGRAPH ALONG WITH OTDR TEST RESULTS.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	SPLICE DETAIL		
	DIVISION 09 FORSYTH CO.		
PLAN DATE: MARCH 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, PE REVIEWED BY:		DocuSigned by: Andrew J. Skuce 03/31/2022
REVISIONS	INIT.	DATE	





- 1) FIVE (5) DAYS PRIOR TO BEGINNING WORK CONTACT THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) TO ARRANGE FOR PROGRAMING OF THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SYSTEM IS OPERATIONAL
- 2) ETHERNET SWITCH TERMINATION CONFIGURATIONS ARE GENERIC. CONTRACTOR IS RESPONSIBLE FOR DETERMINING \ ENSURING PROPER TERMINATIONS.
- 3) INCLUDE ON THE COVER OF EACH SPLICE TRAY THE FOLLOWING: REFERENCE SECTION 1731 "FIBER OPTIC SPLICE ENCLOSURE"

- 1) SPLICE LOCATION
- 2) DATE
- 3) COMPANY NAME
- 4) NAME OF INDIVIDUAL PERFORMING THE SPLICING

PRIOR TO INSTALLING THE COVER ON THE SPLICE TRAY TAKE A DIGITAL PHOTOGRAPH SHOWING THE SPLICE TRAY AND INFORMATION SHOWN ABOVE (1-4) AND SUBMIT PHOTOGRAPH ALONG WITH OTDR TEST RESULTS.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	SPLICE DETAIL		
	DIVISION 09 FORSYTH CO. PLAN DATE: MARCH 2022 PREPARED BY: J. WALDEN		
750 N. Greenfield Pkwy., Garner, NC 27529		REVISIONS	INIT. DATE
			DocuSigned by: Andrew J. Skuce 03/31/2022




- 1) FIVE (5) DAYS PRIOR TO BEGINNING WORK CONTACT THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) TO ARRANGE FOR PROGRAMING OF THE NEW FIELD ETHERNET SWITCHES WITH THE NECESSARY NETWORK CONFIGURATION DATA, INCLUDING BUT NOT LIMITED TO: THE PROJECT IP ADDRESS, DEFAULT GATEWAY, SUBNET MASK AND VLAN ID INFORMATION. NOTIFY THE THE INCIDENT MANAGEMENT ENGINEER (336-315-7080) AFTER ALL WORK IS PERFORMED TO ENSURE THAT ALL FIBER CIRCUITS ARE FUNCTIONING PROPERLY. WORK IS NOT COMPLETE UNTIL THE SYSTEM IS OPERATIONAL
- 2) ETHERNET SWITCH TERMINATION CONFIGURATIONS ARE GENERIC. CONTRACTOR IS RESPONSIBLE FOR DETERMINING \ ENSURING PROPER TERMINATIONS.
- 3) INCLUDE ON THE COVER OF EACH SPLICE TRAY THE FOLLOWING: REFERENCE SECTION 1731 "FIBER OPTIC SPLICE ENCLOSURE"
 - 1) SPLICE LOCATION
 - 2) DATE
 - 3) COMPANY NAME
 - 4) NAME OF INDIVIDUAL PERFORMING THE SPLICING

PRIOR TO INSTALLING THE COVER ON THE SPLICE TRAY TAKE A DIGITAL PHOTOGRAPH SHOWING THE SPLICE TRAY AND INFORMATION SHOWN ABOVE (1-4) AND SUBMIT PHOTOGRAPH ALONG WITH OTDR TEST RESULTS.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	SPLICE DETAIL		
	DIVISION 09 FORSYTH CO.		
PLAN DATE: MARCH 2022	REVIEWED BY: A. J. SKUCE, PE		
PREPARED BY: J. WALDEN	REVIEWED BY:		
REVISIONS	INIT.	DATE	
DocuSigned by: Andrew J. Skuce		DATE: 03/31/2022	

NEW HUB CABINET
HUB-1
US 311 AT NORTHERN BELTWAY




- 1) ETHERNET SWITCH TERMINATION CONFIGURATIONS ARE GENERIC. CONTRACTOR IS RESPONSIBLE FOR DETERMINING \ ENSURING PROPER TERMINATIONS.
- 2) INCLUDE ON THE COVER OF EACH SPLICE TRAY THE FOLLOWING: REFERENCE SECTION 1731 "FIBER OPTIC SPLICE ENCLOSURE"
 - 1) SPLICE LOCATION
 - 2) DATE
 - 3) COMPANY NAME
 - 4) NAME OF INDIVIDUAL PERFORMING THE SPLICING

PRIOR TO INSTALLING THE COVER ON THE SPLICE TRAY TAKE A DIGITAL PHOTOGRAPH SHOWING THE SPLICE TRAY AND INFORMATION SHOWN ABOVE (1-4) AND SUBMIT PHOTOGRAPH ALONG WITH OTDR TEST RESULTS.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

	SPLICE DETAIL		
	DIVISION 09 FORSYTH CO.		
PLAN DATE: MARCH 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, PE. REVIEWED BY:		SEAL 050152 ENGINEER ANDREW J. SKUCE
REVISIONS _____ _____	INIT. _____ _____	DATE _____ _____	DocuSigned by: Andrew J. Skuce 03/31/2022








- 1) ETHERNET SWITCH TERMINATION CONFIGURATIONS ARE GENERIC. CONTRACTOR IS RESPONSIBLE FOR DETERMINING \ ENSURING PROPER TERMINATIONS.
- 2) INCLUDE ON THE COVER OF EACH SPLICE TRAY THE FOLLOWING:
REFERENCE SECTION 1731 "FIBER OPTIC SPLICE ENCLOSURE"
 - 1) SPLICE LOCATION
 - 2) DATE
 - 3) COMPANY NAME
 - 4) NAME OF INDIVIDUAL PERFORMING THE SPLICING

PRIOR TO INSTALLING THE COVER ON THE SPLICE TRAY TAKE A DIGITAL PHOTOGRAPH SHOWING THE SPLICE TRAY AND INFORMATION SHOWN ABOVE (1-4) AND SUBMIT PHOTOGRAPH ALONG WITH OTDR TEST RESULTS.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

 <small>Prepared in the Offices of: 750 N. Greenfield Pkwy., Garner, NC 27529</small>	<p>SPLICE DETAIL</p> <p>DIVISION 09 FORSYTH CO.</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"><small>PLAN DATE:</small> MARCH 2022</td> <td style="width: 50%;"><small>REVIEWED BY:</small> A. J. SKUCE, PE</td> </tr> <tr> <td><small>PREPARED BY:</small> J. WALDEN</td> <td><small>REVIEWED BY:</small></td> </tr> </table>	<small>PLAN DATE:</small> MARCH 2022	<small>REVIEWED BY:</small> A. J. SKUCE, PE	<small>PREPARED BY:</small> J. WALDEN	<small>REVIEWED BY:</small>	 <small>DocuSigned by: Andrew J. Skuce</small>		
<small>PLAN DATE:</small> MARCH 2022	<small>REVIEWED BY:</small> A. J. SKUCE, PE							
<small>PREPARED BY:</small> J. WALDEN	<small>REVIEWED BY:</small>							
	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 80%;"><small>REVISIONS</small></th> <th style="width: 10%;"><small>INIT.</small></th> <th style="width: 10%;"><small>DATE</small></th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>	<small>REVISIONS</small>	<small>INIT.</small>	<small>DATE</small>				<small>DocuSigned by: Andrew J. Skuce</small> <small>03/31/2022</small> <small>DATE</small>
<small>REVISIONS</small>	<small>INIT.</small>	<small>DATE</small>						









NOTES

1. BOND 0.5 INCH DIAMETER, 28 STRAND (MINIMUM) CLASS II COPPER CONDUCTOR TO THE MAIN GROUND ROD BY AN IRREVERSIBLE MECHANICAL CRIMP METHOD.
2. ALL CONNECTIONS TO GROUND RODS SHOULD BE MADE WITH AN IRREVERSIBLE MECHANICAL CRIMP METHOD.
3. BOND #4 AWG SOLID BARE COPPER WIRE TO REBAR CAGE AND THE MAIN GROUND ROD BY AN IRREVERSIBLE MECHANICAL CRIMP.
4. ENSURE CAMERA HOUSING, CAMERA, AND PAN -TILT UNIT ARE BONDED TO POLE.
5. REMOVE BONDING JUMPER BETWEEN EQUIPMENT CABINET GROUND BUSS AND NEUTRAL BUSS.
6. REFER TO STANDARD DRAWING 1700-2 FOR ALTERNATE GROUND ROD INSTALLATION METHOD AS APPROVED BY THE ENGINEER.
7. INSTALL MARKER TAPE DIRECTLY ABOVE ALL GROUNDING ELECTRODES AND CONDUCTORS AT A DEPTH OF 12 INCHES.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	Prepared in the Offices of: CCTV CAMERA INSTALLATION FOR METAL POLE WITH AERIAL ELECTRICAL SERVICE TYPICAL DETAIL FORSYTH CO.		SEAL NORTH CAROLINA PROFESSIONAL ENGINEER ANDREW J. SKUCE 050152 03/31/2022
	DIVISION 09 PLAN DATE: FEBRUARY 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, PE. REVIEWED BY:	




- NOTES**
1. BOND 0.5 INCH DIAMETER, 28 STRAND (MINIMUM) CLASS II COPPER CONDUCTOR TO THE MAIN GROUND ROD BY AN IRREVERSIBLE MECHANICAL CRIMP METHOD.
 2. ALL CONNECTIONS TO GROUND RODS SHOULD BE MADE WITH AN IRREVERSIBLE MECHANICAL CRIMP METHOD.
 3. BOND #4 AWG SOLID BARE COPPER WIRE TO REBAR CAGE AND THE MAIN GROUND ROD BY AN IRREVERSIBLE MECHANICAL CRIMP.
 4. ENSURE CAMERA HOUSING, CAMERA, AND PAN -TILT UNIT ARE BONDED TO POLE.
 5. REMOVE BONDING JUMPER BETWEEN EQUIPMENT CABINET GROUND BUSS AND NEUTRAL BUSS.
 6. REFER TO STANDARD DRAWING 1700-2 FOR ALTERNATE GROUND ROD INSTALLATION METHOD AS APPROVED BY THE ENGINEER.
 7. INSTALL MARKER TAPE DIRECTLY ABOVE ALL GROUNDING ELECTRODES AND CONDUCTORS AT A DEPTH OF 12 INCHES.

DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

	CCTV CAMERA INSTALLATION FOR METAL POLE WITH UNDERGROUND ELECTRICAL SERVICE TYPICAL DETAIL FORSYTH CO.		SEAL NORTH CAROLINA PROFESSIONAL ENGINEER ANDREW J. SKUCE 05/31/2022
	DIVISION 09 PLAN DATE: FEBRUARY 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, PE REVIEWED BY:	

Prepared in the Offices of:
 750 N. Greenfield Pkwy., Garner, NC 27529




NOTES

1. INSTALL A MINIMUM OF THREE (3) GROUNDING ELECTRODES SPACED A MINIMUM OF 10 FEET APART. ENSURE THAT EXISTING UNDERGROUND FACILITIES ARE NOT DAMAGED DURING INSTALLATION.
2. TEST GROUNDING SYSTEM USING AN APPROVED METHOD. SYSTEM SHOULD MEASURE TWENTY (20) OHMS OR LESS. ADDITIONAL GROUNDING ELECTRODES SHALL BE INSTALLED AS DIRECTED BY THE ENGINEER TO MEET THIS REQUIREMENT.
3. MECHANICALLY CRIMP ALL CONNECTIONS TO GROUND RODS USING AN IRREVERSIBLE COMPRESSION TOOL.
4. INSTALL MARKER TAPE DIRECTLY ABOVE ALL GROUNDING ELECTRODES AND CONDUCTORS AT A DEPTH OF 12 INCHES.
5. REMOVE BONDING JUMPER IN EQUIPMENT CABINET IF INSTALLED BETWEEN AC NEUTRAL AND EQUIPMENT GROUND.
6. BOND ALL RIGID GALVANIZED STEEL CONDUITS ENTERING THE CABINET TO "EQUIPMENT GROUND".
7. INSTALL CONDUIT BETWEEN DISCONNECT AND CABINET.
8. ENSURE EQUIPMENT GROUND IS ELECTRICALLY BONDED TO CABINET.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

	Prepared in the Offices of: DYNAMIC MESSAGE SIGN WITH UNDERGROUND ELECTRICAL SERVICE TYPICAL DETAIL DIVISION 09 FORSYTH CO.		SEAL NORTH CAROLINA PROFESSIONAL ENGINEER ANDREW J. SKUCE 050152
	PLAN DATE: FEBRUARY 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, PE REVIEWED BY:	
750 N. Greenfield Pkwy., Garner, NC 27529			DocuSigned by: Andrew J. Skuce 03/31/2022



NOTES



1. INSTALL A MINIMUM OF THREE (3) GROUNDING ELECTRODES SPACED A MINIMUM OF 10 FEET APART. ENSURE THAT EXISTING UNDERGROUND FACILITIES ARE NOT DAMAGED DURING INSTALLATION.
2. TEST GROUNDING SYSTEM USING AN APPROVED METHOD. SYSTEM SHOULD MEASURE TWENTY (20) OHMS OR LESS. ADDITIONAL GROUNDING ELECTRODES SHALL BE INSTALLED AS DIRECTED BY THE ENGINEER TO MEET THIS REQUIREMENT.
3. MECHANICALLY CRIMP ALL CONNECTIONS TO GROUND RODS USING AN IRREVERSIBLE COMPRESSION TOOL.
4. INSTALL MARKER TAPE DIRECTLY ABOVE ALL GROUNDING ELECTRODES AND CONDUCTORS AT A DEPTH OF 12 INCHES.
5. REMOVE BONDING JUMPER IN EQUIPMENT CABINET IF INSTALLED BETWEEN AC NEUTRAL AND EQUIPMENT GROUND.
6. BOND ALL RIGID GALVANIZED STEEL CONDUITS ENTERING THE CABINET TO "EQUIPMENT GROUND".
7. INSTALL CONDUIT BETWEEN DISCONNECT AND CABINET.
8. ENSURE EQUIPMENT GROUND IS ELECTRICALLY BONDED TO CABINET.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

	Prepared in the Offices of: 		DYNAMIC MESSAGE SIGN WITH AERIAL ELECTRICAL SERVICE TYPICAL DETAIL	
	DIVISION 09 FORSYTH CO.		SEAL 050152 ENGINEER ANDREW J. SKUCE	
PLAN DATE: FEBRUARY 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, PE. REVIEWED BY:	REVISIONS	INIT.	DATE
750 N. Greenfield Pkwy., Garner, NC 27529		DocuSigned by: Andrew J. Skuce 03/31/2022		


NOTES

1. INSTALL A MINIMUM OF THREE GROUND RODS SPACED A MINIMUM OF 10 FEET APART. ENSURE THAT EXISTING UNDERGROUND FACILITIES ARE NOT DAMAGED DURING INSTALLATION.
2. TEST GROUNDING SYSTEM USING AN APPROVED METHOD. SYSTEM SHALL MEASURE TWENTY (20) OHMS OR LESS. ADDITIONAL GROUND RODS SHALL BE INSTALLED AS DIRECTED BY THE ENGINEER TO MEET THIS REQUIREMENT.
3. EXOTHERMICALLY WELD ALL CONNECTIONS TO GROUND RODS.
4. INSTALL MARKER TAPE DIRECTLY ABOVE ALL GROUNDING ELECTRODES AND CONDUCTORS AT A DEPTH OF 12 INCHES.
5. REMOVE BONDING JUMPER BETWEEN EQUIPMENT GROUND AND AC NEUTRAL IN THE EQUIPMENT CABINET.
6. BOND ALL RIGID GALVANIZED STEEL CONDUITS (RGC) ENTERING THE CABINET TO EQUIPMENT GROUND.
7. ALL ABOVE GROUND CONDUITS MUST BE RIGID GALVANIZED STEEL. PVC CONDUITS ARE ALLOWED FOR UNDERGROUND INSTALLATIONS.
8. ENSURE EQUIPMENT GROUND BUSS IS ELECTRICALLY BONDED TO EQUIPMENT CABINET.



DOCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED




	Prepared in the Offices of: DYNAMIC MESSAGE SIGN ELECTRICAL SERVICE WITH ISOLATION TRANSFORMER DIVISION 09 FORSYTH CO.		SEAL NORTH CAROLINA PROFESSIONAL ENGINEER SEAL 050152 ANDREW J. SKUCE
	PLAN DATE: MARCH 2022 PREPARED BY: J. WALDEN	REVIEWED BY: A. J. SKUCE, P.E. REVIEWED BY:	
750 N. Greenfield Pkwy., Garner, NC 27529			DocuSigned by: Andrew J. Skuce 03/31/2022




NOTES

1. CONTRACTOR IS RESPONSIBLE FOR FURNISHING ELEVATION DRAWINGS FOR ENGINEER'S APPROVAL.
2. PROVIDE A FIXED LADDER LEADING TO THE ACCESS PLATFORM.
3. EQUIP THE LADDER WITH A SECURITY COVER (LADDER GUARD). START THE FIRST LADDER RUNG NO MORE THAN 18 INCHES ABOVE A CONCRETE LANDING PAD. DESIGN RUNGS ON 12 INCH CENTER-TO-CENTER TYPICAL SPACING.
4. INSTALL A CONCRETE LANDING PAD MEASURING A MINIMUM 4 INCHES DEEP, 24 INCHES WIDE, AND 36 INCHES LONG DIRECTLY BENEATH THE LADDER.
5. USE ACTUAL DIMENSIONS AND WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE.
6. FIELD VERIFY ALL FOOTING ELEVATIONS AND GROUND SLOPES AT THE FOOTING USING THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES.
7. ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING.
8. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT CABLES DURING CONSTRUCTION.
9. DESIGN THE STRUCTURE AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 90 MPH.
10. SEE ROADWAY PLANS FOR GUARDRAIL DETAILS.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**



 Prepared in the Offices of: 750 N. Greenfield Pkwy., Garner, NC 27529	ELEVATION DETAIL		
	DIVISION 09 FORSYTH CO. WINSTON-SALEM PLAN DATE: MARCH 2022 REVIEWED BY: A. SKUCE PREPARED BY: J. WALDEN REVIEWED BY:	REVISIONS _____ _____ _____	
SCALE 0 N/A	DocuSigned by:  Andrew J. Skuce 03/31/2022		DATE 03/31/2022




NOTES

1. CONTRACTOR IS RESPONSIBLE FOR FURNISHING ELEVATION DRAWINGS FOR ENGINEER'S APPROVAL.
2. PROVIDE A FIXED LADDER LEADING TO THE ACCESS PLATFORM.
3. EQUIP THE LADDER WITH A SECURITY COVER (LADDER GUARD). START THE FIRST LADDER RUNG NO MORE THAN 18 INCHES ABOVE A CONCRETE LANDING PAD. DESIGN RUNGS ON 12 INCH CENTER-TO-CENTER TYPICAL SPACING.
4. INSTALL A CONCRETE LANDING PAD MEASURING A MINIMUM 4 INCHES DEEP, 24 INCHES WIDE, AND 36 INCHES LONG DIRECTLY BENEATH THE LADDER.
5. USE ACTUAL DIMENSIONS AND WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE.
6. FIELD VERIFY ALL FOOTING ELEVATIONS AND GROUND SLOPES AT THE FOOTING USING THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES.
7. ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING.
8. VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT CABLES DURING CONSTRUCTION.
9. DESIGN THE STRUCTURE AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 90 MPH.
10. SEE ROADWAY PLANS FOR GUARDRAIL DETAILS.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**




 Prepared in the Offices of: 750 N. Greenfield Pkwy., Garner, NC 27529	ELEVATION DETAIL		
	DIVISION 09 FORSYTH CO. WINSTON-SALEM PLAN DATE: MARCH 2022 REVIEWED BY: A. SKUCE PREPARED BY: J. WALDEN REVIEWED BY:	REVISIONS _____ _____ _____	
SCALE 0 N/A	DocuSigned by: Andrew J. Skuce 03/31/2022		DATE _____



NOTES

- CONTRACTOR IS RESPONSIBLE FOR FURNISHING ELEVATION DRAWINGS FOR ENGINEER'S APPROVAL.
- PROVIDE A FIXED LADDER LEADING TO THE ACCESS PLATFORM.
- EQUIP THE LADDER WITH A SECURITY COVER (LADDER GUARD). START THE FIRST LADDER RUNG NO MORE THAN 18 INCHES ABOVE A CONCRETE LANDING PAD. DESIGN RUNGS ON 12 INCH CENTER-TO-CENTER TYPICAL SPACING.
- INSTALL A CONCRETE LANDING PAD MEASURING A MINIMUM 4 INCHES DEEP, 24 INCHES WIDE, AND 36 INCHES LONG DIRECTLY BENEATH THE LADDER.
- USE ACTUAL DIMENSIONS AND WEIGHT OF THE DMS TO COMPLETE THE DESIGN OF THE DMS STRUCTURE.
- FIELD VERIFY ALL FOOTING ELEVATIONS AND GROUND SLOPES AT THE FOOTING USING THE LATEST NCDOT STANDARD SPECIFICATIONS FOR ROADS AND STRUCTURES.
- ENSURE THAT THE TOP OF THE FOOTING EXTENDS AT LEAST 6 INCHES AND NOT MORE THAN 24 INCHES ABOVE THE HIGHEST POINT OF THE GROUND SURFACE AT THE FOOTING.
- VERIFY ALL UNDERGROUND UTILITY LOCATIONS BEFORE BEGINNING ANY UNDERGROUND WORK. DO NOT DAMAGE ANY EXISTING UTILITIES OR NCDOT CABLES DURING CONSTRUCTION.
- DESIGN THE STRUCTURE AND DMS ENCLOSURE TO WITHSTAND WIND VELOCITIES OF 90 MPH.
- SEE ROADWAY PLANS FOR GUARDRAIL DETAILS.

**DOCUMENT NOT CONSIDERED FINAL
UNLESS ALL SIGNATURES COMPLETED**

 Prepared in the Offices of: 750 N. Greenfield Pkwy., Garner, NC 27529	ELEVATION DETAIL		
	DIVISION 09 FORSYTH CO. WINSTON-SALEM PLAN DATE: MARCH 2022 REVIEWED BY: A. SKUCE PREPARED BY: J. WALDEN REVIEWED BY:	REVISIONS _____ _____ _____	
SCALE 0 N/A	DocuSigned by:  Andrew J. Skuce DATE: 03/31/2022		