



PAVEMENT REMOVAL

-YI- <i>PI Sta 14+25.91</i> Δ = 50° 22' 00.7" (LT) D = 10' 42' 34.2" L = 470.30' T = 251.56' R = 535.00' V = 40 MPH SE = .04 RO = 100'	-YI- <i>PI Sta 20+28.61</i> Δ = 44° 52' 04.1" (RT) D = 6' 09' 39.0" L = 728.27' T = 383.96' R = 930.00' V = 50 MPH SE = .04 RO = 120'	-YI- <i>PI Sta 11+23.64</i> Δ = 49° 43' 41.6" (LT) D = 32' 44' 25.6" L = 151.89' T = 81.0' R = 175.00' V = 25 MPH SE = .04 RO = 70'	-YI- <i>PI Sta 12+67.90</i> Δ = 0° 22' 32.9" (LT) D = 1' 08' 45.3" L = 32.79' T = 16.40' R = 5,000.00'	-YI- <i>PI Sta 14+30.79</i> Δ = 5° 15' 06.7" (LT) D = 5' 43' 46.5" L = 91.66' T = 45.86' R = 1,000.00'	-YI- <i>PI Sta 15+19.67</i> Δ = 24° 18' 49.0" (LT) D = 28' 38' 52.4" L = 84.87' T = 43.08' R = 200.00'	-YI- <i>PI Sta 15+95.81</i> Δ = 14° 46' 28.4" (LT) D = 21' 37' 15.8" L = 68.33' T = 34.36' R = 265.00'	-YI- <i>PI Sta 16+68.25</i> Δ = 12° 32' 34.3" (LT) D = 16' 22' 12.8" L = 76.62' T = 38.46' R = 350.00' V = 40 MPH	-DRI- <i>PI Sta 10+56.11</i> Δ = 31° 15' 39.0" (LT) D = 38' 11' 49.9" L = 81.84' T = 41.97' R = 150.00' V = 15 MPH SE = R.C. RO = 30'
---	--	--	--	--	--	--	--	--

FOR -YI- PROFILE, SEE SHT. 7
FOR -YIA- PROFILE, SEE SHT. 7
FOR -DRI- PROFILE, SEE SHT. 7
FOR DITCH DETAILS, SEE SHT. 2D-1