

APPROVED: *David M. Eaton*
 DATE: 9/3/2021

SEAL

DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED

SIGN NUMR: 3B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05

SYMBOL TABLE:

SYMBOL	X	Y	WID	HT
70 EAST	38.31	76.94	36	36
Raleigh	68.8	4.88	22.82	35.63

USE NOTES: 1,3,5,7

- Legend and border shall be direct applied Grade A reflective sheeting.
- Legend and border shall be direct applied Grade C reflective sheeting.
- Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
- Background shall be Grade B reflective sheeting.
- Background shall be Grade C reflective sheeting.
- Center arrow(s) vertically on sign.
- Bottom panel shall be Yellow Grade C sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is: 174" X 36".

Letter spacings are to start of next letter

Series/Size	Text Length
E 2000	46.38
EM 2000	92.16
E 2000	39.52
E 2000	47.88

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 5A TYPE: B Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05

SYMBOL TABLE:

SYMBOL	X	Y	WID	HT
EXIT 3				

USE NOTES: 1,5

- Legend and border shall be direct applied Grade A reflective sheeting.
- Legend and border shall be direct applied Grade C reflective sheeting.
- Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
- Background shall be Grade B reflective sheeting.
- Background shall be Grade C reflective sheeting.
- Center arrow(s) vertically on sign.

Letter spacings are to start of next letter

Series/Size	Text Length
E 2000	57.75

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 4B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05

SYMBOL TABLE:

SYMBOL	X	Y	WID	HT
70 WEST	37.11	76.94	36	36
Durham	68.8	4.88	22.82	35.63

USE NOTES: 1,3,5,7

- Legend and border shall be direct applied Grade A reflective sheeting.
- Legend and border shall be direct applied Grade C reflective sheeting.
- Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
- Background shall be Grade B reflective sheeting.
- Background shall be Grade C reflective sheeting.
- Center arrow(s) vertically on sign.
- Bottom panel shall be Yellow Grade C sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is: 174" X 36".

Letter spacings are to start of next letter

Series/Size	Text Length
E 2000	48.78
EM 2000	96.64
E 2000	39.52
E 2000	47.88

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 5B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05

SYMBOL TABLE:

SYMBOL	X	Y	WID	HT
Lumley Rd				
1 MILE				

USE NOTES: 1,5

- Legend and border shall be direct applied Grade A reflective sheeting.
- Legend and border shall be direct applied Grade C reflective sheeting.
- Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
- Background shall be Grade B reflective sheeting.
- Background shall be Grade C reflective sheeting.
- Center arrow(s) vertically on sign.

Letter spacings are to start of next letter

Series/Size	Text Length
EM 2000	134.24
E 2000	52.6

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

11/20/2021 10:58 AM
 C:\STATION\CONDO\USLE\USLE\

TYPE "A" AND "B" SIGNS