

APPROVED: *David M. Eaton*
 DATE: 9/3/2021



DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED

SIGN NUMR: 128 TYPE: A Overhead QUANTITY: 1
 BACKG. COLOR: Green COPY COLOR: Black
 DESIGN BY: DME CHECKED BY: AIA LOCATION: I-540
 DATE: Aug 25, 2021 DIV: 05

SIGN WIDTH: 168" HEIGHT: 144" TOTAL AREA: 168.0 Sq.Feet(')

SYMBOL	X	Y	WID	HT
M1_4	66	94	36	36

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12"
 NO. Z BARS: 3 LENGTH: 160.0"

USE NOTES: 1,3,5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size Text Length	
	D	u	r	h	a	m								EM 2000
	35.68	17.76	16.96	11.84	15.52	16.96	17.6	35.68						96.64
	R	a	l	e	i	g	h							EM 2000
	37.92	15.84	16.96	8.16	15.52	8.16	16.96	10.56	37.92					92.16
	1	M	I	L	E									E 2000
	57.7	4.5	15	12	4.4	9.2	7.5	57.7						52.6

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 14A,18A,20A,22A,24A,28A TYPE: B Overhead QUANTITY: 6
 BACKG. COLOR: Green COPY COLOR: White
 DESIGN BY: DME CHECKED BY: AIA LOCATION: I-540
 DATE: Aug 25, 2021 DIV: 05

SIGN WIDTH: 114" HEIGHT: 30" TOTAL AREA: 23.8 Sq.Feet

SYMBOL	X	Y	WID	HT

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 3"
 NO. Z BARS: 2 LENGTH: 106.0"

USE NOTES: 1.5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size Text Length	
	E	X	I	T	9									E 2000
	28.13	8.9	10.7	3.5	7.5	15	12.15	28.13						57.75

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 14B TYPE: A Overhead QUANTITY: 1
 BACKG. COLOR: Green COPY COLOR: White
 DESIGN BY: DME CHECKED BY: AIA LOCATION: I-540
 DATE: Aug 25, 2021 DIV: 05

SIGN WIDTH: 168" HEIGHT: 144" TOTAL AREA: 168.0 Sq.Feet

SYMBOL	X	Y	WID	HT
M1-5-2-36-15C	66	95	36	36

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12"
 NO. Z BARS: 3 LENGTH: 160.0"

USE NOTES: 1,3,5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size Text Length	
	R	a	l	e	i	g	h							EM 2000
	37.92	15.84	16.96	8.16	15.52	8.16	16.96	10.56	37.92					92.16
	C	r	e	e	d	m	o	o	r					EM 2000
	17.12	17.44	10.4	14.08	14.08	16.96	22.56	14.4	15.84	8	17.12			133.76
	2	3/4	M	I	L	E	S							E 2000
	32.89	12.15	10	24.98	15	12	4.4	9.2	8.9	8.1	30.39			104.73

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 13B TYPE: A Overhead QUANTITY: 1
 BACKG. COLOR: Green COPY COLOR: White
 DESIGN BY: DME CHECKED BY: AIA LOCATION: I-540
 DATE: Aug 25, 2021 DIV: 05

SIGN WIDTH: 186" HEIGHT: 66" TOTAL AREA: 85.3 Sq.Feet

SYMBOL	X	Y	WID	HT

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 9"
 NO. Z BARS: 2 LENGTH: 178.0"

USE NOTES: 1.5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size Text Length	
	L	e	e	s	v	i	l	l	e	R	d			EM 2000
	16.6	13.92	14.08	13.76	13.76	16.96	9.6	9.6	8.16	10.56	16	15.84	10.56	152.8
	1/2	M	I	L	E									E 2000
	57.96	21.98	15	12	4.4	9.2	7.5	57.96						70.08

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

TYPE "A" AND "B" SIGNS