

APPROVED: *David M. Eaton*
DocuSigned by: David M. Eaton
 DD41C5F2478A8F7...

DATE: 9/3/2021



DOCUMENT NOT CONSIDERED FINAL
 UNLESS ALL SIGNATURES COMPLETED

SIGN NUMR: 15B,16B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05
 QUANTITY: 2

SIGN WIDTH: 222" HEIGHT: 42" TOTAL AREA: 64.8 Sq.Feet

SYMBOL	X	Y	WID	HT
AR_Type A	179.61	7.21	22.24	35.02

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 6"
 NO. Z BARS: 2 LENGTH: 214.0"

USE NOTES: 1,5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size	
													Text Length	
L	e	e	s	v	i	l	l	e	R	d			EM 2000	
14.81	13.92	14.08	13.76	13.76	16.96	9.6	9.6	8.16	10.56	12	15.84	10.56	58.39	148.8

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 19A,23A,25A,27A,29A,30A,32A,37A TYPE: B Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05
 QUANTITY: 8

SIGN WIDTH: 114" HEIGHT: 30" TOTAL AREA: 23.8 Sq.Feet

SYMBOL	X	Y	WID	HT

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 3"
 NO. Z BARS: 2 LENGTH: 106.0"

USE NOTES: 1,5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size
													Text Length
E	X	I	T	1	1								E 2000
26.7	8.9	10.7	3.5	7.5	15	4.5	6	4.5	26.7				60.6

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 17B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05
 QUANTITY: 1

SIGN WIDTH: 186" HEIGHT: 66" TOTAL AREA: 85.3 Sq.Feet

SYMBOL	X	Y	WID	HT

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12"
 NO. Z BARS: 2 LENGTH: 178.0"

USE NOTES: 1,5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size	
													Text Length	
L	e	e	s	v	i	l	l	e	R	d			EM 2000	
16.6	13.92	14.08	13.76	13.76	16.96	9.6	9.6	8.16	10.56	16	15.84	10.56	16.6	152.8
1	M	I	L	E										E 2000
66.7	4.5	15	12	4.4	9.2	7.5	66.7							52.6

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 18B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA DATE: Aug 25, 2021 DIV: 05
 QUANTITY: 1

SIGN WIDTH: 168" HEIGHT: 144" TOTAL AREA: 168.0 Sq.Feet

SYMBOL	X	Y	WID	HT
M1-5-2-36-15C	66	94.19	36	36

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH RECESS: 0" WIDTH: 2" RADII: 12"
 NO. Z BARS: 3 LENGTH: 160.0"

USE NOTES: 1,3,5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

Letter spacings are to start of next letter													Series/Size
													Text Length
R	a	l	e	i	g	h							EM 2000
37.92	15.84	16.96	8.16	15.52	8.16	16.96	10.56	37.92					92.16
C	r	e	e	d	m	o	o	r					EM 2000
17.12	17.44	10.4	14.08	14.08	16.96	22.56	14.4	15.84	8	17.12			133.76
1	M	I	L	E									E 2000
57.7	4.5	15	12	4.4	9.2	7.5	57.7						52.6

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

11/20/2021 10:58:58 AM
 C:\STAFF\GSENG\PROJECTS\I-5999\SIGNAGE\15B,16B\15B,16B_SIGN_3F.DWG
 11/20/2021 10:58:58 AM
 C:\STAFF\GSENG\PROJECTS\I-5999\SIGNAGE\17B\17B_SIGN_3F.DWG
 11/20/2021 10:58:58 AM
 C:\STAFF\GSENG\PROJECTS\I-5999\SIGNAGE\18B\18B_SIGN_3F.DWG

TYPE "A" AND "B" SIGNS