

SIGN NUMR: 44B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA LOCATION: I-540 DATE: Aug 25, 2021 DIV: 05

SIGN WIDTH: 168" HEIGHT: 96" TOTAL AREA: 112.0 Sq.Feet

| SYMBOL | X | Y | WID | HT |
|--------|---|---|-----|----|
| | | | | |
| | | | | |
| | | | | |
| | | | | |

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 12"
 NO. Z BARS: 3
 LENGTH: 160.0"

USE NOTES: 1,5
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.

| Letter spacings are to start of next letter | | | | | | | | | | | Series/Size | Text Length | |
|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|-------------|-------------|--------|
| | T | r | i | a | n | g | l | e | | | | EM 2000 | 103.84 |
| 32.08 | 15.68 | 11.84 | 8.16 | 16.96 | 15.52 | 16.96 | 8.16 | 10.56 | 32.08 | | | | |
| | T | o | w | n | | B | l | v | d | | | EM 2000 | 127.2 |
| 20.4 | 14.24 | 14.08 | 20.96 | 10.56 | 16 | 17.44 | 7.84 | 15.52 | 10.56 | 20.4 | | | |
| | 1/2 | | M | I | L | E | | | | | E 2000 | 70.07 | |
| 48.96 | 21.96 | 15 | 12 | 4.4 | 9.2 | 7.5 | 48.96 | | | | | | |

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 43B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA LOCATION: I-540 DATE: Aug 25, 2021 DIV: 05

SIGN WIDTH: 192" HEIGHT: 180" TOTAL AREA: 240.0 Sq.Feet EXIT PANEL AREA: 48.0 Sq.Ft.

| SYMBOL | X | Y | WID | HT |
|--------|-------|-----|-------|----|
| M1_4 | 78 | 131 | 36 | 36 |
| ARDOWN | 77.39 | 8 | 32.06 | 22 |

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 12"
 NO. Z BARS: 6
 LENGTH: 184.0"

USE NOTES: 1,3,5,7
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.
 7. Bottom panel shall be Yellow Grade C sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is: 192" X 36".

| Letter spacings are to start of next letter | | | | | | | | | | | Series/Size | Text Length | | | |
|---|-------|-------|-------|-------|--------|-------|-------|-------|-------|-------|-------------|-------------|----|---------|--------|
| | C | a | p | i | t | a | l | | B | l | v | d | | EM 2000 | 156 |
| 18 | 16 | 16.96 | 15.52 | 8 | 12 | 16.96 | 3.2 | 16 | 17.44 | 7.84 | 15.52 | 10.56 | 18 | | |
| | R | a | l | e | i | g | h | | | | | | | EM 2000 | 92.16 |
| 49.92 | 15.84 | 16.96 | 8.16 | 15.52 | 8.16 | 16.96 | 10.56 | 49.92 | | | | | | | |
| | W | a | k | e | | F | o | r | e | s | t | | | EM 2000 | 153.92 |
| 19.04 | 19.36 | 16.96 | 14.08 | 10.56 | 16 | 14.72 | 15.84 | 10.4 | 13.76 | 13.92 | 8.32 | 19.04 | | | |
| | E | X | I | T | | | | | | | | | | EM 2000 | 39.59 |
| 22.83 | 11.25 | 14 | 5.45 | 8.88 | 129.59 | | | | | | | | | | |
| | O | N | L | Y | | | | | | | | | | EM 2000 | 47.76 |
| 121.46 | 12.96 | 13.08 | 9.6 | 12.12 | 22.78 | | | | | | | | | | |

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

SIGN NUMR: 45B TYPE: A Overhead BACKG. COLOR: Green COPY COLOR: White DESIGN BY: DME CHECKED BY: AIA LOCATION: I-540 DATE: Aug 31, 2021 DIV: 05

SIGN WIDTH: 222" HEIGHT: 180" TOTAL AREA: 277.5 Sq.Feet EXIT PANEL AREA: 55.5 Sq.Ft.

| SYMBOL | X | Y | WID | HT |
|-----------|-------|------|-------|-------|
| M1_4 | 93 | 131 | 36 | 36 |
| AR_Type A | 16.75 | 4.98 | 22.62 | 35.63 |
| AR_Type A | 177.2 | 4.98 | 22.62 | 35.63 |

MAT'L: 0.125" ALUMINUM
 BORDER TYPE: FLUSH
 RECESS: 0"
 WIDTH: 2"
 RADII: 12"
 NO. Z BARS: 6
 LENGTH: 214.0"

USE NOTES: 1,3,5,7
 1. Legend and border shall be direct applied Grade A reflective sheeting.
 2. Legend and border shall be direct applied Grade C reflective sheeting.
 3. Shields shall be Grade A reflective sheeting on 0.032" aluminum and demountable.
 4. Background shall be Grade B reflective sheeting.
 5. Background shall be Grade C reflective sheeting.
 6. Center arrow(s) vertically on sign.
 7. Bottom panel shall be Yellow Grade C sheeting. Legend shall be direct applied black non-reflective sheeting. Yellow panel is: 222" X 36".

| Letter spacings are to start of next letter | | | | | | | | | | | Series/Size | Text Length | | | |
|---|-------|-------|-------|-------|--------|-------|-------|-------|-------|-------|-------------|-------------|----|---------|--------|
| | C | a | p | i | t | a | l | | B | l | v | d | | EM 2000 | 156 |
| 33 | 16 | 16.96 | 15.52 | 8 | 12 | 16.96 | 3.2 | 16 | 17.44 | 7.84 | 15.52 | 10.56 | 33 | | |
| | R | a | l | e | i | g | h | | | | | | | EM 2000 | 92.16 |
| 64.92 | 15.84 | 16.96 | 8.16 | 15.52 | 8.16 | 16.96 | 10.56 | 64.92 | | | | | | | |
| | W | a | k | e | | F | o | r | e | s | t | | | EM 2000 | 153.92 |
| 34.04 | 19.36 | 16.96 | 14.08 | 10.56 | 16 | 14.72 | 15.84 | 10.4 | 13.76 | 13.92 | 8.32 | 34.04 | | | |
| | E | X | I | T | | | | | | | | | | E 2000 | 39.59 |
| 62.8 | 11.45 | 13.94 | 5.13 | 9 | 119.68 | | | | | | | | | | |
| | O | N | L | Y | | | | | | | | | | E 2000 | 47.76 |
| 117.32 | 12.84 | 12.84 | 9.96 | 12.24 | 56.8 | | | | | | | | | | |

Spacing Factor is 1 unless specified otherwise
 FILENAME: GSENG

TYPE "A" AND "B" SIGNS