

LOCATION SKETCH

INFORMATION INDICATED ON THE LOCATION SKETCH SHALL BE CONSIDERED GENERAL INFORMATION ONLY. CONTRACTOR SHALL CONFIRM, THROUGH OTHER SOURCES, SPECIFIC INFORMATION REGARDING BRIDGES, ROADWAY, UTILITIES, THE SURROUNDING AREA, AND ANY OTHER ASPECTS THAT MAY BE NECESSARY TO PERFORM AND COMPLETE THE PROJECT.

03

DRAWN BY :	J. MYA	DATE : <u>6/2022</u>
CHECKED BY : _	J. YANNACCONE	DATE : <u>6/2022</u>

BRIDGE CO	ORDINATES
LATITUDE	LONGITUDE
35°-33′-29.10′′	82°-35′-45.40′′

SEE TRANSPORTATION MANAGEMENT PLANS FOR LANE WIDTHS, SEQUENCING AND OTHER TRAFFIC CONTROL MEASURES FOR STAGING OF OVERLAY SURFACE PREPARATION AND LATEX MODIFIED CONCRETE - VERY EARLY STRENGTH (LMC-VES) PLACEMENT.

FOR NEW ASPHALT PLACEMENT, SEE STANDARD SPECIFICATIONS.

BE PROVIDED BY THE DEPARTMENT. THE CONTRACTOR'S ATTENTION IS CALLED TO THE FACT THAT DUE TO THE NATURE OF PRESERVATION PROJECTS, THE EXTENT OF WORK CANNOT ALWAYS BE ALL PAVEMENT MARKING WILL BE IN ACCORDANCE ACCURATELY DETERMINED PRIOR TO COMMENCEMENT WITH THE TRANSPORTATION MANAGEMENT PLANS. OF WORK, REPAIR LOCATIONS AND ESTIMATES OF QUANTITIES ARE GIVEN WITH THE BEST INFORMATION EXISTING JOINTS AND DECK DRAINS SHALL BE SEALED PRIOR TO BEGINNING SURFACE PREPARATIONS OF THE BRIDGE DECK. THE CONTRACTOR SHALL TAKE AVAILABLE, IF ADDITIONAL REPAIRS NOT SHOWN ON THE DRAWINGS ARE DEEMED NECESSARY BY THE ENGINEER, THE ENGINEER SHALL NOTE ON THE CARE THAT ANY CONSTRUCTION DEBRIS THAT DRAWINGS THE APPROXIMATE LOCATION AND COLLECTS IN THE DRAINS IS CONTAINED. DRAINS IN DESCRIPTION OF THE REPAIRS. SHOULDERS OF ADJACENT TRAVEL LANE(S) SHALL BE KEPT FREE AND CLEAR OF DEBRIS.

EXISTING DIMENSIONS AND BRIDGE CONDITION ARE FOR LATEX MODIFIED CONCRETE - VERY EARLY STRENGTH FROM THE BEST INFORMATION AVAILABLE. THE CONTRACTOR SHALL FIELD VERIFY THE INFORMATION AND PLACING AND FINISHING LATEX MODIFIED CONCRETE SHOWN ON THE PLANS AND NOTIFY THE ENGINEER - VERY EARLY STRENGTH, SEE LATEX MODIFIED CONCRETE IF ACTUAL DIMENSIONS AND CONDITIONS DIFFER. - VERY EARLY STRENGTH SPECIAL PROVISION.

FOR FINE MILLING BRIDGE DECK, HYDRO-DEMOLITION OF THE CONTRACTOR SHALL HAVE NO CLAIM WHATSOEVER BRIDGE DECK, CLASS II AND CLASS III SURFACE AGAINST THE DEPARTMENT FOR ANY DELAYS OR PREPARATION. SEE LMC OVERLAY SURFACE PREPARATION ADDITIONAL COST INCURRED BASED ON DIFFERENCES BETWEEN WHAT IS SHOWN ON THE PLANS AND THE SPECIAL PROVISION. ACTUAL CONDITIONS AT THE PROJECT SITE.

IT IS THE CONTRACTOR'S RESPONSIBILITY TO FOLLOW ALL STATE AND FEDERAL SAFETY REQUIREMENTS.

WORK ON THE BRIDGE SHALL BE PERFORMED SO AS NOT TO ALLOW DEBRIS TO FALL BELOW, EXCEPT WHERE THE CONTRACTOR'S PLAN USES PLATFORMS, NETS, SCREENS OR OTHER PROTECTIVE DEVICES TO CATCH THE MATERIAL. THE CONTRACTOR SHALL SUBMIT PLANS FOR CONSTRUCTION IN ACCORDANCE WITH ARTICLE 402-2 OF THE STANDARD SPECIFICATIONS AND THE PROJECT SPECIAL PROVISIONS.

ENGINEER DETERMINES THAT PROTECTIVE DEVICES ARE NOT ADEQUATE OR NOT BEING EMPLOYED, THE THE CONTRACTOR SHALL PERFORM ALL WORK WITH CARE SO THAT THE EXISTING STRUCTURE WHICH IS TO REMAIN IN PLACE WILL NOT BE DAMAGED. IF THE WORK SHALL BE SUSPENDED UNTIL ADEQUATE CONTRACTOR DAMAGES ANY PART OF THE EXISTING PROTECTION IS PROVIDED. STRUCTURE WHICH IS TO REMAIN IN PLACE. THE DAMAGED AREA SHALL BE REPAIRED OR REPLACED FOR ELASTOMERIC CONCRETE FOR PRESERVATION, SEE IN A MANNER SATISFACTORY TO THE ENGINEER AT SPECIAL PROVISIONS. NO ADDITIONAL COST TO THE DEPARTMENT.

ANY DAMAGE TO EXISTING REINFORCING STEEL, DURING CONTRACTOR'S OPERATIONS, SHALL BE REPAIRED AS DIRECTED BY THE ENGINEER AND PERFORMED AT NO ADDITIONAL COST TO THE DEPARTMENT.

FOR CONTROL OF TRAFFIC AND LIMITS ON PHASING OF CONSTRUCTION, SEE TRANSPORTATION MANAGEMENT PLANS.

PRIOR TO BEGINNING WORK, THE CONTRACTOR SHALL SUBMIT FOR REVIEW AND APPROVAL A COMPLETE FOR EPOXY COATING AND DEBRIS REMOVAL, SEE SPECIAL SEQUENCE OF TASKS FOR EACH OPERATION AFFECTING PROVISIONS. THE BRIDGE SURFACE AND/OR TRAFFIC.

FOR OTHER DESIGN DATA AND GENERAL NOTES, SEE SHEET SN.

FOR SUBMITTAL OF WORKING DRAWINGS, SEE SPECIAL PROVISIONS.

FOR FALSEWORK AND FORMWORK. SEE SPECI PROVISIONS.

FOR CRANE SAFETY, SEE SPECIAL PROVISIO

FOR GROUT FOR STRUCTURES, SEE SPECIAL PROVISIONS.

FOR FLOWABLE FILL, SEE SPECIAL PROVIS



GENERAL NOTES

OCUMENT NOT CONSIDERED FINAL UNLESS ALL SIGNATURES COMPLETED

THE ELEVATION(S) AND CLEARANCE(S) SHOWN ON THE PLANS AT THE POINT(S) OF MINIMUM VERTICAL CLEARANCE ARE FROM THE BEST INFORMATION AVAILABLE. PRIOR TO BEGINNING BRIDGE CONSTRUCTION, VERIFY THE ELEVATION(S) ON THE EXISTING PAVEMENT AND CHECK THE CLEARANCE. REPORT ANY VARIATIONS TO THE ENGINEER. ANY PLAN REVISIONS NECESSARY TO ACHIEVE THE REQUIRED MINIMUM VERTICAL CLEARANCE WILL

FOR LMC OVERLAY SURFACE PREPARATION. SEE SPECIAL PROVISIONS.

THE CONTRACTOR MUST COLLECT, TREAT AND DISPOSE OF RUN-OFF WATER FROM THE HYDRO-DEMOLITION PROCESS, SEE LMC OVERLAY SURFACE PREPARATION SPECIAL PROVISION.

THE CONTRACTOR SHALL TAKE CARE DURING JOINT REHAB OPERATIONS NOT TO DROP ANY MATERIAL BELOW THE BRIDGE WITHOUT PROTECTIVE DEVICES BELOW TO CATCH THE MATERIAL. ANY MATERIAL THAT FALLS BELOW THE BRIDGE SHALL BE CONTAINED, REMOVED AND DISPOSED OF BY THE CONTRACTOR AT NO EXTRA COST TO THE DEPARTMENT. IF THE

FOR BRIDGE JOINT DEMOLITION, SEE SPECIAL PROVISIONS.

FOR FOAM JOINT SEALS FOR PRESERVATION, SEE SPECIAL PROVISIONS.

FOR CONCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR SHOTCRETE REPAIRS, SEE SPECIAL PROVISIONS.

FOR EPOXY RESIN INJECTION, SEE SPECIAL PROVISIONS.

FOR FINE MILLING, SEE SPECIAL PROVISIONS.

FOR REMOVAL AND REPLACEMENT OF TUBULAR BEAM GUARDRAIL, SEE SPECIAL PROVISIONS.

AL	PROJECT NO. <u>I-5889B</u>	
ONS.		DUNTY
IONS.	BRIDGE NO100347	7
	SHEET 2 OF 2	
Docusigned by: Exist Brack of 7/25/2022 ACB8082119D74CD	STATE OF NORTH CAROLINA DEPARTMENT OF TRANSPORTA RALEIGH GENERAL DRAWIN FOR BRIDGE ON I-40 WBI SR 3620 (HOMINY CREEK AND HOMINY CREEK	NG Lovef Road)
	REVISIONS	SHEET NO

DATE:

BY:

S4-2

TOTAL SHEETS

DATE:

BY: